

METHOD AND DEVICE FOR MONITORING SEARCH SPACE

CROSS-REFERENCE TO RELATED APPLICATIONS

5 [0001] This application claims priority to Chinese Patent Application No. 202010082038.3, filed in China on February 6, 2020, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

[0002] Embodiments of the present invention relate to the communications field, and in particular, to a search space monitoring method and a device.

10

BACKGROUND

[0003] A 5G NR system supports carrier aggregation (carrier aggregation, CA) to configure and activate multiple carriers (component carriers, CC) or cells for terminal devices, and support cross-carrier scheduling in a CA scenario. In addition, the NR supports a multi-transmission panel (multiple Transmission and Reception Panel, M-TRP) scenario, and a terminal device can be scheduled by using a plurality of TRPs for data transmission and reception. However, in release-15 NR, one cell
15 can be scheduled only by one scheduling cell (that is, being scheduled by itself or by another cell), and a PCell can be scheduled only by a primary cell (Primary Cell, PCell).

20

[0004] In order to enhance coverage of a control channel, the PCell is generally deployed on a low-band carrier. Due to an insufficient bandwidth of the low-band carriers that have been deployed in other series (such as LTE), the PCell has a limited control channel capacity, and therefore such scheduling manner in the related

art is difficult to resolve the problem of the limited control channel capacity of the PCell.

SUMMARY

[0005] Embodiments of the present invention aim to provide a search space monitoring method and a device, so as to resolve the problem of a limited control channel capacity in a scheduling manner in the related art.

[0006] According to a first aspect, a search space monitoring method is provided, where the method is executed by a terminal device, a plurality of transmission objects are configured for the terminal device, and the method includes:

obtaining scheduling configuration information; and

monitoring a search space SS based on the scheduling configuration information, where the SS includes an SS in which at least two transmission objects schedule one transmission object.

[0007] According to a second aspect, a search space monitoring method is provided, where the method is executed by a network device, and the method includes:

sending scheduling configuration information; where

the scheduling configuration information is used for monitoring an SS by a terminal device, a plurality of transmission objects are configured for the terminal device, and the SS includes an SS in which at least two transmission objects schedule one transmission object.

[0008] According to a third aspect, a terminal device is provided, where a plurality of transmission objects are configured for the terminal device, and the terminal device includes:

an obtaining module, configured to obtain scheduling configuration information; and

a monitoring module, configured to monitor an SS based on the scheduling configuration information, where the SS includes an SS in which at least two transmission objects schedule one transmission object.

[0009] According to a fourth aspect, a network device is provided, where the network device includes:

a sending module, configured to send scheduling configuration information; where

the scheduling configuration information is used for monitoring an SS by a terminal device, a plurality of transmission objects are configured for the terminal device, and the SS includes an SS in which at least two transmission objects schedule one transmission object.

[0010] According to a fifth aspect, a terminal device is provided, where the terminal device includes a processor, a memory, and a computer program stored in the memory and capable of running on the processor, and when the computer program is executed by the processor, the steps of the search space monitoring method according to the first aspect are implemented.

[0011] According to a sixth aspect, a network device is provided, where the network device includes a processor, a memory, and a computer program stored in the memory and capable of running on the processor, and when the computer program is executed by the processor, the search space monitoring method according to the second aspect are implemented.

[0012] According to a seventh aspect, a computer-readable storage medium is provided, where a computer program is stored in the computer-readable storage medium, and when the computer program is executed by a processor, the search space monitoring method according to any one of the first aspect and the second aspect are implemented.

[0013] According to the search space monitoring method provided in the embodiments of the present invention, a plurality of transmission objects (for example, a plurality of cells or a plurality of TRPs) are configured for the terminal device, to support self-scheduling of one cell (or TRP) and scheduling by another

cell (or TRP), for example, supporting both self-scheduling of a PCell and scheduling the PCell by using an SCell. This resolves the problem of a limited control channel capacity (of the PCell), thereby improving communication efficiency.

5

BRIEF DESCRIPTION OF DRAWINGS

[0014] The accompanying drawings described herein are intended for better understanding of this application, and constitute a part of this application. Exemplary embodiments and descriptions thereof in this application are intended to interpret this application and do not constitute any improper limitation on this application. In
10 the accompanying drawings:

[0015] FIG. 1 is a schematic flowchart of a search space monitoring method according to an embodiment of the present invention;

[0016] FIG. 2 is a schematic flowchart of a search space monitoring method according to another embodiment of the present invention;

15 [0017] FIG. 3 is a schematic structural diagram of a terminal device according to an embodiment of the present invention;

[0018] FIG. 4 is a schematic structural diagram of a network device according to an embodiment of the present invention;

20 [0019] FIG. 5 is a schematic structural diagram of a terminal device according to another embodiment of the present invention; and

[0020] FIG. 6 is a schematic structural diagram of a network device according to another embodiment of the present invention.

DETAILED DESCRIPTION OF EMBODIMENTS

25 [0021] To make the objectives, technical solutions, and advantages of this application clearer, the following clearly and completely describes the technical solutions in the embodiments of this application with reference to the accompanying

drawings in the embodiments of this application. Obviously, the described embodiments are merely some but not all of the embodiments of this application. All other embodiments obtained by a person of ordinary skill in the art based on the embodiments of this application without creative efforts shall fall within the protection scope of this application. The term "and/or" in the embodiments of this specification represents presence of at least one of the connected objects.

[0022] It should be understood that the technical solutions in the embodiments of the present invention may be applied to various communications systems, such as a long term evolution (Long Term Evolution, LTE) system, an LTE frequency division duplex (Frequency Division Duplex, FDD) system, an LTE time division duplex (Time Division Duplex, TDD) system, a universal mobile telecommunication system (Universal Mobile Telecommunications System, UMTS), a worldwide interoperability for microwave access (Worldwide Interoperability for Microwave Access, WiMAX) communications system, a 5G system or new radio (New Radio, NR), and a later evolved communications system.

[0023] In the embodiments of the present invention, a terminal device may include but is not limited to a mobile station (Mobile Station, MS), a mobile terminal (Mobile Terminal), a mobile phone (Mobile Telephone), user equipment (User Equipment, UE), a handset (handset), a portable equipment (portable equipment), a vehicle (vehicle), and the like. The terminal device may communicate with one or more core networks through a radio access network (Radio Access Network, RAN). For example, the terminal device may be a mobile phone (also referred to as a "cellular" phone), or a computer having a wireless communication function; or the terminal device may be a portable, pocket-sized, handheld, computer built-in, or in-vehicle mobile apparatus.

[0024] In the embodiments of the present invention, a network device is an apparatus deployed in a radio access network and configured to provide a wireless communication function for terminal devices. The network device may be a base station, and the base station may include forms of a macro base station, a micro base station, a relay station, an access point, and the like. Names of devices having

functions of the base station may vary with systems using different radio access technologies. For example, the base station is referred to as an evolved NodeB (Evolved NodeB, eNB or eNodeB) in an LTE network, or referred to as a Node B (Node B) in a 3rd generation (3rd Generation, 3G) network, or a network device in a later evolved communications system. Use of the terms does not constitute any limitation.

[0025] As shown in FIG. 1, an embodiment of the present invention provides a search space monitoring method 100. The method may be executed by a terminal device. In other words, the method may be executed by software or hardware installed in the terminal device. The method 100 includes the following steps.

[0026] S102: Obtain scheduling configuration information.

[0027] In this embodiment of the present invention, a plurality of transmission objects may be configured for the terminal device, and the plurality of transmission objects may be a plurality of cells or a multi-transmission point (multiple Transmission and Reception Point, M-TRP, or referred to as multi-transmission and reception point). In other words, a search space for the transmission object is associated with a specific CORESET or CORESET pool.

[0028] Optionally, the scheduling configuration information obtained (for example, received) by the terminal device may be used to configure at least one of the following: configuration of the plurality of transmission objects, a search space (Search Space, SS) to be monitored, a downlink control information (Downlink Control Information, DCI) format for scheduling, and the like. The scheduling configuration information may be used to configure a scheduling relationship between the plurality of transmission objects.

[0029] S104: Monitor an SS based on the scheduling configuration information, where the SS includes an SS in which at least two transmission objects schedule one transmission object (which may also be referred to as a scheduled transmission object).

[0030] Optionally, the SS includes an SS in which at least two cells (which may be referred to as scheduling cells) schedule one cell (which may be referred to as a

scheduled cell); or the SS includes an SS in which at least two TRPs (which may be referred to as scheduling TRPs) schedules one TRP (which may be referred to as a scheduled TRP).

[0031] Optionally, the plurality of transmission objects include at least a first transmission object and a second transmission object, and the SS being monitored by the terminal device includes at least one of the following:

(1) a first SS in which a transmission object (for example, the first transmission object, a third transmission object, or a fourth transmission object) other than the second transmission object in the plurality of transmission objects schedules the first transmission object, where in a case that the first transmission object schedules the first transmission object, the first SS may be referred to as an SS in which the first transmission object is self-scheduled.

(2) a second SS in which the second transmission object schedules the first transmission object; and

(3) a third SS in which the second transmission object is self-scheduled.

[0032] In an example, the SS monitored by the terminal device includes the first SS in which the first transmission object is self-scheduled and the second SS in which the second transmission object schedules the first transmission object, and certainly, may also include the third SS in which the second transmission object is self-scheduled.

[0033] In another example, the SS monitored by the terminal device includes a second SS in which the second transmission object, the third transmission object, and the like schedule the first transmission object.

[0034] Optionally, in an embodiment, the monitoring an SS in S104 may be that at least one of the following is satisfied within a first specific time:

(1) a processing capability for monitoring the first SS does not exceed a maximum processing capability for a single transmission object;

(2) a total processing capability for monitoring the second SS and the third SS does not exceed a maximum processing capability for a single transmission object; and

(3) a total processing capability for monitoring the second SS and the third SS does not exceed L multiplied by a maximum processing capability for a single transmission object, where L is a positive number.

[0035] Optionally, L is less than or equal to the number of transmission objects scheduled by the second transmission object.

[0036] Optionally, L is predefined; or L is related to a maximum processing capability M reported by the terminal device.

[0037] According to the search space monitoring method provided in this embodiment of the present invention, a plurality of transmission objects (for example, a plurality of cells or a plurality of TRPs) are configured for the terminal device, to support self-scheduling of one cell (or TRP) and scheduling by another cell (or TRP), for example, supporting both self-scheduling of a PCell and scheduling the PCell by using an SCell. This resolves the problem of a limited control channel capacity (of the PCell), thereby improving communication efficiency.

[0038] In a specific embodiment, a cell-1 and a cell-2 are configured for the terminal device in the embodiment 100. The cell-1 is self-scheduled, and the cell-2 can also schedule the cell-1. The terminal device monitors an SS (hereinafter referred to as SE-SS) in which the cell-1 is self-scheduled, and an SS (hereinafter referred to as CR-SS) in which the cell-2 schedules the cell-1, so as to obtain a scheduling instruction DCI for scheduling the cell-1.

[0039] In addition, the terminal device may also monitor other SSs (hereinafter referred to as O-SSs) on the cell-2 to obtain scheduling DCI for scheduling the cell-2.

[0040] Optionally, the SE-SS, CR-SS, or O-SS described in this embodiment may be a common search space (common search space, CSS) or a terminal-device specific search space (UE-specific search space, USS).

[0041] A special scenario is that no self-scheduling is for the cell-1, and one DCI-J is configured on the cell-2 to simultaneously/jointly schedule data of the

cell-1 and the cell-2. In this case, DCI-2 may alternatively be configured on the cell-2 to schedule the cell-1 separately.

[0042] In the foregoing embodiment, with regard to the processing capability of the terminal device for monitoring the SS, three schemes a, b, and c are described below.

[0043] (a) Optionally, within a specific time (for example, within one slot), a processing capability of the terminal device for monitoring a PDCCH (for example, SE-SS) on the cell-1 does not exceed a maximum processing capability of the terminal device for a single cell. That is, the number of PDCCH candidates monitored by the terminal device does not exceed a maximum number of PDCCH candidates in a single cell; the number of non-overlapping control channel elements (Control Channel Element, CCE) monitored by the terminal device does not exceed a maximum number of non-overlapping CCEs in a single cell; and a maximum number of DCI formats of different sizes monitored by the terminal device does not exceed the number of DCI formats (DCI size budget) of a single cell. This holds true for the following embodiments.

[0044] The processing capability described in this embodiment is related to parameters (for example, numerology/SCS) of the scheduling cell and/or the scheduled cell, for example, being determined based on an SCS of the cell-1 or cell-2 or based on a largest or smallest one of the SCSs; and so on.

[0045] The "processing capability of the terminal device for monitoring ..." described in this embodiment means a processing capability required for monitoring a PDCCH by the terminal device based on configuration parameters of the network device, or a processing capability required for monitoring a PDCCH by the terminal device and obtained in other manners (for example, being determined by the terminal device itself). This holds true for the following embodiments.

[0046] (b) Optionally, within a specific time, a total processing capability of the terminal device for monitoring the PDCCH (for example, the CR-SS and O-SS) on the cell-2 does not exceed a maximum processing capability of the terminal device

for a single cell. (For details, refer to Embodiment 1 of the present invention hereinafter.)

[0047] In this embodiment, the CR-SS and the O-SS may be different SSs, or the CR-SS and the O-SS may be a same SS. In this case, different PDCCH candidates in the SSs correspond to DCI of different scheduled cells, which is identified by cell ID or CIF.

[0048] The processing capability in this embodiment is related to parameters (for example, numerology/SCS) of the scheduling cell and/or the scheduled cell, for example, being determined based on an SCS of the cell-1 or cell-2 or based on a largest or smallest one of the SCSs; and so on.

[0049] Essence of the scheme (b) lies in that part of the processing capability for the cell-2 is allocated to the cell-1, with an advantage of simple implementation. However, this may also reduce the number of candidates that can be monitored on the cell-2, while a monitoring capacity for the cell-1 is wasted, which may lead to lower scheduling flexibility.

[0050] The scheme (b) is also applicable to a scenario in which self-scheduling is not configured for the cell-1, and the cell-1 is merely scheduled by using cross-carrier scheduling DCI or joint/multi-cell scheduling DCI of the cell-2.

[0051] (c) Optionally, the total processing capability of the terminal device for monitoring the CR-SS and O-SS does not exceed ($N \times$ the maximum processing capability of the terminal device for a single cell) (For details, refer to Embodiment 2 of the present invention.)

[0052] Optionally, $N \leq$ the number of cells scheduled by the cell-2, for example, when the cell-2 schedules the cell-1 and the cell-2, $N = 2$ or $N = 1.5$.

[0053] The foregoing scheme (b) is a special case of $N = 1$.

[0054] Optionally, N may be predefined by a protocol, or N may be related to the processing capability M reported by the terminal device (for example, $N \leq M$).

[0055] An advantage of the scheme (c) lies in that scheduling flexibility of the cell-2 can be maintained. However, a greater processing capability is required for the cell-2, possibly leading to higher hardware costs and energy consumption.

[0056] It should be noted that specific times mentioned in the foregoing three schemes (a), (b), and (c) may be a same specific time, such as a same slot; or may be different specific times, for example, in the schemes (a), (b), and (c), monitoring an SS is performed in different slots.

5 **[0057]** Optionally, in an embodiment, a processing capability threshold X_i is assigned to the i-th transmission object A_i in the at least two transmission objects described in the embodiment 100, and X_i does not exceed a maximum processing capability for a single transmission object. Within a second specific time, a processing capability for an SS in which the A_i schedules one transmission object
10 does not exceed X_i .

[0058] This embodiment may also include a self-scheduling scenario, that is, a transmission object scheduled by a specific transmission object A_i is the transmission object A_i itself.

[0059] Optionally, at least two of the X_i satisfy the following relationship:

15
$$\sum_{i=1}^N X_i = R; \text{ where}$$

N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

R is a maximum processing capability determined based on at least one of parameters of the at least two transmission objects; or

20 R is a maximum processing capability determined based on a parameter of the one transmission object that is scheduled; or

R is a maximum processing capability reported by the terminal device.

[0060] Optionally, at least two of the X_i satisfy the following relationship:

$$\sum_{i=1}^N \frac{X_i}{P_i} = 1; \text{ where}$$

N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

P_i is a maximum processing capability determined based on a parameter of the A_i .

5 **[0061]** For detailed description, the following provides description with reference to a specific embodiment. The previous example is still used as an example, that is, a cell-1 and a cell-2 are configured for the terminal device. The cell-1 is self-scheduled, and the cell-2 can also schedule the cell-1. The terminal device monitors an SS (hereinafter referred to as SE-SS) in which the cell-1 is
10 self-scheduled, and an SS (hereinafter referred to as CR-SS) in which the cell-2 schedules the cell-1, so as to obtain a scheduling instruction DCI for scheduling the cell-1. In addition, the terminal device may also monitor other SSs (hereinafter referred to as O-SSs) on the cell-2 to obtain scheduling DCI for scheduling the cell-2.

15 **[0062]** Optionally, within a specific time, for the scheduled cell cell-1:
a processing capability of the terminal device for monitoring the SE-SS does not exceed a threshold X_1 , and X_1 is not greater than a maximum processing capability for a single cell; and a processing capability of the terminal device for monitoring the CR-SS does not exceed a threshold X_2 , and X_2 is not greater than the
20 maximum processing capability for the single cell.

[0063] In this embodiment, a specific time for monitoring the SE-SS and a specific time for monitoring the CR-SS may be a same specific time, for example, a same slot; or may be different specific times. For example, monitoring on the SE-SS and the CR-SS is performed in different slots.

25 **[0064]** Optionally, the threshold X_1 and the threshold X_2 are related to parameters (for example, numerology/SCS) of the scheduling cell and/or the scheduled cell, for example, being determined based on an SCS of the cell-1 or cell-2 or based on a largest or smallest one of the SCSs; and so on.

[0065] Preferably, the threshold X_1 and the threshold X_2 satisfy a specific relationship:

$X_1 + X_2 = R$, where R is a maximum processing capability determined based on the parameter (SCS) of the cell-1 or the cell-2, or R is reported by the user.

5 **[0066]** For example, using the maximum number of PDCCH candidates as an example and assuming that the cell-1 and the cell-2 have different SCSs (cell-1: $\mu = 0$, and cell-2: $\mu = 1$), $X_1 + X_2 = 44$ (for the cell-1) or $X_1 + X_2 = 36$ (for the cell-2).

[0067] Alternatively, $X_1/P_1 + X_2/P_2 = 1$, where P_1 is a maximum processing capability determined for a cell (namely, the cell-1) of the SE-SS, and P_2 is a
10 maximum processing capability determined for a cell (namely, the cell-2) of the CR-SS (for details, refer to Embodiment 3 of the present invention hereinafter).

[0068] For example, using the maximum number of PDCCH candidates as an example and assuming that the cell-1 and the cell-2 have a same SCS ($\mu = 0$), possible thresholds are $X_1 = 30$ and $X_2 = 14$, satisfying $30/44 + 14/44 = 1$

15 **[0069]** Assuming that the cell-1 and the cell-2 have different SCSs (cell-1: $\mu = 0$, and cell-2: $\mu = 1$), possible thresholds are $X_1 = 22$ and $X_2 = 18$, satisfying $X_1/P_1 + X_2/P_2 = 22/44 + 18/36 = 1$.

[0070] Essence of this scheme lies in that part of a hardware processing capability for the cell-1 is allocated to the cell-2 for PDCCH monitoring, which has
20 an advantage of maintaining high scheduling flexibility without increasing hardware costs and energy consumption.

[0071] Preferably, the threshold X_1 and the threshold X_2 are quantized integer values, that is, candidate values of X_1 and X_2 are several positive integers. For example, using the maximum number of PDCCH candidates as an example, X_1 is
25 not an integer within a range of 0, ..., and 44, but is an arithmetic sequence of 0, 4, 8, ..., 40, and 44 with K as a step (for example, $K = 4$). This can simplify implementation complexity of the terminal device.

[0072] It should be noted that the description in this embodiment uses two cells as an example, but this solution is applicable to a scenario of more than two cells,
30 and there may alternatively be more thresholds X_i , such as X_3 and X_4 .

[0073] Optionally, X_1 and X_2 may be predefined by a protocol, or configured by the network, or X_1 and X_2 may be related to a capability reported by the terminal device (the terminal device reports X_1 and X_2 , or X_1 and X_2 are obtained through calculation based on one or more capability values reported by the terminal device).

5 The terminal device may report only one of X_1 or X_2 , and the other value is calculated based on the foregoing specific relationship that needs to be satisfied.

[0074] Optionally, in an embodiment, a processing capability G_i is assigned to the i -th transmission object A_i in the at least two transmission objects described in the embodiment 100, and G_i does not exceed a maximum processing capability for a single transmission object. Within a third specific time, a processing capability for an SS in which the A_i schedules one transmission object is G_i .

[0075] Optionally, at least two of the G_i satisfy the following relationship:

$$\sum_1^N G_i \leq S; \text{ where}$$

15 N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

S is a maximum processing capability determined based on at least one of parameters of the at least two transmission objects; or

S is a maximum processing capability determined based on a parameter of the one transmission object that is scheduled.

20 [0076] Optionally, at least two of the G_i satisfy the following relationship:

$$\sum_1^N \frac{G_i}{Q_i} \leq 1; \text{ where}$$

N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

25 Q_i is a maximum processing capability determined based on a parameter of the A_i .

[0077] For detailed description, the following provides description with reference to a specific embodiment. The previous example is still used as an example, that is, a cell-1 and a cell-2 are configured for the terminal device. The cell-1 is self-scheduled, and the cell-2 can also schedule the cell-1. The terminal device
5 monitors an SS (hereinafter referred to as SE-SS) in which the cell-1 is self-scheduled, and an SS (hereinafter referred to as CR-SS) in which the cell-2 schedules the cell-1, so as to obtain a scheduling instruction DCI for scheduling the cell-1. In addition, the terminal device may also monitor other SSs (hereinafter referred to as O-SSs) on the cell-2 to obtain scheduling DCI for scheduling the
10 cell-2.

[0078] Within a specific time, for the scheduled cell cell-1, a processing capability required by the terminal device for monitoring the SE-SS is G_1 , a processing capability required by the terminal device for monitoring the CR-SS is G_2 , and G_1 and G_2 satisfy a specific relationship:

15 $G_1 + G_2 \leq S$, where S is a maximum processing capability determined based on a parameter (SCS) of the cell-1 or the cell-2; or

$G_1/Q_1 + G_2/Q_2 \leq 1$, where Q_1 is a maximum processing capability determined for a cell (namely, the cell-1) of the SE-SS, and Q_2 is a maximum processing capability determined for a cell (namely, the cell-2) of the CR-SS (for
20 details, refer to Embodiment 4 of the present invention).

[0079] In this embodiment, a specific time for monitoring the SE-SS and a specific time for monitoring the CR-SS may be a same specific time, for example, a same slot; or may be different specific times. For example, monitoring on the SE-SS and the CR-SS is performed in different slots.

25 **[0080]** Optionally, G_1 and G_2 are related to a parameter (for example, numerology/SCS) of the scheduling cell and/or the scheduled cell.

[0081] Preferably, G_1 and G_2 are quantized integer values. For details, refer to the foregoing embodiments.

[0082] Optionally, in an embodiment, in the embodiment 100, within a fourth specific time, for the i -th transmission object A_i in the at least two transmission objects, a processing capability for monitoring an SS in which the A_i schedules one transmission object does not exceed a maximum processing capability for the A_i .

5 **[0083]** For detailed description, the following provides description with reference to a specific embodiment. The previous example is still used as an example, that is, a cell-1 and a cell-2 are configured for the terminal device. The cell-1 is self-scheduled, and the cell-2 can also schedule the cell-1. The terminal device monitors an SS (hereinafter referred to as SE-SS) in which the cell-1 is
10 self-scheduled, and an SS (hereinafter referred to as CR-SS) in which the cell-2 schedules the cell-1, so as to obtain a scheduling instruction DCI for scheduling the cell-1. In addition, the terminal device may also monitor other SSs (hereinafter referred to as O-SSs) on the cell-2 to obtain scheduling DCI for scheduling the cell-2.

15 **[0084]** Within a specific time:

for the scheduled cell cell-1, a total processing capability of the terminal device for monitoring (the SE-SS and the CR-SS) does not exceed a maximum processing capability of the terminal device for a single scheduled cell cell-1; and

for the scheduling cell cell-2, a total processing capability of the terminal
20 device for monitoring the CR-SS and the O-SS does not exceed a maximum processing capability of the terminal device for the single scheduling cell cell-2.

[0085] In this embodiment, a specific time for monitoring the SE-SS and the CR-SS and a specific time for monitoring the CR-SS and the O-SS may be a same specific time, for example, a same slot; or may be different specific times. For
25 example, monitoring on the SE-SS and the CR-SS and monitoring on the CR-SS and the O-SS are performed in different slots.

[0086] In this embodiment, the network device may flexibly select one SS for scheduling, provided that the maximum processing capability is not exceeded.

[0087] Essence of this embodiment lies in dynamical allocation of a hardware processing capability for PDCCH monitoring on the cell-1 and cell-2, thereby implementing maximum scheduling flexibility.

[0088] Optionally, in an embodiment, the processing capability for monitoring the SS described in the foregoing embodiments is related to at least one of the following: a specific DCI format or size; a specific SS; a parameter of the transmission object; a configured quantity of the plurality of transmission objects; and a control resource set CORESET identifier.

[0089] That is, within a specific time, a monitoring capability allocated by the terminal device is related to at least one of a specific DCI format or size, a specific search space, a cell parameter (numerology/SCS), the number of scheduled cells, and a CORESET identifier (CORESET ID, pool ID, or the like).

[0090] In this embodiment, a monitoring capability for monitoring DCI may be a same monitoring capability for the scheduling cell or any one or more scheduled cells; or, this part of capability is formed by a portion divided from a monitoring capability for the scheduling cell and a portion divided from a monitoring capability for the scheduled cell (for details, refer to Embodiment 6 of the present invention hereinafter).

[0091] Optionally, in an embodiment, the specific time described in the foregoing embodiments and at least one of the specific first specific time, second specific time, third specific time, and fourth specific time include one of the following:

a specific time point;

at least one slot;

one time interval;

within a valid time of a monitoring timer; and

a physical downlink control channel PDCCH monitoring opportunity, where earliest starting positions of schedulable physical downlink shared channels PDSCHs or physical uplink shared channels PUSCHs corresponding to the PDCCH monitoring opportunity are the same. For example, the PDCCH monitoring

opportunity satisfies that the earliest starting positions of the scheduled PDSCHs/PUSCHs both are N.

[0092] Optionally, in an embodiment, in the embodiment 100, before the obtaining scheduling configuration information, the method further includes:
5 sending a terminal capability, where the terminal capability includes at least one of the following:

whether monitoring on scheduling of one transmission object by at least two transmission objects is supported;

10 a maximum processing capability for monitoring at least two transmission objects;

an earliest starting position of a schedulable PDSCH or PUSCH;

a length of a specific time interval; and

a length of a monitoring timer.

[0093] Optionally, in each of the foregoing embodiments, the network device
15 may configure, for the terminal device, the foregoing configuration of the cell-1 and cell-2, an SS (including CR-SS, SE-SS, or O-SS) to be monitored, a scheduled DCI format, and the like. Optionally, the configuration needs to meet the foregoing restriction on monitoring by the terminal device; or the network device receives a capability reported by the terminal device, and performs configuration based on the
20 capability of the terminal device.

[0094] In order to describe in detail the search space monitoring method provided in the embodiments of the present invention, the following provides descriptions with reference to several specific embodiments.

[0095] Embodiment 1:

25 **[0096]** The network device configures a PCell and an SCell for the terminal device, and the SCell schedules the PCell. SCSs of the PCell and the SCell are both 15 kHz (that is, $\mu = 0$).

[0097] The network device configures the number A of PDCCH candidates for an SE-SS in which the PCell is self-scheduled to be 40, the number B of PDCCH
30 candidates for an O-SS in which the SCell is self-scheduled to be 15, and the number

C of PDCCH candidates for a CR-SS in which the SCell schedules the PCell to be 20, that is, part of a processing capability for the SCell is allocated for scheduling the PCell.

[0098] The terminal device monitors the foregoing SSs simultaneously, where $A < 44$ and $B + C = 35 < 44$, both not exceeding a maximum processing capability of the terminal device within one slot.

[0099] Embodiment 2:

[00100] The network device configures a PCell and an SCell for the terminal device, and the SCell schedules the PCell. SCSs of the PCell and the SCell are both 15 kHz (that is, $\mu = 0$).

[00101] A cross-carrier scheduling capability N supported and reported by the terminal device is 1.5.

[00102] The network device configures the number A of PDCCH candidates for an SE-SS in which the PCell is self-scheduled to be 40, the number B of PDCCH candidates for an O-SS in which the SCell is self-scheduled to be 40, and the number C of PDCCH candidates for a CR-SS in which the SCell schedules the PCell to be 20, that is, part of a processing capability for the SCell is allocated for scheduling the PCell.

[00103] The terminal device monitors the foregoing SSs simultaneously, where $A < 44$, $B + C = 60$, and $60 > 44$; however, $60 < 44 \times N = 66$, thereby not exceeding a maximum processing capability of the terminal device within one slot.

[00104] Embodiment 3:

[00105] The network device configures a PCell and an SCell for the terminal device, and the SCell schedules the PCell. An SCS of the PCell is 15 kHz (that is, $\mu = 0$), and an SCS of the SCell is 30 kHz (that is, $\mu = 1$).

[00106] A threshold X_1 for the scheduled cell reported by the terminal device is 22, and the network device calculates $X_2 = 18$, satisfying $22/44 + 18/36 = 1$.

[00107] The network device configures the number A of PDCCH candidates for an SE-SS in which the PCell is self-scheduled to be 20, the number B of PDCCH candidates for an O-SS in which the SCell is self-scheduled to be 20, and the number

C of PDCCH candidates for a CR-SS in which the SCell schedules the PCell to be 10, that is, part of a processing capability for the SCell is allocated for scheduling the PCell.

5 [00108] The terminal device monitors the foregoing SSs simultaneously, where $A < X_1 = 22$, $C < X_2 = 18$, and $B < 36$, not exceeding a maximum processing capability of the terminal device within one slot.

[00109] Embodiment 4:

10 [00110] The network device configures a PCell and an SCell for the terminal device, and the SCell schedules the PCell. An SCS of the PCell is 15 kHz (that is, $\mu = 0$), and an SCS of the SCell is 30 kHz (that is, $\mu = 1$).

[00111] A threshold X_1 for the scheduled cell reported by the terminal device is 22, and the network device calculates $X_2 = 18$, satisfying $22/44 + 18/36 = 1$.

15 [00112] The network device configures the number A of PDCCH candidates for an SE-SS in which the PCell is self-scheduled to be 20, the number B of PDCCH candidates for an O-SS in which the SCell is self-scheduled to be 20, and the number C of PDCCH candidates for a CR-SS in which the SCell schedules the PCell to be 10, that is, part of a processing capability for the SCell is allocated for scheduling the PCell.

20 [00113] The terminal device monitors the foregoing SSs simultaneously, where $A/44 + C/36 = 20/44 + 10/36 < 1$, and $B < 36$, thereby not exceeding a maximum processing capability of the terminal device within one slot.

[00114] Embodiment 5:

25 [00115] The network device configures a PCell and an SCell for the terminal device, and the SCell schedules the PCell. SCSs of the PCell and the SCell are both 15 kHz (that is, $\mu = 0$).

[00116] The network device configures a scaling factor N, which indicates how to allocate a maximum processing capability between cells. $N = 0.5$, which means that half of the capability is allocated for self-scheduling of the PCell, and the other half of the capability is used for the SCell scheduling the PCell.

[00117] Based on the configured N and the SCS of the cell, the terminal device determines a capability for PDCCH monitoring in the scheduled PCell.

[00118] The maximum number of PDCCH candidates for the SE-SS in which the PCell is self-scheduled is $44 \times N = 24$, and the maximum number of PDCCH candidates for the CR-SS in which the SCell schedules the PCell is $44 \times N = 22$.

[00119] A DCI size budget for self-scheduling of the PCell is $4 \times N = 2$, a DCI size budget for the SCell scheduling the PCell is $4 \times N = 2$, that is, the number of different DCI formats for monitoring self-scheduling is 2, and the number of different DCI formats for the SCell scheduling the PCell is 2.

[00120] Embodiment 6:

[00121] The network device configures a PCell and an SCell for the terminal device, where SCSs of both the PCell and the SCell are 15 kHz (that is, $\mu = 0$); and a DCI-J is configured for the PCell, for scheduling data of both the PCell and the SCell.

[00122] The terminal device configures part of a monitoring capability for monitoring the DCI-J.

[00123] This part of monitoring capability may be a same monitoring capability for the PCell or the SCell, or this part of capability is formed by a portion of a monitoring capability for the PCell and a portion of a monitoring capability for the SCell.

[00124] Based on a specific proportion (scaling factor), the terminal device may report an allocation ratio to the network device, or according to a specific rule, for example, DCI-J is only for scheduling the PDSCH, the SCell self-schedules the PUSCH, or the PCell performs cross-carrier scheduling of the PUSCH on the SCell.

[00125] In this case, a scheduling capability for the PDSCH on the SCell is allocated for monitoring the DCI-J.

[00126] Embodiment 7:

[00127] The network device configures the terminal device to monitor a TRP-1 (whose associated CORESET pool ID is 0) and a TRP-2 (whose associated

CORESET pool ID is 1) on the PCell. Each TRP performs self-scheduling, and the TRP-1 may also schedule the TRP-2. An SCS of the PCell is 15 kHz (that is, $\mu = 0$).

[00128] An SS-0 and an SS-1 are associated with a CORESET pool ID-0, an SS-2 is associated with a CORESET pool ID-1, the SS-0 schedules a TRP-0, and the SS-1 and the SS-2 can schedule a TRP-1.

[00129] The terminal device reports its supported cross-TRP scheduling capability L being 1, and a total scheduling capability of the two TRPs R being 1.5, that is, the maximum number of PDCCH candidates = $44 * R = 66$.

[00130] The network device configures the number A of PDCCH candidates for the SS-0 to be 20, the number B of PDCCH candidates for the SS-2 to be 20, and the number C of PDCCH candidates for the SS-1 to be 10, that is, part of a processing capability for the TRP-1 is allocated for monitoring scheduling of the TPR-2.

[00131] The terminal device monitors the foregoing SSs simultaneously, where $A + B + C < 66$ and $A + C = 30 < 44$, both not exceeding a maximum processing capability of the terminal device.

[00132] The foregoing embodiments of the present invention can be applied to the search space monitoring method in a CA or M-TRP scenario. Both self-scheduling of one cell (or TRP) and being scheduled by another cell (or TRP) can be supported. For example, monitoring on DCI for scheduling the PCell and that for the SCell scheduling the PCell is performed. The maximum number of PDCCH candidates blindly detected by the terminal device, the maximum number of non-overlapping CCEs, the DCI size budget, and the like are allocated between two scheduling cells, thereby simplifying implementation of the terminal device and reducing power consumption.

[00133] It should be noted that the descriptions of the foregoing embodiments are mostly made by using two cells as an example, and this solution is applicable to scenarios with more than two cells.

[00134] The descriptions of the foregoing embodiments use the cell-2 scheduling only the cell-1 and the cell-2 itself as an example, and this solution is also applicable to a scenario in which the cell-2 schedules more than two cells.

[00135] In the foregoing solution, DCI for the cell-2 scheduling the cell-1 may be DCI for scheduling one cell alone, or DCI for simultaneously/jointly scheduling a plurality of cells. For example, when the cell-2 schedules the cell-1, one piece of special DCI may be for scheduling data of two cells simultaneously.

5 **[00136]** The foregoing embodiments of the present invention may also be applied to a multiple transmission panel (multiple Transmission and Reception Panel, M-TRP) scenario, that is, the cell-1 and the cell-2 in the present invention may alternatively be a TRP-1 and a TRP-2 of the same cell, the terminal device monitors a PDCCH of an SS corresponding to different TRPs (that is, configured with
10 different CORESET pool indexes).

[00137] It should be noted that the foregoing embodiments in this specification are described by using at least two cells scheduling one cell as an example. Actually, the foregoing embodiments are also applicable to a scenario in which at least two TRPs schedule one TRP. That is, the cells in the foregoing embodiments may be
15 replaced with TRPs.

[00138] The foregoing describes in detail the search space monitoring method according to the embodiments of the present invention with reference to FIG. 1. The following describes in detail the search space monitoring method according to another embodiment of the present invention with reference to FIG. 2. It can be
20 understood that interaction between the network device and the terminal device described from the network device side is the same as the description on the terminal device side in the method shown in FIG. 1. To avoid repetition, related descriptions are appropriately omitted.

[00139] FIG. 2 is a schematic diagram of an implementation flowchart of a search
25 space monitoring method according to an embodiment of the present invention. The method may be applied to a network device side. As shown in FIG. 2, the method 200 includes the following steps.

[00140] S202: Send scheduling configuration information; where the scheduling configuration information is used for monitoring an SS by a terminal device, a
30 plurality of transmission objects are configured for the terminal device, and the SS

includes an SS in which at least two transmission objects schedule one transmission object.

[00141] According to the search space monitoring method provided in this embodiment of the present invention, a plurality of transmission objects (for example, a plurality of cells or a plurality of TRPs) are configured for the terminal device, to support self-scheduling of one cell (or TRP) and scheduling by another cell (or TRP), for example, supporting both self-scheduling of a PCell and scheduling the PCell by using an SCell. This resolves the problem of a limited control channel capacity (of the PCell), thereby improving communication efficiency.

[00142] Optionally, in an embodiment, the plurality of transmission objects include at least a first transmission object and a second transmission object, and the SS being monitored includes at least one of the following:

a first SS in which the first transmission object is self-scheduled;

a second SS in which the second transmission object schedules the first transmission object; and

a third SS in which the second transmission object is self-scheduled.

[00143] Optionally, in an embodiment, before the sending scheduling configuration information, the method further includes: receiving a terminal capability, where the terminal capability includes at least one of the following:

whether monitoring on scheduling of one transmission object by at least two transmission objects is supported;

a maximum processing capability for monitoring at least two transmission objects;

an earliest starting position of a schedulable PDSCH or PUSCH;

a length of a specific time interval; and

a length of a monitoring timer.

[00144] The foregoing describes in detail the search space monitoring method according to the embodiments of the present invention with reference to FIG. 1 and

FIG. 2. The following describes in detail a terminal device according to an embodiment of the present invention with reference to FIG. 3.

[00145] FIG. 3 is a schematic structural diagram of a terminal device according to an embodiment of the present invention. A plurality of transmission objects are configured for the terminal device. As shown in FIG. 3, the terminal device 300 includes:

an obtaining module 302, configured to obtain scheduling configuration information; and

a monitoring module 304, configured to monitor an SS based on the scheduling configuration information, where the SS includes an SS in which at least two transmission objects schedule one transmission object.

[00146] A plurality of transmission objects (for example, a plurality of cells or a plurality of TRPs) are configured for the terminal device provided in this embodiment of the present invention, to support self-scheduling of one cell (or TRP) and scheduling by another cell (or TRP), for example, supporting both self-scheduling of a PCell and scheduling the PCell by using an SCell. This resolves the problem of a limited control channel capacity (of the PCell), thereby improving communication efficiency.

[00147] Optionally, in an embodiment, the plurality of transmission objects include at least a first transmission object and a second transmission object, and the SS being monitored includes at least one of the following:

a first SS in which the first transmission object is self-scheduled;

a second SS in which the second transmission object schedules the first transmission object; and

a third SS in which the second transmission object is self-scheduled.

[00148] Optionally, in an embodiment, at least one of the following is satisfied within a first specific time:

a processing capability for monitoring the first SS does not exceed a maximum processing capability for a single transmission object;

a total processing capability for monitoring the second SS and the third SS does not exceed a maximum processing capability for a single transmission object; and

5 a total processing capability for monitoring the second SS and the third SS does not exceed L multiplied by a maximum processing capability for a single transmission object, where L is a positive number.

[00149] Optionally, in an embodiment, L is less than or equal to the number of transmission objects scheduled by the second transmission object.

[00150] Optionally, in an embodiment, L is predefined; or

10 L is related to a maximum processing capability M reported by the terminal device.

[00151] Optionally, in an embodiment, a processing capability threshold A_i is assigned to the i-th transmission object X_i in the at least two transmission objects, and X_i does not exceed a maximum processing capability for a single transmission
15 object; and

within a second specific time, a processing capability for an SS in which the A_i schedules one transmission object does not exceed X_i .

[00152] Optionally, in an embodiment, at least two of the X_i satisfy the following relationship:

20
$$\sum_{i=1}^N X_i = R; \text{ where}$$

N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

R is a maximum processing capability determined based on at least one of parameters of the at least two transmission objects; or

25 R is a maximum processing capability determined based on a parameter of the one transmission object that is scheduled; or

R is a maximum processing capability reported by the terminal device.

[00153] Optionally, in an embodiment, at least two of the X_i satisfy the following relationship:

$$\sum_{i=1}^N \frac{X_i}{P_i} = 1; \text{ where}$$

5 N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

P_i is a maximum processing capability determined based on a parameter of the A_i .

[00154] Optionally, in an embodiment, a processing capability G_i is assigned to the i-th transmission object A_i in the at least two transmission objects, and G_i does not exceed a maximum processing capability for a single transmission object; and

10

within a third specific time, a processing capability for an SS in which the A_i schedules one transmission object is G_i .

[00155] Optionally, in an embodiment, at least two of the G_i satisfy the following relationship:

15

$$\sum_{i=1}^N G_i \leq S; \text{ where}$$

N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

S is a maximum processing capability determined based on at least one of parameters of the at least two transmission objects; or

20

S is a maximum processing capability determined based on a parameter of the one transmission object that is scheduled.

[00156] Optionally, in an embodiment, at least two of the G_i satisfy the following relationship:

$$\sum_{i=1}^N \frac{G_i}{Q_i} \leq 1; \text{ where}$$

N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

Q_i is a maximum processing capability determined based on a parameter of the A_i .

[00157] Optionally, in an embodiment, within a fourth specific time, for the i-th transmission object A_i in the at least two transmission objects, a processing capability for monitoring an SS in which the A_i schedules one transmission object does not exceed a maximum processing capability for the A_i .

[00158] Optionally, in an embodiment, a processing capability for monitoring the SS is related to at least one of the following:

a specific downlink control information DCI format or size; a specific SS; a parameter of the transmission object; a configured quantity of the plurality of transmission objects; and a control resource set CORESET identifier.

[00159] Optionally, in an embodiment, at least one of the first specific time, the second specific time, the third specific time, and the fourth specific time includes one of the following:

a specific time point;

at least one slot;

one time interval;

within a valid time of a monitoring timer; and

a PDCCH monitoring opportunity, where earliest starting positions of schedulable PDSCHs or PUSCHs corresponding to the PDCCH monitoring opportunity are the same.

[00160] Optionally, in an embodiment, the scheduling configuration information is used to configure at least one of the following

configuration of the plurality of transmission objects, an SS to be monitored, and a DCI format for scheduling.

[00161] Optionally, in an embodiment, the terminal device 300 further includes a sending module, configured to send a terminal capability, and the terminal capability includes at least one of the following:

whether monitoring on scheduling of one transmission object by at least two transmission objects is supported;

a maximum processing capability for monitoring at least two transmission objects;

an earliest starting position of a schedulable PDSCH or PUSCH;

a length of a specific time interval; and

a length of a monitoring timer.

[00162] For the terminal device 300 in this embodiment of the present invention, refer to the processes of the method 100 in the corresponding embodiment of the present invention, and the units or modules of the terminal device 300 and other operations and/or functions described above are used to implement the corresponding processes in the method 100, with the same or equivalent technical effects achieved. For brevity, details are not repeated herein.

[00163] FIG. 4 is a schematic structural diagram of a network device according to an embodiment of the present invention. As shown in FIG. 4, the network device 400 includes:

a sending module 402, configured to send scheduling configuration information; where

the scheduling configuration information is used for monitoring an SS by a terminal device, a plurality of transmission objects are configured for the terminal device, and the SS includes an SS in which at least two transmission objects schedule one transmission object.

[00164] In this embodiment of the present invention, a plurality of transmission objects (for example, a plurality of cells or a plurality of TRPs) are configured for the terminal device, to support self-scheduling of one cell (or TRP) and scheduling

by another cell (or TRP), for example, supporting both self-scheduling of a PCell and scheduling the PCell by using an SCell. This resolves the problem of a limited control channel capacity (of the PCell), thereby improving communication efficiency.

5 **[00165]** Optionally, in an embodiment, the plurality of transmission objects include at least a first transmission object and a second transmission object, and the SS being monitored includes at least one of the following:

 a first SS in which the first transmission object is self-scheduled;

 a second SS in which the second transmission object schedules the first
10 transmission object; and

 a third SS in which the second transmission object is self-scheduled.

[00166] Optionally, in an embodiment, the network device 400 further includes a receiving module that may be configured to receive a terminal capability, and the terminal capability includes at least one of the following:

15 whether monitoring on scheduling of one transmission object by at least two transmission objects is supported;

 a maximum processing capability for monitoring at least two transmission objects;

 an earliest starting position of a schedulable PDSCH or PUSCH;

20 a length of a specific time interval; and

 a length of a monitoring timer.

[00167] For the network device 400 in this embodiment of the present invention, refer to the processes of the method 200 in the corresponding embodiment of the present invention, and the units or modules of the network device 400 and other
25 operations and/or functions described above are used to implement the corresponding processes in the method 200, with the same or equivalent technical effects achieved. For brevity, details are not repeated herein.

[00168] All the embodiments in this specification are described in a progressive manner. Each embodiment focuses on differences from other embodiments. For the
30 part that is the same or similar between different embodiments, reference may be

made between the embodiments. The device embodiment is essentially similar to the method embodiment, and therefore is described briefly. For related information, refer to descriptions of the related parts in the method embodiment.

[00169] FIG. 5 is a block diagram of a terminal device according to another embodiment of the present invention. The terminal device 500 shown in FIG. 5 includes at least one processor 501, a memory 502, at least one network interface 504, and a user interface 503. The components of the terminal device 500 are coupled together by using a bus system 505. It can be understood that the bus system 505 is configured to implement connection communication between these components. The bus system 505 may include not only a data bus but also a power supply bus, a control bus, and a status signal bus. However, for clarity of description, various types of buses in FIG. 5 are marked as the bus system 505.

[00170] The user interface 503 may include a display, a keyboard, a click device (for example, a mouse or a trackball (trackball)), a touch board, or a touchscreen.

[00171] It can be understood that the memory 502 in this embodiment of the present invention may be a volatile memory or a nonvolatile memory, or may include both a volatile memory and a nonvolatile memory. The non-volatile memory may be a read-only memory (Read-Only Memory, ROM), a programmable read only memory (Programmable ROM, PROM), an erasable programmable read-only memory (Erasable PROM, EPROM), and an electrically erasable programmable read-only memory (Electrically EPROM, EEPROM), or flash memory. The volatile memory may be a random access memory (Random Access Memory, RAM), and the RAM is used as an external cache. As exemplary rather than restrictive description, many forms of RAM can be used, such as a static random access memory (Static RAM, SRAM), a dynamic random access memory (Dynamic RAM, DRAM), a synchronous dynamic random access memory (Synchronous DRAM, SDRAM), a double data rate synchronous dynamic random access memory (Double Data Rate SDRAM, DDRSDRAM), an enhanced synchronous dynamic random access memory (Enhanced SDRAM, ESDRAM), a synchronous link dynamic random access memory (Synchlink DRAM, SLDRAM), and a direct Rambus random access

memory (Direct Rambus RAM, DRRAM). The memory 502 in the system and method described in the embodiments of the present invention is intended to include but is not limited to these and any other suitable types of memories.

[00172] In some implementations, the memory 502 stores the following elements:
5 an executable module or a data structure, or a subset thereof, or an extended set thereof: an operating system 5021 and an application program 5022.

[00173] The operating system 5021 includes various system programs, such as a framework layer, a kernel library layer, and a driver layer, and is configured to implement various basic services and process hardware-based tasks. The application
10 program 5022 includes various application programs, such as a media player (Media Player) and a browser (Browser), and is configured to implement various application services. A program that implements the methods of the embodiments of the present invention may be included in the application program 5022.

[00174] In this embodiment of the present invention, the terminal device 500
15 further includes a computer program stored in the memory 502 and capable of running on the processor 501. When being executed by the processor 501, the computer program implements the steps of the following method embodiment 100.

[00175] The method disclosed in the embodiment of the present invention is applicable to a processor 501, or implemented by the processor 501. The processor
20 501 may be an integrated circuit chip with a signal processing capability. In an implementation process, the steps in the foregoing method may be implemented by using a hardware integrated logic circuit in the processor 501, or by using instructions in a form of software. The foregoing processor 501 may be a general processor, a digital signal processor (Digital Signal Processor, DSP), an
25 application-specific integrated circuit (Application Specific Integrated Circuit, ASIC), a field programmable gate array (Field Programmable Gate Array, FPGA) or another programmable logic device, a discrete gate or transistor logic device, or a discrete hardware component. It may implement or perform the methods, the steps, and logical block diagrams that are disclosed in the embodiments of the present
30 invention. The general-purpose processor may be a microprocessor or any regular

processor. Steps of the methods disclosed with reference to the embodiments of the present invention may be directly performed by a hardware decoding processor, or may be performed by using a combination of hardware and software modules in the decoding processor. The software module may be located in a computer-readable storage medium that is mature in the art, such as a random access memory, a flash memory, a read-only memory, a programmable read-only memory, or an electrically erasable programmable memory, or a register. The computer-readable storage medium is located in the memory 502, and the processor 501 reads information in the memory 502 and implements, in combination with its hardware, the steps of the foregoing methods. Specifically, a computer program is stored in the computer-readable storage medium, and when the computer program is executed by the processor 501, the steps of the embodiments of the foregoing method 100 are implemented.

[00176] It can be understood that the embodiments described in the present invention may be implemented by hardware, software, firmware, middleware, microcode, or a combination thereof. For hardware implementation, the processing unit may be implemented in one or more application specific integrated circuits (Application Specific Integrated Circuit, ASIC), digital signal processors (Digital Signal Processing, DSP), digital signal processing devices (DSP Device, DSPD), programmable logic devices (Programmable Logic Device, PLD), field-programmable gate arrays (Field-Programmable Gate Array, FPGA), general purpose processors, controllers, microcontrollers, microprocessors, and other electronic units for performing the functions described in this disclosure, or a combination thereof.

[00177] For software implementation, the technologies described in the embodiments of the present invention may be implemented by modules (for example, processes or functions) that perform the functions described in the embodiments of the present invention. Software code may be stored in the memory and executed by the processor. The memory may be implemented in or outside the processor.

[00178] The terminal device 500 is capable of implementing the processes that are implemented by the terminal device in the foregoing embodiments, with the same or equivalent technical effects achieved. To avoid repetition, details are not described herein again.

5 **[00179]** Referring to FIG. 6, FIG. 6 is a structural diagram of a network device to which the embodiments of the present invention are applied. Details of the method embodiment 200 can be implemented to achieve the same effects. As shown in FIG. 6, the network device 600 includes a processor 601, a transceiver 602, a memory 603, and a bus interface.

10 **[00180]** In this embodiment of the present invention, the network device 600 further includes a computer program stored in the memory 603 and capable of running on the processor 601. When the computer program is executed by the processor 601, the steps of the method embodiment 200 are implemented.

[00181] In FIG. 6, a bus architecture may include any quantity of interconnected
15 buses and bridges, specifically for interconnecting various circuits of one or more processors represented by the processor 601 and a memory represented by the memory 603. The bus architecture may further interconnect various other circuits such as a peripheral device, a voltage regulator, and a power management circuit. These are all well known in the art, and therefore are not further described in this
20 specification. The bus interface provides an interface. The transceiver 602 may be a plurality of components, that is, the transceiver 602 includes a transmitter and a receiver, and provides a unit for communicating with various other apparatuses on a transmission medium.

[00182] The processor 601 is responsible for bus architecture management and
25 general processing. The memory 603 may store data used when the processor 601 performs an operation.

[00183] An embodiment of the present invention further provides a computer-readable storage medium, where a computer program is stored in the computer-readable storage medium. When the computer program is executed by a
30 processor, the processes of any one of the foregoing method embodiment 100 and the foregoing method embodiment 200 are implemented, with the same technical

effects achieved. To avoid repetition, details are not described herein again. The computer-readable storage medium is, for example, a read-only memory (Read-Only Memory, ROM), a random access memory (Random Access Memory, RAM), a magnetic disk, or an optical disc.

5 **[00184]** It should be noted that in this specification, the term "include", "comprise", or any of their variants are intended to cover a non-exclusive inclusion, so that a process, a method, an article, or an apparatus that includes a list of elements not only includes those elements but also includes other elements that are not expressly listed, or further includes elements inherent to such process, method,
10 article, or apparatus. In absence of more constraints, an element preceded by "includes a ..." does not preclude existence of other identical elements in the process, method, article, or apparatus that includes the element.

[00185] According to the foregoing description of the implementations, a person skilled in the art may clearly understand that the methods in the foregoing
15 embodiments may be implemented by using software in combination with a necessary common hardware platform, and certainly may alternatively be implemented by using hardware. However, in most cases, the former is a preferred implementation. Based on such an understanding, the technical solutions of the present invention essentially or the part contributing to the prior art may be
20 implemented in a form of a software product. The software product is stored in a storage medium (such as a ROM/RAM, a magnetic disk, or an optical disc), and includes several instructions for instructing a terminal (which may be a mobile phone, a computer, a server, an air conditioner, a network device, or the like) to perform the methods described in the embodiments of the present invention.

25 **[00186]** Some embodiments of the present invention have been described with reference to the attached drawings; however, the present invention is not limited to the aforesaid embodiments, and these embodiments are merely illustrative but are not intended to limit the present invention. Persons of ordinary skill in the art may further derive many other implementations according to the teachings of the present

invention and within the scope defined in the claims, and all of the implementations shall fall within the scope of the present invention.

CLAIMS

What is claimed is:

1. A search space monitoring method, wherein the method is executed by a terminal device, a plurality of transmission objects are configured for the terminal device, and the method comprises:

obtaining scheduling configuration information; and

monitoring a search space SS based on the scheduling configuration information, wherein the SS comprises an SS in which at least two transmission objects schedule one transmission object.

2. The method according to claim 1, wherein the plurality of transmission objects comprise at least a first transmission object and a second transmission object, and the SS being monitored comprises at least one of the following:

a first SS in which the first transmission object is self-scheduled;

a second SS in which the second transmission object schedules the first transmission object; and

a third SS in which the second transmission object is self-scheduled.

3. The method according to claim 2, wherein at least one of the following is satisfied within a first specific time:

a processing capability for monitoring the first SS does not exceed a maximum processing capability for a single transmission object; and

a total processing capability for monitoring the second SS and the third SS does not exceed a maximum processing capability for a single transmission object; and

a total processing capability for monitoring the second SS and the third SS does not exceed L multiplied by a maximum processing capability for a single transmission object, wherein L is a positive number.

4. The method according to claim 3, wherein L is less than or equal to the number of transmission objects scheduled by the second transmission object.

5. The method according to claim 3, wherein

L is predefined; or

L is related to a maximum processing capability M reported by the terminal device.

6. The method according to claim 1, wherein

5 a processing capability threshold X_i is assigned to the i-th transmission object A_i in the at least two transmission objects, and X_i does not exceed a maximum processing capability for a single transmission object; and

within a second specific time, a processing capability for an SS in which the A_i schedules one transmission object does not exceed X_i .

10 7. The method according to claim 6, wherein at least two of the X_i satisfy the following relationship:

$$\sum_1^N X_i = R; \text{ wherein}$$

N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

15 R is a maximum processing capability determined based on at least one of parameters of the at least two transmission objects; or

R is a maximum processing capability determined based on a parameter of the one transmission object that is scheduled; or

R is a maximum processing capability reported by the terminal device.

20 8. The method according to claim 6, wherein at least two of the X_i satisfy the following relationship:

$$\sum_1^N \frac{X_i}{P_i} = 1; \text{ wherein}$$

N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

P_i is a maximum processing capability determined based on a parameter of the A_i .

9. The method according to claim 1, wherein

a processing capability G_i is assigned to the i-th transmission object A_i in the
5 at least two transmission objects, and G_i does not exceed a maximum processing capability for a single transmission object; and

within a third specific time, a processing capability for an SS in which the A_i schedules one transmission object is G_i .

10. The method according to claim 9, wherein at least two of the G_i satisfy the
10 following relationship:

$$\sum_1^N G_i \leq S; \text{ wherein}$$

N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

S is a maximum processing capability determined based on at least one of
15 parameters of the at least two transmission objects; or

S is a maximum processing capability determined based on a parameter of the one transmission object that is scheduled.

11. The method according to claim 9, wherein at least two of the G_i satisfy the
following relationship:

20
$$\sum_1^N \frac{G_i}{Q_i} \leq 1; \text{ wherein}$$

N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

Q_i is a maximum processing capability determined based on a parameter of the A_i .

12. The method according to claim 1, wherein, within a fourth specific time, for the i-th transmission object A_i in the at least two transmission objects, a processing capability for monitoring an SS in which the A_i schedules one transmission object does not exceed a maximum processing capability for the A_i .

5 13. The method according to claim 1, wherein a processing capability for monitoring the SS is related to at least one of the following:

a specific downlink control information DCI format or size; a specific SS; a parameter of the transmission object; a configured quantity of the plurality of transmission objects; and a control resource set CORESET identifier.

10 14. The method according to claim 3, 6, 9, or 12, wherein at least one of the first specific time, the second specific time, the third specific time, and the fourth specific time comprises one of the following:

a specific time point;

at least one slot;

15 one time interval;

within a valid time of a monitoring timer; and

a physical downlink control channel PDCCH monitoring opportunity, wherein earliest starting positions of schedulable physical downlink shared channels PDSCCHs or physical uplink shared channels PUSCHs corresponding to the PDCCH monitoring opportunity are the same.

20 15. The method according to claim 1, wherein the scheduling configuration information is used to configure at least one of the following:

configuration of the plurality of transmission objects, an SS to be monitored, and a DCI format for scheduling.

25 16. The method according to claim 1, wherein before the obtaining scheduling configuration information, the method further comprises: sending a terminal capability, wherein the terminal capability comprises at least one of the following:

whether monitoring on scheduling of one transmission object by at least two transmission objects is supported;

a maximum processing capability for monitoring at least two transmission objects;

an earliest starting position of a schedulable PDSCH or PUSCH;

a length of a specific time interval; and

5 a length of a monitoring timer.

17. A search space monitoring method, wherein the method is executed by a network device, and the method comprises:

sending scheduling configuration information; wherein

10 the scheduling configuration information is used for monitoring an SS by a terminal device, a plurality of transmission objects are configured for the terminal device, and the SS comprises an SS in which at least two transmission objects schedule one transmission object.

18. The method according to claim 17, wherein the plurality of transmission objects comprise at least a first transmission object and a second transmission object, and the SS being monitored comprises at least one of the following:

a first SS in which the first transmission object is self-scheduled;

a second SS in which the second transmission object schedules the first transmission object; and

a third SS in which the second transmission object is self-scheduled.

20 19. The method according to claim 17, wherein before the sending scheduling configuration information, the method further comprises: receiving a terminal capability, wherein the terminal capability comprises at least one of the following:

whether monitoring on scheduling of one transmission object by at least two transmission objects is supported;

25 a maximum processing capability for monitoring at least two transmission objects;

an earliest starting position of a schedulable PDSCH or PUSCH;

a length of a specific time interval; and

a length of a monitoring timer.

20. A terminal device, wherein a plurality of transmission objects are configured for the terminal device, and the terminal device comprises:

an obtaining module, configured to obtain scheduling configuration information;
and

5 a monitoring module, configured to monitor an SS based on the scheduling configuration information, wherein the SS comprises an SS in which at least two transmission objects schedule one transmission object.

21. The terminal device according to claim 20, wherein the plurality of transmission objects comprise at least a first transmission object and a second
10 transmission object, and the SS being monitored comprises at least one of the following:

a first SS in which the first transmission object is self-scheduled;

a second SS in which the second transmission object schedules the first
transmission object; and

15 a third SS in which the second transmission object is self-scheduled.

22. The terminal device according to claim 21, wherein at least one of the following is satisfied within a first specific time:

a processing capability for monitoring the first SS does not exceed a maximum
processing capability for a single transmission object;

20 a total processing capability for monitoring the second SS and the third SS does not exceed a maximum processing capability for a single transmission object; and

a total processing capability for monitoring the second SS and the third SS does not exceed L multiplied by a maximum processing capability for a single transmission object, wherein L is a positive number.

25 23. The terminal device according to claim 22, wherein L is less than or equal to the number of transmission objects scheduled by the second transmission object.

24. The terminal device according to claim 22, wherein

L is predefined; or

L is related to a maximum processing capability M reported by the terminal
30 device.

25. The terminal device according to claim 20, wherein

a processing capability threshold A_i is assigned to the i-th transmission object X_i in the at least two transmission objects, and X_i does not exceed a maximum processing capability for a single transmission object; and

5 within a second specific time, a processing capability for an SS in which the A_i schedules one transmission object does not exceed X_i .

26. The terminal device according to claim 25, wherein

at least two of the X_i satisfy the following relationship:

$$\sum_{i=1}^N X_i = R; \text{ wherein}$$

10 N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

R is a maximum processing capability determined based on at least one of parameters of the at least two transmission objects; or

15 R is a maximum processing capability determined based on a parameter of the one transmission object that is scheduled; or

R is a maximum processing capability reported by the terminal device.

27. The terminal device according to claim 25, wherein

at least two of the X_i satisfy the following relationship:

$$\sum_{i=1}^N \frac{X_i}{P_i} = 1; \text{ wherein}$$

20 N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

P_i is a maximum processing capability determined based on a parameter of the A_i .

28. The terminal device according to claim 20, wherein

a processing capability A_i is assigned to the i-th transmission object G_i in the at least two transmission objects, and G_i does not exceed a maximum processing capability for a single transmission object; and

5 within a third specific time, a processing capability for an SS in which the A_i schedules one transmission object is G_i .

29. The terminal device according to claim 28, wherein at least two of the G_i satisfy the following relationship:

$$\sum_1^N G_i \leq S; \text{ wherein}$$

10 N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

S is a maximum processing capability determined based on at least one of parameters of the at least two transmission objects; or

S is a maximum processing capability determined based on a parameter of the one transmission object that is scheduled.

15 30. The terminal device according to claim 28, wherein at least two of the G_i satisfy the following relationship:

$$\sum_1^N \frac{G_i}{Q_i} \leq 1; \text{ wherein}$$

N is a quantity of the at least two transmission objects, and N is greater than or equal to 2; and

20 Q_i is a maximum processing capability determined based on a parameter of the A_i .

31. The terminal device according to claim 28, wherein, within a fourth specific time, for the i-th transmission object A_i in the at least two transmission objects, a

processing capability for monitoring an SS in which the A_i schedules one transmission object does not exceed a maximum processing capability for the A_i .

32. The terminal device according to claim 20, wherein a processing capability for monitoring the SS is related to at least one of the following:

- 5 a specific downlink control information DCI format or size; a specific SS; a parameter of the transmission object; a configured quantity of the plurality of transmission objects; and a control resource set CORESET identifier.

33. The terminal device according to claim 22, 25, 28, or 31, wherein at least one of the first specific time, the second specific time, the third specific time, and the
10 fourth specific time comprises one of the following:

- a specific time point;
- at least one slot;
- one time interval;
- within a valid time of a monitoring timer; and

15 a physical downlink control channel PDCCH monitoring opportunity, wherein earliest starting positions of schedulable physical downlink shared channels PDSCHs or physical uplink shared channels PUSCHs corresponding to the PDCCH monitoring opportunity are the same.

34. The terminal device according to claim 20, wherein
20 the scheduling configuration information is used to configure at least one of the following:

- configuration of the plurality of transmission objects, an SS to be monitored, and a DCI format for scheduling.

35. The terminal device according to claim 20, wherein the terminal device
25 further comprises a sending module, configured to send a terminal capability, and the terminal capability comprises at least one of the following:

- whether monitoring on scheduling of one transmission object by at least two transmission objects is supported;

a maximum processing capability for monitoring at least two transmission objects;

an earliest starting position of a schedulable PDSCH or PUSCH;

a length of a specific time interval; and

5 a length of a monitoring timer.

36. A network device, comprising:

a sending module, configured to send scheduling configuration information; wherein

10 the scheduling configuration information is used for monitoring an SS by a terminal device, a plurality of transmission objects are configured for the terminal device, and the SS comprises an SS in which at least two transmission objects schedule one transmission object.

15 37. The network device according to claim 36, wherein the plurality of transmission objects comprise at least a first transmission object and a second transmission object, and the SS being monitored comprises at least one of the following:

a first SS in which the first transmission object is self-scheduled;

a second SS in which the second transmission object schedules the first transmission object; and

20 a third SS in which the second transmission object is self-scheduled.

38. The network device according to claim 36, wherein the network device further comprises a receiving module, configured to receive a terminal capability, and the terminal capability comprises at least one of the following:

25 whether monitoring on scheduling of one transmission object by at least two transmission objects is supported;

a maximum processing capability for monitoring at least two transmission objects;

an earliest starting position of a schedulable PDSCH or PUSCH;

a length of a specific time interval; and

30 a length of a monitoring timer.

39. A terminal device, comprising a memory, a processor, and a computer program stored in the memory and capable of running on the processor, wherein when the computer program is executed by the processor, the search space monitoring method according to any one of claims 1 to 16 are implemented.

5 40. A network device, comprising a memory, a processor, and a computer program stored in the memory and capable of running on the processor, wherein when the computer program is executed by the processor, the steps of the search space monitoring method according to any one of claims 17 to 19 are implemented.

10 41. A computer-readable storage medium, wherein the computer-readable storage medium stores a computer program, and when the computer program is executed by a processor, the steps of the search space monitoring method according to any one of claims 1 to 19 are implemented.

15 42. A computer program product, wherein the computer program product is executed by at least one processor to implement the search space monitoring method according to any one of claims 1 to 19.

43. A search space monitoring apparatus, wherein the apparatus is configured to perform the search space monitoring method according to any one of claims 1 to 19.