



- (51) **International Patent Classification:**
F41G 1/02 (2006.01) *F41G 1/30* (2006.01)
F41G 1/033 (2006.01)
- (21) **International Application Number:** PCT/US2012/042709
- (22) **International Filing Date:** 15 June 2012 (15.06.2012)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/498,226 17 June 2011 (17.06.2011) US
61/594,075 2 February 2012 (02.02.2012) US
- (71) **Applicant (for all designated States except US):** COLT DEFENSE, LLC [US/US]; 547 New Park Avenue, West Hartford, Connecticut 06110-1336 (US).
- (72) **Inventors; and**
- (75) **Inventors/Applicants (for US only):** LANGEVIN, Kevin [US/US]; 35 Harris Street, Berlin, Connecticut 06037 (US). JOSEY, Michael A. [US/US]; 7 Blueberry Lane, Farmington, Connecticut 06032 (US).
- (74) **Agent:** BOEHM, Christopher C.; Cantor Colburn LLP, 20 Church Street, 22nd Floor, Hartford, Connecticut 06103 (US).
- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) **Title:** LOCKING FRONT SIGHT FOR A FIREARM AND FIREARM WITH LOCKING FRONT SIGHT




FIG. 2

(57) **Abstract:** A front sight for a weapon, the front sight having: a mounting block; a tower pivotally mounted to the mounting block for movement between a first position and a second position; a first locking mechanism comprising a plurality of spring biased members for retaining the tower in the first position and the second position, the plurality of spring biased members being configured to allow movement of the tower between the first position and the second position in response to a force applied to the tower; and a second locking mechanism configured to lock the tower in the second position, wherein the second locking mechanism must be manually released before the tower can be moved from the second position to the first position.

**Published:****(88) Date of publication of the international search report:**

11 April 2013

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*