

Description

FIELD OF THE INVENTION AND RELATED ART STATEMENT

1. FIELD OF THE INVENTION

The present invention relates generally to a gas shutoff apparatus for a gas equipment using a town gas or liquefied petroleum gas, and more particularly to a gas shutoff apparatus for preventing gas explosion or gas poisoning due to a gas leakage from a gas supply tube or gas equipment.

2. DESCRIPTION OF THE RELATED ART

The greater part of gas accidents are caused by escape of unburned gas such as town gas or liquefied petroleum gas (hereinafter is referred to as the gas). The gas escapes when a main cock for supplying the gas to a gas equipment is opened without burning of the gas, when unexpected disconnection of a rubber tube supplying the gas to the gas equipment occurs or the rubber tube has cracks thereon, for example. In order to prevent escape of the gas in the prior art, an automatic shutoff valve, a reinforced tube, an alarm to detect the escaping gas and an automatic gas shutoff system which is connected to the alarm etc. are used.

However, the automatic shutoff valve usually cannot be activated under a small flow rate of the escaping gas, and the escape of the gas cannot be interrupted. On the other hand, in the gas alarm, it only generates an alarm, and therefore, if a person is absent from there or fails to notice it, the main cock cannot be shut, and dangerous escape of the gas cannot be interrupted. Furthermore, with regard to the automatic gas shutoff system connected to the alarm, installation of such system to existing houses is difficult owing to its high cost and necessity of connecting construction. Moreover, the above-mentioned conventional countermeasures are not effective to gas suicide which is liable to cause gas explosion.

In order to improve these defects, recently, a gas shutoff apparatus for preventing the gas explosion or gas suicide has been developed for household use. In such gas shutoff apparatus, a flow rate of the gas is detected, and when the flow rate exceeds a predetermined total flow rate per a predetermined time period, occurrence of an abnormal state is detected and supply of the gas is interrupted (by shutoff function at excess of a predetermined total flow rate). Then, when the flow rate greatly increases and is significantly larger than a predetermined flow rate, an abnormal state is detected, and supply of the gas is interrupted (by shutoff function at excess of a predetermined limit of flow rate). Moreover, when the gas equipment continuously consumes gas without variation of a flow

rate, and the time of continuous gas consumption with the flow rate exceeds a predetermined time period which is determined corresponding to an average normal consumption rate thereof, the state is detected as an abnormal state and supply of the gas is interrupted (by gas shutoff function at excess of a predetermined continuous use time).

The respective predetermined reference values of these "total flow rates", "limit of increase of flow rate" and "continuous use time" are decided, for example, corresponding to a rated measurement capacity in the respective consumer. A prior art gas shutoff apparatus embodying the above-mentioned method is disclosed in the Japanese published unexamined patent application (Tokkai) Sho 63-101619 and 108118, for example.

GB-A-1182786 describes a method and apparatus for preventing the accumulation of an explosive amount of a gas in a chemical reactor to which the gas is fed as a reactant. The flow rate of the gas is measured and compared with a delayed flow rate signal. Reduction of flow or shut-off occurs when a predetermined difference occurs.

Patent Abstracts of Japan vol. 7 no.47 (M-196)(1192) 24th February 1983 & JP-A-57195978 describes apparatus to control discharge of unburnt gas by measuring flow rate, determining average flow rate at intervals, and comparing with a standard average value, or a duration time, to issue a shut off signal when necessary. US-A-4589435 discloses a water shut-off valve which shuts off if water flows for more than a predetermined time.

EP A 0 264 856 (published 27.04.88) discloses in Fig. 10 an arrangement with first and second starting signal generators coupled to a timer via an AND-gate, and in Fig. 11 the use of a shutoff reset signal line to the timer.

FIG.1 is the block diagram of a modified form of the prior art gas shutoff apparatus of the Tokkai Sho 63-101619. Referring to FIG.1, a flow rate measurement means 1 detects a flow rate of the gas flowing from a gas supply tube to a gas equipment, and it generates a flow rate signal corresponding to the flow rate. A consumption state detection means 2 detects a "consumption state" which is represented by a maximum flow rate, a total amount of gas consumption or a time period of continuous gas consumption, on the basis of the flow rate signal.

A "reference consumption condition" is represented by combination of reference values of the "maximum gas flow rate", the "total amount of gas consumption" and the "time period of continuous gas consumption". Therefore, the words "reference consumption condition" generally imply any one of the above-mentioned three. These values are used as reference condition to produce a shutoff signal. An "initial consumption condition" is determined by an initial consumption condition setting means 3. Then

the initial consumption condition is set or varied in a varying means 10 in compliance to the reference consumption condition for starting operation of the gas shutoff apparatus.

Data of the reference consumption condition of the varying means 10 for reference consumption condition is applied to a consumption state judging means 4. Further, data of the consumption state detection means 2 is also applied to the consumption state judging means 4. The data of the consumption state detection means 2 is compared with the data of the reference consumption condition at the consumption state judging means 4. Then, when value of the consumption state exceeds that of the reference consumption condition, and a shutoff signal for closing a valve is issued to the shutoff means 5.

A timer 7 measures a predetermined time period by means of a starting signal which is issued from a starting signal generating means 8. A consumption state memory means 9 memorizes the consumption state of the house, wherein this gas shutoff apparatus is installed, on the basis of the flow rate signal issued from the flow rate measurement means 1 during an operation time period of the timer 7. The time period is selected in the order of two weeks or one month, for example. Then the "total amount of the gas consumption, the "maximum gas flow rate" and the "time period of continuous gas consumption", which are measured on the basis of the flow rate signal of the flow rate measurement means 1, are memorized in the consumption state memory means 9 from start of the timer 7. A state represented by a combination consisting of three kinds data, namely, the total amount of gas consumption, the maximum gas flow rate and the time period of continuous gas consumption is hereafter defined as "a gas consumption state". Memorized data in the consumption state memory means 9 represents pattern of the gas consumption state. The maximum data of the gas consumption state is applied to the varying means 10 for reference consumption condition, and is compared with the data of the initial consumption condition set in the initial consumption setting means 3 after a finishing of the counting operation of the timer 7. Subsequently, in case that the maximum data is different from the data of the initial consumption condition, the maximum data is set in the varying means 10 for consumption state, as a new reference consumption condition. After once setting the new reference consumption condition, a consumption state is compared with the new reference consumption condition.

A reset signal generator 6 generates a reset signal upon receipt of signal of open-state from the shutoff means 5 when it is opened. The reset signal is given to the starting signal generating means 8, which makes the timer 7 start to count from the beginning to measure the gas consumption state again. At that time, the timer 7 is cleared by the shutoff signal is-

sued from the consumption state judging means 4, and further, output data from the initial consumption condition setting means 3 is cleared and the initial consumption condition is set as a reference consumption condition.

However, in the above-mentioned constitution, from the point of time when the starting signal generating means 8 operates, for instance from the time when a push-button switch is pressed at first, or when an outside signal transfer means operates, the shutoff means 5 restores. Therefore, the time-counting starts from the time when the reset signal is inputted to the starting signal generating means 8. Consequently, there is such problem that useless and undesirable time-counting is carried out when no actual gas consumption is made, for instance, due to a long time travelling.

SUMMARY OF THE INVENTION

The invention is as defined in claims 1 and 3.

An actual or present consumption state is measured during a time period given by the operation of the timer, and a reference consumption condition is set on the basis of the data of the actual consumption state after lapse of the time period of the timer; and that the gas consumption states are always monitored even during the counting of time by the timer and after completion of the time, so that when the gas consumption state exceeds the reference consumption condition the shutoff means is actuated to operate and at the same time the timer and output data from the consumption state memory means are cleared. And, after a reset signal from the reset signal generator is inputted to the first starting signal generator, when a second starting signal generator detects a gas flow rate above a predetermined level the timer is actuated again.

Thus, according to the present invention, during actual time-counting by the timer after an initial and pre-consumption setting of the reference consumption condition, the actual gas consumption state is measured; and the reference consumption data for the consumers home is set again.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG.1 is the block diagram of the gas shutoff apparatus in the prior art;

FIG.2 is a block diagram of a gas shutoff apparatus of a first embodiment in accordance with the present invention;

FIG.3 is a graph of a reference consumption condition in the first embodiment;

FIG.4, FIG.5 and FIG.6 are flow charts in operation of the first embodiment;

FIG.7 is a block diagram of the gas shutoff apparatus of a second embodiment in accordance

with the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

FIG.2 is a block diagram of a gas shutoff apparatus of a first embodiment in the present invention. Referring to FIG.2, a flow rate measurement means 1 detects a flow rate of the gas flowing from a gas supply tube to gas equipment(s), and generates a flow rate signal corresponding to the flow rate. A consumption state detection means 2 detects a "consumption state" of the gas which is representing a maximum flow rate or total flow rate, an increase of total amount in a period or an increase of flow rate of gas consumption, and a time period of continuous gas consumption above a certain level, on the basis of the flow rate signal. A "consumption condition" is a condition for examining the consumption state and is representing the same elements as the above-mentioned three ones. A "reference consumption condition" is reference condition for producing a shutoff signal and represents combination of reference condition values of the "maximum gas flow rate", the "limit of increase of gas flow rate" and the "time period of continuous gas consumption". Therefore, the words "reference consumption condition" generally imply any one of the above-mentioned three. An "initial consumption condition" is determined by an initial consumption condition setting means 3. Then the initial consumption condition is set or adjusted in a varying means 10 for reference consumption condition for starting operation of the gas shutoff apparatus.

Data of the reference consumption condition of the varying means 10 for reference consumption condition is applied to a consumption state judging means 4. Further, data of the consumption state detection means 2 is also applied to the consumption state judging means 4, and the data of the consumption state detection means 2 is compared with the data of the reference consumption condition in the consumption state judging means 4. Then, when value of the consumption state exceeds that of the reference consumption condition, a shutoff signal for closing a valve is issued to a shutoff means 5.

A timer 7 measures a predetermined time period by means of a starting signal which is issued from a starting signal judging means 13.

Starting signal judging means 13 issues a timer start signal to make the timer 7 start, when the second starting signal generator 12 detects a gas flow above the predetermined level and gives a second starting signal thereto after reception of the first starting signal from the first starting signal generator 11.

A consumption state memory means 9 memorizes the consumption state on the basis of the flow rate signal from the flow rate measurement means 1 during counting by the time period by the timer 7. The

time period is selected, for instance, in the order of two weeks or one month. Then the consumption state comprising and representing (i) increase of gas flow rate, (ii) maximum gas flow rate and (iii) time period of continuous gas consumption, which are measured by the flow rate signal, is detected and is memorized in the consumption state memory means 9, from start of the timer 7 on.

A reset signal generator 6 generates a reset signal to reset the shutoff means 5, when an opening operation is made to once-closed shutoff means 5 for restoration of use of the gas. The reset signal is inputted to the first starting signal generator 11, which transfers a starting signal to the starting signal judging means 13. Thereafter, when a second starting signal is issued upon detection of gas flow above the predetermined level by the second starting signal generator 12 to the starting signal judging means 13, the latter gives starting signal for time-count to the timer 7. Thereafter, the gas consumption state is memorized during the time-counting in the consumption state memory means 9, and a reference consumption condition is set basing on data of actual gas consumption state observed at the time of completion of the time-counting.

FIG.3 is a graph showing operation of the first embodiment. Referring to the graph the abscissa is graduated by time and the ordinate by a reference consumption condition. Cross marks designate levels of measured consumption states. A maximum limit M_1 of a consumption condition is designated by an alternate long and short dash line.

At the point of time t_0 the first starting signal generator 11 is activated, and at the time t_1 the second starting signal generator 12 detects the excessive gas flow above the predetermined level of reference condition, and the timer 7 starts counting of time.

A time period T_1 from the time t_1 to a time t_2 is an operating time period of the timer 7. The maximum consumption state P_1 of plural consumption states which are measured in the time period T_1 is selected, and a reference consumption condition M_2 is calculated by multiplying the maximum consumption state P_1 by a safety factor K (for example, $K = 1.5$) in the consumption state memory means 9. Namely, the reference consumption condition in the time period T_1 is equal to the maximum reference consumption condition M_1 , which is compared with the reference consumption condition M_2 in the varying means 10 at the time t_2 . Then, the lower reference consumption condition M_2 is set in the varying means 10 as a new reference consumption condition.

In the above-mentioned status, when a consumption state exceeds the reference consumption condition M_2 , the consumption state judging means 4 detects abnormal state and outputs a signal for activating the shutoff means 5. At the point of time t_3 , the measured data P_2 is above the reference consumption state M_2 ,

and hence the output is issued to the shutoff means 5 to shutoff the gas supply. At that time, the reference consumption condition is reset from the level M_2 to the maximum limit value M_1 .

Thereafter, at the time t_4 the shutoff means is reset, and simultaneously the reset signal is given from the reset signal generator 6 to the first starting signal generator 11.

Subsequently, when a gas flow increases above a predetermined level at the time t_5 , the second starting signal generator 12 detects the increased gas flow and issues a start signal to the starting signal judging means 13. From the time t_5 , the timer 7 again starts the time-counting, and a gas consumption state within a second time period T_1 , which is of equal length to the time period t_1 to t_2 , is stored in the consumption state memory means 9. And at the time t_6 when the counting of time by the timer 7 is over, a fresh reference consumption condition M_4 is set. To explain a little in detail, in this state, a reference consumption condition M_4 (FIG.3) is computed by multiplying the maximum consumption state P_3 by the safety factor K at the point of time t_6 completion of operation of the timer 7, and the reference consumption condition M_4 is set in the varying means 10. The above-mentioned operation of the gas shutoff apparatus is similarly continued, also after the time t_6 .

FIG.4, FIG.5 and FIG.6 are respectively partial flow charts of the steps of operation of the gas shutoff apparatus in the first embodiment.

Referring to FIG.4, an initial consumption condition is set for a reference consumption condition from the initial consumption condition setting means 3 (step 14). A gas flow rate is measured (step 15), and a consumption state is detected on the basis of the output signal of the flow rate measurement means 1 (step 16). In a step 17, operation of the timer 7 is examined, and when the timer 7 is in operation, the present consumption state is detected and the maximum consumption state thereof is memorized in the consumption state memory means 9 (step 18). When the timer 7 is not in operation, the second starting signal generator 12 examines whether the gas flow rate is above the predetermined level or not; and when the gas flow rate is above the level, the second starting signal is issued (step 20). In case when gas flow rate is below the level or when passing through the steps 18 or 20, the judging of the consumption state by the consumption state judging means 4 is made (step 21). Then, when the result of the judging is abnormal, the step branches to the step 23 of issuing shutoff signal; but when the judge result is normal, the step advances through a junction 3 and the point 3 of FIG.6 to the step 34.

Referring to FIG.5, the flow from the junction point (2) and thereafter is elucidated. In the step 24, whether the timer 7 is counting or not is examined; and when the timer 7 is in the counting, the counting

is interrupted in the step 25. And the operation of the consumption state memory means 9 is interrupted in the step 26; and subsequently the timer 7 is cleared in the step 27, and the consumption state memory means 9 is also cleared, and in the step 29 the reference consumption condition is set with maximum limit value which is the initial consumption state. When the step 24 is not in the timer counting, the flow goes to the step 29. That is, after the gas consumption state has been judged abnormal (by the consumption state judging means 4) in the step 22 and the shutoff signal has been issued, the reference consumption condition is reset to be initialized; and the memory of previous variation of the reference consumption condition is also reset. Thereafter, the step 30 judges whether the reset signal generator 6 issues a reset signal or not. When there is no reset signal, the flow advances to the step 31 wherein whether there is a predetermined gas flow or not is checked; and when there is a gas flow at that time, a shutoff signal is issued again in the step 32 and the flow advances to the point (2) of FIG.5. When there is no gas flow, the flows come back to the step 30 and checks whether there is the reset signal or not; and when there is the reset signal, the first starting signal is stored in the step 33, and the flow returns to the point (1) of FIG.4.

Next, referring to FIG.6, the flow from the branch point (3) is elucidated. In the step 34, whether the reference consumption condition is already varied or not yet varied is checked. And when it has been checked, the flow returns to the point (1) of FIG.4. When the flow has not been varied, whether the timer has completed its time-counting or not is checked in the step 35. When the counting has been over, the output of the consumption state memory means 9 and output of the initial consumption condition setting means 3 are compared in the varying means for reference consumption condition 10 (the step 36), and either smaller one is selected and the reference consumption condition is varied thereto. When the time-counting has not yet completed yet in the step 35, whether the time-counting is still on or is over is checked in the step 38; and when the time-counting has not been completed, the counting is made continue in the step 39. When the time-counting has been completed, it is checked in the step 40 whether the first starting signal has come, or in the step 33 of FIG.5 whether the first starting signal is stored or not. Then, when the first starting signal has come, in the step 41 it is checked whether the second starting signal has come or not; and when the second starting signal has come the counting of the timer 7 is started in the step 42. And the flow returns to the point (1) of FIG.4 in the following cases: when the varying has been made in the step 34, when the flow goes through the steps 37 and 39, when the first starting signal has not come in the step 40, when the second starting signal has not come in the step 41 and when the flow goes through

the step 42.

As mentioned above, in the gas shutoff apparatus in accordance with the present invention, a consumption state of the gas is always monitored and is compared with a predetermined reference consumption condition. Therefore, when the consumption state exceeds the reference consumption condition because of escape of the gas or significant increase of gas consumption, the consumption state is determined to be abnormal, and the shutoff means 5 is activated to shutoff supply of the gas. Consequently, gas explosion or gas poisoning can be prevented.

Furthermore, an actual consumption state of a consumer is measured during a predetermined time period measured by the timer 7, and a reference consumption condition is set on the basis of the measured consumption state. Consequently, character of the consumer in gas consumption is introduced into the reference consumption condition, and effect for preventing gas accident is significantly improved. And, by using two (the first and the second) starting signals for starting the time-counting and by providing the first starting signal generator 11 which responds to the reset signal of the shutoff means 5 and the second starting signal generator 12 which responds to the gas flow amount signal, the timer for determining time period for measuring the gas consumption state is actuated to start the time-counting only after actual gas consumption by the user. Therefore, meaningful and effective data can be collected, and the setting of the reference consumption data becomes appropriate.

FIG.7 is a block diagram of a second embodiment of the gas shutoff apparatus in accordance with the present invention. Corresponding parts and components to the first embodiment are shown by the same numerals and marks, and the description thereon made in the first embodiment similarly apply. Differences and features of this second embodiment from the first embodiment are as follows.

The feature of this example is a configuration for enabling abnormal state checking by use of plural kinds of conditions. That is, the embodiment of FIG.7 comprises a second sets of circuits 2', 3', 4', 9', 10', 11' and 13' which are substantially the same as the circuits 2, 3, 4, 7, 9, 10, 11 and 13 of the first embodiment of FIG.2, respectively, and similarly connected to the circuits 1, 5, 6 and 12.

When a second starting signal is given from the second starting signal generator 12 after a first starting signal has been given from the first starting signal generator 11, the starting signal judging means 13 judges that the starting signals are given in a predetermined sequential order and issues a starting signal for time-counting to the first timer 7. Similarly, when a second starting signal is given from the second starting signal generator after a third starting signal has been given from the third starting generator 11',

the second starting signal judging means 13' judges that the starting signals are given in a predetermined sequential order and issues a starting signal for time-counting to the second timer 7'. The consumption state memory means 9 and 9' store gas consumption condition during time-counting period of the first timer 7 and the second timer 7' under individual abnormality judging conditions, respectively. For example, the first consumption state memory means 9 stores shutoff condition on the gas flow rate, while the second consumption state memory means 9' stores shutoff condition on the time period of continuous gas consumption. Hereupon, the first timer 7 and the second timer 7' are reset only when the consumption state judging means 4 and 4' judge that an abnormal gas consumption state arises on their own side (or of own set), respectively. And the timer 7 or 7' in the side (or of own set) wherein the timer 7 or 7' has been reset in the above-mentioned step is actuated to start again for measuring the gas consumption state, only when the second starting signal generator 12 detects a gas consumption above a predetermined level after the first and the third starting signal generators 11 and 11' issue signal. By the way, at the initial starting time after installation to home of this apparatus, by means of the initial processing, the system is set in a standby state such that the timers 7 and 7' are both reset and they are actuated to start time-counting by the starting signal.

In this second embodiment, in either side of the plural sets of circuits, wherein a gas consumption state above the predetermined level is detected, a new gas consumption state measurement is started afresh individually apart from the other side. Therefore, among plural gas consumption equipments, only that wherein the gas consumption state previously exceeds the predetermined level is observed, and for the other side (set) of circuit wherein the gas consumption state have not varied, there is no varying of the reference consumption state. Therefore, there is no fear of lowering the safety level by lowering of the reference gas consumption condition for the kind of the gas consumption data.

Although the invention has been described in its preferred form with a certain degree of particularity, it is understood that the present disclosure of the preferred form has been changed in the details of construction and the combination and arrangement of parts may be resorted to without departing from the spirit and the scope of the invention as hereinafter claimed.

Claims

1. A gas shutoff apparatus comprising:
flow rate measurement means (1) for generating a flow rate signal corresponding to a flow



the step 42.

As mentioned above, in the gas shutoff apparatus in accordance with the present invention, a consumption state of the gas is always monitored and is compared with a predetermined reference consumption condition. Therefore, when the consumption state exceeds the reference consumption condition because of escape of the gas or significant increase of gas consumption, the consumption state is determined to be abnormal, and the shutoff means 5 is activated to shutoff supply of the gas. Consequently, gas explosion or gas poisoning can be prevented.

Furthermore, an actual consumption state of a consumer is measured during a predetermined time period measured by the timer 7, and a reference consumption condition is set on the basis of the measured consumption state. Consequently, character of the consumer in gas consumption is introduced into the reference consumption condition, and effect for preventing gas accident is significantly improved. And, by using two (the first and the second) starting signals for starting the time-counting and by providing the first starting signal generator 11 which responds to the reset signal of the shutoff means 5 and the second starting signal generator 12 which responds to the gas flow amount signal, the timer for determining time period for measuring the gas consumption state is actuated to start the time-counting only after actual gas consumption by the user. Therefore, meaningful and effective data can be collected, and the setting of the reference consumption data becomes appropriate.

FIG.7 is a block diagram of a second embodiment of the gas shutoff apparatus in accordance with the present invention. Corresponding parts and components to the first embodiment are shown by the same numerals and marks, and the description thereon made in the first embodiment similarly apply. Differences and features of this second embodiment from the first embodiment are as follows.

The feature of this example is a configuration for enabling abnormal state checking by use of plural kinds of conditions. That is, the embodiment of FIG.7 comprises a second sets of circuits 2', 3', 4', 9', 10', 11' and 13' which are substantially the same as the circuits 2, 3, 4, 7, 9, 10, 11 and 13 of the first embodiment of FIG.2, respectively, and similarly connected to the circuits 1, 5, 6 and 12.

When a second starting signal is given from the second starting signal generator 12 after a first starting signal has been given from the first starting signal generator 11, the starting signal judging means 13 judges that the starting signals are given in a predetermined sequential order and issues a starting signal for time-counting to the first timer 7. Similarly, when a second starting signal is given from the second starting signal generator after a third starting signal has been given from the third starting generator 11',

the second starting signal judging means 13' judges that the starting signals are given in a predetermined sequential order and issues a starting signal for time-counting to the second timer 7'. The consumption state memory means 9 and 9' store gas consumption condition during time-counting period of the first timer 7 and the second timer 7' under individual abnormality judging conditions, respectively. For example, the first consumption state memory means 9 stores shutoff condition on the gas flow rate, while the second consumption state memory means 9' stores shutoff condition on the time period of continuous gas consumption. Hereupon, the first timer 7 and the second timer 7' are reset only when the consumption state judging means 4 and 4' judge that an abnormal gas consumption state arises on their own side (or of own set), respectively. And the timer 7 or 7' in the side (or of own set) wherein the timer 7 or 7' has been reset in the above-mentioned step is actuated to start again for measuring the gas consumption state, only when the second starting signal generator 12 detects a gas consumption above a predetermined level after the first and the third starting signal generators 11 and 11' issue signal. By the way, at the initial starting time after installation to home of this apparatus, by means of the initial processing, the system is set in a standby state such that the timers 7 and 7' are both reset and they are actuated to start time-counting by the starting signal.

In this second embodiment, in either side of the plural sets of circuits, wherein a gas consumption state above the predetermined level is detected, a new gas consumption state measurement is started afresh individually apart from the other side. Therefore, among plural gas consumption equipments, only that wherein the gas consumption state previously exceeds the predetermined level is observed, and for the other side (set) of circuit wherein the gas consumption state have not varied, there is no varying of the reference consumption state. Therefore, there is no fear of lowering the safety level by lowering of the reference gas consumption condition for the kind of the gas consumption data.

Although the invention has been described in its preferred form with a certain degree of particularity, it is understood that the present disclosure of the preferred form has been changed in the details of construction and the combination and arrangement of parts may be resorted to without departing from the spirit and the scope of the invention as hereinafter claimed.

Claims

1. A gas shutoff apparatus comprising:
flow rate measurement means (1) for generating a flow rate signal corresponding to a flow



rate of gas in a gas supply line,

consumption state detection means (2) for detecting particular consumption parameters including the current flow rate and the time elapsed since consumption of gas has commenced on the basis of said flow rate signal,

consumption state judging means (4) which compares a current detected consumption state with reference consumption parameters and generates a gas shutoff signal if any said current consumption parameter exceeds a corresponding reference consumption parameter,

initial consumption condition setting means (3) for setting initial reference consumption parameters in said judging means and comprising a memory for storing said reference parameters as an initial condition,

shutoff means (5) for interrupting said gas supply by reception of said shutoff signal,

a timer (7) for measuring a predetermined time period, during which a consumption pattern is to be monitored, said pattern comprising data as to maximum flow rate occurring during said period, and longest time of consumption during said period,

a first starting signal generator (11) for generating a first starting signal for said timer,

a second starting signal generator (12) for generating a second starting signal for said timer on occurrence of a gas flow rate above a predetermined level,

a starting signal judging means (13) connected to receive the starting signals from said first and second starting signal generators, and whose output is connected to said timer, said starting signal judging means (13) judging whether the second starting signal from the second starting signal generator (12) is received after receipt of the first starting signal from the first starting signal generator (11) and starting the timer (7) only if the starting signals are received in this predetermined sequential order,

consumption state memory means (9) for memorizing a consumption states detected during the time period given by operation of said timer and for producing a consumption pattern on the basis of said memorized consumption states,

varying means (10) for setting a new reference consumption parameter in said consumption state judging means, if the consumption pattern involves larger values of consumption parameters than the initial reference consumption parameters, and

a reset signal generator (6) for generating a reset signal to said first starting signal generator (11) upon receipt of a signal from said shutoff means when it is actuated.

2. A gas shutoff apparatus in accordance with claim 1 wherein

said varying means varies the reference consumption condition immediately after starting of the operation of the apparatus to a new value basing on the maximum level of measured actual consumption states during a first time period, by multiplying a tolerance factor, which is between 1 and 2, on the maximum level, and

when a measured actual consumption state exceeds said new value varies the reference consumption condition to another new value basing on the newly measured value by multiplying the tolerance factor on said varied new value, and thereafter repeating the same.

3. A gas shutoff apparatus comprising:

flow rate measurement means (1) for generating a flow rate signal corresponding to a flow rate of gas in a gas supply line,

plural consumption state detection means (2,2') for detecting respective consumption parameters including current flow rates and the time elapsed since consumption of the gas has commenced on the basis of said flow rate signal,

plural consumption state judging means (4,4') which respectively compare a current detected consumption state with reference consumption parameters and generate respective gas shutoff signals if any said current consumption parameters exceeds a corresponding reference consumption parameter,

plural initial consumption condition setting means (3, 3') for setting initial reference consumption parameters in said judging means each comprising a memory for storing said reference consumption parameters as an initial condition,

shutoff means (5) for interrupting said gas supply by reception of said shutoff signal,

plural timers (7,7') respectively for measuring respective predetermined time periods during which a consumption pattern is to be monitored, said pattern comprising data as to maximum flow rate occurring during said period, and longest time of consumption during said period,

plural first starting signal generators (11,11') for generating plural first starting signals for respective ones of said timers,

one second starting signal generator (12) for generating a second starting signal for each of said timers on occurrence of a gas flow rate above a predetermined level,

plural starting signal judging means (13,13') each of which is connected to receive the starting signals from a respective one of the first starting signal generators and from the second starting signal generator, and whose output is connected to a respective timer, each said start-



ing signal judging means (13,13') judging whether the second starting signal from the second starting signal generator (12) is received after receipt of the first starting signal from the first starting signal generator (11,11') and starting the respective timer (7) only if the starting signals are received in this predetermined sequential order,

plural consumption state memory means (9,9') for memorizing respective consumption states detected during the respective time periods given by operation of said timers and for producing a consumption pattern on the basis of said memorized consumption states,

plural varying means (10,10') for setting new reference consumption parameters in said respective consumption state judging means if the consumption pattern involves larger values of consumption parameters than the initial reference consumption parameters, and

a reset signal generator (6) for generating a reset signal to said first starting signal generators upon reception of a signal from said shutoff means when it is actuated.

4. A gas shutoff apparatus in accordance with claim 3 wherein

said varying means varies the reference consumption condition immediately after starting of the operation of the apparatus to a new value basing on the maximum level of measured actual consumption states during a first time period, by multiplying a tolerance factor, which is between 1 and 2, on the maximum level, and

when a measured actual consumption states exceeds said new value varies the reference consumption condition to another new value basing on the newly measured value by multiplying the tolerance factor on said varied new value, and thereafter repeating the same.

Patentansprüche

1. Gasabschaltungs Vorrichtung umfassend:

Strömungsrate-Meßeinrichtung (1) zum Erzeugen eines Strömungsrate-Signals entsprechend einer Strömungsrate des Gases in einer Gaszufuhrleitung,

Verbrauchszustandsdetektoreinrichtung (2) zur Detektierung auf der Basis des Strömungsrate-Signals, insbesondere der Verbrauchsparameter einschließlich der gegenwärtigen Strömungsrate und der Zeit, die verstrichen ist, seit der Verbrauch von Gas begonnen hat,

Verbrauchszustandsbeurteilungseinrichtung (4), welche einen gegenwärtig detektierten Verbrauchszustand in bezug auf die Verbrauchsparameter vergleicht und ein Gasabschaltsignal er-

zeugt, wenn der gegenwärtige Verbrauchsparameter einen entsprechenden Bezugsverbrauchsparameter übersteigt,

Anfangsverbrauchsbedienungseinrichtung (3) zum Einstellen der anfänglichen Bezugsverbrauchsparameter in der Beurteilungseinrichtung und umfassend einen Speicher zum Speichern der Bezugsparameter als eine Anfangsbedienung,

Abschalteinrichtung (5) zum Unterbrechen der Gaszufuhr beim Empfang des Abschaltsignals, Zeitgeber (7) zum Messen einer vorbestimmten Zeitspanne, während derer ein Verbrauchsmuster überwacht werden soll, wobei das Muster Daten bezüglich der maximalen Strömungsrate während dieser Zeitspanne und der längsten Verbrauchszeit während dieser Spanne umfaßt, ersten Startsignalgenerator (11) zum Erzeugen eines ersten Startsignals für den Zeitgeber,

zweiten Startsignalgenerator (12) zum Erzeugen eines zweiten Startsignals für den Zeitgeber beim Auftreten einer Gasströmungsrate über einen vorbestimmten Pegel, eine Startsignalbeurteilungseinrichtung (13), die so angeschlossen ist, daß sie die Startsignale von dem ersten und zweiten Startsignalgenerator empfängt, und deren Ausgang so verbunden ist mit dem Zeitgeber, wobei die Startsignalbeurteilungseinrichtung (13) beurteilt, ob das zweite Startsignal von dem zweiten Startsignalgenerator (12) nach Empfang des ersten Startsignals von dem ersten Startsignalgenerator (11) empfangen wurde, und die den Zeitgeber (7) nur startet, wenn die Startsignale in der vorgegebenen Reihenfolge empfangen wurden,

Verbrauchszustandsspeichereinrichtung (9) zum Speichern eines Verbrauchszustandes, welcher während der Zeitspanne festgestellt wurde, die durch Betrieb des Zeitgebers gegeben ist, und zur Erzeugung eines Verbrauchsmusters auf der Basis des gespeicherten Verbrauchszustandes, Variationseinrichtung (10) zum Einstellen eines neuen Bezugsverbrauchsparameters in der Verbrauchszustandsbeurteilungseinrichtung, wenn das Verbrauchsmuster größere Werte der Verbrauchsparameter einschließt, als die anfänglichen Bezugsverbrauchsparameter, und einen Rücksetzsignalgenerator (6) zum Erzeugen eines Rücksetzsignals für den ersten Startsignalgenerator (11) beim Empfang eines Signals von der Abschalteinrichtung, wenn sie betätigt wurde.

2. Eine Gasabschaltungs Vorrichtung nach Anspruch 1, worin die Variationseinrichtung die Bezugsverbrauchsbedienung unmittelbar nach Start des Betriebes der Vorrichtung zu einem neuen Wert variiert basierend auf einem maxima-



len Pegel des gemessenen aktuellen Verbrauchszustandes während einer ersten Zeitspanne durch Multiplizieren eines Toleranzfaktors, welcher zwischen 1 und 2 liegt an den Maximalpegel, und worin, wenn ein gemessener aktueller Verbrauchszustand die neuen Werte überschreitet, die Bezugsverbrauchsbedienung zu einem neuen Wert variiert wird basierend auf dem neugemessenen Wert durch Multiplizieren des Toleranzfaktors an den variierten neuen Wert und anschließendem Wiederholen desselben.

3. Gasabschaltungsvorrichtung, umfassend:
 - Strömungsrate-Meßeinrichtung (1) zum Erzeugen eines Strömungsrate-Signals entsprechend einer Strömungsrate eines Gases in einer Gaszufuhrleitung,
 - mehrere Verbrauchszustandsdetektoreinrichtungen (2, 2') zum Detektieren der jeweiligen Verbrauchsparameter einschließlich der gegenwärtigen Strömungsraten und der Zeit, die verstrichen ist, seit der Gasverbrauch begonnen hat, auf der Basis des Strömungsrate-Signals,
 - mehrere Verbrauchszustandsbeurteilungseinrichtungen (4, 4'), welche jeweils einen gegenwärtig detektierten Verbrauchszustand in bezug auf Verbrauchsparameter vergleichen und jeweils Gasabschaltsignale erzeugen, wenn einer der gegenwärtigen Verbrauchsparameter einen entsprechenden Bezugsverbrauchsparameter übersteigt,
 - mehrere Anfangsverbrauchsbedienungseinstelleinrichtungen (3, 3') zum Einstellen von anfänglichen Bezugsverbrauchsparametern in der Beurteilungseinrichtung, wobei jeder einen Speicher zum Speichern der Bezugsverbrauchsparameter als eine Anfangsbedienung aufweist,
 - Abschaltelinrichtung (5) zum Unterbrechen der Gaszufuhr beim Empfang des Abschaltsignals,
 - mehrere Zeitgeber (7, 7') die jeweils zum Messen jeweiliger vorgegebener Zeitspannen vorgesehen sind, während denen ein Verbrauchsmuster zu überwachen ist, wobei das Muster Daten bezüglich der maximalen Strömungsrate, die während dieser Zeitspanne auftritt, und die längste Verbrauchszeit während dieser Zeitspanne umfaßt,
 - mehrere erste Startsignalgeneratoren (11, 11') zum Erzeugen mehrerer erster Startsignale für die jeweiligen Zeitgeber,
 - einen zweiten Startsignalgenerator (12) zum Erzeugen eines zweiten Startsignals für jeden Zeitgeber beim Auftreten einer Gasströmungsrate über einen vorgegebenen Pegel,
 - mehrere Startsignalbeurteilungseinrichtungen (13, 13'), die jeweils verbunden sind, um die Startsignale von den jeweiligen ersten Startsi-

gnalgeneratoren und von dem zweiten Startsignalgenerator zu empfangen, und deren Ausgang verbunden ist mit einem jeweiligen Zeitgeber, wobei jede Startsignalbeurteilungseinrichtung (13, 13') beurteilt, ob das zweite Startsignal von dem zweiten Startsignalgenerator (12) empfangen wurde nach Empfang des ersten Startsignals von dem ersten Startsignalgenerator (11, 11'), und den jeweiligen Zeitgeber (7) nur startet, wenn die Startsignale empfangen wurden in dieser vorgegebenen Reihenfolge, mehrere Verbrauchszustandsspeichereinrichtungen (9, 9') zum Speichern der jeweiligen Verbrauchszustände, die während der jeweiligen Zeitspannen detektiert wurden, die durch Betrieb der Zeitgeber gegeben sind, und zum Erzeugen eines Verbrauchsmusters auf der Basis der gespeicherten Verbrauchszustände, mehrere Variationseinrichtungen (10, 10') zum Einstellen von neuen Bezugsverbrauchsparametern in den jeweiligen Verbrauchszustandsbeurteilungseinrichtungen, wenn das Verbrauchsmuster größere Verbrauchsparameter einschließt, als die anfänglichen Bezugsverbrauchsparameter und ein Rücksetzsignalgenerator (6) zum Erzeugen eines Rücksetzsignals an die ersten Startsignalgeneratoren beim Empfang eines Signals von der Abschaltelinrichtung, wenn sie betätigt wurde.

4. Gasabschaltungsvorrichtung nach Anspruch 3, worin die Variationseinrichtungen die Bezugsverbrauchsbedienung unmittelbar nach Start des Betriebes der Vorrichtung variieren zu einem neuen Wert basierend auf dem maximalen Pegel der gemessenen aktuellen Verbrauchszustände während einer ersten Zeitspanne durch Multiplizieren eines Toleranzfaktors, welcher zwischen 1 und 2 liegt, an den maximalen Pegel und worin, wenn ein gemessener aktueller Verbrauchszustand den neuen Wert überschreitet, die Bezugsverbrauchsbedienung zu einem anderen neuen Wert basierend auf neu gemessenen Werten variiert wird durch Multiplizierung des Toleranzfaktors an den variierten neuen Wert und anschließendem Wiederholen desselben.

Revendications

1. Appareil de coupure de gaz comprenant :
 - un moyen de mesure de débit (1) pour produire un signal de débit correspondant au débit du gaz dans une conduite de fourniture de gaz,
 - un moyen de détection d'état de consommation (2) pour détecter des paramètres de consommation particuliers comprenant le



- débit courant et le temps écoulé depuis le commencement de la consommation du gaz sur la base dudit signal de débit,
- un moyen pour juger de l'état de la consommation (4) qui compare un état courant de la consommation détectée à des paramètres de consommation de référence et produit un signal de coupure de gaz si l'un quelconque desdits paramètres de la consommation courante dépasse un paramètre de consommation de référence correspondant, 5
 - un moyen d'établissement d'une condition initiale de consommation (3) pour établir des paramètres de consommation initiaux de référence dans ledit moyen de jugement et comportant une mémoire pour stocker lesdits paramètres de référence comme condition initiale, 10
 - un moyen de coupure (5) pour interrompre ladite fourniture de gaz par la réception dudit signal de coupure, 15
 - une minuterie (7) pour mesurer une période de temps prédéterminée au cours de laquelle un profil de consommation doit être surveillé, ledit profil comprenant une donnée quant au débit maximum se produisant pendant ladite période, et le temps de consommation le plus long pendant ladite période, 20
 - un premier générateur de signal de départ (11) pour produire un premier signal de départ pour ladite minuterie, 25
 - un second générateur de signal de départ (12) pour produire un second signal de départ pour ladite minuterie lors de l'apparition d'un débit du gaz supérieur à un niveau prédéterminé, 30
 - un moyen de jugement de signal de départ (13) connecté de façon à recevoir les signaux de départ provenant desdits premier et second générateurs de signal de départ, et dont la sortie est connectée à ladite minuterie, ledit moyen de jugement du signal de départ (13) jugeant le fait que le second signal de départ provenant du second générateur de signal de départ (12) est ou non reçu après la réception du premier signal de départ provenant du premier générateur de signal de départ (11) et démarrant la minuterie (7) seulement si les signaux de départ sont reçus dans cet ordre séquentiel prédéterminé, 35
 - un moyen de mémoire d'état de consommation (9) pour mémoriser un état de la consommation détecté pendant la période de temps donnée par le fonctionnement de ladite minuterie et pour produire un profil de 40

consommation sur la base desdits états mémorisés de la consommation,

- un moyen de variation (10) pour établir un nouveau paramètre de consommation de référence dans ledit moyen de jugement de l'état de la consommation, si le profil de la consommation implique des valeurs de la consommation plus grandes que les paramètres de consommation de référence initiaux, et
 - un générateur de signal de remise à l'état initial (6) pour produire un signal de remise à l'état initial qui est appliqué audit premier générateur de signal de départ (11) lors de la réception d'un signal provenant dudit moyen de coupure lorsqu'il est actionné.
2. Appareil de coupure de gaz selon la revendication 1, dans lequel :
- ledit moyen de variation fait varier la condition de consommation de référence immédiatement après le départ du fonctionnement de l'appareil pour prendre une nouvelle valeur basée sur le niveau maximum des états de la consommation réelle mesurée pendant une première période de temps, par multiplication d'un facteur de tolérance, qui est compris entre 1 et 2, sur le niveau maximum, et
 - lorsqu'un état de la consommation réelle mesurée dépasse ladite nouvelle valeur fait varier la condition de consommation de référence pour qu'elle prenne une autre nouvelle valeur sur la base de la valeur nouvellement mesurée en multipliant le facteur de tolérance sur ladite nouvelle valeur ayant varié, et ensuite en répétant l'opération.
3. Appareil de coupure de gaz comprenant :
- un moyen de mesure de débit (1) pour produire un signal de débit correspondant au débit du gaz dans une conduite de fourniture de gaz,
 - plusieurs moyens de détection d'état de consommation (2, 2') pour détecter des paramètres de consommation respectifs comprenant des débits courants et le temps écoulé depuis que la consommation du gaz a commencé sur la base dudit signal de débit,
 - plusieurs moyens de jugement d'état de consommation (4, 4') qui comparent respectivement un état de consommation courante détecté à des paramètres de consommation de référence et produisent des signaux respectifs de coupure du gaz si l'un quelconque desdits paramètres de consommation courante dépasse un para- 45



- mètre de consommation de référence correspondant,
- plusieurs moyens d'établissement de condition initiale de consommation (3, 3') pour établir des paramètres de consommation initiale de référence dans ledit moyen de jugement, chacun comprenant une mémoire pour stocker lesdits paramètres de consommation de référence comme condition initiale,
- un moyen de coupure (5) pour interrompre ladite fourniture de gaz par la réception dudit signal de coupure,
- plusieurs minuterie (7, 7') respectivement pour mesurer des périodes de temps prédéterminées respectives au cours desquelles un profil de consommation doit être surveillé, ledit profil comprenant une donnée sur le débit maximum se produisant pendant ladite période, et le temps de consommation le plus long pendant ladite période,
- plusieurs premiers générateurs de signal de départ (11, 11') pour produire plusieurs premiers signaux de départ pour des minuterie respectives parmi lesdites minuterie,
- un second générateur de signal de départ (12) pour produire un second signal de départ pour chacune desdites minuterie lors de l'apparition d'un débit du gaz supérieur à un niveau prédéterminé,
- plusieurs moyens de jugement de signal de départ (13, 13') dont chacun est connecté de manière à recevoir les signaux de départ provenant d'un générateur respectif parmi les premiers générateurs de signal de départ et le second générateur de signal de départ, et dont la sortie est connectée à une minuterie respective, chaque dit moyen de jugement de signal de départ (13, 13') portant un jugement sur le fait que le second signal de départ provenant du second générateur de signal de départ (12) est ou non reçu après la réception du premier signal de départ provenant du premier générateur de signal de départ (11, 11') et démarrant la minuterie respective (7) seulement si les signaux de départ sont reçus dans cet ordre séquentiel prédéterminé,
- plusieurs moyens de mémoire d'état de consommation (9, 9') pour mémoriser des états de consommation respectifs détectés au cours des périodes de temps respectives données par le fonctionnement desdites minuterie et pour produire un profil de consommation sur la base desdits états de consommation mémorisés,
- plusieurs moyens de variation (10, 10') pour

établir de nouveaux paramètres de consommation de référence dans ledit moyen respectif de jugement d'état de la consommation si le profil de la consommation implique des valeurs des paramètres de consommation plus élevées que les paramètres de la consommation initiale de référence, et

- un générateur de signal de remise à l'état initial (6) pour produire un signal de remise à l'état initial appliqué auxdits premiers générateurs de signal de départ lors de la réception d'un signal provenant dudit moyen de coupure lorsqu'il est actionné.

4. Appareil de coupure de gaz selon la revendication 3, dans lequel :

- ledit moyen de variation fait varier la condition de consommation de référence immédiatement après le début du fonctionnement de l'appareil pour prendre une nouvelle valeur sur la base du niveau maximum des états de la consommation réelle mesurée pendant une première période de temps, par multiplication par un facteur de tolérance, qui est compris entre 1 et 2, sur le niveau maximum, et
- lorsqu'un état de la consommation réelle mesurée dépasse ladite nouvelle valeur fait varier la condition de consommation de référence pour prendre une nouvelle valeur sur la base de la valeur nouvellement mesurée par multiplication par le facteur de tolérance sur ladite nouvelle valeur ayant varié, et ensuite en répétant la même opération.