

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
7 March 2013 (07.03.2013)



(10) International Publication Number
WO 2013/032401 A8

(51) International Patent Classification:
H02K 16/04 (2006.01) *H02K 1/28* (2006.01)
H02K 1/27 (2006.01)

(21) International Application Number:
PCT/SG2011/000300

(22) International Filing Date:
31 August 2011 (31.08.2011)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **AKRIBIS SYSTEMS PTE LTD** [SG/SG]; Blk 5012 Techplace II, #01-05 Ang Mo Kio Avenue 5, Singapore 569876 (SG).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LIM, Howe Yuen** [SG/SG]; 41 Jalan Keruing, Singapore 808961 (SG). **GOH, Chai Meng** [SG/SG]; Blk 408 Serangoon Ave 1, #11-79, Singapore 550408 (SG).

(74) Agent: **CHONG, Y F**; P. O. Box 0399, Psa Building, Singapore 911144 (SG).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

[Continued on next page]

(54) Title: HIGH TORQUE, LOW INERTIA DIRECT DRIVE MOTOR



(57) Abstract: A high torque, low inertia direct drive motor comprises a circular outer stator 21 and a circular inner stator 25 and a ring of magnets 23a, 23b, 23c. The ring of magnets 23a, 23b, 23c is held by a support structure 31, said ring of magnets 23a, 23b, 23c positioned between the circular outer stator 21 and the circular inner stator 25. The circular outer stator 21 and ring of magnets and circular inner stator and ring of magnets are separated by an air gap. The circular outer stator 21 and circular inner stator 25 each have a plurality of teeth with coils wound around the teeth. The teeth of the circular inner stator 44a, 44b, 44c are aligned in the same radial direction as the teeth of the circular outer stator 46a, 46b, 46c.



Published:

— *with international search report (Art. 21(3))*

(15) Information about Correction:

see Notice of 20 February 2014

(48) Date of publication of this corrected version:

20 February 2014