G00002

RECORDING AND/OR REPRODUCTION METHOD

FIELD OF THE INVENTION

The present invention relates to a method for recording and/or reproduction in real time.

DESCRIPTION OF THE RELATED ART

In a computer or audio and/or video (A/V) apparatus constituted of a file system for an A/V file required to be recorded/reproduced in real time, control information representing that the A/V file is a real time recording/reproduction file is not recorded in file control information. Thus, it is impossible to reproduce in real time a file comprised of data blocks physically scattered on a recording medium even if they are logically successive.

Here, a conventional file system, as shown in FIG. 1, is comprised of file control information having the length of a file, information on the position of file data, information on the possibility or impossibility of reading/writing a file, etc., and file data stored in positions designated by the file control information. When a file on a disc is read, file control information is first read, and file data in the positions designated by the read file control information is then read and reproduced. Such a method of allocating a block of a fixed size used in the conventional file system cannot guarantee real time reproduction of a file.

That is, recording/reproduction of the conventional file system is described by taking as an example the case in which two files occupy blocks on a disc as shown in FIG. 2. Here, a file A, requiring real time reproduction, occupies blocks 0, 3, 5 and 6 of the disc, and a file B, a general file, occupies blocks 1, 2, 4 and 7 of the disc.

The process for reproducing the file A is as follows.
In the first step, block 0 is read.

159159

In the second step, block 3 is searched for.

In the third step, block 3 is read and played back.

In the fourth step, the block 5 is searched for.

In the fifth step, blocks 5 and 6 are read and played back.

In the conventional file system, since information associated with real time recording/reproduction is not recorded even when recording a file requiring real time recording/reproduction, a data arrangement for real time recording/reproduction is not considered. Thus, real time reproduction may not be achieved.

That is, the file A (for example, a video file) of FIG. 2 requires real time reproduction, but the conventional file system arranges data files without consideration of the requirement of real time reproduction, thus causing a screen to be interrupted during playback. In order to record/reproduce files in real time, the sum of a seek time and a read time must be smaller than a playback time, as shown in the following expression:

$$\text{seek time} + \text{read time} < \text{playback time} \quad \ldots(1)$$

In order to prevent a screen from being interrupted, a next block must be searched for during reading and reproducing a current block before the next block is read. However, in an apparatus for driving a disc such as a compact disc (CD) and a digital versatile disc (DVD), the seek time is significantly longer than the read time. Therefore, real time reproduction is impossible if the next block is not physically adjacent to the current block.

SUMMARY OF THE INVENTION

The present invention therefore provides a recording and/or reproducing method comprising:

arranging and recording real time files requiring real time recording/reproduction according to real time recording/reproduction in a recording medium according to real time recording/reproduction information for ensuring real time reproduction, and recording the real time recording/reproduction information in the recording medium;

and reading and reproducing the real time files using the real time recording/reproduction information.

The recording of the real time recording/reproduction information may comprise storing the real time recording/reproduction information in a file control information area of the recording medium.

Alternatively the recording of the real time recording/reproduction information comprise storing the real time recording/reproduction information in a file control information area of a UDF system of the recording medium.

Preferably the recording of the real time recording/reproduction information comprises storing the real time recording/reproduction information in each corresponding real time file.

The recording of the real time recording/reproduction information may comprise storing the real time recording/reproduction information associated with the real time files in a separate file from the real time files.

The recording/reproduction information may comprise storing the real time recording/reproduction information in a volume structure area of the recording medium.

The real time recording/reproduction information may include file indication information indicating that the real time files require real time recording/reproduction.

The real time files may have sections with different bit rates, and the real time recording/reproduction information may include recording/reproduction bit rate information which includes information associated with the sections and a plurality of bit rate values corresponding to the different bit rates of the sections.

The arranging may comprise automatically arranging file data areas of the real time files according to the recording/reproduction bit rate information.

The real time recording/reproduction information may include a maximum allowable value of the real time recording/reproduction bit rates.

The real time recording/reproduction information may include at least one of minimum contiguous storage blocks satisfying a condition in which a playback time of a current data block is greater than a sum of the seek time and a read time of a data block to be played back next, and a playback time for ensuring minimum contiguous storage.

The real time files may be arranged in the minimum contiguous storage blocks.

The recording of the real time recording/reproduction information may comprise if an end portion of one of the real time files is not filled with data by one of the minimum contiguous storage blocks while the one real time file is recorded in units of the minimum contiguous storage blocks, recording as the real time recording/reproduction information an attribute indicating that a number of data blocks corresponding to a size of the unfilled portion are allocated but unrecorded.

The minimum contiguous storage blocks may be classified according to a size of an error correction code block and a maximum seek time.

The arranging may comprise arranging the real time files in the classified minimum contiguous storage blocks.

The real time recording/reproduction information may further include current real time recordable/reproducible state information indicating whether a current file is arranged so as to be recorded/reproduced in real time.

The real time recording/reproduction information may further include contiguous recording/reproduction type information classified by conditions for controlling real time files, the conditions preferably including recording/reproduction bit rate information, file defect management information, file allocation information, file

buffering information, and the information of the minimum contiguous storage blocks.

The real time recording/reproduction information may further include at least one of file defect management information indicating that replacement of a defective block with a block in a spare area of the recording medium and rereading or rewriting of the defective block are not attempted when reading or writing has failed, file allocation information indicating that a data block is not allocated to the defective block replaced by the spare area, and the buffering information associated with an amount of data to be initially read from a buffer and an amount of data written from the buffer at a time.

The reading and reproducing the real time files may comprise reading a volume area on the recording medium; and reproducing a file as one of the real time files in consideration of the real time recording/reproduction information if the real time recording/reproduction information exists in the volume area.

The reproducing of the file may comprise analyzing recording/reproduction bit rate information, defect management information, file allocation, and file buffering information according to the real time recording/reproduction information in the volume area, and reading and reproducing file data in minimum contiguous storage blocks of the file.

The reading and reproducing the real time files may comprise determining whether the real time recording/reproduction information exists in a file area; and reproducing a file in consideration of the real time recording/reproduction information if the real time recording/reproduction information exists in the file area.

The reproducing of the file may comprise analyzing recording/reproduction bit rate information, defect management information, file allocation information, and file buffering information according to the real time recording/reproduction information in the file area, and reading and reproducing file data in minimum contiguous storage blocks.

The method may further comprise copying a file to free area from which a defective block is excluded, based upon the real time recording/reproduction information and general defect management information recorded on the recording medium.

The copying of the file may comprise copying the real time recording/reproduction information and the file together.

The copying of the file may comprise copying only real time file data based on the real time recording/reproduction information.

The real time recording/reproduction information may further include current real time recordable/reproducible state information indicating whether it is possible to record/reproduce a current file in real time.

General defect management information may be recorded in the recording medium; and copying a file may be copied to a free area from which a defective block is excluded, based upon the real time recording/reproduction information and the general defect management information recorded in the recording medium.

The copying of the file may comprise copying the real time recording/reproduction information and the file together. Alternatively, the copying of the file may comprise copying only real time file data based on the real time recording/reproduction information.

In a second form, the present invention provides a recording method comprising the steps of:

arranging and recording real time files requiring real time recording/reproduction according to real time recording/reproduction in a recording medium according to real time recording/reproduction information for ensuring real time reproduction; and recording the real time recording/reproduction information in the recording medium.

The recording of the real time recording/reproduction information may comprise one or

more of:

(a) storing the real time recording/reproduction information in a file control information area of the recording medium;

(b) storing the real time recording/reproduction information in a file control information area of a UDF system of the recording medium;

(c) storing the real time recording/reproduction information in each corresponding real time file;

(d) the real time recording/reproduction information associated with the real time files in a separate file form the real time files;

(e) storing the real time recording/reproduction information in a volume structure area of the recording medium;

The real time recording/reproduction information may include file indication information indicating that the real time files require real time recording/reproduction;

The real time files have may sections with different bit rates, and the real time recording/reproduction information may include recording/reproduction bit rate information which includes information associated with the sections and a plurality of bit rate values corresponding to the different bit rates of the sections.

The recording of the real time recording/reproduction information may comprise automatically arranging file data areas of the real time files according to the recording/reproduction bit rate information. The real time recording/reproduction information may include a maximum allowable value of the real time recording/reproduction bit rates.

The real time recording/reproduction information may include at least one of minimum contiguous storage block satisfying a condition in which a playback time of a current data block is greater than a sum of the seek time and a read time of a data block to be played back next, and a playback time for ensuring minimum contiguous storage.

The recording of the real time recording/reproduction information may comprise

arranging the real time files in the minimum contiguous storage blocks.

The recording of the real time recording/reproduction information may comprise, if an end portion of one of the real time files is not filled with data by one of the minimum contiguous storage blocks while the one real time file is recorded in units of the minimum contiguous storage blocks, recording as the real time recording/reproduction information an attribute indicating that a number of data blocks corresponding to a size of the unfilled portion are allocated but unrecorded.

The minimum contiguous storage blocks may be classified according to a size of an error correction code block and a maximum seek time. The arranging and recording of the real time files may comprise arranging the real time files in the classified minimum contiguous storage blocks.

The real time recording/reproduction information may also include current real time recordable/reproducible state information indicating whether a current file is arranged so as to be recorded/reproduced in real time.

The real time recording/reproduction information may further include contiguous recording/reproduction type information classified by conditions for controlling real time files, the conditions including recording/reproduction bit rate information, file defect management information, file allocation information, file buffering information, and the information of the minimum contiguous storage blocks.

The real time recording/reproduction information may also further include at least one of file defect management information indicating that replacement of a defective block with a block in a spare area of the recording medium and rereading or rewriting of the defective block are not attempted when reading or writing has failed, file allocation information indicating that a data block is not allocated to the defective block replaced by the spare area, and file buffering information associated with an amount of data to be initially read from a buffer and an amount of data written from the buffer at a time.

The real time recording/reproduction information may further include current real time recordable/reproducible state information indicating whether it is possible to record/reproduce a current file in real time.

In a third form, the present invention provides a reproducing method of a recording medium, wherein real time files requiring real time recording/reproduction according to real time recording/reproduction are stored in a recording medium according to real time recording/reproduction information for ensuring real time reproduction, and the real time recording/reproduction information is stored in the recording medium, the method comprising:
reading the real time files using the real time recording/reproduction information; and
reproducing the read real time files.

Thee reading of the real time files may comprise one or more of:

(a) reading the real time recording/reproduction information from a file control information area of the recording medium;
(b) reading the real time recording/reproduction information from a file control information area of a UDF system of the recording medium;
(c) reading the real time recording/reproduction information in each corresponding real time file;
(d) reading the real time recording/reproduction information associated with the real time files in a separate file from the real time files; and
(e) reading the real time recording/reproduction information in a volume structure area of the recording medium.

The real time recording/reproduction information may include the indication information indicating that the real time files require real time recording/reproduction.

The real time files may have sections with different bit rates, and the real time recording/reproduction information includes recording/reproduction bit rate information which includes information associated with the sections and a plurality of bit rate values corresponding to the different bit rates of the sections, the method further comprising:

reading the sections of the real time files in accordance with the corresponding plurality of bit rate values.

The file data areas of the real time files may be arranged according to the recording/reproduction bit rate information; and the real time recording/reproduction information may include a maximum allowable value of the real time recording/reproduction bit rates.

The real time recording/reproduction information may include at least one of minimum contiguous storage blocks satisfying a condition in which a playback time of a current data block is greater than a sum of the seek time and a read time of a data block to be played back next, and a playback time for ensuring minimum contiguous storage. The real time files may be arranged in the minimum contiguous storage blocks.

If an end portion of one of the real time files is not filled with data by one of the minimum contiguous storage blocks while the one real time file is recorded in units of the minimum contiguous storage blocks, the real time recording/reproduction information may be recorded as an attribute indicating that a number of data blocks corresponding to a size of the unfilled portion are allocated but unrecorded.

The minimum contiguous storage blocks may be classified according to a size of an error correction code block and a maximum seek time; and the real time recording/reproduction information may further include current real time recordable/reproducible state information indicating whether a current file is arranged so as to be recorded/reproduced in real time.

The real time recording/reproduction information may further include contiguous recording/reproduction type information classified by conditions for controlling real time files, the conditions including recording/reproduction bit rate information, file defect management information, file allocation information, file buffering information, and the information of the minimum contiguous storage blocks.

The real time recording/reproduction information may also include at least one of file defect management information indicating that replacement of a defective block with a block in a spare area of the recording medium and rereading or rewriting of the defective block are not attempted when reading or writing has failed, file allocated information indicating that a data block is not allocated to the defective block replaced by the spare area, and file buffering information associated with an amount of data to be initially read from a buffer and an amount of data written from the buffer at a time.

The reading of the real time files may comprise the steps of:
reading a volume area on the recording medium; and
reproducing a file as one of the real time files in consideration of the real time recording/reproduction information if the real time recording/reproduction information exists in the volume area.

The reproducing of the file may comprise analyzing recording/reproduction bit rate information, defect management information, file allocation information, and file buffering information according to the real time recording/reproduction information in the volume area, and reading and reproducing file data in minimum contiguous storage blocks of the file.

The reproducing of the file may also comprises the steps of:
determining whether the real time recording/reproduction information exists in a file area; and
reproducing a file in consideration of the real time recording/reproduction information if the real time recording/reproduction information exists in the file area.

Reproducing of the file may further comprise analyzing recording/reproduction bit rate information, defect management information, file allocation information, and file buffering information according to the real time recording/reproduction information in the file area, and reading and reproducing file data in minimum contiguous storage blocks.

The method may also further comprises the steps of :

(c) copying a file to a free area from which a defective block is excluded, based upon the real time recording/reproduction information and general defect management information recorded on the recording medium.

The copying of the file may comprises copying the real time recording/reproduction information and the file together; or copying only real time file data based on the real time recording/reproduction information.

The real time recording/reproduction information may further include current real time recordable/reproducible state information indicating whether it is possible to record/reproduce a current file in real time.

In a final form, the present invention provides a recording and/or reproducing method comprising the steps of:

recording real time files requiring real time recording and/or reproduction on a recording medium according to real time recording and/or reproduction information for ensuring real time reproduction.

recording the real time recording and/or reproduction information in a file type field in an (ICB) TAG field of a file entry for a universal disk format (UDF) system.

The real time files may be reproduced using the real time recording and/or reproduction information.

The recording of the real time files and the real time recording and/or reproduction method may comprise storing the real time recording/reproduction information in corresponding ones of the real time files.

The real time recording/reproduction information may include file indication information indicating that the real time files require real time recording and/or reproduction.

The real time recording/reproduction information may include at least one of recording/reproduction bit rate information, information on minimum contiguous storage block satisfying a condition in which a playback time of a current data block is greater than a sum of a seek time and a read time of a data block to be played back next, and information on a play back time for ensuring minimum contiguous storage.

The reproducing of the real time files may comprise:
reading a volume area on the recording medium; and
reproducing a file as one of the real time files in accordance with the real time recording/reproduction information.

The reproducing of the file may comprise analyzing recording/reproduction bit rate information, defect management information, file allocation information, and file buffering information according to the real time recording/reproduction information.

BRIEF DESCRIPTION OF THE DRAWINGS

The above objectives and advantages of the present invention will become more apparent by describing in detail preferred embodiments thereof with reference to the attached drawings in which:

FIG. 1 is a view illustrating the one-dimensional structure of a recording medium, the structure showing the relationship between file control information and file data;

FIG. 2 is a view illustrating an example in which two conventional files occupy blocks on a disc;

FIGS. 3A through 3D show examples of storage of real time recording/reproduction attribute information according to the present invention;

FIG. 4 is a view illustrating an example in which real time files according to the present

invention, comprised of minimum contiguous storage blocks, occupy blocks on a disc;

FIG. 5 is a view illustrating the one-dimensional structure of a recording medium for recording real time AV data allocated into minimum contiguous storage blocks according to the present invention;

FIGS. 6A and 6B are views illustrating examples of copying a file comprised of minimum contiguous storage blocks according to the present invention;

FIG. 7 is a flowchart illustrating a reproducing method using real time recording/reproduction information according to an embodiment of the present invention;

FIG. 8 is a schematic block diagram of a disc recording and reproducing apparatus applied to the present invention;

FIG. 9 is a view showing the flow of control for real time recording/ reproduction for a real time rewritable system;

FIG. 10 is a block diagram showing the flow of data for real time recording/ reproduction for a real time rewritable system;

FIG. 11 is a view illustrating an example of allocating an unrecorded/unallocated area in a real time recorded/reproduced file;

FIGS. 12A through 12D are views illustrating examples of recording data of a real time recorded/reproduced file;

FIGS. 13A through 13D are views illustrating file control information corresponding to when different bit rates are provided in different sections and when an identical bit rate is provided in the entire file data section; and

FIGS. 14A through 14C are views illustrating partial deletion of real time recorded/reproduced file data.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Preferred embodiments of a recording medium for storing real time recording/reproduction information, a real time recording and reproducing method and apparatus, and a file operating method using the real time recording/reproduction information will now be described referring to the attached drawings.

FIGS. 3A through 3D show examples of storing real time recording/reproduction information (this can be called real time recording/reproduction attribute information) according to the present invention. As shown in FIG. 3A, the real time recording/reproduction information can be provided as an attribute to each real time file. As an example, the real time recording/reproduction attribute information can be stored in a extended attribute field in a file entry or a stream directory ICB (information control block) field when a file system is a universal disk format (UDF) system.

Alternatively, the real time recording/reproduction attribute information can be stored in a file identifier descriptor field, a file type field, or a flag field among an ICB TAG field in a file entry. The file entry can be called a file control information area or a file structure area.

As shown in FIG. 3B, real time recording/reproduction attribute information for each file can be stored in a predetermined area (information area) in each file. For example, in the case of a real time rewritable (RTRW) format, real time recording/reproduction attribute information can be stored in a data file named RTRW_TS.VOB.

As shown in FIG. 3C, real time recording/reproducing attribute information for each file can be stored in a separate file. As an example, real time recording/reproduction attribute information can be stored in an information file having an RTRW format named RTRW_TS.IFO. As another example, when the file system is the UDF system, the real time recording/reproduction attribute information can be stored in a volume

structure area separate from a file structure area, as shown in FIG. 3D.

Therefore, when real time recording/reproduction attribute information is stored in the volume structure area or file structure area in the UDF system, the real time recording/reproduction attribute information is first interpreted upon mounting a volume or opening a file, and data is then recorded/reproduced in real time according to the interpreted information.

Real time recording/reproduction file indication information (e.g., identifier = "AV file") representing that a file requires real time recording/reproduction is included in the real time recording/reproduction attribute information. Among information on the size of the minimum contiguous storage block satisfying the condition of expression 1, reproduction time information for ensuring minimum contiguous storage, recording/reproduction bit rate information, and information on the contiguous recording/reproduction type, at least one can be stored in the real time recording/reproduction attribute information. Here, if there are three types of discs A, B and C, the contiguous recording/reproduction type information can be predetermined as follows:
type A = 10.08 Mbps, type B = 1.4 Mbps, type C = 8 Mbps

An attribute representing whether files are currently arranged so as to be recorded/reproduced in real time, i.e., an attribute representing the current real time recordable/reproducible state of files, is also included in the real time recording/reproduction attribute information.

Real time recording/reproduction bit rate information is stored in the real time recording/reproduction attribute information. When the recording/reproduction bit rate is changed in each section, information associated with a plurality of bit rate values and sections (e.g., position information) can be stored in the real time recording/reproduction attribute information. The maximum allowable value of the real time recording/reproduction bit rate can be further stored in the real time recording/reproduction attribute information. Here, the control information of a spindle

motor can be obtained by using the recording/reproduction bit rate information.

In addition, file defect management information, file buffering information, file allocation information, etc. can be included in the real time recording/reproduction attribute information. That is, if file defect management information is stored in the real time recording/reproduction attribute information, replacement of a defective block with a spare area is not attempted when reading or writing fails, and further reading or writing of the defective block is not attempted.

For example, file allocation information such as non-allocation of a defective block replaced by a spare area as a data block can be stored in the real time recording/reproduction attribute information. File buffering information associated with the amount of data to be initially read from a track buffer and the amount of data to be recorded in the track buffer at a time can also be stored as the real time recording/reproduction attribute information.

Instead of individually storing many real time recording/reproduction attributes such as file defect management information, file allocation information, and file buffering information, the conditions for controlling real time files are classified into types, and the information of the classified types is recorded in a real time recording/reproduction file attribute information area. In this way, easy real time recording and reproduction can be achieved. For example, the following types of information can be provided:

type A: a data bit rate of 10Mbps, impossibility of allocation of a data block to a defective block replaced by a spare area, and impossibility of reattempt of reading upon failure in reading; and
type B: a data bit rate of 8Mbps, possibility of allocating a data block to a defective block replaced by a spare area, and impossibility of reattempting reading upon failure in reading.

Meanwhile, referring to FIG. 4 showing an example of real time files comprised of minimum contiguous storage blocks occupying blocks on a disc according to the present

invention, a file A is a file requiring real time reproduction. If a minimum contiguous storage block satisfying the condition of expression 1 is comprised of four blocks, the file A is recorded in real time in units of four blocks. That is, the real time file A occupies blocks 0, 1, 2, 3, 5, 6, 7, 8, 11, 12, 13 and 14 on a disc. A general file B occupies blocks 4, 9, 10 and 15 on the disc. The general file B not requiring real time reproduction has a minimum contiguous storage block comprised of one block, and one or an arbitrary number of segments can be stored. This block generally corresponds to a sector of a disc.

The file A operates for real time reproduction, as follows.
In step 1, blocks 0, 1, 2 and 3 are read.
In step 2, block 5 is searched for during playback of the blocks 0, 1, 2 and 3.
In step 3, blocks 5, 6, 7 and 8 are read.
In step 4, block 11 is searched for during playback of the blocks 5, 6, 7 and 8.
In step 5, blocks 11, 12, 13 and 14 are read and played back.

If no areas for contiguous blocks capable of satisfying the minimum contiguous storage block
exist on a disc upon storage of a file requiring real time reproduction, recording of the file is not possible. However, if a warning message like "contiguous recording is not possible. Shall the minimum contiguous storage block be designated as one block and the file be stored in the designated block length ?" is sent to a user, and if the user requires storage, the file can be stored in the minimum contiguous storage blocks comprised of one block. In this case, the value of the initially-designated minimum contiguous storage block is stored in the information associated with the minimum contiguous storage block length included in the real time recording/reproduction attributes, but information indicating that the arrangement of currently stored files makes real time recording/reproduction impossible is stored in a current real time recordable/reproducible state attribute. This is done so that a file to be copied can be contiguously treated as a real time recording/reproduction file when the file is copied on different discs or the same disc.

In the present invention, a driving apparatus, such as a CD drive and a DVD drive, having a seek time (e.g., 150ms) significantly longer than a read time (e.g., 1.43ms), which is expressed by seek time >> read time, can also realize real time reproduction if it satisfies the condition of expression 1: seek time + read time < playback time.

Meanwhile, the minimum contiguous storage block limits the allocation of a free block on a disc to satisfy a predetermined purpose. Here, the free block means a non-used area having no defective blocks or a rewritable area among user areas that can be used by a user.

If the minimum contiguous storage block is defined as 16 blocks arranged in an error correction code (ECC) block, the allocation of a data block is not possible for less than 16 contiguous free blocks. Also, the allocation of a data block is not possible for 16 contiguous free blocks ranging over two ECC blocks. Here, the minimum contiguous storage block has the purpose of recording and reproducing a DVD-RAM in an ECC unit.

When all real time data is stored on physically-contiguous blocks on a disc, no seeking occurs, and thus recording/reproduction is prevented from being interrupted. However, since contiguous blocks do not infinitely exist, a minimum contiguous storage block is calculated and stored as the real time recording/reproduction attributes of a file, and real time data is recorded in the minimum contiguous storage block. In this way, the interruption of a screen can be prevented.

If an MPEG playback bit rate (=Vb) of 8Mbps, a seek time of 150ms, a read bit rate (=Va) of 11Mbps, a block of 2048 bytes, and data having ECC blocks each comprised of 16 blocks is recorded in a recording medium such as a disc, the minimum contiguous storage block S can be obtained according to the condition of expression 1 as shown in the following expression 2:

(1-Vb/Va)□(2048□8)□S > Vb□seek time/1000 ...(2)

From this expression, the minimum contiguous storage block S is 261 blocks. When

data is recorded in units of at least 261 blocks designated as the minimum contiguous storage block, real time reproduction is possible. However, 272 blocks corresponding to 17 contiguous ECC blocks can be designated as the minimum contiguous storage block. Here, the predetermined purpose is to ensure recording/reproduction when the maximum seek time is 150ms.

With one ECC block comprised of 16 blocks designated as the minimum contiguous storage block, and a limitation such as the seek time added as shown in expression 2, a free block allocation method for real time recording and reproduction is classified into steps, and the steps can be arranged as shown in Table 1:

[Table 1]

	number of contiguous blocks	purposes
third step	1088 blocks (ECC arrangement)	ensuring real time recording/reproduction between blocks requiring a seek time of 600ms
second step	272 blocks (ECC arrangement)	ensuring real time recording/reproduction between blocks requiring a seek time of 150ms
first step	16 blocks (ECC arrangement)	ensuring recording and reproduction in an ECC unit (_ all allocated blocks must satisfy the first step)

A/V data is recorded and reproduced by arranging blocks satisfying a limitation on the minimum contiguous storage block whose number of blocks depends on each step, so that the blocks can be physically connected to each other, whereby real time recording and reproduction can be ensured. For example, when there are three groups of blocks of the minimum contiguous storage block: 16 blocks, 272 blocks and 1088 blocks, and the seek time is 150ms, the possibility of real time recording/reproduction depends on the method of connecting the blocks.

That is, when 272 blocks, 1088 blocks, and 16 blocks are sequentially arranged, real time recording and reproduction is possible, and when 16 blocks, 272 blocks and 1088 blocks are sequentially arranged, real time recording and reproduction is not possible.

Accordingly, the minimum contiguous storage block can be effectively recorded and reproduced in real time using the allocation of blocks by steps and the block connecting method.

Meanwhile, if the end portion of a file is not filled with as much data as in a minimum contiguous storage block as shown in FIG. 5, even when the file is recorded according to the condition of the minimum contiguous storage block, an attribute representing that data blocks for the unfilled area are allocated but not recorded is stored as real time recording/reproduction information, thus allowing real time playback upon additional recording.

That is, referring to FIG. 5 showing the one-dimensional structure of a recording medium in which real time AV data stored in the minimum contiguous storage block is placed, real time recording/reproduction attribute information in addition to the length of a file, information on the position of file data, information on the possibility or impossibility of reading/writing a file, etc. is further stored in file control information positioned at a disk block #1. Two minimum contiguous storage blocks each comprised of 272 data blocks are allocated to first file data placed at a disk block #m, 272 data blocks for the minimum contiguous storage block are allocated to second file data positioned at a disk block #n, and 200 data blocks and 72 allocated/unrecorded blocks are allocated to third file data positioned at a disk block #o.

When a file for real time recording/reproduction is copied on the same disc or different discs, the data blocks of the file must be arranged on the disc using real time recording/reproduction attribute information so that the file can be played back in real time. If the arrangement of the data blocks is not possible, the data blocks are arranged on the same basis as the arrangement basis of general file blocks. Here, the real time

recording/reproduction attribute information maintains the original attribute information, but the impossibility of real time recording/reproduction is set as a current real time recordable/reproducible state attribute.

Also, when an operating system (OS) detects defective blocks on a disc upon copying of a file, data blocks to be copied must be arranged in consideration of the original real time recording/reproduction attribute information and medium defect management information recorded in a secondary defect list (SDL). For example, when the minimum contiguous storage block is 40 blocks as shown in FIG. 6A, data blocks are arranged in consideration of a defective area of a disc to copy a file on, as shown in FIG. 6B. On the other hand, when the OS does not detect defects recorded in the SDL, data is allocated to blocks other than the defective block area in an application program for copying and in consideration of real time recording/reproduction attribute information as shown in FIG. 6B.

FIG. 7 is a flowchart illustrating a reproducing method using real time recording/reproduction information, according to an embodiment of the present invention. A disc is loaded on a player in step S101, and the player reads a volume area from the disc in step S102. A determination of whether real time recording/reproduction information exists on the volume area is made in step S103. If real time recording/reproduction information exists on the volume area, playback of files is set in consideration of the real time recording/reproduction information, in step S104. If it is determined in step S103 or after step S104 that no real time recording/reproduction information exists on the volume area, reading of the volume area is completed in step S105.

Thereafter, a file is read in step S106. It is determined whether real time recording/reproduction information exists in the read file, in step S107. If the real time recording/reproduction information exists in the read file, playback of the file is set in consideration of the real time recording/reproduction information, in step S108. If it is determined in step S107 or after step S108 that no real time recording/reproduction information exists in the read file, the read file is played back in consideration of

whether the real time recording/reproduction information has been set, in step S109.

Here, when real time recording/reproduction information exists in the volume structure area, steps S107 and S108 may not be performed. Also, when real time recording/reproduction information exists in a file control information area, steps S103, S104 and S105 may not be performed.

FIG. 8 is a schematic block diagram of a disc recording and reproducing apparatus to be applied to the present invention. The function of the apparatus for recording and reproducing A/V data using a recordable and rewritable disc is divided into recording and reproduction.

Upon recording, a codec 110 compresses and encodes an audio/video (A/V) signal from an external bitstream using a predetermined compression scheme, and writes data compressed according to a recording/reproduction bit rate (Vb) to a track buffer 120. An error correction encoder and decoder (ECC) 130 error-correct encodes the data written to the track buffer 120, reads the error-correction encoded data at a write/read bit rate Va, and applies the result to a pickup unit 140. Also, the ECC 130 applies real time recording/reproduction information generated under the control of a controller 170 to the pickup unit 140 so that the information can be recorded on a volume structure area or a file control information area. The pickup unit 140 converts the error-correction encoded data into a radio frequency (RF) signal and records the RF signal on a disc 150. Here, the recording rotating speed of a spindle motor 160 for driving the disc 150 is controlled according to a servo control signal from the controller 170.

Upon reproduction, when real time recording/reproduction information is stored in the file control information area or the volume structure area, buffering information associated with the amount of data to be initially read from the track buffer, file allocation information, defect management information, recording/reproduction bit rate information, etc. are read in advance, and reading of file data is controlled on the basis of the read information. File data to be satisfied by the condition of the minimum contiguous storage block is read from the disc 150 at a write/read bit rate Va. The read

file data is error-correction decoded by the ECC 130 via the pickup unit 140, and written to the track buffer 120. The codec 110 reads data written to the track buffer 120 at the recording/reproduction bit rate Vb, decodes the read data, and reproduces A/V data.

When recording/reproducing bit rate information exists in the real time recording/reproduction information, the controller 170 obtains the control information of the spindle motor 160 from the recording/reproducing bit rate information provided from the pickup unit 140 and the ECC 130, and can drive not only the spindle motor but also a servo mechanism.

FIG. 9 is a view showing the flow of control for recording/reproducing data on a disc to which real time real time recording/reproduction attributes are provided, in a real time rewritable (RTRW) system.

The RTRW system is comprised of an application layer 201 for producing a command associated with A/V data recording/reproduction, a Windows kernel 202 for interpreting the produced command, and a device driver 203 having a file system the same as the file system of a DVD-RAM device driver for requesting a corresponding function according to the command interpreted by the Windows kernel 202 by transmitting a driver command to a drive 204. Here, the Windows kernel 202 and the device driver 203 correspond to a file system layer, and the Windows kernel 202 can be called a kernel layer.

FIG. 10 is a block diagram showing the flow of real time recording/reproduction data for a computer system among RTRW systems. Upon recording, the following processes are performed in a multitasking manner: storing A/V data input to an A/V encoder 211 in a computer main memory 212 in real time; storing A/V data stored in the computer main memory 212 in a first-in first-out (FIFO) file of a hard disk drive (HDD) 213; and storing the A/V data from the FIFO file of the HDD 213 in a DVD-RAM disk 214. Here, when a sufficient main memory exists on a computer, the FIFO file may not exist in the HDD.

Upon reproduction, a process for storing A/V data from the DVD-RAM disk 214 in a computer main memory 215 in real time and a process for reading the A/V data stored in the main memory 215 through an A/V decoder 216 are performed in a multitasking way.

For example, the function of a RTRW system using a Windows kernel is divided into creation of a file to which real time recording/reproduction attributes are provided, allocation of a data area, data recording, data reproduction, data deletion, and file closing, and these divided functions will now be described referring to FIG. 9.

<method of creating a real time recording/reproduction file>

In the first step, a Windows kernel API (application programming interface) called to create a real time recording/reproduction file is a create file. The application layer 201 assigns a file attribute as FILE_ATTRIBUTE_RTRW to a create file to create the real time recording/reproduction file, and calls the Windows kernel 202 as in the following example:

example: FileHandle = CreateFile ("AVFILE.MPG",FILE_ATRIBUTE_RTRW,...)

In the second step, the Windows kernel 202 orders the DVD-RAM device driver 203 to create a file.

In the third step, the DVD-RAM device driver 203 designates a FILE_ATTRIBUTE_RTRW attribute when the file generation function is ordered. When the FILE_ATTRIBUTE_RTRW attribute is designated, file control information is stored in an extended attribute area of a file entry, a stream directory ICB (information control block) area, a file identifier descriptor area, or a file type area or flag area of an ICB TAG field in a file entry. Here, bit rate information can also be set when an A/V file is created.

<method of allocating an allocated/unrecorded area of a real time recording/reproduction file>

In the first step, a Windows kernel API called to allocate an allocated/unrecorded area of a real time recording/reproduction file is a set file pointer having a seek function. In order for the application layer 201 to pre-allocate a data area of a real time recording/reproduction file in advance as an allocated/unrecorded area as large as a minimum contiguous storage block, the set file pointer calls the Windows kernel 202 as in the following example:

example: SetFilePointer (FileHandle,8_1024_1024,NULL,FILE_END)
SetFileBitrate (FileHandle,bitrate)

Alternatively, a data area necessary for real time recording/reproduction can be pre-allocated in advance as an allocated/unrecorded state using the SetFileBitrate (FileHandle,bitrate). Here, when the application layer knows a bit rate, and an API for converting the bit rate into the number of blocks exists in the file system layer, the number of blocks obtained by the API can be secured as the data area necessary for real time recording/reproduction in an allocated/unrecorded state using the SetFilePointer.

In the second step, the Windows kernel 202 orders the DVD-RAM device driver 203 to seek for a file.

In the third step, the DVD-RAM device driver 203 checks if real time recording/reproduction attributes are assigned to a file, upon ordering of the file seeking function, and secures an allocated/unrecorded data area as large as the length for seeking according to minimum contiguous storage conditions (for example, file defect management, file allocation, file buffering, the magnitude of a minimum contiguous storage block, and bit rate information) specified in the assigned real time recording/reproduction attributes, as shown in FIG. 11. One pre-allocated area or a plurality of areas are arranged in an ECC unit and can be allocated.

<method of recording data of a real time recording/reproduction file>

In the first step, a Windows kernel API called to record the data of the real time recording/reproduction file is a write file. The application layer 201 calls a Windows

kernel using a write file as in the following example, to store real time data:

example: WriteFile (FileHandle,AV_Buffer,32_1024,NULL,NULL)

In the second step, the Windows kernel 202 calls the file recording function of the DVD-RAM device driver 203.

In the third step, the DVD-RAM device driver 203 checks if real time recording/reproduction attributes are assigned to a file, upon calling the file recording function. If the real time recording/reproduction attributes are assigned, A/V data to be recorded is recorded in an allocated/unrecorded area according to real time recording conditions. Upon recording, when no allocated/unrecorded area exist, the magnitude of recorded data is reported to the application layer 201. The application layer 201 pre-allocates an allocated/unrecorded area designated as the real time recording/reproduction attributes to record the left-over unrecorded data using a seek command SetFilePointer with reference to the amount of recorded data, and again records the left-over data.

That is, as shown in FIG. 12A, A/V data of 32_1024 bytes is recorded in an allocated/unrecorded area of 8_1024_1024 bytes shown in FIG. 11, and the residual area is still allocated as the allocated/unrecorded area.

As shown in FIG. 12B, when the amount of data recorded in a variable written of the application layer 201 is reported since the allocated/unrecorded area is 32_1024 bytes short, the file system layer automatically pre-allocates an unallocated area using bit rate information designated through the SetFileBitrate. As shown in FIG. 12C, the residual data is recorded in the ECC block unit. When a defective block is generated during recording and an error is thus generated, a block corresponding to the defective block is excluded from the allocated/unrecorded area as shown in FIG. 12D.

Here, when the bit rates for sections can be distinguished from each other, information associated with the bit rate for each section can be recorded in a file control information area. That is, FIGS. 13A and 13B show an example of a plurality of bit rate values (here, V_1, V_2 and V_3) and information associated with sections stored as real time

recording/reproduction information in a file control information area when different bit rates are provided in different sections. FIGS. 13C and 13D show an example of one bit rate value (here, V_b) stored as real time recording/reproduction information in a file control information area when an identical bit rate is provided in the entire file data section.

<method of reproducing real time recording/reproduction file data>

In the first step, a Windows kernel API called to reproduce the data of a real time recording/reproduction file is a read file. The application layer 201 calls a Windows kernel using the read file as in the following example, to reproduce real time data:
example: ReadFile (FileHandle,AV_Buffer,32_1024,NULL,NULL)

In the second step, the Windows kernel 202 orders the DVD-RAM device driver 203 to read a file.

In the third step, the DVD-RAM device driver 203 checks if real time recording/reproduction attributes are assigned to the file, when the file reading function is ordered. If the real time recording/reproduction attributes are assigned, A/V data as long as the length for reproduction is reproduced from an A/V data area according to real time reproduction conditions.

Here, when a defect is generated in a block to be reproduced, a read command indicating that allocated/unrecorded file attributes are assigned but not read is transmitted from the DVD-RAM device driver 203 to the drive 204.

a real time recording command and a reproducing command provided by a command interface of the DVD-RAM device driver must be used upon real time recording/reproduction.

<method of deleting part of real time recording/reproduction file data>

In the first step, a "DeletePartOfFile" is called as the Windows kernel API to delete part of the data of a real time recording/reproduction file. In order to delete part of real time data, the application layer 201 calls a Windows kernel using the "DeletePartOfFile" as in the following example:

example: DeletePartOfFile (FileHandle,Offset,Size)

In the second step, the Windows kernel 202 orders the DVD-RAM device driver 203 to delete part of the file.

In the third step, when partial deletion of the file is ordered, the DVD-RAM device driver 203 checks if real time recording/reproduction attributes are assigned to the file, and deletes data from an A/V data area according to real time conditions if the real time recording/reproduction attributes have been assigned. Upon partial deletion of a file, a file for managing a dummy file or an ECC padding space list is created under a root directory on a system file.

FIG. 14A shows an area to be deleted from a real time file in which A/V data is arranged in ECC units. The deletion area is allocated to a free area as shown in FIG. 14B, and an A/V data section pertaining to the deletion area, among an ECC block ranging over the boundary of the deletion area, is called a padding space. A/V data in this padding space is managed as a separate file on the system file and stored in an allocation descriptor (AD) list in an ECC padding space list. A/V data not pertaining to the deletion area, in the ECC block, is stored in the AD list of a file entry. The ECC padding space list is again updated according to a function such as deletion or writing. When an application of the method according to the present invention is an UDF system, the ECC padding space list can be described by a short allocation descriptor.

In FIG. 14B, the A/V file space and the padding space of the ECC block ranging over the boundary of the deletion area have extent lengths. As shown in FIG. 14C, the A/V file space of the ECC block ranging over the boundary of the deletion area has both an extent length and an information length, but the padding space is managed as an allocation descriptor having an extent length and an information length of "0" in the AD

list in an A/V file entry. The an A/V file space not pertaining to the deletion area, in the ECC block, is also managed in the AD list in the AV file entry. In this case, the padding space can be defined as an extended allocation descriptor of UDF.

<method of closing a real time recording/reproduction file>

In the first step, a CloseHandle function is called as a Windows kernel API to close a real time file. In order to close a real time recording/reproduction file, the application layer 201 calls the window kernel 202 using the CloseHandle as in the following example:
example: CloseHandle (FileHandle)

In the second step, the window kernel 202 orders the DVD-RAM device driver 203 to seek for a file.

In the third step, when the file closing function is ordered, the DVD-RAM device driver 203 updates file control information (file entry, etc.) and disk information (e.g., free area information, etc.).

According to the present invention as described above, real time recording/reproduction attributes are assigned to a file, and the file is recorded/reproduced in a different way from a general file. In this way, a real time recording/reproduction file can be recorded/reproduced in real time.

Also, in the present invention, files are divided into real time files and general files, and defect management information, file allocation information, buffering information, and the magnitude information of a minimum contiguous storage block provided in each step are assigned as real time recording/reproduction information to the real time file upon recording/reproduction. Thus, real time recording/reproduction can be effectively performed.

Furthermore, in the present invention, the control information of a spindle motor is

obtained from real time recording/reproduction information associated with a recording/reproduction bit rate, thus controlling the spindle motor.

What is claimed is:

1. A recording and/or reproducing method comprising:
arranging and recording real time files requiring real time recording/reproduction according to real time recording/reproduction in a recording medium according to real time recording/reproduction information for ensuring real time reproduction, and recording the real time recording/reproduction information in the recording medium; and
reading and reproducing the real time files using the real time recording/reproduction information.

2. The recording and/or reproducing method as claimed in claim 1, wherein the recording of the real time recording/reproduction information comprises storing the real time recording/reproduction information in a file control information area of the recording medium.

3. The recording and/or reproducing method as claimed in claim 1, wherein the recording of the real time recording/reproduction information comprises storing the real time recording/reproduction information in a file control information area of a UDF system of the recording medium.

4. The recording and/or reproducing method as claimed in claim 1, wherein the recording of the real time recording/reproduction information comprises storing the real time recording/reproduction information in each corresponding real time file.

5. The recording and/or reproducing method as claimed in claim 1, wherein the comprises storing the real time recording/reproduction information associated with the real time files in a separate file from the real time files.

6. The recording and/or reproducing method as claimed in claim 1, wherein the recording of the real time recording/reproduction information comprises storing

the real time recording/reproduction information in a volume structure area of the recording medium.

7. The recording and/or reproducing method as claimed in claim 1, wherein the real time recording/reproduction information includes file indication information indicating that the real time files require real time recording/reproduction.

8. The recording and/or reproducing method as claimed in claim 1, wherein the real time files have sections with different bit rates, and the real time recording/reproduction information includes recording/reproduction bit rate information which includes information associated with the sections and a plurality of bit rate values corresponding to the different bit rates of the sections.

9. The recording and/or reproducing method as claimed in claim 8, wherein the arranging comprises automatically arranging file data areas of the real time files according to the recording/reproduction bit rate information.

10. The recording and/or reproducing method as claimed 9, wherein the real time recording/reproduction information includes a maximum allowable value of the real time recording/reproduction bit rates.

11. The recording and/or reproducing method as claimed in claim 1, wherein the real time recording/reproduction information includes at least one of minimum contiguous storage blocks satisfying a condition in which a playback time of a current data block is greater than a sum of the seek time and a read time of a data block to be played back next, and a playback time for ensuring minimum contiguous storage.

12. The recording and/or reproducing method as claimed in claim 11, wherein the real time files are arranged in the minimum contiguous storage blocks.

13. The recording and/or reproducing method as claimed in claim 11, wherein the

recording of the real time recording/reproduction information comprises if an end portion of one of the real time files is not filled with data by one of the minimum contiguous storage blocks while the one real time file is recorded in units of the minimum contiguous storage blocks, recording as the real time recording/reproduction information an attribute indicating that a number of data blocks corresponding to a size of the unfilled portion are allocated but unrecorded.

14. The recording and/or reproducing method as claimed in claim 11, wherein the minimum contiguous storage blocks are classified according to a size of an error correction code block and a maximum seek time.

15. The recording and/or reproducing method as claimed in claim 14, wherein the arranging comprises arranging the real time files in the classified minimum contiguous storage blocks.

16. The recording and/or reproducing method as claimed in claim 11, wherein the real time recording/reproduction information further includes current real time recordable/reproducible state information indicating whether a current file is arranged so as to be recorded/reproduced in real time.

17. The recording and/or reproducing method as claimed in claim 11, wherein the real time recording/reproduction information further includes contiguous recording/reproduction type information classified by conditions for controlling real time files, the conditions including recording/reproduction bit rate information, file defect management information, file allocation information, file buffering information, and the information of the minimum contiguous storage blocks.

18. The recording and/or reproducing method as claimed in claim 11, wherein the real time recording/reproduction information further includes at least one of file defect management information indicating that replacement of a defective block

with a block in a spare area of the recording medium and rereading or rewriting of the defective block are not attempted when reading or writing has failed, file allocation information indicating that a data block is not allocated to the defective block replaced by the spare area, and the buffering information associated with an amount of data to be initially read from a buffer and an amount of data written from the buffer at a time.

19. The recording and/or reproducing method as claimed in claim 1, wherein the reading and reproducing the real time files comprises:
reading a volume area on the recording medium; and
reproducing a file as one of the real time files in consideration of the real time recording/reproduction information if the real time recording/reproduction information exists in the volume area.

20. The recording and/or reproducing method as claimed in claim 19, wherein the reproducing of the file comprises analyzing recording/reproduction bit rate information, defect management information, file allocation. and file buffering information according to the real time recording/reproduction information in the volume area, and reading and reproducing file data in minimum contiguous storage blocks of the file.

21. The recording and/or reproducing method as claimed in claim 1, wherein the reading and reproducing the real time files comprises:
determining whether the real time recording/reproduction information exists in a file area; and
reproducing a file in consideration of the real time recording/reproduction information if the real time recording/reproduction information exists in the file area.

22. The recording and/or reproducing method as claimed in claim 21, wherein the reproducing of the file comprises analyzing recording/reproduction bit rate information, defect management information, file allocation information, and

file buffering information according to the real time recording/reproduction information in the file area, and reading and reproducing file data in minimum contiguous storage blocks.

23. The recording and/or reproducing method as claimed in claim 1, wherein the method further comprises:
copying a file to free area from which a defective block is excluded, based upon the real time recording/reproduction information and general defect management information recorded on the recording medium.

24. The recording and/or reproducing method as claimed in claim 23, wherein the copying of the file comprises copying the real time recording/reproduction information and the file together.

25. The recording and/or reproducing method as claimed in claim 23, wherein the copying of the file comprises copying only real time file data based on the real time recording/reproduction information.

26. The recording and/or reproducing method as claimed in claim 11, wherein the real time recording/reproduction information further includes current real time recordable/reproducible state information indicating whether it is possible to record/reproduce a current file in real time.

27. The recording method as claimed in claim 1, wherein the method further comprises the steps of:
recording general defect management information in the recording medium; and
copying a file to a free area from which a defective block is excluded, based upon the real time recording/reproduction information and the general defect management information recorded in the recording medium.

28. The recording method as claimed in claim 27, wherein the copying of the file comprising copying the real time recording/reproduction information and the file

together.

29. The recording method as claimed in claim 27, wherein the copying of the file comprises copying only real time file data based on the real time recording/reproduction information.

30. A recording method comprising the steps of:
arranging and recording real time files requiring real time recording/reproduction according to real time recording/reproduction in a recording medium according to real time recording/reproduction information for ensuring real time reproduction; and
recording the real time recording/reproduction information in the recording medium.

31. The recording method as claimed in claim 30, wherein the recording of the real time recording/reproduction information comprises storing the real time recording/reproduction information in a file control information area of the recording medium.

32. The recording method as claimed in claim 30, wherein the recording of the real time recording/reproduction information comprises storing the real time recording/reproduction information in a file control information area of a UDF system of the recording medium.

33. The recording method as claimed in claim 30, wherein the recording of the real time recording/reproduction information comprises storing the real time recording/reproduction information in each corresponding real time file.

34. The recording method as claimed in claim 30, wherein the recording of the real time recording/reproduction information comprises the real time recording/reproduction information associated with the real time files in a separate file form the real time files.

35. The recording method as claimed in claim 30, wherein the recording of the real time recording/reproduction information comprises storing the real time recording/reproduction information in a volume structure area of the recording medium.

36. The recording method as claimed in claim 30, wherein the real time recording/reproduction information includes file indication information indicating that the real time files require real time recording/reproduction.

37. The recording method as claimed in claim 30, wherein the real time files have sections with different bit rates, and the real time recording/reproduction information includes recording/reproduction bit rate information which includes information associated with the sections and a plurality of bit rate values corresponding to the different bit rates of the sections.

38. The recording method as claimed in claim 37, wherein the recording of the real time recording/reproduction information comprises automatically arranging file data areas of the real time files according to the recording/reproduction bit rate information.

39. The recording method as claimed in claim 38, wherein the real time recording/reproduction information includes a maximum allowable value of the real time recording/reproduction bit rates.

40. The recording method as claimed in claim 30, wherein the real time recording/reproduction information includes at least one of minimum contiguous storage block satisfying a condition in which a playback time of a current data block is greater than a sum of the seek time and a read time of a data block to be played back next, and a playback time for ensuring minimum contiguous storage.

41. The recording method as claimed in claim 40, wherein the recording of the real time recording/reproduction information comprises arranging the real time files in the minimum contiguous storage blocks.

42. The recording method as claimed in claim 40, wherein the recording of the real time recording/reproduction information comprises, if an end portion of one of the real time files is not filled with data by one of the minimum contiguous storage blocks while the one real time file is recorded in units of the minimum contiguous storage blocks, recording as the real time recording/reproduction information an attribute indicating that a number of data blocks corresponding to a size of the unfilled portion are allocated but unrecorded.

43. The recording method as claimed in claim 40, further comprising classifying the minimum contiguous storage blocks according to a size of an error correction code block and a maximum seek time.

44. The recording method as claimed in claim 43, wherein the arranging and recording of the real time files comprises arranging the real time files sin the classified minimum contiguous storage blocks.

45. The recording method as claimed in claim 40, wherein the real time recording/reproduction information further includes current real time recordable/reproducible state information indicating whether a current file is arranged so as to be recorded/reproduced in real time.

46. The recording method as claimed in claim 40, wherein the real time recording/reproduction information further includes contiguous recording/reproduction type information classified by conditions for controlling real time files, the conditions including recording/reproduction bit rate information, file defect management information, file allocation information, file buffering information, and the information of the minimum contiguous storage blocks.

47. The recording method as claimed in claim 40, wherein the real time recording/reproduction information further includes at least one of file defect management information indicating that replacement of a defective block with a block in a spare area of the recording medium and rereading or rewriting of the defective block are not attempted when reading or writing has failed, file allocation information indicating that a data block is not allocated to the defective block replaced by the spare area, and file buffering information associated with an amount of data to be initially read from a buffer and an amount of data written from the buffer at a time.

48. The recording method as claimed in claim 40, wherein the real time recording/reproduction information further includes current real time recordable/reproducible state information indicating whether it is possible to record/reproduce a current file in real time.

49. A reproducing method of a recording medium, wherein real time files requiring real time recording/reproduction according to real time recording/reproduction are stored in a recording medium according to real time recording/reproduction information for ensuring real time reproduction, and the real time recording/reproduction information is stored in the recording medium, the method comprising:

reading the real time files using the real time recording/reproduction information; and

reproducing the read real time files.

50. The reproducing method as claimed in claim 49, wherein the reading of the real time files comprises reading the real time recording/reproduction information from a file control information area of the recording medium.

51. The reproducing method as claimed in claim 49, wherein the reading of the real time files comprises reading the real time recording/reproduction information

from a file control information area of a UDF system of the recording medium.

52. The reproducing method as claimed in claim 49, wherein the reading of the real time files comprises reading the real time recording/reproduction information in each corresponding real time file.

53. The reproducing method as claimed in claim 49, wherein the reading of the real time files comprises reading the real time recording/reproduction information associated with the real time files in a separate file from the real time files.

54. The reproducing method as claimed in claim 49, wherein the reading of the real time files comprises reading the real time recording/reproduction information in a volume structure area of the recording medium.

55. The reproducing method as claimed in claim 49, wherein the real time recording/reproduction information includes the indication information indicating that the real time files require real time recording/reproduction.

56. The reproducing method as claimed in claim 49, wherein the real time files have sections with different bit rates, and the real time recording/reproduction information includes recording/reproduction bit rate information which includes information associated with the sections and a plurality of bit rate values corresponding to the different bit rates of the sections, the method further comprising:

reading the sections of the real time files in accordance with the corresponding plurality of bit rate values.

57. The reproducing method as claimed in claim 56, wherein the file data areas of the real time files are arranged according to the recording/reproduction bit rate information.

58. The reproducing method as claimed in claim 57, wherein the real time

recording/reproduction information includes a maximum allowable value of the real time recording/reproduction bit rates.

59. The reproducing method as claimed in claim 49, wherein the real time recording/reproduction information includes at least one of minimum contiguous storage blocks satisfying a condition in which a playback time of a current data block is greater than a sum of the seek time and a read time of a data block to be played back next, and a playback time for ensuring minimum contiguous storage.

60. The reproducing method as claimed in claim 59, wherein the real time files are arranged in the minimum contiguous storage blocks.

61. The reproducing method as claimed in claim 59, wherein if an end portion of one of the real time files is not filled with data by one of the minimum contiguous storage blocks while the one real time file is recorded in units of the minimum contiguous storage blocks, the real time recording/reproduction information is recorded as an attribute indicating that a number of data blocks corresponding to a size of the unfilled portion are allocated but unrecorded.

62. The reproducing method as claimed in claim 59, wherein the minimum contiguous storage blocks are classified according to a size of an error correction code block and a maximum seek time.

63. The reproducing method as claimed in claim 59, wherein the real time recording/reproduction information further includes current real time recordable/reproducible state information indicating whether a current file is arranged so as to be recorded/reproduced in real time.

64. The reproducing method as claimed in claim 59, wherein the real time recording/reproduction information further includes contiguous recording/reproduction type information classified by conditions for controlling

real time files, the conditions including recording/reproduction bit rate information, file defect management information, file allocation information, file buffering information, and the information of the minimum contiguous storage blocks.

65. The reproducing method as claimed in claim 59, wherein the real time recording/reproduction information further includes at least one of file defect management information indicating that replacement of a defective block with a block in a spare area of the recording medium and rereading or rewriting of the defective block are not attempted when reading or writing has failed, file allocated information indicating that a data block is not allocated to the defective block replaced by the spare area, and file buffering information associated with an amount of data to be initially read from a buffer and an amount of data written from the buffer at a time.

66. The reproducing method as claimed in claim 49, wherein the reading of the real time files comprises the steps of:
reading a volume area on the recording medium; and
reproducing a file as one of the real time files in consideration of the real time recording/reproduction information if the real time recording/reproduction information exists in the volume area.

67. The reproducing method as claimed in claim 66, wherein the reproducing of the file comprises analyzing recording/reproduction bit rate information, defect management information, file allocation information, and file buffering information according to the real time recording/reproduction information in the volume area, and reading and reproducing file data in minimum contiguous storage blocks of the file.

68. The reproducing method as claimed in claim 49, wherein the reproducing of the file comprises the steps of:
determining whether the real time recording/reproduction information exists in

a file area; and

reproducing a file in consideration of the real time recording/reproduction information if the real time recording/reproduction information exists in the file area.

69. The recording and reproducing method as claimed in claim 68, wherein reproducing of the file comprises analyzing recording/reproduction bit rate information, defect management information, file allocation information, and file buffering information according to the real time recording/reproduction information in the file area, and reading and reproducing file data in minimum contiguous storage blocks.

70. The reproducing method as claimed in claim 49, wherein the method further comprises the steps of :

(c) copying a file to a free area from which a defective block is excluded, based upon the real time recording/reproduction information and general defect management information recorded on the recording medium.

71. The reproducing method as claimed in claim 70, wherein the copying of the file comprises copying the real time recording/reproduction information and the file together.

72. The reproducing method as claimed in claim 70, wherein the copying of the file comprises copying only real time file data based on the real time recording/reproduction information.

73. The reproducing method as claimed in claim 59, wherein the real time recording/reproduction information further includes current real time recordable/reproducible state information indicating whether it is possible to record/reproduce a current file in real time.

74. A recording and/or reproducing method comprising the steps of:

recording real time files requiring real time recording and/or reproduction on a recording medium according to real time recording and/or reproduction information for ensuring real time reproduction.

recording the real time recording and/or reproduction information in a file type field in an (ICB) TAG field of a file entry for a universal disk format (UDF) system.

75. The recording and/or reproducing method as claimed in claim 74, further comprising reproducing the real time files using the real time recording and/or reproduction information.

76. The recording and/or reproducing method as claimed in claims 74, wherein the recording of the real time files and the real time recording and/or reproduction method comprises storing the real time recording and/or reproduction information in corresponding ones of the real time files.

77. The recording and/or reproducing method as claimed in claim 74, wherein the real time recording and/or reproduction information includes file indication information indicating that the real time files require real time recording and/or reproduction.

78. The recording and/or reproducing method as claimed in claim 74, wherein the real time recording and/or reproduction information includes at least one of recording/reproduction bit rate information, information on minimum contiguous storage block satisfying a condition in which a playback time of a current data block is greater than a sum of a seek time and a read time of a data block to be played back next, and information on a play back time for ensuring minimum contiguous storage.

79. The recording and/or reproducing method as claimed in claim 75, wherein the reproducing of the real time files comprise:

reading a volume area on the recording medium; and

reproducing a file as one of the real time files in accordance with the real time recording/reproduction information.

80. The recording and/or reproducing method as claimed in claim 79, wherein the reproducing of the file comprises analyzing recording/reproduction bit rate information, defect management information, file allocation information, and file buffering information according to the real time recording/reproduction information.