

SPHERICAL-ANNULAR BLOWOUT PREVENTER HAVING A PLURALITY OF PISTONS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation-in-part under 35 U.S.C. §120 of U.S. application Ser. No. 14/087,091, filed on November 22, 2013, the entirety of which is hereby incorporated by reference for all purposes.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

[0002] Not applicable.

REFERENCE TO A COMPACT DISK APPENDIX

[0003] Not applicable.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0004] The following description relates to blowout preventers used in the oil and gas industry during oil and gas well drilling and work over to prevent escape of well bore pressure into the outside environment in the event of an unexpected pressure “kick” due to the influx of formation fluid or other uncontrolled situations. For example, an annular-spherical blowout preventer design may include multiple pistons and glands.

2. Description of Related Art

[0005] Well control is an important aspect of oil and gas exploration. For example, when drilling a well, safety devices must be put in place to prevent damage to equipment and, most importantly, to personnel resulting from unexpected events associated with drilling operations. Because of safety conditions and risk of blowouts devices known as blowout preventers (BOPs) are installed above the wellhead at the surface or on the sea floor in deep water situations to effectively seal a wellbore until measures can be taken to control the kick. Blowout preventers are large, specialized high-pressure valves or similar mechanical devices, typically installed

redundantly in stacks and used to seal and control downhole pressure and monitor oil and gas wells to ultimately prevent the uncontrolled flow of liquids and gases during well drilling operations. Blowout preventers come in a variety of styles, sizes and pressure ratings and often several individual units serving various functions are combined to compose a blowout preventer stack. Some of the functions of a blowout preventer system include, but are not limited to, confining well fluid to the wellbore, providing a means to add fluid to the wellbore, allowing controlled volumes of fluid to be withdrawn from the wellbore, regulating and monitoring wellbore pressure, and sealing the wellhead.

[0006] In addition to controlling the downhole pressure and the flow of oil and gas, blowout preventers are intended to prevent tubing, tools and drilling fluid from being blown out of the wellbore when a blowout threatens. Blowout preventers are critical to the safety of crew, rig and environment, and to the monitoring and maintenance of well integrity. Thus, blowout preventers are intended to be fail-safe devices. Multiple blowout preventers of the same type are frequently provided for redundancy, an important factor in the effectiveness of fail-safe devices.

[0007] There are two major types of blowout preventers, annular and RAM. Annular BOPs are usually mounted to the very top of a BOP stack. The drilling crew then typically mounts a predetermined number of RAM BOPs below the annular blowout preventer. Blowout preventers were developed to cope with extreme erratic pressures and uncontrolled flow, often referred to as formation kick, emanating from a well reservoir during drilling. Kicks can lead to a potentially catastrophic event known as a "blowout." If a kick is detected, the annular is usually closed first and then the RAM is used as a backup if the annular should fail. Often times during operation BOPs are damaged and repair is difficult if not impossible when dealing with internal component damage such as pistons.

[0008] In drilling a typical high-pressure well, drill strings are routed through a blowout preventer stack toward the reservoir of oil and gas. As the well is drilled, drilling fluid, "mud", is fed through the drill string down to the drill bit, "blade," and returns up the wellbore in the ring-shaped void, annulus, between the outside of the drill pipe and the casing (piping that lines the wellbore). The column of drilling mud exerts downward hydrostatic pressure to counter opposing pressure from the formation being drilled, allowing drilling to proceed. When a kick

occurs, rig operators or automatic systems close the blowout preventer units, sealing the annulus to stop the flow of fluids out of the wellbore. Denser mud is then circulated into the wellbore down the drill string, up the annulus and out through the choke line at the base of the BOP stack through chokes until downhole pressure is overcome. If the blowout preventers and mud do not restrict the upward pressures of a kick a blowout results, potentially shooting tubing, oil and gas up the wellbore, damaging the rig, and leaving well integrity in question.

SUMMARY OF THE INVENTION

[0009] According to an example, a blowout preventer includes an upper housing comprising an inner ceiling with a cavity configured to accommodate a main seal, a lower housing comprising a plurality of internal fluidly interconnected cylinders, a plurality of annular pistons and glands configured to be placed within the plurality of internal fluidly interconnected cylinders, an energizing ring configured to be operated on by the annular pistons in order to operate the main seal, and disposed circumferentially within a void area of the lower housing, and an upper gland assembly configured to isolate the plurality of internal fluidly interconnected cylinders from the void area of the lower housing.

[00010] In another example, a blowout preventer includes a housing comprising a plurality of fluidly interconnected cylinders formed therein, a main seal positioned within the housing, a plurality of cylindrical sleeves removably placed within the plurality of fluidly interconnected cylinders, a plurality of annular pistons and glands configured to be placed within the plurality of cylindrical sleeves, and an energizing ring configured to be operated on by the annular pistons in order to operate the main seal.

[00011] In another example, a piston cartridge configured to be used in a blowout preventer includes a cylindrical sleeve forming the outer wall of the piston cartridge, an annular piston placed within the cylindrical sleeve, and a gland retained on a distal portion of the piston cartridge, wherein the annular piston comprises a hole configured to receive a piston rod.

[00012] In another example, a method of using a blowout preventer includes providing a piston cartridge, comprising a cylindrical sleeve, an annular piston, and a gland, into a cavity formed within the blowout preventer, connecting a piston rod of the blowout preventer to a hole

formed within the annular piston of the piston cartridge; and covering the cavity of the blowout preventer using a bottom cover plate.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[00013] The foregoing summary, as well as the following detailed description, will be better understood when read in conjunction with the appended drawings. For the purpose of illustration, certain embodiments of the present disclosure are shown in the drawings. It should be understood, however, that the invention is not limited to the precise arrangements and instrumentalities shown. The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate an implementation of system, apparatuses, and methods consistent with the present invention and, together with the description, serve to explain advantages and principles consistent with the invention.

[00014] FIG. 1 illustrates a perspective view of an example of a blowout preventer assembly.

[00015] FIG. 2 illustrates a cross-sectional perspective view of the blowout preventer assembly connected according to one embodiment.

[00016] FIG. 3A illustrates a cross-sectional elevation view of the blowout preventer assembly rotated approximately 90 degrees from that as shown in FIG. 2, according to one embodiment.

[00017] FIG. 3B illustrates a cross-sectional elevation view of the blowout preventer assembly with Detail A of an annular piston and associated gland indicated according to one embodiment.

[00018] FIG. 3C illustrates a magnified depiction of Detail A as shown in FIG. 3B of a cross-sectional side view of the annular piston and gland according to one embodiment.

[00019] FIG. 4 illustrates a cross-sectional view of an energizing ring utilized with one embodiment of the blowout preventer.

[00020] FIG. 5 illustrates a cross-sectional view of a lower housing utilized with one embodiment of the blowout preventer.

[00021] FIG. 6 illustrates a cross-sectional view of an upper housing utilized with one embodiment of the blowout preventer.

[00022] FIG. 7 illustrates a cross-sectional view of another example of a blowout preventer assembly.

[00023] FIGS. 7A and 7B illustrate magnified depictions of an example of the blowout preventer including an adaptor ring with thru holes and a filter or wire mesh as shown in FIG. 7.

[00024] FIG. 8 illustrates a cross-sectional view of an example of a lower housing including an upper gland assembly and a cylindrical sleeve.

[00025] FIG. 9 illustrates a cross-sectional view of an example of the lower housing including an indicator/bleed port.

[00026] FIG. 9A illustrates a magnified depiction of an example of the indicator/bleed port as shown in FIG. 9.

[00027] FIG. 10 illustrates a cross-sectional view of an example of a removable piston cartridge of the blowout preventer.

DETAILED DESCRIPTION OF THE INVENTION

[00028] Before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The Figures and written description are provided to teach any person skilled in the art to make and use the inventions for which patent protection is sought. The invention is capable of other embodiments and of being practiced and carried out in various ways. Those skilled in the art will appreciate that not all features of a commercial embodiment are shown for the sake of clarity and understanding. Persons of skill in the art will also appreciate that the development of an actual commercial embodiments incorporating aspects of the present inventions will require numerous implementation specific decisions to achieve the inventors' ultimate goal for the commercial embodiment. While these efforts can be complex and time-consuming, these efforts nevertheless would be a routine undertaking for those of skill in the art having the benefit of this disclosure.

[00029] In addition, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting. For example,

the use of a singular term, such as, “a” is not intended as limiting of the number of items. Also the use of relational terms, such as but not limited to, “top,” “bottom,” “left,” “right,” “upper,” “lower,” “down,” “up,” “side,” and “surface” are used in the description for clarity in specific reference to the Figures and are not intended to limit the scope of the invention or the appended claims. Further, it should be understood that any one of the features of the invention can be used separately or in combination with other features. Other systems, methods, features, and advantages of the invention will be or become apparent to one with skill in the art upon examination of the Figures and the detailed description. It is intended that all such additional systems, methods, features, and advantages be included within this description, be within the scope of the present invention, and be protected by the accompanying claims.

[00030] Reference will now be made in detail to an implementation consistent with the present invention as illustrated in the accompanying drawings. For the purpose of clarification, embodiments described herein reference the term “fluid,” which refers to a gas, liquid, as well as liquid solution with solid aggregates, as well as any other material that can reasonably be expected to flow.

[00031] Referring to FIG. 1, by way of non-limiting example, and consistent with embodiments of the invention, a blowout preventer assembly **1** is shown, wherein the blowout preventer assembly **1** is hydraulically actuated and is annular-spherical in overall design. When describing the operational function of the present embodiment of the blowout preventer assembly **1**, the volume of hydraulic fluid to effectuate desired operation is about 4 gallons to “close” and about 3 ½ gallons to “open” a main seal **25** (see FIGS. 2 and 3A) of the blowout preventer assembly **1**. Further, in the preferred embodiment, the inner dimensions of well pipe that can be accommodated can range from about 5 ½ inches to about 21 ¼ inches. All metal components utilized in manufacture of the present embodiment, when possible and not restricted by pressure constraints or other operational reasons, are manufactured and machined from commercially available 4130 steel. One skilled in the art will recognize that other diameters, types and thicknesses of steel or preferred materials can be utilized when taking into consideration safety and the high pressure functioning capacity of the present embodiment which can range in operation from 3,000 psi to 20,000 psi.

[00032] The blowout preventer assembly **1** will now be discussed in detail with reference to the cross-sectional views as shown in FIGS. 2 and 3A together, wherein FIG. 3A is rotated clockwise in view about 90 degrees as compared to the view depicted in FIG. 2. The blowout preventer assembly **1** comprises a plurality of constituent components that provide blowout prevention in oil and gas well operation through implementation and operation of a plurality of annular pistons **40** (also shown in specific detail in FIG. 3C), as will be further described. The blowout preventer assembly's **1** containment structure is generally configured having a lower housing **10** with a plurality of internal fluidly interconnected cylinders **160**, an upper housing **5** (also shown in specific detail in FIG. 6), a one piece energizing ring **15** (also shown in specific detail in FIG. 4), and a plurality of individual bottom cover plates **65**. The blowout preventer assembly **1** also comprises a commercially available off-the-shelf main seal **25** with a plurality of main seal ribs **27**, an adaptor ring **30**, a plurality of glands **45** (also shown in specific detail in FIG. 3C) dedicated to each annular piston **40**, and various dedicated and associated seals and threaded attachments which will be detailed hereinbelow with associated components. The main seal is positioned over a bowl **155** machined into one end of the energizing ring **15**.

[00033] Referring to FIGS. 2, 3A and 6 together, the present embodiment of the blowout preventer assembly **1** comprises the upper housing **5** having a concave inner design defining a spherical or concave shaped main bore **26** in an inner ceiling **28** of the upper housing **5** that allows for accommodation, fitment and operation of the main seal **25**. The main bore's **26** inner ceiling's **28** concave design provides circumferential closure guidance and integrity to bifurcations the main seal **25** which for the main seal ribs **27**. The main seal ribs **27** function in conjunction with the inner ceiling **28** shape to cause sealing closure around and contact with the outer diameter of pipe (not shown) positioned within the lower housing column bore **130** when demand for closure of the blowout preventer assembly **1** is required by induced well bore factors. The upper housing **5** further comprises a series of spaced about female threaded connections **9** for receiving upper housing bolts **8** used to provide attachment and securement of other desired gas or oil well/drilling components. Further provided in an upper housing attachment end **4** of the upper housing **5** are a plurality of spaced apart individually machined bifurcated upper housing retainer lugs **150** for secured attachment with the lower housing **10** as will be described below. The bifurcated upper housing retainer lugs **150** are positionally machined in a bifurcated

spaced apart protruding fashion about an outer circumference of an upper housing attachment end **4**, as shown in FIG. 6. The bifurcated upper housing retainer lugs **150** operate to interlace, lock and secure, once mated, the lower housing **10** with the upper housing **5** via a quarter turn twist, thus securing both together.

[00034] Referring to FIGS. 2, 3A, and 5 together, the present embodiment of the blowout preventer assembly **1** comprises the lower housing **10** having a unitary structure design that provides for and contains much of the functional components and machined portions of the overall blowout preventer assembly **1**. Specifically, the unitary structure of the lower housing **10** defines a generally cylindrical shape having a lower housing flange **75**, a plurality of machined bifurcated lower housing retainer lugs **145**, a lower housing wall **167**, a machined upper seat **6**, a machined upper shoulder **119**, a lower seat **31**, a lower housing column **164** having a lower housing column wall **165** which defines an inner area of the lower housing column bore **130**, lower housing column wall seals **166**, and a plurality of internal fluidly interconnected cylinders **160** machined into a cylinder plane surface **163** wherein each cylinder has a dedicated cylinder fluid channel **161**. Each of the previous mentioned components and its integral function will be further detailed hereinbelow.

[00035] An upper shoulder seal **120** and an adaptor ring upper seal **140** are utilized as mud and cutting scrapers and are designed to prevent ingress of mud and cuttings into a plurality of column primary seals **122** and into a plurality of primary seals **95** and as a result prolongs the overall life of each. The upper shoulder seal **120** is removably attached to and circumferentially rests around and on the surface of an upper shoulder **119** via a plurality of upper shoulder seal retaining bolts **105** and is further secured into position via a retainer lip **118** on the energizing ring **15**. An adaptor ring **30**, having a plurality of adaptor ring primary seals **95** and a plurality of adaptor ring secondary seals **100**, is removably disposed on a lower seat **31** around the outer diameter of the adaptor ring **30** and covering the area adjacent to the adaptor ring upper seal **140** and the adaptor ring primary seal **95** to prevent external escape of pressure built up in the blowout preventer assembly **1**.

[00036] The lower housing **10** mates for operation with the upper housing **5** and the bifurcated upper housing retainer lugs **150** in a rotatable locking attachment fashion via a plurality of

spaced apart and machined bifurcated lower housing retainer lugs **145** similar to those machined into the upper housing **5** described above. The plurality of bifurcated lower housing retainer lugs **145**, however, are positionally machined in a bifurcated spaced apart protruding fashion about an inner circumference of a lower housing attachment end **11**, as shown in FIG. 5. The bifurcated lower housing retainer lugs **145** function to interlace, lock and secure, the lower housing **10** with the upper housing **5** via a quarter turn twist once mated together and the upper housing **5** is properly seated on the upper seat **6** of the lower housing **10**. The bifurcated upper housing retainer lug **150** and bifurcated lower housing retainer lug **145** connection design also allows rapid disassembly and assembly in-house and in the field.

[00037] The present embodiment of the lower housing **10**, as shown in FIGS. 2, 3A and 5 permits flow supply of demanded hydraulic fluid into the plurality of internal fluidly interconnected cylinders **160** through two primary supply ports, either an open port **305** or close port **310**. The close port **310** supplies hydraulic pressure in the bottom or close side of each annular piston **40** to activate the main seal **25**. When the main seal **25** is activated from hydraulic fluid pressure through the close port **310** the blowout preventer assembly **1** is closed and the well bore is isolated and thus prevents well bore pressure from migrating above the main seal **25**. When the main seal **25** is activated from the open port **305**, hydraulic fluid pressure is supplied into an open side of the annular piston **40**. The open and close function will be further described below.

[00038] As shown with specific reference to FIG. 5, in a preferred embodiment, six (6) internal fluidly interconnected cylinders **160** are machined into the steel body of the lower housing **10**. Each internal fluidly interconnected cylinder **160** is machined bored into a cylinder plane surface **163** that is located in a radial area bounded by the lower housing wall **167** and the lower housing column wall **165**. Each of the internal fluidly interconnected cylinders **160** is substantially equally spaced apart from adjacent cylinders. The fluid interconnectivity of each internal fluidly interconnected cylinders **160** within the lower housing **10** is achieved via implementation of the machined cylinder fluid channel **161** disposed in a horizontal plane within a circumferential portion of a cylinder wall **162** within each of the internal fluidly interconnected cylinders **160**.

[00039] A gland **45** having a circumferential channel **86**, as shown in FIGS. 2, 3A, and 3C, with a plurality of gland seals **85** is disposed in a distal portion of the internal fluidly interconnected cylinder **160**, wherein the distal portion of the internal fluidly interconnected cylinders **160** diameter that surrounds the gland **45** is of a second diameter larger than the first inner diameter of the internal fluidly interconnected cylinder **160** that encloses the annular piston **40**. Such smaller inner diameter portion of the cylinder **160** that encloses the annular piston **40** serves as a stop lip **146** and prevents movement during operation, or otherwise, of the gland **45** into the internal fluidly interconnected cylinder **160** portion enclosing the annular piston **40**. During all operations the gland **45** is removably fixed in a stationary position and attached to a bottom cover plate **65** with a half tap gland plug **60**. The only time the gland **45** is removed is for repair or replacement of the annular piston **40** or the gland **45**. The gland **45** can also be used as a secondary access to provide hydraulic power into the annular piston **40**. The gland **45** is the primary component that provides for test access and isolation of the annular pistons **40**.

[00040] As shown in FIGS. 3B and 3C an isolation and test plug **168** is provided for conducting pressure testing on an individual internal fluidly interconnected cylinder **160** or an annular piston **40**. The isolation and test plug **168** can be used when inserted into the gland test plug cavity **55** via an access aperture **115** to isolate an inoperable annular piston **40** from all other annular pistons **40** within the blowout preventer assembly **1**, thereby preventing substantial downtime to drilling operations. During normal operations, the isolation and test plug **168** is removed and is not present and is replaced by the half tap gland plug **60** for continued operations. FIGS. 2 and 3C show the cross section of the gland **45**. The gland **45** has two longitudinal gland channels **50** traversing an inner portion of the gland **45**. The gland channel **50** allows hydraulic fluid to flow to the annular piston **40** in the same internal fluidly interconnected cylinder **160** and allows hydraulic fluid to flow to the cylinder wall **162** and into the cylinder fluid channel **161**, thereby providing the aforementioned internal fluidly interconnected cylinder's **160** interconnectivity. The bottom cover plates **65** are positioned in a plate channel **66** and are removably attached by a plurality of threaded fasteners, such as bottom cover plate bolts **70** into the lower housing **10** to secure the glands **45** in place and to provide for easy access to the annular pistons **40** and the gland **45** for maintenance and/or removal.

[00041] The diameter and bore length of the internal fluidly interconnected cylinders **160** are a predetermined factor and are based on of the overall size and dimensions of the blowout preventer assembly **1** design which is dictated by operational necessity. Each annular piston **40** is fabricated having an annular design of predetermined diameter to provide proper fitment within the inner diameter of the internal fluidly interconnected cylinder **160**. The diameter and thickness of each annular piston **40** is dependent upon pressure requirements and other specifications of the overall blowout preventer assembly **1** size and design. One skilled in the art will recognize the overall blowout preventer assembly **1** size requirements and the internal fluidly interconnected cylinder **160**, annular pistons **40** and other herein described components and associated sizing required can vary in size, length, diameter and type of steel for proper operation without departing from the scope and spirit of the invention. The preferred embodiment can operate in the field to provide blowout prevention capability with fewer than six (6) functioning annular pistons **40** disposed in the internal fluidly interconnected cylinders **160**. However, blowout prevention is severely diminished or threatened with three (3) or fewer operating internal fluidly interconnected cylinders **160** and/or annular pistons **40**.

[00042] As shown in FIGS. 2, 3C and 4, the annular piston **40** is removably attached to a surface of a heel **16** on the energizing ring **15** by way of a piston connector **90** for enabling operation of the blowout preventer assembly **1** to facilitate proper and sufficient component movement for ultimate closure of the main seal ribs **27** of the main seal **25** around a pipe (not shown) when positioned within the lower housing column bore **130** and closure is demanded through a close port **310** due to hydraulic fluid operation. The annular pistons **40** have a plurality of side perimeter grooves **81** for accommodating associated piston seals **80** to prevent pressurized fluid leakage into undesired portions of the internal fluidly interconnected cylinder **160**.

[00043] As shown in FIGS. 2 and 3A, the lower housing **10** and upper housing **5** also enclose the energizing ring **15**. The energizing ring **15** (detailed in FIG. 4) is disposed such that at least three of the heels **16**, being bifurcated in an equidistant and spaced apart fashion about a distal end of the energizing ring **15** can functionally engage at least three (3), preferably six (6), independent annular pistons **40**, wherein the internal fluidly interconnected cylinders **160** and annular pistons **40** form a honeycomb design within the lower housing **10**. The energizing ring

15 heels **16** are each separately connected to one side of the heels' **16** accompanying annular pistons **40** via a piston connector **90** comprised of a male threaded bolt, seals and a nut. The piston connector **90** allows removal of either the annular piston **40** or the energizing ring **15**.

[00044] Now, the close and open operation of the blowout preventer assembly **1** will be described with reference to the Figures in general but with specific reference to FIG. 3A. To close the blowout preventer assembly **1**, hydraulic fluid pressure is primarily supplied through the close port **310**. The hydraulic pressure provided exerts force on a piston close side **169** to move the annular pistons **40** against the heel **16** of the energizing ring **15**. The force generated by the hydraulic pressure will then be transferred to the main seal **25** via the energizing ring **15**. This will cause closure to the main bore **26** of the blowout preventer assembly **1** thereby preventing all well bore pressure from escaping.

[00045] To open the blowout preventer assembly **1**, hydraulic pressure is primarily supplied through the open port **305**. The hydraulic pressure provided exerts force on a piston open side **170** to move the annular pistons **40** in a direction toward the gland **45**. The force generated by the hydraulic pressure will then be transferred to the energizing ring **15** and will cause opening of the main seal **25** and as a result will open the main bore **26** of the blowout preventer assembly **1**.

[00046] FIG. 7 is a diagram illustrating another example of a blowout preventer assembly **2**. The blowout preventer assembly **2** may include any of the components of blowout preventer assembly **1** as described above, and may operate in the same way. For example, the blowout preventer assembly **2** includes the upper housing **5**, the lower housing **10**, the main seal **25**, the adaptor ring **30**, the plurality of annular pistons **40** operating within the plurality of internal fluidly interconnected cylinders **160** formed in the lower housing **10**, the plurality of glands **45** formed on the bottom of the fluidly interconnected cylinders **160**, the bottom cover plates **65** covering the fluidly interconnected cylinders **160**, among other components of the blowout preventer assembly **1**. Additionally, blowout preventer assembly **2** includes an open port **305** and close port **310** for the supply of hydraulic fluid pressure to the annular pistons **40** and for operating the main seal **25**. A description of these components and their operations is provided in detail with reference to FIGS. 1-6 above.

[00047] Referring to the example shown in FIG. 7, the blowout preventer assembly **2** includes an energizing ring **215** which may operate in a similar way as the energizing ring **15** of the blowout preventer assembly **1**. In this example, energizing ring **215** is placed within a void area **230** which is separated from the fluidly interconnected cylinders **160** by an upper gland assembly **245**. Accordingly, the upper gland assembly **245** isolates and protects the fluidly interconnected cylinders **160** and components therein, such as the annular pistons **40** and the plurality of glands **45**, from debris and well fluid which may enter the blowout preventer **2** during drilling operations. For example, the upper gland assembly **245** may include a plurality of upper gland assemblies **245** each being used with one of the plurality of fluidly interconnected cylinders **160**, or the upper gland assembly **245** may be one assembly wrapping around the circumference of the blowout preventer **2** to isolate all fluidly interconnected cylinders **160**. The energizing ring **215** is connected to the annular pistons **40** by a piston rod **216**, which will be described in greater detail with reference to FIG. 8 below.

[00048] Still referring to FIG. 7, blowout preventer assembly **2** includes a cylindrical sleeve **250** which is removably placed within the fluidly interconnected cylinder **160** of the lower housing **10**. In this example, hydraulic fluid pressure drives the movement of the annular piston **40** within the cylindrical sleeve **250**, and a gland **45** is attached to the bottom of the cylindrical sleeve **250**. The cylindrical sleeve **250** may be removed entirely from the blowout preventer assembly **2** by removing the bottom cover plate **65**. This will be described in greater detail with reference to FIG. 10 below.

[00049] In an aspect, a removable cylindrical sleeve **250** protects the walls of the fluidly interconnected cylinders **160** of the lower housing **10** from corrosion or damage, and provides a cheaper and faster process of refurbishing or reworking the lower housing **10**. Further, the cylindrical sleeve **250** may be replaced with a new or refurbished cylindrical sleeve **250** in a quick and easy replacement process. The cylindrical sleeve **250** may be formed of any material, and is preferably formed of a light weight, resilient, and non-corrosive material. For example, the cylindrical sleeve **250** may be formed of aluminum, Grade 410 Stainless Steel, or 17-4 PH Stainless Steel.

[00050] FIGS. 7A and 7B are diagrams illustrating magnified depictions of an example of the blowout preventer assembly **2** including the adaptor ring **30** having thru holes **280** and a filter or wire mesh **285**. In this example, the adaptor ring **30** includes one or more thru holes **280**, each of which extends through the entire thickness of the adaptor ring **30**. Any number of thru holes **280** may be formed in any number of positions on the adaptor ring **30**, and in a preferred example, eight thru holes **280** are formed in equally spaced positions around the circumference of the adaptor ring **30**. Also, referring to FIG. 7B, a filter or wire mesh **285** is formed in a slot within the upper circumference of the adaptor ring **30** such that air may move freely between the void area **230** and the upper area of the blowout preventer **2** which holds the main seal **25**. In an example, the thru holes **280** and the filter or wire mesh **285** of the adaptor ring **30** allow the void area **230** to breathe freely thus preventing hydraulic lock which may result from pressure build-up within the void area **230**, while the filter or wire mesh **285** protects the void area **230** from wellbore debris.

[00051] FIG. 8 is a diagram illustrating a cross-sectional view of an example of the lower housing **10** including the upper gland assembly **245** and the cylindrical sleeve **250**. Referring to FIG. 8, the cylindrical sleeve **250** includes the annular piston **40** operating therein and the gland **45** attached at the bottom of the cylindrical sleeve **250**. The gland **45** includes the gland plug **60** and longitudinal gland channels **50** traversing an inner portion of the gland **45** for receiving hydraulic fluid pressure as described above.

[00052] Referring to FIG. 8, the annular piston **40** is connected to the energizing ring **215** by a piston rod **216** which includes a shoulder bolt **217** and a connector **218**. The shoulder bolt **217** is connected to the bottom of the energizing ring **215**, and the connector **218** is connected to the annular piston **40** by projecting therethrough and connecting to a corresponding retainer **222** on the opposite side. In this example, the connector **218** is threadedly engaged with the retainer **222**. A face seal **221** may be placed on the upper side of the annular piston **40** and around the connector **218**. Further, the upper gland assembly **245** includes a plurality of gland seals **85** within its outer and inner diameters for preventing intrusion of wellbore fluid and debris. The upper gland assembly **245** includes a plurality of fastening holes **246** for receiving fasteners and securing the upper gland assembly **245** into the lower housing **10**.

[00053] FIG. 9 is a diagram illustrating a cross-sectional view of an example of the lower housing **10** including an indicator/bleed port **290** and interconnecting holes **251**, and FIG. 9A is a diagram illustrating a magnified view of the indicator/bleed port **290**. The indicator/bleed port **290** may include an indicator **295** for determining conditions within the void area **230** such as pressure or temperature. In this example, the indicator **295** is a pressure indicator or bleed port for indicating to an operator the pressure within the void area **230**. Also, in an example, an operator may access the void area **230** through the indicator/bleed port **290** with a number of different tools.

[00054] FIG. 10 is a diagram illustrating a cross sectional view of the internal fluidly interconnected cylinders **160** and a removable piston cartridge **200** in a nearly removed position. Referring to FIG. 10, the removable piston cartridge **200** is a modular unit which includes the annular piston **40** and the cylindrical sleeve **250**. Also, the removable piston cartridge **200** may include the gland **45** at the bottom of the cylindrical sleeve **250** as shown in FIG. 8. The removable piston cartridge **200** may be sold and manufactured separately or together with the blowout preventer assembly **2**. Also, each of the components of the removable piston cartridge **200**, including the annular piston **40**, the cylindrical sleeve **250**, and gland **45**, may be sold and used as a modular unit together or separately.

[00055] The removable piston cartridge **200** may easily and quickly be removed from the fluidly interconnected cylinders **160** as a modular unit or in separate components. For example, an operator or a machine may first remove the bottom cover plate **65**. The gland plug **60** of the gland **45** may then be removed, and the gland **45** may subsequently be removed. An operator or machine may then loosen and remove retainer **222**, as shown in FIG. 8, for detaching the connector **218** from the piston **40**. The sleeve **250** including the piston **40** may then be removed from the fluidly interconnected channel **160** as illustrated in FIG. 10. In another example, each of the components, such as the cylindrical sleeve **250**, the annular piston **40**, and the gland **45** may be individually removed or replaced without removing or replacing the entire piston cartridge **200** as a modular unit.

[00056] Referring to FIGS. 9 and 10, the lower housing **10** includes inner-connection holes **251** which allow the interconnection of the fluidly interconnected cylinders **160**, and the

cylindrical sleeves **250** include corresponding connection holes **252** which allow the interconnection of the cylindrical sleeves **250**. In this example, the uniform actuation of the main seal **25** is ensured through the equal distribution of hydraulic fluid pressure formed between the interconnected cylindrical sleeves **250**. Accordingly, the operation of the annular piston **40** within the cylindrical sleeve **250** may be similar to the operations described above for the blowout preventer assembly **1**. Hydraulic fluid pressure is introduced through an open port **305** for pushing down the annular piston **40** and opening the main seal **25**, and hydraulic fluid pressure is introduced through a close port **310** for pushing up the annular piston **40** and closing the main seal **25**.

[00057] It should be appreciated by one of ordinary skill in the art that the dimensions of the cylindrical sleeve **250** may vary, but the cylindrical sleeve **250** should be sized to fit within the fluidly interconnected cylinders **160**. In an example, an inner diameter of a fluidly interconnected cylinder **160** is 9.5 inches, the outer diameter of the cylindrical sleeve **250** is 9.48 inches, the inner diameter of the cylindrical sleeve **250** is 8.12 inches, and the height of the cylindrical sleeve **250** is 14 inches. Nevertheless, it should be appreciated that a number of different dimensions may be used for any of the components of the blowout preventer assembly **1** and the blowout preventer assembly **2**, and the dimensions described herein are not limiting.

[00058] One of skill in the art will recognize that the embodiments described above are not limited to any particular size and the size of the blow out preventer and will depend upon the particular application and intended components. It will be appreciated by those skilled in the art that changes could be made to the embodiments described above without departing from the broad inventive concept thereof. It is understood, therefore, that the invention disclosed herein is not limited to the particular embodiments disclosed, and is intended to cover modifications within the spirit and scope of the present invention.

WHAT IS CLAIMED IS:

1. A blowout preventer, comprising:
 - an upper housing comprising an inner ceiling with a cavity configured to accommodate a main seal;
 - a lower housing comprising a plurality of internal fluidly interconnected cylinders;
 - a plurality of annular pistons and glands configured to be placed within the plurality of internal fluidly interconnected cylinders;
 - an energizing ring configured to be operated on by the annular pistons in order to operate the main seal, and disposed circumferentially within a void area of the lower housing; and
 - an upper gland assembly configured to isolate the plurality of internal fluidly interconnected cylinders from the void area of the lower housing.
2. The blowout preventer of claim 1, further comprising a plurality of cylindrical sleeves configured to be removably placed within the plurality of internal fluidly interconnected cylinders, each of the cylindrical sleeves configured to hold one of the plurality of annular pistons.
3. The blowout preventer of claim 1, further comprising an adaptor ring positioned between the concave shaped cavity of the upper housing and the void area of the lower housing, the adaptor ring comprising a wire mesh surrounding a circumference of the adaptor ring and a thru-hole extending through a thickness of the adaptor ring.

4. The blowout preventer of claim 1, further comprising an indicator port for determining a pressure level within the void area.

5. The blowout preventer of claim 1, wherein the plurality of internal fluidly interconnected cylinders each comprises a dedicated cylinder fluid channel disposed within a portion therein, wherein the cylinder fluid channel permits hydraulic fluid interconnectivity of each of the plurality of internal fluidly interconnected cylinders.

6. The blowout preventer of claim 2, wherein the plurality of internal fluidly interconnected cylinders each comprises a dedicated cylinder fluid channel disposed within a portion therein, and the plurality of cylindrical sleeves comprises one or more corresponding connecting holes disposed therein for permitting hydraulic fluid interconnectivity of each of the plurality of internal fluidly interconnected cylinders and each of the plurality of cylindrical sleeves.

7. The blowout preventer of claim 1, wherein the lower housing comprises an open port and a close port for accommodating hydraulic connections for providing and relieving hydraulic fluid to cause the annular pistons to force the energizing ring in a direction to open or close the main seal.

8. The blowout preventer of claim 7, wherein hydraulic fluid flows through the close port to the gland, wherein each gland further comprises a plurality of longitudinal gland channels traversing the diameter of the gland and a circumferential channel about the circumference of the

gland, wherein each of the longitudinal gland channels and the circumferential channels combine in design and function to accommodate the hydraulic fluid flow to responsively effectuate movement of the piston and energizing ring in a direction to cause the seal to close.

9. The blowout preventer assembly of claim 2, wherein each of the plurality of cylindrical sleeves has a first inner diameter for properly accommodating an outer diameter of each of the annular pistons and a second larger inner diameter for accommodating an outer diameter of each of the glands, such that the juncture of the first inner diameter and the second inner diameter form a stop lip.

10. The blowout preventer assembly of claim 9, wherein each of the glands is positionally retained within a distal portion of each of the plurality of cylindrical sleeves by the stop lip.

11. The blowout preventer assembly of claim 1, further comprising a piston rod for connecting the energizing ring to one of the plurality of annular pistons, wherein the upper gland assembly comprises a hole for receiving the piston rod.

12. A blowout preventer, comprising:
a housing comprising a plurality of fluidly interconnected cylinders formed therein;
a main seal positioned within the housing;
a plurality of cylindrical sleeves removably placed within the plurality of fluidly interconnected cylinders;

a plurality of annular pistons and glands configured to be placed within the plurality of cylindrical sleeves; and

an energizing ring configured to be operated on by the annular pistons in order to operate the main seal.

13. The blowout preventer of claim 12, further comprising an upper gland assembly, wherein the energizing ring is disposed circumferentially within a void area of the housing, and the upper gland assembly is configured to isolate the plurality of internal fluidly interconnected cylinders from the void area of the lower housing.

14. The blowout preventer of claim 12, wherein the housing comprises a plurality of connecting holes formed between the plurality of fluidly interconnected cylinders, and the plurality of cylindrical sleeves comprise a plurality of corresponding holes which correspond to the plurality of connecting holes, the plurality of connecting holes and the plurality of corresponding holes interacting together to provide fluid interconnectivity of all of the plurality of fluidly interconnected cylinders and all of the plurality of cylindrical sleeves.

15. A piston cartridge configured to be used in a blowout preventer, comprising:
a cylindrical sleeve forming the outer wall of the piston cartridge;
an annular piston placed within the cylindrical sleeve; and
a gland retained on a distal portion of the piston cartridge,
wherein the annular piston comprises a hole configured to receive a piston rod.

16. The piston cartridge of claim 15, further comprising connecting holes formed within the cylindrical sleeve for allowing the fluid interconnectivity of the piston cartridge with an internal environment of the blowout preventer.

17. The piston cartridge of claim 15, further comprising a retainer for securing the annular piston to the piston rod, wherein in response to removing the retainer, the piston cartridge is detachable from the piston rod.

18. A method of using a blowout preventer, comprising:
providing a piston cartridge, comprising a cylindrical sleeve, an annular piston, and a gland, into a cavity formed within the blowout preventer;
connecting a piston rod of the blowout preventer to a hole formed within the annular piston of the piston cartridge; and
covering the cavity of the blowout preventer using a bottom cover plate.

19. The method of claim 18, further comprising removing the piston cartridge, wherein the removing the piston cartridge comprises:
removing the bottom cover plate;
removing the gland;
detaching a retainer holding the piston rod within the hole of the annular piston in order to detach the annular piston from the piston rod;
simultaneously removing the cylindrical sleeve and the annular piston.

20. The method of claim 19, wherein the removing of the piston cartridge is performed in order to replace or refurbish the piston cartridge, or in order to rework the cavity of the blowout preventer.