

25 JUL 2000

PLACEMENT SYSTEM APPARATUS AND METHOD

FIELD OF THE INVENTION

This invention relates to an apparatus and method for the placement elements
5 on a surface, and in particular, but not exclusively to an apparatus and method for
placing solder balls and flux droplets on a ball grid array (BGA) substrate in the
mounting process of integrated circuit components.

BACKGROUND OF THE INVENTION

10 BGA techniques have become more common in recent years for connecting
high-density IC components onto circuit boards. A regular array of fluxed solder balls
is deposited on the circuit board at points where the leads of an IC component may be
desired to be connected. An IC component may then be mounted on the board and
connections are made between the leads of the component and the solder balls
15 contacted by those leads.

To achieve this end, in a ball grid array technique droplets of flux and solder
balls must be transferred to a substrate where they are deposited in a predetermined
array. A common technique is to use a ball pick head. The ball pick head is used for
transferring the solder balls to the substrate and is designed to carry the balls in the
20 same array configuration as is required on the substrate and then subsequently to
deposit the balls on the substrate. It is important, indeed essential, that all locations on
the circuit board intended to be provided with a solder ball are so provided, since
otherwise if a solder ball is missing a IC component lead may not be properly
connected to the board and the entire circuit board may be useless. Conventionally the
25 ball pick head is formed with a plurality of locations for receiving solder balls, these
locations being disposed in the same array configuration as the desired configuration
of solder balls on the circuit board. A corresponding flux head is used for depositing
flux droplets on the array locations of the substrate.

While such techniques are generally effective, they present a number of
30 challenges to the design of fast and efficient apparatus for the placement of solder
balls and flux droplets in the context of a real-life production system. The apparatus
must be designed so that the ball pick head and the flux head are brought in turn to a
position over the substrate, and since the dimensions of the array and in particular the
spacing between solder ball locations on the array is small, accurate alignment

techniques must be employed. The need in a production process to transfer BGA substrates between locations, and to accurately align ball and flux pick heads over the substrate, presents challenges to the design of a fast and efficient apparatus.

5

SUMMARY OF THE INVENTION

According to the invention there is provided apparatus for placing at least two elements on a surface, comprising:

- (a) means for supplying a said surface, said supplying means being adapted to move in a first direction,
 - 10 (b) first transferring means for transferring a said first element to said surface,
 - (c) second transferring means for transferring a said second element to said surface,
 - (d) means provided on at least one of said transferring means for recognising and detecting the position of alignment marks on said surface,
 - 15 (e) means for adjusting the position of said first and second transferring means relative to said surface in response to the position of said alignment marks,
- wherein said first and second transferring means are fixed together at a single position in said first direction and means are provided to move said first and second transferring means independently of each other in a second direction transverse to said
- 20 first direction.

In a preferred embodiment of the invention said first and second transferring means are moved in said second direction to a position over said surface, and means are provided for moving said first and second transferring means in a third direction normal to the said surface. Preferably each said transferring means is provided with a

25 respective recognising means, and means are provided to move each said recognising means with respect to each said transferring means in said first direction. Each said recognising means may comprise a camera assembly.

Preferably each said transferring means is provided with a respective recognising means, and means are provided to move each said recognising means

30 with respect to each said transferring means in said first direction. Additionally, preferably means are provided for adjusting the position of the surface in the first direction

Each said transferring means may be adapted to move in the second direction between a first position in which said transferring means receives an element to be

placed, and a second position in which said transferring means is positioned above the surface. Each said transferring means may be adapted to transfer a plurality of elements, which elements may be disposed in a desired configuration. The apparatus is particularly suitable for transferring flux droplets and solder balls to a BGA substrate.

Viewed from another broad aspect the present invention provides apparatus for placing flux droplets and solder balls on a ball grid array substrate, comprising:

- (a) means for supplying and supporting said substrate, said supplying means being adapted to move in a first direction,
- 10 (b) first transferring means for transferring flux droplets to said surface,
- (c) second transferring means for transferring solder balls to said surface,
- (d) means provided on at least one of said transferring means for recognising and detecting the position of alignment marks on said substrate,
- (e) means for adjusting the position of said first and second transferring means relative to said substrate in response to the position said alignment marks,
- 15 wherein said first and second transferring means are fixed together at a single position in said first direction and means are provided to move said first and second transferring means independently of each other in a second direction transverse to said first direction, and
- 20 (f) means for adjusting the position of each said recognising means with respect to each said transferring means in said first direction.

Viewed from a still further broad aspect the present invention provides a method for placing at least two elements on a surface, comprising:

- (a) supplying a said surface in a first direction to a receiving position,
- 25 (b) transferring a said first element to said surface by moving a first transferring means in a second direction transverse to said first direction to overly said surface,
- (c) transferring a second element to said surface by moving a second transferring means in said second direction transverse to said first direction to overly said surface,
- 30 (d) recognising and detecting the position of alignment marks on said surface,
- (e) adjusting the position of said first and second transferring means relative to said surface in response to the position said alignment marks,

(f) moving said first transferring means in a third direction normal to said surface, and

(g) moving said second transferring means in said third direction normal to said surface.

5 Preferably the positions of the transferring means may be adjusted as required in the second direction and in a rotary direction about an axis parallel to said third direction. The position of the surface may be adjusted in the first direction.

 Preferably step (d) is performed by recognising means provided on at least one of the transferring means.

10 For example, the recognising means may be provided on only one of the transferring means and step (d) may be performed by moving one of said transferring means in said second direction until said recognising means provided on said transferring means identifies a first alignment mark on the surface, moving said one
15 said transferring means further in said second direction and moving said recognising means in said first direction relative to said transferring means until a second alignment mark is identified.

 Alternatively recognising means may be provided on both of the transferring means and step (d) may be performed by prepositioning in the first direction the recognising means formed on said first transferring means and moving said first
20 transferring means in the second direction until the recognising means of the first transferring means identifies a first alignment mark on the surface, and prepositioning in the first direction the recognising means formed on said second transferring means and moving said second transferring means in the second direction until the recognising means of the second transferring means identifies a second alignment
25 mark on the surface.

 This method is particularly suitable for placing solder balls and flux droplets on a BGA substrate.

BRIEF DESCRIPTION OF THE DRAWINGS

30 An embodiment of the invention will now be described by way of example and with reference to the accompanying drawings, in which:-

 Fig.1 is a perspective view of apparatus according to a first embodiment of the invention,

 Fig.2 is a plan view of the apparatus of Fig.1,

Fig.3 is a side view of the apparatus of Fig.1,

Fig.4 is a plan view of the apparatus of Fig.1 showing movement of the ball pick head,

5 Fig.5 is a plan view of the apparatus of Fig.1 showing movement of the flux pick head,

Fig.6 is a perspective view of the apparatus of Fig.1 showing the flux pick head located over the ball grid array substrate, and

Fig.7 is a perspective view similar to Fig.6 but showing the ball pick head located over the ball grid array substrate.

10

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

Referring firstly to Fig.1 there is shown an apparatus according to a preferred embodiment of the invention. The apparatus comprises as major components a BGA substrate support 1 for holding thereon a BGA substrate 2, ball pick head 3 and flux pick head 4. Support 1 is adapted to be driven along an X axis by a motor 5 so that the BGA substrate 2 can be moved along the X-axis. The X axis corresponds to the long axis of the generally rectangular BGA substrate 2.

20 Ball pick head 3 and flux pick head 4 are mounted on a common transverse member 6 which extends along a Y axis transverse to the X axis. The Y axis corresponds to the transverse short axis of the rectangular BGA substrate 2. The heads 3,4 are each adapted to move back and forth along the transverse member 6 in the direction of the Y axis by means of respective Y axis motors. Ball pick head Y axis motor 7 is shown in Fig.1, the corresponding Y axis motor 8 for the flux pick head is shown in Fig.2 but cannot be seen in Fig.1.

25 Ball pick head 3 and flux pick head 4 are also both adapted to be moved in a Z direction by respective Z axis motors 9,10 such that the pick heads 3,4 can be raised and lowered with respect to the BGA substrate 2. Finally, both pick heads 3,4 are also adapted to be rotated about a theta axis by respective theta axis motors 11,12 which act to rotate the pick heads 3,4 through the theta axis as shown by the arrows in Fig.1 through gearing (not shown). Ball pick head 3 and flux pick head 4 are also each provided with a respective camera 13,14 directed towards the BGA substrate 2. Cameras 13,14 are adapted to move along the X-axis with respect to their respective pick heads 3,4. Cameras 13,14 are used for alignment purposes as will be described

30

below. The operation of the apparatus of the preferred embodiment of the invention will now be described.

Before placement of the flux droplets and solder balls on the BGA substrate 2, cameras 13,14 are used in alignment technique to align the pick heads 3,4 over the substrate 2. One way of achieving this is shown in Figs.2 and 3. The BGA substrate 2 is provided with a pair of alignment marks^{1,5} at diagonally opposed corners of the substrate 2. One of the pick heads 3,4 is moved into a position such that the respective camera on that pick head recognizes an alignment mark provided on the substrate 2. The camera then moves along the X axis and the pick head is moved along the Y axis until the camera recognizes the second alignment mark. Once the camera has recognized both alignment marks the position of the substrate can be calculated and the pick heads can be aligned with the substrate by making any necessary adjustments in the Y and theta axes.

An alternative alignment technique is for one of the pick heads 3,4 to move in the Y-direction and for its associated camera 13,14 to be pre-positioned in the X-direction such that the camera assembly 13,14 is able to recognise the corresponding alignment mark on the substrate. Simultaneously, or after the recognition of the first alignment mark, the other of the heads 3,4 is moved in the Y-direction with its associated camera 13,14 being pre-positioned in the X-direction to recognise the second alignment mark. In this way the alignment process is split between the two pick heads 3,4 each of which recognizes one of the two alignment marks. Based on the information from the two cameras 13,14 the position of the substrate with respect to the heads can be calculated. This alternative technique has the advantage that the travelling time and distance of the two camera assemblies 13,14 is reduced because they are prepositioned in the X-direction. This pre-positioning in the X-direction is possible because the location of the alignment marks on the same type of BGA substrate should be very close from one substrate to another.

The sequence of operation will now be described with reference to Figs.4 to 7. Referring firstly to Fig.4, the ball pick head 3 moves to a position in the Y-direction such that its associated camera 13 is directly above the first alignment mark of the BGA substrate. Before this movement of the ball pick head 3 the camera 13 of the ball pick head 3 will have been prepositioned in the X-direction so that it is aligned in the X-direction with the first alignment mark. The camera assembly 13 will then

recognize the first alignment mark and will supply position information of that alignment mark to a control apparatus (not shown).

The ball pick head 3 is then moved in the Y-direction away from the BGA substrate 2 to a ball supply unit 20 where the ball pick head 3 collects a supply of solder balls in any manner conventional in the art and which need not be described here.

While the ball pick head 3 is collecting solder balls from the ball supply unit 20, the flux pick head 4 bearing flux droplets moves (Fig.5) in the Y-direction to a position directly above the BGA substrate 2 such that the flux pick head camera 14 is located directly over the second alignment mark. Before this movement in the Y-direction the camera 14 has been prepositioned in the X-axis to correspond with the second alignment mark. Once the second alignment mark has been recognized this information is passed to the control apparatus and together with the information from the ball pick head camera 13 the position of the substrate may be determined and thus the flux pick head 4 position can be adjusted in the Y-direction and θ direction and the substrate support can be adjusted in the X-direction if necessary so that the flux pick head 4 is in proper alignment above the substrate 2 (Fig.6). The flux pick head 4 is then lowered in the Z-direction to deposit flux droplets on the required positions on the BGA substrate.

Following deposition of flux droplets on the substrate 2, the flux pick head 4 is raised again and moved away from the substrate 2 in the Y-direction towards a flux station 21 where the flux pick head 3 receives further flux droplets in advance of the next cycle with a further BGA substrate. Meanwhile, as shown in Fig.7, the ball pick head 3 moves in the Y-direction from the ball supply station 20 to a position aligned with the BGA substrate 2 using the alignment information previously obtained by the alignment of the ball pick head in the θ direction and the substrate support in the X-direction. The ball pick head 3 is then lowered in the Z-direction to deposit the solder balls on the BGA substrate 2.

The final stage in the process cycle is that the ball pick head 3 is then raised again in the Z-direction. However, the ball pick head 3 does not then immediately move away. Instead the substrate 2 is moved in the X-direction to a further station for the supply of components to be mounted in the substrate, and a new substrate 2 is moved in its place ready for the supply of solder balls and flux droplets. Since the ball

pick head 3 is still in a position such that it is above the new substrate 2, the ball pick head may take the first alignment operation using camera 13 before it is moved away in the Y-direction to collect a supply of solder balls and the cycle starts again.

It will be seen that the present invention provides a number of advantages.

- 5 Firstly, the flux and solder ball transfer processes can both be preformed while the substrate is located on a single support, so that the cost of having separate supports for the two operations can be avoided. Secondly, the overall process cycle can be shortened by performing only one alignment operation for both the flux and solder ball supply operations. Thirdly, because the camera assemblies are able to move in the
- 10 X-direction when performing the alignment operation, the pick heads themselves do not need to move in the X-direction. Since the camera assemblies are much lighter than the pick heads, this simplifies the mechanism. Finally, because the substrate support is able to move in the X-direction when performing the positional adjustment using the alignment information obtained from the two cameras, the pick heads
- 15 themselves do not need to be able to move in the X-direction to perform the position adjustment. As a result the mechanism of the pick heads is further simplified.

- It should be noted that while the present invention is described above with reference to the placing of solder balls and flux droplets on a BGA substrate, the invention is not limited thereto and could applied to any situation where two sets of
- 20 elements or object must be located accurately on a surface, eg a surface mount system for placing IC and other components on a BGA or other semiconductor package.



CLAIMS

1. Apparatus for placing at least two elements on a surface, comprising:
 - (a) means for supplying a said surface, said supplying means being adapted to move in a first direction,
 - (b) first transferring means for transferring a said first element to said surface,
 - (c) second transferring means for transferring a said second element to said surface,
 - (d) means provided on at least one of said transferring means for recognising and detecting the position of alignment marks on said surface,
 - (e) means for adjusting the position of said first and second transferring means relative to said surface in response to the position of said alignment marks, wherein said first and second transferring means are fixed together at a single position in said first direction and means are provided to move said first and second transferring means independently of each other in a second direction transverse to said first direction.
2. Apparatus as claimed in claim 1 wherein said first and second transferring means are moved in said second direction to a position over said surface, and means are provided for moving said first and second transferring means in a third direction normal to the said surface.
3. Apparatus as claimed in claim 1 wherein each said transferring means is provided with a respective recognising means, and means are provided to move each said recognising means with respect to each said transferring means in said first direction.
4. Apparatus as claimed in claim 1 wherein each said recognising means comprises a camera assembly.
5. Apparatus as claimed in claim 1 wherein each said transferring means is provided with a respective recognising means, and means are provided to move each said recognising means with respect to each said transferring means in said first direction.



6. Apparatus as claimed in claim 1 wherein means are provided for adjusting the position of the surface in the first direction.
- 5 7. Apparatus as claimed in claim 1 wherein each said transferring means moves in said second direction between a first position in which said transferring means receives an element to be placed, and a second position in which said transferring means is positioned above said surface.
- 10 8. Apparatus as claimed in claim 1 wherein each said transferring means is adapted to transfer a plurality of elements.
9. Apparatus as claimed in claim 8 wherein said transferring means comprises means for transferring a plurality of said elements to said surface in a desired
15 configuration.
10. Apparatus as claimed in claim 9 wherein said first transferring means is adapted to transfer flux droplets and said second transferring means is adapted to transfer solder balls, and wherein said surface is a ball grid array substrate.
- 20 11. Apparatus for placing flux droplets and solder balls on a ball grid array substrate, comprising:
- (a) means for supplying and supporting said substrate, said supplying means being adapted to move in a first direction,
 - 25 (b) first transferring means for transferring flux droplets to said surface,
 - (c) second transferring means for transferring solder balls to said surface,
 - (d) means provided on at least one of said transferring means for recognising and detecting the position of alignment marks on said substrate,
 - (e) means for adjusting the position of said first and second transferring means
30 relative to said substrate in response to the position said alignment marks, wherein said first and second transferring means are fixed together at a single position in said first direction and means are provided to move said first and second transferring means independently of each other in a second direction transverse to said first direction, and



(f) means for adjusting the position of each said recognising means with respect to each said transferring means in said first direction.

12. A method for placing at least two elements on a surface, comprising:
- 5 (a) supplying a said surface in a first direction to a receiving position,
- (b) transferring a said first element to said surface by moving a first transferring means in a second direction transverse to said first direction to
- 10 overly said surface,
- (c) transferring a second element to said surface by moving a second transferring means in said second direction transverse to said first direction to
- 10 overly said surface,
- (d) recognising and detecting the position of alignment marks on said surface,
- (e) adjusting the position of said first and second transferring means relative to said surface in response to the position said alignment marks,
- 15 (f) moving said first transferring means in a third direction normal to said surface, and
- (g) moving said second transferring means in said third direction normal to said surface.
- 20 13. A method as claimed in claim 12 wherein the positions of said transferring means are adjusted as required in said second direction, and in a rotary direction about an axis parallel to said third direction.
14. A method as claimed in claim 13 wherein the position of said surface is
- 25 adjusted in said first direction.
15. A method as claimed in claim 12 wherein step (d) is performed by recognising means provided on at least one of said transferring means.
- 30 16. A method as claimed in claim 15 wherein step (d) is performed by the recognising means provided on one of the transferring means.
17. A method as claimed in claim 16 wherein said step (d) is performed by moving one of said transferring means in said second direction until said recognising



means provided on said transferring means identifies a first alignment mark on the surface, moving said one said transferring means further in said second direction and moving said recognising means in said first direction relative to said transferring means until a second alignment mark is identified.

5

18. A method as claimed in claim 12 wherein step (d) is performed by recognising means formed on both of said transferring means.

19. A method as claimed in claim 18 wherein step (d) is performed by
10 prepositioning in the first direction the recognising means formed on said first transferring means and moving said first transferring means in the second direction until the recognising means of the first transferring means identifies a first alignment mark on the surface, and prepositioning in the first direction the recognising means formed on said second transferring means and moving said second transferring means
15 in the second direction until the recognising means of the second transferring means identifies a second alignment mark on the surface.

20. A method as claimed in claim 12 wherein said method is a method for placing flux droplets and solder balls on a ball grid array substrate.

20

25

30