PRESSURE EQUALIZING A BALL VALVE THROUGH AN UPPER SEAL BYPASS

FIELD OF THE INVENTION

[0001] The field of this invention is an equalizing pressure feature for subterranean or downhole valves and more particularly a way to equalize trapped lower pressure in a ball or plug of a valve without having to run a tool in the valve.

BACKGROUND OF THE INVENTION

[0002] Downhole valves are used to isolate portions of the wellbore for a variety of reasons such as for safety systems or to allow building a long bottom hole assembly in the wellbore, to name a few examples. Such valves have featured a rotating ball with a bore through it that can be aligned or misaligned with the path through the tubing string where the valve is mounted. The ball is surrounded by a sliding cage that is operated by a hydraulic control system from the surface. One such design that features opposed pistons actuated by discrete control lines is illustrated in US Publication 2009/0184278. This design was concerned about a pressure imbalance on an operating piston and provided a passage through the piston with two check valves 64, 70 in series to allow pressure equalization across the actuating piston with the ball in the closed position.

[0003] What can happen in this type of a ball valve that has upper and lower seats against the ball in the closed position is that pressure from downhole can rise, which leads to a pressure differential between the passage inside the ball and the downhole pressure. This pressure differential can distort the ball and make it hard or impossible for the piston actuation system to operate the ball back into the open position. One way this was solved is described in a commonly assigned application 12/366,752 filed on February 6, 2009 and having the title Pressure Equalization Device for Downhole Tools. The solution described in this application was to use a tool that goes into the upper sleeve that hold a seat against the ball and separate the seat from the ball while providing pressure from the surface at the same time to equalize the pressure on the ball before trying to rotate it to the open position. The problem

with this technique was that it required a run into the well with coiled tubing, latching and shifting the upper sleeve and associated seat enough to give access into the ball for equalizing pressure. One of the downsides of this technique was that the pressure admitted to try to equalize the pressure in the ball could be high enough to unseat the lower seat from the ball so that the higher pressure below the ball would get to above the ball. This technique also took time which cost the operator money and required specialized equipment at the well location, which could be remote or offshore and add yet additional costs to the effort to operate the ball when subjected to high differential pressures that increases opening friction or could distort the ball enough to make it hard for the hydraulic system to rotate it.

[0004] In flapper type safety valves such as USP 5,564,502 the preferred method to get pressure equalization on a closed flapper was to simply apply tubing pressure on top of it to reduce the differential before using the control system to try to rotate the flapper. Of course, the flapper is built to rotate open with pressure applied above so that this technique did not equalize pressure around the flapper when it was closed but simply built up pressure above it when it was closed. Other equalizer valves mounted in the flapper were actuated by the hydraulic system moving down a flow tube that impacted the equalizing valve before the flapper was engaged by the flow tube as seen in USP 6,848,509 or 4,478,286.

[0005] Also relevant are US Publications 2001/0045285; 2009/0184278 and USP 4,130,166; 4,197,879; 4,288,165; 4,446,922; 5,865,246; 6,223,824; 6,708,946; 6,695,286 and 4,368,871.

[0006] The basic components of the valve of FIG. 1 are reviewed in more detail in US Publication 2008/0110632 whose description is fully incorporated by reference herein as though full set forth. The portions of such valve relevant to the understanding of the present invention will be reviewed below in sufficient detail and for completeness so as to fully understand the operation of the claimed invention. While the actuation system of the valve in FIG. 1 in the present case is somewhat different in that it uses mechanically operated rod pistons to move the ball cage, the remainder of the structure of the ball and the way it seals and turns are the same with the further exception

that the present invention is employed to equalize pressure as between the inside of the closed ball and the pressure below the ball by virtue of application of uphole pressure to accomplish a bypass of an uphole seal to achieve pressure equalization.

[0007] Those skilled in the art will better understand how pressure equalization is obtained before the ball is turned from a review of the detailed description of the preferred embodiment and the associated drawings while recognizing that the technique is by no means limited to downhole ball valves but can be used in a variety of tools where trapped pressure results in differentials that may damage the component to be moved or the actuating system for it if such differentials are not resolved before attempting to move the component. Those skilled in the art will further understand that the full scope of the invention is to be found in the appended claims.

SUMMARY OF THE INVENTION

[0008] A pressure equalizing system allows flow past an upper seal on a movable member downhole that in turn allows pressure to be delivered from uphole into what had previously been an isolated low pressure zone. The pressure differential across the member is equalized before attempting to move the member into another position. In the preferred embodiment the member is a ball in a ball valve for subterranean use.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 is a section view of a ball valve in the closed position and including the portion where the pressure equalizing feature is located;

[0010] FIG. 2 is a close up view of the valve of FIG. 1 showing the path for pressure equalizing with applied pressure from above; and

[0011] FIG. 3 is an alternative embodiment to the design of FIG. 2.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0012] FIG. 1 shows a multi-component housing **10** that holds a ball **12** pinned at pins **14** to a frame **16**. A cage **18** extends through the open frame **16** and is connected to the ball **12** offset from the center pivot pins **14** so that sliding the cage **18** in opposed directions results in 90 degree rotation of ball **12** between an open position and the illustrated closed position. A connecting rod assembly **20** is secured to cage **18** at connection location **22**. A shifting

tool (not shown) can engage the connecting rod assembly **20** to selectively move it back and forth to open or close the ball **12**.

[0013] A lower seat sleeve **24** has a seat **26** in which a seal **28** is located for contact with the ball **12**. The sleeve **24** is biased against the ball **12** by a spring that is not shown that is located on the housing **10** but further downhole. An upper seat sleeve **30** has a seat **32** in which a seal **34** is located for contact with the ball **12**. The biasing spring that is not shown pushes the assembly of the lower seat sleeve **24**, the ball **12** and its frame **16** and the upper seat sleeve **30** against housing component **36**. The cage **18** moves relatively to the frame **16** and over the frame **16** to operate the ball **12**. Seal **38** seals between the lower seat sleeve **24** and the housing **10**. Together seals **38** and **28** retain downhole pressure in higher pressure zone **40** from reaching the lower pressure zone **42**, which extends from below to above cage **18** and further encompasses the passage **44** inside the ball **12**. In the closed position pressure in zone **42** migrates into passage **44** around the pins **14**. Above the ball **12** the zone **42** is further defined by seal **34** located in the upper seat sleeve **30** as well as seal **46** shown in FIG. 2 and seal **48** around the pushrod assembly **20**. Accordingly, an uphole pressure zone **50** is defined by these seals. The present invention deals with a pressure imbalance where pressure in zone **40** goes up when the ball **12** is in the closed position and a lower pressure is trapped in zone **42** which includes the passage **44** inside the ball **12**. This pressure imbalance can increase opening friction or distort the ball **12** making it hard to rotate such that any attempt to rotate the ball **12** while under such a pressure imbalance can adversely affect the pushrod assembly **20** or its seal **48** or the ball **12** itself. The present invention allows pressure applied to zone **50** before rotating the ball **12** to get past seal **46** and into zone **42** which also includes the passage **44** in ball **12**. Different embodiments are presented in FIGS. 2 and 3 that are discussed below.

[0014] As seen in FIG. 2 the upper seat sleeve **30** has an external shoulder **52** that is biased by the spring previously described and not shown against shoulder **54** of housing component **36**. While shown apart in FIG. 2 for clarity of illustration of the flow path into zone **42** represented by arrows labeled **56** surfaces **52** and **54** will normally be touching but there is no seal

between them. To equalize pressure in zone **42** and include the flow passage **44** in the ball **12**, the pressure is built up in zone **50** generally from the surface with available equipment or pressure sources. Normally, the pressure in zone **42** acts on preferably metallic seal **46** between legs **58** and **60** to spread them apart to retain pressure in zone **42** thus preventing pressure communication from zone **42** into upper zone **50**. Keeping in mind that the objective is to cure the pressure imbalance between zones **42** and **40** by raising the pressure in zone **50** to a point of bypassing the seal **46** those skilled in the art will appreciate that the c-shaped ring seal **46** is configured to resist flow or pressure loss from zone **42** into zone **50** but is also able to permit flow and pressure migration when the pressure in zone **50** is raised substantially over the pressure in zone **42**. During normal operations some leakage from zone **50** into zone **42** is acceptable because the volume will be insignificant to affect the operation of the valve assembly. The seal **46** has a u-shaped cross-section and is a commercially available seal.

[0015] FIG. 3 is an alternative embodiment showing parts **30** and **36** having a small clearance **62** that is closed off by a seal **64** in a surrounding groove **66**. The equalization concept in FIG. 3 is the same as in FIG. 2. Pressure is introduced from zone **50** which typically will come from the surface. At a predetermined differential between zones **50** and **42** the seal **64** will be pushed further back into groove **66** and flow will bypass the seal **64** increasing the pressure in zone **42** to get it closer to the pressure in zone **40** so that the connecting rod assembly **20** can be safely operated with little to no risk of damage to the assembly **20** or its seal **48** or the ball **12** itself.

[0016] Those skilled in the art can appreciate that the disclosed modes of pressure equalization are cheaper and faster than running a tool into the valve assembly to provide access into zone **42** by physically shifting a part such as seat sleeve **30** to get seal **34** away from ball **12** so that pressure from the wellhead can then be applied to equalize zone **42** with zone **40**. In the present invention the housing does not need to be expensively machined for internal bypass passages that need one or more check valves which have small moving parts that also need protection from debris that may be in the well fluid. Instead, the mere creation of enough differential across a seal so that

flow and pressure can migrate from zone **50** into zone 4**2** gets the job done and the ball **12** can then be operated in the normal manner.

[0017] The above description is illustrative of the preferred embodiment and various alternatives and is not intended to embody the broadest scope of the invention, which is determined from the claims appended below, and properly given their full scope literally and equivalently.

I claim:

1. A pressure equalizing system for a subterranean tool operable from a surface through a tubing string, comprising:

a housing having a passage therethrough and a movable member operable in said passage to selectively close said passage while defining a downhole pressure zone and an uphole pressure zone, said zones separated by an intermediate pressure zone such that said movable member is subjected to a positive pressure differential of said lower zone with respect to said intermediate zone;

said upper and intermediate zones separated by at least one seal, whereupon pressure buildup in said upper zone said seal is bypassed as pressure is changed in said intermediate zone as flow from said upper zone into said intermediate zone brings said intermediate zone closer to the pressure in said lower zone to facilitate movement of said movable member to open said passage.

2. The system of claim **1**, wherein:

said seal is a resilient ring seal.

3. The system of claim **2**, wherein:

said seal has a circular cross section.

4. The system of claim **2**, wherein:

said seal is disposed in a groove and extends against an opposed sealing surface until pressure buildup in said upper zone moves said seal from said opposed sealing surface to allow pressure to build in said intermediate zone.

5. The system of claim **4**, wherein:

said movable member comprises a ball having a flow path therethrough and an upper seat sleeve and a lower seat sleeve in sealing contact with said ball in said passage on opposed sides of said ball;

said seal is disposed on an outer surface of said upper seat sleeve to selectively seal against said opposing sealing surface located on said housing.

6. The system of claim **5**, wherein:

said upper seat sleeve defining a clearance with respect to said housing in a path leading from said upper pressure zone to said seal with said

intermediate pressure zone accessible on the opposite side of said seal from said clearance.

7. The system of claim **1**, wherein:

said seal comprises a gapped cross-section defined by spaced legs.

8. The system of claim **7**, wherein:

said gap is oriented toward said intermediate pressure zone.

9. The system of claim **8**, wherein:

said movable member comprises a ball having a flow path therethrough and an upper seat sleeve and a lower seat sleeve in sealing contact with said ball in said passage on opposed sides of said ball;

said seal is disposed on an outer surface of said upper seat sleeve to selectively seal against said opposing sealing surface located on said housing.

10. The system of claim **9**, wherein:

said ball is operated by a rod having a rod seal around it to seal to said housing to separate said high and intermediate pressure zones.

11. The system of claim **10**, wherein:

said ball is operated to rotate in opposed directions to open and close said passage by a force applied to said rod.

12. The system of claim **9**, wherein:

said lower seat sleeve further comprises a lower sleeve seal against said housing to isolate said lower pressure zone from said intermediate pressure zone.

13. The system of claim **9**, wherein:

said lower seat sleeve comprises a lower seat with a resilient seal in said lower seat contacting said ball;

said upper seat sleeve comprises an upper seat with a resilient seal in said upper seat contacting said ball.

14. The system of claim **13**, wherein:

a frame pivotally supports said ball on an axis through its center, said frame retaining said seals on said upper and lower seats to said ball.

15. The system of claim **14**, wherein:

a cage is mounted through said frame and is connected to said ball off center from where said ball is pivotally supported by said frame such that axial movement of said cage rotates said ball.

16. The system of claim **15**, wherein:

said ball is operated by a rod connected to said cage;

said rod having a rod seal around it to seal to said housing to separate said high and intermediate pressure zones.

17. The system of claim **16**, wherein:

said ball is operated to rotate in opposed directions to open and close said passage by a force applied to said rod and transferred to said cage.

18. The system of claim **7**, wherein:

said seal is metallic.