

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 July 2004 (22.07.2004)

PCT

(10) International Publication Number
WO 2004/062038 A1

(51) International Patent Classification⁷: **H01R 4/24**
(21) International Application Number:
PCT/US2003/039826

(22) International Filing Date:
12 December 2003 (12.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/321,400 16 December 2002 (16.12.2002) US

(71) Applicant: **TYCO ELECTRONICS CORPORATION**
[US/US]; 2901 Fulling Mill Road, Middletown, PA 17057
(US).

(72) Inventors: **DENOVICH, Sam**; 2416 Wicklow Drive, Harrisburg, PA 17112 (US). **GREEN, Michael, Patrick**; 204 Fairway Drive, Mechanicsburg, PA 17055 (US). **MUIR, Sheldon, Easton**; 529 Foxridge Road, Greensboro, NC 27046 (US).

(74) Agents: **ARONOFF, Michael, J.** et al.; Tyco Technology Resources, Suite 140, 4550 New Linden Hill Road, Wilmington, DE 19808 (US).


(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

[Continued on next page]

(54) Title: PLUG AND BLOCK CONNECTOR SYSTEM FOR DIFFERENTIAL CONTACT PAIRS



(57) Abstract: A connector plug is provided including a plug body formed along a longitudinal axis and holding multiple contacts arranged in differential pairs. The channels extend along a vertical axis of the plug body and are perpendicular to the longitudinal axis. The channels are grouped in first differential pairs located on a common side of the longitudinal axis adjacent second differential pairs of channels being located on opposite sides of the longitudinal axis. The connector plug also includes a wire guide having a first end configured to join an end of the plug body. The wire guide has a second end configured to receive a cable containing twisted differential pairs of wires. The wire guide has guide slots that carry corresponding twisted differential pairs of wires. The second end has wire dress grooves extending from the guide slots to the channels. Each of the wire dress grooves receives a wire.

WO 2004/062038 A1



(48) Date of publication of this corrected version:

11 August 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(15) Information about Correction:

see PCT Gazette No. 32/2005 of 11 August 2005, Section II