

DESCRIPTION

[TITLE OF THE INVENTION] INK CARTRIDGE AND INK JET PRINTER

- 5 **[0001]** The present invention relates to an ink cartridge and an ink jet printer capable of printing on a print medium using ink supplied from the ink cartridge.

[BACKGROUND ART]

- 10 **[0002]** The ink cartridge detachably mountable to a receiver (cartridge mounting portion) of a main assembly of the ink jet printer is provided with a cartridge side interface portion connectable with an interface portion provided in a main assembly side of the printer (International Publication No. 2012 - 054050). In International Publication No. 2012 - 054050, there are provided an electrical contact, an ink supply opening (ink discharge opening, tube inserting opening), a
15 cartridge side locking portion as the cartridge side interface portion. As for the interface portion of the main assembly side of the printer, a receiver is provided with an electrical connecting portion electrically connectable with the electrical contact, an ink receiving tube to be inserted into the ink supply port, a locking mechanism of the main assembly side of the printer for engaging with the
20 cartridge side locking portion. When the ink cartridge is inserted into the receiver, the electrical contact of the ink cartridge is connected with the electrical connecting portion of the receiver, and the ink receiving tube of the receiver is inserted into the supply opening of the ink cartridge. In addition, the cartridge side locking portion is engaged with the locking portion of the main assembly
25 side of the printer, by which the ink cartridge is locked with the receiver. By this, the connection between the ink cartridge and the main assembly of the printer is completed.

[0003] As will be understood from Figures 6 - 9 of International Publication No. 2012 - 054050, the electrical contact is provided adjacent to a right-hand surface of a cartridge parallel with a cartridge mounting direction (Y axis direction).

The cartridge side locking portion for fixing the cartridge to the receiver is
5 provided on a cartridge bottom surface far from the electrical contact.

SUMMARY OF THE INVENTION:

[The problem to be solved by the invention]

[0004] The cartridge side interface portion disclosed in International
10 Publication No. 2012 - 054050 involves a point which can be improved. For example, in International Publication No. 2012 - 054050, the cartridge side locking portion is provided on the bottom surface which is relatively remoter from the electrical contact, and therefore, a positional deviation of the electrical contact may be large even if the locking position deviation provided by the
15 locking portion is small. Thus, in the prior art, the structures and arrangements of the parts in the cartridge side interface portion involves a point which can be improved.

[Means for solving the problem]

[0005] The present invention provides an ink cartridge mountable to a cartridge
20 mounting portion provided with an ink receiving tube, an electrical connecting portion and a locking lever, in a mounting direction crossing with a direction of gravity, said ink cartridge comprising a casing including an ink accommodating chamber configured to accommodate ink to be supplied to the ink receiving tube, said casing including a front surface at a leading side with respect to the
25 mounting direction, an upper surface and a bottom surface; a tube inserting portion into which the ink receiving tube is insertable and which is provided at said front surface in a position closer to said bottom surface than to said upper

surface; an electrical contact electrically connectable to the electrical connecting portion and provided in a position above said tube inserting portion, said electrical contact including an area crossing with the mounting direction; and an engaging portion provided in a position closer to said electrical contact than to said tube inserting portion, said engaging portion being engageable with the locking lever to maintain a inserted state in which the ink receiving tube is inserted in said tube inserting portion and a connected state in which said electrical contact is connected with the electrical connecting portion.

[Advantageous effect of the invention]

10 **[0006]** An improved ink cartridge is provided. In addition, a novel ink jet printer with which a satisfactory connection is accomplished between the ink cartridge and the cartridge mounting portion is provided.

[BRIEF DESCRIPTION OF THE DRAWINGS]

15 **[0007]**

Figure 1 illustrates a schematic structure of an ink jet printer.

Figure 2 is a perspective view of an outer appearance of the ink cartridge.

20 Figure 3 illustrates an outer appearance of a substrate of the ink cartridge.

Figure 4 is an exploded view of the ink cartridge.

Figure 5 illustrates a internal structure of the ink cartridge, in which a part (a) is a view of the ink cartridge as seen from a right-hand surface side along a X axis direction, and part (b) is a view of the ink cartridge as seen from a rear side along the Y axis direction.

Figure 6 is a perspective view illustrating a state before the ink cartridge is mounted to the mounting portion of a cartridge mounting unit.

Figure 7 is a perspective view illustrating a mounting completed state in which the ink cartridge has been mounted to the mounting portion of the cartridge mounting unit.

Figure 8 is a sectional view of the cartridge mounting unit.

5 Figure 9 is a perspective view illustrating a connection relation between the ink cartridge and a joint unit taken out of the cartridge mounting unit.

Figure 10 illustrates a process of insertion of the ink cartridge into the mounting portion, in which a part (a) shows an initial state of the insertion, and part (b) shows a completed state of the insertion.

10 Figure 11 is a schematic view of an ink cartridge 1BK applicable to a first embodiment of the present invention.

Figure 12 illustrates an example of a position of an electrode pad on the substrate.

15 Figure 13 illustrates an example of the arrangement and the mounting method of the substrate.

20 Figure 14 illustrates an internal structure of the ink cartridge applicable to a second embodiment of the present invention, in which part (a) is a view of the ink cartridge as seen from the right-hand surface side along the X axis direction, and part (b) is a view of the ink cartridge as seen from the rear side along the Y axis direction.

Figure 15 shows a process of inserting the ink cartridge into the mounting portion in the second embodiment, in which part (a) shows the initial state of the insertion, and part (b) shows a completed state of the insertion.

25 Figure 16 illustrates a schematic structure of the ink cartridge 1801 applicable to a third embodiment of the present invention, in which part (a) is a perspective view of an outer appearance of the ink cartridge 1801, and part (b) illustrates an internal structure of the ink cartridge 1801.

Figure 17 is a perspective view illustrating a connection relation between the ink cartridge 1801 and a joint unit 59 taken out of the cartridge mounting unit in the third embodiment.

Figure 18 illustrates a process of inserting the ink cartridge 1801 in the third embodiment, in which part (a) shows an initial state of the insertion, and
5 part (b) shows a completed state of the insertion.

Figure 19 is a schematic view illustrating an ink cartridge 1BK applicable in the third embodiment.

Figure 20 is a schematic view illustrating a schematic structure of the
10 ink cartridge 201 applicable in the fourth embodiment.

Figure 21 illustrates a schematic structure of the ink cartridge 301 applicable in a fifth embodiment, in which part (a) is a perspective view of an outer appearance of the ink cartridge 301, and part (b) shows an internal structure of the ink cartridge 301 as seen from the right-hand surface side along the X axis
15 direction.

Figure 22 illustrates a process of inserting the ink cartridge 301 in the fifth embodiment, in which part (a) shows an initial state of the insertion, and part (b) shows a completed state of the insertion.

Figure 23 illustrates a schematic structure of the ink cartridge 401
20 applicable in a sixth embodiment, in which part (a) is a perspective view of an outer appearance of the ink cartridge 401, and part (b) shows an internal structure of the ink cartridge 401 as seen from the right-hand surface side along the X axis direction.

Figure 24 illustrates a process of inserting the ink cartridge 401 in the sixth embodiment, in which part (a) shows an initial state of the insertion, and
25 part (b) shows a completed state of the insertion.

Figure 25 illustrates a schematic structure of the ink cartridge 501

applicable in a seventh embodiment, in which part (a) is a perspective view of an outer appearance of the ink cartridge 501, and part (b) shows an internal structure of the ink cartridge 501 as seen from the right-hand surface side along the X axis direction.

5 Figure 26 illustrates a process of inserting the ink cartridge 501 in the seventh embodiment, in which part (a) shows an initial state of the insertion, and part (b) shows a completed state of the insertion.

 Figure 27 illustrates a schematic structure of the ink cartridge 601 applicable in an eighth embodiment, in which part (a) is a perspective view of an
10 outer appearance of the ink cartridge 601, and part (b) shows an internal structure of the ink cartridge 601 as seen from the right-hand surface side along the X axis direction.

 Figure 28 illustrates a process of inserting the ink cartridge 601 in the eighth embodiment, in which part (a) shows an initial state of the insertion, and
15 part (b) shows a completed state of the insertion.

 Figure 29 illustrates a schematic structure of the ink cartridge 701 applicable in a ninth embodiment, in which part (a) is a perspective view of an
 outer appearance of the ink cartridge 701, and part (b) shows an internal structure of the ink cartridge 701 as seen from the right-hand surface side along the X axis
20 direction.

 Figure 30 illustrates a process of inserting the ink cartridge 701 in the ninth embodiment, in which part (a) shows an initial state of the insertion, and part (b) shows a completed state of the insertion.

 Figure 31 illustrates a schematic structure of the ink cartridge 801
25 applicable in a tenth embodiment, in which part (a) is a perspective view of an outer appearance of the ink cartridge 801, and part (b) shows an internal structure of the ink cartridge 701 as seen from the right-hand surface side along the X axis

direction.

Figure 32 illustrates a schematic structure of the ink cartridge 901 applicable in an eleventh embodiment, in which part (a) is a perspective view of an outer appearance of the ink cartridge 901, and part (b) shows an internal
5 structure of the ink cartridge 901 as seen from the right-hand surface side along the X axis direction.

Figure 33 illustrates a process of inserting the ink cartridge 901 in the eleventh embodiment, in which part (a) shows an initial state of the insertion, and part (b) shows a completed state of the insertion.

10 Figure 34 illustrates a schematic structure of the ink cartridge 10701 applicable in a twelfth embodiment, in which part (a) is a perspective view of an outer appearance of the ink cartridge 1001, and part (b) shows an internal structure of the ink cartridge 1001 as seen from the right-hand surface side along the X axis direction.

15 Figure 35 illustrates a process of inserting the ink cartridge 1001 in the twelfth embodiment, in which part (a) shows an initial state of the insertion, and part (b) shows a completed state of the insertion.

Figure 36 illustrates a schematic structure of the ink cartridge 1101 applicable in a fourteenth embodiment, in which part (a) is a perspective view of
20 an outer appearance of the ink cartridge 1101, and part (b) shows an internal structure of the ink cartridge 1101 as seen from the right-hand surface side along the X axis direction.

Figure 37 illustrates a schematic structure of the ink cartridge 1201 applicable in a thirteenth embodiment, in which part (a) is a perspective view of
25 an outer appearance of the ink cartridge 1201, and part (b) shows an internal structure of the ink cartridge 1201 as seen from the right-hand surface side along the X axis direction.

Figure 38 illustrates a schematic structure of the ink cartridge 1301 applicable in a fourteenth embodiment, in which part (a) is a perspective view of an outer appearance of the ink cartridge 1301, and part (b) shows an internal structure of the ink cartridge 1301 as seen from the right-hand surface side along the X axis direction.

Figure 39 illustrates a structure of a positioning portion applicable in a fifteenth embodiment.

Figure 40 illustrates a schematic structure of an ink cartridge applicable in a sixteenth embodiment, in which part (a) illustrates a second casing member 41 which is a constituent-element of a casing 2, and part (b) is a perspective view of an ink cartridge 1701 having the second casing member 41.

Figure 41 illustrates a schematic structure of an ink cartridge 1901 applicable in a seventeenth embodiment and shows a movement of the engaging portion 1924 in accordance with a movement of an engagement lever 1926.

Figure 42 illustrates a process of inserting the ink cartridge 1901 in the seventeenth embodiment, in which part (a) shows an initial state of the insertion, and part (b) shows a completed state of the insertion.

Figure 43 illustrates a schematic structure of ink cartridges 2001, 2101, 2201, 2301 applicable in an eighteenth embodiment.

[DESCRIPTION OF THE EMBODIMENTS]

[0008] An ink cartridge and an ink jet printer according to embodiments of the present invention will be described in detail in conjunction with accompanying drawings. The embodiments are preferable ones that implement the present invention which is not limited to these embodiments.

[0009]

[First embodiment]

<Ink jet printer>

Figure 1 illustrates a schematic structure of the ink jet printer as an image forming apparatus. Figure 1 shows a state in which an ink cartridge 1 as an ink reservoir is mounted on a main assembly of the printer (main assembly A)
5 30.

[0010] The printer main assembly 30 comprises a carriage 31, an ink jet head 32, a mounting portion 33, a feeding means 34, a controller 35 and an input/output portion 36, and in addition, an opening and closing outer cover, a feeding means, a feeding cassette, a discharging tray, an operating portion and so
10 on which are unshown. The printer main assembly 30 is connectable with an external device (unshown) such as a computer, a digital camera, a memory card or the like, through the input/output portion 36.

[0011] The controller 35 carries out overall control, control of information communication with the ink cartridge 1, analysis and processing of the
15 information inputted from the external device through the input/output portion 36, and outputting of information to the input/output portion 36. For example, the controller 35 produces instructions for actuating devices such as the carriage 31, the ink jet head 32, the feeding means 34 and the feeding means and for controlling the devices. In addition, the controller 35 can control the devices for
20 reading ink colors, initial ink filling amounts, ink consumption amounts and other individuality information of the cartridges out of a storing element provided in the ink cartridge 1, and for writing the information of the ink consumption amounts in the storing element provided in the ink cartridge 1. Furthermore, the controller 35 can analyze and process print instructions and/or image data
25 inputted through the input/output portion 36 from the external device, and can output the information such as the remaining ink amount to the input/output portion 36.

[0012] The carriage 31 is provided with a mounting portion (cartridge mounting portion or cartridge holder) 33 to which the ink jet head 32 and ink cartridge 1 are detachably mountable. In this embodiment, a head unit (cartridge mounting unit) 38 integrally including the ink jet head 32 and the mounting portion 33 is
5 detachably mounted to the carriage 31, as shown in Figure 6 and Figure 8 which will be described hereinafter. The carriage 31 is movable along an X axis direction which is perpendicular to a feeding direction of a print medium 37.

[0013] On the mounting portion 33 of the carriage 31, ink cartridges 1C, 1Bk, 1M, 1Y containing cyan (C) ink, black (Bk) ink, magenta (M) ink and yellow (Y) ink, respectively can be detachably mounted. The ink cartridge 1Bk has a larger
10 capacity than those of the other three ink cartridges 1C, 1M, 1Y. In addition, the ink jet head 32 is provided with respective color head portions for ejecting the cyan (C), black (Bk), magenta (M) and yellow (Y) inks supplied from the ink cartridges 1.

[0014] When a user mounts and dismounts or exchanges the ink cartridge 1 relative to such a carriage 31, the user opens the outer cover (unshown) covering the carriage 31 and the feeding means 34. When the printer main assembly detects the opening state of the outer cover, the carriage 31 moves to a cartridge exchange position (unshown). The user can insert the ink cartridge 1 into the
15 carriage 31 placed in the cartridge exchange position, and can take the ink cartridge 1 out of the carriage 31 placed in the cartridge exchange position.

[0015] After the mounting and dismounting or the exchange of the ink cartridge 1, the user closes the outer cover, and then the closed state of the outer casing is detected. When the closed state is detected, the controller 35 of the printer main
20 assembly reads the ink color information from the storing element of the ink cartridge 1 mounted to the carriage 31. The controller 35 discriminates whether or not the ink cartridges for all colors (four colors in this example) to be mounted

to the carriage 31 are mounted, on the basis of the read ink color information. If the result of the discrimination indicates that an ink cartridge for a particular color is not mounted to the carriage 31, the controller 35 produces error display instructions to the operating portion and/or the external device to display an error message on the display panel of the operating portion (unshown) and/or the display portion of the external device (unshown). On the other hand, if the result of discrimination indicates that all the color ink cartridges to be mounted are mounted to the carriage 31, the ink jet printer becomes operable for printing.

[0016] When the print instructions is inputted to the controller 35 from the external device (unshown) or the operating portion (unshown), the controller 35 discriminates whether or not the printer is in the operable state. If it is in the operable state, the feeding means (unshown) picks up the print medium 37 stacked in the feeding cassette (unshown) and feeds the picked-up print medium 37 toward the feeding means 34. The feeding means 34 is provided with a platen for supporting the print medium at the bottom surface thereof, a feeding roller capable of intermittently feeding the print medium, driving means for rotating the feeding roller and so on, and feeds the print medium 37 toward the discharging tray (unshown). In the period between adjacent the feeding operations for the print medium 37, the carriage 31 moves above the print medium along the X axis direction perpendicular to the feeding direction of the print medium 37. During the movement of the carriage 31, the inks are ejected toward the print medium 37 from the ink jet head 32, so that an image is formed on the print medium. In this manner, an image is formed on the print medium by the repetition of the carriage movement and the print medium feeding.

[0017] In this embodiment, the head unit (cartridge mounting unit) 38 is detachably mounted to the carriage 31, but the present invention is not limited to such a structure. The ink jet head 32 and the mounting portion 33 may be

detachably mounted to the carriage 31, individually. In addition, the mounting portion 33 may be integral with the carriage 31, and only the ink jet head 32 may be detachably mounted to the carriage 31. Furthermore, both of the ink jet head 32 and the mounting portion 33 may be integral with the carriage 31. It will suffice if the carriage 31 is capable of mounting the ink jet head 32, and the ink cartridge 1 is mountable and dismountable thereto.

[0018]

<Ink cartridge>

Referring to Figures 2 - 5, an example of the ink cartridge usable with the ink jet printer of Figure 1 will be described. The four ink cartridges 1C, 1Bk, 1M, 1Y of this embodiment have the same fundamental structures with the exception that the kinds of the inks therein, the cartridge widths (the cartridge for the black color is wider than the other color cartridges) and the discrimination portions 9 which will be described hereinafter are different. Therefore, an ink cartridge 1M will be taken as a representative ink cartridge in the following description.

[0019]Figure 2 is a perspective view illustrating an outer appearance of the ink cartridge 1M according to a first embodiment. Figure 3 illustrates an outer appearance of a substrate provided on the ink cartridge of Figure 2, in which part (a) is a front view, and part (b) is a side view. Figure 4 is an exploded view of the ink cartridge of Figure 2. Figure 5 illustrates an internal structure of the ink cartridge of Figure 2, in which part (a) is a view of the ink cartridge as seen from a right-hand surface side along the X axis direction, and part (b) is a view of the ink cartridge as seen from the rear side along the Y axis direction.

[0020]

(Casing)

As shown in Figures 2, 4 and 5, the ink cartridge 1 as the ink reservoir

includes a casing (main assembly of the cartridge or container body) 2 of rectangular parallelepiped shape having an inside ink accommodating chamber 11.

[0021] The casing 2 comprises an upper surface 2a which is an outer wall surface of an upper wall thereof, a lower surface (bottom surface) 2b which is an outer wall surface of a lower wall (bottom wall) thereof, a plurality of side surfaces 2c - 2f which are outer wall surfaces of side walls connecting the upper wall and the lower wall with each other. These upper wall, the upper surface, the bottom wall, the bottom surface, the plurality of side walls and the plurality of side surfaces are defined on the basis of the orientation (attitude) of the ink cartridge at the time when the ink cartridge is mounted to the mounting portion, that is, on the basis of the state in use.

[0022] The plurality of the side surfaces include a front surface (front side) 2c which is a first side surface, a rear surface (rear side) 2d which is a second side surface, a left surface 2e which is a third side surface connecting the first side surface and the second side surface with each other, and a right-hand surface 2f which is a fourth side surface connecting the first side surface and the second side surface with each other. The front surface 2c is on the leading side with respect to the mounting direction of the ink cartridge. The rear surface (rear side) 2d is on the trailing side with respect to the mounting direction of the ink cartridge and is at the opposite side of the front surface 2c across the ink accommodating chamber 11. The left surface 2e is on the left side as the ink cartridge is seen from a front side. The right-hand surface 2f is on the right side as the ink cartridge is seen from the front side and is at the opposite side of the left surface 2e across the ink accommodating chamber 11.

[0023] In this embodiment, the casing 2 is substantially in the form of a rectangular parallelepiped including six major surfaces or sides. The left surface

2e and the right-hand surface 2f of the six surfaces have the maximum area, and the front surface (front side) 2c and the rear surface 2d have the minimum area. The size relationships are the front surface 2c and the rear surface 2d < the upper surface 2a; and the lower surface (bottom surface) 2b < the left surface 2e and the right-hand surface 2f.

[0024] In this embodiment, the sizes of the casing 2 are approx. 4.7 cm in height (measured in the Z axis direction), approx. 8.4 cm in the depth (measured in the Y axis direction), and approx. 1.6 mm in the width (measured in the X axis direction). Therefore, an area of the left surface 2e (and the right-hand surface 2f) is approx. 39.48 ($=4.7 \times 8.4$) cm². The area of the upper surface 2a (and the lower surface 2b) is approx. 13.44 ($=1.6 \times 8.4$) cm². The area of the front surface (front side) 2c (and the rear surface (rear side)) is approx. 7.52 ($=1.6 \times 4.7$) cm². The specific sizes of the height, the depth and the width are merely examples, and the sizes of the casing 2 of this embodiment are not limited to these examples.

[0025] Here, the first side wall having the first side surface which is the front surface 2c is called "front wall", the second side wall having the second side surface which is the rear surface 2d is called "rear wall", the third side wall having the third side surface which is the left surface 2e is called "left-hand wall" or "left wall", and the fourth side wall having the fourth side surface which is the right-hand surface 2f is called "right-hand wall". The front wall and the rear wall are opposed to each other across the ink accommodating chamber 11, and the left-hand wall and the right-hand wall are opposed to each other across the ink accommodating chamber 11.

[0026] In Figure 2, the X axis direction is a widthwise direction of the ink cartridge 1, and is a moving direction of the ink cartridge 1 (moving direction of the carriage) in the state that the ink cartridge 1 is mounted on the carriage. The

widthwise direction is in the direction from the right-hand surface 2f of the casing 2 toward the left surface 2e thereof. The Y axis direction is the depth direction of the ink cartridge, and is the mounting direction (inserting direction) and a dismounting direction (removing direction) of the cartridge. The depth direction
 5 is the direction from the front surface 2c of the casing 2 toward the rear surface 2d thereof. The Z axis direction is the height direction of the ink cartridge, and is the direction perpendicular to the X axis direction and to the Y axis direction. The height direction is the direction from the lower surface 2b of the casing 2 toward the upper surface 2a thereof. A θ_x direction is a rotational moving
 10 direction about the X axis, a θ_y direction is a rotational moving direction about the Y axis, and a θ_z direction is a rotational moving direction about the Z axis.

[0027] In this embodiment, the casing has the rectangular parallelepiped shape, and therefore, the X axis direction is perpendicular to the left surface 2e and the right-hand surface 2f, and the Y axis direction is perpendicular to the front
 15 surface (front side) and to the rear surface 2d, and the Z axis direction is perpendicular to the upper surface 2a and to the lower surface (bottom surface) 2b.

[0028] However, as will be described hereinafter, the configuration of the casing usable with this embodiment is not limited to the rectangular
 20 parallelepiped shape, and all or a part of the surfaces constituting the casing may be curved surface or inclined surface, for example. When the all or a part of the surface is a curved surface or an inclined surface, the X axis, the Y axis and the Z axis are not necessarily perpendicular to one another.

[0029]

25 (Cartridge side interface portion)

As shown in Figures 2, 4 and 5, the front surface 2c of the casing is provided thereon with a substrate 3 having electrical contacts 4, a positioning

hole 6 as a positioning portion, a through-opening 27 as a penetrated portion, a tube inserting opening 8 as a tube inserting portion, and a discrimination portion 9. The electrical contact 4, the positioning hole 6, the through-opening 27, the tube inserting opening 8 and the discrimination portion 9 function as the cartridge side interface portion which are connected with or engaged with a printer main assembly side interface portion provided in the mounting portion 33.

[0030] The electrical contact 4, the positioning hole 6, the through-opening 27, the tube inserting opening 8 and the discrimination portion 9 are connected with or engaged with an electrical connecting portion 55, a positioning pin 53, an unsealing pin 51, an ink receiving tube 52 and a discrimination member 60 of the printer main assembly side interface portion, respectively. The details of the structures of the printer main assembly side interface portion will be described hereinafter in conjunction with Figure 8, Figure 9 and so on.

[0031] The structure of the ink cartridge, particularly the cartridge side interface portion will be described.

[0032] As shown in Figures 2, 4 and 5, the tube inserting opening 8 is disposed adjacent to the bottom side which is a lower portion (a portion closer to the bottom surface 2b than to the upper surface 2a) of the front surface 2c of the casing 2. The tube inserting opening 8 is disposed at one end portion of a tube insertion path 22, and the other end portion of the tube insertion path 22 is connected to the ink accommodating chamber 11. The tube insertion path 22 extends from one end portion to the other end portion along a cartridge depth direction (direction parallel with a normal line of a surface defining the tube inserting opening 8 or Y axis direction). In the example shown in Figure 5, the entire portion of the hollow path from the one end portion to the other end portion extends along the cartridge depth direction (direction parallel with a normal line of a surface defining the tube inserting opening 8 or Y axis direction), but this

embodiment is not limited to such an example. It will suffice if the tube insertion path 22 is capable of receiving the ink receiving tube 52 extending along the Y axis direction. For example, a hollow extending portion extending along the cartridge depth direction from the one end portion having the tube inserting opening 8 is provided only in a part of the tube insertion path 22.

[0033] As shown in Figures 4 and 5, the tube insertion path 22 is provided with a sealing member 19 as an elastic member. At a rear side end portion of the sealing member 19 (the side closer to the ink accommodating chamber 11 than the tube inserting opening 8), an opening and closing slit is provided, and the slit is closed when the ink receiving tube 52 is not inserted. In the state that the slit is closed, the tube inserting opening 8 and the ink accommodating chamber 11 are in non-fluid-communication state relative to each other. When the ink reception tube 52 is inserted into the tube insertion path 22, the slit is expanded to open, so that a fluid communication state is established between the ink reception tube 52 and the ink accommodating chamber 11, and an inner surface of the sealing member 19 elastically contacts to an outer peripheral surface of the ink receiving tube 52 to prevent leakage of the ink. By the insertion of the ink receiving tube 52 into the tube insertion path 22, the ink in the ink accommodating chamber 11 can be supplied into the ink receiving tube 52.

[0034] In the ink cartridge mounted state, the ink reception tube 52 is in the tube inserting opening 8, and therefore, the movement of the casing 2 is limited in the direction perpendicular to the cartridge mounting direction (X axis direction and Z axis direction, for example, which are along the front surface 2c). That is, the tube inserting opening 8 as the tube inserting portion functions also to suppress a positional deviation in a plane of the front surface 2c.

[0035] In this embodiment, a tube inserting opening (opening) is employed as the tube inserting portion, but the tube inserting portion is not limited to an

opening. It will suffice if the tube inserting portion 8 permits the insertion of the ink receiving tube 52, and therefore, it is not necessarily open in the state prior to the insertion of the ink receiving tube 52. For example, the tube inserting portion 8 may be closed when the ink receiving tube 52 is not inserted, but is
 5 open only when the ink receiving tube 52 is inserted.

[0036] From the standpoint of the functions, the tube insertion path, the tube inserting opening and the tube inserting portion can be called as follows. For example, the tube insertion path 22 is a portion for receiving the ink receiving tube 52, and therefore, it can be called "tube receiving path". The tube inserting
 10 opening 8 is positioned at one end portion of the tube receiving path and functions to receive the ink receiving tube 52, and therefore, it can be called "tube receiving opening". The tube inserting portion 8 is positioned at one end portion of the tube receiving path and functions to receives the ink receiving tube 52, and therefore, it can be called "tube receiving portion".

[0037] From the standpoint of the functions, the tube insertion path, the tube inserting opening and the tube inserting portion can be called as follows. For example, the tube insertion path 22 functions to supply the ink from the inside of the ink accommodating chamber 11 to an outside (ink receiving tube 52) of the cartridge, and therefore, it can be called "ink supply path". The tube inserting
 20 opening 8 is positioned at one end portion of the ink supply passage and functions to supply the ink from the inside of the ink accommodating chamber 11 to an outside (ink receiving tube 52), and therefore, it can be called "ink supply opening". The tube inserting portion 8 is positioned at one end portion of the ink supply passage and functions to supply the ink from the inside of the ink
 25 accommodating chamber 11 to an outside of the cartridge (ink receiving tube 52), and therefore, it can be called "ink supplying portion".

[0038] From the standpoint of the functions, the tube insertion path, the tube

inserting opening and the tube inserting portion can be called as follows. For example, the tube insertion path 22 is a discharging path capable of discharging the ink from the inside of the ink accommodating chamber 11 to an outside of the cartridge, and therefore, it can be called "ink discharging path". The tube inserting opening 8 is positioned at one end portion of the ink discharging path and is an opening capable of discharging the ink from the inside of the ink accommodating chamber 11 to an outside of the cartridge, and therefore, it can be called "ink discharge opening". The tube inserting portion 8 is positioned at the one end portion of the ink discharging path and is a portion capable of discharging the ink from the inside of the ink accommodating chamber 11 to a outside of the cartridge, and therefore, it can be called "ink discharging portion".

[0039] As shown in part (a) of Figure 5, in the state before the ink cartridge 1 is mounted to the mounting portion 33, that is, in the unused state of the ink cartridge 1, a sealing film 18 as a sealing member is mounted on the portion around the tube inserting opening 8 to cover the tube inserting opening 8. The sealing film 18 (tube inserting opening sealing film, supply opening sealing film or tube reception opening sealing film) functions as ink leakage preventing means for preventing ink leakage before the start of use of the cartridge, that is, during transportation or the like. The sealing film 18 is pierced by the ink receiving tube 52 when the ink cartridge 1 is mounted.

[0040] The substrate 3 provided with an electrode pad as an electrical contact (cartridge side electrical contact) 4 is provided in a position above the supply opening 8 on the front surface 2c of the casing 2, more particularly, in the neighborhood of the upper surface 2a. As shown in Figure 3, the substrate 3 is provided on the front surface thereof with a plurality of electrical contacts 4 and is provided on the back side thereof with a storing element 5. The electrical contact 4 and the storing element 5 are connected with electrical lines through a

through hole of the substrate. Here, the back side of the substrate 3 means a surface facing toward the inside of the casing, and the front surface of the substrate 3 means a surface facing toward the outside of the casing. The configuration and the structure of the substrate 3 is not limited to particular ones, but it will suffice if they can properly support the electrical contact and the storing element 5. The substrate 3 may be a so-called glass-epoxy substrate in the form of a plate comprising a mixture of glass fibers and epoxy resin material on which wiring patterns are formed, or a so-called flexible substrate of a film on which the wiring patterns are formed.

10 **[0041]** The storing element 5 is an IC chip provided with an information storing portion (memory portion) and a control circuit. The information storing portion stores cartridge individuality information. The cartridge individuality information is information relating to a color of the ink accommodated in the ink accommodating chamber, information relating to an initial filling amount of the ink, information relating to an ink consumption amount supplied to the outside from the ink accommodating chamber, information relating to the date of manufacturing of the cartridge, and so on, for example. The structure of the information storing portion (memory portion) is not limited to a particular one, and it may be EEPROM, FeRAM or another element. On the other hand, the control circuit can analyze the information supplied from the controller 35 of the printer main assembly 30, can write information in the information storing portion, can read the information out of the information storing portion, and can output information to the controller 35. For example, the control circuit can analyze the ink consumption amount information and the ink color information supplied from the controller 35 and can write the ink consumption amount information and the ink color information in the information storing portion. In addition, the control circuit can read the ink color information and the ink

consumption amount information out of the information storing portion and output the read information to the controller 35.

[0042] The electrode pad as the cartridge side electrical contact 4 is electrically connectable with an electrical terminal as a main assembly side electrical contact 55 (electrical connecting portion), and as shown in part (a) of Figure 3, a part of the electrode pad 4 provides a contact position 4a relative to the electrical terminal 55. On the surface of the substrate 3, a plurality of electrical contacts (electrode pads) are provided. The plurality of electrical contacts 4 include a contact to which a clock signal is inputted from the printer main assembly, a contact at which the data of the ink consumption amount or the like are inputted and outputted, a contact to which electric power for operating the storing element is supplied from the printer main assembly, a contact connected with the ground, for example. In the example of Figure 3, the number of the electrical contact is five, but the number is not limiting, and it can be increased or decreased depending on the necessity.

[0043] In this embodiment, it will suffice if the electrode pads 4 are disposed at the positions at which they are connectable with the electrical terminals 55 provided in the mounting portion 33 as indicated in Figure 8 and Figure 9 which will be described hereinafter. For this reason, it is preferable that the electrode pad 4 is provided on the surface (on the area of the substrate 3 crossing with the cartridge mounting direction, for example) crossing with the cartridge mounting direction (Y axis direction).

[0044] It is particularly preferable that the plurality of electrode pads 4 are arranged in a direction crossing with the height direction (Z axis direction) of the cartridge on the surface crossing with the above-described cartridge mounting direction. Furthermore, it is further preferable that the plurality of electrode pads 4 are arranged in the widthwise direction (horizontal direction) of the

cartridge which is an example of the direction crossing with the height direction (Z axis direction) of the cartridge.

[0045] In the example of part (a) of Figure 3, the plurality of electrode pads 4 are arranged along the cartridge widthwise direction (X axis direction) on the front surface 2c which is a XZ surface perpendicular to the cartridge mounting direction (Y axis direction), but this is merely an example of the preferable example. For example, the plurality of electrode pads 4 are arranged on a surface inclined relative to the XZ surface.

[0046] The arrangement of the electrode pad shown in part (a) of Figure 3 can be expressed in various ways. For example, it can be said that the plurality of electrode pads 4 are arranged in the direction (horizontal direction, for example) crossing with the cartridge height direction (Z axis direction) in an area crossing with the cartridge depth direction (Y axis direction). In addition, it can be said plurality of electrode pads 4 are arranged in the direction (horizontal direction, for example) crossing with the cartridge height direction (Z axis direction) in an area crossing with a direction in which the tube insertion path 22 having the tube inserting opening 8 extends. In addition, the plurality of electrode pads 4 can be said are arranged in an area crossing with a direction parallel with a normal line of the formation surface / formation area of the tube inserting opening 8, along a direction (horizontal direction, for example) crossing with the cartridge height direction (Z axis direction). Furthermore, the polarity of the electrode pads 4 can be said are arranged in a area crossing with the direction parallel with a center line of the tube inserting opening 8, along the direction (horizontal direction, for example) crossing with the cartridge height direction (Z axis direction).

[0047] As described, the electrode pad 4 preferably includes (1) the area crossing with the cartridge mounting direction, (2) the area crossing with the Y

axis direction, (3) the area crossing with the cartridge depth direction, (4) the area crossing with the direction parallel with the normal line of the formation surface of the tube inserting opening (ink discharge opening) 8, (5) the area crossing with the direction parallel with the direction in which the tube insertion path (ink

5 discharging path) 22 extends, or (6) the area crossing with the direction parallel with the center line of the tube inserting opening (ink discharge opening).

[0048] By the connection between the electrode pad 4 and the electrical terminal 55, the storing element 5 of the ink cartridge 1 is electrically connected with the controller 35 of the printer main assembly 30. By this, the controller 35

10 becomes capable of reading out the information (the cartridge individuality information) stored in the storing element 5 by a known method. Similarly, the controller 35 becomes capable of writing the information (information relating to the ink consumption amount, for example) in the storing element 5.

[0049] As shown in Figures 2, 4 and 5, a positioning portion 6 is provided

15 between the tube inserting opening 8 and the electrical contact 4 in the longitudinal direction (height direction) of the front surface 2c of the casing 2, more particularly in a position closer to the electrical contact 4 than to the tube inserting opening 8. That is, the positioning portion 6 is disposed at the position closer to the electrical contact 4 than to the tube inserting opening 8 above the

20 tube inserting opening 8 and below the electrical contact 4. The positioning portion 6 is a portion into which a tapered columnar positioning pin 53 is inserted and is engageable with the positioning pin 53, so that the movement of the casing 2 in the direction (X axis direction and/or Z axis direction which are along the front surface 2c, for example) perpendicular to the cartridge mounting direction is

25 limited. In this embodiment, the positioning portion 6 may have any structure if it can limit the movement of the cartridge in the direction (along the front surface 2c, for example) perpendicular to the cartridge mounting direction by the

engagement with the positioning pin 53. For example, the positioning portion 6 may be a through hole portion penetrating the front wall, and a recess formed in the front wall on the like, and a positioning opening for receiving the positioning pin 53 is one of preferable examples. By the insertion of the ink reception tube 52 into the tube inserting opening 8, the movement of the cartridge is limited to a certain extent, but in this embodiment, the function of the high precision positioning of the ink cartridge to the mounting portion is effected by the positioning portion 6 and a position regulation surface 10 which will be described hereinafter.

10 **[0050]** As shown in Figures 4 and 5, an air vent 7 and the through-opening 27 are between the tube inserting opening 8 and the positioning portion 6 in the cartridge height direction. That is, the air vent 7 and the through-opening 27 are disposed above the tube inserting opening 8 and below the positioning portion 6.

[0051] Into the air vent 7 and the through-opening 27, the unsealing pin 51 is 15 inserted. The through-opening 27 is a through hole provided in the front wall, and the unsealing pin can penetrate it. On the other hand, the air vent 7 is an opening provided at one end portion of an air vent path 16 in a rear side beyond the through-opening 27, more particularly, it is provided in an air vent formation wall which is an inner wall provided between the front wall and the ink 20 accommodating chamber 11 in the cartridge depth direction. As will be described hereinafter, when the ink cartridge 1 is mounted to the mounting portion 33, the unsealing pin 51 is inserted through the through-opening 27 and is then inserted into the air vent 7 after penetrating the through-opening 27.

[0052] As shown in part (a) of Figure 5, the one end portion of the air vent path 25 16 is the air vent 7 which is the opening formed in the air vent formation wall, and the other end portion of the air vent path 16 is connected with the ink accommodating chamber 11. In the connecting portion between the air vent

path 16 and the ink accommodating chamber 11, a filter 15 having a meniscus force is provided. When a negative pressure in the ink accommodating chamber reaches a level exceeding the meniscus force of the filter by the consumption of the ink, the ambient air in the air vent path side breaks the meniscus of the filter 15 to flow into the ink accommodating chamber, thus establishing the fluid-communication state. In the fluid-communication state, the ambient air is taken into the ink accommodating chamber 11 through the air vent path 16 by the amount corresponding to the consumption of the ink out of the ink accommodating chamber 11, and therefore, the negative pressure in the ink accommodating chamber 11 is prevented from becoming too high. Therefore, it can be avoided that the ink supply from the ink accommodating chamber 11 to the outside is not impeded as a result of the too high negative pressure inside the ink accommodating chamber 11, and therefore, most of the ink can be used up out of the ink accommodating chamber.

[0053] As shown in part (a) of Figure 5, in the state before the start of use of the ink cartridge 1, a sealing film 17 as a sealing member covers the air vent 7. The sealing film 17 will be called also "air vent sealing film". As shown in Figure 4, the air vent sealing film 17 is bent by approx. 90° relative to the major surface of the flexible member 12 and is closely contacted to the air vent formation wall (the inner wall of the first casing member 40) so as to cover the air vent 7 provided in a first casing member 40. When the ink cartridge 1 is mounted, the air vent sealing film 17 is unsealed by the unsealing pin 51 inserted into the air vent 7 through the through-opening 27. In this embodiment, the air vent sealing film 17 is formed integrally with the flexible member 12, but the present invention is not limited to such a example, but the air vent sealing film 17 and the flexible member 12 may be separate members.

[0054] The air vent sealing film 17 functions as means for suppressing ink

evaporation and/or ink leakage before the start of the use of the cartridge such as during transportation thereof. Therefore, it is preferable that the timing of the unsealing of the air vent sealing film 17 is immediately before the start of use of the ink cartridge. To assure this, in this embodiment, the air vent sealing film 17 is unsealed by the unsealing pin 51 of the printer main assembly, so that the air vent sealing film 17 is unsealed at the time of the mounting of the ink cartridge 1 to the printer main assembly.

[0055] In addition, in this embodiment, as shown in part (a) of Figure 5, the air vent sealing film 17 is disposed in a rear side of the front surface 2c, more particularly in the position between the front surface and the ink accommodating chamber, which cannot be accessed by the user. Therefore, it can be avoided that the air vent sealing film 17 is removed by the user before the start of use of the cartridge.

[0056] The discrimination portion 9 mechanically functions to prevent the ink cartridge 1 from being mounted to a wrong mounting position (the position to which the cartridge of another ink color is to be mounted) and has unique configurations peculiar to the respective ink colors. As shown in Figure 2 and Figure 4, the discrimination portion 9 is provided with a recess at the position which is different if the color of the ink cartridge is different. Corresponding to the discrimination portion 9, a cartridge mounting portion 33 is provided with a projection as the discrimination member 60 (Figure 9). The mounting portions have the projections at different positions so as to prevent mounting of wrong color ink cartridges. As shown in Figure 2 and Figure 4, the discrimination portion 9 is between the tube inserting opening 8 and the electrical contact 4 in the longitudinal direction (height direction) of the front surface 2c of the casing 2. More particularly, the discrimination portion 9 is provided along the longitudinal direction, and the arranging range thereof is wider than the distance between the

positioning portion 6 and the through-opening 27.

[0057] As shown in Figure 2 and Figure 4, a circumference of the through-opening 27 in the front surface 2c of the casing 2 is projected into a cylindrical shape. The projected portion and the neighborhood thereof function as an
 5 ejection spring contact portion 23 which can be contacted by an ejection spring 57 provided in the mounting portion 33, as will be described hereinafter (Figure 9). The ejection spring contact portion 23 depicted by a broken line in Figure 9 is urged in a cartridge dismounting direction by the ejection spring 57 in the state that the ink cartridge is mounted to the mounting portion. That is, the ejection
 10 spring contact portion 23 functions as a force receiving portion for receiving from the ejection spring 57 an urging force for urging the ink cartridge 1 in the dismounting direction or a force (external force) for moving the ink cartridge 1 in the dismounting direction. The position of the ejection spring contact portion 23 is between the electrical contact 4 and the tube inserting opening 8 in the
 15 cartridge height direction, more particularly, below the positioning portion 6 and above the tube inserting opening 8.

[0058] As described in the foregoing, the front surface 2c of the casing 2 is provided concentrically with cartridge side interface portions including the electrical contact 4, the positioning portion (positioning opening) 6, the through-
 20 opening 27, the tube inserting opening 8, the discrimination portion 9, the ejection spring contact portion (force receiving portion) 23 or the like. By the concentric arrangement of the cartridge side interface portions, the printer main assembly side interface portions can be concentrically arranged, so that the printer main assembly side interface portions can be made as a unit, which can be
 25 downsized.

[0059] The cartridge side interface portion is provided not only on the front surface 2c of the casing 2 but also on the upper surface 2a of the casing 2. The

upper surface 2a of the casing 2 is provided with an engaging portion 24 engageable with a locking portion 54 of a locking lever 58 provided in the mounting portion 33 shown in Figure 8. As shown in Figure 2 and Figure 5, the engaging portion 24 is in the form of a recess engageable with the locking
 5 projection as the locking portion 54 to retain the ink cartridge 1 in the mounting completion position against the urging force of the ejection spring 57. The engaging portion 24 functions as a locking portion for fixing the ink cartridge 1 to the cartridge mounting portion 33.

[0060] As shown in Figures 5 and 10, in this embodiment, the recess as the
 10 engaging portion 24 has a side which is an area 24a crossing with the Y axis direction, and at least a part of the area 24a contacts the locking projection 54. The area 24a is a surface crossing with the direction parallel with normal line of the electrical contact 4 or the normal line of the area on the substrate 3 provided with the electrical contact 4, more particularly in this embodiment, said area 24a
 15 is perpendicular to the direction parallel with the normal line. The area 24a is an area crossing with the direction parallel with the normal line of the formation surface of the ink discharge opening 8 and is an area crossing with the direction parallel with the direction in which the ink discharging path 22 extends. Furthermore, the area 24a is an area crossing with the direction parallel with the
 20 center line (a phantom line passing through the center of the ink discharge opening 8) of the ink discharge opening 8.

[0061] In the engaged state (locked state) between the engaging portion 24 and the locking portion 54, the connected state between the cartridge side interface portions and the printer main assembly side interface portions (the connected
 25 state between the electrical contact 4 and the electrical connecting portion 55, the connected state between the positioning portion 6 and the positioning pin 53 (engaged state between the positioning portion 6 and the positioning pin 53), the

connected state between the tube inserting opening 8 and the ink reception tube 52 (the inserted state of the ink reception tube in the tube inserting opening 8), the fluid-communication state between the ink accommodating chamber 11 and the ink reception tube 52, or the like, for example) are maintained to retain the ink cartridge 1 in the mounting completion position. On the other hand, when the engaged state (locked state) between the engaging portion 24 and the locking portion 54 is released, the ink cartridge 1 is moved in the dismounting direction by the urging force of the ejection spring 57, and the connected state between the cartridge side interface portion and the printer main assembly side interface portion is also released. In this manner, the engaging portion 24 functions together with the locking portion 54 as the means for maintaining the connected state between the cartridge side interface portion and the printer main assembly side interface portion.

[0062] From another standpoint, the engaging portion 24 functions as a portion capable of receiving a regulating force for regulating movement of the casing 2 in the dismounting direction (the direction from the front surface toward the rear surface, for example) against the urging force of the ejection spring 57. In the case of this embodiment, the area 24a of the engaging portion 24 receives the regulating force from the locking projection 54 of the locking lever 58. In this manner, the engaging portion 24 is a regulating member for limiting the movement of the casing 2 caused by the force (external force) received from the outside of the ink cartridge 1.

[0063] As shown in Figure 2 and Figure 5, the engaging portion 24 is provided on the upper surface 2a of the casing 2. With the structure of this embodiment in which the engaging portion 24 is provided on the upper surface 2a of the casing 2, the distance between the engaging portion 24 and the electrical contact 4 is smaller than that in the case where the engaging portion is provided on the

bottom surface of the casing, and therefore, even if positional deviation occurs about the engaging portion 24 with the locking operation, the positional deviation of the electrical contact attributable to the deviation can be reduced. Therefore, satisfactory electrical connection can be easily accomplished.

- 5 **[0064]** In this embodiment, the engaging portion 24 is disposed in a position closer to the electrical contact than to the tube inserting opening 8, and therefore, the satisfactory connection between the ink cartridge and the printer main assembly can be easily accomplished. That is, regarding the connection between the ink cartridge and the printer main assembly, the movement tolerable
- 10 range of electrical contact in the front-rear direction (Y axis direction) is narrower than that of the tube inserting opening 8. In other words, the tolerance of the electrical contact 4 is smaller than that of the tube inserting opening 8, with respect to the deviation in the front-rear direction (Y axis direction) of the cartridge. On the other hand, upon the engagement (locking) between the
- 15 engaging portion 24 and the locking portion 54, the movement may occur in the front-rear direction with the movement of the casing 2 about the engaging portion 24 in a θx direction. It is preferable that the positional relations between the engaging portion 24, the tube inserting opening 8 and the electrical contact are selected such that the movement distance of the electrical contact 4 of the casing
- 20 2 in the front-rear direction with the movement of the casing 2 in the θx direction about the engaging portion 24 is smaller than that of the tube inserting opening 8. In a example to accomplish this, the engaging portion 24 is disposed on the upper surface 2a of the casing 2, by which the engaging portion 24 is disposed closer to the electrical contact than to the tube inserting opening 8.
- 25 **[0065]** As shown in Figure 2 and Figure 5, the engaging portion 24 is disposed in a position closer to the front surface 2c than to the rear surface 2d in the longitudinal direction (depth direction) of the upper surface 2a of the casing 2.

By disposing the engaging portion 24 in a position close to the electrical contact, the tolerance of the distance between the engaging portion 24 and the electrical contact 4 in the Y axis direction can be reduced, and therefore, the position tolerance of the electrical contact 4 relative to the engaging portion 24 in the front-rear direction (Y axis direction) upon the cartridge mounting can be reduced. When the position tolerance in the front-rear direction is small, the movable distance (stroke) of the electrical terminal 55 in the front-rear direction can be reduced in the design.

[0066] As shown in Figure 2, the position regulation surfaces 10 adjacent to the bottom surface and adjacent to the front surface in the left surface 2e and the right-hand surface 2f of the casing 2 are contact surfaces contacting to a positioning wall 56 of the mounting portion 33 shown in Figure 8 and Figure 9 when the ink cartridge 1 is mounted to the mounting portion 33. The left and right position regulation surfaces 10 functions as position regulating means for regulating movement in the X axis direction and θ_y direction by contacting to the positioning wall 56. The ink cartridge of this embodiment is provided with the position regulation surfaces 10 in the left surface 2e and the right-hand surface 2f, but this is not restrictive to the present invention. For example, two grooves may be formed extending in the Y axis direction on the bottom surface 2b in the neighborhood of the front surface, and the side surfaces of the two grooves may function as the position regulation surfaces 10. What is required is that the position regulation surface 10 is effective to make a neighborhood of the bottom surface of the ink cartridge contact to the positioning wall 56 to limit the movement in the X axis direction and θ_y direction.

[0067]

(Ink accommodating chamber)

The inside structures of the ink cartridge will be described particularly

about the structure of the ink accommodating chamber. Figure 4 is an exploded view of the ink cartridge shown Figure 2. The casing 2 comprises a first casing member 40 including the upper surface 2a, the front surface 2c, the rear surface 2d and the left surface 2e, and a second casing member 41 including the right-hand surface 2f. The second casing member 41 functions as a closing member for closing the opening of the first casing member 40. The ink accommodating chamber 11 is a chamber for accommodating the ink in the inside space defined by an internal wall surface of the first casing member 40 and the flexible member 12 (flexible sheet) welded to the inner wall edge of the first casing member 40.

10 **[0068]** A sealing member unit 20 is a member to be inserted into the tube insertion path 22 of the first casing member 40. The sealing member unit 20 includes a cylindrical sealing member 19 having an opening and closing slit at one end portion thereof and having an opening on the other end and an outer casing 21 integral with the outer peripheral surface of the sealing member 19.

15 When the sealing member unit 20 is inserted into the tube insertion path 22, the opening at the other end constitutes the tube inserting opening 8.

[0069] Inside the ink accommodating chamber 11, there are provided a negative pressure generation spring 13 as a negative pressure producing member and a plate member 14 which is slightly smaller than the inner wall circumference of the first casing member 40. One end portion of the negative pressure generation spring 13 is engaged with the inner wall of the left surface 2e of the first casing member 40, and the other end portion of the negative pressure generation spring 13 is engaged with the plate member 14. The negative pressure generation spring 13 urges the flexible member 12 through the plate member 14 in the

20 direction of expanding the ink accommodating chamber, by which the ink accommodating chamber is maintained under a predetermined range of the negative pressure. When the ink amount in the ink accommodating chamber

decreases by the ink supply to the outside of the ink accommodating chamber 11, the negative pressure in the ink accommodating chamber 11 tends to increase, but the negative pressure generation spring 13 contracts, so that the plate member 14 moves in the direction of reducing the inside volume of the ink accommodating chamber 11, thus suppressing the increase of the negative pressure.

[0070] The space (non-ink-accommodating space) between the ink accommodating chamber 11 and the second casing member 41 is in fluid communication with the outside of the ink cartridge 1 through the fluid communication path (unshown) provided in the rear wall of the ink cartridge 1 and through the ambient air opening 26 (Figure 6). More particularly, the rear wall of the ink cartridge 1 is provided with a snaking groove (unshown) having one end portion in fluid communication with the non-ink-accommodating space and the other end in fluid communication with the ambient air opening 26. The snaking groove is covered with a label 25 (Figure 6), and the groove covered with the label 25 functions as the fluid communication path for fluid communication between the non-ink-accommodating space and the ambient air opening 26. Therefore, when the plate member 14 moves in the direction of reducing the inside volume of the ink accommodating chamber 11, the ambient air is introduced into the space (non-ink-accommodating space) between the ink accommodating chamber 11 and the second casing member 41 from the ambient air opening 26 through the fluid communication path (unshown).

[0071] By the movement of the plate member 14, the ink supply is carried out, but when the negative pressure in the ink accommodating chamber 11 exceeds the meniscus force as a result of further consumption of the ink, the air is introduced into the ink accommodating chamber 11 passing through the filter 15 from the air vent path 16, as described above. Subsequently, the ambient air is introduced into the ink accommodating chamber through the air vent path 16 by

the amount corresponding to the supply of the ink, and therefore, the negative pressure in the ink accommodating chamber is maintained within a predetermined range, so that the negative pressure does not increase unnecessarily. By the introduction of the ambient air into the ink accommodating chamber from a certain stage of the ink supply, the almost all the ink in the ink accommodating chamber can be used up.

[0072]

<Injection of ink>

In this embodiment, the method of injecting the ink into the ink cartridge 1 is not limited to a particular method. For example, an empty ink cartridge (free of the tube inserting opening sealing film 18) as shown in Figure 4 is prepared, and the ink can be injected through the tube inserting opening 8. After the ink injection, the tube inserting opening sealing film 18 is stuck on the front surface 2c of the casing 2.

[0073] In the case that the air vent sealing film 17 and the flexible member 12 are separate members as described hereinbefore, the ink cartridge can be manufactured through the following steps. First, an empty ink cartridge (free of the air vent sealing film 17 and the tube inserting opening sealing film 18) as shown in Figure 4 is prepared. More particularly, a casing 2 comprising (i) the ink accommodating chamber 11, (ii) the air vent path 16 capable of introducing the air into the ink accommodating chamber 11, (iii) the through hole formation wall (front wall 2c) provided with the through hole 27 into which the unsealing pin 51 can be inserted, (iv) the air vent formation wall disposed between the through hole formation wall (front wall) and the ink accommodating chamber 11 and provided with the air vent 7 at the end portion of the air vent path 16 is prepared. Then, the air vent sealing film 17 which can be unsealed by the unsealing pin 51 having passed through the through hole 27 is stuck covering the

air vent 17. Then, the ink is injected, and finally, the tube inserting opening sealing film 18 which can be unsealed by the ink receiving tube 52 is stuck on the front surface 2c of the casing 2. The ink cartridge 1 can be manufactured through such the steps, too.

5 **[0074]**

<Cartridge mounting unit>

Referring to Figures 6 - 9, a cartridge mounting unit (head unit) 38 to which the ink cartridge 1 is detachably mountable will be described.

[0075] Figure 6 is a perspective view illustrating a state before the ink cartridge
 10 1 is mounted to the mounting portion 33 of the cartridge mounting unit 38 shown in Figure 1. Figure 7 is a perspective view in the state that the ink cartridge 1 has been mounted to the mounting portion 33 of the cartridge mounting unit 38 shown in Figure 1. Figure 8 is a sectional view of the cartridge mounting unit. Figure 9 is a perspective view illustrating a connection relation between a joint
 15 unit (main assembly side connecting unit) 59 taken out of the cartridge mounting unit 38 of Figure 8 and the ink cartridge 1. Figure 9 illustrates the joint unit corresponding to two color ink cartridges.

[0076] As described hereinbefore, the cartridge mounting unit (head unit) 38 integrally comprises the ink jet head 32 and the cartridge mounting portion 33
 20 and is detachably mountable to the carriage 31 of Figure 1. As shown in Figures 6 and 8, the mounting portion 33 comprises a frame 49 constituting a generally rectangular parallelepiped outer configuration having an open front surface and a joint unit 59 provided in the rear side of the frame. The ink cartridges 1 are accommodated in the inside space of the frame 49. As shown in Figures 6 and 7,
 25 the four ink cartridges 1C, 1Bk, 1M, 1Y are arranged in the X axis direction. The black ink cartridge 1Bk has a larger width than the other color ink cartridges 1C, 1M and 1Y, and therefore, the mounting region for the black ink cartridge

has a larger width than the other mounting regions.

[0077] As shown in Figure 6, the ink cartridge 1 is mounted (inserted) in the Y axis direction perpendicular to the moving direction (X axis direction) of the carriage. A white arrow in Figure 6 depicts the mounting direction (inserting
 5 direction) of the ink cartridge, and the ink cartridge dismounting direction is the opposite. In this embodiment, the cartridge mounting direction (Y axis direction) is the direction crossing with the direction of gravity (vertical direction), and in this example, it is inclined by an angle 5° relative to the horizontal surface crossing with the direction of gravity, and therefore, it is not
 10 completely horizontal direction, but substantially horizontal direction.

[0078] As shown in Figures 6, 8 and 9, the mounting portion 33 is provided with the joint unit 59 having the printer main assembly side interface portion. The joint unit 59 includes the unsealing pin 51 having a pointed free end and extended from a surface to oppose the front surface 2c of the ink cartridge, the
 15 ink reception tube 52 in the form of a tapered cylindrical hollow needle having a opening at the free end, the tapered cylindrical positioning pin 53, an electrical terminal 55, a positioning wall 56, the ejection spring 57 and the discrimination member 60 in the form of a projection. The unsealing pin 51, the ink reception tube 52, the positioning pin 53 and the discrimination member 60 are arranged in
 20 the Y axis direction, and the ejection spring 57 is contractable and expandable in the Y axis direction.

[0079] The unsealing pin 51 is an unsealing member for unsealing the air vent sealing film 17 piercing the air vent sealing film 17 upon the mounting of the ink cartridge 1. In this embodiment, the unsealing pin 51 is first inserted through
 25 the through-opening 27 and then through the air vent sealing film 17 into the air vent 7.

[0080] The ink receiving needle as the ink reception tube 52 is an ink receiving

member for piercing the tube inserting opening sealing film 18 to unseal it, and insertable into the tube inserting opening 8 to connect with the tube insertion path 22, thus receiving the ink through the tube insertion path 22. The ink receiving tube 52 is in fluid communication with the ink jet head 32 to supply the ink

5 received through the tube insertion path 22 into the ink jet head 32. That is, the ink receiving tube 52 functions as an ink supply tube for supplying the ink into the ink jet head 32. In this example, the ink receiving tube 52 is in the form of a tapered hollow cylindrical needle having the opening at the free end, but the present invention is not limited to such a configuration, and it will suffice if it is a

10 hollow member capable of being inserted through the tube inserting opening 8 and having an opening capable of receiving the ink from the ink cartridge 1. The position of the opening is not necessarily at the free end, and the configuration is not necessarily a tapered cylinder.

[0081] The positioning pin 53 is a position regulation member insertable into

15 the positioning portion 6 to limit the movement of the casing 2 in the direction (X axis direction and/or Z axis direction which is the direction along the front surface 2c, for example) perpendicular to the mounting direction of the ink cartridge 1, by engagement with the positioning portion 6.

[0082] The electrical terminals 55 are the electrical connecting portions (main

20 assembly side electrical contacts) electrically connectable with the electrode pads 4, and the number of the electrical terminals 55 corresponds to the number of the electrode pads 4. In this embodiment, five electrical connecting portions (electrical terminals) 55 are provided corresponding to the five electrode pads 4, but the numbers are not limited to five. It will suffice if a plurality of electrical

25 connecting portions (electrical terminals) 55 are provided corresponding to the plurality of electrode pads 4. The electrical connecting portions (electrical terminals) 55 are electrically connected with the controller 35 of the printer main

assembly 30.

[0083] As shown in Figure 9, the electrical connecting portions (electrical terminals) 55 are provided in an electrical connection unit 47. The electrical connection unit 47 includes the plurality of electrical connecting portions 55, a supporting member 46 supporting the electrical connecting portions 55, and an urging spring (unshown) for urging the supporting member 46 in the cartridge dismounting direction. The electrical connection unit 47 constitutes a part of the joint unit 59. The electrical connecting portions 55 disposed in an upper portion of the joint unit 59 are provided in the position capable of opposing the electrode pads 4 in the Y axis direction. The electrical connecting portions 55 are movable in the Y axis direction in interrelation with the expansion and contraction of the urging spring (unshown). More particularly, when the electrical connecting portion 55 is not in contact with the electrode pad 4, the electrical connecting portion 55 is in a first position with respect to the Y axis direction. When the ink cartridge moves in the cartridge mounting direction (Y axis direction) in the mounting operation of the ink cartridge, the electrode pads 4 of the ink cartridge contact to the electrical connecting portions 55 placed in the first position. Thereafter, by further insertion of the ink cartridge toward the rear side of the mounting portion, the electrical connecting portions 55 move to a second position which is in the rear side of the first position while keeping the contact with the electrode pads 4. Taking the manufacturing error or the like into account, the electrical connecting portion 55 is movable to a third position which is in the rear side of the second position in the mounting portion. On the other hand, upon the dismounting of the ink cartridge, the electrical connecting portion 55 returns from the second position to the first position in the Y axis direction with the movement of the dismounting direction of the ink cartridge, as is opposite from that in the mounting case. In this manner, the electrical

connecting portions 55 are movable, and therefore, the contact pressure relative to the electrode pad 4 does not become unnecessarily high, thus suppressing the damage and/or failure of the electrode pad 4 and/or the electrical connecting portion 55.

5 **[0084]** As shown in Figure 9, the positioning walls 56 are the position regulation members which are contactable to the position regulation surfaces 10 provided in the bottom end portion of the right-hand surface and the bottom end portion of the left surface of the ink cartridge 1 to limit the movement of the ink cartridge in the X axis direction and θy direction. Two positioning walls 56
10 sandwich the two position regulation surfaces from the left and right sides of the ink cartridge 1, so that the positional deviation of the ink cartridge adjacent to the bottom surface in the X axis direction and θy direction is suppressed.

[0085] The ejection spring 57 is an urging member for contacting to the ejection spring contact portion 23 of the front surface 2c of the ink cartridge and
15 to elastically urge the ink cartridge 1 in the cartridge dismounting direction in order to dismount the ink cartridge 1 from the mounting portion 33. The ejection spring 57 is a coil spring provided so as to surround the unsealing pin 51 and expandable and contractable in the Y axis direction. The ejection spring 57 is in the expanded state when it is not contacted by the ink cartridge, and is
20 contracted with the mounting of the ink cartridge. In the dismounting of the cartridge, the ink cartridge 1 is moved in the cartridge dismounting direction by the expansion of the ejection spring 57. By this movement, the connected state between the electrical contact 4 and the electrical connecting portion 55, the fluid-communication state between the ink accommodating chamber 11 and the
25 ink receiving tube 52, the engaged state (connected state) between the positioning portion 6 and the positioning pin 53, the connected state between the tube inserting opening 8 and the ink receiving tube 52 (the state that the ink receiving

tube 52 is inserted in the tube inserting opening 8) are broken, so that the ink cartridge is placed in a dismountable state.

- [0086]** In this example, the function of the ejection spring 57 is to break (1) connected state between the electrical contact 4 and the electrical connecting portion 55, (2) the fluid-communication state between the ink accommodating chamber 11 and the ink receiving tube 52, (3) the engaged state between the positioning portion 6 and the positioning pin 53 (the state that the positioning pin 53 is inserted in the positioning portion 6) and (4) the inserted state in which the ink receiving tube 52 is inserted in the tube inserting opening 8, are broken, in addition to the movement of the ink cartridge in the dismounting direction with the release of the engaged state between the engaging portion 24 and the locking portion 54. It is possible that the ink cartridge is dismounted even when a part of the ink receiving tube 52 remains in the tube insertion path 22, or a part of the positioning pin 53 remains in the positioning portion 6, for example, and the dismounting operation of the ink cartridge by the user is made easy if the ink cartridge is moved in the dismounting direction. It will suffice if the ejection spring 57 is capable of applying the urging force for moving the ink cartridge in the dismounting direction. Therefore, the force receiving portion 23 for receiving the urging force from the ejection spring 57 preferably receives from the ejection spring 57 the force urging the ink cartridge 1 in the dismounting direction to break the connected state, the fluid-communication state, the engagement and the inserted state, but such a structure is not restricted to the present invention, and it will suffice if the ink cartridge 1 is capable of receiving the force for moving the ink cartridge in the dismounting direction.
- [0087]** The discrimination member 60 is the projection configuration portion engageable with the recess which is the discrimination portion 9 of the ink cartridge. The positions of the projections of different mounting portions are

different from each other to prevent mounting of non-corresponding color ink cartridges. That is, the discrimination member 60 engages with the discrimination portion 9 only of the corresponding color ink cartridge, and does not engage with a discrimination portion 9 of another color ink cartridge.

- 5 **[0088]** The above-described unsealing pin 51, ink receiving tube 52, positioning pin 53, electrical terminal 55, positioning walls 56, ejection spring 57 and discrimination member 60 are arranged in the positional relation shown in Figures 8 and 9. More particularly, the positioning wall 56, the ink receiving tube 52, the ejection spring 57, the positioning pin 53 and the electrical terminal
- 10 55 are arranged in the order named in the direction from the bottom to the top. In addition, the unsealing pin 51 is provided inside the ejection spring 57, and therefore, is disposed below the positioning pin 53 and above the ink receiving tube 52. Furthermore, the discrimination member 60 is disposed above the ink receiving tube and below the electrical terminal 55.
- 15 **[0089]** As shown in Figures 6 and 8, the mounting portion 33 of the cartridge mounting unit 38 is provided with the frame 49 constituting the inside space for receiving the ink cartridge 1, as well as the joint unit 59. The frame 49 is provided with a plate 48 for partitioning the space in the frame, and a locking lever 58 as a locking mechanism for fixing the ink cartridge 1 to the mounting
- 20 portion 33. The frame 49 and the plate 48 function as a mounting guide 50 for regulating the attitude of the ink cartridge when it is mounted.

- [0090]** As shown in Figure 6, the upper wall and bottom wall of the frame 49 are provided with respective plates 48 partitioning the inside space. The ink cartridges 1 are placed in the four spaces provided by the partition plates 48.
- 25 The plates 48 are extended from the rear side toward the front surface of the frame 49. The plates 48 are arranged in parallel with each other at predetermined intervals in the X axis direction. The interval between the

adjacent plates corresponds to the width of ink cartridge 1 to receive. The mounting guide 50 is constituted by the plates 48 and the bottom wall, the upper wall and the side walls of the frame 49, and the attitude of the ink cartridge is regulated by the mounting guide 50 in the mounting operation of the ink cartridge.

- 5 **[0091]** As shown in Figure 8, the locking lever 58 extends from the front surface toward the rear side of the mounting guide 50, and a supporting shaft 78 is provided in the neighborhood of the center thereof in the extending direction. The supporting shaft 78 is rotatably supported by the upper part mounting guide 50 provided by the upper wall of the frame 49, and the locking lever 58 is
- 10 rotatable about the supporting shaft 78. A rear side end portion of the locking lever 58 is provided with a locking projection as the locking portion 54 engageable with the engaging portion 24 of the ink cartridge 1. A push-up spring (unshown) is provided between the upper part mounting guide 50 and a lower surface portion of the locking lever 58 in the opposite side from the locking
- 15 projection 54 across the supporting shaft 78. The push-up spring urges the locking lever 58 in the direction of pushing-up the locking lever portion in the opposite from the locking projection 54 across the supporting shaft 78, so that the locking projection 54 is in the inside space of the frame. When the locking lever 58 is free of an external force, a lower surface of a part between the locking
- 20 projection 54 and the supporting shaft 78 in the locking lever 58 contacts the end portion of the upper part mounting guide 50, so that the locking lever 58 is prevented from rotating. With this attitude, the locking projection 54 is in a position (first position) in which it is contactable to the engaging portion 24 of the ink cartridge 1 being inserted into the mounting portion 33. When the ink
- 25 cartridge 1 is inserted, the locking projection 54 contacts to the ink cartridge 1, by which the locking lever 58 rotates against the push-up force of the push-up spring, so that the locking projection 54 is moved to the second position above the first

position. In the second position, the locking projection 54 contacts the upper surface 2a of the ink cartridge 1. Thereafter, when the engaging portion (engaging recess) of the recess configuration is moved to the position capable of contacting to the locking projection 54 as a result of the further insertion of the ink cartridge 1, the locking projection 54 is moved to the first position by the push-up force to engage with a side surface 24a of the engaging recess 24. By this, the ink cartridge 1 is fixed to the mounting portion 33 against the urging force of the ejection spring 57, thus completing the mounting of the ink cartridge 1. In the engaged state between the locking projection 54 and the engaging recess 24, the connected state between the electrical contact 4 and the electrical connecting portion 55, the fluid-communication state between the ink accommodating chamber 11 and the ink receiving tube 52, the engaged state between the positioning portion 6 and the positioning pin 53 are maintained.

[0092] On the other hand, when the ink cartridge 1 is dismounted from the mounting portion 33, the user moves the locking lever 58 to disengage the locking projection 54 of the locking lever 58 from the engaging portion 24 of the ink cartridge 1. When the engaged state is released, the ink cartridge 1 is moved in the dismounting direction by the urging force of the ejection spring 57, by which the ink cartridge becomes dismountable.

[0093]

<Mounting operation and dismounting operation of ink cartridge>

Figure 10 illustrates the process of mounting (inserting) the ink cartridge 1 into the mounting portion 33, in which (a) shows an initial state of insertion (initial state of mounting), and (b) shows an insertion completed state (completion of mounting).

[0094] As shown in part (a) of Figure 10, in the initial stage of the mounting operation, the ink cartridge 1 is inserted along the inside of the mounting guide

50. When the ink cartridge 1 contacts to the ejection spring 57, the ink cartridge 1 receives the urging force of the ejection spring 57 thereafter, and therefore, if the insertion is stopped before the mounting is completed, the ink cartridge 1 is pushed back.

5 **[0095]** When the ink cartridge 1 this is further inserted against the urging force of the ejection spring 57, the recess of the discrimination portion 9 of the ink cartridge 1 is checked in effect as to whether or not it matches the projection of the discrimination member 60 of the mounting portion 33. If the correspondence (correspondence in the color) between the ink cartridge 1 and the mounting position is correct, the recess of the discrimination portion 9 and the projection of the discrimination member 60 are complementary with each other, and therefore, the ink cartridge 1 can be further inserted. On the other hand, if the correspondence (correspondence in the color) between the ink cartridge 1 and the mounting position is not correct, the recess of the discrimination portion 9 and the projection of the discrimination member 60 are not complementary with each other, and therefore, the ink cartridge 1 cannot be inserted any further. At this stage, the air vent sealing film 17 or the tube inserting opening sealing film 18 are not yet unsealed. Therefore, if the ink cartridge is inserted into a wrong mounting position, the air vent sealing film 17 and the tube inserting opening sealing film 18 are kept unsealed.

[0096] The ink cartridge 1 is further inserted after the engagement between the discrimination portion 9 and the discrimination member 60, the tube inserting opening sealing film 18 is unsealed by the free end of the ink receiving tube 52, and the ink receiving tube 52 is inserted into the tube inserting opening 8. Then, the positioning pin 53 is inserted into the positioning portion 6, and two position regulation surfaces 10 are sandwiched between the two positioning walls 56, so that the positional deviation is suppressed thereafter. By the two position

regulation surfaces 10, the position regulation is effected at two positions adjacent to the bottom surface, and by the positioning portion 6, the position regulation is effected at one position above the two position regulation surfaces 10, so that the movement of the ink cartridge 1 is generally limited in the
5 directions (X axis direction, Z axis direction) along the front surface (XZ flat surface) 2c of the ink cartridge 1 and the θy direction.

[0097] Subsequently, the air vent sealing film 17 is unsealed by the unsealing pin 51 piercing into the through-opening 27, and the unsealing pin 51 is inserted into the air vent 7. Then, the ink receiving tube 52 is inserted into the slit of the
10 sealing member 19 provided in the tube insertion path 22, by which the ink accommodating chamber 11 and the ink receiving tube 52 are brought into fluid communication with each other. Thereafter, the electrical contacts 4 are brought into contact to the electrical connecting portion 55.

[0098] Finally, the ink cartridge is pushed in until the engaging portion 24 is
15 engaged with the locking projection 54, by which the ink cartridge 1 is fixed, and the mounting operation is completed, as shown in part (b) of Figure 10. The position shown in part (b) of Figure 10 is the position where the mounting is completed.

[0099] On the other hand, as described hereinbefore, when the ink cartridge 1 is
20 dismounted from the mounting portion 33, the locking lever 58 is rotated to disengage the locking projection 54 from the engaging portion 24. When the engaged state is disestablished, the ink cartridge 1 is pushed back by the urging force of the ejection spring 57 to the position shown in part (a) of Figure 10.

[0100] The connection steps between the ink cartridge and the printer main
25 assembly having been described in conjunction with Figure 10 is a preferable example of this embodiment, and this embodiment is not limited to the ink cartridge which is to be mounted through the above-described connecting steps.

This embodiment is applicable to an ink cartridge which is mounted through the steps different from those described above.

[0101]

<Arrangement of cartridge side interface>

5 As shown in Figure 2, in this embodiment, the electrical contact 4 is disposed in a position above the tube inserting opening 8, that is, in the position closer to the upper surface 2a than to the tube inserting opening 8 in the cartridge height direction. With this position in relationship, even if the ink leaks from the tube inserting opening 8, the contact of the ink to the electrical contact 4 can
10 be suppressed. If the relationship between the tube inserting opening 8 and the electrical contact 4 is the opposite, that is, if the tube inserting opening 8 is disposed above the electrical contact 4, the ink receiving tube 52 of the printer main assembly side is also above the electrical connecting portion 55. Then, the ink draining from the ink receiving tube 52 contact to the electrical connecting
15 portion 55c, and the ink may be transferred onto the electrical contact 4, but according to this embodiment, no such a problem arises.

[0102] In this embodiment, the electrical contacts 4 are provided on the surface crossing with the inserting direction of the cartridge (XZ surface perpendicular to the Y axis direction in the example of Figure 2), and therefore, the amount of
20 rubbing between the electrical contacts and the electrical terminals 55 is smaller than that in the case in which the electrical contacts 4 are provided on the surface (right-hand surface, left surface, upper surface or bottom surface) parallel with the inserting direction of the cartridge. Therefore, the disadvantages which may arise significant rubbing between the electrical terminals 55 can be suppressed.

25 For example, with the structure in which the electrical contacts 4 are provided on the surface parallel with the cartridge inserting direction, the electrical terminals 55 relatively significantly rub the electrical contacts 4. Therefore, when the

mounting and dismounting of the ink cartridge is repeated, the electrical terminals
55 may be worn with the possible result of adverse influence to the electrical
connection therebetween. However, according to this embodiment, the amount
of the rubbing between the electrical terminals 55 and the electrical contacts 4 is
5 small, and therefore, the deterioration of the reliability in the electrical connection
therebetween attributable to the wearing of the electrical terminals can be easily
suppressed.

[0103] As shown in Figure 2 and Figure 5, in this embodiment, the engaging
portion 24 as the locking portion for fixing the ink cartridge 1 to the cartridge
10 mounting portion 33 is provided on the upper surface 2a of the casing 2. With
this structure in which the engaging portion 24 is provided on the upper surface
2a of the casing 2, the distance between the engaging portion 24 and the electrical
contact 4 is smaller than that in the case in which the engaging portion is
provided on the bottom surface of the casing, and therefore, even if the positional
15 deviation about the engaging portion 24 with the locking action occurs, the
positional deviation of the electrical contact resulting from the positional
deviation can be suppressed. Therefore, satisfactory electrical connection can
be easily accomplished.

[0104] In this embodiment, the engaging portion 24 is disposed in a position
20 closer to the electrical contact than to the tube inserting opening 8, and therefore,
the satisfactory connection between the ink cartridge and the printer main
assembly can be easily accomplished. That is, regarding the connection
between the ink cartridge and the printer main assembly, the movement tolerable
range of electrical contact in the front-rear direction (Y axis direction) is narrower
25 than that of the tube inserting opening 8. In the other words, the tolerance of the
electrical contact 4 is smaller than that of the tube inserting opening 8, with
respect to the deviation in the front-rear direction (Y axis direction) of the

cartridge. On the other hand, upon the engagement (locking) between the engaging portion 24 and the locking portion 54, the movement may occur in the front-rear direction with the movement of the casing 2 about the engaging portion 24 in a θx direction. It is preferable that the positional relations between the engaging portion 24, the tube inserting opening 8 and the electrical contact are selected such that the movement distance of the electrical contact 4 of the casing 2 in the front-rear direction with the movement of the casing 2 in the θx direction about the engaging portion 24 is smaller than that of the tube inserting opening 8. In order to accomplish this, it is preferable that the engaging portion 24 is provided on the upper surface 2a, so that the engaging portion 24 is disposed in the position closer to the electrical contacts 4 than to the tube inserting opening 8. If the engaging portion is provided on the bottom surface as disclosed in International Publication 2012 - 054050, the engaging portion is not closer to the electrical contact than to the tube inserting opening, and therefore, the above-described advantageous effects are not provided.

[0105] In addition, in this embodiment, as shown in Figure 2 and Figure 5, the engaging portion 24 is provided in a position closer to the front surface 2c than to the rear surface 2d on the upper surface 2a with respect to the depth direction. By disposing the engaging portion 24 in the position close to the front surface side on the upper surface 2a, the engaging portion 24 can be made closer to the electrical contacts 4 than in the case that the engaging portion 24 is disposed in a rear side on the upper surface 2a. By disposing the engaging portion 24 in a position close to the electrical contact, the variation of the distance between the engaging portion 24 and the electrical contact 4 in the Y axis direction can be reduced, and therefore, the positional variation of the electrical contact 4 relative to the engaging portion 24 in the front-rear direction (Y axis direction) upon the cartridge mounting can be reduced. When the position tolerance in the front-

rear direction is small, the movable distance (stroke) of the electrical terminal 55 in the front-rear direction can be reduced in the design.

[0106] In this embodiment, the plurality of electrode pads 4 are arranged in the horizontal direction (widthwise direction of the cartridge, X axis direction) on the surface (preferably XZ surface) crossing with the cartridge mounting direction (Y axis direction). As described hereinbefore, when the ink cartridge is mounted, the movement of the cartridge in the direction (X axis direction or Z axis direction) along the front surface 2c and the θ_y direction are limited by the position regulation surface 10 provided adjacent to the bottom surface and the positioning portion 6 provided thereabove, when the ink cartridge is mounted. However, the movement in the θ_x direction occurs to a some extent. When the movement in the θ_x direction occurs, the lower end side of the substrate 3 is farther from the electrical connecting portion 55 in the Y axis direction than the upper end side. In other words, the deviation amount of the substrate 3 is larger in the lower end side than in the upper end side. Therefore, with the structure in which the plurality of electrode pads are arranged along the cartridge height direction (Z axis direction), the deviation amounts of the different electrode pads from the electrical terminal 55 are significantly different, and therefore, the contact pressures are different correspondingly, with the possible result of difficulty in assuring the stabilized electrical connection. If the entirety design is carried out to suit the contact pressure proper between the upper end side electrode pad of the substrate and the main assembly side electrical terminal 55, the contact pressure may be too low between the lower end side electrode pad and the main assembly side electrical terminal. On the other hand, if the entirety design is carried out to suit the contact pressure proper between the lower end side electrode pad of the substrate and the main assembly side electrical terminal 55, the contact pressure may be too high between the upper end side electrode

pad and the main assembly side electrical terminal. If the main assembly side electrical terminals are designed to suit the respective electrode pads, the part have to be separate parts with the result in the increase in cost and design load. On the contrary, according to this embodiment in which the plurality of electrode pads are arranged in the horizontal direction (widthwise direction of the cartridge, X axis direction), even if the movement in the θx direction is produced, the deviation amounts from the electrical terminals 55 are not significantly different from each other, and therefore, the above-described disadvantages will not result.

[0107] With this structure of this example in which the movement in the θx direction may occur, the positional deviation may be produced in the Z axis direction. In this case, the size of the electrode pad is to be designed, taking the positional deviation in the Z axis direction into account. If the electrode pads are arranged along the Z axis direction, the substrate size in the Z axis direction is relatively large because of the size of the electrode pad. When the size of the electrode pad and/or the substrate is large, the possibility of deposition of the ink and/or foreign matter which may be a cause of the failure of the substrate increases, and in addition, the possibility of the user contacting the substrate also increases. Furthermore, the increase in cost arises. According to this embodiment, the substrate size measured in the Z axis direction can be made smaller than that in the case in which the electrode pads are arranged along the Z axis direction.

[0108] With the structure of this embodiment in which the electrical contacts 4 are arranged in the horizontal direction (widthwise direction of the cartridge, X axis direction), even if the ink or liquid deposited on the main assembly side electrical connecting portion 55 is transferred onto the electrical contacts of the ink cartridge, the possibility of the short circuit between the electrical contacts due to the bridge of the ink or liquid therebetween is lower than in the case in

which the electrical contacts are arranged in the cartridge height direction (Z axis direction).

[0109] For example, when an empty cartridge from which the ink has been used up is dismounted, and a fresh cartridge is mounted, the user might remount the empty cartridge erroneously. If the liquid leaks from the empty cartridge when the empty cartridge is dismounted, the liquid or ink may be deposited on the electrical contact of the empty cartridge. Then, the liquid and/or ink deposited on the empty cartridge may be transferred onto the main assembly side electrical connecting portion 55. If the fresh cartridge is mounted thereafter, the liquid and/or ink now deposited on the main assembly side electrical connecting portion 55 may be transferred onto the electrical contact 4 of the fresh cartridge.

[0110] In another case, in the case of an ink jet printer with which the printing operation can be carried out under the condition that a great amount of ink mist is produced, the ink mist floating in the printer main assembly may be deposited on the printer main assembly side electrical connecting portion 55. If this occurs, when the fresh ink cartridge is mounted to the printer main assembly, the ink mist deposited on the electrical connecting portion 55 of the printer main assembly side may be transferred onto the electrical contact 4 of the cartridge. And, the ink transfer amount may be great.

[0111] In such a case, if the electrical contacts 4 are arranged in the cartridge height direction (Z axis direction), the liquid deposited on the upper side electrical contact 4 may fall to the lower side electrical contact 4 with the result of short circuit between the upper and lower electrical contacts 4. The short circuit may lead to a malfunction of the electrical contacts. On the other hand, according to this embodiment, the electrical contacts 4 are arranged in the widthwise direction (X axis direction) of the cartridge, and therefore, if the liquid deposited on the electrical contact 4 falls, the possibility of the short-circuit

between the electrical contacts is lower than in the case that the electrical contacts 4 are arranged in the cartridge height direction (Z axis direction).

[0112] As shown in Figure 9 and Figure 10, in this embodiment, the ejection spring contact portion 23 is provided between the tube inserting opening 8 and the electrical contact 4 in the height direction of the front surface 2c. With this arrangement, the ejection spring contact portion 23 disposed in the position close to the tube inserting opening 8 receives the force from the ejection spring 57, and therefore, the ink receiving tube 52 can be easily removed from the sealing member 19 of annular rubber member provided in the tube insertion path 22. In this embodiment, the sealing member 19 of the annular rubber member is provided in the tube insertion path 22, and when the ink receiving tube 52 is inserted in the tube insertion path 22, the ink receiving tube 52 is press-contacted by the sealing member 19. Therefore, the press-contact state between the ink receiving tube 52 and the sealing member 19 is not easily broken than in the other interface portions. For the purpose of smooth disconnection between the ink receiving tube 52 and the sealing member 19, it is preferable that the ejection spring contact portion 23 is disposed in the position close to the tube inserting opening 8.

[0113] In this embodiment, the ejection spring contact portion 23 is disposed between the tube inserting opening 8 and the electrical contact 4, more particularly between the tube inserting opening 8 and the positioning portion 6, and therefore, the ejection spring contact portion 23 is not remote from the tube inserting opening 8, the electrical contact 4 and the positioning portion 6. Therefore, in addition to the disconnection between the ink receiving tube 52 and the sealing member 19, the smooth disconnection is easily accomplished as to the engagement between the positioning portion 6 and the positioning pin 53 and as to the connection between the electrical contact 4 and the electrical connecting

portion 55.

[0114] In addition, as shown in Figure 2, in this embodiment, the electrical contacts 4 are provided on the front surface 2C on which the positioning portion 6 and the tube inserting opening 8 are also provided, and therefore, the positional deviation of the electrical contacts 4 in the plane of the front surface 2c can be suppressed.

[0115] Furthermore, as shown in Figure 2, in this embodiment, the positioning portion 6 is provided between the tube inserting opening 8 and the electrical contact 4, more particularly in the position closer to the electrical contact than to the tube inserting opening 8. Of the interface portions of the cartridge, the ones for which the highest positioning accuracy is required are electrical contacts 4, and the required positioning accuracy is higher in the electrical contacts 4 than in the tube inserting opening 8. On the other hand, the high precision positioning for the cartridge is effected by the positioning portion 6. Therefore, it is preferable that the positioning portion 6 is disposed adjacent to the electrical contact 4. In order to accomplish this, it is preferable that positioning portion 6 is provided in a position closer to the electrical contact than to the tube inserting opening 8. With such an arrangement, the electrical contact 4 can be positioned with high precision corresponding to the positioning precision provided by the positioning accuracy of the positioning portion 6, and therefore, the satisfactory electrical connection can be accomplished between the electrical contacts 4 and the electrical connecting portions 55.

[0116]

<Wide ink cartridge>

Figure 11 is a schematic view of an ink cartridge 1BK according to the first embodiment. The basic structures of the black ink cartridge 1BK shown in Figure 11 are substantially the same as the color ink cartridge 1M (1C,

1Y) shown in Figure 2. For example, the heights and the depths are the same, and the kinds, the arrangements and the arrangement widths of the cartridge interface portions are also the same.

[0117] A major difference between the black ink cartridge 1Bk and the color ink cartridge is that the width of the black ink cartridge 1Bk is larger than those of the color ink cartridges, and that the cartridge interface portions are offset to one side (more particularly to the right side) of the front surface. By the offset structure, the width of the cartridge interface portions of the black cartridge is the same as those of the color cartridges. By this, the size and the general structure of the joint unit 59 can be made common between the black and the other colors.

[0118]

<Modified example of the first embodiment>

The specific structures of the ink cartridge is merely an example of this embodiment, and this embodiment is not limited to the exemplary specific structures. It is possible to modify the structure of the ink cartridge of this embodiment in various aspects. Some of such modified examples will be described.

[0119]

(Arrangement of the electrical contacts on the substrate)

The arrangement of the electrical contacts (electrode pads) on the substrate of this embodiment is not limited to that shown in Figure 3. For example, the arrangement of the electrode pads shown in Figure 12 can be used in this embodiment.

[0120] In Figure 12, a plurality of electrode pads 61, 71 are arranged in the X axis direction (horizontal direction) on the XZ flat surface, similarly to Figure 3. In part (a) of Figure 12, the positions of the different electrode pads 61 are different in the Z axis direction, and in part (b) of Figure 12, the configurations of

different electrode pads 71 and the positions thereof in the Z axis direction are different. However, in these examples, the contact positions 61a, 71a relative to the electrical terminals 55 are arranged in the horizontal direction (X axis direction), similarly to Figure 3. Therefore, similarly to Figure 3, even if the movement of the ink cartridge in the θx direction occurs upon the mounting of the ink cartridge, the satisfactory electrical connection can be accomplished between the electrode pads 4 and the electrical terminals 55.

[0121]

(Configuration of the casing)

The configuration of the casing (body of the cartridge) 2 of this embodiment is not restricted to the rectangular parallelepiped shape shown in Figure 2. Depending on the internal function, the outer casing, the design or the structure of the cartridge mounting portion 33, a part or all of the surfaces constituting the casing 2 (upper surface, bottom surface, side surfaces) may include at least one of a pit-and-projection, a stepped portion, a cut-away portion, a bent portion and an inclined portion.

[0122] For example, as shown in part (a) of Figure 13, a part of the front surface 2c may be curved. In the example of part (a) of Figure 13, the electrical contact 4 is projected toward the front side beyond the opening (positioning opening) of the positioning portion 6, the through-opening 27 and the tube inserting opening 8, and the positioning opening 6 and the through-opening 27 are retracted toward the rear side beyond the tube inserting opening 8, and such a configuration is usable in this embodiment. In the example of part (a) of Figure 13, the substrate 3 is provided on the front surface 2c of the casing 2, similarly to Figure 3. In the example of part (a) of Figure 13, the plurality of electrical contacts are provided on the area of the substrate crossing with the cartridge mounting direction (cartridge depth direction), similarly to the example of Figure

3. Other examples are shown in part (b) and part (c) of Figure 13, in which a cut-away portion and/or recess is provided in a part of the front surface 2c, and the substrate 3 is provided in the cut-away portion or recess. In the example shown in Figure 13, the substrate 3 is provided directly on the front surface 2c including the tube inserting opening (8) formation region or indirectly thereon through a supporting member, and the electrical contacts 4 on the substrate include areas crossing with the direction parallel with the normal line of the tube inserting opening (8) formation region.

[0123]

10 (Mounting method of the substrate)

In the mounting method for mounting the substrate 3 usable in this embodiment, the substrate 3 is directly mounted on the casing 2 as shown in Figure 4, but the method is not restrictive to this embodiment, and the substrate 3 may be mounted to the casing 2 through another member. In a example, the substrate 3 is mounted on a substrate supporting member 81, and the substrate supporting member 81 is mounted on the casing 2, as shown in part (b) and part (c) of Figure 13. In part (b) of Figure 13, the casing 2 is cut away at a corner portion. The substrate 3 is provided on the substrate supporting member 81 having a configuration corresponding to the cut-away portion, and the substrate supporting member 81 is engaged with the cut-away portion to constitute an ink cartridge. As shown in part (b) of Figure 13, the cut-away portion also constitutes the front surface 2c of the casing. The cut-away portion is not flush with the front surface 2c provided with the tube inserting opening 8, and the structure is usable. In part (b) of Figure 13, the substrate 3 is mounted on the front surface 2c of the casing 2 through the substrate supporting member 81. The casing 2 shown in part (c) of Figure 13 is cut away into a rectangular parallelepiped shape at the part of the front surface of the casing, and similarly to

part (b) of Figure 13, the substrate supporting member 81 provided with the substrate 3 is engaged with the cut-away portion (recess). As shown in part (c) of Figure 13, the recess also constitutes the front surface 2c of the casing. Similarly, the substrate 3 is provided on the front surface 2c of the casing 2 through the substrate supporting member 81. As described, the substrate 3 may be electrically connected to the casing 2 and may be indirectly connected to the casing 2 through another member. In part (b) and part (c) of Figure 13, similarly to Figure 3, the substrate 3 is provided on the front surface 2c of the casing 2. In these examples of part (b) and part (c) of Figure 13, the plurality of contacts are provided on the substrate crossing with the mounting direction of the cartridge (cartridge depth direction), and this is the same as with Figure 3.

[0124]

(Surface on which electrical contacts are arranged)

The examples shown in Figure 2 and Figures 11, 13 in which the electrode pads 4 as the electrical contacts are arranged on the surface parallel with the front surface 2c (XZ surface), are merely preferable examples of this embodiment, and the surface on which the electrode pads 4 are provided is not limited to the XZ surface.

[0125] As described hereinbefore, in this embodiment, it will suffice if the

electrode pads 4 are provided in the position capable of connecting with the electrical terminals 55 shown in Figure 9 and Figure 10. For this purpose, the electrode pads 4 as the electrical contacts are preferably provided on (1) the surface / area crossing with the cartridge mounting direction, (2) the surface crossing with the Y axis direction, (3) the surface / area crossing with the cartridge depth direction, (4) the surface / area crossing with the direction parallel with the normal line of the formation surface / formation region of the tube inserting opening (ink discharge opening) 8, (5) the surface / area crossing with

the direction parallel with the extending direction of the tube insertion path (ink discharging path) 22, or (6) the surface / area crossing with the direction parallel with the center line of the tube inserting opening (ink discharge opening). The above-described (1) surface / area crossing with the cartridge mounting direction,

5 (2) surface / area crossing with the Y axis direction, (3) surface / area crossing with the cartridge depth direction, (4) surface / area crossing with the direction parallel with the normal line of the formation surface / formation region of the tube inserting opening (ink discharge opening) 8, (5) surface / area crossing with the direction parallel with the extending direction of the tube insertion path (ink

10 discharging path) 22, and (6) surface / area crossing with the direction parallel with the center line of the tube inserting opening (ink discharge opening) are not limited to the XZ surface, but includes a surface inclined relative to the XZ surface. The electrical contact 4 is preferably provided with (1) the area crossing with the cartridge mounting direction, (2) the area crossing with the Y

15 axis direction, (3) the area crossing with the cartridge depth direction, (4) the area crossing with the direction parallel with the normal line of the tube inserting opening (ink discharge opening) 8 formation surface, (5) the area crossing with the direction parallel with the extending direction of the tube insertion path (ink discharging path) 22, or (6) the area crossing with the direction parallel with the

20 center line of the tube inserting opening (ink discharge opening).

[0126]

[Second embodiment]

Referring to Figure 14 and 15, an ink cartridge according to a second embodiment will be described. This embodiment is different from the first

25 embodiment mainly in the structure of the tube insertion path 22, the structure of the air vent path 16, the position of the air vent sealing film 17 and the structure of the connecting portion between the air vent path 16 and the ink

accommodating chamber 11, and the other structures of this embodiment are substantially the same as of the first embodiment. Therefore, in the description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

[0127]Figure 14 shows the internal structure of the ink cartridge of the second embodiment, in which (a) is a view of the ink cartridge as seen in the X axis direction, and (b) is a view of the ink cartridge as seen from the rear side in the Y axis direction. Figure 15 shows the process of mounting of the ink cartridge into the mounting portion in the second embodiment, in which (a) shows the initial state of the insertion, and (b) shows the final stage in which the insertion is completed.

[0128]

<Internal structure of the ink cartridge>

(Structure of the tube insertion path)

As shown in Figure 14, the tube inserting opening 8 is provided on the front surface 2c of the casing 2 in the neighborhood of the bottom surface. The tube inserting opening 8 is disposed at one end portion of a tube insertion path 22, and the other end portion of the tube insertion path 22 is connected to the ink accommodating chamber 11. The tube insertion path 22 is provided with a sealing member 74 of elastic member (annular rubber member, for example), the valve 75 movable between a position for contacting to the sealing member 74 and the position spaced away from the sealing member 74, and a spring 76 for urging the valve 75 toward the sealing member 74. The outer peripheral surface of the sealing member 74 is in close contact with the inner surface of the tube insertion path 22. In the state that an ink receiving tube 52 is not yet inserted into the tube insertion path 22, the valve 75 contacts with the sealing member 74 to seal

the opening of the sealing member 74. Therefore, the tube insertion path 22 is isolated from the sealing member 74 by the valve 75, and the fluid communication between the ink accommodating chamber 11 and the outside is not established. When the ink receiving tube is inserted into the tube insertion path 22 through the tube inserting opening 8, the valve 75 is moved in the direction of compressing the spring 76 to space the valve 75 from the sealing member 74, so that the fluid communication between the ink receiving tube 52 and the ink accommodating chamber 11 is established, and the inner surface of the sealing member 74 contacts to the outer peripheral surface of the ink receiving tube 52 to prevent the leakage of the ink. By the insertion of the ink receiving tube 52 into the tube insertion path 22, the ink in the ink accommodating chamber 11 can be supplied into the ink receiving tube 52.

[0129]

(Structure of the connecting portion between air vent path and ink accommodating chamber)

As shown in Figure 14, one end portion of the air vent path 16 is provided with an air vent 7, and the other end portion of the air vent path 16 is connected with the ink accommodating chamber 11. The air vent sealing film 17 sealing the air vent 7 is mounted to the front surface 2c which is an outer wall surface of the casing 2, and is a member separate from a flexible member 12. In the connecting portion between the air vent path 16 and the ink accommodating chamber 11, there is provided an interrelation valve 77 capable of opening and closing in interrelation with movement of a plate member 14, and when the interrelation valve 77 is opened, the air vent path 16 and the ink accommodating chamber 11 is brought into fluid communication with each other. More particularly, when the ink amount in the ink accommodating chamber 11 is not less than a predetermined amount, the interrelation valve 77 is in the closed

position as shown in part (b) of Figure 14, so that the ink accommodating chamber 11 is not in fluid communication with the air vent path 16. The plate member 14 is constituted such that it moves toward the left surface 2e with consumption of the ink, and the ink amount in the ink accommodating chamber

5 11 becomes less than the predetermined amount, the plate member 14 pushes the interrelation valve 77 to open it. By this, the ink accommodating chamber 11 and the air vent path 16 are brought into fluid communication with each other. In the fluid communication state, the ambient air is introduced into the ink accommodating chamber 11 through the air vent path 16 corresponding to the

10 amount of the ink consumption from the ink accommodating chamber 11, and therefore, the negative pressure in the ink accommodating chamber 11 does not become too high. Therefore, it can be avoided that the ink supply from the ink accommodating chamber 11 to the outside is impeded as a result of the too high negative pressure inside the ink accommodating chamber 11, and therefore, most

15 of the ink can be used up out of the ink accommodating chamber.

[0130]

<Mounting operation and dismounting operation of ink cartridge>

The mounting operation of the ink cartridge in this embodiment is as shown in Figure 15, and it is substantially similar to the mounting operation in

20 the first embodiment shown in Figure 10.

[0131] As shown in part (a) of Figure 15, the ink cartridge 1 is inserted along the inside of the mounting guide 50 to contact to the ejection spring 57. When the ink cartridge 1 is further inserted, the recess of the discrimination portion 9 of the ink cartridge 1 is checked in effect as to whether or not it meets the projection

25 of the discrimination member 60 of the mounting portion 33, and if so, the cartridges is further inserted toward the rear side. Then, the tube inserting opening sealing film 18 is unsealed by the free end of the ink receiving tube 52,

and the ink receiving tube 52 is inserted into the tube inserting opening 8. The positioning pin 53 is inserted into the positioning portion 6, and thereafter, the air vent sealing film 17 is unsealed by the unsealing pin 51, and the unsealing pin 51 is inserted into the air vent 7. Subsequently, the ink receiving tube 52 is inserted
5 into the opening of the sealing member 74 provided in the tube insertion path 22 to push the valve 75, so that the ink accommodating chamber 11 and the ink receiving tube 52 are brought into fluid communication with each other. Then, the electrical contact contacts to the electrical connecting portion 55, and finally, the engaging portion 24 is engaged with the locking projection 54 of the locking
10 lever 58, and the mounting operation is completed (part (b) of Figure 15)

[0132] As described, in the second embodiment, too, similarly to the first embodiment, the cartridge side interface portions are properly connected with the printer main assembly side interface portions.

[0133]

15 <Modified example of second embodiment>

The structures of this embodiment shown in Figure 14 is different from the first embodiment in the four structures (the structure of the tube insertion path, the structure of the air vent path, the position of the air vent sealing film and the structure of the connecting portion between the air vent path
20 and the ink accommodating chamber), but this embodiment is not restricted to such structures. For example, only the structure of the tube insertion path 22 may be different from that of the first embodiment, or only the structure of the connecting portion between the air vent path 16 and the ink accommodating chamber 11 may be different from the first embodiment. In addition, at least
25 one of the structures of the four structures (one, two or three of the structures) may be different from the first embodiment, and such modifications are within the modified examples of this embodiment.

[0134]

[Third embodiment]

Referring to Figures 16 - 19, a third embodiment will be described.

The ink cartridge 1801 according to the third embodiment is substantially the same as the first embodiment except that the size of the casing is different from that of the first embodiment. More particularly, the ink cartridge 1801 according to the third embodiment is provided with the cartridge side interface portions such as the tube inserting opening 8, the electrical contacts, the positioning portion 6 and the engaging portion 24, similarly to the ink cartridge 1 of the first embodiment. The positional relationship among the cartridge side interface portions in the third embodiment are common with the positional relationships among the cartridge side interface portions in the first embodiment at least in the following points (1) - (4). (1) the tube inserting opening 8 is disposed in a position closer to the bottom surface than to the upper surface, on the front surface of the casing. (2) the electrical contact 4 is disposed in a position above the tube inserting opening 8. (3) the positioning portion 6 is disposed in a position above the tube inserting opening 8 and below the electrical contact 4. (4) the engaging portion 24 is provided on the upper surface of the casing. In the description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

[0135]

<Structure of ink cartridge >

Figure 16 shows a schematic structure of the ink cartridge 1801 according to the third embodiment, in which (a) is a perspective view of an outer appearance of the ink cartridge 1801, and (b) shows an inside structure of the ink

cartridge 1801. Figure 9 is a perspective view illustrating a connection relation between the ink cartridge 1801 and a joint unit 59 taken out of the cartridge mounting unit. As will be understood from Figure 17, the joint unit 59 of the third embodiment is the same as the joint unit 59 of the first embodiment.

5 Therefore, the structure, the positional relation and the size of the cartridge side interface portions connectable with the joint unit 59 as the printer main assembly side interface portions are the same as those of the first embodiment. More particularly, the structure, the positional relation and the sizes the electrical contact, the positioning hole 6, the through-opening 27, the tube inserting
 10 opening 8 and the discrimination portion 9 provided on the front surface 1802c of the ink cartridge 1801 in the third embodiment are the same as those of the electrical contact, the positioning hole 6, the through-opening 27, the tube inserting opening 8 and the discrimination portion 9 provided on the front surface 2c of the ink cartridge 1 in the first embodiment. Therefore, in designing both
 15 of the ink cartridge 1 (Figure 9) of the first embodiment and the ink cartridge 1801 (Figure 17) of the third embodiment, the joint unit 59 as the printer main assembly side interface portion may be common, and the cost of the joint unit 59 can be reduced. In addition, the structure, the positional relation and the size of the cartridge side interface portions such as the electrical contacts 4, the
 20 positioning hole 6, the through-opening 27, the tube inserting opening 8 and the discrimination portion 9 may be common, and therefore, the design load of the ink cartridge can be reduced.

[0136] As will be understood from Figures 16 and 17, the ink cartridge 1801 is provided with a rectangular parallelepiped shape casing 1802 including an ink
 25 accommodating chamber 11 therein. The casing 1802 includes an upper surface 1802a, a lower surface (bottom surface) 1802b, a plurality of side surfaces 1802c - 1802f. The side surfaces include a front surface (front side) 1802c as a first

side surface, a rear surface (rear side) 1802d as a second side surface, a left surface 1802e as a third side surface connecting the first side surface and the second side surface with each other, and a right-hand surface 1802f as a fourth side surface connecting the first side surface and the second side surface with each other.

[0137] The size of the casing 1802 is larger than that of the casing 2 of the first embodiment. More particularly, the size (height) of the casing 1802 in the Z axis direction is larger than that of the casing 2 of the first embodiment, and the size (depth) of the casing 1802 in the Y axis direction is larger than that of the casing 2 of the first embodiment. For example, in the example of the sizes of the casing 1802, the height is approx. 7.8 cm, the depth is approx. 9.5 cm which are larger than the height of approx. 4.7 cm and the depth of approx. 8.4 cm of the casing 2 of the first embodiment, respectively. On the other hand, the size (width) of the casing 1802 measured in the X axis direction is the same as that of the casing 2 of the first embodiment (approx. 1.6 cm, for example). The specific dimensions are merely preferable examples, and this embodiment is not limited to such dimensions.

[0138] The casing 1802 has a generally rectangular parallelepiped shape having six major sides. The left surface 2e and the right-hand surface 2f of the 6 surfaces have the maximum area, and the front surface (front side) 2c and the rear surface (rear side) 2d have the minimum area. The relationship of the areas of the six sides is the front surface 2c and the rear surface 2d < upper surface 2a and the lower surface (bottom surface) 2b < the left surface 2e and right-hand surface 2f. The areas of the left surface 2e and the right-hand surface 2f are approx. 74.10 (=7.8x9.5) cm². The areas of the upper surface 2a and the lower surface 2b are approx. 15.20 (=1.6x9.5) cm². The areas of the front surface (front side) 2c and the rear surface (rear side) is each approx. 12.48 (=1.6x7.8) cm².

[0139] As described above, the positional relation in the cartridge side interface portions are the same as that of the first embodiment, and for example, the tube inserting opening 8, the through-opening 27, the positioning hole 6 and the substrate 3 are disposed in the order named from the bottom side toward the upper side. However, as contrasted to the ink cartridge 1 of the first embodiment, in the ink cartridge 1801 according to the third embodiment, the electrical contacts 4 are disposed in the neighborhood of the center of the front surface 1802c in the height direction. More particularly, the electrical contacts are disposed slightly above the center portion of the front surface 1802c with respect to the height direction. That is, the electrical contacts 4 are disposed on the positions in an upper side of the front surface 1802c (the portion above the center with respect to the height direction) and closer to the center portion than to the upper surface. With such a structure, the relative positional relationship between the tube inserting opening 8, the electrical contact and the engaging portion 24 are the same as that of the first embodiment. More particularly, even if the electrical contacts 4 are provided adjacent to the neighborhood of the center of the front surface 1802c, the engaging portion 24 it is still disposed in the position closer to the electrical contacts 4 than to the tube inserting opening 8, and therefore, the advantageous effects of the first embodiment are provided. In the third embodiment, the engaging portion 24 is provided on the upper surface 1802a (more particularly, the position closer to the front surface 1802a than to the rear surface 1802d on the upper surface 1802a) in order to dispose engaging portion 24 in the position closer to the electrical contact than to the tube inserting opening 8, but the structure for disposing the engaging portion 24 to the position closer to the electrical contact than to the tube inserting opening 8 is not limited to the above-described structure.

[0140] In addition, in the third embodiment, the positioning portion 6 is

disposed in the position closer to the electrical contact than to the tube inserting opening 8, similarly to the first embodiment, and therefore, the advantageous effects similar to those of the first embodiment in this respect are provided in the third embodiment. Similarly to the first embodiment, the electrical contacts 4
 5 are arranged along the X axis direction in the third embodiment, and therefore, the same advantageous effects similar to the first embodiment in this respect can be provided in the third embodiment.

[0141]

<Mounting operation and dismounting operation of ink cartridge>

10 The mounting operation of the ink cartridge 1801 in the third embodiment is shown in Figure 18 and is almost the same as the mounting operation in the first embodiment. The ink cartridge 1801 of the third embodiment is taller than the ink cartridge 1 of the first embodiment, and therefore, the locking lever 58 is at a higher position, correspondingly. The
 15 mounting guide and the inside space of the mounting portion 33 in the third embodiment are larger than those in the first embodiment, but the functions of the mounting portions of these embodiments are the same, and the detailed description is omitted for the sake of simplicity.

[0142] As shown in part (a) of Figure 18, the ink cartridge 1801 is inserted
 20 along the inside of the mounting guide 50 to contact to the ejection spring 57. When the ink cartridge 1801 is further inserted, the recess of the discrimination portion 9 of the ink cartridge 1 is checked in effect as to whether or not it meets the projection of the discrimination member 60 of the mounting portion 33, and if so, the cartridges is further inserted toward the rear side. Then, the tube
 25 inserting opening sealing film 1801 is unsealed by the free end of the ink receiving tube 52, and the ink receiving tube 52 is inserted into the tube inserting opening 8. The positioning pin 53 is inserted into the positioning portion 6, and

thereafter, the air vent sealing film 17 is unsealed by the unsealing pin 51, and the unsealing pin 51 is inserted into the air vent 7. Subsequently, the ink receiving tube 52 is inserted into the slit of the sealing member 74 provided in the tube insertion path 22 to push the valve 75, so that the ink accommodating chamber 11 and the ink receiving tube 52 are brought into fluid communication with each other. Then, the electrical contact contacts to the electrical connecting portion 55, and finally, the engaging portion 24 is engaged with the locking projection 54 of the locking lever 58, and the mounting operation is completed (part (b) of Figure 18) .

10 **[0143]** As described, in the third embodiment, too, similarly to the first embodiment, the cartridge side interface portions are properly connected with the printer main assembly side interface portions.

[0144]

<Wide ink cartridge> <

15 Figure 19 is a schematic view of an ink cartridge 1801BK of the third embodiment. The basic structures of the black ink cartridge 1801BK shown in Figure 19 are substantially the same as the color ink cartridge 1801 shown in Figure 16. For example, the heights and the depths are the same, and the kinds, the arrangements and the arrangement widths of the cartridge interface portions are also the same.

20 **[0145]** A major difference between the black ink cartridge 1801Bk and the color ink cartridge 1801 is that the width of the black ink cartridge 1801Bk is larger than those of the color ink cartridges, and that the cartridge interface portions are offset to one side (more particularly to the right side) of the front surface. By the offset structure, the width of the cartridge interface portions of the black cartridge is the same as those of the color cartridges. By this, the size and the general structure of the joint unit 59 can be made common between the

black and the other colors.

[0146]

[Fourth embodiment]

Referring to Figure 20, a fourth embodiment will be described.

5 Figure 20 is a schematic view schematically showing the structure of the ink cartridge of this embodiment, which is characterized in the structure of an engaging portion 224. This embodiment is different from the first embodiment only in the structure of the engaging portion, and the other structures are substantially the same as those of the first embodiment. Therefore, in the
10 description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

[0147] In the foregoing embodiments, in order to provide the engaging portion 24 in the position closer to the electrical contact than to the tube inserting opening
15 8, the engaging portion 24 is placed on the upper surface of the casing, but the structure of placing the engaging portion 24 in the position closer to the electrical contact than to the tube inserting opening 8 is not limited to the structures of the foregoing embodiments. The engaging portion may be disposed in the position closer to the electrical contact than to the tube inserting opening 8, by placing the
20 engaging portion in a portion different from the upper surface of the casing. In order to place the engaging portion 24 in the position closer to the electrical contact 4 than to the tube inserting opening 8, it is preferable that the engaging portion is placed in a position closer to the upper surface than to the bottom surface.

25 **[0148]** As shown in Figure 20, a second casing member (closing member) 41 constituting a right-hand surface 2f of the casing is provided with the engaging portion 224. More particularly, the engaging portion 224 is in the form of a

projection extending from the right-hand surface 2f in the X axis direction (widthwise direction perpendicular to the right-hand surface). The projection 224 includes a side which is an area 224a crossing with the cartridge mounting direction (Y axis direction), and at least a part of the area 224a contacts to the locking projection 54 of the locking lever 58 so that the engaging portion 124 and the locking projection 54 are engaged with each other. Similarly to the area 24a of the engaging recess 24 shown in Figure 5, the contact region 224a of the engaging portion 224 is the area crossing with the direction parallel with the normal line of the electrical contact 4 or the normal line of the area on the substrate 3 on which the electrical contacts 4 are provided, and particularly in this embodiment, the area 224a is perpendicular to the direction parallel with the normal line. The area 224a is an area crossing with the direction parallel with the normal line of the formation surface of the ink discharge opening 8 and is an area crossing with the direction parallel with the direction in which the ink discharging path 22 extends. Furthermore, the area 224a is an area crossing with the direction parallel with the center line of the ink discharge opening 8 (a phantom line passing through the center of the ink discharge opening 8).

[0149] In this embodiment, the engaging portion is provided in a portion different from the upper surface of the casing, as shown in Figure 20, but the present invention is not limited to such a structure. For example, the engaging portion may be provided in the position used in a fifth embodiment or a sixth embodiment which will be described hereinafter. Similarly to this embodiment, the engaging portion is disposed in a position closer to the upper surface than to the lower the surface also in the fifth embodiment and the sixth embodiment which will be described hereinafter.

[0150] As will be understood from the description of this embodiment, the engaging portion used in the present invention is not limited to the recess

configuration, but it may be a projected configuration as shown in Figure 20.

[0151]

[Fifth embodiment]

Referring to Figures 21 - 22, a fifth embodiment will be described.

5 This embodiment is different from the first embodiment only in the structure of the engaging portion and the configuration of the casing, and the major structures in the other aspects of this embodiment are substantially the same as first embodiment. Therefore, in the description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having
10 the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity. Corresponding to the difference in the configuration of the casing, the internal structures (the configuration of the ink accommodating chamber, the configuration of the air vent path, for example) are different, but the functions are the same despite the difference in the
15 configuration, and therefore, the description of the internal structures will be omitted.

[0152]Figure 21 schematically shows the structure of the ink cartridge 301 of the fifth embodiment, in which (a) is a perspective view of the outer appearance of the ink cartridge 301, and (b) shows the internal structure of the ink cartridge 301
20 as seen from the right-hand surface side along the X axis direction. As shown in Figure 21, the configuration of the casing 2 is peculiar, that is, the upper surface 2a is small, and the rear surface 2d is constituted by a curved surface and an inclined surface. An area of a part of the rear surface 2d functions as an engaging portion 324. More particularly, the inclined surface or the curved
25 surface of the rear surface 2d adjacent to the upper surface constitutes the engaging portion 324. The engaging portion 324 is closer to the upper surface 2a than to the bottom surface 2b.

[0153] The mounting operation of the ink cartridge 301 of the fifth embodiment is shown in Figure 22, and is almost the same as the mounting operation in the first embodiment shown in Figure 10. Therefore, the detailed description is omitted, but briefly, the engaging portion 324 is engaged with the locking
5 projection 54 of the locking lever 58 as shown in Figure 22. As will be understood from the foregoing, the engaging portion usable in the ink cartridge of the present invention is not limited to the recesses used in the first-third embodiments or to the projection used in the fourth embodiment, but may be a curved surface or an inclined surface. In addition, the position of the engaging
10 portion is not limited to the upper surface 2a of the casing 2 as shown in Figure 2 or to the side surface 2f of the casing 2 as shown in Figure 20, but it may be a rear surface 2d of the casing 2 of this embodiment as shown in Figure 21.

[0154] Similarly to the area 24a shown in Figure 5 or the area 224a shown in Figure 20, the inclined surface or the curved surface constituting the engaging
15 portion 324 crosses with the direction parallel with the normal line of the electrical contact 4 or the normal line of the area on the substrate 3 on which the electrical contact 4 is provided, and particularly in this embodiment, the engaging portion 324 is perpendicular to the direction parallel with the normal line. The engaging portion 324 crosses with the direction parallel with the normal line of
20 the formation surface of the ink discharge opening 8 and crosses with the direction parallel with the extending direction of the ink discharging path 22. Furthermore, the engaging portion 324 crosses with the direction parallel with the center line of the ink discharge opening 8 (phantom line passing through the center of the ink discharge opening 8).

25 **[0155]**

[Sixth embodiment]

Referring to Figures 23 - 24, a sixth embodiment will be described.

This embodiment is different from the first embodiment only in the structure of the engaging portion and the configuration of the casing, and the major structures in the other aspects of this embodiment are substantially the same as first embodiment. Therefore, in the description of this embodiment, the same
5 reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity. Corresponding to the difference in the configuration of the casing, the internal structures (the configuration of the ink accommodating chamber, the configuration of the air vent path, for example) are
10 different, but the functions are the same despite the difference in the configuration, and therefore, the description of the internal structures will be omitted.

[0156]Figure 23 schematically shows the structure of the ink cartridge 401 of the sixth embodiment, in which (a) is a perspective view of the outer appearance of
15 the ink cartridge 401, and (b) shows the internal structure of the ink cartridge 401 as seen from the right-hand surface side along the X axis direction. In Figure 23, the configuration of the casing 2 is peculiar, and the upper surface 2a and the rear surface 2d a small, and there is provided a connection region 2 g connecting the upper surface 2a and the rear surface 2d. A part of the connection region 2 g
20 functions as the engaging portion 424. More particularly, the connection region 2 g includes a first area which is connected with the upper surface 2a and which extends substantially in parallel with the front surface 2c, and a second area which is connected with the rear surface 2d and which extends substantially in parallel with the bottom surface 2b, in which a flat surface portion which is
25 adjacent to the upper surface and which is a part of the first area functions as the engaging portion 424. The engaging portion 424 is in the position closer to the upper surface 2a than to the bottom surface 2b.

[0157] The mounting operation of the ink cartridge 401 in the sixth embodiment is shown in Figure 24, and is almost the same as the mounting operation in the first embodiment shown in Figure 10. Therefore, the detailed description is omitted, but briefly, the engaging portion 424 is engaged with the locking projection 54 of the locking lever 58 as shown in Figure 242. As will be understood, the engaging portion of the ink cartridge usable in the present invention is not limited to the recesses used in the first-third embodiments or to the curved surface, the projection used in the fourth embodiment or the inclined surface used in the fifth embodiment. The position of the engaging portion is not limited to the upper surface 2a of the casing 2 as shown in Figure 2, the side surface 2f of the casing 2, the rear surface 2d of the casing 2 as shown in Figure 20, but it may be that connection region 2 g between the upper surface 2a and the rear surface 2d of the casing 2 of this embodiment as shown in Figure 23.

[0158] Similarly to the area 24a shown in Figure 5 and the area 224a shown in Figure 20, the surface constituting the engaging portion 424 crosses with the direction parallel with the normal line of the electrical contact 4 or the normal line of the area on the substrate 3 on which the electrical contact 4 is provided. The engaging portion 424 crosses with the direction parallel with the normal line of the formation surface of the ink discharge opening 8 and crosses with the direction parallel with the extending direction of the ink discharging path 22. Furthermore, the engaging portion 424 crosses with the direction parallel with the center line of the ink discharge opening 8 (phantom line passing through the center of the ink discharge opening 8).

[0159]

[Seventh embodiment]

Referring to Figures 25 - 26, a seventh embodiment will be described. This embodiment is different from the first embodiment only in the structure of

the engaging portion, and the major structures in the other aspects of this embodiment are substantially the same as first embodiment. Therefore, in the description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

[0160]Figure 25 schematically shows the structure of the ink cartridge 501 of the seventh embodiment, in which (a) is a perspective view of the outer appearance of the ink cartridge 501, and (b) shows the internal structure of the ink cartridge 501 as seen from the right-hand surface side along the X axis direction. As

shown in Figure 25, the engaging portion 524 in the form of a projection is provided on the upper surface 2a of the casing 2. More particularly, the engaging portion 524 is a projection having a pentahedron shape in the form of a horizontal triangular prism. The projection 524 includes a side which is an area 524a crossing with the cartridge mounting direction (Y axis direction), and at least a part of the area 524a contacts the locking projection 54 of the locking lever 58 so that the engaging portion 124 and the locking projection 54 of the locking lever 58 are engaged. Similarly to the area 24a of the engaging recess 24 shown in Figure 5, the contact region 524a of the engaging portion 524 is the area crossing with the direction parallel with the normal line of the electrical contact 4 or the normal line of the area on the substrate 3 on which the electrical contacts 4 are provided, and particularly in this embodiment, the area 524a is perpendicular to the direction parallel with the normal line. The area 524a is an area crossing with the direction parallel with the normal line of the formation surface of the ink discharge opening 8 and is an area crossing with the direction parallel with the direction in which the ink discharging path 22 extends. Furthermore, the area 524a is an area crossing with the direction parallel with the center line (a phantom line passing through the center of the ink discharge

opening 8) of the ink discharge opening 8.

[0161] The mounting operation of the ink cartridge 501 in the seventh embodiment is shown in Figure 26, and it is almost the same as the mounting operation in the first embodiment shown in Figure 10. Therefore, only the relationship between the engaging portion 524 and the locking lever 58 will be described. When the ink cartridge 501 placed in the position indicated in part (a) of Figure 26 further enters in the mounting direction (Y axis direction), the engaging portion 524 pushes up the locking projection side of the locking lever 58 by the contact with the locking projection 54. When the ink cartridge 701 further enters to the point where the engaging portion 524 is downstream of the locking projection 54 with respect to the mounting direction, the area 524a of the engaging portion 524 is engaged with the locking projection 54 as shown in part (b) of Figure 26. Thus, the mounting of the ink cartridge 501 is completed. As described above, the engaging portion usable with the ink cartridge of the present invention is not limited to the recess shown in the first - third embodiments of the present invention, the projection used in the fourth embodiment, the curved surface or inclined surface used in the fifth embodiment, the flat surface of the sixth embodiment, or the like.

[0162]

[Eighth embodiment]

Referring to Figures 27 - 28, an eighth embodiment will be described. This embodiment is different from the first embodiment only in the structure of the engaging portion, and the major structures in the other aspects of this embodiment are substantially the same as first embodiment. Therefore, in the description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

[0163] Figure 27 schematically shows the structure of the ink cartridge 601 of the eighth embodiment, in which (a) is a perspective view of the outer appearance of the ink cartridge 601, and (b) shows the internal structure of the ink cartridge 601 as seen from the right-hand surface side along the X axis direction. An

5 engaging portion 624 is a movable member provided on the upper surface 2a of the casing 2. More particularly, the engaging portion 624 includes an elastically deformable lever supported by the upper surface 2a of the casing 2 so that a projection 624a extending in the Z axis direction is movable toward the upper surface 2a of the casing 2. By the projection 624a engaging with a locking

10 projection 54 of the locking lever 58, the engaging portion 624 engages with the locking lever 58. Similarly to the area 24a of the engaging recess 24 shown in Figure 5, the projection 624a crosses with a direction parallel with the normal line of the electrical contact 4 or the normal line of the area on the substrate 3 on which the electrical contact 4 is provided, and more particularly, in this

15 embodiment the projection 624a is perpendicular to the direction parallel with the normal line. The projection 624a is a portion crossing with the direction parallel with the normal line of the ink discharge opening (8) formation surface, and is also a station crossing with the direction parallel with the extending direction of the ink discharging path 22. Furthermore, the projection 624a is a portion

20 crossing with the direction parallel with the center line of the ink discharge opening 8 (phantom line passing through the center of the ink discharge opening 8).

[0164] The mounting operation of the ink cartridge 601 according to the eighth embodiment is shown in Figure 28, and is almost the same as the mounting

25 operation in the first embodiment shown in Figure 10. Therefore, only the relationship between the engaging portion 624 and the locking lever 58 will be described. When the ink cartridge 601 placed in the position shown in part (a)

of Figure 28 advances in the mounting direction (Y axis direction), the projection 624a contacts to the locking projection 54 to raise a locking projection side of the locking lever 58. When the ink cartridge 601 further advances, and projection 624a becomes downstream of the locking projection 54 with respect to the mounting direction, the engaging portion 624 is pushed down by the locking projection 54 at this position, and as shown in part (b) of Figure 28, the projection 624a of the engaging portion 624 is engaged with the locking projection 54 of the locking lever 58. Thus, the mounting of the ink cartridge 601 is completed.

As will be understood from the foregoing, the engaging portion usable with the ink cartridge according to the present invention is not limited to a stationary (non-movable) engaging portion used in the first-seventh embodiments.

[0165]

[Ninth embodiment]

Referring to Figures 29 - 30, a ninth embodiment will be described.

This embodiment is different from the first embodiment only in the structure of the engaging portion, and the major structures in the other aspects of this embodiment are substantially the same as first embodiment. Therefore, in the description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

[0166] Figure 29 schematically shows the structure of the ink cartridge 701 of the ninth embodiment, in which (a) is a perspective view of the outer appearance of the ink cartridge 701, and (b) shows the internal structure of the ink cartridge 7601 as seen from the right-hand surface side along the X axis direction. The engaging portion 724 is a member movable relative to the front surface 2c of the casing 2a, and is provided on the upper surface 2a of the casing 2. The movable engaging portion 724 is urged by a spring 725 as an elastic portion in -A direction,

and is movable in the -A and +A directions by the expansion and contraction of the spring 725. The spring 725 functions as engaging portion moving means for moving the engaging portion 724 relative to the casing 2. Similarly to the area 24a of the engaging recess 24 shown in Figure 5, the engaging portion 724 crosses with the direction parallel with the normal line of the electrical contact 4 or the normal line of the area on the substrate 3 on which the electrical contact 4 is provided, and particularly in this embodiment, the engaging portion 724 is perpendicular to the direction parallel with the normal line.

[0167] The mounting operation of the ink cartridge 701 according to the ninth embodiment is shown in Figure 30, and is almost the same as the mounting operation in the first embodiment shown in Figure 10. Therefore, only the relationship between the engaging portion 724 and the locking lever 58 will be described. In the state that the engaging portion 724 does not contact the locking projection 54 (non-engagement state), the spring 725 is expanded as shown in part (a) of Figure 30. When the ink cartridge 701 advances in the mounting direction (Y axis direction), the engaging portion 724 contacts to the locking projection 54 so that they are brought into engagement with each other, as shown in part (b) of Figure 30. In the engagement state, the spring 725 is in the compressed state. The position of the engaging portion 724 in part (b) of Figure 30 is closer to the front surface 2c or electrical contact 4 than the position of the engaging portion 724 in part (a) of Figure 30.

[0168]

[Tenth embodiment]

Referring to Figure 31, a tenth embodiment will be described. This embodiment is different from the first embodiment only in the disposition of the substrate having the electrical contacts, and the major structures in the other aspects of this embodiment are substantially the same as first embodiment.

Therefore, in the description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

5 **[0169]** Figure 31 schematically shows the structure of the ink cartridge 801 of the tenth embodiment, in which (a) is a perspective view of the outer appearance of the ink cartridge 801, and (b) shows the internal structure of the ink cartridge 801 as seen from the right-hand surface side along the X axis direction. As will be understood from Figure 31, the substrate 3 is provided on an inclined surface
10 2h connecting the upper surface 2a and the front surface 2c. More particularly, the electrical contact 4 on the substrate 3 has an area crossing with the Y axis direction so as to be electrically connectable to the main assembly side electrical connecting portion 55, and the area is inclined relative to both of the upper surface 2a and the front surface 2c. With this structure of Figure 31, the
15 electrical contact 4 has the area crossing with the cartridge inserting direction (Y axis direction), and therefore, the electrical contact 4 is not provided on a surface parallel with the Y axis direction, and the amount of rubbing between the electrical contact 4 and the main assembly side electrical connecting portion 55 upon the insertion of the ink cartridge 801 can be suppressed. Furthermore,
20 similarly to the first embodiment, the plurality of electrical contacts 4 are arranged along the widthwise direction (X axis direction) of the ink cartridge 1101, and therefore, the same advantageous effects as of the first embodiment are provided. As will be understood from the description of this embodiment, the structures of the substrate 3 and the electrical contacts 4 of the ink cartridge
25 according to the present invention are not limited to the structure in which they are provided on the front surface 2c as in the first-ninth embodiments.

[0170] The electrical contact 4 shown in Figure 31 has (1) a area crossing with

the cartridge inserting direction (mounting direction), (2) a area crossing with the Y axis direction, (3) a area crossing with the cartridge depth direction, (4) a area crossing with the direction parallel with the normal line of the tube inserting opening 8 (ink discharge opening) the formation surface, (5) a area crossing with the direction parallel with the extending direction of the tube insertion path (ink discharging path) 22, and (6) a area crossing with the direction parallel with the center line of the tube inserting opening (ink discharge opening) 8. The substrate 3 shown in Figure 31 has (1) a surface crossing with the cartridge inserting direction (mounting direction), (2) a surface crossing with the Y axis direction, (3) a surface crossing with the cartridge depth direction, (4) a surface crossing with the direction parallel with the normal line of the tube inserting opening 8 (ink discharge opening) formation surface, (5) a surface crossing with the direction parallel with the extending direction of the tube insertion path (ink discharging path the 22, and (6) a surface crossing with the direction parallel with the center line of the tube inserting opening (ink discharge opening) 8.

[0171]

[Eleventh embodiment]

Referring to Figures 32 - 33, an eleventh embodiment will be described. This embodiment is different from the first embodiment only in the structure of supporting the substrate having the electrical contacts, and the major structures in the other aspects of this embodiment are substantially the same as first embodiment. Therefore, in the description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

[0172] Figure 32 schematically illustrates the structure of the ink cartridge 901 of the eleventh embodiment. The substrate 3 provided with the electrical

contacts 4 is urged in the direction indicated by +A by a spring as an elastic member 937, and is movable in the directions +A and -A by the expansion and contraction of the spring 937. The spring 937 functions as a substrate moving means for moving the substrate 3 relative to the casing. The spring 937 is

5 positioned by a projection 936 provided on the back side of the substrate 3 and a projection 938 provided on the front wall of the casing 2. In the state that the ink cartridge 901 is not mounted to the mounting portion 33 (non-use state of the ink cartridge), the spring 937 is in the expanded state, as shown in part (a) of Figure 32. On the other hand, in the state that the ink cartridge 901 is mounted

10 in the mounting portion 33, the spring 937 is in the compressed state as shown in part (b) of Figure 32, and the substrate 3 retracts toward the rear side beyond the front surface 2c correspondingly to the compression of the spring 937.

[0173] Figure 33 shows of the process in which the ink cartridge 901 of the eleventh embodiment is inserted into the mounting portion 33, in which a (a)

15 shows an initial state of insertion, and on (b) shows the insertion completed state. The mounting operation in this embodiment is shown in Figure 33, and is almost the same as the mounting operation in the first embodiment shown in Figure 10. Therefore, only the expansion and contraction of the spring 937 and the movement of the substrate 3 will be described. In the state the electrical contact

20 on the substrate 3 is not contacted with the main assembly side electrical connecting portion 55, as shown in part (a) of Figure 33, the spring 937 is in the expanded state. When the ink cartridge 901 is inserted from the position shown in part (a) of Figure 33 to the position shown in part (b) of Figure 33, the electrical contact 4 contacts to the main assembly side electrical connecting

25 portion 55. The cartridge 901 is further inserted toward the rear side, then the electrical contact 4 is pressed by the main assembly side electrical connecting portion 55, and the spring 937 is compressed, and the substrate 3 is moved toward

the rear side beyond the front surface 2c. Thereafter, as shown in part (b) of Figure 33, the engaging portion 24 is engaged with the locking lever 58, by which the mounting of the ink cartridge 901 is completed.

[0174] With this structure of Figure 32, the substrate 3 is urged by the spring 937 in the direction of +A (mounting direction), and the contact between the electrical contacts 4 and the main assembly side electrical connecting portion 55 is easily stabilized. In addition, the substrate 3 is movable in the -A direction using the spring 937, and therefore, when the electrical contacts 4 contact to the main assembly side electrical connecting portions 55, the contact pressure therebetween does not increase beyond the necessity. As will be understood from the description of this embodiment, the substrate 3 and the electrical contacts 4 of the ink cartridge of the present invention is not limited to those fixed on the front surface 2c.

[0175] The electrical contact 4 shown in Figures 32 and 33 has (1) a area crossing with the cartridge inserting direction (mounting direction), (2) a area crossing with the Y axis direction, (3) a area crossing with the cartridge depth direction, (4) a area crossing with the direction parallel with the normal line of the tube inserting opening 8 (ink discharge opening) the formation surface, (5) a area crossing with the direction parallel with the extending direction of the tube insertion path (ink discharging path) 22, and (6) a area crossing with the direction parallel with the center line of the tube inserting opening (ink discharge opening) 8. The substrate 3 shown in Figures 32 and 33 has (1) a surface crossing with the cartridge inserting direction (mounting direction), (2) a surface crossing with the Y axis direction, (3) a surface crossing with the cartridge depth direction, (4) a surface crossing with the direction parallel with the normal line of the tube inserting opening 8 (ink discharge opening) formation surface, (5) a surface crossing with the direction parallel with the extending direction of the tube

insertion path (ink discharging path the 22, and (6) a surface crossing with the direction parallel with the center line of the tube inserting opening (ink discharge opening) 8.

[0176]

5 [Twelfth embodiment]

Referring to Figures 34 - 35, a twelfth embodiment will be described. This embodiment is different from the first embodiment only in the structure of the substrate having the electrical contacts, and the major structures in the other aspects of this embodiment are substantially the same as first embodiment.

10 Therefore, in the description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

[0177] Figure 34 schematically shows the structure of the ink cartridge 801 of
 15 the twelfth embodiment, in which (a) shows an internal structure of the ink cartridge 1001 as seen from the right-hand surface side along the X axis direction, and (b) is a perspective view of a substrate 1003. The substrate 1003 provided with the electrical contact 1004 is rotatable about a rotation shaft 1037. The substrate 1003 has a L shape including a first portion 1003a and a second portion
 20 1003b substantially perpendicular to the first portion, wherein the first portion 1003a and the second portion 1003b are connected with each other by the rotation shaft 1037. The rotation shaft 1037 is fixed to the casing at the opposite ends thereof. A back side of the second portion 1003b of the substrate 1003 is provided with a tension spring (unshown) connected to a lower surface of the
 25 upper wall of the casing 2. The tension spring urges the second portion 1003b of the substrate 1003 such that in the non-use state of the ink cartridge, the electrical contact 1004 faces substantially downwardly. On the other hand, the

first portion 1003a of the substrate 1003 functions to receive a rotational force from the mounting portion 33 by being contacted by the mounting portion 33 in the insertion of the ink cartridge 1001. By the first portion 1003a receiving the rotational force, the entire substrate 1003 is rotated about the rotation shaft 1037,
5 and the electrical contacts 1004 provided on the second portion 1003b of the substrate 1003 are electrically connected to the main assembly side electrical connecting portions 55. In this manner, the electrical contact 1004 faces substantially downwardly in the non-use state of the ink cartridge, but in the electrical connection state connecting with the main assembly side electrical
10 connecting portions 55, it faces toward the front.

[0178] Figure 35 shows the process in which the ink cartridge 1001 of the twelfth embodiment is inserted into the mounting portion 33, in which (a) shows an initial state of the insertion, (b) shows the state during the insertion, and (c) shows the insertion completed state. As shown in part (a) of Figure 35, when
15 the ink cartridge 1001 is inserted, the first portion 1003a of the substrate 1003 contacts to the upper mounting guide 50, so that the substrate 1003 is rotated. As shown in part (b) of Figure 35, the ink cartridge 1001 is inserted in the state that the second portion 1003b of the substrate 1003 faces frontwardly. Thereof, as shown in part (c) of Figure 35, the electrical contact of the substrate 1003 is
20 electrically connected to the main assembly side electrical connecting portion 55, and the engaging portion 24 is engaged with the locking lever 58, thus completing the mounting. When the ink cartridge 1001 is dismounted from the cartridge mounting portion 33, the substrate 1003 is rotated in the opposite direction by the tension spring (unshown) provided on the back side of the second
25 portion 1003b of the substrate 1003, by which the electrical contact 1004 faces downward as shown in part (a) of Figure 34. The tension spring functions as substrate moving means for moving the substrate 1003 relative to the casing.

[0179] With this structure shown in Figures 34 and 35, the electrical contact the 1004 are placed in the casing at a deep portion which is less accessible by the user before the cartridge is mounted, and with the mounting operation of the ink cartridge, the substrate 1003 is rotated so that the electrical contacts 1004 are
5 moved to the positions where they are electrically connectable with the main assembly side electrical connecting portion 55, and therefore, the likelihood of the user touching the electrical contacts 1004 before the mounting of the cartridge mounting can be reduced.

[0180] In the non-use state of the cartridge, the electrical contact 1004 shown in
10 Figures 34 and 35 does not have (1) a area crossing with the cartridge inserting direction (mounting direction), (2) a area crossing with the Y axis direction, (3) a area crossing with the cartridge depth direction, (4) a area crossing with the direction parallel with the normal line of the tube inserting opening 8 (ink discharge opening) the formation surface, (5) a area crossing with the direction
15 parallel with the extending direction of the tube insertion path (ink discharging path) 22, or (6) a area crossing with the direction parallel with the center line of the tube inserting opening (ink discharge opening) 8. However, in the mounting completed state of the ink cartridge 1001 or in the connected state relative to the main assembly side electrical connecting portion 55, the electrical
20 contact 1004 shown in Figures 34 and 35 has these areas (1) - (6).

[0181]

[Thirteenth embodiment]

Referring to Figures 36 and 37, a thirteenth embodiment will be described. This embodiment is different from the first embodiment only in the
25 structure and disposition of the substrate having the electrical contacts, and the major structures in the other aspects of this embodiment are substantially the same as the first embodiment. Therefore, in the description of this embodiment,

the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

[0182] Figure 36 schematically shows the structure of the ink cartridge 1101 of the tenth embodiment, in which (a) is a perspective view of the outer appearance of the ink cartridge 1101, and (b) shows the internal structure of the ink cartridge 1101 as seen from the right-hand surface side along the X axis direction. As shown in Figure 36, the substrate 1103 has a substantially L shape including a first portion 1103a parallel with the upper surface and a second portion 1103b substantially perpendicular to the first portion 1103a, and a back side of the first portion 1103a is supported by the upper surface 2a, and a back side of the second portion 1103b is supported by the front surface 2c. The electrode contact 1104 is supported by the second portion 1103b of the substrate 1103 such that it includes an area contactable to the main assembly side electrical connecting portion 55 (area crossing with the Y axis direction). The electrical contact 1104 is connected with a storing element 1105 provided in the first portion 1103a of the substrate 1103 through electric wiring.

[0183] Figure 37 schematically shows the structure of the ink cartridge 1201 of the tenth embodiment, in which (a) is a perspective view of the outer appearance of the ink cartridge 1201, and (b) shows the internal structure of the ink cartridge 1201 as seen from the right-hand surface side along the X axis direction. As shown in Figure 37, the substrate 1203 has a substantially L shape including a first portion 1203a parallel with the upper surface and a second portion 1203b bent from the first portion 1203a, and a back side of the first portion 1203a is supported by the upper surface 2a. The back side of the second portion 1203b is spaced from the front surface 2c, as is different from the structure of Figure 36. The electrode contact 1204 is supported by the second portion 1203b of the

substrate 1203 such that it includes an area contactable to the main assembly side electrical connecting portion 55 (area crossing with the Y axis direction). The electrical contact 1204 is connected with a storing element 1205 provided in the first portion 1203a of the substrate 1203 through electric wiring. When the ink cartridge 1201 is inserted into the mounting portion 33, the electrical contact 1204 contacts to the main assembly side electrical connecting portion 55, and then the second portion 1203b of the substrate 1203 is deformed while keeping the contact state therebetween and contacts to the front surface 2c of the casing 2. In this state, the engaging portion 24 is engaged with the locking lever 58, thus completing the mounting operation.

[0184] With this structures shown in Figures 36 and 37, the electrical contacts 1104, 1204 have areas crossing with the cartridge inserting direction (Y axis direction), and are not provided on a surface parallel with the Y axis direction, and therefore, the amount of rubbing between the electrical contacts and the main assembly side electrical connecting portions 55 can be suppressed. Furthermore, similarly to the first embodiment, the plurality of electrical contacts 1104, 1204 are arranged in the widthwise direction (X axis direction) of the ink cartridge 1301, and therefore, the same advantageous effects as with the first embodiment are provided. As will be understood from the description of this embodiment, the substrate 3 of the ink cartridge of the present invention is not limited to that supported by the front surface 2c.

[0185] The electrical contacts 1104 and 1204 shown in Figures 36 and 37 each have (1) a area crossing with the cartridge inserting direction (mounting direction), (2) a area crossing with the Y axis direction, (3) a area crossing with the cartridge depth direction, (4) a area crossing with the direction parallel with the normal line of the tube inserting opening 8 (ink discharge opening) the formation surface, (5) a area crossing with the direction parallel with the

extending direction of the tube insertion path (ink discharging path) 22, and (6) a
 area crossing with the direction parallel with the center line of the tube inserting
 opening (ink discharge opening) 8. The substrate (1103, 1203) shown in
 Figures 36 and 37 each have (1) a surface (1103b, 1203b) crossing with the
 5 cartridge inserting direction (mounting direction), (2) a surface (1103b, 1203b)
 crossing with the Y axis direction, (3) a surface (1103b, 1203b) crossing with the
 cartridge depth direction, (4) a surface (1103b, 1203b) crossing with the direction
 parallel with the normal line of the tube inserting opening 8 (ink discharge
 opening) formation surface, (5) a surface (1103b, 1203b) crossing with the
 10 direction parallel with the extending direction of the tube insertion path (ink
 discharging path the 22, and (6) a surface (1103b, 1203b) crossing with the
 direction parallel with the center line of the tube inserting opening (ink discharge
 opening) 8.

[0186]

15 [Fourteenth embodiment]

Referring to Figure 38, a fourteenth embodiment will be described.
 This embodiment is different from the first embodiment only in the structure and
 disposition of the substrate having the electrical contacts, and the major structures
 in the other aspects of this embodiment are substantially the same as first
 20 embodiment. Therefore, in the description of this embodiment, the same
 reference numerals as in the first embodiment are assigned to the elements having
 the corresponding functions in this embodiment, and the detailed description
 thereof is omitted for simplicity.

[0187] Figure 38 schematically shows the structure of the ink cartridge 1301 of
 25 the tenth embodiment, in which (a) is a perspective view of the outer appearance
 of the ink cartridge 1301, and (b) shows the internal structure of the ink cartridge
 1301 as seen from the right-hand surface side along the X axis direction. A

substrate 1303 is provided on a cut-away portion of the positional connecting the upper surface 2a and the front surface 2c substantially in parallel with the upper surface 2c. Electrical contacts 1304 are provided at a front surface free end of the substrate 1303, and storing element 1305 is provided behind the electrical
5 contacts 1304, that is, in the rear side on the substrate 1303. The electrical contacts 1304 and the storing element 1305 are connected with each other through electric wiring.

[0188] With this structure of Figure 38, the electrical contacts 1304 have areas crossing with the cartridge inserting direction (Y axis direction) and are not
10 provided on a surface parallel with Y axis direction, and therefore, the amount of rubbing between the electrical contacts 4 and the main assembly side electrical connecting portions 55 during the inserting operation can be suppressed.

Furthermore, similarly to the first embodiment, the plurality of electrical contacts 4 are arranged in the widthwise direction (X axis direction) of the ink cartridge
15 1301, and therefore, the same advantageous effects as with the first embodiment are provided. With this structure of Figure 38, the substrate 1303 is provided on the cut-away portion, but the present invention is not limited to such a structure, and the substrate 1303 may be provided on the upper surface 2a. Even in such a case, the electrical contacts 1304 are disposed at the free end of the front side on
20 the substrate 1303.

[0189] As is different from the substrates 3 shown in Figure 2, Figure 31 and Figure 32, the substrate 1303 shown in Figure 38 does not have (1) a surface crossing with the cartridge inserting direction (mounting direction), (2) a surface crossing with the Y axis direction, (3) a surface crossing with the cartridge depth
25 direction, (4) a surface crossing with the direction parallel with the normal line of the tube inserting opening 8 (ink discharge opening) the formation surface, (5) a surface crossing with the direction parallel with the extending direction of the

tube insertion path (ink discharging path) 22, or (6) a surface crossing with the direction parallel with the center line of the tube inserting opening (ink discharge opening) 8. However, as will be understood from Figure 38, the electrical contacts 1304 on the substrate 1303 each have (1) a area crossing with the

5 cartridge inserting direction (mounting direction), (2) a area crossing with the Y axis direction, (3) a area crossing with the cartridge depth direction, (4) a area crossing with the direction parallel with the normal line of the tube inserting opening 8 (ink discharge opening) formation surface, (5) a area crossing with the direction parallel with the extending direction of the tube insertion path (ink

10 discharging path the 22, and (6) a area crossing with the direction parallel with the center line of the tube inserting opening (ink discharge opening) 8.

[0190]

[Fifteenth embodiment]

Referring to Figure 39, a fifteenth embodiment will be described.

15 This embodiment is different from the first embodiment only in the structure of the positioning portion, and the major structures in the other aspects of this embodiment are substantially the same as first embodiment. Therefore, in the description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in

20 this embodiment, and the detailed description thereof is omitted for simplicity.

[0191] Figure 39 shows a structure of a positioning portion used in the fifteenth embodiment. The ink cartridge 1401 shown in part (a) of Figure 39 is provided with a plurality of projections 1406 engageable with a positioning pin 53, and the projections 1406 function as a positioning portion 1406. The plurality of

25 projections 1406 are provided behind the front surface 2c. The opening surrounded by the projections 1406 are disposed below the electrical contacts 4 and above the ink discharge opening 8, more particularly in the position closer to

the electrical contacts than the ink discharge opening 8. The positioning pin 53 is inserted into the opening surrounded by the plurality of projections 1406 so that the positioning pin 53 is engaged with the plurality of projections 1406, by which the movement of the cartridge in a direction (along the front surface 2c, for example) perpendicular to the cartridge mounting direction is limited.

[0192] In addition, an ink cartridge 1501 shown in part (b) of Figure 39 is provided with a slit formation member 1506 defining a slit capable of receiving the positioning pin 53, and the slit formation member 1506 functions as the positioning portion. The slit formation member 1506 is provided behind the front surface 2c. The slit provided by the slit formation member 1506 is below the electrical contacts 4 and above the ink discharge opening 8, more particularly in a position closer to the electrical contact than the ink discharge opening 8.

The positioning pin 53 is inserted into the slit and is engaged with the slit formation member 1506, so that the movement of the cartridge in the direction (along the front surface 2c, for example) perpendicular to the cartridge mounting direction is limited.

[0193] The ink cartridge 1601 shown in part (c) of Figure 39 is provided with a C-shape member 1606 having an opening capable of receiving the positioning pin 53, and the C-shaped member 1606 functions as the positioning portion. The C-shaped member 1606 is provided behind the front surface 2c. The opening defined by the C-shaped member 1606 is disposed below the electrical contacts 4 and above the ink discharge opening 8, more particularly in the position closer to the electrical contacts 4 than to the ink discharge opening 8. The positioning pin 53 is inserted into the opening and is engaged with the C-shaped member 1606, so that the movement of the cartridge in the direction (along the front surface 2c, for example) perpendicular to the cartridge mounting direction.

[0194] As described above, the positioning portion of the present invention is

not limited to the positioning hole 6 provided in the front surface 2c of the casing 2 of the first embodiment. The positioning portion 6 may be any if it can act on the positioning pin 53 to position the ink cartridge.

[0195]

5 [Sixteenth embodiment]

Referring to Figure 40, the sixteenth embodiment will be described. In this embodiment, a substrate 3, a positioning portion 3 and a penetrated portion 27 are provided in a second casing member 1741 which is a constituent-element of the casing 2, and a tube inserting opening 8 and a discrimination portion 9 are
 10 provided in the first casing member 1740 which is another constituent-element of the casing 2. This embodiment is different from the first embodiment only in that a part of the cartridge interface portions is provided in the second casing member functioning as a closing member, and the major structures in the other aspects of this embodiment are substantially the as first embodiment. Therefore,
 15 in the description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

[0196] Figure 40 schematically shows the structure of the sixteenth embodiment, in which (a) shows the second casing member 1741 which is a
 20 constituent-element of the casing 2, and (b) as a perspective view of an ink cartridge 1701 including the first casing member 1740 and the second casing member 1741. As shown in part (a) of Figure 40, the second casing member 1741 in this embodiment is similar to the second casing member 41 of the first embodiment shown in Figure 4, but it is additionally provided with a second front
 25 wall forming member 1702c2 which is a major part of the front wall / front surface of the casing 2. The second front wall forming member 1702c2 is provided with the substrate 3 having the electrical contacts 4, the positioning

portion 6 and the penetrated portion 27. On the other hand, the first casing member 1740 is similar to the first casing member but it is deprived of the substrate 3, the positioning portion 6 and the penetrated portion 27, and only a part of the front wall 2c remains as the first front wall forming member 1702c1.

5 That is, the first casing member 1740 includes an upper surface 2a provided with an engaging portion 24, a lower surface 2b, a rear surface 2d, a left surface 2e (unshown) and the first front wall forming member 1702c1, which is provided with the tube inserting opening 8 and the discrimination portion 9. By mounting such a second casing member 1741 to the first casing member 1740, the ink
10 cartridge 1701 shown in part (b) of Figure 40 is provided. As will be apparent from part (b) of Figure 40, the front wall / front surface 2c of the casing 2 comprises the first the front wall forming member 1702c1 which is a constituent-element of the first casing member 1740 and the second the front wall forming member 1702c2 which is a constituent-element of the second casing member
15 1741. As will be understood from the above, the casing of the ink cartridge of the present invention is not limited to that formed by the first casing member and the second casing member according to the first embodiment. In addition, the front wall / front surface 2c of the casing is not limited to that formed by a single member, but the front wall / front surface 2c of the casing may be formed by a
20 plurality of members. In addition, the cartridge side interface portions to be provided on the front wall / front surface of the casing may be distributed in the members constituting the front wall / front surface of the casing.

[0197]

[Seventeenth embodiment]

25 Referring to Figures 41 - 42 a seventeenth embodiment will be described. This embodiment is different from the first embodiment only in the structure of the engaging portion of the ink cartridge and the locking portion of

the cartridge mounting portion 33, and the major structures in the other aspects of this embodiment are substantially the same as first embodiment. Therefore, in the description of this embodiment, the same reference numerals as in the first embodiment are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity

[0198] Figure 41 schematically shows the structure of the ink cartridge 1901 of the seventeenth embodiment, in which the engaging portion 1924 moves with the movement of the engagement lever 1926. As shown in Figure 41, the ink cartridge 1901 includes a movable engagement lever 1926 having an engaging portion 1942. The engagement lever 1926 is rotatable about a rotation shaft 1925 supported by the upper surface 2a, and the engaging portion 1924 is movable toward and away from the upper surface 1902a of the casing 1902 by the rotation of the locking lever 1926, so that the distance between the engaging portion 1924 and the upper surface 1902a of the casing 1902 changes. Part (a) of Figure 41 shows the state of the engagement lever when the distance between the engaging portion 1924 and the upper surface 1902a of the casing 1902 is relatively large, and part (b) of Figure 41 shows the state of the engagement lever when the distance between the engaging portion 1924 and the upper surface 1902a of the casing 1902 is relatively small. The engaging portion 1924 provided on the engagement lever 1926 is movable to the neighborhood of the upper surface 2c, and similarly to the first embodiment, it is disposed in a position closer to the electrical contact 4 than to the ink discharge opening 8. Therefore, the same advantageous effects as of the first embodiment are provided.

[0199] Figure 42 shows of the process in which the ink cartridge 901 of the seventeenth embodiment is inserted into the mounting portion 33, in which a (a) shows an initial state of insertion, and (b) shows the insertion completed state. When the ink cartridge 1901 is inserted, the engaging portion 1924 contacts to the

upper part mounting guide 50 provided in the cartridge mounting portion 33, by which the engaging portion 1924 is moved so that the engagement lever 1926 moves toward the upper surface 2a. Part (a) of Figure 42 shows the state in which the engaging portion 1924 comes close to the upper surface 2a. When the
5 ink cartridge 1901 is further inserted from the position shown in part (a) of Figure 42, and the engaging portion 1924 passes an end portion of the upper part mounting guide 50, the engagement lever 1926 moves so that the engaging portion 1924 is away from the upper surface 2a. By this, the engaging portion 1924 is brought into engagement with the engageable member 1954 provided at
10 the end of the upper part mounting guide 50, thus completing the mounting of the ink cartridge 1901.

[0200] When the ink cartridge 1901 is to be dismounted from the cartridge mounting portion 33, the rear side end portion 1927 of the engagement lever 1926 is raised (Z axis direction). By this, the engaged state between the engaging
15 portion 1924 and the engageable member 1954 is released, by which the ink cartridge 1901 is moved in the dismounting direction by the urging force of the ejection spring 57, thus permitting the user to dismount the ink cartridge 1901 from the cartridge mounting portion 33. When the user operates the locking lever 1926 to disengage the engaging portion 1924 from the engageable member
20 1954, the ink cartridge 1901 is moved in the dismounting direction by the spring force, and at this time, a hand of the user is in the neighborhood of the dismounting position, and therefore, if the spring force is strong, the ink cartridge 1901 popped out by the spring force can be easily caught by the hand of the user, and the stronger popping out of the ink cartridge 1901 than is necessary can be
25 suppressed.

[0201] As will be understood from the description of this embodiment, the engaging portion usable in the ink cartridge of the present invention is not limited

to the structure engageable with the locking lever 58 of the cartridge mounting portion 33. The engaging portion may be replaced with any of various structures engageable with the element of the cartridge mounting portion 33.

[0202]

5 [Eighteenth embodiment]

Referring to Figure 43, an eighteenth embodiment will be described. Figure 43 illustrates a schematic structure of ink cartridges 2001, 2101, 2201, 2301 applicable in an eighteenth embodiment. This embodiment is different from the first embodiment only in that the positioning portion 6 and/or the
10 penetrated portion 27 is not provided on the ink cartridge, and the positioning pin 53 and/or the unsealing pin 51 is not provided in the cartridge mounting portion 33, and the major structures in the other aspects of this embodiment are substantially the same as the first embodiment. Therefore, in the description of this embodiment, the same reference numerals as in the first embodiment are
15 assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity.

[0203] The ink cartridge 2001 shown in part (a) of Figure 43 is similar to the ink cartridge 1 of the first embodiment except that the positioning portion 6 and the penetrated portion 27 are not provided, and that the air vent (unshown) and
20 the air vent sealing film 2017 are provided on the upper surface 2a of the casing 2. Correspondingly, the cartridge mounting portion to which the ink cartridge 2001 can be dismountably mounted is not provided with the positioning pin 53 and the unsealing pin 51, as compared with the cartridge mounting portion 33 of the first embodiment. Because of the cartridge mounting portion is not provided with
25 the unsealing pin 51, it is necessary that the air vent sealing film is removed by the user. Therefore, the ink cartridge 2001 shown in part (a) of Figure 43 is provided with the air vent sealing film 2017 on the upper surface 2a of the casing

2 where the user can easily remove the film.

[0204] With such a structure, no positioning portion 6 or positioning pin 53 is provided, and therefore, the ink cartridge 2001 is positioned by the tube inserting opening 8 and the ink receiving tube 52 and by the position regulation surface 10
5 and the positioning wall 56. For this reason, the accuracy of the positioning is it not as good as in the first embodiment. However, the engaging portion 24 is disposed in the position closer to the electrical contact 4 than to the tube inserting opening 8, and the engaging portion 24 is disposed in the position of the upper surface 2c or adjacent to the upper surface which is close to the electrical contact
10 4, similarly to the first embodiment, and therefore, the same advantageous effects as of the first embodiment can be provided in these respects.

[0205] With the structure of part (a) of Figure 43, the user is required to remove the seal, and therefore, there is a likelihood that the air vent film 2017 is removed before the cartridge mounting, and the advantageous effects of the first
15 embodiment in this respect is not provided in this embodiment. On the other hand, the air vent sealing film can be more easily stuck than in the first embodiment, and since the unsealing pin 51 is not provided, the number of parts of the printer main assembly can be reduced. In part (a) of Figure 43, the air vent sealing film 2017 may be disposed at any position if the user can easily
20 remove it. For example, the air vent and the air vent sealing film 2017 may be disposed on the rear surface 2d, the right-hand surface 2f, the left surface 2e or the like.

[0206] The ink cartridge 2101 shown in part (b) of Figure 43 is not provided with the positioning portion 6, the penetrated portion 27, the air vent 7, the filter
25 15, the air vent path 16 and the air vent sealing film 17, as compared with the ink cartridge 1 of the first embodiment, and the structure of the inside ink accommodating chamber 11 is changed from that of the first embodiment.

[0207] The ink cartridge 2201 shown in part (c) of Figure 43 is not provided with the penetrated portion 27 as compared with the ink cartridge 1 of the first embodiment, and the air vent (unshown) and the air vent sealing film 2217 is provided on the upper surface 2a of the casing 2. The cartridge mounting
5 portion to which this ink cartridge 2001 can be detachably mounted is similar to the cartridge mounting portion 33 of the first embodiment but is not provided with the unsealing pin 51. The user is required to remove the seal, and therefore, there is a likelihood that the air vent film 2217 is removed before the cartridge
10 mounting, and the advantageous effects of the first embodiment in this respect is not provided in this embodiment. Instead, however, the air vent sealing film can be more easily stuck than in the first embodiment.

[0208] The ink cartridge 2301 shown in part (d) of Figure 43 is not provided with the positioning portion 6, as compared with the ink cartridge 1 of the first embodiment. The cartridge mounting portion to which the ink cartridge 2301
15 can be detachably mounted is not provided with the positioning pin 53, as compared with the cartridge mounting portion 33 of the first embodiment. With such a structure, no positioning portion 6 or positioning pin 53 is provided, and therefore, the positioning of the ink cartridge 2301 is effected by the tube inserting opening 8 in the ink receiving tube and by the position regulation
20 surface 10 and the positioning wall 56. For this reason, the accuracy of the positioning is not as good as in the first embodiment. However, the engaging portion 24 is disposed in the position closer to the electrical contact 4 than to the tube inserting opening 8, and the engaging portion 24 is disposed in the position of the upper surface 2c or adjacent to the upper surface which is close to the
25 electrical contact 4, similarly to the first embodiment, and therefore, the same advantageous effects as of the first embodiment can be provided in these respects.

[0209]

[Preferable aspects of the present invention]

The preferable aspects of the ink cartridge or the ink jet printer of the embodiments having been described in the foregoing are as follows.

5 **[0210]**

(Aspect 1)

According to aspect 1, there is provided:

An ink cartridge mountable to a cartridge mounting portion provided with an ink receiving tube, an electrical connecting portion and a locking lever, in
10 a mounting direction crossing with a direction of gravity, said ink cartridge comprising:

a casing including an ink accommodating chamber configured to accommodate ink to be supplied to the ink receiving tube, said casing including a front surface at a leading side with respect to the mounting direction, an upper
15 surface and a bottom surface;

a tube inserting portion into which the ink receiving tube is insertable and which is provided at said front surface in a position closer to said bottom surface than to said upper surface;

an electrical contact electrically connectable to the electrical
20 connecting portion and provided in a position above said tube inserting portion, said electrical contact including an area crossing with the mounting direction;

an engaging portion provided in a position closer to said electrical contact than to said tube inserting portion, said engaging portion being engageable with the locking lever to maintain a inserted state in which the ink
25 receiving tube is inserted in said tube inserting portion and a connected state in which said electrical contact is connected with the electrical connecting portion.

[0211]

(Aspect 2)

An ink cartridge according to aspect 1 preferably further comprises a force receiving portion capable of receiving, from an urging spring provided in the cartridge mounting portion, the urging force for urging said ink cartridge in a
5 dismounting direction which is opposite to the mounting direction, said force receiving portion being provided in a position above said tube inserting portion and below said electrical contact, wherein said engaging portion is engageable with said locking lever to maintain the inserted state and the connected state against the urging force.

10 **[0212]**

(Aspect 3)

In an ink cartridge according to aspect 2, it is preferable that said force receiving portion is capable of receiving the urging force to release the inserted state and the connected state with release of an engaged state between said
15 engaging portion and the locking lever.

[0213]

(Aspect 4)

An ink cartridge according to aspect 1 preferably further comprises a positioning portion engageable with a positioning member provided in the
20 cartridge mounting portion to limit movement of said casing in a direction perpendicular to the mounting direction, said positioning portion being provided in a position above said tube inserting portion and below said electrical contact, and

a force receiving portion capable of receiving, from an urging spring
25 provided in the cartridge mounting portion, the urging force for urging said ink cartridge in a dismounting direction which is opposite to the mounting direction, said force receiving portion being provided in a position above said tube inserting

portion and below said electrical contact,

wherein said engaging portion is engageable with said locking lever to maintain the inserted state, the connected state and a engaged state between said positioning portion and the positioning member against the urging force.

5 **[0214]**

(Aspect 5)

In an apparatus according to aspect 4, it is preferable that said force receiving portion is capable of receiving the urging force to release the inserted state the connected state and the engaged state between said positioning portion
10 and the positioning member with release of a engaged state between said engaging portion and the locking lever.

[0215]

(Aspect 6)

An ink cartridge according to aspect 1 preferably further comprises a
15 positioning portion provided in a position above said tube inserting portion and below said electrical contact and engageable with a positioning member provided in the cartridge mounting portion to limit movement of said casing in a direction perpendicular to the mounting direction, wherein said engaging portion is engageable with the locking lever to maintain an engaged state between said
20 positioning portion and the positioning member.

[0216]

(Aspect 7)

In an ink cartridge according to aspect 4 or 6, it is preferable that said positioning portion is disposed in a position close to said electrical contact than to
25 said tube inserting portion.

[0217]

(Aspect 8)

In an ink cartridge according to aspect 4or 7, it is preferable that said positioning portion is disposed at said front surface.

[0218]

(Aspect 9)

5 In an ink cartridge according to aspect 4or 8, it is preferable that said positioning portion includes a positioning opening into which the positioning member is inserted.

[0219]

(Aspect 10)

10 In an ink cartridge according to aspect 4or 9, it is preferable that the direction perpendicular to the mounting direction is a direction away from said bottom surface toward said upper surface.

[0220]

(Aspect 11)

15 In an apparatus according to aspect 4or 9, it is preferable that the direction perpendicular to the mounting direction is a direction along said front surface.

[0221]

(Aspect 12)

20 In an ink cartridge according to aspect 2or 5, it is preferable that a part of said front surface functions as said force receiving member.

[0222]

(Aspect 13)

25 In an ink cartridge according to aspect 1 or 12, it is preferable that said engaging portion is disposed in a position closer to said upper surface than to said bottom surface.

[0223]

(Aspect 14)

In an ink cartridge according to aspect 1 or 12, it is preferable that said engaging portion is disposed at said upper surface.

[0224]

5 (Aspect 15)

In an ink cartridge according to aspect 1 or 14, it is preferable that said engaging portion is a recess engageable with a projection of said locking lever.

[0225]

(Aspect 16)

10 In an ink cartridge according to aspect 1 or 14, it is preferable that said engaging portion is a recess engageable with a projection of said locking lever.

[0226]

(Aspect 17)

15 An ink cartridge according to aspect 1 or 16 preferably further comprises an elastically deformable elastic portion configured to move said engaging portion relative to said casing.

[0227]

(Aspect 18)

20 An ink cartridge according to aspect 1 or 17 preferably further comprises a substrate provided with said electrical contact.

[0228]

(Aspect 19)

In an ink cartridge according to aspect 18, it is preferable that said substrate is provided at said front surface.

25 **[0229]**

(Aspect 20)

In an ink cartridge according aspect 18, it is preferable that said

substrate is provided on said casing so as to be inclined relative to said front surface and said upper surface.

[0230]

(Aspect 21)

5 In an ink cartridge according aspect 18, it is preferable that said substrate is supported on said upper surface so that said electrical contact has an area crossing with the mounting direction.

[0231]

(Aspect 22)

10 An ink cartridge according to aspect 18 preferably further comprises moving means configured to move said substrate relative to said casing.

[0232]

(Aspect 23)

15 In an ink cartridge according to aspect 18 or 22, it is preferable that said substrate is directly supported by said casing or is indirectly supported by said casing through a supporting member.

[0233]

(Aspect 24)

20 An ink cartridge according to aspect 1 or 23 preferably further comprises an air vent path provided on said casing and configured to introduce ambient air into said ink accommodating chamber, said air vent path having one end portion provided with an air vent and the other end portion connected with said ink accommodating chamber, and a sealing film sealing said air vent, said sealing film being unsealable by an unsealing pin provided on said cartridge mounting portion.

[0234]

(Aspect 25)

An ink cartridge according to aspect 24 preferably further comprises a through hole into which the unsealing pin is insertable, said through hole is provided at said front surface, and said sealing film being disposed at such a position that said sealing film is capable of being unsealed by the unsealing pin
5 passed through said through hole.

[0235]

(Aspect 26)

An ink cartridge according to aspect 24 or 25, it is preferable that said casing is provided with an air vent formation wall provided with said air vent,
10 and said air vent formation wall being provided between said front surface and said ink accommodating chamber.

[0236]

(Aspect 27)

An ink cartridge according to aspect 2 or 25 preferably further
15 comprises an air vent path provided on said casing and configured to introduce ambient air into said ink accommodating chamber, said air vent path having one end portion provided with an air vent and the other end portion connected with said ink accommodating chamber,

a through hole into which the unsealing pin provided on said cartridge
20 mounting portion is insertable, said through hole being provided at said front surface so as to be inside said force receiving portion, and

a sealing film capable of being unsealed by the unsealing pin passed through said through hole.

[0237]

25 (Aspect 28)

In an ink cartridge according to aspect 27, it is preferable that said sealing film is provided on air vent formation wall disposed in a position in a rear

side of said front surface so as to be unsealed by the unsealing pin after said force receiving portion disposed at said front surface receives the urging force.

[0238]

(Aspect 29)

5 An ink cartridge according to aspect 1 or 28 preferably further comprises a tube insertion path provided in said casing to connect said tube inserting portion and said ink accommodating chamber with each other, an elastic member provided in said tube insertion path and elastically deformable with insertion of said ink receiving tube into said tube insertion path.

10 **[0239]**

(Aspect 30)

In an ink cartridge according to aspect 29, it is preferable that said elastic member includes a rubber member contactable to an outer peripheral surface of said ink receiving tube inserted into the tube insertion path.

15 **[0240]**

(Aspect 31)

According to an aspect 31, there is provided:

20 An ink cartridge mountable to a cartridge mounting portion provided with an ink receiving tube, an electrical connecting portion and a locking lever, in a mounting direction crossing with a direction of gravity, said ink cartridge comprising:

25 a casing including an ink accommodating chamber configured to accommodate ink to be supplied to the ink receiving tube and a tube inserting opening into which said ink receiving tube is inserted, said casing including a front surface at a leading side with respect to the mounting direction, an upper surface and a bottom surface, and said tube inserting opening is disposed in a position closer to said bottom surface than to said upper surface adjacent to said

front surface;

a substrate provided at said front surface in a position above said tube inserting opening;

an electrical contact provided on said substrate and electrically
5 connectable to the electrical connecting portion;

an engaging portion provided on said upper surface in a position closer to front surface than to rear surface, said engaging portion is engageable with the locking lever to maintain an inserted state in which the ink receiving tube is inserted in said tube inserting portion and a connected state in which said
10 electrical contact is connected with the electrical connecting portion.

[0241]

(Aspect 32)

According to an aspect 32, there is provided:

An ink cartridge mountable to a cartridge mounting portion provided
15 with an ink receiving tube, an electrical connecting portion, an urging spring and a locking lever, in a mounting direction crossing with a direction of gravity, said ink cartridge comprising:

a casing including an ink accommodating chamber configured to accommodate ink to be supplied to the ink receiving tube and a tube inserting
20 opening into which said ink receiving tube is inserted, said casing including a front surface at a leading side with respect to the mounting direction, an upper surface and a bottom surface, and said tube inserting opening is disposed in a position closer to said bottom surface than to said upper surface adjacent to said front surface;

25 a substrate provided at said front surface in a position above said tube inserting opening;

an electrical contact provided on said substrate and electrically

connectable to the electrical connecting portion;

a force receiving portion provided on said front surface in a position above said tube inserting opening below said electrical contact and configured to receive from the urging spring an urging force for urging said ink cartridge in a
5 dismounting direction which is opposite the mounting direction;

an engaging portion provided on said upper surface in a position closer to front surface than to rear surface, said engaging portion is engageable with the locking lever to maintain, against the urging force, an inserted state in which the ink receiving tube is inserted in said tube inserting portion and a
10 connected state in which said electrical contact is connected with said electrical connecting portion.

[0242]

(Aspect 33)

According to an aspect 33, there is provided:

15 An ink cartridge mountable to a cartridge mounting portion provided with an ink receiving tube, an electrical connecting portion, a positioning member, an urging spring and a locking lever, in a mounting direction crossing with a direction of gravity, said ink cartridge comprising:

a casing including an ink accommodating chamber configured to
20 accommodate ink to be supplied to the ink receiving tube and a tube inserting opening into which said ink receiving tube is inserted, said casing including a front surface at a leading side with respect to the mounting direction, an upper surface and a bottom surface, and said tube inserting opening is disposed in a position closer to said bottom surface than to said upper surface adjacent to said
25 front surface;

a substrate provided at said front surface in a position above said tube inserting opening;

an electrical contact provided on said substrate and electrically connectable to the electrical connecting portion;

a positioning opening into which the positioning member is capable of inserting to limit movement of said casing in a direction along said front side,
5 said positioning opening being provided at said front surface in a position above said tube inserting opening and below said electrical contact in a position closer to said electrical contact than to said tube inserting opening;

a force receiving portion provided at said front surface in a position above said tube inserting opening below said electrical contact and configured to
10 receive from the urging spring an urging force for urging said ink cartridge in a dismounting direction which is opposite the mounting direction;

an engaging portion provided on said upper surface in a position closer to front surface than to rear surface, said engaging portion is engageable with the locking lever to maintain, against the urging force, a inserted state in
15 which the ink receiving tube is inserted in said tube inserting portion, a connected state in

[0243]

(Aspect 34)

An ink cartridge according to aspect 31 or 33 preferably further
20 comprises a tube insertion path provided on said casing to connect said tube inserting opening and said ink accommodating chamber with each other, an elastic member provided in said tube insertion path and elastically deformable with insertion of said ink receiving tube into said tube insertion path.

[0244]

25 (Aspect 35)

An apparatus according to aspect 34, it is preferable that said elastic member includes a rubber member contactable to an outer peripheral surface of

said ink receiving tube inserted into the tube insertion path.

[0245]

(Aspect 36)

An ink cartridge according to aspect 31 or 35 preferably further
5 comprises an air vent path provided on said casing and configured to introduce
ambient air into said ink accommodating chamber, said air vent path having one
end portion provided with an air vent and the other end portion connected with
said ink accommodating chamber, a sealing film sealing said air vent and
capable of being unsealed by an unsealing pin provided in the cartridge mounting
10 portion.

[0246]

(Aspect 37)

An ink cartridge according to aspect 36 preferably further comprises a
through hole into which the unsealing pin is insertable, said through hole being
15 provided at the front surface, said sealing film being disposed at such a position
that said sealing film being capable of being unsealed by the unsealing pin passed
through said through hole.

[0247]

(Aspect 38)

20 In an ink cartridge according to aspect 36 or 37, it is preferable that
said casing is provided with an air vent formation wall provided with said air vent,
and wherein said air vent formation wall is provided between said front surface
and said ink accommodating chamber with respect to a direction away from said
front side toward said rear side.

25 **[0248]**

(Aspect 39)

According to aspect 39, there is provided:

An ink cartridge comprising:

a casing including a plurality of side surfaces, an upper surface and bottom surface as defined on the basis of use state of said ink cartridge and provided with an ink accommodating chamber and the ink discharge opening
 5 configured to discharge the ink from said ink accommodating chamber to an outside, said side surface including a first side surface and a second side surface at an opposite side from said first side surface across said ink accommodating chamber, said ink discharge opening being provided at said first side surface in a position closer to said bottom surface than to said upper surface;

10 an electrical contact provided in a position above said ink discharge opening;

a substrate provided at said first side surface and provided with said electrical contact;

an engaging portion provided at said upper surface in a position closer
 15 to said electrical contact than to said ink discharge opening and closer to said first side surface than to said second side surface.

[0249]

(Aspect 40)

According to aspect 40, there is provided:

20 An ink cartridge comprising:

a casing including a plurality of side surfaces, an upper surface and bottom surface as defined on the basis of use state of said ink cartridge and provided with an ink accommodating chamber and a ink discharge opening configured to discharge the ink from said ink accommodating chamber to an
 25 outside, said side surface including a first side surface and a second side surface at an opposite side from said first side surface across said ink accommodating chamber, said ink discharge opening being provided at said first side surface in a

position closer to said bottom surface than to said upper surface;

an electrical contact provided in a position above said ink discharge opening;

a substrate provided at said first side surface and provided with said
5 electrical contact;

a force receiving portion provided at said first side surface in a position above said ink discharge opening and below said electrical contact and configured to receive an urging force for urging said casing in a direction away from said first side surface toward said second side surface;

10 an engaging portion provided at said upper surface in a position closer to said electrical contact than to said ink discharge opening and closer to said first side surface than to said second side surface and configured to receive a limiting force for limiting movement of said casing against the urging force in the direction.

15 **[0250]**

(Aspect 41)

According to aspect 41, there is provided:

An ink cartridge comprising:

a casing including a plurality of side surfaces, an upper surface and
20 bottom surface as defined on the basis of use state of said ink cartridge and provided with an ink accommodating chamber and an ink discharge opening configured to discharge the ink from said ink accommodating chamber to an outside, said side surface including a first side surface and a second side surface at an opposite side from said first side surface across said ink accommodating
25 chamber, said ink discharge opening being provided at said first side surface in a position closer to said bottom surface than to said upper surface;

an electrical contact provided in a position above said ink discharge

opening;

a substrate provided at said first side surface and provided with said electrical contact;

a positioning opening provided at said first side surface in a position
5 above said ink discharge opening and below said electrical contact and closer to said electrical contact than to said ink discharge opening;

a force receiving portion provided at said first side surface in a position above said ink discharge opening and below said positioning opening and configured to receive an urging force for urging said casing in a direction
10 away from said first side surface toward said second side surface; and

an engaging portion provided at said upper surface in a position closer to said electrical contact than to said ink discharge opening and closer to said first side surface than to said second side surface and configured to receive a limiting force for limiting movement of said casing against the urging force in the
15 direction.

[0251]

(Aspect 42)

According to aspect 42, there is provided:

An ink cartridge comprising:

20 a casing including a plurality of side surfaces, an upper surface and bottom surface as defined on the basis of use state of said ink cartridge and provided with an ink accommodating chamber and an ink discharge opening configured to discharge the ink from said ink accommodating chamber to an outside, said side surface including a first side surface and a second side surface
25 at an opposite side from said first side surface across said ink accommodating chamber, said ink discharge opening being provided at said first side surface in a position closer to said bottom surface than to said upper surface;

an electrical contact provided in a position above said ink discharge opening;

a substrate provided at said first side surface and provided with said electrical contact;

5 a positioning opening provided at said first side surface in a position above said ink discharge opening and below said electrical contact and closer to said electrical contact than to said ink discharge opening;

an engaging portion provided at said upper surface in a position closer to said electrical contact than to said ink discharge opening and closer to said first
10 side surface than to said second side surface.

[0252]

(Aspect 43)

In an ink cartridge according to aspect 39 or 42, it is preferable that said engaging portion includes a recess.

15 **[0253]**

(Aspect 44)

In an ink cartridge according to aspect 39 or 43, it is preferable that said side surfaces further including a third side surface connected with said first side surface, said second side surface, said upper surface and said bottom surface,
20 and a fourth side surface opposite from said third side surface across said ink accommodating chamber and connected with said first side surface, said second side surface, and said upper surface and said bottom surface,

wherein said third side surface has a larger area than those of said first side surface, said second side surface, said upper surface and said bottom surface,

25 wherein said fourth side surface has a larger area than those of said first side surface, said second side surface, said upper surface and said bottom surface,

wherein said first side surface has a smaller area than those of said third side surface, said fourth side surface, said upper surface and said bottom surface, and

wherein said second side surface has a smaller area than those of said third side surface, said fourth side surface, said upper surface and said bottom surface.

[0254]

(Aspect 45)

An ink cartridge according to aspect 39 or 44 preferably further comprises an air vent path provided on said casing and configured to introduce ambient air into said ink accommodating chamber, said air vent path having one end portion provided with an air vent and the other end portion connected with said ink accommodating chamber, a through hole provided at said first side surface;

a sealing film sealing said air vent in a position in a rear side of the through hole with respect to a direction away from said first side surface toward the second side surface.

[0255]

(Aspect 46)

In an ink cartridge according to aspect 45, it is preferable that said casing is provided with an air vent formation wall provided with said air vent, and wherein said air vent formation wall is provided between said first side surface and said ink accommodating chamber with respect to a direction away from said first side surface side toward said second side surface.

[0256]

(Aspect 47)

According to aspect 47, there is provided:

An ink cartridge comprising:

a casing including an ink accommodating chamber and including a first surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, a second surface opposite
 5 from said first surface across said ink accommodating chamber, a third surface connecting said first surface and said second surface with each other and having an area larger than those of said first surface and said second surface, and a fourth surface opposite from said third surface across said ink accommodating chamber, said ink discharge opening being disposed in a position closer to said third
 10 surface than to said fourth surface;

an electrical contact disposed in a position above said ink discharge opening in the state in which said third surface is a bottom surface;

a substrate provided at said first surface and supporting said electrical contact;

15 an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said electrical contact than to said ink discharge opening and closer to said first surface than to said second surface.

[0257]

(Aspect 48)

20 According to aspect 48, there is provided:

An ink cartridge comprising:

a casing including an ink accommodating chamber and including a first surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, a second surface opposite
 25 from said first surface across said ink accommodating chamber, a third surface connecting said first surface and said second surface with each other and having an area larger than those of said first surface and said second surface, and a fourth

surface opposite from said third surface across said ink accommodating chamber,
said ink discharge opening being disposed in a position closer to said third
surface than to said fourth surface;

an electrical contact disposed in a position above said ink discharge
5 opening in the state in which said third surface is a bottom surface;
a substrate provided at said first surface and supporting said electrical
contact;

a force receiving portion provided at said first surface in a position
below said substrate and above said ink discharge opening in a state in which said
10 third surface is a bottom surface and configured to receive an urging force for
urging said casing in a direction away from said first surface toward said second
surface in a state in which said third surface is a bottom surface;

an engaging portion in the form of a recess and provided at said fourth
surface in a position closer to said electrical contact than to said ink discharge
15 opening and closer to said first surface than to said second surface, said engaging
portion being capable of receiving a limiting force for limiting movement of said
casing in a direction away from said first surface toward second surface.

[0258]

(Aspect 49)

20 According to aspect 49, there is provided:

An ink cartridge comprising:

a casing including an ink accommodating chamber and including a
first surface provided with an ink discharge opening configured to discharge ink
from said ink accommodating chamber to an outside, a second surface opposite
25 from said first surface across said ink accommodating chamber, a third surface
connecting said first surface and said second surface with each other and having
an area larger than those of said first surface and said second surface, and a fourth

surface opposite from said third surface across said ink accommodating chamber, said ink discharge opening being disposed in a position closer to said third surface than to said fourth surface;

an electrical contact disposed in a position above said ink discharge opening in the state in which said third surface is a bottom surface;
 5 a substrate provided at said first surface and supporting said electrical contact;

a positioning opening provided at said first surface in a position above said ink discharge opening and below said substrate in a state in which said third surface is a bottom surface and closer to said substrate than to said ink discharge opening and configured to limit movement of said casing in a direction along the first surface;
 10

a force receiving portion provided at said first surface in a position below said positioning opening and above said ink discharge opening in a state in which said third surface is a bottom surface and configured to receive an urging force for urging said casing in a direction away from said first surface toward said second surface in a state in which said third surface is a bottom surface; and
 15

an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said electrical contact than to said ink discharge opening and closer to said first surface than to said second surface, said engaging portion being capable of receiving a limiting force for limiting movement of said casing in a direction from said first surface toward second surface.
 20

[0259]

(Aspect 50)

25 According to aspect 50, there is provided:

An ink cartridge comprising:

a casing including an ink accommodating chamber and including a

first surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, a second surface opposite from said first surface across said ink accommodating chamber, a third surface connecting said first surface and said second surface with each other and having
 5 an area larger than those of said first surface and said second surface, and a fourth surface opposite from said third surface across said ink accommodating chamber, said ink discharge opening being disposed in a position closer to said third surface than to said fourth surface;

an electrical contact disposed in a position above said ink discharge
 10 opening in the state in which said third surface is a bottom surface;

a substrate provided at said first surface and supporting said electrical contact;

a positioning opening provided at said first surface in a position above said ink discharge opening and below said substrate in a state in which said third
 15 surface is a bottom surface and closer to said substrate than to said ink discharge opening; and

an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said electrical contact than to said ink discharge opening and closer to said first surface than to said second surface, said engaging
 20 portion having an area crossing with a direction parallel with a normal line of said substrate.

[0260]

(Aspect 51)

In an ink cartridge according to aspect 47 or 50, it is preferable that
 25 said casing further includes a fifth surface connecting with said first surface, said second surface, said third surface and said fourth surface and having an area larger than those of said first surface, said second surface, said third surface and

said fourth surface, and includes a sixth surface opposite away from said fifth surface.

[0261]

(Aspect 52)

5 According to aspect 52, there is provided:

An ink cartridge comprising:

a casing having a substantially rectangular parallelepiped shape and including an ink accommodating chamber, said casing including (a) a first surface provided with an ink discharge opening configured to discharge ink from said ink
 10 accommodating chamber to an outside, (b) a second surface opposite from said first surface across said ink accommodating chamber, (c) a third surface crossing with said first surface and said second surface and having an area larger than those of said first surface and said second surface, (d) a fourth surface opposite from said third surface across said ink accommodating chamber and having an
 15 area larger than those of said first surface and said second surface, (e) a fifth surface crossing with said first surface, said second surface, said third surface and said fourth surface and having an area larger than those of said first surface, said second surface, said third surface and said fourth surface, (f) a sixth surface opposite from said fifth surface across said ink accommodating chamber and
 20 having an area larger than those of said first surface, said second surface, said third surface and said fourth surface, and (g) said ink discharge opening being disposed closer to said third surface than to said fourth surface;

a substrate provided at said first surface such that said substrate is in a position above said ink discharge opening in a state in which said third surface is
 25 a bottom surface;

a plurality of electrical contacts provided on said substrate and arranged in a direction crossing with a direction away from said third surface

toward said fourth surface;

an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said substrate than to said ink discharge opening and closer to said first surface than to said second surface.

5 **[0262]**

(Aspect 53)

According to aspect 53, there is provided:

An ink cartridge comprising:

- a casing having a substantially rectangular parallelepiped shape and
- 10 including an ink accommodating chamber, said casing including (a) a first surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, (b) a second surface opposite from said first surface across said ink accommodating chamber, (c) a third surface crossing with said first surface and said second surface and having an area larger than
- 15 those of said first surface and said second surface, (d) a fourth surface opposite from said third surface across said ink accommodating chamber and having an area larger than those of said first surface and said second surface, (e) a fifth surface crossing with said first surface, said second surface, said third surface and said fourth surface and having an area larger than those of said first surface, said
- 20 second surface, said third surface and said fourth surface, (f) a sixth surface opposite from said fifth surface across said ink accommodating chamber and having an area larger than those of said first surface, said second surface, said third surface and said fourth surface, and (g) said ink discharge opening being disposed closer to said third surface than to said fourth surface;
- 25 a substrate provided at said first surface such that said substrate is in a position above said ink discharge opening in a state in which said third surface is a bottom surface;

a plurality of electrical contacts provided on said substrate and arranged in a direction crossing with a direction away from said third surface toward said fourth surface;

an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said substrate than to said ink discharge opening and closer to said first surface than to said second surface.

[0263]

(Aspect 54)

According to aspect 54, there is provided:

10 An ink cartridge comprising:

a casing having a substantially rectangular parallelepiped shape and including an ink accommodating chamber, said casing including (a) a first surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, (b) a second surface opposite from said first surface across said ink accommodating chamber, (c) a third surface crossing with said first surface and said second surface and having an area larger than those of said first surface and said second surface, (d) a fourth surface opposite from said third surface across said ink accommodating chamber and having an area larger than those of said first surface and said second surface, (e) a fifth surface crossing with said first surface, said second surface, said third surface and said fourth surface and having an area larger than those of said first surface, said second surface, said third surface and said fourth surface, (f) a sixth surface opposite from said fifth surface across said ink accommodating chamber and having an area larger than those of said first surface, said second surface, said third surface and said fourth surface, and (g) said ink discharge opening being disposed closer to said third surface than to said fourth surface;

a substrate provided at said first surface such that said substrate is in a

position above said ink discharge opening in a state in which said third surface is a bottom surface;

a plurality of electrical contacts provided on said substrate and arranged in a direction crossing with a direction away from said third surface
5 toward said fourth surface;

a positioning opening provided at said first surface in a position above said ink discharge opening and below said substrate in a state in which said third surface is a bottom surface and closer to said plurality of electrical contacts than said ink discharge opening and configured to limit movement of said casing in a
10 direction along said first surface;

a force receiving portion provided at said first surface in a position above said ink discharge opening below said positioning opening in a state in which said third surface is a bottom surface and configured to receive an urging force for urging said casing in a direction away from said first surface toward said
15 second surface;

an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said substrate than to said ink discharge opening and closer to said first surface than to said second surface and configured to receive a regulating force for limiting movement of said casing in the direction
20 away from said first surface toward said second surface against the urging force.

[0264]

(Aspect 55)

According to aspect 55, there is provided:

An ink cartridge comprising:

25 a casing having a substantially rectangular parallelepiped shape and including an ink accommodating chamber, said casing including (a) a first surface provided with an ink discharge opening configured to discharge ink from said ink

accommodating chamber to a outside, (b) a second surface opposite from said first surface across said ink accommodating chamber, (c) a third surface crossing with said first surface and said second surface and having a area larger than those of said first surface and said second surface, (d) a fourth surface opposite from
 5 said third surface across said ink accommodating chamber and having a area larger than those of said first surface and said second surface, (e) a fifth surface crossing with said first surface, said second surface, said third surface and said fourth surface and having a area larger than those of said first surface, said second surface, said third surface and said fourth surface, (f) a sixth surface
 10 opposite from said fifth surface across said ink accommodating chamber and having a area larger than those of said first surface, said second surface, said third surface and said fourth surface, and (g) said ink discharge opening being disposed closer to said third surface than to said fourth surface;

a substrate provided at said first surface such that said substrate is in a
 15 position above said ink discharge opening in a state in which said third surface is a bottom surface;

a substrate provided at said first surface such that said substrate is in a position above said ink discharge opening in a state in which said third surface is a bottom surface;

20 a positioning opening provided at said first surface in a position above said ink discharge opening and below said substrate in a state in which said third surface is a bottom surface and closer to said plurality of electrical contacts than to said ink discharge opening; and

an engaging portion in the form of a recess provided at said fourth
 25 surface in a position closer to said substrate than to said ink discharge opening and closer to said first surface than to said second surface.

[0265]

(Aspect 56)

An ink cartridge according to aspect 47 or 55 preferably further comprises an air vent path provided in said casing and configured to introduce ambient air into said ink accommodating chamber, said air vent path having one
5 end portion provided with an air vent and the other end portion connected with said ink accommodating chamber,

a through hole provided at said first side surface; and

a sealing film sealing said air vent in a position in a rear side of the through hole with respect to a direction away from said first side surface toward
10 the second side surface.

[0266]

(Aspect 57)

In an ink cartridge according to aspect 56, it is preferable that said casing is provided with an air vent formation wall provided with said air vent,
15 and wherein said air vent formation wall is provided between said first side surface and said ink accommodating chamber with respect to a direction away from said first side surface side toward said second side surface.

[0267]

(Aspect 58)

20 An ink cartridge according to aspect 39 or 57 preferably further comprises a hollow path provided in said casing and configured to connect said ink accommodating chamber and said ink discharge opening with each other, a rubber member provided in said hollow path.

[0268]

25 (Aspect 59)

According to aspect 59, there is provided:

An ink cartridge comprising:

a casing including an ink accommodating chamber, an ink discharge opening configured to discharge ink from said ink accommodating chamber, a hollow path connecting said ink accommodating chamber and said ink discharge opening, said casing including a first side surface provided with said ink
 5 discharge opening, a second side surface opposite to said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being provided in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

10 an electrical contact provided on said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with an extending direction of said hollow path; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and having a area
 15 crossing with a direction parallel with the extending direction.

[0269]

(Aspect 60)

According to aspect 60, there is provided:

An ink cartridge comprising:

20 a casing including an ink accommodating chamber, an ink discharge opening configured to discharge ink from said ink accommodating chamber, a hollow path connecting said ink accommodating chamber and said ink discharge opening with each other, said casing including a first side surface provided with said ink discharge opening, a second side surface opposite to said first side
 25 surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being provided in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with an extending direction of said hollow path;

5 a force receiving portion provided at said first side surface in a position above said ink discharge opening and below said electrical contact and configured to receive an urging force for urging said casing in a depth direction which is parallel with the extending direction and which is away from said first side surface toward said second side surface; and

10 an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and including a area crossing with a direction parallel with the extending direction and capable of receiving a limiting force for limiting movement of said casing in the depth direction and against the urging force.

15 **[0270]**

(Aspect 61)

According to aspect 61, there is provided:

An ink cartridge comprising:

a casing including an ink accommodating chamber, an ink discharge
20 opening configured to discharge ink from said ink accommodating chamber, a hollow path connecting said ink accommodating chamber and said ink discharge opening with each other, said casing including a first side surface provided with said ink discharge opening, a second side surface opposite to said first side surface across said ink accommodating chamber, an upper surface and a bottom
25 surface, said ink discharge opening being provided in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided at said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with an extending direction of said hollow path;

a positioning portion provided on said casing in a position above said ink discharge opening and below said substrate and configured to limit movement of said casing in a direction perpendicular to the extending direction;

a force receiving portion provided at said first side surface in a position above said ink discharge opening and below said positioning opening and configured to receive an urging force for urging said casing in a depth direction which is parallel with the extending direction and which is away from said first side surface toward said second side surface; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and including a area crossing with a direction parallel with the extending direction and capable of receiving a limiting force for limiting movement of said casing in the depth direction against the urging force.

[0271]

(Aspect 62)

According to aspect 62, there is provided:

An ink cartridge comprising:

a casing including an ink accommodating chamber, an ink discharge opening configured to discharge ink from said ink accommodating chamber, a hollow path connecting said ink accommodating chamber and said ink discharge opening with each other, said casing including a first side surface provided with said ink discharge opening, a second side surface opposite to said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being provided in a position closer to said

bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel

5 with an extending direction of said hollow path;

a positioning portion provided on said casing in a position above said ink discharge opening and below said substrate; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and including a area

10 crossing with a direction parallel with the extending direction.

[0272]

(Aspect 63)

In an ink cartridge according to aspect 61 or 62, it is preferable that said positioning portion includes a positioning opening provided at said first side

15 surface, said positioning opening being provided in a position closer to said electrical contact than to said ink discharge opening.

[0273]

(Aspect 64)

An ink cartridge according to aspect 59 or 63 preferably further

20 comprises a rubber member provided in said hollow path.

[0274]

(Aspect 65)

According to aspect 65, there is provided:

An ink cartridge comprising:

25 a casing including an ink accommodating chamber, a first side surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, a second side surface opposite from said

first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being disposed in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

5 an electrical contact provided on said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with a center line of said ink discharge opening; and

an engaging portion provided in a position closer to said electrical contact than to said ink discharge opening and having an area crossing with a
10 direction parallel with the center line.

[0275]

(Aspect 66)

According to aspect 66, there is provided:

An ink cartridge comprising:

15 a casing including an ink accommodating chamber, a first side surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, a second side surface opposite from said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being disposed in a position closer to
20 said bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with a center line of said ink discharge opening;

25 a force receiving portion provided at said first side surface in a position above said ink discharge opening and below said electrical contact and configured to receive an urging force for urging said casing in depth direction

which is parallel with the center line and which is away from said first side surface toward second side surface; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and having a area
 5 crossing with a direction parallel with the center line and capable of receiving a limiting force for limiting movement of said casing in the depth direction against the urging force.

[0276]

(Aspect 67)

10 According to aspect 67, there is provided:

An ink cartridge comprising:

a casing including an ink accommodating chamber, a first side surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, a second side surface opposite from said
 15 first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being disposed in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate in a position above
 20 said ink discharge opening and having an area crossing with a direction parallel with a center line of said ink discharge opening;

a positioning portion provided on said casing in a position above said ink discharge opening and below said electrical contact and configured to limit movement of said casing in a direction perpendicular to a direction parallel with
 25 the center line;

a force receiving portion provided at said first side surface in a position above said ink discharge opening and below said positioning portion and

configured to receive an urging force for urging said casing in depth direction which is parallel with the center line and which is away from said first side surface toward second side surface; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and having a area crossing with a direction parallel with the center line and capable of receiving a limiting force for limiting movement of said casing in the depth direction against the urging force.

[0277]

10 (Aspect 68)

According to aspect 68, there is provided:

An ink cartridge comprising:

a casing including an ink accommodating chamber, a first side surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, a second side surface opposite from said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being disposed in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

20 an electrical contact provided on said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with a center line of said ink discharge opening;

a positioning portion provided on said casing in a position above said ink discharge opening and below said electrical contact and closer to said first side surface than to said second side surface; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and having a area

crossing with a direction parallel with the center line.

[0278]

(Aspect 69)

In an ink cartridge according to aspect 67 or 68, it is preferable that
5 said positioning portion includes a positioning opening provided at said first side
surface, and said positioning opening is disposed in a position closer to said
electrical contact than to said ink discharge opening.

[0279]

(Aspect 70)

10 In an ink cartridge according to aspect 65 or 69 preferably further
comprises a hollow path provided in said casing and connecting said ink
accommodating chamber and said ink discharge opening with each other, and a
rubber member provided in said hollow path.

[0280]

15 (Aspect 71)

In an ink cartridge according to aspect 59 or 70, it is preferable that
said engaging portion is disposed in a position closer to said upper surface than to
said bottom surface.

[0281]

20 (Aspect 72)

In an ink cartridge according to aspect 59 or 70, it is preferable that
said engaging portion is provided with a upper surface.

[0282]

(Aspect 73)

25 In an ink cartridge according to aspect 59 or 72, it is preferable that
said engaging portion includes a recess.

[0283]

(Aspect 74)

In an ink cartridge according to aspect 59 or 73, it is preferable that said engaging portion is disposed closer to said first side surface than to said second side surface.

5 **[0284]**

(Aspect 75)

In an ink cartridge according to aspect 59 or 74, it is preferable that said substrate is provided at said first side surface.

[0285]

10 (Aspect 76)

In an ink cartridge according to aspect 59 or 74, it is preferable that said substrate is provided on said casing so as to be inclined relative to said first side surface and the upper surface.

[0286]

15 (Aspect 77)

In an ink cartridge according to aspect 59 or 64, it is preferable that said substrate is supported on said upper surface such that said electrical contact has an area crossing with a direction parallel with the extending direction.

[0287]

20 (Aspect 78)

In an ink cartridge according to aspect 65 or 70, it is preferable that said substrate is supported on said upper surface such that said electrical contact has an area crossing with a direction parallel with the center line.

[0288]

25 (Aspect 79)

In an ink cartridge according to aspect 59 or 78, it is preferable that said substrate is supported directly by said casing or indirectly by said casing

through a supporting member.

[0289]

(Aspect 80)

According to aspect 80, there is provided:

5 An ink cartridge comprising:

a casing including an ink accommodating chamber, a first side surface having a formation region in which an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, an upper surface and a bottom surface, said ink discharge opening being disposed in a

10 position close to said bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate and including an area in a position above said ink discharge opening, the area crossing with a direction parallel with a normal line of said formation region;

15 an engaging portion provided in a position closer to said electrical contact than to said ink discharge opening, said engaging portion including an area crossing with a direction parallel with the normal line of said formation region.

[0290]

20 (Aspect 81)

According to aspect 81, there is provided:

An ink cartridge comprising:

a casing including an ink accommodating chamber, a first side surface having a formation region in which an ink discharge opening configured to

25 discharge ink from said ink accommodating chamber to a outside, a second side surface opposite from said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being

disposed in a position close to said bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate and including an area in a position above said ink discharge opening, the area crossing with a direction

5 parallel with a normal line of said formation region;

a force receiving portion provided at said first side surface in a position above said ink discharge opening below said electrical contact capable of receiving an urging force for urging said casing in a depth direction which is in parallel with the normal line of said formation region and away from said first

10 side surface toward said second side surface;

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening, said engaging portion including a area crossing with a direction parallel with the normal line of said formation region and capable of receiving a limiting force for limiting movement of said casing in the depth direction against the urging force.

15

[0291]

(Aspect 82)

According to aspect 82, there is provided:

An ink cartridge comprising:

20 a casing including an ink accommodating chamber, a first side surface having a formation region in which an ink discharge opening configured to discharge ink from said ink accommodating chamber to a outside, a second side surface opposite from said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being

25 disposed in a position close to said bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate and including an area

in a position above said ink discharge opening, the area crossing with a direction parallel with a normal line of said formation region;

a positioning portion provided on said casing above said ink discharge opening below said electrical contact and configured to limit movement of said casing in a direction perpendicular to a direction parallel with a normal line of said formation region;

a force receiving portion provided at said first side surface in a position above said ink discharge opening below said positioning portion capable of receiving an urging force for urging said casing in a depth direction which is in parallel with the normal line of said formation region and away from said first side surface toward said second side surface; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening, said engaging portion including a area crossing with a direction parallel with the normal line of said formation region and capable of receiving a limiting force for limiting movement of said casing in the depth direction against the urging force.

[0292]

(Aspect 83)

According to aspect 83, there is provided:

An ink cartridge comprising:

a casing including an ink accommodating chamber, a first side surface having a formation region in which an ink discharge opening configured to discharge ink from said ink accommodating chamber to a outside, an upper surface and a bottom surface, said ink discharge opening being disposed in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate and including an area

in a position above said ink discharge opening, the area crossing with a direction parallel with a normal line of said formation region;

a positioning portion provided on said casing above said ink discharge opening below said electrical contact;

- 5 an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening, said engaging portion including a area crossing with a direction parallel with the normal line of said formation region.

[0293]

- 10 (Aspect 84)

In an ink cartridge according to aspect 82 or 83, it is preferable that said positioning portion includes a positioning opening provided at said first side surface, and said positioning opening is disposed in a position closer to said electrical contact than to said ink discharge opening.

- 15 **[0294]**

(Aspect 85)

An ink cartridge according to aspect 80 or 84 preferably further comprises a hollow path provided on said casing and connecting said ink accommodating chamber and said ink discharge opening with each other, and a
20 rubber member provided in said hollow path.

[0295]

(Aspect 86)

- In an ink cartridge according to aspect 80 or 85, it is preferable that said engaging portion is disposed in a position closer to said upper surface than to
25 said bottom surface.

[0296]

(Aspect 87)

In an ink cartridge according to aspect 80 or 85, it is preferable that said engaging portion is provided at said upper surface.

[0297]

(Aspect 88)

5 In an ink cartridge according to aspect 80 or 87, it is preferable that said engaging portion includes a recess.

[0298]

(Aspect 89)

10 In an ink cartridge according to aspect 80 or 88, it is preferable that said substrate is provided at said first side surface.

[0299]

(Aspect 90)

15 In an ink cartridge according to aspect 80 or 88, it is preferable that said substrate is provided on said casing so as to be inclined relative to said first side surface and the upper surface.

[0300]

(Aspect 91)

20 In an apparatus according to aspect 80 or 88, it is preferable that said substrate is supported on said upper surface such that said electrical contact has an area crossing with a direction parallel with the extending direction.

[0301]

(Aspect 92)

25 In an apparatus according to aspect 80 or 91, it is preferable that said substrate is supported directly by said casing or indirectly by said casing through a supporting member.

[0302]

(Aspect 93)

According to aspect 93, there is provided:

An ink jet printer comprising a cartridge mounting portion including an ink receiving tube, an electrical connecting portion and a locking lever, and an ink cartridge mountable to said cartridge mounting portion in a mounting

5 direction crossing with a direction of gravity, said ink cartridge including,

(A) a casing including an ink accommodating chamber configured to accommodate ink to be supplied to the ink receiving tube, said casing including a front surface at a leading side with respect to the mounting direction, an upper surface and a bottom surface, (B) a tube inserting portion into which the ink

10 receiving tube is inserted and which is provided at said front surface in a position closer to said bottom surface than to said upper surface, (C) an electrical contact electrically connectable to the electrical connecting portion and having a area crossing with the mounting direction in a position above said tube inserting portion, and (D) an engaging portion provided in a position closer to said
15 electrical contact than to said tube inserting portion, said engaging portion being engageable with the locking lever to maintain a inserted state in which the ink receiving tube is inserted in said tube inserting portion and a connected state in which said electrical contact is connected with the electrical connecting portion.

[0303]

20 (Aspect 94)

In an ink jet printer according to aspect 93, it is preferable that said cartridge mounting portion further includes an urging spring, and said ink cartridge further includes a force receiving portion capable of receiving, from an urging spring provided in the cartridge mounting portion, the urging force for
25 urging said ink cartridge in a dismounting direction which is opposite to the mounting direction, said force receiving portion being provided in a position above said tube inserting portion and below said electrical contact, wherein said

engaging portion is engageable with said locking lever to maintain the inserted state and the connected state against the urging force.

[0304]

(Aspect 95)

5 In an ink jet printer according to aspect 93, it is preferable that said cartridge mounting portion further includes a positioning member and an urging spring, and (A) a positioning portion engageable with a positioning member provided in the cartridge mounting portion to limit movement of said casing in a direction perpendicular to the mounting direction, said positioning portion being
10 provided in a position above said tube inserting portion and below said electrical contact, and (B) a force receiving portion capable of receiving, from an urging spring, a urging force for urging said ink cartridge in a dismounting direction which is opposite to the mounting direction, said force receiving portion being provided in a position above said tube inserting portion and below said electrical
15 contact, wherein said engaging portion is engageable with said locking lever to maintain the inserted state, the connected state and a engaged state between said positioning portion and the positioning member against the urging force.

[0305]

(Aspect 96)

20 In an ink jet printer according to aspect 93, it is preferable that said cartridge mounting portion further comprising positioning member, and
said ink cartridge further includes a positioning portion provided in a position above said tube inserting portion and below said electrical contact and engageable with a positioning member provided in the cartridge mounting portion
25 to limit movement of said casing in a direction perpendicular to the mounting direction, wherein said engaging portion is engageable with the locking lever to maintain an engaged state between said positioning portion and the positioning

member.

[0306]

(Aspect 97)

According to aspect 97, there is provided:

- 5 An ink cartridge detachably mountable to a cartridge mounting portion provided with an unsealing pin, said ink cartridge comprising:
- a casing including (i) an ink accommodating chamber, (ii) an air vent path connected with said ink accommodating chamber and configured to introduce the ambient air into said ink accommodating chamber, (iii) a through
- 10 hole formation wall in which a through hole into which the unsealing pin is insertable, and (iv) an air vent formation wall in which an air vent opening at an end of said air vent path, said air vent formation wall and being disposed between said through hole formation wall and said ink accommodating chamber; and
- a sealing film covering said air vent opening, said film being capable
- 15 of being unsealed by the unsealing pin having passed through said through hole.

[0307]

(Aspect 98)

According to aspect 98, there is provided:

- An ink cartridge detachably mountable to a cartridge mounting
- 20 portion provided with an ink receiving tube and an unsealing pin, said ink cartridge comprising:
- a casing including (i) an ink accommodating chamber configured to accommodate ink to be supplied into said ink receiving tube, (ii) an air vent path connected with said ink accommodating chamber and configured to introduce the
- 25 ambient air into said ink accommodating chamber, (iii) a tube inserting opening into which said ink receiving tube is insertable, (iv) a through hole into which the unsealing pin is insertable, (v) a side wall provided with said tube inserting

opening and said through hole, (vi) an air vent formation wall in which an air vent opening at a end of said air vent path is formed, said air vent formation wall being disposed between said side wall and said ink accommodating chamber, (vii) a bottom wall and (viii) an upper wall;

5 a sealing film covering said air vent opening, said film being capable of being unsealed by the unsealing pin having passed through said through hole; and

 a second sealing film covering said tube inserting opening, said second sealing film being capable of being unsealed by the ink receiving tube.

10 **[0308]**

(Aspect 99)

According to aspect 99, there is provided:

An ink cartridge detachably mountable to a cartridge mounting portion provided with an unsealing pin, said ink cartridge comprising: &

15 a preparing step of preparing a casing including (i) an ink accommodating chamber, (ii) an air vent path connected with said ink accommodating chamber and configured to introduce the ambient air into said ink accommodating chamber, (iii) a through hole formation wall in which a through hole into which the unsealing pin is insertable, and (iv) an air vent
20 formation wall in which an air vent opening at an end of said air vent path, said air vent formation wall and being disposed between said through hole formation wall and said ink accommodating chamber;

 a sticking step of sticking a sealing film capable of being unsealed by the unsealing pin having passed through said through hole, so as to cover said air
25 vent opening.

[0309]

(Aspect 100)

A manufacturing method according to aspect 99 preferably further comprises an injection step of injecting the ink into said ink accommodating chamber, wherein said injecting step is carried out after said sticking step.

[0310]

5 (Aspect 101)

According to aspect 101, there is provided:

A manufacturing method for manufacturing an ink cartridge detachably mountable to a cartridge mounting portion provided with an ink receiving tube and an unsealing pin, said method comprising:

10 a preparing step of preparing a casing including (i) an ink accommodating chamber configured to accommodate ink to be supplied into said ink receiving tube, (ii) an air vent path connected with said ink accommodating chamber and configured to introduce the ambient air into said ink accommodating chamber, (iii) a tube inserting opening into which said ink
15 receiving tube is insertable, (iv) a through hole into which the unsealing pin is insertable, (v) a side wall provided with said tube inserting opening and said through hole, (vi) an air vent formation wall in which an air vent opening at a end of said air vent path is formed, said air vent formation wall being disposed between said side wall and said ink accommodating chamber, (vii) a bottom wall
20 and (viii) an upper wall;

a sticking step of sticking a sealing film capable of being unsealed by the unsealing pin having passed through said through hole, so as to cover said air vent opening; and

a sticking step of sticking a second sealing film capable of being
25 unsealed by the ink receiving tube, so as to cover said tube inserting opening.

[0311]

(Aspect 102)

A manufacturing method according to aspect 83 preferably further comprises an injection step of injecting the ink into said ink accommodating chamber,

wherein said injecting step is carried out after said first sticking step
5 and before said second sticking step.

[0312]

(Aspect 103)

According to aspect 103, there is provided:

An ink cartridge mountable to a cartridge mounting portion provided
10 with an ink receiving tube, an electrical connecting portion and a positioning member, in a mounting direction crossing with a direction of gravity, said ink cartridge comprising:

a casing including an ink accommodating chamber configured to accommodate ink to be supplied into the ink receiving tube, said casing further
15 including a front surface provided at a leading side with respect to the mounting direction, an upper surface and a bottom surface seven:

a tube inserting portion into which the ink receiving tube is insertable and which is provided at said front surface in a position closer to said bottom surface than to said upper surface;

20 an electrical contact electrically connectable to the electrical connecting portion and provided in a position above said tube inserting portion, said electrical contact including an area crossing with the mounting direction;

a positioning portion provided at a position closer to said electrical contact than to said tube inserting portion above said tube inserting portion and
25 below said electrical contact and engageable with said positioning member to limit movement of said casing in a direction perpendicular to the mounting direction.

[0313]

(Aspect 104)

In an ink cartridge according to a aspect 85, it is preferable that said positioning portion is provided on said front surface and includes a positioning
5 opening into which the positioning member is inserted.

[0314]

(Aspect 105)

According to aspect 105, there is provided:

An ink cartridge mountable to a cartridge mounting portion provided
10 with an ink receiving tube, an electrical connecting portion, a positioning member, an urging spring and a locking lever, in a mounting direction crossing with a direction of gravity, said ink cartridge comprising:

a casing including an ink accommodating chamber configured to accommodate ink to be supplied to the ink receiving tube and a tube inserting
15 opening into which said ink receiving tube is inserted, said casing including a front surface at a leading side with respect to the mounting direction, an upper surface and a bottom surface, and said tube inserting opening is disposed in a position closer to said bottom surface than to said upper surface adjacent to said front surface;

20 a substrate provided at said front surface in a position closer to said than to said bottom surface;

an electrical contact provided on said substrate and electrically connectable to the electrical connecting portion;

a positioning opening provided at said front surface in a position
25 closer to said electrical contact than to said tube inserting opening above said tube inserting opening and below said electrical contact, wherein said positioning member is insertable into said positioning opening to limit movement of said

casing in a direction along said front surface.

[0315]

(Aspect 106)

According to aspect 106, there is provided:

5 An ink cartridge mountable to a cartridge mounting portion provided with an ink receiving tube and a plurality of electrical connecting portions, in a mounting direction crossing with a direction of gravity, said ink cartridge comprising:

 a casing including an ink accommodating chamber configured to
10 accommodate ink to be supplied into said ink receiving tube, said casing further including a first side surface at a leading side with respect to the mounting direction, an upper surface and a bottom surface;

 a tube inserting portion into which the ink receiving tube is insertable, said tube inserting portion being disposed at said first side surface in a position
15 closer to said bottom surface than to said upper surface;

 a substrate provided on said casing above said tube inserting portion and having an area crossing with the mounting direction; and

 a plurality of electrical contacts electrically connectable with said plurality of electrical connecting portions, said electrical contacts being arranged
20 in the area of said substrate in a direction crossing with a direction of a height toward said upper surface from said bottom surface.

[0316]

(Aspect 107)

According to aspect, there is provided:

25 An ink cartridge mountable to a cartridge mounting portion provided with an ink receiving tube and a plurality of electrical connecting portions, in a mounting direction crossing with a direction of gravity, said ink cartridge

comprising:

a casing including an ink accommodating chamber configured to accommodate ink to be supplied into said ink receiving tube, said casing further including a first side surface at a leading side with respect to the mounting

5 direction, an upper surface and a bottom surface;

a tube inserting portion into which the ink receiving tube is insertable, said tube inserting portion being disposed at said first side surface in a position closer to said bottom surface than to said upper surface;

a substrate provided at said upper surface;

10 a plurality of electrical contacts provided on said substrate and electrically connectable with said plurality of electrical connecting portions, said electrical contacts each including an area crossing with the mounting direction, wherein said areas of said electrical contacts are arranged in a direction crossing with a direction of a height toward said upper surface from said bottom surface.

15 **[0317]**

(Aspect 108)

According to aspect 108, there is provided:

An ink cartridge mountable to a cartridge mounting portion provided with an ink receiving tube and a plurality of electrical connecting portions, in a

20 mounting direction crossing with a direction of gravity, said ink cartridge comprising:

a casing including an ink accommodating chamber configured to accommodate ink to be supplied into said ink receiving tube, said casing further including a first side surface at a leading side with respect to the mounting

25 direction, a second side surface at the trailing side with respect to the mounting direction, a third side surface connecting said first side surface and said second side surface with each other, a fourth side surface in an opposite side from said

third side surface across said ink accommodating chamber and connecting said first side surface and said second side surface, an upper surface and a bottom surface;

a tube inserting portion into which the ink receiving tube is insertable,
5 said tube inserting portion being disposed at said first side surface in a position closer to said bottom surface than to said upper surface;

a substrate provided at said first side surface above said tube inserting portion; and

a plurality of electrical contacts electrically connectable and said
10 plurality of electrical connecting portions, said electrical contacts being arranged on said substrate in a direction perpendicular to said third side surface and said fourth side surface.

[0318]

(Aspect 109)

15 According to aspect 109, there is provided:

An ink cartridge comprising:

a casing including a plurality of side surfaces, an upper surface and a bottom surface on the basis of an orientation of said ink cartridge in use, said casing further including an ink accommodating chamber and an ink discharge
20 opening configured to discharge ink from said ink accommodating chamber to an outside, wherein said plurality of side surfaces include a first side surface, and said ink discharge opening is disposed at a position closer to said bottom surface than to said upper surface;

a substrate provided at said first side surface;

25 a plurality of electrical contacts provided above said ink discharge opening, said electrical contacts being arranged on said substrate in a direction of height toward said upper surface from said bottom surface.

[0319]

(Aspect 110)

According to aspect 110, there is provided:

An ink cartridge comprising:

- 5 a casing including a plurality of side surfaces, an upper surface and a bottom surface on the basis of an orientation of said ink cartridge in use, said casing further including an ink accommodating chamber and an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, wherein said plurality of side surfaces include a first side surface, and
- 10 said ink discharge opening is disposed at a position closer to said bottom surface than to said upper surface;

 a substrate provided on said casing and having an area crossing with a normal line of said first side surface;

- a plurality of electrical contacts provided above said ink discharge
- 15 opening, said electrical contacts be arranged in said area of said substrate in a direction crossing with a direction of height toward said upper surface from said bottom surface.

[0320]

(Aspect 111)

- 20 According to aspect 111, there is provided:

an ink cartridge comprising:

- a casing having a substantially rectangular parallelepiped shape and including an ink accommodating chamber, said casing including (a) a first surface provided with an ink discharge opening configured to discharge ink from said ink
- 25 accommodating chamber to an outside, (b) a second surface opposite from said first surface across said ink accommodating chamber, (c) a third surface crossing with said first surface and said second surface and having an area larger than

those of said first surface and said second surface, (d) a fourth surface opposite from said third surface across said ink accommodating chamber and having an area larger than those of said first surface and said second surface, (e) a fifth surface crossing with said first surface, said second surface, said third surface and said fourth surface and having an area larger than those of said first surface, said second surface, said third surface and said fourth surface, (f) a sixth surface opposite from said fifth surface across said ink accommodating chamber and having an area larger than those of said first surface, said second surface, said third surface and said fourth surface, and (g) said ink discharge opening being disposed closer to said third surface than to said fourth surface;

a substrate provided at said first surface such that said substrate is in a position above said ink discharge opening in a state in which said third surface is a bottom surface;

a plurality of electrical contacts provided on said substrate and arranged in a direction crossing with a direction away from said third surface toward said fourth surface;

[0321]

(Aspect 112)

According to aspect 112, there is provided:

An ink cartridge comprising:

a casing including an ink accommodating chamber, an ink discharge opening configured to discharge ink from said ink accommodating chamber, a hollow path connecting said ink accommodating chamber and said ink discharge opening, said casing further including a side surface provided with said ink discharge opening, an upper surface and a bottom surface, wherein said ink discharge opening is disposed in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

a plurality of electrical contacts provided on said substrate, said electrical contacts being arranged in the direction of height toward said upper surface from said bottom surface, wherein said electrical contacts each including
5 a area above said ink discharge opening, the area crossing with a direction parallel with the direction in which said hollow path extends.

[0322]

(Aspect 113)

According to aspect 113, there is provided:

10 An ink cartridge comprising:

a casing including an ink accommodating chamber, a side surface in which an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, an upper surface and a bottom surface, wherein said ink discharge opening is disposed in a position closer to said bottom
15 surface than to said upper surface;

a substrate provided on said casing;

a plurality of electrical contacts provided on said substrate, said electrical contacts being arranged in the direction of height toward said upper surface from said bottom surface, wherein said electrical contacts each including
20 a area above said ink discharge opening, said areas crossing with a direction parallel with a center line of said ink discharge opening.

[0323]

(Aspect 114)

According to aspect 114, there is provided:

25 An ink cartridge comprising:

a casing including an ink accommodating chamber, a side surface having a formation region in which an ink discharge opening configured to

discharge ink from said ink accommodating chamber to a outside, an upper surface and a bottom surface, wherein said ink discharge opening is disposed in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

5 a plurality of electrical contacts provided on said substrate, said electrical contacts being arranged in the direction of height toward said upper surface from said bottom surface, wherein said electrical contacts each including an area above said ink discharge opening, said area crossing with a direction parallel with a normal line of said formation region.

10

[INDUSTRIAL APPLICABILITY]

[0324] A novel ink cartridge and a novel ink jet printer with which the satisfactory connection between the ink cartridge and the cartridge mounting portion can be accomplished are provided.

15 [Reference numerals]

1: ink cartridge

2: casing

2a: upper surface

2b: bottom surface

20 2c: front surface

2d: rear surface

2e: left surface

2f: right-hand surface

3: substrate

25 4: electrical contact (electrode pad)

4a: contact position

5: storing element

- 6: positioning portion (positioning hole, positioning opening)
- 7: air vent (air vent)
- 8: tube inserting portion (tube inserting opening)
- 9: discrimination portion
- 5 10: position regulation surface
- 11: ink accommodating chamber
- 12: flexible member
- 13: negative pressure generation spring
- 14: plate member
- 10 15: filter
- 16: air vent path
- 17: air vent sealing film
- 18: tube inserting opening sealing film
- 19: sealing member
- 15 20: sealing member unit
- 21: outer casing
- 22: tube insertion path
- 23: ejection spring contact portion (force receiving portion)
- 24: engaging portion (recess)
- 20 25: label
- 26: ambient air opening
- 27: penetrated portion (through-opening)
- 30: printer main assembly
- 31: carriage
- 25 32: ink jet head
- 33: mounting portion (cartridge mounting portion, cartridge holder)
- 34: feeding means

- 35: controller
- 36: input/output portion
- 37: print medium
- 38: head unit (cartridge mounting unit)
- 5 40: first casing member
- 41: second casing member
- 46: supporting member of electrical connecting portion
- 47: electrical connection unit
- 48: plate
- 10 49: frame
- 50: mounting guide
- 51: unsealing member (unsealing pin)
- 52: ink receiving member (ink receiving tube)
- 53: positioning member (positioning pin)
- 15 54: locking portion (locking projection)
- 55: electrical connecting portion (electrical terminal, main assembly side electrical contact)
- 56: positioning wall
- 57: urging member (ejection spring)
- 20 58: locking lever
- 59: joint unit (main assembly side connecting unit)
- 60: discrimination member
- 61: electrical contact (electrode pad)
- 61a: contact position.
- 25 62: storing element.
- 63: substrate.
- 71: electrical contact (electrode pad).

	71a: contact position.
	72: storing element.
	73: substrate.
	74: sealing member.
5	75: valve.
	76: spring.
	77: interrelation valve.
	78: supporting shaft.
	81: substrate supporting member.
10	101: ink cartridge.
	201: ink cartridge.
	224: engaging portion (projection).
	301: ink cartridge.
	324: engaging portion (curved surface or inclined surface).
15	401: ink cartridge.
	424: engaging portion (flat surface).
	501: ink cartridge.
	524: engaging portion (projection).
	601: ink cartridge.
20	624: engaging portion.
	701: ink cartridge.
	724: engaging portion.
	725: elastic member.
	801: ink cartridge.
25	901: ink cartridge.
	936: projection.
	937: elastic member (spring).

	938: projection.
	1001: ink cartridge.
	1003: substrate.
	1004: electrical contact.
5	1037: rotation shaft.
	1101: ink cartridge.
	1103: substrate.
	1104: electrical contact.
	1105: storing element.
10	1201: ink cartridge.
	1203: substrate.
	1204: electrical contact.
	1205: storing element.
	1301: ink cartridge.
15	1303: substrate.
	1304: electrical contact.
	1305: storing element.
	1401: ink cartridge.
	1406: positioning portion (polarity of projections).
20	1501: ink cartridge.
	1506: positioning portion (slit formation member).
	1601: ink cartridge.
	1606: positioning portion.
	1701: ink cartridge.
25	1702c1: first front wall forming member.
	1702c2: second front wall forming member.
	1801: ink cartridge.

	1802: casing.
	1901: ink cartridge.
	1902: casing.
	1924: engaging portion.
5	1925: rotation shaft.
	1926: engagement lever.
	2001: ink cartridge.
	2017: air vent sealing film.
	2101: ink cartridge.
10	2201: ink cartridge.
	2301: ink cartridge.

CLAIMS

1. An ink cartridge mountable to a cartridge mounting portion provided with an ink receiving tube, an electrical connecting portion and a locking lever, in
5 a mounting direction crossing with a direction of gravity, said ink cartridge comprising:

a casing including an ink accommodating chamber configured to accommodate ink to be supplied to the ink receiving tube, said casing including a front surface at a leading side with respect to the mounting direction, an upper
10 surface and a bottom surface;

a tube inserting portion into which the ink receiving tube is insertable and which is provided at said front surface in a position closer to said bottom surface than to said upper surface;

an electrical contact electrically connectable to the electrical
15 connecting portion and provided in a position above said tube inserting portion, said electrical contact including an area crossing with the mounting direction; and

an engaging portion provided in a position closer to said electrical contact than to said tube inserting portion, said engaging portion being engageable with the locking lever to maintain a inserted state in which the ink
20 receiving tube is inserted in said tube inserting portion and a connected state in which said electrical contact is connected with the electrical connecting portion.

2. An ink cartridge according to Claim 1, further comprising a force receiving portion capable of receiving, from an urging spring provided in the
25 cartridge mounting portion, the urging force for urging said ink cartridge in a dismounting direction which is opposite to the mounting direction, said force receiving portion being provided in a position above said tube inserting portion

and below said electrical contact, wherein said engaging portion is engageable with said locking lever to maintain the inserted state and the connected state against the urging force.

5 3. An ink cartridge according to Claim 2, wherein said force receiving portion is capable of receiving the urging force to release the inserted state and the connected state with release of an engaged state between said engaging portion and the locking lever.

10 4. An ink cartridge according to Claim 1, further comprising a positioning portion engageable with a positioning member provided in the cartridge mounting portion to limit movement of said casing in a direction perpendicular to the mounting direction, said positioning portion being provided in a position above said tube inserting portion and below said electrical contact,
15 and

 a force receiving portion capable of receiving, from an urging spring provided in the cartridge mounting portion, the urging force for urging said ink cartridge in a dismounting direction which is opposite to the mounting direction, said force receiving portion being provided in a position above said tube inserting
20 portion and below said electrical contact,

 wherein said engaging portion is engageable with said locking lever to maintain the inserted state, the connected state and a engaged state between said positioning portion and the positioning member against the urging force.

25 5. An apparatus according to Claim 4, wherein said force receiving portion is capable of receiving the urging force to release the inserted state the connected state and the engaged state between said positioning portion and the

positioning member with release of a engaged state between said engaging portion and the locking lever.

6. An ink cartridge according to Claim 1, further comprising a
5 positioning portion provided in a position above said tube inserting portion and below said electrical contact and engageable with a positioning member provided in the cartridge mounting portion to limit movement of said casing in a direction perpendicular to the mounting direction, wherein said engaging portion is engageable with the locking lever to maintain an engaged state between said
10 positioning portion and the positioning member.

7. An ink cartridge according to Claim 4 or 6, wherein said positioning portion is disposed in a position close to said electrical contact than to said tube inserting portion.

15

8. An ink cartridge according to Claim 4 or 7, wherein said positioning portion is disposed at said front surface.

9. An ink cartridge according to Claim 4 or 8, wherein said positioning
20 portion includes a positioning opening into which the positioning member is inserted.

10. An ink cartridge according to Claim 4 or 9, wherein the direction perpendicular to the mounting direction is a direction away from said bottom
25 surface toward said upper surface.

11. An apparatus according to Claim 4 or 9, wherein the direction

perpendicular to the mounting direction is a direction along said front surface.

12. An ink cartridge according to Claim 2 or 5, wherein a part of said front surface functions as said force receiving member.

5

13. An ink cartridge according to Claim 1 or 12, wherein said engaging portion is disposed in a position closer to said upper surface than to said bottom surface.

10 14. An ink cartridge according to Claim 1 or 12, wherein said engaging portion is disposed at said upper surface.

15. An ink cartridge according to Claim 1 or 14, wherein said engaging portion is a recess engageable with a projection of said locking lever.

15

16. An ink cartridge according to Claim 1 or 15, wherein said casing further includes a rear surface opposite from said front surface with said ink accommodating chamber therebetween, said rear surface is in a trailing side with respect to the mounting direction, wherein said engaging portion is disposed in a position closer to said front surface than to said rear surface.

20

17. An ink cartridge according to Claim 1 or 16, further comprising an elastically deformable elastic portion configured to move said engaging portion relative to said casing.

25

18. An ink cartridge according to Claim 1 or 17, further comprising a substrate provided with said electrical contact.

19. An ink cartridge according to Claim 18, wherein said substrate is provided at said front surface.

5 20. An ink cartridge according Claim 18, wherein said substrate is provided on said casing so as to be inclined relative to said front surface and said upper surface.

21. An ink cartridge according Claim 18, wherein said substrate is
10 supported on said upper surface so that said electrical contact has an area crossing with the mounting direction.

22. An ink cartridge according to Claim 18, further comprising moving means configured to move said substrate relative to said casing.

15

23. An ink cartridge according to Claim 18 or 22, wherein said substrate is directly supported by said casing or is indirectly supported by said casing through a supporting member.

20 24. An ink cartridge according to Claim 1 or 23, further comprising an air vent path provided on said casing and configured to introduce ambient air into said ink accommodating chamber, said air vent path having one end portion provided with an air vent and the other end portion connected with said ink accommodating chamber, and a sealing film sealing said air vent, said sealing
25 film being unsealable by an unsealing pin provided on said cartridge mounting portion.

25. An ink cartridge according to Claim 24, further comprising a through hole into which the unsealing pin is insertable, said through hole is provided at said front surface, and said sealing film being disposed at such a position that said sealing film is capable of being unsealed by the unsealing pin passed through said
5 through hole.

26. An ink cartridge according to Claim 24 or 25, wherein said casing is provided with an air vent formation wall provided with said air vent, and said air vent formation wall being provided between said front surface and said ink
10 accommodating chamber.

27. An ink cartridge according to Claim 2 or 25, further comprising an air vent path provided on said casing and configured to introduce ambient air into said ink accommodating chamber, said air vent path having one end portion
15 provided with an air vent and the other end portion connected with said ink accommodating chamber,

a through hole into which the unsealing pin provided on said cartridge mounting portion is insertable, said through hole being provided at said front surface so as to be inside said force receiving portion, and
20 a sealing film capable of being unsealed by the unsealing pin passed through said through hole.

28. An ink cartridge according to Claim 27, wherein said sealing film is provided on air vent formation wall disposed in a position in a rear side of said
25 front surface so as to be unsealed by the unsealing pin after said force receiving portion disposed at said front surface receives the urging force.

29. An ink cartridge according to Claim 1 or 28, further comprising a tube insertion path provided in said casing to connect said tube inserting portion and said ink accommodating chamber with each other, an elastic member provided in said tube insertion path and elastically deformable with insertion of said ink
5 receiving tube into said tube insertion path.

30. An ink cartridge according to Claim 29, wherein said elastic member includes a rubber member contactable to an outer peripheral surface of said ink receiving tube inserted into the tube insertion path.

10

31. An ink cartridge mountable to a cartridge mounting portion provided with an ink receiving tube, an electrical connecting portion and a locking lever, in a mounting direction crossing with a direction of gravity, said ink cartridge comprising:

15 a casing including an ink accommodating chamber configured to accommodate ink to be supplied to the ink receiving tube and a tube inserting opening into which said ink receiving tube is inserted, said casing including a front surface at a leading side with respect to the mounting direction, an upper surface and a bottom surface, and said tube inserting opening is disposed in a
20 position closer to said bottom surface than to said upper surface adjacent to said front surface;

a substrate provided at said front surface in a position above said tube inserting opening;

25 an electrical contact provided on said substrate and electrically connectable to the electrical connecting portion; and

an engaging portion provided on said upper surface in a position closer to front surface than to rear surface, said engaging portion is engageable

with the locking lever to maintain an inserted state in which the ink receiving tube is inserted in said tube inserting portion and a connected state in which said electrical contact is connected with the electrical connecting portion.

- 5 32. An ink cartridge mountable to a cartridge mounting portion provided with an ink receiving tube, an electrical connecting portion, an urging spring and a locking lever, in a mounting direction crossing with a direction of gravity, said ink cartridge comprising:

 a casing including an ink accommodating chamber configured to
10 accommodate ink to be supplied to the ink receiving tube and a tube inserting opening into which said ink receiving tube is inserted, said casing including a front surface at a leading side with respect to the mounting direction, an upper surface and a bottom surface, and said tube inserting opening is disposed in a position closer to said bottom surface than to said upper surface adjacent to said
15 front surface;

 a substrate provided at said front surface in a position above said tube inserting opening;

 an electrical contact provided on said substrate and electrically connectable to the electrical connecting portion;

20 a force receiving portion provided on said front surface in a position above said tube inserting opening below said electrical contact and configured to receive from the urging spring an urging force for urging said ink cartridge in a dismounting direction which is opposite the mounting direction; and

 an engaging portion provided on said upper surface in a position
25 closer to front surface than to rear surface, said engaging portion is engageable with the locking lever to maintain, against the urging force, an inserted state in which the ink receiving tube is inserted in said tube inserting portion and a

connected state in which said electrical contact is connected with said electrical connecting portion.

33. An ink cartridge mountable to a cartridge mounting portion provided
5 with an ink receiving tube, an electrical connecting portion, a positioning member, an urging spring and a locking lever, in a mounting direction crossing with a direction of gravity, said ink cartridge comprising:

a casing including an ink accommodating chamber configured to
accommodate ink to be supplied to the ink receiving tube and a tube inserting
10 opening into which said ink receiving tube is inserted, said casing including a front surface at a leading side with respect to the mounting direction, an upper surface and a bottom surface, and said tube inserting opening is disposed in a position closer to said bottom surface than to said upper surface adjacent to said front surface;

15 a substrate provided at said front surface in a position above said tube inserting opening;

an electrical contact provided on said substrate and electrically connectable to the electrical connecting portion;

a positioning opening into which the positioning member is capable of
20 inserting to limit movement of said casing in a direction along said front side, said positioning opening being provided at said front surface in a position above said tube inserting opening and below said electrical contact in a position closer to said electrical contact than to said tube inserting opening;

a force receiving portion provided at said front surface in a position
25 above said tube inserting opening below said electrical contact and configured to receive from the urging spring an urging force for urging said ink cartridge in a dismounting direction which is opposite the mounting direction; and

an engaging portion provided on said upper surface in a position closer to front surface than to rear surface, said engaging portion is engageable with the locking lever to maintain, against the urging force, a inserted state in which the ink receiving tube is inserted in said tube inserting portion, a connected
5 state in which said electrical contact is connected with said electrical connecting portion and an inserted state in which the positioning member is inserted in said positioning opening.

34. An ink cartridge according to Claim 31 or 33, further comprising a
10 tube insertion path provided on said casing to connect said tube inserting opening and said ink accommodating chamber with each other, an elastic member provided in said tube insertion path and elastically deformable with insertion of said ink receiving tube into said tube insertion path.

15 35. An apparatus according to Claim 34, wherein said elastic member includes a rubber member contactable to an outer peripheral surface of said ink receiving tube inserted into the tube insertion path.

36. An ink cartridge according to Claim 31 or 35, further comprising an air
20 vent path provided on said casing and configured to introduce ambient air into said ink accommodating chamber, said air vent path having one end portion provided with an air vent and the other end portion connected with said ink accommodating chamber, a sealing film sealing said air vent and capable of being unsealed by an unsealing pin provided in the cartridge mounting portion.

25

37. An ink cartridge according to Claim 36, further comprising a through hole into which the unsealing pin is insertable, said through hole being provided

at the front surface, said sealing film being disposed at such a position that said sealing film being capable of being unsealed by the unsealing pin passed through said through hole.

- 5 38. An ink cartridge according to Claim 36 or 37, wherein said casing is provided with an air vent formation wall provided with said air vent, and wherein said air vent formation wall is provided between said front surface and said ink accommodating chamber with respect to a direction away from said front side toward said rear side.

10

39. An ink cartridge comprising:
- a casing including a plurality of side surfaces, an upper surface and bottom surface as defined on the basis of use state of said ink cartridge and provided with an ink accommodating chamber and the ink discharge opening
- 15 configured to discharge the ink from said ink accommodating chamber to an outside, said side surface including a first side surface and a second side surface at an opposite side from said first side surface across said ink accommodating chamber, said ink discharge opening being provided at said first side surface in a position closer to said bottom surface than to said upper surface;
- 20 an electrical contact provided in a position above said ink discharge opening;
- a substrate provided at said first side surface and provided with said electrical contact; and
- an engaging portion provided at said upper surface in a position closer
- 25 to said electrical contact than to said ink discharge opening and closer to said first side surface than to said second side surface.

40. An ink cartridge comprising:

a casing including a plurality of side surfaces, an upper surface and bottom surface as defined on the basis of use state of said ink cartridge and provided with an ink accommodating chamber and a ink discharge opening
5 configured to discharge the ink from said ink accommodating chamber to an outside, said side surface including a first side surface and a second side surface at an opposite side from said first side surface across said ink accommodating chamber, said ink discharge opening being provided at said first side surface in a position closer to said bottom surface than to said upper surface;

10 an electrical contact provided in a position above said ink discharge opening;

a substrate provided at said first side surface and provided with said electrical contact;

a force receiving portion provided at said first side surface in a
15 position above said ink discharge opening and below said electrical contact and configured to receive an urging force for urging said casing in a direction away from said first side surface toward said second side surface; and

an engaging portion provided at said upper surface in a position closer to said electrical contact than to said ink discharge opening and closer to said first
20 side surface than to said second side surface and configured to receive a limiting force for limiting movement of said casing against the urging force in the direction.

41. An ink cartridge comprising:

25 a casing including a plurality of side surfaces, an upper surface and bottom surface as defined on the basis of use state of said ink cartridge and provided with an ink accommodating chamber and an ink discharge opening

configured to discharge the ink from said ink accommodating chamber to an outside, said side surface including a first side surface and a second side surface at an opposite side from said first side surface across said ink accommodating chamber, said ink discharge opening being provided at said first side surface in a position closer to said bottom surface than to said upper surface;

an electrical contact provided in a position above said ink discharge opening;

a substrate provided at said first side surface and provided with said electrical contact;

a positioning opening provided at said first side surface in a position above said ink discharge opening and below said electrical contact and closer to said electrical contact than to said ink discharge opening;

a force receiving portion provided at said first side surface in a position above said ink discharge opening and below said positioning opening and configured to receive an urging force for urging said casing in a direction away from said first side surface toward said second side surface; and

an engaging portion provided at said upper surface in a position closer to said electrical contact than to said ink discharge opening and closer to said first side surface than to said second side surface and configured to receive a limiting force for limiting movement of said casing against the urging force in the direction.

42. An ink cartridge comprising:

a casing including a plurality of side surfaces, an upper surface and bottom surface as defined on the basis of use state of said ink cartridge and provided with an ink accommodating chamber and an ink discharge opening configured to discharge the ink from said ink accommodating chamber to an

outside, said side surface including a first side surface and a second side surface at an opposite side from said first side surface across said ink accommodating chamber, said ink discharge opening being provided at said first side surface in a position closer to said bottom surface than to said upper surface;

5 an electrical contact provided in a position above said ink discharge opening;

 a substrate provided at said first side surface and provided with said electrical contact;

 a positioning opening provided at said first side surface in a position
10 above said ink discharge opening and below said electrical contact and closer to said electrical contact than to said ink discharge opening; and

 an engaging portion provided at said upper surface in a position closer to said electrical contact than to said ink discharge opening and closer to said first side surface than to said second side surface.

15

43. An ink cartridge according to Claim 39 or 42, wherein said engaging portion includes a recess.

44. An ink cartridge according to Claim 39 or 43, wherein said side
20 surfaces further including a third side surface connected with said first side surface, said second side surface, said upper surface and said bottom surface, and a fourth side surface opposite from said third side surface across said ink accommodating chamber and connected with said first side surface, said second side surface, and said upper surface and said bottom surface,

25 wherein said third side surface has a larger area than those of said first side surface, said second side surface, said upper surface and said bottom surface,
 wherein said fourth side surface has a larger area than those of said

first side surface, said second side surface, said upper surface and said bottom surface,

wherein said first side surface has a smaller area than those of said third side surface, said fourth side surface, said upper surface and said bottom surface, and

wherein said second side surface has a smaller area than those of said third side surface, said fourth side surface, said upper surface and said bottom surface.

10 45. An ink cartridge according to Claim 39 or 44, further comprising an air vent path provided on said casing and configured to introduce ambient air into said ink accommodating chamber, said air vent path having one end portion provided with an air vent and the other end portion connected with said ink accommodating chamber, a through hole provided at said first side surface;

15 a sealing film sealing said air vent in a position in a rear side of the through hole with respect to a direction away from said first side surface toward the second side surface.

20 46. An ink cartridge according to claim 45, wherein said casing is provided with an air vent formation wall provided with said air vent, and wherein said air vent formation wall is provided between said first side surface and said ink accommodating chamber with respect to a direction away from said first side surface side toward said second side surface.

25 47. An ink cartridge comprising:
a casing including an ink accommodating chamber and including a first surface provided with an ink discharge opening configured to discharge ink

from said ink accommodating chamber to an outside, a second surface opposite from said first surface across said ink accommodating chamber, a third surface connecting said first surface and said second surface with each other and having an area larger than those of said first surface and said second surface, and a fourth
 5 surface opposite from said third surface across said ink accommodating chamber, said ink discharge opening being disposed in a position closer to said third surface than to said fourth surface;

an electrical contact disposed in a position above said ink discharge opening in the state in which said third surface is a bottom surface;

10 a substrate provided at said first surface and supporting said electrical contact; and

an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said electrical contact than to said ink discharge opening and closer to said first surface than to said second surface.

15

48. An ink cartridge comprising:

a casing including an ink accommodating chamber and including a first surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, a second surface opposite
 20 from said first surface across said ink accommodating chamber, a third surface connecting said first surface and said second surface with each other and having an area larger than those of said first surface and said second surface, and a fourth surface opposite from said third surface across said ink accommodating chamber, said ink discharge opening being disposed in a position closer to said third
 25 surface than to said fourth surface;

an electrical contact disposed in a position above said ink discharge opening in the state in which said third surface is a bottom surface;

a substrate provided at said first surface and supporting said electrical contact;

a force receiving portion provided at said first surface in a position below said substrate and above said ink discharge opening in a state in which said
 5 third surface is a bottom surface and configured to receive an urging force for urging said casing in a direction away from said first surface toward said second surface in a state in which said third surface is a bottom surface; and

an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said electrical contact than to said ink discharge
 10 opening and closer to said first surface than to said second surface, said engaging portion being capable of receiving a limiting force for limiting movement of said casing in a direction away from said first surface toward second surface.

49. An ink cartridge comprising:

15 a casing including an ink accommodating chamber and including a first surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, a second surface opposite from said first surface across said ink accommodating chamber, a third surface connecting said first surface and said second surface with each other and having
 20 an area larger than those of said first surface and said second surface, and a fourth surface opposite from said third surface across said ink accommodating chamber, said ink discharge opening being disposed in a position closer to said third surface than to said fourth surface;

an electrical contact disposed in a position above said ink discharge
 25 opening in the state in which said third surface is a bottom surface;

a substrate provided at said first surface and supporting said electrical contact;

a positioning opening provided at said first surface in a position above said ink discharge opening and below said substrate in a state in which said third surface is a bottom surface and closer to said substrate than to said ink discharge opening and configured to limit movement of said casing in a direction along the
5 first surface;

a force receiving portion provided at said first surface in a position below said positioning opening and above said ink discharge opening in a state in which said third surface is a bottom surface and configured to receive an urging force for urging said casing in a direction away from said first surface toward said
10 second surface in a state in which said third surface is a bottom surface; and

an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said electrical contact than to said ink discharge opening and closer to said first surface than to said second surface, said engaging portion being capable of receiving a limiting force for limiting movement of said
15 casing in a direction from said first surface toward second surface.

50. An ink cartridge comprising:

a casing including an ink accommodating chamber and including a first surface provided with an ink discharge opening configured to discharge ink
20 from said ink accommodating chamber to an outside, a second surface opposite from said first surface across said ink accommodating chamber, a third surface connecting said first surface and said second surface with each other and having an area larger than those of said first surface and said second surface, and a fourth surface opposite from said third surface across said ink accommodating chamber,
25 said ink discharge opening being disposed in a position closer to said third surface than to said fourth surface;

an electrical contact disposed in a position above said ink discharge

opening in the state in which said third surface is a bottom surface;

a substrate provided at said first surface and supporting said electrical contact;

a positioning opening provided at said first surface in a position above
 5 said ink discharge opening and below said substrate in a state in which said third surface is a bottom surface and closer to said substrate than to said ink discharge opening; and

an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said electrical contact than to said ink discharge
 10 opening and closer to said first surface than to said second surface, said engaging portion having an area crossing with a direction parallel with a normal line of said substrate.

51. An ink cartridge according to Claim 47 or 50, wherein said casing
 15 further includes a fifth surface connecting with said first surface, said second surface, said third surface and said fourth surface and having an area larger than those of said first surface, said second surface, said third surface and said fourth surface, and includes a sixth surface opposite away from said fifth surface.

20 52. An ink cartridge comprising:
 a casing having a substantially rectangular parallelepiped shape and including an ink accommodating chamber, said casing including (a) a first surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, (b) a second surface opposite from said
 25 first surface across said ink accommodating chamber, (c) a third surface crossing with said first surface and said second surface and having an area larger than those of said first surface and said second surface, (d) a fourth surface opposite

from said third surface across said ink accommodating chamber and having an area larger than those of said first surface and said second surface, (e) a fifth surface crossing with said first surface, said second surface, said third surface and said fourth surface and having an area larger than those of said first surface, said
 5 second surface, said third surface and said fourth surface, (f) a sixth surface opposite from said fifth surface across said ink accommodating chamber and having an area larger than those of said first surface, said second surface, said third surface and said fourth surface, and (g) said ink discharge opening being disposed closer to said third surface than to said fourth surface;

10 a substrate provided at said first surface such that said substrate is in a position above said ink discharge opening in a state in which said third surface is a bottom surface;

a plurality of electrical contacts provided on said substrate and arranged in a direction crossing with a direction away from said third surface
 15 toward said fourth surface; and

an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said substrate than to said ink discharge opening and closer to said first surface than to said second surface.

20 53. An ink cartridge comprising:

a casing having a substantially rectangular parallelepiped shape and including an ink accommodating chamber, said casing including (a) a first surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, (b) a second surface opposite from said
 25 first surface across said ink accommodating chamber, (c) a third surface crossing with said first surface and said second surface and having an area larger than those of said first surface and said second surface, (d) a fourth surface opposite

from said third surface across said ink accommodating chamber and having an area larger than those of said first surface and said second surface, (e) a fifth surface crossing with said first surface, said second surface, said third surface and said fourth surface and having an area larger than those of said first surface, said
5 second surface, said third surface and said fourth surface, (f) a sixth surface opposite from said fifth surface across said ink accommodating chamber and having an area larger than those of said first surface, said second surface, said third surface and said fourth surface, and (g) said ink discharge opening being disposed closer to said third surface than to said fourth surface;

10 a substrate provided at said first surface such that said substrate is in a position above said ink discharge opening in a state in which said third surface is a bottom surface;

a plurality of electrical contacts provided on said substrate and arranged in a direction crossing with a direction away from said third surface
15 toward said fourth surface;

a force receiving portion provided at said first surface in a position above said ink discharge opening below said substrate in a state in which said third surface is a bottom surface and configured to receive an urging force for urging said casing in a direction away from said first surface toward said second
20 surface; and

an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said substrate than to said ink discharge opening and closer to said first surface than to said second surface and configured to receive a regulating force for limiting movement of said casing in the direction
25 away from said first surface toward said second surface against the urging force.

54. An ink cartridge comprising:

a casing having a substantially rectangular parallelepiped shape and including an ink accommodating chamber, said casing including (a) a first surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, (b) a second surface opposite from said first surface across said ink accommodating chamber, (c) a third surface crossing with said first surface and said second surface and having an area larger than those of said first surface and said second surface, (d) a fourth surface opposite from said third surface across said ink accommodating chamber and having an area larger than those of said first surface and said second surface, (e) a fifth surface crossing with said first surface, said second surface, said third surface and said fourth surface and having an area larger than those of said first surface, said second surface, said third surface and said fourth surface, (f) a sixth surface opposite from said fifth surface across said ink accommodating chamber and having an area larger than those of said first surface, said second surface, said third surface and said fourth surface, and (g) said ink discharge opening being disposed closer to said third surface than to said fourth surface;

a substrate provided at said first surface such that said substrate is in a position above said ink discharge opening in a state in which said third surface is a bottom surface;

a plurality of electrical contacts provided on said substrate and arranged in a direction crossing with a direction away from said third surface toward said fourth surface;

a positioning opening provided at said first surface in a position above said ink discharge opening and below said substrate in a state in which said third surface is a bottom surface and closer to said plurality of electrical contacts than said ink discharge opening and configured to limit movement of said casing in a direction along said first surface;

a force receiving portion provided at said first surface in a position above said ink discharge opening below said positioning opening in a state in which said third surface is a bottom surface and configured to receive an urging force for urging said casing in a direction away from said first surface toward said
 5 second surface; and

an engaging portion in the form of a recess and provided at said fourth surface in a position closer to said substrate than to said ink discharge opening and closer to said first surface than to said second surface and configured to receive a regulating force for limiting movement of said casing in the direction
 10 away from said first surface toward said second surface against the urging force.

55. An ink cartridge comprising:

a casing having a substantially rectangular parallelepiped shape and including an ink accommodating chamber, said casing including (a) a first surface
 15 provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to a outside, (b) a second surface opposite from said first surface across said ink accommodating chamber, (c) a third surface crossing with said first surface and said second surface and having a area larger than those of said first surface and said second surface, (d) a fourth surface opposite from
 20 said third surface across said ink accommodating chamber and having a area larger than those of said first surface and said second surface, (e) a fifth surface crossing with said first surface, said second surface, said third surface and said fourth surface and having a area larger than those of said first surface, said second surface, said third surface and said fourth surface, (f) a sixth surface
 25 opposite from said fifth surface across said ink accommodating chamber and having a area larger than those of said first surface, said second surface, said third surface and said fourth surface, and (g) said ink discharge opening being disposed

closer to said third surface than to said fourth surface;

a substrate provided at said first surface such that said substrate is in a position above said ink discharge opening in a state in which said third surface is a bottom surface;

5 a substrate provided at said first surface such that said substrate is in a position above said ink discharge opening in a state in which said third surface is a bottom surface;

a positioning opening provided at said first surface in a position above said ink discharge opening and below said substrate in a state in which said third
10 surface is a bottom surface and closer to said plurality of electrical contacts than to said ink discharge opening; and

an engaging portion in the form of a recess provided at said fourth surface in a position closer to said substrate than to said ink discharge opening and closer to said first surface than to said second surface.

15

56. An ink cartridge according to claim 47 or 55, further comprising an air vent path provided in said casing and configured to introduce ambient air into said ink accommodating chamber, said air vent path having one end portion provided with an air vent and the other end portion connected with said ink
20 accommodating chamber,

a through hole provided at said first side surface; and

a sealing film sealing said air vent in a position in a rear side of the through hole with respect to a direction away from said first side surface toward the second side surface.

25

57. An ink cartridge according to claim 56, wherein said casing is provided with an air vent formation wall provided with said air vent, and wherein

said air vent formation wall is provided between said first side surface and said ink accommodating chamber with respect to a direction away from said first side surface side toward said second side surface.

5 58. An ink cartridge according to Claim 39 or 57, further comprising a hollow path provided in said casing and configured to connect said ink accommodating chamber and said ink discharge opening with each other, a rubber member provided in said hollow path.

10 59. An ink cartridge comprising:
 a casing including an ink accommodating chamber, an ink discharge opening configured to discharge ink from said ink accommodating chamber, a hollow path connecting said ink accommodating chamber and said ink discharge opening, said casing including a first side surface provided with said ink
 15 discharge opening, a second side surface opposite to said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being provided in a position closer to said bottom surface than to said upper surface;

 a substrate provided on said casing;
 20 an electrical contact provided on said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with an extending direction of said hollow path; and

 an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and having a area
 25 crossing with a direction parallel with the extending direction.

60. An ink cartridge comprising:

a casing including an ink accommodating chamber, an ink discharge opening configured to discharge ink from said ink accommodating chamber, a hollow path connecting said ink accommodating chamber and said ink discharge opening with each other, said casing including a first side surface provided with
 5 said ink discharge opening, a second side surface opposite to said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being provided in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

10 an electrical contact provided on said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with an extending direction of said hollow path;

a force receiving portion provided at said first side surface in a position above said ink discharge opening and below said electrical contact and
 15 configured to receive an urging force for urging said casing in a depth direction which is parallel with the extending direction and which is away from said first side surface toward said second side surface; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and including a area
 20 crossing with a direction parallel with the extending direction and capable of receiving a limiting force for limiting movement of said casing in the depth direction and against the urging force.

61. An ink cartridge comprising:

25 a casing including an ink accommodating chamber, an ink discharge opening configured to discharge ink from said ink accommodating chamber, a hollow path connecting said ink accommodating chamber and said ink discharge

opening with each other, said casing including a first side surface provided with said ink discharge opening, a second side surface opposite to said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being provided in a position closer to said

5 bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided at said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with an extending direction of said hollow path;

10 a positioning portion provided on said casing in a position above said ink discharge opening and below said substrate and configured to limit movement of said casing in a direction perpendicular to the extending direction;

a force receiving portion provided at said first side surface in a position above said ink discharge opening and below said positioning opening
15 and configured to receive an urging force for urging said casing in a depth direction which is parallel with the extending direction and which is away from said first side surface toward said second side surface; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and including a area
20 crossing with a direction parallel with the extending direction and capable of receiving a limiting force for limiting movement of said casing in the depth direction against the urging force.

62. An ink cartridge comprising:

25 a casing including an ink accommodating chamber, an ink discharge opening configured to discharge ink from said ink accommodating chamber, a hollow path connecting said ink accommodating chamber and said ink discharge

opening with each other, said casing including a first side surface provided with said ink discharge opening, a second side surface opposite to said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being provided in a position closer to said

5 bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with an extending direction of said hollow path;

10 a positioning portion provided on said casing in a position above said ink discharge opening and below said substrate; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and including a area crossing with a direction parallel with the extending direction.

15

63. An ink cartridge according to claim 61 or 62, wherein said positioning portion includes a positioning opening provided at said first side surface, said positioning opening being provided in a position closer to said electrical contact than to said ink discharge opening.

20

64. An ink cartridge according to Claim 59 or 63, further comprising a rubber member provided in said hollow path.

65. An ink cartridge comprising:

25 a casing including an ink accommodating chamber, a first side surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, a second side surface opposite from said

first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being disposed in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

5 an electrical contact provided on said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with a center line of said ink discharge opening; and

an engaging portion provided in a position closer to said electrical contact than to said ink discharge opening and having an area crossing with a
10 direction parallel with the center line.

66. An ink cartridge comprising:

a casing including an ink accommodating chamber, a first side surface provided with an ink discharge opening configured to discharge ink from said ink
15 accommodating chamber to an outside, a second side surface opposite from said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being disposed in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

20 an electrical contact provided on said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with a center line of said ink discharge opening;

a force receiving portion provided at said first side surface in a position above said ink discharge opening and below said electrical contact and
25 configured to receive an urging force for urging said casing in depth direction which is parallel with the center line and which is away from said first side surface toward second side surface; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and having a area crossing with a direction parallel with the center line and capable of receiving a limiting force for limiting movement of said casing in the depth direction against
 5 the urging force.

67. An ink cartridge comprising:

a casing including an ink accommodating chamber, a first side surface provided with an ink discharge opening configured to discharge ink from said ink
 10 accommodating chamber to an outside, a second side surface opposite from said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being disposed in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

15 an electrical contact provided on said substrate in a position above said ink discharge opening and having an area crossing with a direction parallel with a center line of said ink discharge opening;

a positioning portion provided on said casing in a position above said ink discharge opening and below said electrical contact and configured to limit
 20 movement of said casing in a direction perpendicular to a direction parallel with the center line;

a force receiving portion provided at said first side surface in a position above said ink discharge opening and below said positioning portion and configured to receive an urging force for urging said casing in depth direction
 25 which is parallel with the center line and which is away from said first side surface toward second side surface; and

an engaging portion provided on said casing in a position closer to

said electrical contact than to said ink discharge opening and having a area crossing with a direction parallel with the center line and capable of receiving a limiting force for limiting movement of said casing in the depth direction against the urging force.

5

68. An ink cartridge comprising:

a casing including an ink accommodating chamber, a first side surface provided with an ink discharge opening configured to discharge ink from said ink accommodating chamber to an outside, a second side surface opposite from said
10 first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being disposed in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate in a position above
15 said ink discharge opening and having an area crossing with a direction parallel with a center line of said ink discharge opening;

a positioning portion provided on said casing in a position above said ink discharge opening and below said electrical contact and closer to said first side surface than to said second side surface; and

20 an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening and having a area crossing with a direction parallel with the center line.

69. An ink cartridge according to claim 67 or 68, wherein said positioning
25 portion includes a positioning opening provided at said first side surface, and said positioning opening is disposed in a position closer to said electrical contact than to said ink discharge opening.

70. An ink cartridge according to claim 65 or 69, further comprising a hollow path provided in said casing and connecting said ink accommodating chamber and said ink discharge opening with each other, and a rubber member
5 provided in said hollow path.

71. An ink cartridge according to Claim 59 or 70, wherein said engaging portion is disposed in a position closer to said upper surface than to said bottom surface.
10

72. An ink cartridge according to Claim 59 or 70, wherein said engaging portion is provided with a upper surface.

73. An ink cartridge according to Claim 59 or 72, wherein said engaging
15 portion includes a recess.

74. An ink cartridge according to Claim 59 or 73, wherein said engaging portion is disposed closer to said first side surface than to said second side surface.

20 75. An ink cartridge according to Claim 59 or 74, wherein said substrate is provided at said first side surface.

76. An ink cartridge according to Claim 59 or 74, wherein said substrate is provided on said casing so as to be inclined relative to said first side surface and
25 the upper surface.

77. An ink cartridge according to Claim 59 or 64, wherein said substrate is

supported on said upper surface such that said electrical contact has an area crossing with a direction parallel with the extending direction.

78. An ink cartridge according to Claim 65 or 70, wherein said substrate is
5 supported on said upper surface such that said electrical contact has an area crossing with a direction parallel with the center line.

79. An ink cartridge according to Claim 59 or 78, wherein said substrate is supported directly by said casing or in directly by said casing through a
10 supporting member.

80. An ink cartridge comprising:
a casing including an ink accommodating chamber, a first side surface having a formation region in which an ink discharge opening configured to
15 discharge ink from said ink accommodating chamber to an outside, an upper surface and a bottom surface, said ink discharge opening being disposed in a position close to said bottom surface than to said upper surface;
a substrate provided on said casing;
an electrical contact provided on said substrate and including an area
20 in a position above said ink discharge opening, the area crossing with a direction parallel with a normal line of said formation region; and
an engaging portion provided in a position closer to said electrical contact than to said ink discharge opening, said engaging portion including an area crossing with a direction parallel with the normal line of said formation
25 region.

81. An ink cartridge comprising:

a casing including an ink accommodating chamber, a first side surface having a formation region in which an ink discharge opening configured to discharge ink from said ink accommodating chamber to a outside, a second side surface opposite from said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being

5 disposed in a position close to said bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate and including an area in a position above said ink discharge opening, the area crossing with a direction

10 parallel with a normal line of said formation region;

a force receiving portion provided at said first side surface in a position above said ink discharge opening below said electrical contact capable of receiving an urging force for urging said casing in a depth direction which is in parallel with the normal line of said formation region and away from said first

15 side surface toward said second side surface; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening, said engaging portion including a area crossing with a direction parallel with the normal line of said formation region and capable of receiving a limiting force for limiting movement

20 of said casing in the depth direction against the urging force.

82. An ink cartridge comprising:

a casing including an ink accommodating chamber, a first side surface having a formation region in which an ink discharge opening configured to

25 discharge ink from said ink accommodating chamber to a outside, a second side surface opposite from said first side surface across said ink accommodating chamber, an upper surface and a bottom surface, said ink discharge opening being

disposed in a position close to said bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate and including an area in a position above said ink discharge opening, the area crossing with a direction

5 parallel with a normal line of said formation region;

a positioning portion provided on said casing above said ink discharge opening below said electrical contact and configured to limit movement of said casing in a direction perpendicular to a direction parallel with a normal line of said formation region;

10 a force receiving portion provided at said first side surface in a position above said ink discharge opening below said positioning portion capable of receiving an urging force for urging said casing in a depth direction which is in parallel with the normal line of said formation region and away from said first side surface toward said second side surface; and

15 an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening, said engaging portion including a area crossing with a direction parallel with the normal line of said formation region and capable of receiving a limiting force for limiting movement of said casing in the depth direction against the urging force.

20

83. An ink cartridge comprising:

a casing including an ink accommodating chamber, a first side surface having a formation region in which an ink discharge opening configured to discharge ink from said ink accommodating chamber to a outside, an upper

25 surface and a bottom surface, said ink discharge opening being disposed in a position closer to said bottom surface than to said upper surface;

a substrate provided on said casing;

an electrical contact provided on said substrate and including an area in a position above said ink discharge opening, the area crossing with a direction parallel with a normal line of said formation region;

a positioning portion provided on said casing above said ink discharge opening below said electrical contact; and

an engaging portion provided on said casing in a position closer to said electrical contact than to said ink discharge opening, said engaging portion including a area crossing with a direction parallel with the normal line of said formation region.

10

84. An ink cartridge according to Claim 82 or 83, wherein said positioning portion includes a positioning opening provided at said first side surface, and said positioning opening is disposed in a position closer to said electrical contact than to said ink discharge opening.

15

85. An ink cartridge according to Claim 80 or 84, further comprising a hollow path provided on said casing and connecting said ink accommodating chamber and said ink discharge opening with each other, and a rubber member provided in said hollow path.

20

86. An ink cartridge according to Claim 80 or 85, wherein said engaging portion is disposed in a position closer to said upper surface than to said bottom surface.

25 87. An ink cartridge according to Claim 80 or 85, wherein said engaging portion is provided at said upper surface.

88. An ink cartridge according to Claim 80 or 87, wherein said engaging portion includes a recess.

89. An ink cartridge according to Claim 80 or 88, wherein said substrate is
5 provided at said first side surface.

90. An ink cartridge according to Claim 80 or 88, wherein said substrate is provided on said casing so as to be inclined relative to said first side surface and the upper surface.

10

91. An apparatus according to Claim 80 or 88, wherein said substrate is supported on said upper surface such that said electrical contact has an area crossing with a direction parallel with the extending direction.

15 92. An apparatus according to Claim 80 or 91, wherein said substrate is supported directly by said casing or indirectly by said casing through a supporting member.

93. An ink jet printer comprising a cartridge mounting portion including
20 an ink receiving tube, an electrical connecting portion and a locking lever, and an ink cartridge mountable to said cartridge mounting portion in a mounting direction crossing with a direction of gravity, said ink cartridge including,

(A) a casing including an ink accommodating chamber configured to accommodate ink to be supplied to the ink receiving tube, said casing including a
25 front surface at a leading side with respect to the mounting direction, an upper surface and a bottom surface, (B) a tube inserting portion into which the ink receiving tube is inserted and which is provided at said front surface in a position

closer to said bottom surface than to said upper surface, (C) an electrical contact electrically connectable to the electrical connecting portion and having a area crossing with the mounting direction in a position above said tube inserting portion, and (D) an engaging portion provided in a position closer to said
5 electrical contact than to said tube inserting portion, said engaging portion being engageable with the locking lever to maintain a inserted state in which the ink receiving tube is inserted in said tube inserting portion and a connected state in which said electrical contact is connected with the electrical connecting portion.

10 94. An ink jet printer according to Claim 93, wherein said cartridge mounting portion further includes an urging spring, and said ink cartridge further includes a force receiving portion capable of receiving, from an urging spring provided in the cartridge mounting portion, the urging force for urging said ink cartridge in a dismounting direction which is opposite to the mounting direction,
15 said force receiving portion being provided in a position above said tube inserting portion and below said electrical contact, wherein said engaging portion is engageable with said locking lever to maintain the inserted state and the connected state against the urging force.

20 95. An ink jet printer according to Claim 93, wherein said cartridge mounting portion further includes a positioning member and an urging spring, and (A) a positioning portion engageable with a positioning member provided in the cartridge mounting portion to limit movement of said casing in a direction perpendicular to the mounting direction, said positioning portion being provided
25 in a position above said tube inserting portion and below said electrical contact, and (B) a force receiving portion capable of receiving, from an urging spring, a urging force for urging said ink cartridge in a dismounting direction which is

opposite to the mounting direction, said force receiving portion being provided in a position above said tube inserting portion and below said electrical contact, wherein said engaging portion is engageable with said locking lever to maintain the inserted state, the connected state and a engaged state between said
5 positioning portion and the positioning member against the urging force.

96. An ink jet printer according to Claim 93, wherein said cartridge mounting portion further comprising positioning member, and wherein said ink cartridge further includes a positioning portion provided in a position above said
10 tube inserting portion and below said electrical contact and engageable with a positioning member provided in the cartridge mounting portion to limit movement of said casing in a direction perpendicular to the mounting direction, wherein said engaging portion is engageable with the locking lever to maintain an engaged state between said positioning portion and the positioning member.