

METHOD AND APPARATUS FOR GENERATING AND UPDATING TILES MAPS IN VIRTUAL MAPS

TECHNICAL FIELD

[0001] The present application relates to the field of image processing, and in
5 particular, to a method and an apparatus for generating and updating tiles maps in
virtual maps.

BACKGROUND

[0002] Due to a large data amount in a map, the map needs to be partially loaded
through slicing, namely, a tile map technology, to ensure a map loading speed in a
10 client and reduce server load.

[0003] When an actual map such as Baidu Map or Auto Navi Map is used to
generate a virtual map in a virtual application, because the actual map has a large size,
the virtual map generated based on the actual map is also very large, and if all tile
maps in the virtual map are loaded at a time, great pressure is brought to performance
15 and memory of the virtual application, resulting in poor display efficiency of the
virtual map.

[0004] How to improve display efficiency of the virtual map is a technical
problem that needs to be dealt with in implementations of the present application.

SUMMARY

20 [0005] To alleviate the previous technical problem, the implementations of the
present application are implemented as follows:

[0006] According to a first aspect, a method for updating tile maps in virtual maps
is provided. The method includes the following: determining, in a first area, a central
area that a virtual object is located in, where the first area is an area map that includes
25 tile maps loaded into a virtual map that the virtual object is located in, a border of the
central area is located in the first area, a maximum distance between any tile map in

the central area and the virtual object in an x-axis direction in a tile map coordinate system of the virtual map is less than X_1 , a maximum distance between any tile map in the central area and the virtual object in a y-axis direction in the tile map coordinate system is less than Y_1 , a length of one tile map is used as a unit on the x-axis in the tile map coordinate system, a width of one tile map is used as a unit on the y-axis in the tile map coordinate system, and X_1 and Y_1 are predetermined positive integers; and determining a distance parameter after the virtual object moves out of the central area, and updating a loading status of a tile map not shared by the first area and a second area based on the distance parameter and the first area, where the distance parameter indicates relative distances of a tile map that the virtual object is located in relative to the central area in the x-axis direction and the y-axis direction in the tile map coordinate system, and the second area is a map area determined after moving the first area based on the distance parameter.

[0007] According to a second aspect, a method for generating tile maps in virtual maps is provided. The method includes the following: determining a map area of a virtual map based on a scaling relationship between an actual electronic map and the virtual map; dividing the map area into a plurality of equally sized tile areas; and performing image processing on each tile area based on an area map that corresponds to the tile area in the actual electronic map, to generate a tile map of the tile area, where the image processing includes rendering processing.

[0008] According to a third aspect, an apparatus for drawing a virtual map is provided, including a determining unit and an updating unit. The determining unit determines, in a first area, a central area that a virtual object is located in, where the first area is an area map that includes tile maps loaded into a virtual map that the virtual object is located in, a border of the central area is located in the first area, a maximum distance between any tile map in the central area and the virtual object in an x-axis direction in a tile map coordinate system of the virtual map is less than X_1 , a maximum distance between any tile map in the central area and the virtual object in a y-axis direction in the tile map coordinate system is less than Y_1 , a length of one tile map is used as a unit on the x-axis in the tile map coordinate system, a width of one tile map is used as a unit on the y-axis in the tile map coordinate system, and X_1 and Y_1 are predetermined positive integers. The determining unit further determines a distance parameter after the virtual object moves out of the central area, where the distance parameter indicates relative distances of a tile map that the virtual object is

located in relative to the central area in the x-axis direction and the y-axis direction in the tile map coordinate system. The updating unit updates a loading status of a tile map not shared by the first area and a second area based on the distance parameter and the first area, where the second area is a map area determined after moving the first area based on the distance parameter.

[0009] According to a fourth aspect, an apparatus for drawing a virtual map is provided, including: a determining unit, configured to determine a map area of a virtual map based on a scaling relationship between an actual electronic map and the virtual map; an area division unit, configured to divide the map area into a plurality of equally sized tile areas; and an image processing unit, configured to perform image processing on each tile area based on an area map that corresponds to the tile area in the actual electronic map, to generate a tile map of the tile area, where the image processing includes rendering processing.

[0010] It can be seen from the technical solutions provided in the implementations of the present application that, in the implementations of the present application, after the virtual object moves out of the central area that the virtual object is located in, a tile map whose loading status needs to be updated is determined based on a distance parameter of a tile map that the virtual object moves to relative to the central area and a currently loaded tile map. Therefore, loading redundant tile maps can be alleviated to implement seamless connection between the tile maps, and efficiency of displaying the virtual map and an experience effect are improved to an extent.

BRIEF DESCRIPTION OF DRAWINGS

[0011] To describe the technical solutions in the implementations of the present application or in the existing technology more clearly, the following briefly describes the accompanying drawings required for describing the implementations or the existing technology. Apparently, the accompanying drawings in the following description show merely some implementations of the present application, and a person of ordinary skill in the art can still derive other drawings from these accompanying drawings without creative efforts.

[0012] FIG. 1 is a flowchart illustrating a method for generating tile maps in virtual maps, according to an implementation of the present application;

[0013] FIG. 2 is a schematic diagram illustrating area division and coordinates of

tile maps, according to an implementation of the present application;

[0014] FIG. 3 is a schematic diagram illustrating a method for generating tile maps in virtual maps, according to an implementation of the present application;

[0015] FIG. 4 is a schematic diagram illustrating a method for updating tile maps
5 in virtual maps, according to an implementation of the present application;

[0016] FIG. 5 is a schematic diagram illustrating tile maps in a virtual map in a tile map coordinate system, according to an implementation of the present application;

[0017] FIG. 6 is a schematic diagram illustrating coordinates of some tile maps in a virtual map, according to an implementation of the present application;

10 [0018] FIG. 7 is a schematic diagram illustrating a mapping relationship between coordinates in a virtual map and latitude and longitude in an actual electronic map, according to an implementation of the present application;

[0019] FIG. 8 is a schematic structural diagram illustrating an electronic device, according to an example implementation of the present application;

15 [0020] FIG. 9 is a schematic structural diagram illustrating an apparatus for drawing a virtual map, according to an implementation of the present application; and

[0021] FIG. 10 is a schematic structural diagram illustrating an apparatus for drawing a virtual map, according to another implementation of the present application.

20 DESCRIPTION OF IMPLEMENTATIONS

[0022] To make a person skilled in the art understand the technical solutions in the present application better, the following clearly and comprehensively describes the technical solutions in the implementations of the present application with reference to the accompanying drawings in the implementations of the present application.

25 Apparently, the described implementations are merely some rather than all of the implementations of the present application. All other implementations obtained by a person of ordinary skill in the art based on the implementations of the present application without creative efforts shall fall within the protection scope of the present application.

30 [0023] FIG. 1 is a flowchart illustrating a method for generating tile maps in virtual maps, according to an implementation of the present application. The method in FIG. 1 is performed by an apparatus for generating tile maps in virtual maps. In

specific applications, the apparatus for generating tile maps in virtual maps can be a graphics engine of a virtual map, for example, a 2D graphics engine, a 3D graphics engine, or another virtual map drawing tool. Implementations are not limited in the present application. Specifically, the virtual map can be a 2D map or a 3D map. The method in FIG. 1 can include the following steps.

[0024] S110. Determine a map area of a virtual map based on a scaling relationship between an actual electronic map and the virtual map.

[0025] It should be understood that the actual electronic map in the implementation of the present application is an electronic map such as Baidu Map or Auto Navi Map drawn based on an actual environment.

[0026] It should be understood that the virtual map in the implementation of the present application is a map such as a virtual map in a virtual application.

[0027] It should be understood that, in the implementation of the present application, a size of the virtual map can be determined based on a scaling relationship between the actual electronic map and the virtual map.

[0028] For example, it is predetermined that the relationship between the actual electronic map and the virtual map is 2:1. In this case, a length and a width of the actual electronic map can be separately shortened by half to determine the size of the virtual map.

[0029] S120. Divide the map area into a plurality of equally sized tile areas.

[0030] Specifically, the map area can be divided into the plurality of equally sized tile areas.

[0031] Preferably, the tile areas can be rectangular, for example, 10 cm × 10 cm, 5 cm × 5 cm, and 4 cm × 2 cm. It should be understood that a length and a width of a tile area are not necessarily equal. Certainly, preferably, the length and the width of the tile area are equal to each other.

[0032] Certainly, it should be understood that the tile area can alternatively be in another shape, for example, the tile area can be a rhombus or a regular hexagon. In this case, an edge of the virtual map may not be an even straight line.

[0033] S130. Perform operations including image processing on each tile area based on an area map that corresponds to the tile area in the actual electronic map, to generate a tile map of the tile area.

[0034] The image processing operation includes rendering processing.

[0035] For example, assume that the actual electronic map is an electronic map generated based on a campus of a university. In this case, rendering processing is performed on each tile area in a virtual map based on an area map that corresponds to the tile area in the electronic map that corresponds to the university, and a tile map of the tile area can be generated.

[0036] Certainly, it should be understood that other image processing operations than the rendering processing can be performed on the virtual map based on the electronic map. Implementations are not limited in the present application.

[0037] In the implementation of the present application, the area of the virtual map is determined based on the actual electronic map, the virtual map is divided into a plurality of equally sized tile areas, and rendering processing is performed on the tile areas based on corresponding area maps of the tile areas in the actual electronic map, so that a tile map of the virtual map can be generated fast based on the actual electronic map, thereby improving efficiency of generating the virtual map.

[0038] Optionally, in the implementation of the present application, step S130 is specifically implemented as follows: determining a first actual area map that corresponds to a first tile area in the plurality of equally sized tile areas in the actual electronic map based on a size of the tile area and an index of the first tile area, and performing image processing on the first tile area based on the first actual area map to obtain a first tile map that corresponds to the first tile area.

[0039] An index of each tile area is related to a position of the tile area. Specifically, for example, the index of the tile area can be point coordinates of a specified position in the tile area. For example, when the tile area is rectangular, the coordinates can be center coordinates of the tile area, lower left vertex coordinates of the tile area, upper left vertex coordinates of the tile area, upper right vertex coordinates of the tile area, lower right vertex coordinates of the tile area, etc. The index can alternatively be a number of the tile area, etc.

[0040] Certainly, it should be understood that, before step S130, the method further includes the following: creating an index of a tile area based on a position of the tile area.

[0041] The method in the implementation of the present application is further described with reference to FIG. 2 and FIG. 3.

[0042] In the implementation of the present application, when a virtual map needs to be generated based on an actual electronic map, an area size of the virtual map can

be determined based on a scaling relationship between the actual electronic map and the virtual map. Especially, when the virtual map is a 3D virtual map, because a size of the 3D virtual map is generally unchanged, a scaling ratio of the 3D virtual map to the actual electronic map is generally a constant value.

5 **[0043]** After a virtual map area is determined based on the actual electronic map and the scaling relationship, the virtual map can be divided into a plurality of equally sized rectangular areas. Each rectangular area has a size of one tile map, and one rectangular area can be referred to as one tile area. FIG. 2 is a schematic diagram illustrating area division and coordinates of tile maps, according to an implementation
10 of the present application. Assume that an entire area shown in FIG. 2 is an entire virtual map area determined based on the actual electronic map. As shown in FIG. 2, the virtual map can be divided into a plurality of equally sized tile areas. In addition, an index can be created for each tile area based on a position of the tile area. For example, coordinates or a sequence number can be used to represent the index of the
15 tile area. In the implementation shown in FIG. 2, a length of one tile area is used as a unit of measurement for horizontal coordinates, and a width of one tile area is used as a unit of measurement for vertical coordinates.

[0044] After tile area division is completed and the index is created, image processing including the rendering processing can be performed based on the actual
20 electronic map to obtain the tile map. FIG. 3 is a schematic diagram illustrating a method for generating tile maps in virtual maps, according to an implementation of the present application. As shown in FIG. 3, layer initialization first needs to be performed on the tile area. Specifically, the virtual map area that corresponds to the actual electronic map can be determined based on a scaling level, and then the virtual
25 map area is divided into tile areas. In addition, when layer initialization is performed on the tile area, usually layer styles in the tile area can be initialized, for example, what color a road is, and whether a building is displayed. For ease of identifying and locating a tile area, the tile area can be further indexed.

[0045] After layer initialization on the tile area is completed, an actual area that
30 corresponds to the tile area in the actual electronic map can be calculated based on an index and a size of the tile area. As shown in FIG. 2, the tile areas are adjacently arranged on a two-dimensional plane, and all the tile areas have the same size. Two-dimensional coordinates of each tile area can be determined based on an index of the tile area (or the index of the tile area is the two-dimensional coordinates). Then,

latitude and longitude of a rectangular area covered by each tile area can be determined based on the size of the tile area. In other words, the actual area that corresponds to the tile area in the actual electronic map can be determined.

[0046] After the actual area that corresponds to the tile area in the actual electronic map is obtained, layers in the tile area can be processed based on an actual area map. For example, a third-party map API (such as Google Map) can be called to render map pictures in the tile area based on the actual area map. Finally, the pictures are stored, and a tile map is obtained. The index of the tile area can be used as an index of the tile map.

[0047] Certainly, it should be understood that the tile area can alternatively be in another shape, for example, the tile area can be a rhombus or a regular hexagon. When the shape changes, an algorithm for calculating an actual map area based on the index and the size of the tile area changes accordingly.

[0048] FIG. 4 is a flowchart illustrating a method for updating tile maps in virtual maps, according to an implementation of the present application. The method in FIG. 4 is performed by a virtual map drawing apparatus. In specific applications, the virtual map drawing apparatus can be a graphics engine, for example, a 2D graphics engine, a 3D graphics engine, or another virtual map drawing tool. Implementations are not limited in the present application. It should be understood that the virtual map in the implementation of the present application can be a virtual map such as a 3D virtual map or a 2D virtual map, or another map in a virtual application, etc. The method in FIG. 4 can include the following steps.

[0049] S410. Determine, in a first area, a central area that a virtual object is located in.

[0050] The first area is an area map that includes tile maps loaded into a virtual map that the virtual object is located in. A border of the central area is located in the first area. A maximum distance between any tile map in the central area and the virtual object in an x-axis direction in a tile map coordinate system of the virtual map is less than X_1 . A maximum distance between any tile map in the central area and the virtual object in a y-axis direction in the tile map coordinate system is less than Y_1 . A length of one tile map is used as a unit on the x-axis in the tile map coordinate system, a width of one tile map is used as a unit on the y-axis in the tile map coordinate system, and X_1 and Y_1 are predetermined positive integers.

[0051] It should be understood that a specific form of the virtual object is not

limited in the implementation of the present application. A 3D game is used as an example for description. For example, the virtual object can be a character or a vehicle driven by a character in the 3D game.

[0052] It should be understood that all tile maps have the same size in the implementation of the present application.

[0053] It should be understood that, in the implementation of the present application, the loaded first area should cover a visual field of the virtual object. In other words, all tile maps in the visual field of the virtual object should be loaded. In the implementation of the present application, the first area at least includes the tile maps in the visual field of the virtual object. Certainly, it should be understood that the first area can also be greater than the visual field of the virtual object.

[0054] It should be understood that, in the implementation of the present application, a length of one tile map is used as a unit on the x-axis in the tile map coordinate system, and a width of one tile map is used as a unit on the y-axis in the tile map coordinate system. FIG. 5 is a schematic diagram illustrating tile maps in a virtual map in a tile map coordinate system, according to an implementation of the present application. As shown in FIG. 5, each rectangular area is a tile map. A length of the tile map is used as a unit on the x-axis (x-axis) in the tile map coordinate system, and a width of the tile map is used as a unit on the y-axis (y-axis) in the tile map coordinate system.

[0055] In addition, position coordinates can alternatively be used as an index of the tile map. For example, in the tile map coordinate system shown in FIG. 5, lower left vertex coordinates of the tile map are used as the index of the tile map.

[0056] S420. Determine a distance parameter after the virtual object moves out of the central area, and update a loading status of a tile map not shared by the first area and a second area based on the distance parameter and the first area.

[0057] The distance parameter indicates relative distances of a tile map that the virtual object is located in relative to the central area in the x-axis direction and the y-axis direction in the tile map coordinate system, and the second area is a map area determined after moving the first area based on the distance parameter.

[0058] It should be understood that the second area is the map area determined after moving the first area based on the distance parameter. Therefore, the first area and the second area have the same shape and the same size. For example, in FIG. 2, assume that the first area is a rectangular area that includes (2, 0) and (1, 1), and the

distance parameter indicates that the first area moves to the right by one tile map. In this case, the second area is a rectangular area that includes (2, 1) and (1, 2), and has the same shape and size as those of the first area.

[0059] It should be understood that a tile map not shared by the first area and the second area is a tile map that exists in either only the first area or only the second area.

[0060] In the implementation of the present application, after the virtual object moves out of the central area that the virtual object is located in, the virtual object moves in to a tile map, and a distance parameter of the tile map that is relative to the central area is determined. Then, a tile map whose loading status needs to be updated is determined based on the distance parameter of the tile map and a currently loaded tile map. Therefore, loading redundant tile maps can be alleviated to implement seamless connection between the tile maps, and efficiency of displaying the virtual map and an experience effect are improved to an extent.

[0061] Optionally, in an implementation, the determining a distance parameter in step S420 can be specifically implemented in the following method: determining that the distance parameter is (1, 0) when the virtual object moves to a tile map that is on the right of the central area and adjacent to the central area; or determining that the distance parameter is (1, 1) when the virtual object moves to a tile map that is at the upper right of the central area and adjacent to the central area; or determining that the distance parameter is (0, 1) when the virtual object moves to a tile map that is right above the central area and adjacent to the central area; or determining that the distance parameter is (-1, 1) when the virtual object moves to a tile map that is at the upper left of the central area and adjacent to the central area; or determining that the distance parameter is (-1, 0) when the virtual object moves to a tile map that is on the left of the central area and adjacent to the central area; or determining that the distance parameter is (-1, -1) when the virtual object moves to a tile map that is at the lower left of the central area and adjacent to the central area; or determining that the distance parameter is (0, -1) when the virtual object moves to a tile map that is right below the central area and adjacent to the central area; or determining that the distance parameter is (1, -1) when the virtual object moves to a tile map that is at the lower right of the central area and adjacent to the central area, where in the tile map coordinate system, a right direction is a positive direction for horizontal coordinates,

and an upward direction is a positive direction for vertical coordinates.

[0062] It should be understood that, in the implementation of the present application, the distance parameter (a, b) indicates that the central area moves to the right by a tile maps and upward by b tile maps, and a and b are integers. When a value
5 of a or b is a negative number, it indicates that the central area moves in an opposite direction; or when the value of a or b is 0, it indicates that the central area does not move.

[0063] Optionally, in another implementation, the determining a distance parameter in step S420 can be specifically implemented in the following method:
10 determining a second central area, where after the virtual object moves out of the central area, a maximum distance, in the x-axis direction in the tile map coordinate system of the virtual map, between any tile map in the second central area and the tile map that the virtual object is located in is less than X_1 , and a maximum distance, in the y-axis direction in the tile map coordinate system of the virtual map, between the
15 tile map in the second central area and the tile map that the virtual object is located in is less than Y_1 ; and determining that a relative distance of the second central area relative to the central area in the x-axis direction and the y-axis direction in the tile map coordinate system is the distance parameter.

[0064] Optionally, in an implementation, step 420 is specifically implemented as
20 follows: determining the distance parameter after the virtual object moves out of the central area for a time duration that exceeds a preset time, and updating the loading status of the tile map not shared by the first area and the second area based on the distance parameter and the first area.

[0065] In the implementation of the present application, the tile map is updated
25 after the virtual object moves out of the central area for a predetermined time, so that frequently updating the tile map is alleviated when the virtual object moves between critical areas in a short time.

[0066] Optionally, in an implementation, in step 420, the updating a loading status of a tile map not shared by the first area and a second area is specifically implemented
30 as follows: loading added tile maps in the second area relative to tile maps in the first area, and removing reduced tile maps in the second area relative to tile maps in the first area.

[0067] In the implementation of the present application, a tile map that does not need to be displayed is removed, and a tile map that needs to be displayed is loaded,

so that efficiency of loading the tile map can be increased, seamless connection between the tile maps is implemented, and efficiency of displaying the virtual map and an experience effect are improved to an extent.

[0068] Optionally, in an implementation, in step 420, the updating a loading status of a tile map not shared by the first area and a second area based on the distance parameter and the first area is specifically implemented as follows: determining an index of a tile map that needs to be updated based on the distance parameter and indexes of tile maps in the first area; and updating a loading status of a tile map of the virtual object in the virtual map based on the index of the tile map that needs to be updated.

[0069] Preferably, X_1 is equal to Y_1 . Further, a value of X_1 can be 1, 2, 3, 4, 5, etc.

[0070] Optionally, a maximum distance, in the x-axis direction, between any tile map in the first area and the tile map that the virtual object is located in is less than X_2 times a first unit length, and a maximum distance, in the y-axis direction, between the tile map in the first area and the tile map that the virtual object is located in is less than Y_2 times a second unit length, where X_2 and Y_2 are positive integers, and $X_1 < X_2$ and $Y_1 < Y_2$. Preferably, the first area and the central area are rectangular. Further, $Y_2 = Y_1 + 1$, and $X_2 = X_1 + 1$. In this case, a new rectangular area is generated by separately extending the periphery of the central area upward and downward and to the left and the right by one tile map, and the new rectangular area is the first area.

[0071] For example, when values of X_1 and Y_1 are 1, values of X_2 and Y_2 are 2. In this case, tile maps loaded for the virtual object are a nine-rectangular-grid map, and the virtual object is always located in the center of the nine-rectangular-grid map.

[0072] For another example, when values of X_1 and Y_1 are 2, values of X_2 and Y_2 are 3. In this case, tile maps loaded for the virtual object are a sixteen-rectangular-grid map, and the virtual object is always located on four tile maps in the center of the sixteen-rectangular-grid map.

[0073] For another example, when values of X_1 and Y_1 are 3, values of X_2 and Y_2 are 4. In this case, tile maps loaded for the virtual object are a twenty-five-rectangular-grid map, and the virtual object is always located on nine tile maps in the center of the twenty-five-rectangular-grid map.

[0074] Optionally, in an implementation, before step S420, the method further includes the following: determining corresponding map coordinates of the virtual

object in the virtual map based on latitude and longitude of an actual object that corresponds to the virtual object in an actual environment, where the virtual map is generated based on an actual electronic map.

[0075] For example, assume that a global electronic map is used as a virtual map
5 in a game. In this case, when logging in to the game on Tian'anmen Square in Beijing, a user is located at 39°54'27" N, 116°23'17" E. In this case, the user is located in the game at a position in the virtual map that corresponds to the position (39°54'27" N, 116°23'17" E) in the actual electronic map.

[0076] After corresponding map coordinates of the virtual object in the virtual
10 map is determined based on latitude and longitude of an actual object that corresponds to the virtual object in an actual environment, an initial position of the virtual object in a virtual application can be determined, and whether the virtual object moves out of a current central area can be further determined.

[0077] Optionally, in an implementation, before step S420, the method further
15 includes the following: determining a corresponding moving direction and moving distance of the virtual object in the virtual map based on a moving direction and a moving distance of an actual object that corresponds to the virtual object in an actual environment, where the virtual map is generated based on an actual electronic map.

[0078] For example, still assume that a global electronic map is used as a virtual
20 map in a game, currently, a user is on Tian'anmen Square 39°54'27" N, 116°23'17" E in Beijing, and a corresponding coordinate position in the virtual map is (x_0, y_0) . Assume that the user moves to the west by 50 kilometers, a distance that corresponds to one kilometer in the virtual map is 1 cm, and directions of the virtual map are as follows: upper north, lower south, left west, and right east. In this case, the user can
25 determine that a position of the virtual object is a position obtained after the coordinates (x_0, y_0) move to the left by 50 cm in the virtual map.

[0079] A moved position can be determined based on a current position, a moving distance, and a moving direction of the virtual object in the virtual map so as to determine whether the virtual object moves out of the current central area.

30 [0080] The following further describes the method in the implementations of the present application with reference to a specific implementation.

[0081] FIG. 6 is a schematic diagram illustrating coordinates of some tile maps in a virtual map, according to an implementation of the present application. In FIG. 6, tile maps loaded by a player character are a nine-rectangular-grid map in a gray part.

In the implementation shown in FIG. 6, two-dimensional coordinates of a tile map in a virtual map is used as an index of the tile map. The two-dimensional coordinates of the tile map in the virtual map can be center coordinates of the tile map, coordinates of a vertex of the tile map, coordinates of a fixed position in the tile map, etc.

5 **[0082]** In a scenario shown in FIG. 6, when values of X_1 and Y_1 in the implementation shown in FIG. 4 are 1, values of X_2 and Y_2 are 2. In this case, a first area of a virtual object includes tile maps (1, 1), (1, 2), (1, 3), (2, 1), (2, 2), (2, 3), (3, 1), (3, 2), and (3, 3), and a central area of the virtual object includes a tile map (2, 2). It should be understood that, when the virtual object moves in the central area, no tile
10 map needs to be updated, and when the virtual object moves out of the central area, a tile map needs to be updated.

[0083] As an arrow A in FIG. 6 shows, it can be determined that a distance parameter is (0, 1) when the virtual object moves to a tile map (2, 3) from the central area, that is, the tile map (2, 2). In this case, coordinates of tile maps that need to be
15 loaded for the virtual object are (1, 2), (1, 3), (1, 4), (2, 2), (2, 3), (2, 4), (3, 2), (3, 3), and (3, 4). In other words, loading statuses of tile maps that are not shared by the tile maps (1, 1), (1, 2), (1, 3), (2, 1), (2, 2), (2, 3), (3, 1), (3, 2), and (3, 3) and the tile maps (1, 2), (1, 3), (1, 4), (2, 2), (2, 3), (2, 4), (3, 2), (3, 3), and (3, 4) need to be updated. In other words, coordinate indexes of tile maps whose loading statuses need to be
20 updated are (1, 1), (2, 1), (3, 1), (1, 4), (2, 4), and (3, 4). The tile maps (1, 1), (2, 1), and (3, 1) need to be removed, and the tile maps (1, 4), (2, 4), and (3, 4) need to be loaded.

[0084] As an arrow B in FIG. 6 shows, when the virtual object moves to a tile map (3, 1) from the tile map (2, 2), it can be determined that the distance parameter is
25 (1, -1). In this case, coordinates of tile maps that need to be loaded for the virtual object are (2, 0), (2, 1), (2, 2), (3, 0), (3, 1), (3, 2), (4, 0), (4, 1), and (4, 2). In other words, loading statuses of tile maps that are not shared by the tile maps (2, 0), (2, 1), (2, 2), (3, 0), (3, 1), (3, 2), (4, 0), (4, 1), and (4, 2) and the tile maps (1, 1), (1, 2), (1, 3), (2, 1), (2, 2), (2, 3), (3, 1), (3, 2), and (3, 3) need to be updated. In other words,
30 loading statuses of tile maps (2, 0), (3, 0), (4, 0), (4, 1), (4, 2), (1, 1), (1, 2), (1, 3), (2, 3), and (3, 3) need to be updated. To be specific, the tile maps (1, 1), (1, 2), (1, 3), (2, 3), and (3, 3) need to be removed, and the tile maps (2, 0), (3, 0), (4, 0), (4, 1), and (4, 2) need to be loaded.

[0085] Certainly, it should be understood that the virtual object can alternatively move to other six directions in the nine-rectangular-grid map from the tile map (2, 2). A movement distance parameter of the virtual object is shown by the distance parameter in the implementation shown in FIG. 4. Details are omitted in the implementation of the present application for simplicity.

[0086] In addition, it should be understood that a predetermined time can be further set to alleviate frequent map refreshing because of frequent switching. A tile map is updated after the virtual object moves out of the central area for the predetermined time. In this way, frequent refreshing because of frequent map switching can be alleviated to improve user experience.

[0087] Certainly, it should be understood that other indexes can alternatively be used as indexes of tile maps in actual applications. For example, a numerical index is determined based on coordinates. Specifically, for example, if coordinates of a tile map is (x_0, y_0) , a numerical index of the tile map is $a \cdot x_0 + b \cdot y_0$.

[0088] In addition, it should be understood that the central area of the virtual object can include more than one tile map. For example, when values of X_1 and Y_1 are 2, values of X_2 and Y_2 are 3. The central area includes four tile maps, and tile maps that need to be loaded constitute a sixteen-rectangular-grid map. Similar to a nine-rectangular-grid map, in the sixteen-rectangular-grid map, areas other than the central area can also be divided into eight areas that respectively correspond to eight directions: right, upper right, right above, upper left, left, lower left, right below, and lower right. A method for calculating a movement distance parameter in the sixteen-rectangular-grid map is similar to that in the nine-rectangular-grid map.

[0089] In addition, a quantity of tile maps included in the central area in the y-axis direction can be unequal to a quantity of tile maps included in the central area in the x-axis direction. For example, a value of X_1 is 1, a value of Y_1 is 2, and values of X_2 and Y_2 are 3.

[0090] In addition, a shape of the first area including the tile maps loaded for the virtual object is also not limited in the implementation of the present application, as long as the first area includes the central area of the virtual object and the central area is not on an edge of the first area. Preferably, the first area and the central area are rectangular.

[0091] For example, in the tile maps shown in FIG. 6, the first area can include

the nine-rectangular-grid map in the gray part and an area including tile maps (4, 0), (4, 1), (4, 2), (4, 3), and (4, 4).

[0092] To determine an area that needs to be updated, it only needs to compare the first area with a second area obtained after moving the first area based on the distance parameter, and update a loading status of a tile map in an area not shared by the first area and the second area.

[0093] In a preferable solution, the first area is an area obtained by extending the central area by one tile map in all directions.

[0094] In addition, it should be understood that, in the method in the implementation of the present application, an association relationship can be further established between position information of a user in an actual environment and position information of the virtual object in the virtual map.

[0095] In a specific example, a virtual map can be generated based on an actual electronic map, and then corresponding map coordinates of the virtual object in the virtual map are determined based on latitude and longitude of an actual object that corresponds to the virtual object in an actual environment. It should be understood that the virtual map generated based on the actual electronic map corresponds to the latitude and longitude in the actual environment.

[0096] For example, assume that the virtual map is a 3D game map, the virtual object is a game character in a 3D game, and a map origin corresponds to latitude and longitude in the actual electronic map, that is, (0, 0) corresponds to latitude and longitude (O-lat, O-lng). Assume that a length and a width of a tile map in a 3D graphics engine are respectively w and h, and latitude and longitude actually covered by the tile map are respectively d-lat and d-lng, as shown in FIG. 7. FIG. 7 is a schematic diagram illustrating a mapping relationship between coordinates in a virtual map and latitude and longitude in an actual electronic map, according to an implementation of the present application.

[0097] If current latitude and longitude of the user in the actual environment is (x, y), a coordinate index of a tile map that a game character corresponding to the user is located in is as follows:

$$\left(\left[\frac{x - O_{lat}}{d_{lat}} \right], \left[\frac{y - O_{lng}}{d_{lng}} \right] \right)$$

[0098] Further, it can be obtained that coordinates (the z-axis is ignored) of the game character in the 3D graphics engine are as follows:

$$\left(\frac{x - O_{lat}}{d_{lat}} w, \frac{y - O_{lng}}{d_{lng}} h \right)$$

[0099] Correspondingly, the latitude and longitude of the user in the actual environment can also be calculated based on the coordinates of the game character in the 3D graphics engine.

[0100] In addition, it should be understood that, in the method in the implementation of the present application, an action of the user in the actual environment can be further associated with an action of the virtual object.

[0101] In a specific example, based on an action parameter of the actual object that corresponds to the virtual object in the actual environment, a corresponding action parameter of the virtual object in the virtual map can be determined, and the virtual object can be operated. Specifically, the action parameter can be a parameter related to movement of a part such as a hand, a foot, the head, or the body of the user. For example, an arm swing distance, an arm swing speed, a leg lifting angle, a leg lifting direction, and a leg lifting speed of the user in the actual environment can be captured by using a sensor. Certainly, the sensor can also be used to collect relatively simpler data, such as a moving distance, a moving direction, and a moving speed of the user.

[0102] Certainly, it should be understood that the method for determining the coordinates in the virtual map based on the latitude and longitude and the method for determining the action parameter of the virtual object in the virtual map based on the action parameter in the actual environment can be applied to the same implementation. The virtual object and the user maintain good consistency based on latitude and longitude data and action parameter data of the user, making virtual experience of the user more real.

[0103] FIG. 8 is a schematic structural diagram illustrating an electronic device, according to an example implementation of the present application. Referring to FIG. 8, in terms of hardware, the electronic device includes a processor, an internal bus, a network interface, a memory, and a nonvolatile memory, and certainly can further include hardware needed by other services. The processor reads a corresponding

computer program from the nonvolatile memory to the memory for running, and a user interface unlocking apparatus is logically formed. Certainly, in addition to a software implementation, the present application does not exclude another implementation, for example, a logic device or a combination of hardware and software. That is, an execution body of the following processing procedure is not limited to each logical unit, and can also be hardware or a logic device.

[0104] FIG. 9 is a schematic structural diagram illustrating an apparatus 900 for drawing a virtual map, according to an implementation of the present application. Referring to FIG. 9, in a software implementation, the apparatus 900 for drawing a virtual map can include a determining unit 901 and an updating unit 902.

[0105] The determining unit 901 determines, in a first area, a central area that a virtual object is located in, where the first area is an area map that includes tile maps loaded into a virtual map that the virtual object is located in, a border of the central area is located in the first area, a maximum distance between any tile map in the central area and the virtual object in an x-axis direction in a tile map coordinate system of the virtual map is less than X_1 , a maximum distance between any tile map in the central area and the virtual object in a y-axis direction in the tile map coordinate system is less than Y_1 , a length of one tile map is used as a unit on the x-axis in the tile map coordinate system, a width of one tile map is used as a unit on the y-axis in the tile map coordinate system, and X_1 and Y_1 are predetermined positive integers.

[0106] The determining unit 901 further determines a distance parameter after the virtual object moves out of the central area, where the distance parameter indicates relative distances of a tile map that the virtual object is located in relative to the central area in the x-axis direction and the y-axis direction in the tile map coordinate system.

[0107] The updating unit 902 updates a loading status of a tile map not shared by the first area and a second area based on the distance parameter and the first area, where the second area is a map area determined after moving the first area based on the distance parameter.

[0108] In the implementation of the present application, after the virtual object moves out of the central area that the virtual object is located in, the virtual object moves in to a tile map, and a distance parameter of the tile map that is relative to the central area is determined. Then, a tile map whose loading status needs to be updated is determined based on the distance parameter of the tile map and a currently loaded

tile map. Therefore, loading redundant tile maps can be alleviated to implement seamless connection between the tile maps, and efficiency of displaying the virtual map and an experience effect are improved to an extent.

[0109] Optionally, the determining unit 901 is specifically configured to:

- 5 determine that the distance parameter is (1, 0) when the virtual object moves to a tile map that is on the right of the central area and adjacent to the central area; or determine that the distance parameter is (1, 1) when the virtual object moves to a tile map that is at the upper right of the central area and adjacent to the central area; or determine that the distance parameter is (0, 1) when the virtual object moves to a tile map that is right above the central area and adjacent to the central area; or determine that the distance parameter is (-1, 1) when the virtual object moves to a tile map that is at the upper left of the central area and adjacent to the central area; or determine that the distance parameter is (-1, 0) when the virtual object moves to a tile map that is on the left of the central area and adjacent to the central area; or determine that the distance parameter is (-1, -1) when the virtual object moves to a tile map that is at the lower left of the central area and adjacent to the central area; or determine that the distance parameter is (0, -1) when the virtual object moves to a tile map that is right below the central area and adjacent to the central area; or determine that the distance parameter is (1, -1) when the virtual object moves to a tile map that is at the lower right of the central area and adjacent to the central area, where the distance parameter (a, b) indicates that the central area moves to the right by a tile maps and upward by b tile maps, and x and y are integers.

- [0110]** It should be understood that, in the implementation of the present application, the distance parameter (a, b) indicates that the central area moves to the right by a tile maps and upward by b tile maps, and a and b are integers. When a value of a or b is a negative number, it indicates that the central area moves in an opposite direction; or when the value of a or b is 0, it indicates that the central area does not move.

- [0111]** Optionally, the updating unit 902 is specifically configured to determine the distance parameter after the virtual object moves out of the central area for a time duration that exceeds a preset time, and update the loading status of the tile map not shared by the first area and the second area based on the distance parameter and the first area.

[0112] Optionally, the updating unit 902 is specifically configured to load added tile maps in the second area relative to tile maps in the first area, and remove reduced tile maps in the second area relative to tile maps in the first area.

[0113] Optionally, the updating unit 902 is specifically configured to determine an index of a tile map that needs to be updated based on the distance parameter and indexes of tile maps in the first area; and update a loading status of a tile map of the virtual object in the virtual map based on the index of the tile map that needs to be updated.

[0114] Preferably, X_1 is equal to Y_1 . Further, a value of X_1 is 1, 2, 3, 4, or 5.

[0115] Optionally, a maximum distance, in the x-axis direction, between any tile map in the first area and the tile map that the virtual object is located in is less than X_2 times a first unit length, and a maximum distance, in the y-axis direction, between the tile map in the first area and the tile map that the virtual object is located in is less than Y_2 times a second unit length, where X_2 and Y_2 are positive integers, and $X_1 < X_2$ and $Y_1 < Y_2$. Preferably, the first area and the central area are rectangular. Further, $Y_2 = Y_1 + 1$, and $X_2 = X_1 + 1$. In this case, a new rectangular area is generated by separately extending the periphery of the central area upward and downward and to the left and the right by one tile map, and the new rectangular area is the first area.

[0116] Optionally, the determining unit 901 further determines corresponding map coordinates of the virtual object in the virtual map based on latitude and longitude of an actual object that corresponds to the virtual object in an actual environment, where the virtual map is generated based on an actual electronic map.

[0117] Optionally, the determining unit 901 further determines a corresponding action parameter of the virtual object in the virtual map and operates the virtual object based on an action parameter of the actual object that corresponds to the virtual object in the actual environment.

[0118] The apparatus 900 for drawing a virtual map can further perform the method in FIG. 4, and implement functions of an apparatus for drawing a virtual map, a graphics engine, etc. in the implementations shown in FIG. 4 and FIG. 6. Details are omitted in the implementation of the present application for simplicity.

[0119] FIG. 10 is a schematic structural diagram illustrating an apparatus 1000 for drawing a virtual map, according to an implementation of the present application. Referring to FIG. 10, in a software implementation, the apparatus 1000 for drawing a

virtual map can include a determining unit 1001, an area division unit 1002, and an image processing unit 1003.

5 [0120] The determining unit 1001 is configured to determine a map area of a virtual map based on a scaling relationship between an actual electronic map and the virtual map.

[0121] The area division unit 1002 is configured to divide the map area into a plurality of equally sized tile areas.

10 [0122] The image processing unit 1003 is configured to perform image processing on each tile area based on an area map that corresponds to the tile area in the actual electronic map, to generate a tile map of the tile area, where the image processing includes rendering processing.

15 [0123] In the implementation of the present application, the area of the virtual map is determined based on the actual electronic map, the virtual map is divided into a plurality of equally sized tile areas, and rendering processing is performed on the tile areas based on corresponding area maps of the tile areas in the actual electronic map, so that a tile map of the virtual map can be generated fast based on the actual electronic map, thereby improving efficiency of generating the virtual map.

20 [0124] Optionally, the determining unit 1001 further determines a first actual area map that corresponds to a first tile area in the plurality of equally sized tile areas in the actual electronic map based on a size of the tile area and an index of the first tile area, and the image processing unit 1003 further performs image processing on the first tile area based on the first actual area map to obtain a first tile map that corresponds to the first tile area.

25 [0125] Certainly, it should be understood that the area division unit 1002 can further create an index for each tile area in the plurality of equally sized tile areas.

[0126] The apparatus 1000 for drawing a virtual map can further perform the method in FIG. 1, and implement functions of an apparatus for drawing a virtual map, a graphics engine, etc. in the implementations shown in FIG. 1 and FIG. 2. Details are omitted in the implementation of the present application for simplicity.

30 [0127] In the 1990s, whether a technical improvement is a hardware improvement (for example, an improvement to a circuit structure, such as a diode, a transistor, or a switch) or a software improvement (an improvement to a method procedure) can be clearly distinguished. However, as technologies develop, current improvements to many method procedures can be considered as direct improvements to hardware

circuit structures. A designer usually programs an improved method procedure into a hardware circuit, to obtain a corresponding hardware circuit structure. Therefore, a method procedure can be improved by using a hardware entity module. For example, a programmable logic device (PLD) (for example, a field programmable gate array (FPGA)) is such an integrated circuit, and a logical function of the PLD is determined by a user through device programming. The designer performs programming to "integrate" a digital system to a PLD without requesting a chip manufacturer to design and produce an application-specific integrated circuit chip. In addition, at present, instead of manually manufacturing an integrated chip, this type of programming is mostly implemented by using "logic compiler" software. The programming is similar to a software compiler used to develop and write a program. Original code needs to be written in a particular programming language for compilation. The language is referred to as a hardware description language (HDL). There are many HDLs, such as the Advanced Boolean Expression Language (ABEL), the Altera Hardware Description Language (AHDL), Confluence, the Cornell University Programming Language (CUPL), HDCal, the Java Hardware Description Language (JHDL), Lava, Lola, MyHDL, PALASM, and the Ruby Hardware Description Language (RHDL). The very-high-speed integrated circuit hardware description language (VHDL) and Verilog are most commonly used. A person skilled in the art should also understand that a hardware circuit that implements a logical method procedure can be readily obtained once the method procedure is logically programmed by using the several described hardware description languages and is programmed into an integrated circuit.

[0128] A controller can be implemented by using any appropriate method. For example, the controller can be a microprocessor or a processor, or a computer-readable medium that stores computer readable program code (such as software or firmware) that can be executed by the microprocessor or the processor, a logic gate, a switch, an application-specific integrated circuit (ASIC), a programmable logic controller, or a built-in microprocessor. Examples of the controller include but are not limited to the following microprocessors: ARC 625D, Atmel AT91SAM, Microchip PIC18F26K20, and Silicone Labs C8051F320. The memory controller can also be implemented as a part of the control logic of the memory. A person skilled in the art also knows that, in addition to implementing the controller by using the computer readable program code, logic programming can be performed on method

steps to allow the controller to implement the same function in forms of the logic gate, the switch, the application-specific integrated circuit, the programmable logic controller, and the built-in microcontroller. Therefore, the controller can be considered as a hardware component, and an apparatus configured to implement various functions in the controller can also be considered as a structure in the hardware component. Or, the apparatus configured to implement various functions can even be considered as both a software module implementing the method and a structure in the hardware component.

[0129] The system, apparatus, module, or unit illustrated in the previous implementations can be implemented by using a computer chip or an entity, or can be implemented by using a product having a certain function. A typical implementation device is a computer. The computer can be, for example, a personal computer, a laptop computer, a cellular phone, a camera phone, a smartphone, a personal digital assistant, a media player, a navigation device, an email device, a game console, a tablet computer, or a wearable device, or a combination of any of these devices.

[0130] For ease of description, the apparatus above is described by dividing functions into various units. Certainly, when the present application is implemented, a function of each unit can be implemented in one or more pieces of software and/or hardware.

[0131] A person skilled in the art should understand that an implementation of the present invention can be provided as a method, a system, or a computer program product. Therefore, the present invention can use a form of hardware only implementations, software only implementations, or implementations with a combination of software and hardware. Moreover, the present invention can use a form of a computer program product that is implemented on one or more computer-usable storage media (including but not limited to a disk memory, a CD-ROM, an optical memory, etc.) that include computer-usable program code.

[0132] The present invention is described with reference to the flowcharts and/or block diagrams of the method, the device (system), and the computer program product according to the implementations of the present invention. It should be understood that computer program instructions can be used to implement each process and/or each block in the flowcharts and/or the block diagrams and a combination of a process and/or a block in the flowcharts and/or the block diagrams. These computer program instructions can be provided for a general-purpose computer, a special-purpose

computer, a built-in processor, or a processor of another programmable data processing device to generate a machine, so that the instructions executed by the computer or the processor of the another programmable data processing device generate an apparatus for implementing a specific function in one or more flows in the flowcharts and/or in one or more blocks in the block diagrams.

[0133] These computer program instructions can be stored in a computer readable memory that can instruct the computer or the another programmable data processing device to work in a specific way, so that the instructions stored in the computer readable memory generate an artifact that includes an instruction apparatus. The instruction apparatus implements a specific function in one or more flows in the flowcharts and/or in one or more blocks in the block diagrams.

[0134] These computer program instructions can be loaded onto the computer or the another programmable data processing device, so that a series of operations and steps are performed on the computer or the another programmable device, thereby generating computer-implemented processing. Therefore, the instructions executed on the computer or the another programmable device provide steps for implementing a specific function in one or more flows in the flowcharts and/or in one or more blocks in the block diagrams.

[0135] In a typical configuration, a computing device includes one or more processors (CPU), one or more input/output interfaces, one or more network interfaces, and one or more memories.

[0136] The memory can include a non-persistent memory, a random access memory (RAM), a nonvolatile memory, and/or another form in a computer readable medium, for example, a read-only memory (ROM) or a flash memory (flash RAM).

The memory is an example of the computer readable medium.

[0137] The computer readable medium includes persistent, non-persistent, movable, and unmovable media that can implement information storage by using any method or technology. Information can be a computer readable instruction, a data structure, a program module, or other data. A computer storage medium includes but is not limited to a phase-change random access memory (PRAM), a static random access memory (SRAM), a dynamic random access memory (DRAM), a random access memory (RAM) of another type, a read-only memory, an electrically erasable programmable read-only memory (EEPROM), a flash memory or another memory technology, a compact disc read-only memory (CD-ROM), a digital versatile disc

(DVD), or another optical storage, a cassette, a cassette magnetic disk storage, or another magnetic storage device or any other non-transmission medium. The computer storage medium can be configured to store information that can be accessed by a computing device. Based on the definition in the present specification, the computer readable medium does not include transitory media (transitory media), for example, a modulated data signal and carrier.

[0138] It is worthwhile to further note that the terms "include", "comprise", or their any other variant is intended to cover a non-exclusive inclusion, so that a process, a method, an article, or a device that includes a list of elements not only includes those elements but also includes other elements which are not expressly listed, or further includes elements inherent to such a process, method, article, or device. An element preceded by "includes a ..." does not, without more constraints, preclude the existence of additional identical elements in the process, method, article, or device that includes the element.

[0139] A person skilled in the art should understand that an implementation of the present application can be provided as a method, a system, or a computer program product. Therefore, the present application can use a form of hardware only implementations, software only implementations, or implementations with a combination of software and hardware. In addition, the present application can use a form of a computer program product that is implemented on one or more computer-usable storage media (including but not limited to a disk memory, a CD-ROM, an optical memory, etc.) that include computer-usable program code.

[0140] The present application can be described in the general context of computer executable instructions executed by a computer, for example, a program module. Generally, the program module includes a routine, a program, an object, a component, a data structure, etc. executing a specific task or implementing a specific abstract data type. The present application can also be practiced in distributed computing environments. In the distributed computing environments, tasks are performed by remote processing devices connected through a communications network. In a distributed computing environment, the program module can be located in both local and remote computer storage media including storage devices.

[0141] The implementations in the present specification are described in a progressive way. For same or similar parts in the implementations, refer to the implementations. Each implementation focuses on a difference from other

implementations. Particularly, a system implementation is basically similar to a method implementation, and therefore, is described briefly. For related parts, refer to related descriptions in the method implementation.

5 **[0142]** The previous descriptions are merely implementations of the present application, and are not intended to limit the present application. For a person skilled in the art, the present application can have various modifications and changes. Any modifications, equivalent substitutions, improvements, etc. made in the spirit and principle of the present application shall fall in the scope of the claims in the present application.

CLAIMS

1. A method for updating a virtual map, comprising:

determining, in a first area, a central area in which a virtual object is located, wherein the first area is an area of the virtual map that comprises one or more tile maps loaded into the virtual map;

determining a distance parameter corresponding to a location of the virtual object relative to the central area;

detecting the virtual object has moved, or is moving;

determining the virtual object is outside of the central area for a time duration that exceeds a preset time; and

responsive to determining the virtual object is outside of the central area for the time duration that exceeds the preset time, updating a loading status of one or more tile maps not shared by the first area and a second area, wherein the loading status is updated based on the distance parameter and the first area, wherein

the second area is an area of the virtual map determined based on the distance parameter.

2. The method of claim 1, wherein:

a maximum distance between any tile map in the central area and the virtual object in an x-axis direction in a coordinate system of the virtual map is less than X_1 , wherein X_1 represents a first predetermined positive integer;

a maximum distance between any tile map in the central area and the virtual object in a y-axis direction in the coordinate system of the virtual map is less than Y_1 , wherein Y_1 represents a second predetermined positive integer;

a length of one tile map is used as a unit on an x-axis in the coordinate system of the virtual map; and

a width of one tile map is used as a unit on a y-axis in the coordinate system of the virtual map.

3. The method of claim 1, wherein determining the distance parameter comprises:

determining that the distance parameter is (1, 0) when the virtual object moves to a tile map that is on the right of the central area and adjacent to the central area; or

determining that the distance parameter is (1, 1) when the virtual object moves to a tile map that is at the upper right of the central area and adjacent to the central area; or

5 determining that the distance parameter is (0, 1) when the virtual object moves to a tile map that is right above the central area and adjacent to the central area; or

determining that the distance parameter is (-1, 1) when the virtual object moves to a tile map that is at the upper left of the central area and adjacent to the central area; or

10 determining that the distance parameter is (-1, 0) when the virtual object moves to a tile map that is on the left of the central area and adjacent to the central area; or

determining that the distance parameter is (-1, -1) when the virtual object moves to a tile map that is at the lower left of the central area and adjacent to the central area; or

determining that the distance parameter is (0, -1) when the virtual object moves to a tile map that is right below the central area and adjacent to the central area; or

15 determining that the distance parameter is (1, -1) when the virtual object moves to a tile map that is at the lower right of the central area and adjacent to the central area, wherein the tile map is a rectangular area, the distance parameter (a , b) indicates that the central area moves to the right by a tile maps and upward by b tile maps, and x and y are integers.

20 4. The method of claim 1, wherein updating the loading status of one or more tile maps not shared by the first area and the second area comprises:

determining a first group of tile maps of the virtual map that are to be removed;

determining a second group of tile maps of the virtual map that are to be loaded; and

updating the loading status of the one or more tile maps based on the first group or the

25 second group.

5. The method of claim 1, further comprising:

before determining the distance parameter and updating the loading status of the one or more tile maps, determining corresponding map coordinates of the virtual object in the virtual
30 map based on a latitude and a longitude, wherein the virtual map is generated based on a two-

dimensional (2D) electronic map or a three-dimensional (3D) electronic map and the virtual object corresponds to an object on the 2D electronic map or within the 3D electronic map.

6. The method of claim 1 further comprising:

5 based on the loading status of the one or more tile maps, loading at least one tile map not included in the first area into the second area; and
removing at least one tile map included in the first area from the second area.

7. The method of claim 1, wherein a tile map of the one or more tile maps loaded into the
10 virtual map is sub-divided into one or more sub-tile maps.

8. A non-transitory, computer-readable medium storing one or more instructions executable by a computer system to perform operations comprising:

determining, in a first area, a central area in which a virtual object is located, wherein the
15 first area is an area of a virtual map that comprises one or more tile maps loaded into the virtual map;

determining a distance parameter corresponding to a location of the virtual object relative to the central area;

detecting the virtual object has moved, or is moving;

20 determining the virtual object is outside of the central area for a time duration that exceeds a preset time; and

responsive to determining the virtual object is outside of the central area for the time duration that exceeds the preset time, updating a loading status of one or more tile maps not shared by the first area and a second area, wherein the loading status is updated based on the
25 distance parameter and the first area, wherein

the second area is an area of the virtual map determined based on the distance parameter.

9. The non-transitory, computer-readable medium of claim 8, wherein:

30 a maximum distance between any tile map in the central area and the virtual object in an x-axis direction in a coordinate system of the virtual map is less than X_1 , wherein X_1 represents a

first predetermined positive integer;

a maximum distance between any tile map in the central area and the virtual object in a y-axis direction in the coordinate system of the virtual map is less than Y_1 , wherein Y_1 represents a second predetermined positive integer;

5 a length of one tile map is used as a unit on an x-axis in the coordinate system of the virtual map; and

a width of one tile map is used as a unit on an y-axis in the coordinate system of the virtual map.

10 10. The non-transitory, computer-readable medium of claim 8, wherein determining the distance parameter comprises:

determining that the distance parameter is (1, 0) when the virtual object moves to a tile map that is on the right of the central area and adjacent to the central area; or

15 determining that the distance parameter is (1, 1) when the virtual object moves to a tile map that is at the upper right of the central area and adjacent to the central area; or

determining that the distance parameter is (0, 1) when the virtual object moves to a tile map that is right above the central area and adjacent to the central area; or

determining that the distance parameter is (-1, 1) when the virtual object moves to a tile map that is at the upper left of the central area and adjacent to the central area; or

20 determining that the distance parameter is (-1, 0) when the virtual object moves to a tile map that is on the left of the central area and adjacent to the central area; or

determining that the distance parameter is (-1, -1) when the virtual object moves to a tile map that is at the lower left of the central area and adjacent to the central area; or

25 determining that the distance parameter is (0, -1) when the virtual object moves to a tile map that is right below the central area and adjacent to the central area; or

determining that the distance parameter is (1, -1) when the virtual object moves to a tile map that is at the lower right of the central area and adjacent to the central area, wherein the tile map is a rectangular area, the distance parameter (a , b) indicates that the central area moves to the right by a tile maps and upward by b tile maps, and x and y are integers.

30

11. The non-transitory, computer-readable medium of claim 8, wherein updating the loading

status of one or more tile maps not shared by the first area and the second area comprises:
determining a first group of tile maps of the virtual map that are to be removed;
determining a second group of tile maps of the virtual map that are to be loaded; and
updating the loading status of the one or more tile maps based on the first group or the
5 second group.

12. The non-transitory, computer-readable medium of claim 8, further comprising:
before determining the distance parameter and updating the loading status of the one or
more tile maps, determining corresponding map coordinates of the virtual object in the virtual
10 map based on a latitude and a longitude, wherein the virtual map is generated based on a two-
dimensional (2D) electronic map or a three-dimensional (3D) electronic map and the virtual
object corresponds to an object on the 2D electronic map or within the 3D electronic map.

13. The non-transitory, computer-readable medium of claim 8, further comprising:
15 based on the loading status of the one or more tile maps, loading at least one tile map not
included in the first area into the second area; and
removing at least one tile map included in the first area from the second area.

14. The non-transitory, computer-readable medium of claim 8, wherein a tile map of the one
20 or more tile maps loaded into the virtual map is sub-divided into one or more sub-tile maps.

15. A computer-implemented system, comprising:
one or more computers; and
one or more computer memory devices interoperably coupled with the one or more
computers and having tangible, non-transitory, machine-readable media storing one or more
instructions that, when executed by the one or more computers, perform one or more operations
comprising:
determining, in a first area, a central area in which a virtual object is located, wherein the
first area is an area of a virtual map that comprises one or more tile maps loaded into the virtual
25 map;
determining a distance parameter corresponding to a location of the virtual object relative

to the central area;

detecting the virtual object has moved, or is moving;

determining the virtual object is outside of the central area for a time duration that exceeds a preset time; and

5 responsive to determining the virtual object is outside of the central area for the time duration that exceeds the preset time, updating a loading status of one or more tile maps not shared by the first area and a second area, wherein the loading status is updated based on the distance parameter and the first area, wherein

10 the second area is an area of the virtual map determined based on the distance parameter.

16. The computer-implemented system of claim 15, wherein:

a maximum distance between any tile map in the central area and the virtual object in an x-axis direction in a coordinate system of the virtual map is less than X_1 , wherein X_1 represents a
15 first predetermined positive integer;

a maximum distance between any tile map in the central area and the virtual object in a y-axis direction in the coordinate system of the virtual map is less than Y_1 , wherein Y_1 represents a second predetermined positive integer;

20 a length of one tile map is used as a unit on an x-axis in the coordinate system of the virtual map; and

a width of one tile map is used as a unit on an y-axis in the coordinate system of the virtual map.

17. The computer-implemented system of claim 15, wherein determining the distance parameter comprises:

25 determining that the distance parameter is (1, 0) when the virtual object moves to a tile map that is on the right of the central area and adjacent to the central area; or

determining that the distance parameter is (1, 1) when the virtual object moves to a tile map that is at the upper right of the central area and adjacent to the central area; or

30 determining that the distance parameter is (0, 1) when the virtual object moves to a tile map that is right above the central area and adjacent to the central area; or

determining that the distance parameter is (-1, 1) when the virtual object moves to a tile

map that is at the upper left of the central area and adjacent to the central area; or

determining that the distance parameter is $(-1, 0)$ when the virtual object moves to a tile map that is on the left of the central area and adjacent to the central area; or

determining that the distance parameter is $(-1, -1)$ when the virtual object moves to a tile

5 map that is at the lower left of the central area and adjacent to the central area; or

determining that the distance parameter is $(0, -1)$ when the virtual object moves to a tile map that is right below the central area and adjacent to the central area; or

determining that the distance parameter is $(1, -1)$ when the virtual object moves to a tile map that is at the lower right of the central area and adjacent to the central area, wherein the tile

10 map is a rectangular area, the distance parameter (a, b) indicates that the central area moves to the right by a tile maps and upward by b tile maps, and x and y are integers.