



(51) International Patent Classification:
A62B 35/04 (2006.01)

(21) International Application Number:

PCT/US2010/024896

(22) International Filing Date:

22 February 2010 (22.02.2010)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

12/400,208 9 March 2009 (09.03.2009) US

(71) Applicant (for all designated States except US): **D B INDUSTRIES, INC.** [US/US]; 3833 Sala Way, Red Wing, MN 55066-5005 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WOLNER, Thomas, J.** [US/US]; 1504 Norwood Street, Red Wing, MN 55066 (US). **CASEBOLT, Scott, C.** [US/US]; 1460 Laurel Avenue, St. Paul Park, MN 55071 (US). **GAMACHE, Gabriel, Grant** [US/US]; 8346 Jorgensen

Avenue South, Cottage Grove, MN 55016 (US). **BLACKFORD, Matthew, J.** [US/US]; 739 Melville Circle, Hastings, MN 55033 (US).

(74) Agent: **MAU, Michael, L.**; IPLM Group, P.A., Post Office Box 18455, Minneapolis, MN 55418 (US).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: SAFETY DEVICE WITH FALL ARREST AND DESCENDING MODES

FIG. 1



(57) Abstract: A safety device with fall arrest and descending modes includes a housing, a drum, a lifeline, first and second brake assemblies, and a control. The drum is rotatably operatively connected to the housing. The lifeline has an intermediate portion interconnecting a first end and a second end. The first end is operatively connected to the drum. The first and second assemblies are operatively connected to the drum. The control is operatively connected to the first and second brake assemblies and has a first position and a second position. The first position selectively engages the first brake assembly in a descending mode and the second position selectively engages the second brake assembly in a fall arrest mode.



ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, **Published:**

MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM,

TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, — *with international search report (Art. 21(3))*

ML, MR, NE, SN, TD, TG).