



- (51) **International Patent Classification:**
A47C 23/043 (2006.01) *F16F 1/04* (2006.01)
- (21) **International Application Number:**
PCT/US2024/040784
- (22) **International Filing Date:**
02 August 2024 (02.08.2024)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
63/530,429 02 August 2023 (02.08.2023) US
- (71) **Applicant:** **SEALY TECHNOLOGY, LLC** [US/US];
One Office Parkway, Trinity, North Carolina 27370 (US).
- (72) **Inventors:** **TAR, Kevin**; c/o Sealy Technology LLC,
One Office Parkway, Trinity, North Carolina 27370 (US).
MANUSZAK, Brian; c/o Sealy Technology LLC, One Office
Parkway, Trinity, North Carolina 27370 (US).
- (74) **Agent:** **WRIGHT, Terry L.** et al.; c/o Stites & Harbison,
PLLC, 400 West Market Street, Suite 1800, Louisville, Ken-
tucky 40202 (US).
- (81) **Designated States** (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CV, CZ, DE, DJ, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IQ, IR, IS, IT, JM, JO, JP, KE, KG,
KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY,
MA, MD, MG, MK, MN, MU, MW, MX, MY, MZ, NA,
NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO,
RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH,
TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS,
ZA, ZM, ZW.

- (84) **Designated States** (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, CV,
GH, GM, KE, LR, LS, MW, MZ, NA, RW, SC, SD, SL, ST,
SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ,
RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ,
DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT,
LU, LV, MC, ME, MK, MT, NL, NO, PL, PT, RO, RS, SE,
SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*

- (54) **Title:** COIL SPRINGS, POCKETED COIL SPRINGS ASSEMBLIES, AND MATTRESSES INCLUDING THE SAME




FIG. 1

(57) **Abstract:** A coil spring comprises a continuous wire forming a lowermost convolution, an uppermost convolution, and a plurality of helical intermediate convolutions. The coil spring is divided into an upper portion and a lower portion. The intermediate convolutions of the lower portion have a diameter greater than or equal to a lower minimum diameter, and the pitch between each of the convolutions of the lower portion is greater than or equal to a lower minimum pitch. The intermediate convolutions of the upper portion have a diameter greater than or equal to an upper minimum diameter, and the pitch between each of the convolutions of the upper portion is less than or equal to an upper maximum pitch. The upper minimum diameter is greater than, less than, or equal to the lower minimum diameter, and the upper maximum pitch is less than the lower minimum pitch to provide a non-linear and variable response.