

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



G00002

(43) International Publication Date
4 April 2002 (04.04.2002)


PCT

(10) International Publication Number
WO 02/027969 A3

- (51) International Patent Classification⁷: **H04B 7/005**
- (21) International Application Number: PCT/US01/30418
- (22) International Filing Date:
27 September 2001 (27.09.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/675,706 29 September 2000 (29.09.2000) US
- (71) Applicant: **QUALCOMM INCORPORATED** [US/US];
5775 Morehouse Drive, San Diego, CA 92121-1714 (US).
- (72) Inventors: **HOLTZMAN, Jack**; 12970 Caminito Bautizo,
San Diego, CA 92130 (US). **BAO, Gang**; 13255 Larkfield
Court, San Diego, CA 92130 (US).
- (74) Agents: **WADSWORTH, Philip, R.** et al.; Qualcomm Incorporated, 5775 Morehouse Drive, San Diego, CA 92121-1714 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PI, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR DETERMINING AVAILABLE TRANSMIT POWER IN A WIRELESS COMMUNICATION SYSTEM



(57) Abstract: Techniques to (more accurately) estimate the transmit power available for data service in a future time period (e.g., the next frame). In accordance with one aspect, variation in the available transmit power over time is estimated. A first margin is then computed and used to account for the estimated variation in the available transmit power. The available transmit power at a future time instance (e.g., the beginning of the next frame) is predicted and reduced by the first margin to derive a more accurate estimate of the available transmit power for the next frame. In accordance with another aspect, variation in the required transmit power for a particular data user is estimated and used in scheduling data transmission to this data user. A second margin can be computed and used to account for the estimated variation in the required transmit power for the data user. Whereas the first margin accounts for variation in the (overall) available transmit power, the second margin is specific to the particular link conditions experienced by the data user.



162162

WO 02/027969 A3