PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

9705377-9.
1P02

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 :
E03F 5/16

A1

(11) International Publication Number: WO 98/50644

(43) International Publication Date: 12 November 1998 (12.11.98)

(21) International Application Number: PCT/AU98/00310

(22) International Filing Date: 29 April 1998 (29.04.98)

(30) Priority Data:
PO 6595 1 May 1997 (01.05.97) AU

(71) Applicant *(for all designated States except US)*: ECLIPSE ENVIRONMENTAL AUSTRALIA PTY. LIMITED [AU/AU]; Level 20, 99 Walker Street, North Sydney, NSW 2060 (AU).

(72) Inventor; and
(75) Inventor/Applicant *(for US only)*: LAFERLA, Richard [AU/AU]; 1 Clarke Street, Granville, NSW 2142 (AU).

(74) Agent: F.B. RICE & CO.; 605 Darling Street, Balmain, NSW 2041 (AU).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published
With international search report.

(54) Title: GREASE SEPARATING DEVICE

(57) Abstract

A device (10) and method for separating oleaginous matter from a waste fluid. The device (10) includes a chamber (11) having a fluid inlet (19) and a fluid outlet (15) between which a fluid, such as waste water, may pass through the chamber (11). The chamber (11) contains a plurality of oleophilic polypropylene cylindrical rods (14) disposed in the fluid flow path between the inlet and outlet. The rods (14) being oleophilic attract and separate the oleaginous matter from the fluid passing through the chamber (11). The chamber (11) can also be mounted within a larger vessel (20) and over a holding container (30) that provides further treatments of the fluid passing through the device.

