

PIPETTE TIPS AND METHODS AND SYSTEMS INCLUDING SAMECROSS-REFERENCE TO RELATED APPLICATION

[001] The present application claims the benefit of and priority from U.S. Provisional Patent Application No. 62/961,416 filed January 15, 2020, the entire content of which is incorporated herein by reference.

FIELD

[002] The present technology relates to pipette tips and, more particularly, to pipette tips that can be replaceably mounted on a pipettor shaft.

BACKGROUND

[003] Many research and/or manufacturing processes require the delivery or transport of a precise amount of liquid. Precisely controlling the aspiration and/or dispensation of liquid can be important in producing accurate test results and high quality products, as well as being important in reducing the costs associated with such operations. Pipette tips are commonly employed for delivering precise amounts of liquid. In particular, it is known to removably and replaceably mount a pipette tip on a dispensing device (*e.g.*, a manual or automated apparatus). For example, the pipette tip may be mounted on a pipettor shaft or mandrel.

SUMMARY

[004] According to embodiments of the technology, a pipette tip for use with a pipettor including a pipettor shaft having a terminal end has opposed proximal and distal ends and includes a tubular body and a coupling portion. The tubular body extends between the proximal and distal ends. The tubular body defines a fluid passage terminating at a proximal opening adjacent the proximal end and a distal opening adjacent the distal end. The coupling portion is located on the proximal end. The coupling portion includes an interlock feature configured to mechanically interlock with the pipettor shaft proximate the terminal end to selectively and releasably secure the pipette tip to the pipettor shaft.

[005] In some embodiments, the interlock feature includes a circumferentially extending rib or groove configured to interlock with a cooperating groove or rib on the pipettor shaft.

[006] In embodiments, the interlock feature includes a circumferentially extending rib configured to interlock with a cooperating annular groove on the pipettor shaft.

[007] In certain embodiments, the body and the coupling portion are formed of different materials, and the material of the coupling portion is less stiff than the material of the body.

[008] According to some embodiments, the durometer (hardness) of the material of the body is at least 60 Shore D and the durometer of the material of the coupling portion is less than 70 Shore A.

[009] In some embodiments, the material of the body includes polypropylene or polyethylene, and the material of the coupling portion includes a thermoplastic elastomer (TPE).

[0010] In some embodiments, the coupling portion includes a stop shoulder configured to engage the terminal end and thereby limit insertion of the pipettor shaft into the coupling portion. The present disclosure also includes embodiments where the coupling portion includes an integral, annular sealing rib on an inner diameter, and the sealing rib is adapted to form a fluid-tight seal with an outer diameter of the pipettor shaft when the pipettor shaft is inserted into the coupling portion and interlocked with the interlock feature. The coupling portion may include a plurality of integral, circumferentially distributed coupling tabs, where the coupling tabs are configured to be radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion, and the interlock feature is located on at least one of the coupling tabs.

[0011] In certain embodiments, the fluid-tight seal is gas-tight up to at least 5 psi.

[0012] In some embodiments, the body and the sealing rib are formed of different materials, and the material of the sealing rib is less stiff than the material of the body.

[0013] In embodiments, the interlock feature includes a circumferentially extending rib or groove configured to interlock with a cooperating groove or rib on the pipettor shaft, while in some embodiments, the interlock feature includes a circumferentially extending rib configured to interlock with a cooperating annular groove on the pipettor shaft.

[0014] According to some embodiments, the body and the coupling tabs are formed of different materials, and the material of the coupling tabs is less stiff than the material of the body.

[0015] Accordingly, in embodiments, the interlock feature may include a circumferentially extending rib or groove configured to interlock with a cooperating groove or rib on the pipettor shaft, the coupling portion includes a stop shoulder configured to

engage the terminal end and thereby limit insertion of the pipettor shaft into the coupling portion, the coupling portion includes an integral, annular sealing rib on an inner diameter, the sealing rib is adapted to form a fluid-tight seal with an outer diameter of the pipettor shaft when the pipettor shaft is inserted into the coupling portion and interlocked with the interlock feature, the body and the sealing rib are formed of different materials, and the material of the sealing rib is less stiff than the material of the body.

[0016] Also disclosed are methods for mounting a pipette tip on a pipettor shaft having a terminal end, where the methods include providing a pipette tip, the pipette tip having opposed proximal and distal ends and including: a tubular body extending between the proximal and distal ends, the tubular body defining a fluid passage terminating at a proximal opening adjacent the proximal end and a distal opening adjacent the distal end; and a coupling portion on the proximal end, the coupling portion including an interlock feature configured to mechanically interlock with the pipettor shaft proximate the terminal end to selectively and releasably secure the pipette tip to the pipettor shaft. The methods include inserting the terminal end of the pipettor shaft into the coupling portion to mechanically interlock the interlock feature with the pipettor shaft proximate the terminal end and thereby releasably secure the pipette tip to the pipettor shaft.

[0017] In some embodiments, the interlock feature includes a circumferentially extending rib or groove, and the circumferentially extending rib or groove interlocks with a cooperating groove or rib on the pipettor shaft when the terminal end of the pipettor shaft is inserted into the coupling portion.

[0018] In embodiments, the interlock feature includes a circumferentially extending rib configured to interlock with a cooperating annular groove on the pipettor shaft.

[0019] In certain embodiments, the body and the coupling portion are formed of different materials, and the material of the coupling portion is less stiff than the material of the body.

[0020] In some embodiments, the durometer of the material of the body is at least 60 Shore D, and the durometer of the material of the coupling portion is less than 70 Shore A.

[0021] In some embodiments, the material of the body includes polypropylene, and the material of the coupling portion includes a thermoplastic elastomer.

[0022] In some embodiments, the coupling portion includes a stop shoulder that engages the terminal end and thereby limits insertion of the pipettor shaft into the coupling portion when the terminal end of the pipettor shaft is inserted into the coupling portion.

[0023] The present disclosure also includes embodiments where the coupling portion includes an integral, annular sealing rib on an inner diameter, and the sealing rib forms a fluid-tight seal with an outer diameter of the pipettor shaft when the pipettor shaft is inserted into the coupling portion and interlocked with the interlock feature. The coupling portion may include a plurality of integral, circumferentially distributed coupling tabs, where the coupling tabs are radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion, and the interlock feature is located on at least one of the coupling tabs.

[0024] In certain embodiments, the fluid-tight seal is gas-tight up to at least 5 psi.

[0025] In certain embodiments, the body and the sealing rib are formed of different materials, and the material of the sealing rib is less stiff than the material of the body.

[0026] In some embodiments, the coupling portion includes a plurality of integral, circumferentially distributed coupling tabs, the coupling tabs are radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion, and the interlock feature is located on at least one of the coupling tabs.

[0027] In some embodiments, the interlock feature includes a circumferentially extending rib or groove, and the circumferentially extending rib or groove interlocks with a cooperating groove or rib on the pipettor shaft when the terminal end of the pipettor shaft is inserted into the coupling portion, while in some embodiments, the interlock feature includes a circumferentially extending rib configured to interlock with a cooperating annular groove on the pipettor shaft.

[0028] According to some embodiments, the body and the coupling tabs are formed of different materials, and the material of the coupling tabs is less stiff than the material of the body.

[0029] According to some methods, the interlock feature includes a circumferentially extending rib or groove, the circumferentially extending rib or groove interlocks with a cooperating groove or rib on the pipettor shaft when the terminal end of the pipettor shaft is inserted into the coupling portion, the coupling portion includes a stop shoulder that engages the terminal end and thereby limits insertion of the pipettor shaft into the coupling portion when the terminal end of the pipettor shaft is inserted into the coupling portion, the coupling portion includes an integral, annular sealing rib on an inner diameter, the sealing rib forms a fluid-tight seal with an outer diameter of the pipettor shaft when the pipettor shaft is inserted into the coupling portion and interlocked with the interlock feature, the body and the sealing

rib are formed of different materials, and the material of the sealing rib is less stiff than the material of the body.

[0030] Also disclosed are pipetting systems that include a pipettor and a pipette tip. The pipettor includes a pipettor shaft having a terminal end. The pipette tip has opposed proximal and distal ends and includes a tubular body and a coupling portion. The tubular body extends between the proximal and distal ends. The tubular body defines a fluid passage terminating at a proximal opening adjacent the proximal end and a distal opening adjacent the distal end. The coupling portion is located on the proximal end. The coupling portion includes an interlock feature configured to mechanically interlock with the pipettor shaft proximate the terminal end to selectively and releasably secure the pipette tip to the pipettor shaft.

[0031] In some embodiments, the interlock feature includes a circumferentially extending rib or groove configured to interlock with a cooperating groove or rib on the pipettor shaft.

[0032] In embodiments, the interlock feature includes a circumferentially extending rib configured to interlock with a cooperating annular groove on the pipettor shaft.

[0033] In certain embodiments, the body and the coupling portion are formed of different materials, and the material of the coupling portion is less stiff than the material of the body.

[0034] According to some embodiments, the durometer (hardness) of the material of the body is at least 60 Shore D and the durometer of the material of the coupling portion is less than 70 Shore A.

[0035] In some embodiments, the material of the body includes polypropylene or polyethylene, and the material of the coupling portion includes a thermoplastic elastomer (TPE).

[0036] In some embodiments, the coupling portion includes a stop shoulder configured to engage the terminal end and thereby limit insertion of the pipettor shaft into the coupling portion. The present disclosure also includes embodiments where the coupling portion includes an integral, annular sealing rib on an inner diameter, and the sealing rib is adapted to form a fluid-tight seal with an outer diameter of the pipettor shaft when the pipettor shaft is inserted into the coupling portion and interlocked with the interlock feature. The coupling portion may include a plurality of integral, circumferentially distributed coupling tabs, where the coupling tabs are configured to be radially outwardly displaced by

the pipettor shaft when the pipettor shaft is inserted into the coupling portion, and the interlock feature is located on at least one of the coupling tabs.

[0037] In certain embodiments, the fluid-tight seal is gas-tight up to at least 5 psi.

[0038] In some embodiments, the body and the sealing rib are formed of different materials, and the material of the sealing rib is less stiff than the material of the body.

[0039] In embodiments, the interlock feature includes a circumferentially extending rib or groove configured to interlock with a cooperating groove or rib on the pipettor shaft, while in some embodiments, the interlock feature includes a circumferentially extending rib configured to interlock with a cooperating annular groove on the pipettor shaft.

[0040] According to some embodiments, the body and the coupling tabs are formed of different materials, and the material of the coupling tabs is less stiff than the material of the body.

[0041] Accordingly, in embodiments, the interlock feature may include a circumferentially extending rib or groove configured to interlock with a cooperating groove or rib on the pipettor shaft, the coupling portion includes a stop shoulder configured to engage the terminal end and thereby limit insertion of the pipettor shaft into the coupling portion, the coupling portion includes an integral, annular sealing rib on an inner diameter, the sealing rib is adapted to form a fluid-tight seal with an outer diameter of the pipettor shaft when the pipettor shaft is inserted into the coupling portion and interlocked with the interlock feature, the body and the sealing rib are formed of different materials, and the material of the sealing rib is less stiff than the material of the body.

[0042] Also disclosed are pipette tips for use with a pipettor, where the pipettor includes a pipettor shaft having a terminal end has opposed proximal and distal ends and includes a tubular body and a coupling portion. The tubular body extends between the proximal and distal ends. The tubular body defines a fluid passage terminating at a proximal opening adjacent the proximal end and a distal opening adjacent the distal end. The coupling portion is located on the proximal end and is configured to selectively and releasably secure the pipette tip to the pipettor shaft. The coupling portion includes a plurality of integral, circumferentially distributed coupling tabs configured to be radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion.

[0043] According to further embodiments of the technology, disclosed are methods for mounting a pipette tip on a pipettor shaft having a terminal end, where the methods include providing a pipette tip having opposed proximal and distal ends and including: a tubular body extending between the proximal and distal ends, the tubular body defining a

fluid passage terminating at a proximal opening adjacent the proximal end and a distal opening adjacent the distal end; and a coupling portion on the proximal end and configured to selectively and releasably secure the pipette tip to the pipettor shaft, the coupling portion including a plurality of integral, circumferentially distributed coupling tabs configured to be radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion. The method further includes inserting the terminal end of the pipettor shaft into the coupling portion to thereby releasably secure the pipette tip to the pipettor shaft.

[0044] According to further embodiments of the technology, disclosed are pipetting systems that include a pipettor and a pipette tip. The pipettor includes a pipettor shaft having a terminal end. The pipette tip has opposed proximal and distal ends and includes: a tubular body extending between the proximal and distal ends, the tubular body defining a fluid passage terminating at a proximal opening adjacent the proximal end and a distal opening adjacent the distal end; and a coupling portion on the proximal end and configured to selectively and releasably secure the pipette tip to the pipettor shaft, the coupling portion including a plurality of integral, circumferentially distributed coupling tabs configured to be radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion.

[0045] Further features, advantages and details of the present technology will be appreciated by those of ordinary skill in the art from a reading of the figures and the detailed description of the preferred embodiments that follow, such description being merely illustrative of the present technology.

BRIEF DESCRIPTION OF THE DRAWINGS

[0046] **FIG. 1** is a perspective view of a pipetting system according to embodiments of the technology.

[0047] **FIG. 2** is a fragmentary, cross-sectional view of the pipetting system of **FIG. 1** taken along the line 2-2 of **FIG. 1**.

[0048] **FIG. 3** is an enlarged fragmentary, cross-sectional view of the pipetting system of **Figure 1** taken along the line 2-2 of **FIG. 1**.

[0049] **FIG. 4** is a fragmentary, exploded, top perspective view of the pipetting system of **FIG. 1**.

[0050] **FIG. 5** is a fragmentary, exploded, cross-sectional view of the pipetting system of **Figure 1** taken along the line 2-2 of **FIG. 1**.

[0051] FIG. 6 is a fragmentary, exploded, cross-sectional view of a pipette tip forming a part of the pipetting system of FIG. 1 taken along the line 6-6 of FIG. 5.

DETAILED DESCRIPTION

[0052] The present technology now will be described more fully hereinafter with reference to the accompanying drawings, in which illustrative embodiments of the technology are shown. In the drawings, the relative sizes of regions or features may be exaggerated for clarity. This technology may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the technology to those skilled in the art.

[0053] It will be understood that, although the terms first, second, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the present technology.

[0054] Spatially relative terms, such as “beneath”, “below”, “lower”, “above”, “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the exemplary term “below” can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90° or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

[0055] As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless expressly stated otherwise. It will be further understood that the terms “includes,” “comprises,” “including” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. It will be

understood that when an element is referred to as being “connected” or “coupled” to another element, it can be directly connected or coupled to the other element or intervening elements may be present. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

[0056] The term “monolithic” means an object that is a single, unitary piece formed or composed of a material without joints or seams.

[0057] With reference to **FIGS. 1-6**, a pipette tip **100** according to embodiments of the technology is shown therein. The pipette tip **100** may be mounted on a pipettor device **50** in a pipetting system **10**, as shown in **FIGS. 1-3**, for example.

[0058] The pipette tip **100** extends from a distal end **102A** to a proximal end **102B** and defines a pipette tip axis **B-B** (**FIG. 2**). The pipette tip **100** includes a body portion **120** adjacent the pipette tip distal end **102A** and a coupling portion **104** adjacent the pipette tip proximal end **102B**. The illustrated pipette tip **100** includes a body member **110** and a coupling member **140**. In the illustrated embodiment, the body portion **120** forms a part of the body member **110** and the coupling portion **104** includes the coupling member **140** and a proximal portion **130** (**FIG. 6**) of the body member **110**.

[0059] With reference to **FIGS. 2** and **6**, the body member **110** is tubular and extends from a body member proximal end **112B** to the pipette tip distal end **102A**. A frustoconical internal bore or through passage **114** extends axially fully through the body member **110** and terminates at a distal end opening **115A** and a proximal end opening **115B**. In some embodiments, the passage **114** tapers in the direction of the distal end opening **115A**. In some embodiments, the passage **114** includes one or more sections, *e.g.*, **114A**, **114B**, **114C**, and in embodiments, the one or more sections may have different inner diameters and/or rates of taper. The illustrated body portion **120** includes an inner surface **122** (defining at least a portion of the passage **114**) and a frustoconical outer surface **124** (which tapers in correspondence with the passage sections **114A**, **114B**, **114C**).

[0060] As shown in the **FIG. 6** embodiment (bottom portion), the body member proximal portion **130** includes a tubular or annular flange or side wall **132** including an inner surface **132A**, an outer surface **132B**, and a proximal end face **132C**. The inner surface **132A** defines a socket **136** and a socket proximal end opening **133** in communication therewith. In some embodiments, the socket **136** is substantially cylindrical. In the illustrated embodiment, an annular inner flange or stop shoulder **134** is located at the bottom of the socket **136** and extends radially inwardly from the side wall **132**. An annular outer flange **138** extends radially outwardly from the side wall **132**.

[0061] With reference to the upper portion of **FIG. 6**, the coupling member **140** extends from a coupling member distal end **142A** to the pipette tip proximal end **102B**. The illustrated coupling member **140** includes a base section **144**, an integral sealing section **150**, and an integral securing section **160**. A passage **146** extends through the coupling member **140** from a passage distal end opening **145A** to a passage proximal end opening **145B**.

[0062] The **FIG. 6** base section **144** includes an annular or tubular wall **144B** defining a coupling member socket **148**. In such an embodiment, the coupling member **140** is mounted on the body member proximal portion **130** such that the body member side wall **132** is received in the coupling member socket **148**. The mating surfaces **144A** and **130A** of the coupling member base section **144** and the body member proximal portion **130** are bonded (*e.g.*, by adhesive and/or molding) to one another to firmly secure the coupling member **140** to the body member **110**.

[0063] The sealing section **150** includes an annular or tubular body **152** and an integral, annular sealing rib **154** extending radially inwardly into the passage **146**.

[0064] With reference to **FIGS. 1, 4 and 6**, the securing portion or securing section **160** includes two diametrically opposed, circumferentially distributed tabs **162** extending axially from the sealing portion **150** in the proximal direction. The tabs **162** define a portion of the passage **146** as well as circumferentially spaced apart slots **166** between the tabs **162** (defined by opposing tab side edges **162C**). Each tab **162** is attached or merged at its distal end **162A** to the sealing section **150** and has a proximal free end **162B** (**FIG. 6**).

[0065] Each tab **162** of the illustrated embodiment includes a circumferentially extending interlock feature or rib **170** located adjacent its proximal free end **162B**. In some embodiments and as shown in **FIG. 5**, the rib **170** includes (in cross-sectional profile) a rib distal section **172A**, a rib proximal section **172B**, and a rib intermediate section **172C** having different rates of taper with respect to the central axis **B-B**. In some embodiments, the rib distal section **172A** tapers in the proximal direction and the rib proximal section **172B** tapers in the distal direction. In some embodiments, the rate of taper of the rib distal section **172A** is greater than the rate of taper of the rib proximal section **172B**. In some embodiments, the rib intermediate section **172C** is substantially non-tapered (*i.e.*, cylindrical).

[0066] The body member **110** may be formed of any suitable material(s). According to some embodiments, the body member **110** is formed of a polymeric material. According to some embodiments, the body member **110** is formed of a thermoplastic material. Suitable materials for the body member **110** may include polypropylene, polyethylene or similar

thermoplastics. According to some embodiments, the body member **110** is monolithic. The body member **110** may be injection molded.

[0067] The coupling member **140** may be formed of any suitable material(s). According to some embodiments, the coupling member **140** is formed of a polymeric material. According to some embodiments, the coupling member **140** is formed of an elastomeric material. Suitable materials for the coupling member **140** may include thermoplastic elastomers (TPE). According to some embodiments, the coupling member **140** is monolithic. The coupling member **140** may be injection molded. According to some embodiments, the coupling member **140** is overmolded onto or co-molded with the body member **110** (e.g., dual shot molded). The coupling member **140** forms a fluid-tight seal with the body member **110**.

[0068] According to some embodiments, the body member **110** is formed of a more stiff or rigid material than the coupling member **140**. In particular, in some embodiments, the tabs **162** are formed of a less stiff or rigid (i.e., more flexible) material than the body portion **120**. Moreover, in this case, the coupling portion **104** includes a relatively more rigid side wall **132** defining the socket **136** and relatively more flexible tabs **162**. According to some embodiments, the body member **110** is formed of a material having a durometer (hardness) of at least 60 Shore D and the coupling member **140** is formed of a material having a durometer of less than 70 Shore A. According to some embodiments, the body member **110** is formed of a material having a durometer in the range of from 60 Shore D to 80 Shore D and the coupling member **140** is formed of a material having a durometer in the range of from 50 Shore A to 70 Shore A.

[0069] According to some embodiments, the length **L1** (FIG. 2) of the body portion **120** is in the range of from about 10 mm to 125 mm.

[0070] According to some embodiments, the maximum inner diameter of the passage **114** is in the range of from about 0.5 mm to 15 mm.

[0071] According to some embodiments, the depth **H2** (FIG. 6) of the socket **136** is in the range of from about 1 mm to 10 mm. According to some embodiments, the diameter **D2** (FIG. 6) of the socket **136** is in the range of from about 1.5 mm to 8 mm.

[0072] According to some embodiments, the shoulder **134** has a width **W4** (FIG. 6) in the range of from about 0.3 mm to 2.5 mm.

[0073] According to some embodiments, the width **W5** (FIG. 6) of the sealing rib **154** is in the range of from about 0.01 mm to 2 mm. According to some embodiments, the height **H5** (FIG. 6) of the sealing rib **154** is in the range of from about 0.01 mm to 3 mm.

[0074] According to some embodiments, the width **W6** (**Figure 6**) of each interlock tab **162** (not including the interlock rib **170**) is in the range of from about 0.3 mm to 3 mm. According to some embodiments, the height **H6** (**FIG. 6**) of each interlock tab **162** is in the range of from about 1 mm to 10 mm. According to some embodiments, the width **W7** (**FIG. 5**) of each slot **166** is in the range of from about 0.1 mm to 5 mm. However, in other embodiment, the slots **166** may be narrowed to slits so that the tabs **162** are positioned substantially edge to edge. In some embodiments, three or more interlock tabs **162** are provided.

[0075] According to some embodiments, the width **W8** (**FIG. 6**) of each interlock rib **170** is in the range of from about 0.1 mm to 3 mm. According to some embodiments, the height **H8** (**FIG. 6**) of each interlock rib **170** is in the range of from about 0.1 mm to 6 mm.

[0076] With reference to **FIGS. 2 and 3**, a pipettor device **50** includes a pipettor mandrel or shaft **60** having a shaft axis **A-A** (**FIG. 2**) and extending to a shaft distal terminal end **62**. A fluid passage **66** extends through the shaft **60** to a shaft distal terminal opening **64** at the shaft distal terminal end **62**. The outer surface **68** of the shaft **60** may be generally cylindrical or slightly tapered and includes a circumferentially extending shaft interlock feature or groove **70** formed therein. In some embodiments, the groove **70** is annular and endless. The groove **70** has sections **72A**, **72B** and **72C** (upper portion, **FIG. 5**) complementary to the rib sections **172A**, **172B** and **172C** (lower portion, **FIG. 5**), respectively. A distal shaft portion **74** (**FIG. 5**) extends at least from the groove **70** (**FIG. 3**) to the shaft distal terminal end **62**.

[0077] The shaft **60** may be fluidly connected to an actuator **56** (**Figure 1**) by a conduit **52**. The actuator **56** may be a pump operable to apply a positive or negative pressure to the passage **66** to dispense or aspirate a volume of liquid. The pipettor device **50** may be a manual device (*e.g.*, a manual syringe) or an automated device.

[0078] The shaft **60** may be formed of any suitable material(s). In some embodiments, the shaft **60** is formed of metal. In some embodiments, the shaft **60** is formed of a polymeric material.

[0079] In use, the pipette tip **100** can be installed on the pipettor shaft **60** as follows in accordance with methods of the present technology. The distal shaft portion **74** is inserted into the socket **136** in an insertion direction **I** as shown in **FIGS. 4 and 5** until the shaft distal terminal end **62** (**FIG. 5**) abuts the stop shoulder **134** (**FIG. 5**) as shown in **FIGS. 1-3**. The stop shoulder **134** thus limits insertion of the pipettor shaft **60** into the coupling portion **104**.

The stop shoulder **134** may also provide or facilitate concentric alignment between the pipettor shaft **60** and the pipette tip **100**.

[0080] As the portion **74** is inserted, the tabs **162** are thereby resiliently splayed or deflected radially outwardly in directions **R** (as shown in dashed lines in **FIG. 3**). This deflection may include bending in the tabs **162** and/or cantilevering the tabs **162** about the tab distal ends **162A**. The tabs **162** are elastically deflected so that they continue to exert a radially compressive return force on the shaft **60**. When the interlock ribs **170** become aligned with the interlock groove **70**, the tabs **162**, and thereby the ribs **170**, retract or return radially inwardly and thereby seat the ribs **170** in the groove **70**. The distal shaft portion **74** is held captive by the coupling portion **104**. In addition to the mechanical interlock engagement between the interlock ribs **170** and the groove **70**, the sealing rib **154** and the tabs **162** may apply a radially compressive load on the distal shaft portion **74** and provide frictional resistance to removal of the pipette tip **100**.

[0081] According to some embodiments, the axial distance **L9** (**FIG. 3**) from the stop shoulder **134** to the interlock ribs **170** is in the range of from about 1 mm to 10 mm. According to some embodiments, the axial distance **L10** (**FIG. 3**) from the terminal end **62** of the pipettor shaft **60** to the interlock groove **70** is substantially the same as the distance **L9**. As a result, when the proximal shaft portion **74** is properly and fully inserted into the socket **136** to the stop shoulder **134**, the interlock ribs **170** will be axially aligned with the interlock groove **70**. The ribs **170** and the groove **70** are thus interlocked to resist axial displacement of the pipette tip **100** relative to the pipettor shaft **60**.

[0082] With the distal shaft portion **74** inserted in the coupling member socket **136**, the sealing rib **154** (**FIG. 5**) sealingly engages the outer surface of the distal shaft portion **74**. The inner diameter **D5** (**FIG. 5**) of the sealing rib **154** is less than the outer diameter **D11** (**FIG. 5**) of the distal portion **74**. As a result, when the proximal shaft portion **74** is properly and fully inserted into the coupling member socket **136**, the sealing rib **154** is elastically deformed by the shaft portion **74** and exerts a radially inwardly compressive force on the shaft outer surface. In this manner, a fluid-tight seal (*e.g.*, in some embodiments, a liquid-tight, a gas-tight or an air-tight seal) is formed between the sealing section **150** and the shaft **60**. According to some embodiments, the inner diameter **D5** is in the range of from about 0.05 mm to 2 mm less than the outer diameter **D11** of the distal portion **74**.

[0083] In the foregoing manner, the pipette tip **100** is mechanically and removably secured to the pipettor shaft **60**. The pipettor fluid passage **66** is fluidly connected to the pipette tip distal opening **115A** through the passage **114**. The pipette tip **100** sealingly

engages (by the sealing rib **154**) the pipettor shaft **60** to provide a fluid sealed path. The assembly of the pipette tip **100** and the pipettor device **50** can then be used as desired to dispense, aspirate and/or transport liquids through or with the pipette tip **100** (and, in some embodiments, through or with the pipettor shaft **60**) as desired.

[0084] When desired, the pipette tip **100** can be removed by withdrawing the pipettor shaft **60** from the coupling member socket **136** in a direction opposite the installation direction **I**. Upon application of sufficient axial force, the tabs **162** will resiliently deflect radially outwardly again to disengage the ribs **170** from the groove **70**. If desired, the removed pipette tip **100** can be replaced with a new pipette tip **100**. The new pipette tip **100** can be installed in the same manner as the first pipette tip **100**.

[0085] For the pipette tip **100** and pipetting systems and methods disclosed herein, the use of deflectable tabs **162** and cooperating interlock features **170**, **70** permits a geometry that requires low insertion force while nonetheless providing sufficient resistance to removal of the pipette tip **100** from the shaft **60**. The coupling member socket **136** may be sized and configured such that it provides little or no resistance to insertion of the shaft portion **74**. Because the tabs **162** are free to deflect outwardly, the frictional drag applied to the shaft **60** by the contacting interlock ribs **170** is reduced. The sealing rib **154** only needs to provide sufficient radial load and contact surface against the shaft portion **74** to form a fluid-tight (*e.g.*, air-tight, liquid-tight, gas-tight) seal, and can therefore be configured to provide relatively low drag on insertion. The distal shaft portion **74** can itself be configured (*e.g.*, by frustoconically tapering in the distal direction) to provide reduced insertion drag. Because only a low insertion force is required, the size and mass of moving mechanisms (*e.g.*, robotic arms that move the pipettor shaft **60**) can be significantly reduced.

[0086] The sealing rib **154** can eliminate the need to provide a supplemental O-ring on the pipettor shaft **60** to effect a fluid-tight seal with the pipette tip **100**. In some embodiments, the sealing rib **154** forms a gas - or vacuum-tight, hermetic seal about the shaft **60**. In some embodiments, the seal between the sealing rib **154** and the shaft **60** is adapted to withstand at least 5 psi without leakage.

[0087] While an interlock shaft groove **70** and interlock ribs **170** have been shown and described herein, other combinations and configurations of interlock features may be employed. For example, the pipettor shaft **60** may be provided with one or more interlock ribs and the tabs **162** may be provided with cooperating interlock grooves. In this case, the integral interlock rib on the pipettor shaft **60** may be annular and endless. By way of further

example, the shaft and the tabs may both be provided with one or more interlock ribs and one or more interlock grooves.

[0088] Pipette tips and pipetting systems as disclosed herein may be used with liquid displacement technology or gas or air displacement technology. In liquid displacement technology, liquid is moved through the pipettor shaft **60** (*e.g.*, to or toward a syringe or other pump). In gas displacement technology, the syringe or other pump is used only to create a negative or positive pressure and aspirated liquid stays only in the lower portion of the pipette tip (*i.e.*, the body portion **120**) and never contacts the pipettor shaft **60** and the seal of the pipette tip **100**. The gas displacement technique is commonly used to prevent cross-contamination of the liquids.

[0089] Many alterations and modifications may be made by those having ordinary skill in the art, given the benefit of present disclosure, without departing from the spirit and scope of the technology. Therefore, it must be understood that the illustrated embodiments have been set forth only for the purposes of example, and that it should not be taken as limiting the technology as defined by the following claims. The following claims, therefore, are to be read to include not only the combination of elements which are literally set forth but all equivalent elements for performing substantially the same function in substantially the same way to obtain substantially the same result. The claims are thus to be understood to include what is specifically illustrated and described above, what is conceptually equivalent, and also what incorporates the essential idea of the technology.

WHAT IS CLAIMED:

1. A pipette tip for use with a pipettor including a pipettor shaft having a terminal end, the pipette tip having opposed proximal and distal ends and comprising:
 - a tubular body extending between the proximal and distal ends, the tubular body defining a fluid passage terminating at a proximal opening adjacent the proximal end and a distal opening adjacent the distal end; and
 - a coupling portion on the proximal end, the coupling portion including an interlock feature configured to mechanically interlock with the pipettor shaft proximate the terminal end to selectively and releasably secure the pipette tip to the pipettor shaft.
2. The pipette tip of Claim 1 wherein the interlock feature includes a circumferentially extending rib or groove configured to interlock with a cooperating groove or rib on the pipettor shaft.
3. The pipette tip of Claim 2 wherein the interlock feature includes a circumferentially extending rib configured to interlock with a cooperating annular groove on the pipettor shaft.
4. The pipette tip of Claim 1 wherein:
 - the body and the coupling portion are formed of different materials; and
 - the material of the coupling portion is less stiff than the material of the body.
5. The pipette tip of Claim 4 wherein:
 - the durometer of the material of the body is at least 60 Shore D; and
 - the durometer of the material of the coupling portion is less than 70 Shore A.
6. The pipette tip of Claim 4 wherein:
 - the material of the body includes polypropylene; and
 - the material of the coupling portion includes a thermoplastic elastomer.

7. The pipette tip of Claim 1 wherein the coupling portion includes a stop shoulder configured to engage the terminal end and thereby limit insertion of the pipettor shaft into the coupling portion.
8. The pipette tip of Claim 1 wherein:
the coupling portion includes an integral, annular sealing rib on an inner diameter; and
the sealing rib is adapted to form a fluid-tight seal with an outer diameter of the pipettor shaft when the pipettor shaft is inserted into the coupling portion and interlocked with the interlock feature.
9. The pipette tip of Claim 8 wherein:
the coupling portion includes a plurality of integral, circumferentially distributed coupling tabs;
the coupling tabs are configured to be radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion; and
the interlock feature is located on at least one of the coupling tabs.
10. The pipette tip of Claim 8 wherein the fluid-tight seal is gas-tight up to at least 5 psi.
11. The pipette tip of Claim 8 wherein:
the body and the sealing rib are formed of different materials; and
the material of the sealing rib is less stiff than the material of the body.
12. The pipette tip of Claim 1 wherein:
the coupling portion includes a plurality of integral, circumferentially distributed coupling tabs;
the coupling tabs are configured to be radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion; and
the interlock feature is located on at least one of the coupling tabs.

13. The pipette tip of Claim 12 wherein the interlock feature includes a circumferentially extending rib or groove configured to interlock with a cooperating groove or rib on the pipettor shaft.

14. The pipette tip of Claim 13 wherein the interlock feature includes a circumferentially extending rib configured to interlock with a cooperating annular groove on the pipettor shaft.

15. The pipette tip of Claim 12 wherein:
the body and the coupling tabs are formed of different materials; and
the material of the coupling tabs is less stiff than the material of the body.

16. The pipette tip of Claim 15 wherein:
the interlock feature includes a circumferentially extending rib or groove configured to interlock with a cooperating groove or rib on the pipettor shaft;
the coupling portion includes a stop shoulder configured to engage the terminal end and thereby limit insertion of the pipettor shaft into the coupling portion;
the coupling portion includes an integral, annular sealing rib on an inner diameter;
the sealing rib is adapted to form a fluid-tight seal with an outer diameter of the pipettor shaft when the pipettor shaft is inserted into the coupling portion and interlocked with the interlock feature;
the body and the sealing rib are formed of different materials; and
the material of the sealing rib is less stiff than the material of the body.

17. A method for mounting a pipette tip on a pipettor shaft having a terminal end, the method comprising:
providing a pipette tip having opposed proximal and distal ends, the pipette tip including:

a tubular body extending between the proximal and distal ends, the tubular body defining a fluid passage terminating at a proximal opening adjacent the proximal end and a distal opening adjacent the distal end; and
a coupling portion on the proximal end, the coupling portion including an interlock feature configured to mechanically interlock with the pipettor

shaft proximate the terminal end to selectively and releasably secure the pipette tip to the pipettor shaft; and

inserting the terminal end of the pipettor shaft into the coupling portion to mechanically interlock the interlock feature with the pipettor shaft proximate the terminal end and thereby releasably secure the pipette tip to the pipettor shaft.

18. The method of Claim 17 wherein:
the interlock feature includes a circumferentially extending rib or groove; and
the circumferentially extending rib or groove interlocks with a cooperating groove or rib on the pipettor shaft when the terminal end of the pipettor shaft is inserted into the coupling portion.

19. The method of Claim 18 wherein the interlock feature includes a circumferentially extending rib configured to interlock with a cooperating annular groove on the pipettor shaft.

20. The method of Claim 17 wherein:
the body and the coupling portion are formed of different materials; and
the material of the coupling portion is less stiff than the material of the body.

21. The method of Claim 20 wherein:
the durometer of the material of the body is at least 60 Shore D; and
the durometer of the material of the coupling portion is less than 70 Shore A.

22. The method of Claim 20 wherein:
the material of the body includes polypropylene; and
the material of the coupling portion includes a thermoplastic elastomer.

23. The method of Claim 17 wherein the coupling portion includes a stop shoulder that engages the terminal end and thereby limits insertion of the pipettor shaft into the coupling portion when the terminal end of the pipettor shaft is inserted into the coupling portion.

24. The method of Claim 17 wherein:

the coupling portion includes an integral, annular sealing rib on an inner diameter; and

the sealing rib forms a fluid-tight seal with an outer diameter of the pipettor shaft when the pipettor shaft is inserted into the coupling portion and interlocked with the interlock feature.

25. The method of Claim 24 wherein:

the coupling portion includes a plurality of integral, circumferentially distributed coupling tabs;

the coupling tabs are radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion; and

the interlock feature is located on at least one of the coupling tabs.

26. The method of Claim 24 wherein the fluid-tight seal is gas-tight up to at least 5 psi.

27. The method of Claim 24 wherein:

the body and the sealing rib are formed of different materials; and

the material of the sealing rib is less stiff than the material of the body.

28. The method of Claim 17 wherein:

the coupling portion includes a plurality of integral, circumferentially distributed coupling tabs;

the coupling tabs are radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion; and

the interlock feature is located on at least one of the coupling tabs.

29. The method of Claim 28 wherein:

the interlock feature includes a circumferentially extending rib or groove; and

the circumferentially extending rib or groove interlocks with a cooperating groove or rib on the pipettor shaft when the terminal end of the pipettor shaft is inserted into the coupling portion.

30. The method of Claim 29 wherein the interlock feature includes a circumferentially extending rib configured to interlock with a cooperating annular groove on the pipettor shaft.

31. The method of Claim 28 wherein:
the body and the coupling tabs are formed of different materials; and
the material of the coupling tabs is less stiff than the material of the body.

32. The method of Claim 31 wherein:
the interlock feature includes a circumferentially extending rib or groove;
the circumferentially extending rib or groove interlocks with a cooperating groove or rib on the pipettor shaft when the terminal end of the pipettor shaft is inserted into the coupling portion;
the coupling portion includes a stop shoulder that engages the terminal end and thereby limits insertion of the pipettor shaft into the coupling portion when the terminal end of the pipettor shaft is inserted into the coupling portion;
the coupling portion includes an integral, annular sealing rib on an inner diameter;
the sealing rib forms a fluid-tight seal with an outer diameter of the pipettor shaft when the pipettor shaft is inserted into the coupling portion and interlocked with the interlock feature;
the body and the sealing rib are formed of different materials; and
the material of the sealing rib is less stiff than the material of the body.

33. A pipetting system comprising:
a pipettor including a pipettor shaft having a terminal end; and
a pipette tip having opposed proximal and distal ends and including:
a tubular body extending between the proximal and distal ends, the tubular body defining a fluid passage terminating at a proximal opening adjacent the proximal end and a distal opening adjacent the distal end; and
a coupling portion on the proximal end, the coupling portion including an interlock feature configured to mechanically interlock with the pipettor shaft proximate the terminal end to selectively and releasably secure the pipette tip to the pipettor shaft.

34. The pipetting system of Claim 33 wherein the interlock feature includes a circumferentially extending rib or groove configured to interlock with a cooperating groove or rib on the pipettor shaft.

35. The pipetting system of Claim 34 wherein the interlock feature includes a circumferentially extending rib configured to interlock with a cooperating annular groove on the pipettor shaft.

36. The pipetting system of Claim 33 wherein:
the body and the coupling portion are formed of different materials; and
the material of the coupling portion is less stiff than the material of the body.

37. The pipetting system of Claim 36 wherein:
the durometer of the material of the body is at least 60 Shore D; and
the durometer of the material of the coupling portion is less than 70 Shore A.

38. The pipetting system of Claim 36 wherein:
the material of the body includes polypropylene; and
the material of the coupling portion includes a thermoplastic elastomer.

39. The pipetting system of Claim 33 wherein the coupling portion includes a stop shoulder configured to engage the terminal end and thereby limit insertion of the pipettor shaft into the coupling portion.

40. The pipetting system of Claim 33 wherein:
the coupling portion includes an integral, annular sealing rib on an inner diameter; and
the sealing rib is adapted to form a fluid-tight seal with an outer diameter of the pipettor shaft when the pipettor shaft is inserted into the coupling portion and interlocked with the interlock feature.

41. The pipetting system of Claim 40 wherein:

the coupling portion includes a plurality of integral, circumferentially distributed coupling tabs;

the coupling tabs are configured to be radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion; and
the interlock feature is located on at least one of the coupling tabs.

42. The pipetting system of Claim 40 wherein the fluid-tight seal is gas-tight up to at least 5 psi.

43. The pipetting system of Claim 40 wherein:
the body and the sealing rib are formed of different materials; and
the material of the sealing rib is less stiff than the material of the body.

44. The pipetting system of Claim 33 wherein:
the coupling portion includes a plurality of integral, circumferentially distributed coupling tabs;
the coupling tabs are configured to be radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion; and
the interlock feature is located on at least one of the coupling tabs.

45. The pipetting system of Claim 44 wherein the interlock feature includes a circumferentially extending rib or groove configured to interlock with a cooperating groove or rib on the pipettor shaft.

46. The pipetting system of Claim 45 wherein the interlock feature includes a circumferentially extending rib configured to interlock with a cooperating annular groove on the pipettor shaft.

47. The pipetting system of Claim 44 wherein:
the body and the coupling tabs are formed of different materials; and
the material of the coupling tabs is less stiff than the material of the body.

48. The pipetting system of Claim 47 wherein:

the interlock feature includes a circumferentially extending rib or groove configured to interlock with a cooperating groove or rib on the pipettor shaft;

the coupling portion includes a stop shoulder configured to engage the terminal end and thereby limit insertion of the pipettor shaft into the coupling portion;

the coupling portion includes an integral, annular sealing rib on an inner diameter;

the sealing rib is adapted to form a fluid-tight seal with an outer diameter of the pipettor shaft when the pipettor shaft is inserted into the coupling portion and interlocked with the interlock feature;

the body and the sealing rib are formed of different materials; and

the material of the sealing rib is less stiff than the material of the body.

49. A pipette tip for use with a pipettor including a pipettor shaft having a terminal end, the pipette tip having opposed proximal and distal ends and comprising:

a tubular body extending between the proximal and distal ends, the tubular body defining a fluid passage terminating at a proximal opening adjacent the proximal end and a distal opening adjacent the distal end; and

a coupling portion on the proximal end and configured to selectively and releasably secure the pipette tip to the pipettor shaft, the coupling portion including a plurality of integral, circumferentially distributed coupling tabs configured to be radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion.

50. A method for mounting a pipette tip on a pipettor shaft having a terminal end, the method comprising:

providing a pipette tip having opposed proximal and distal ends, the pipette tip including:

a tubular body extending between the proximal and distal ends, the tubular body defining a fluid passage terminating at a proximal opening adjacent the proximal end and a distal opening adjacent the distal end; and

a coupling portion on the proximal end and configured to selectively and releasably secure the pipette tip to the pipettor shaft, the coupling portion including a plurality of integral, circumferentially distributed coupling tabs

configured to be radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion; and
inserting the terminal end of the pipettor shaft into the coupling portion to thereby releasably secure the pipette tip to the pipettor shaft.

51. A pipetting system comprising:
a pipettor including a pipettor shaft having a terminal end; and
a pipette tip having opposed proximal and distal ends and including:
a tubular body extending between the proximal and distal ends, the tubular body defining a fluid passage terminating at a proximal opening adjacent the proximal end and a distal opening adjacent the distal end; and
a coupling portion on the proximal end and configured to selectively and releasably secure the pipette tip to the pipettor shaft, the coupling portion including a plurality of integral, circumferentially distributed coupling tabs configured to be radially outwardly displaced by the pipettor shaft when the pipettor shaft is inserted into the coupling portion.