

INTERNATIONAL APPLICATION PUBLISHED UNDER THE INTERNATIONAL PATENT
COOPERATION TREATY (PCT)

(51) International Patent Classification⁶: **H05K 9/00, F16J 15/14**
A1

(11) International publication number: **WO 99/40769**

(43) International publication date: Aug. 12, 1999 (8/12/99)

(21) International file number: PCT/DE 98/03167

(22) International application date: Oct. 24, 1998 (10/24/98)

(30) Priority data:
198 04861.0 February 9, 1998 (2/9/98) DE

(71) (72) Applicant and inventor: KAHL, Helmut [DE/DE]; Horstwalder Strasse 23, D-12307 Berlin (DE). TIBURTIUS, Bernd [DE/DE]; Rosenhag 10, D-14532 Kleinmachnow (DE).

(74) Attorney: CHRISTIANSEN, Henning; Pacelliallee 43/45, D-14195 Berlin (DE).

(81) Designated states: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO PATENT (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), EURASIAN Patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), EUROPEAN Patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI Patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: **HOUSING**

(57) Abstract: [Translated from the German with a few changes from the English published.]

A housing (3), especially for the electromagnetically shielded location of electronic components, with a first and second housing part (1, 2) and a sealing profile (8) arranged between the first and second housing parts and sealing off the inner space of the housing, made of an elastically hardened sealing material (7) consisting of the substance applied in an initial pasty state or foamed from an initial liquid state and tightly adhered to the housing, whereby the first housing part has a defined receiving area (9), especially a recess, for the locating of a part of the sealing material applied thereto in the area of an initial, final or bifurcation point of the sealing profile embodied with a raised cross section in relation to the rest of the longitudinal extension of the sealing profile.