SG 9700579-7

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H04L 27/00, G08G 1/23 — A1

(11) International Publication Number: WO 96/05678

(43) International Publication Date: 22 February 1996 (22.02.96)

(21) International Application Number: PCT/US95/10170

(22) International Filing Date: 10 August 1995 (10.08.95)

(30) Priority Data: 08/288,040 — 10 August 1994 (10.08.94) — US

(71) Applicant: THE MITRE CORPORATION [US/US]; 202 Burlington Road, Bedford, MA 01730-1420 (US).

(72) Inventors: ERNST, Darrell, E.; 8720 Chipita Park Road, Chipita Park, CO 80809 (US). MCMILLAN, Donald, R.; 6220 Moorfield Avenue, Colorado Springs, CO 80919 (US). FOLK, Thomas, L.; 618 Southern Cross Drive, Colorado Springs, CO 80906 (US). ROGERS, Steven, R.; 5510 Broadmore Bluffs Drive, Colorado Springs, CO 80906 (US).

(74) Agents: HUNT, Ross, F., Jr. et al.; Larson and Taylor, 727 23rd Street, South, Arlington, VA 22202 (US).

(81) Designated States: CA, FI, JP, KR, MX, NO, SG, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.


Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

RTMP copy

(54) Title: LOCATION BASED SELECTIVE DISTRIBUTION OF GENERALLY BROADCAST INFORMATION

(57) Abstract

A system for determining whether information broadcast by a general transmitter is relevant to a particular user based on the location, velocity and/or time of an object of interest includes a remote terminal (110), a general broadcasting unit (200), a transmitter (190) at the general broadcasting unit for broadcasting messages including a segment comprising a region, a velocity and/or a time corresponding to an event, as well as an event specific tag, and storage (130) for storing selection criteria including current position, time and/or velocity information of the use and/or manually entered data of interest. The selection criteria may also include event specific tags. The receiver (120) at the remote terminal (110) receives the messages from the transmitter (190) at the general broadcasting unit (200). A navigational receiver (121) may also be used to acquire navigational information from an appropriate external source. A matching processor (140) at the remote terminal (110) evaluates the segment in the messages, determines if the segment sufficiently matched the stored election criteria and outputs a match signal. A processor (150) in the remote unit (110) receives the match signal, and processes and disseminates the message in accordance with the match signal.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo			SE	Sweden
CH	Switzerland	KR	Republic of Korea	SI	Slovenia
CI	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovakia
CM	Cameroon	LI	Liechtenstein	SN	Senegal
CN	China	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
CZ	Czech Republic	LV	Latvia	TJ	Tajikistan
DE	Germany	MC	Monaco	TT	Trinidad and Tobago
DK	Denmark	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	US	United States of America
FI	Finland	ML	Mali	UZ	Uzbekistan
FR	France	MN	Mongolia	VN	Viet Nam
GA	Gabon				

9700579-7

LOCATION BASED SELECTIVE DISTRIBUTION OF GENERALLY BROADCAST INFORMATION

Background of the Invention

Currently, region-specific information is disseminated by predetermined point-to-point communication or by general broadcast which must be manually monitored in order to extract information peculiar to a position, velocity and time of interest. For example, marine weather data is continuously broadcast. However, mariners must monitor the broadcast for long periods of time in order to obtain the information peculiar to their region. Even then, the exact region affected may require computation or may be ambiguously defined. There is also the possibility that the user may miss information of interest because he or she occupies an unknown location, is unfamiliar with the region, or uses a different frame of reference, among other reasons.

Another example is tactical ballistic missile (TBM) warning, which is derived from space and ground based sensor data, and is provided through a variety of broadcast and general purpose communications systems to a small subset of in-theater forces. Currently, such warning requires transportable processing stations that can generate information about specific situations in the field but cannot

directly communicate with all individuals affected. The timeliness, reliability, and dispersion of information under these conditions are of concern. Because warning is in the form of geographical coordinates and time of predicted impact, users must interpret the data to determine if the warning affects them.

Some current commercial systems are using GPS information to select relevant data from computer based files such as appropriate electronically stored maps for use in automobiles. These are useful for relatively static information but fail to address dynamic environmental or combat factors.

U.S. Patent No. 5,243,652 to Teare et al. discloses a database access system in which each mobile user has a positioning system which transmits position information to a central facility. This central facility then grants or denies database access depending on the geographical location of the mobile user.

U.S. Patent No. 4,860,352 to Laurance et al. discloses a system in which a satellite system determines the position of a transmitter at a first location and a receiver at a second location. The transmitter position is appended to the received message which is sent by the satellite system to the

receiver. The receiver receives the appended message, extracts the transmitter position data and compares the extracted transmitter position with a stored transmitter position. If the positions correlate, the receiver knows it has received an authentic message.

None of these devices allow for automated receiver discrimination of any message broadcast generally in order to only disseminate relevant messages.

Summary of the Invention

It is therefore an object of the present invention to provide a system which is capable of determining whether information broadcast by a general (whether global, regional or local) transmitter is relevant to a particular user based on the location, velocity and/or position of an object of interest.

In accordance with the present invention, these and other objects are achieved by providing a communication system including a remote terminal, a general broadcasting unit, a transmitter at the general broadcasting unit for broadcasting messages including a segment comprising a region, a velocity and/or a time, a receiver at the remote terminal for receiving messages from the transmitter, and a storage for storing data selection criteria. A navigational

receiver may receive current position, velocity, and/or time information for that remote terminal to be stored as data selection criteria. Data selection criteria may also be manually entered into the storage. The segment may further include an event specific tag. Event specific tags may be stored in the storage in response to manual input and/or be predetermined and stored in the matching processor. A matching processor at the remote terminal evaluates the segment in the messages, determines if the stored data selection criteria satisfies a match condition to the segment, and outputs a match signal. A message processor in the remote unit receives the match signal, and, when the match signal indicates it is appropriate for the remote unit to receive the message, processes and disseminates the message in accordance with the match signal.

Other objects, features and advantages of the invention will be apparent from the following description of the preferred embodiments.

Brief Description of the Drawing

The invention will be described below in further detail with reference to the accompanying drawings wherein Fig. 1 is a block diagram of a system according to the present invention.

Detailed Description of the Invention

The present invention is directed to a system which determines whether access to particular information transmitted by a broadcaster is appropriate for a particular unit remote from the broadcaster. The invention is particularly useful for implementing an addressing distribution system of situation awareness information. The present invention can use satellite provided services, such as the Global Positioning System (GPS), to acquire data and establish user relevance based on current location in real time.

Situation awareness encompasses timely understanding of factors within the operational environment which might affect the manner in which the user proceeds. Some specific examples of functions that could be supported are: 1) warning user of impending tactical ballistic missile (TBM) attack, 2) informing combatant of local friend/foe unit positions, 3) advising user on occurrence of Nuclear/ Biological/Chemical (NBC) events, 4) disseminating terrestrial conditions such as impassable mud, flood, fire or snowpack, 5) alerting police unit of nearby robbery in progress, 6) advising users (e.g., mariners) of severe weather conditions, 7) providing pilots with airport information, and 8) supplying

motorists with information such as location of other vehicles in motion, accidents, areas under repair or blocked, etc. Information might also include appropriate situation-specific actions the user might take.

This capability can be implemented on any hardware platform that interfaces with a global positioning or navigation system or other positioning/navigational inputs, and provides world-wide communications connectivity with the sources of the situation alert bulletins. Remote units that receive, process, and display or operate on the situation awareness information can be mobile, transportable, or stationary.

The system of the present invention is shown in Figure 1. The navigational system 100 may be, for example, Loran or GPS, or any other source of navigational information, e.g., position, velocity or time. The present invention may operate with either periodic or continuous information delivery systems.

The general broadcaster 200 may include an event detection unit 160 which detects an event. Examples of events to be detected with a suitable detection unit 160 include weather, enemy activity, criminal activity. Detection unit 160 may detect the event directly itself or may receive a detection signal from

an external source. Once detection unit 160 detects an event, it outputs information to an event processing and message generation unit 170. Message unit 170 outputs a message generated in response to the event detection output of detection unit 160 to a segment generation and incorporation unit 180. Incorporation unit 180 then defines a position, a velocity and a time of effectiveness for a particular message based, e.g., on a projected history of the event, and incorporates this information as a segment in the message. For time critical applications, the time of effectiveness may be set to the same universal clock unit used in positioning system 100. The segment may also advantageously include an event specific tag which indicates the type of event detected. This segment may be, for example, a header or a footer on the message. The message containing the segment is then transmitted by a transmitter 190.

The remote unit 110 includes a navigational receiver 121 for receiving various information including navigational information from navigating system 100. A storage unit 130 stores position, velocity and/or time information acquired from navigating system 100 by navigational receiver 121 and/or other selection criteria inputs from manual input unit 125. The selection criteria input may

include other positions, velocities and/or times to increase the amount of information disseminated, as well as event specific tags to customize and reduce the amount of information disseminated. This information provides the basis for defining matching conditions of interest to the user of remote unit 110. It will be appreciated that there may be a plurality of remote units 110, all receiving information from positioning system 100 and broadcaster 200.

Receiver 120 receives messages transmitted by broadcaster 200. It should be noted that for some applications, the navigation system 100 may serve as the general broadcaster. In this case, the navigational receiver 121 serves as the message receiver. Receiver 120 then outputs this message to a matching processor 140. Matching processor 140 compares the information contained in the segment of the message to the information stored in storage 130. If the stored position, velocity and/or time information are within matching conditions of the position, velocity and/or time information for the segment of the transmitted message, then the message processing and dissemination unit 150 will process and disseminate the information in the message. The matching conditions typically consist of an appropriate position and time window such that exact

correlation is not required. Further, information at other regions of interest may be processed by storing additional times, velocities and/or positions, e.g., time, velocity and/or position information based on a projected trajectory of remote unit 110 or based on other remote unit of interest. Additionally, matching processor 140 may compare any event specific tags included in the segment with any event specific tags either stored or matching processor 140 and/or input at criteria selection unit 125 and only allow messages having appropriate event specific tags to be processed and disseminated by unit 150.

Generally, the correlating requirement is a set of user-specified radial distance to the event, whether the user is heading toward or away from an event area, whether the event is past, present, or future relative to the user and the duration of the event. Alternatively, the matching processor 140 could contain the criteria for predefined event types, with appropriate segments, being generated by unit 180 in general broadcaster 200. Specific examples of matching conditions would include whether a combatant was within the circular error probable (CEP) range of an impacting ballistic missile; remote user was within the path of a severe thunderstorm, NBC cloud, flash flood, or forest fire; or the path of the remote user

would intersect any of these events in the near future based on their respective velocities.

Dissemination may include audio, tactile or visual alarm or display, or any combination thereof, in display unit 152 and may be provided to one or more users. Dissemination may also include further processing at the processing unit 150 or at additional processing devices 155.

Although the present invention has been described above relative to exemplary preferred embodiments thereof, it will be understood by those skilled in the art that variations and modifications can be effected in these embodiments without departing from the scope and spirit of the invention as defined in the claims which follow.

THIS SHEET HAS BEEN REPLACED



What Is Claimed Is:

1. A communication system comprising:

a general broadcasting unit comprising

a message generating means for generating a message,

a segment generating means for generating a segment comprising at least one of a region, a velocity and a time, for incorporating said segment into said generated message, and for outputting an incorporated message, said generated message and said generated segment, and

a transmitter broadcasting said incorporated message;

a remote unit comprising

a receiver for receiving said incorporated message from said transmitter at said general broadcasting unit,

a storing means for storing data selection information,

a matching processor for evaluating said segment in said incorporated message, for determining if said data selection information of

said remote terminal satisfies a match condition to said segment, and for outputting a match signal, and

This Sheet Has Been Replaced



THIS SHEET HAS BEEN REPLACED

* C L M S *

a disseminating means, which receives said match signal, for processing and disseminating said message in accordance with said match signal.

2. The system as recited in claim 1, wherein said remote unit is mobile.

3. The system as recited in claim 1, wherein said remote unit is transportable.

4. The system as recited in claim 1, wherein said remote unit is fixed.

5. The system as recited in claim 1, wherein said segment generating means incorporates said segment as a header on said message.

6. The system as recited in claim 1, wherein said data selection information comprises current position, velocity and time information of said remote unit.

7. The system as recited in claim 6, further comprising a navigational information receiver receiving said current position, velocity and time information from a global navigational system.

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

* C L M S *

8. The system as recited in Claim 1, wherein said segment further includes an event specific tag.

9. The system as recited in Claim 8, wherein said matching processor includes predetermined, stored event specific tags.

10. The system as recited in Claim 1, further comprising means for manually entering at least one of position, velocity, time and event specific information into said storing means.

11. The system as recited in claim 1, wherein said disseminating means includes a means for displaying said messages.

12. The system as recited in claim 1, wherein said disseminating means includes an alarm.

13. The system as recited in claim 1, wherein said data selection information comprises position, velocity and time information of objects of interest remote from said remote unit.

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

14. The system as recited in claim 1, wherein said data selection information comprises a location remote from said remote unit.



15. The system as recited in claim 1, wherein said message generating means further comprises a detecting means for detecting an event and generating a message in response to said event.

16. A method of providing selection at a remote unit of generally broadcast messages from a broadcaster, comprising the steps of:

transmitting from said broadcaster a message including a segment comprising at least one of a position, a velocity, and a time;

storing data selection criteria at said remote unit;

receiving at said remote unit said transmitted messages;

comparing said segment in said transmitted message to said stored data selection criteria;

determining from said comparing step the occurrence of a match condition; and

disseminating said message at said remote unit upon occurrence of said match condition.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN REPLACED

17. The method as recited in claim 16, wherein said disseminating step includes displaying said messages.



18. The method as recited in claim 16, wherein said disseminating step includes activating an aural alarm.

19. The method as recited in claim 16, wherein said disseminating step includes activating a tactile alarm.

20. The method as recited in claim 16, wherein said disseminating step includes activating a visual alarm.

21. The method as recited in claim 16, wherein said disseminating step includes activating another device.

22. The method as recited in claim 16, which, prior to said transmitting step, further comprises the steps of:

detecting an event;

generating an event message in response to said event;

This Sheet Has Been Replaced



THIS SHEET HAS BEEN REPLACED

generating a segment defining at least one of a region, a velocity and a time; and

incorporating said segment into said event message to form said message.



23. The method as recited in claim 16, wherein said storing data selection criteria step comprises manually entering at least one of position, velocity, time and event specific information.


24. The method as recited in claim 16, wherein said storing data selection criteria step comprises receiving current position, velocity and time information of said remote unit.

25. The method as recited in claim 16, wherein said transmitted messages received at said remote unit when transmitted from more than one broadcaster.

26. The method as recited in claim 16, wherein said storing step comprises a plurality of data selection criteria and said comparing step comprises comparing said segment of said plurality of data selection criteria.

This Sheet Has Been Replaced




NAVIGATIONAL SYSTEM
100
NAV. REC.
121
MESSAGE RECEIVER
120
CRITERIA SELECTION UNIT
125
STORAGE
130
140
MATCHING PROCESSOR
150
MESSAGE PROCESSING AND DISSEMINATION
155
ADDITIONAL PROCESSORS
152
DISPLAY
REMOTE UNIT
110
EVENT DETECTION
160
EVENT PROCESSING AND MESSAGE GENERATION
170
SEGMENT GENERATION AND INCORPORATION
180
TRANSMITTER
190
GENERAL BROADCASTER
200

PATENT COOPERATION TREAT

REC'D 15 NOV 1996
WIPO PCT

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70) SG 9700579-7

Applicant's or agent's file reference VII/P1196W0	FOR FURTHER ACTION	See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)
International application No. PCT/US95/10170	International filing date *(day/month/year)* 10 AUGUST 1995	Priority date *(day/month/year)* 10 AUGUST 1994
International Patent Classification (IPC) or national classification and IPC IPC(6): H04L 27/00, G08G 1/23 and US Cl.: 375/259; 340/993		
Applicant THE MITRE CORPORATION		

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.

2. This REPORT consists of a total of 4 sheets.

☒ This report is also accompanied by ANNEXES, i.e., sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority. (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consist of a total of 5 sheets.

3. This report contains indications relating to the following items:

- I [X] Basis of the report
- II [ ] Priority
- III [ ] Non-establishment of report with regard to novelty, inventive step or industrial applicability
- IV [ ] Lack of unity of invention
- V [X] Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI [ ] Certain documents cited
- VII [ ] Certain defects in the international application
- VIII [X] Certain observations on the international application

Date of submission of the demand	Date of completion of this report
06 MARCH 1996	25 OCTOBER 1996
Name and mailing address of the IPEA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230	Authorized officer STEVEN CHIN BRIAN A. HARDEN PARALEGAL SPECIALIST GROUP 2400 Telephone No. (703) 305-4714

Form PCT/IPEA/409 (cover sheet) (January 1994)★

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.
PCT/US95/10170

I. Basis of the report

1. This report has been drawn on the basis of *(Substitute sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments)*:

☐ the international application as originally filed.

☒ the description, pages 1-10 , as originally filed.
pages NONE , filed with the demand.
pages NONE , filed with the letter of _____.
pages _____ , filed with the letter of _____.

☒ the claims, Nos. NONE , as originally filed.
Nos. NONE , as amended under Article 19.
Nos. 1-32 , filed with the demand.
Nos. NONE , filed with the letter of _____.
Nos. _____ , filed with the letter of _____.

☒ the drawings, sheets/~~fig~~ 1 , as originally filed.
sheets/~~fig~~ NONE , filed with the demand.
sheets/~~fig~~ NONE , filed with the letter of _____.
sheets/~~fig~~ _____ , filed with the letter of _____.

2. The amendments have resulted in the cancellation of:

☒ the description, pages NONE.

☒ the claims, Nos. NONE.

☒ the drawings, sheets/~~fig~~ NONE.

3. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the ~~Supplemental Box~~ Additional observations below (Rule 70.2(c)).

4. Additional observations, if necessary:

NONE

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. STATEMENT

Novelty (N)	Claims	1-32	YES
	Claims	NONE	NO
Inventive Step (IS)	Claims	1-32	YES
	Claims	NONE	NO
Industrial Applicability (IA)	Claims	1-32	YES
	Claims	NONE	NO

2. CITATIONS AND EXPLANATIONS

Claims 1-32 meet the criteria set out in PCT Article 33(2)-(4), because the prior art does not teach or fairly suggest a communication system comprising: a general broadcasting unit including a message generating means; a segment generating means; a transmitter for broadcasting the outputted message; and a remote unit including a receiver; a special position input means; a storing means; a matching processor and a disseminating means as claimed in claims 1-32.

NEW CITATIONS

NONE

VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

Claims 1,6,13-14,15 are objected to under PCT Rule 66.2(a)(v) as lacking clarity under PCT Article 6 because the claims are indefinite for the following reason(s):

In claim 1 and 15, is the information stored by the storing means related to the event or the remote unit? Also what is the current special position information related to? Is it related to the event or the remote unit?

In claim 6, it seems to imply that the data selection information comprises current position, velocity and time information related to the remote unit, whereas in claim 13 it seems to imply that the data selection information comprises position, velocity and time information related to object of interest remote from remote unit.

In claim 14, the statement that the "data selection information stored by the storing means comprises a location remote from said remote unit" is unclear.

What is claimed is:

1. A communication system comprising:

a general broadcasting unit comprising

a message generating means for generating a generated message related to detection of an event,

a segment generating means for generating an information segment comprising at least one of a region, a velocity and a time relating to said event, and for incorporating said information segment into said generated message to produce an outputted message, and

a transmitter for broadcasting said outputted message;

a remote unit comprising:

a receiver for receiving said outputted message from said transmitter at said general broadcasting unit,

spacial position input means for inputting current spacial position information derived from an external spacial positioning system,

a storing means for storing said spacial position information and for storing data selection information related to information contained in said information segment,

a matching processor connected to said storing means and to said receiver for comparing said information segment in said outputted message with said spacial position information and said data selection information stored in said storing means to determine whether a match condition is satisfied, and for, when a match condition is satisfied, outputting a match signal, and

a disseminating means for, responsive to receiving said match signal, processing and disseminating said message in accordance with said match signal.

2. The system as recited in claim 1 wherein said remote unit is mobile.

3. The system as recited in claim 1, wherein said remote unit is transportable.

REPLACEMENT SHEET
06 MAR 1996

4. The system as recited in claim 1, wherein said remote unit is fixed.

5. The system as recited in claim 1, wherein said segment generating means incorporates said information segment as a header on said message.

6. The system as recited in claim 1, wherein said data selection information comprises current position, velocity and time information relating to said remote unit.

7. The system as recited in claim 6, wherein said spacial position input means comprises a navigational information receiver receiving said current position, velocity and time information from a global navigational system.

8. The system as recited in claim 1, wherein said information segment further includes an event specific tag.

9. The system as recited in Claim 8, wherein said matching processor includes predetermined, stored event specific tags.

10. The system as recited in Claim 1, wherein said remote unit further comprises means for manually entering at least one of position, velocity, time and event specific information into said storing means.

11. The system as recited in claim 1, wherein said disseminating means includes a means for displaying said messages.

12. The system as recited in claim 1, wherein said disseminating means includes an alarm.

13. The system as recited in claim 1, wherein said data selection information stored by said storing means comprises

AMENDED SHEET

REPLACEMENT SHEET
06 MAR 1996

position, velocity and time information relating objects of interest remote from said remote unit.

14. The system as recited in claim 1, wherein said data selection information stored by said storing means comprises a location remote from said remote unit.

15. A method of providing selection at a remote unit of generally broadcast messages from a broadcaster, said method comprising the steps of:

transmitting from said broadcaster a message related to detection of an event, said message including an information segment comprising at least one of a position, a velocity, and a time related to said event;

storing data selection criteria at said remote unit relating to information contained in said information segment;

receiving at said remote unit said transmitted message;

receiving and storing at said unit current spacial position information derived from an external spacial positioning system;

comparing said information segment in said transmitted message with said stored data selection criteria and said current spacial position information;

determining from said comparing step the occurrence of a match condition; and

disseminating said message at said remote unit upon an occurrence of said match condition.

16. The method as recited in claim 15, wherein said disseminating step includes displaying said messages.

17. The method as recited in claim 15, wherein said disseminating step includes activating an aural alarm.

18. The method as recited in claim 15, wherein said disseminating step includes activating an tactile alarm.

AMENDED SHEET

REPLACEMENT SHEET
06 MAR 1996

19. The method as recited in claim 15, wherein said disseminating step includes activating a visual alarm.

20. The method as recited in claim 15, wherein said disseminating step includes activating another device.

21. The method as recited in claim 15, wherein said storing data selection criteria step comprises manually entering at least one of position, velocity, time and event specific information.

22. The method as recited in claim 15, wherein said storing data selection criteria step comprises inputting current position, velocity and time information relating to said remote unit.

23. The method as recited in claim 15, wherein said remote unit receives transmitted messages from more than one broadcaster.

24. The method as recited in claim 15, wherein said storing step comprises storing a plurality of data selection criteria and said comparing step comprises comparing said information segment with said plurality of data selection criteria.

25. A system as claimed in claim 1, wherein said external spacial positioning system comprises the Global Positioning System.

26. A system as claimed in claim 1, wherein said external spacial positioning system comprises LORAN.

27. A system as claimed in claim 1, wherein said information segment comprises a region of influence impacted by said event.

28. A system as claimed in claim 27, wherein said region of influence is changing.

REPLACEMENT SHEET
06 MAR 1996

AMENDED SHEET

PCT/US95/10170
IPEA/US 06 MAR 1996

29. A system as claimed in claim 1 wherein said event is static.

30. A system as claimed in claim 1 wherein said event is moving.

31. A system as claimed in claim 1 wherein said information segment comprises both region and time.

32. A system as claimed in claim 1 wherein said remote unit is mobile and said storage means stores the current velocity of said remote unit.

REPLACEMENT SHEET
06 MAR 1996