



159159

Acoustic element

This invention concerns acoustic elements, as loudspeakers or microphones in particular for lower frequencies. Bass loudspeakers must today in order to achieve a good sound reproduction and strength of sound be large and also frequently become expensive. When the available space is insufficient, as in cars, one simply have to accept that the sound reproduction is afflicted. In view of the above problem there is a great need for improved loudspeakers for lower frequencies. In particular there is a great need for small loudspeaker elements for lower frequencies since in many cases large loudspeakers can not be installed. The object of the invention is therefor to achieve a compact and efficient loudspeaker and microphone respectively that can cope with low frequencies and that can be made small.

In accordance with the invention the above object is solved by the loudspeaker including a wing provided rotor (loudspeaker rotor) that at use is rotated and where the pitch of the wings is modulated in unison with the tone or sound or sound pressure that is to be achieved. By alternately adjust the wings for pushing the air (positive compression) towards the listener and in the opposite direction respectively (negative compression) from the listener the same compression conditions are achieved as at the vibration of a traditional loudspeaker membrane. With an appropriate control of the pitch of the wings desired air transport and sound pressure respectively can be achieved in every instant. By altering the pitch very slowly extremely low frequency sounds can be generated, even below the audible range. The momentary sound pressure of the sound is thus controlled by means of an electric signal to the loudspeaker rotor for control of the pitch of its wings positive signal - positive pressure and flow and negative signal - negative pressure and flow. The sound level of the generated sound can either be controlled by differently great wing angles or by the speed, this since both measures can influence the sound pressure and the transported amount of air respectively in each sound wave.

One can also conceive that the sound level is controlled as a combination of the inclination of the wings of the loudspeaker rotor and the speed respectively. As is realized the reproduced sound must not necessarily be sine shaped but also sound waves compounded of several tones can be generated with the device in accordance with the invention by controlling the wing angles corresponding to the compound desired shape of the sound pressure curve shape.

If more power is desired several loudspeaker rotors according to the invention can be



G00002

used in parallel alternatively larger loudspeaker rotors may be used. One can also consider to use rotors mounted after each other in order to increase the driving ability, that is the maximally achievable sound pressure. Advantageously one may give the rotors alternating rotation direction and opposed pitch angles in order to decrease turbulence, optimize the airflow and increase efficiency.

By using a rotor with pivotable wings one may instead make a microphone that also may be used for very low tones. By allowing the wings to be freely moveable these may at rotation of the rotor be controlled by the sound inducing airflow back and forth that in a suitable way, for instance optical or electrical way can be detected by a detecting of the angle displacement of the wings.

One can also consider to use the invention in other media than air, for instance water, to generate or detect sound waves or acoustic phenomena.

Further advantages and characteristics of the invention as well as further developments of the invented concept are apparent from the patent claims and the following described embodiment with reference to the enclosed drawings.

Figure 1 shows schematically the relation between wing angle and sound pressure graph.

Figure 2 shows how the wing position is varied with a varying sound pressure as a result.

Figure 3 shows the relation between sound pressure and r.p.m.

Figure 4 shows the relation between sound pressure and frequency at different r.p.m.s

Figure 5 shows schematically a loudspeaker rotor in accordance with the invention that is driven by a motor.

Figure 6 shows wings and compensation weights at force balancing via centrifugal force.

Figure 6.1 shows schematically the compensation weights in the rotor.

Figure 6.2 shows schematically a wing in the rotor.

Figure 6.3 shows schematically a wing pivot axle in the rotor.

Figure 6.4 shows schematically a wing holder in the rotor.

Figure 7 shows the wing forces and the pivoting force that is generated by the centrifugal force.

Figure 8 shows the compensation forces and the pivoting force that is generated by the

centrifugal force.

Figure 9 shows schematically the wing design at force balancing via asymmetric wing design.

Figure 9.1 shows schematically the smaller part of the wing.

5 Figure 9.2 shows schematically the larger part of the wing.

Figure 9.3 shows schematically a wing holder in the rotor.

Figure 10 shows the wing forces and the pivoting force generated by the centrifugal force.

10 Figure 11 shows the compensation forces from wind and the pivot force that is generated by the asymmetric wing design.

Figure 12 shows blade for force linearizing.

Figure 12.5 shows blade with extra wing area for force linearizing.

Figure 13 shows the modulation forces at angled and non angled state for force linearizing.

15 Figure 14 shows a rotor with blades larger than 80%, area subjected to pressure loss is marked.

Figure 15 shows a rotor with blades smaller than 80%.

Figure 16 shows schematically the components modulation rotor, flow brake, cavity and outlet.

20 Figure 16.1 shows modulation rotor component seen from above.

Figure 16.2 shows wings of modulation rotor seen from above.

Figure 16.3 shows modulation rotor component and flow brake seen from the side.

Figure 16.3 shows the outlet to the flow brake seen from below.

25 Figure 17 shows schematically the modulation rotor applied to a flow brake with braking material in the cavity and flow brake in the outlet .

Figure 17.1 shows schematically component modulation rotor.

Figure 17.2 shows schematically the air brake with brake material in the cavity.

Figure 17.3 shows schematically the outlet grid with acoustic brake.

30 Figure 18 shows schematically the modulation rotor applied to a flow brake without braking material in the cavity with flow brake in the outlet.

Figure 18.1 shows schematically the component modulation rotor.

Figure 18.2 shows schematically the air brake without brake material in the cavity.

Figure 18.3 shows schematically the outlet grid with acoustic brake.

Figure 19 shows the rotor component from different angles.

Figure 20 shows the outer wall (tube) form different angles.

Figure 21 shows the rotor mounted in the tube without seals with angled and non angled wings.

Figure 22 shows the rotor mounted in the tube with spherically cut seals with angled and non angled wings.

Figure 23 shows a close up of the rotor mounted in the tube with spherically cut seals.

Figure 24 shows a close up of the rotor mounted in the tube with spherically cut seals and bellow seal.

The loudspeaker shown in figure 5 in accordance with the invention includes a direct driven rotor, that is the rotor is arranged directly on the motor axle of a motor. The loudspeaker rotor has in this example three wings 2, which in their inner ends are pivotable arranged in a hub 3. The wings are pivotable around essentially radial pivot axles 4. The hub 3 is rotated by the motor 1. Each wing in this example has an area corresponding to approximately one third of a circle ring and is in the inner end at a distance from the pivot bearing via an arm 7 connected to a coil axially moveable relative the rotor so that a an axial movement of the coil 5 pivots the wings. The coil 5 is surrounded by a fixed permanent magnet 6 and is fed with electricity against the influence of restraining springs so that it is moved forwards or backwards depending on the direction of electrical current. Advantageously the pivot axles of the wings are situated slightly in front of the pressure center (approximately the center of gravity of the wing area) so that the wings moves towards a center position without driving of the air when the coil is not fed with electric current. At the same time the required forces for the pivoting of the wings around the pivot axles of these become very small. This condition can either be used for sound amplifying alternatively to compensate a possible weak coupling, caused by the construction, between magnets and coil in the wing manoeuvring.

For the generation of sound an electrical signal is applied to the coil that owing to this swing back and forth. The movement is via the arms linked to the wings at which the wing angle is altered in a corresponding way. Energy for the moving of air forth and back, that is the sound generation is supplied by the motor driving the loudspeaker rotor. As a consequence of this the loudspeaker element according to the invention will function as a

power amplifier.

With decreasing sound frequency the number of revolutions that the loud speaker rotor rotates during a sound wave length will increase which increases the transported amount of air and thus the sound pressure can be retained at low frequencies differing from the case at ordinary loudspeakers. The device according to the invention can principally generate sounds of arbitrary low frequency. For sound waves with higher frequency the wings of the loudspeaker rotor should not be too heavy. One can therefore consider to use many smaller wings as in a turbine or to fabricate comparatively small loudspeakers that when more power is needed can be put together in panels. Furthermore the loudspeaker element in accordance with the invention can be arranged together with loudspeaker elements of conventional type in order to achieve a sufficient frequency range. Within the frame of the inventive thought the manoeuvring of the loudspeaker rotor can be designed in different ways as to the journaling of the wings.

The manoeuvring can be electromagnetic with one or several magnets fixed to the wings or these may be magnetic in themselves in order to be influenced by a fixed coil. Alternatively a coil arranged in the rotor may mechanically influence the wings when the current through the coil is altered and this is located in a fixed magnetic field generated by a fixed permanent magnet. Each wing may be provided with one or several coils as alternative. One may also consider to control the wings via a piston or coil placed in the center of the rotor where the inner part of the wing has a mechanical coupling to the piston or coil. Also the fastening of the wings and journaling thereof can be achieved in different ways and one can for instance consider the loudspeaker rotor being made of thin iron panel that has been punched, embossed and magnetized, and surrounded by one or several fixed coils. Within the concept of the invention one can also consider to use other physical phenomena to achieve the required pivoting/bending of the wings of the rotor, as for instance piezoelectric elements.

The loudspeaker rotor need not necessarily be flat or propeller like as above but one can also consider to use a drumlike device with blades adjustable to their angles.

The loudspeaker rotor in accordance with the invention is in much similar to a fan why one can further consider using it for the transportation of air for ventilation purposes. This can be done by instead of varying the pitch of the wings giving these a constant pitch (for the time that ventilation is desired). The loudspeaker rotor then only serves as a fan. If one

instead choose to allow the pitch to vary with intended sound signals, but not around the center position where the rotor does not transport any air but around a position with a certain pitch fan and loudspeaker function is obtained at the same time.

5 The loud speaker element in accordance with the invention can also be arranged in a ventilation outlet by journaling the wings freely moveable with the journaling axle somewhat in front of the pressure center, and with electromagnetic pitch control. This can for instance be done by providing the wings at their outer edges with magnets with circumferential extension. Outside a coil is placed around loud speaker rotor. With an increasing amount of air that is pushed through the loudspeaker rotor by the ventilation system the wings of the rotor will deflect from their middle position, the electromechanically enforced additional angling of the wings will oscillate around the ventilation angling so that the sound is generated independent of the ventilation. By the integration with the ventilation system automatically a discrete mounting is obtained and large parts corresponding to loudspeaker boxes (in the shape of the air conduits) which reduces the distortion of the sound. In particular in cars this may mean a considerable improvement of the sound quality.

10 In the above described embodiment the motor is coupled directly to the loud speaker rotor, but if so desired one can also consider belt drive. Either with one rotor per motor or several rotors that are in common driven by one motor. Also several loudspeakers rotors may be arranged on one and the same axle to increase the acoustic driveability. The wing pitch may in a corresponding way be controlled in common or individually for several rotors. The loud speaker rotors may further be driven by power net connected motors while the wing angle is controlled by signals from sound amplifiers. At this the need for powerful amplifiers as well as thick and low-ohmic connections between amplifier and bass loudspeakers is reduced.

20 Since loudspeakers in accordance with the invention can let through an air flow the wind resistance at outdoor locations is reduced, this counteracts the pressure variations that otherwise arise. A more natural sound with better sound quality can therefore be achieved outdoors.

25 In addition to generate audible sound loudspeakers in accordance with the invention be used to generate infrasounds. In this way it becomes possible to annihilate existing infrasounds which has previously been a problem especially in view of infrasound being able to result in nausea, headache and cause drivers to fall asleep.

If no force is fed to the wings for the pivoting of these when the rotor is rotated the wings alter their inclination according to the flow so that the resistance become as small as possible and one can by recording the varying pitch of the wings for instance by connecting the coil to a measuring instrument alternatively optically register the wing pitch so that a "loudspeaker rotor" instead may function as a microphone in particular for low frequencies even if a superimposed constant air flow is present. If sound is to be detected in a constant flow the wings work with a constant pitch corresponding to the constant flow. Around this zero position the wings pivot at the detection of sound or flow variations. The microphone in accordance with invention has the advantage that it already before the detection separates the constant flow component from the varying one which reduces the noise in the measured sound. If so is desired the average flow may be detected by noting the mean pivoting of the wing pitch.

Advantageously the rotor is driven at a constant speed or at least with monitored or controlled rpm since the rotor speed has a large influence on the generated sound amplitude and the instant sound power. One can also consider providing the rotor with a flywheel or a large rotating mass in order to provide a steady constant rotation even if the wing pitch and thereby the braking is changed due to the delivered sound volume. The motor can also be provided with active control where a speed control compensate the speed variations that load variations may generate.

One can also use motors with constant speed or drive the motor with a power addition corresponding to the delivered sound. One can also consider instead to monitor the speed so that the reduction in speed can be compensated with increased wing deflection so that intended sound pressure can be generated.

Since the angle of the wings directly modulate the sound pressure one may advantageously use active feedback to ascertain blade angle. The angle detection can then be implemented with optical/piezoelectrical or electromechanical sensors.

In figure 5 the pivot axles of the wings are arranged unsymmetrically on the wings of the rotor. The rotor rotates clockwise. This result in the pushing force on that half of the wing that is behind the pivoting center is slightly larger than the pressure on the wing part that is in front of the pivot axle half and the wing will thus always generate a counter force against an increased pivoting. This in turn means that the larger pivoting or pitch for the wing that is to be desired the more power must be applied and in this way a linear acoustic

response is obtained from the rotor and the wing pitch can be controlled through force influence (figures 15, 12, 13).

When the wings of the rotor from an entirely flat position is given an increased angle the pivoting of each wing takes place around its own axle. At a rotor with wider wings as for instance the one shown in figure 5 the wing tips will move perpendicularly inward towards the pivot axles of the wings, that is also inward towards the rotational center of the rotor. The wings must thus move against the influence of the centrifugal force that acts on the wings. At high rotor speeds these centrifugal forces may become most considerable and they brake the electrical deflection of the motor wings. This increase the power consumption in an undesired way. In order to remedy this as is shown in figures 6 balance element 6.1 are arranged perpendicularly relative the area 6.2 of the wings. The balance elements have the shape of arms perpendicular to the surface of the blade fastened for instance in the inner ends of the wing axles provided with weights in their outer ends. These weights will as the wing tips move perpendicularly in relation to the pivot axles of the wings. Through the perpendicular arrangement these weights will at a pivoting of the wing move radially outward in relation to the rotor axle. By appropriate dimensioning of the weights it is possible to achieve centrifugal forces (figure 8) that balance the centrifugal forces from the wings (figure 7) efficiently reducing the control forces that otherwise must be delivered to the wings (figures 6, 7, 8).

By designing the wing unsymmetrically (figure 9) and placing the pivot axle of each wing behind the center of pressure seen in the rotational direction also force generated by the unsymmetry (figure 11) may be used to compensate the pivoting generated by the centrifugal force (figure 10). (Figures 9, 10, 11)

In order to prevent air transport between the sides of the rotor at its outer end this is advantageously arranged in a tube or corresponding housing (figure 2). As described above with reference to figure 21 however the outer corners of the wings move inward as the pitch is increased. At the same time the inner corners move outward. This cause leakage between the front and back side of the rotor, which impairs the efficiency of the device. Therefore the rotor blades and the surrounding housing and the rotor hub respectively are designed in the way shown in figure 22. The sealing surface in the house surrounding the rotor is shaped spherical with the center of the spherical surface in the center of the rotor where the pivot axles of the wings intersect the rotor axle. At a pivoting of the wings the circular outer edges

of the wings will then all the time lie close to the inner surface of the housing.

At the inner edges of the wings also the hub of the rotor is made with a rotational symmetric sealing surface and a corresponding shaping of the inner edges of the wings to achieve a sealed condition (figure 23). By also here using a spherical sealing surface on the hub with the center on the rotation axle of the rotor and with a correspondingly curved inner edge of the wing, at which the center of the spherical surface lies on the pivot axle. In this way also the hub in its entirety can be rotationally symmetric. Since there is no mutual rotation at the inner edges but only pivoting the seal may here be established in some other way, for instance with a below like device (figure 24).

(figures 19, 20, 21, 22, 23, 24)

In the figures 17, 18 a loudspeaker is shown comprising a rotating loudspeaker element in accordance with the invention arranged in a box. The loudspeaker box is not entirely closed but via a flow brake or restriction connected to the surrounding. In this way the risk is eliminated of the rotor being subjected to stall, that is that air transport stops entirely despite the rotation of the rotor. By choosing material and openings the resistance against the flow can be adapted so that it becomes frequency dependent so that optimum flow through the rotor is optimized dependent on frequency. In this way generated pressure can be optimized, stall avoided as well as acoustic short circuiting where inhalation of the pressure wave takes place. (figures 16, 17 18)

Since the efficiency of the component largely is ruled by how well the pressure is built up the blades primarily have to be designed for pressure and not for flow. The largest pressure build up takes place where the blade velocity is as largest. Low blade velocity result in leakage at high pressure and reduced efficiency. This means that the blades should have a blade velocity as high as possible for good efficiency in pressure building. Since the blade velocity is low in the center of the rotor this means that leakage will occur if the blades reach all the way in. A solution to this problem is to design smaller blades and allow the kernel to cover the part where the blade velocity is too low. For efficient build up the blades must be less than 80% of the radius of the rotor. In figure 14 a rotor is shown with blades larger than 80%, the area subjected to pressure loss is marked. In figure 15 a rotor is shown with blades smaller than 80%. (Figures 14, 15)

In order to further increase the efficiency at the pressure build up several layers of blades may be designed in the rotor. One can also consider to mount rotors after each other.

Since the rotation generates a rotation phenomena in the modulated media (e.g. air) one may advantageously allow the rotors to rotate in alternating rotational directions since this leads to the rotors being able to use the rotation phenomena occurring in the media (e.g. air).

5 The invention can be used at all types of elements that with a rotating movement can transport air (or liquid), that is also radial fans, tangential fans, turbines et cetera in turbines one may advantageously by integration of the technique use the technique in the turbine steps. In many situations disturbing sound is generated by rotating air transporting elements and by means of the invention one may consider to reduce these either by the arranging of an extra rotor propeller et cetera or by controlling the rotating element that generate the sound, this
10 in particular since these sounds often are continues.

P A T E N T K R A V

1. Loudspeaker element, **characterized in** that it is constituted by a motor driven rotor provided with wings or blades, which wings or blades are adjustable to their pitch
5 (angling/bending of wing), so that transported air volume and achieved air pressure respectively at rotation of the rotor can be modulated corresponding to a desired sound signal.

2. Loudspeaker element in accordance with claim 1, **characterized in** that the pivoting of blades or wings is done electromechanically.

3. Loudspeaker device according to claim 2, **characterized in** that permanent magnets
10 are arranged on or integrated with blades or wings and that a fixed coil or coils, are arranged for the influencing of the magnets for pivoting of wings or blades. Alternatively the wings have integrated coils.

4. Loudspeaker element according to claim 1, **characterized in** that the altering of the pitch of the wings or blades is done by means of piezoelectric effect.

5. Loudspeaker element according to any of the preceding claims, **characterized in** that
15 the pivot axle of each wing or blade extends approximately through the pressure center or slightly in front of this seen in the direction of the rotation.

6. Loudspeaker element according to any of the proceeding claims, **characterized in**
20 that load dependent speed variations caused by signal modulated wing angles is compensated by a flywheel or active speed control.

7. Loudspeaker element according to any of the proceeding claims, **characterized in**
that the wing angle is controlled with active feedback.

8. Loudspeaker element according to claim 1, **characterized in** that it is constituted by
a circular rotor provided with one or several wings.

9. Loudspeaker element according to any of the proceeding claims, **characterized in**
25 that it also can work as a fan by superimposing an essentially constant pitch over the sound generating varying adjustment of the pitch angles of the rotor wings.

10. Method for generating a sound/airflow that can be modulated, **characterized in** that
30 for a rotor provided with adjustable wings or blades the angles of the wings or blades are so adjusted that the degree of pitch (angling/bending of wing), is controlled so that transported air volume and achieved air pressure respectively can be modulated corresponding to a desired sound signal/pressure way.

11. Microphone/flowmeter, **characterized in** that it is constituted by a rotor provided with wings or blades, which wings or blades are detectable as to their pitch so that transported air volume and achieved air pressure can be measured.

5 12. Microphone/flowmeter, according to claim 11, **characterized in** that the sensing of the pivoting of blades and wings is electromechanical.

13. Microphone/flowmeter, according to claim 12, **characterized in** that permanent magnets are arranged on or integrated with blades or wings and that a fixed coil or coils are arranged for measuring of the magnets for pivoting of wings or blades. Alternatively the wings have integrated coils.

10 14. Microphone/flowmeter, according to claim 11, **characterized in** that the sensing of the pitch of the wings or blades is by means of optic or piezoelectric effect.

15 15. Microphone/flowmeter, according to claim 11, **characterized in** that it is constituted by a circular rotor provided with one or several wings where the wing angle is read.

16. Method for the measuring of modulated sound or air flow, **characterized in** that the air or other medium is led through a rotating rotor with easily moveable wings or blades and that a transported volume can be measured via the angle deflections of the wings or blades.

20 17. Loudspeaker or microphone according to any of the preceding claims, **characterized in** that the wings are adjustable for driving air alternatively sensing air flow or pressure via the angle of the wings in air or other medium.

18. Loudspeaker according to claims 1, 2, **characterized in** that the momentary power delivered to the motor is proportional to the power delivered to control of the wings.

25 19. Method for reproduction of sound, **characterized in** that at a motor driven loudspeaker rotor with to their pitch adjustable wings or blades the wing adjustment is momentarily controlled in accordance with the momentary sound pressure of the sound that is to be delivered.

30 20. Acoustic element according to any of the preceding claims, **characterized in** that the wing area essentially covers the entire flow through area of the loudspeaker element or microphone element.

21. Loudspeaker element according to claim 1, **characterized in** the rotor being surrounded by a spherical sealing wing area for the surrounding housing with center on the

spherical surface in the center of the rotor so that the distance between the housing and the wings remain constant independent of the pivoting of the wings of the rotor.

22. Loudspeaker element according to claim 1, **characterized in** that between the wings and the center of the rotor a rotationally symmetric advantageously spherical sealing slit is arranged between rotor center and wing, the rotationally symmetric surface having its axle coinciding with the pivot axle of the wing so that the distance between the wings and the rotor remain constant independent of the pivoting of the wings of the rotor.

23. Loudspeaker element according to claim 1, **characterized in** that between rotor center and the inner end of the wing a bellow device is arranged for sealing.

24. Loudspeaker element according to claim 1, **characterized in** that the wings are provided with balance weights preferably arranged perpendicularly against the wing surface so that with the pitch angle varying centrifugal forces on the wings are compensated.

25. Loudspeaker element according to claim 1, **characterized in** that the pivot axle of each wing or blade goes behind the pressure center seen in the direction of rotation so that with the pitch angle varying centrifugal forces on the wings are compensated.

26. Loudspeaker element according to claim 1, **characterized in** that the pivoting center for change of pitch for the wings is placed somewhat in front of the symmetry wing of the wings so that the rear area of the wings become slightly larger and thereby provide increasing resistance against increasing pitch so that improved linearity is obtained for pressure and air transport as a response to a controlling signal.

27. Loudspeaker element according to claim 1, **characterized in** that the loudspeaker element comprise several rotors mounted after each other or layers of blades for increased pressure/flow.

28. Loudspeaker element according to claim 1, **characterized in** that the loudspeaker element comprise several rotors mounted after each other or layers with blades with alternating direction of rotation for increased pressure/flow.

29. Loudspeaker element according to claim 1, **characterized in** that the length of the blades is less than 80% of the radius of the rotor for increased pressure.

30. Loudspeaker including loud speaker element according to claim 1, **characterized in** that the element is included as a part component in a turbine or fan.

31. Loudspeaker including loudspeaker element in accordance with claim 1, **characterized in** that it includes a loudspeaker box that in addition to an opening in which

the loudspeaker element is mounted includes one or several restricted or air flow damped so that the flow through the rotor can be optimized for pressure optimizing and that stall can be prevented.
