



(51) International Patent Classification:
H04W 40/12 (2009.01) *H04W 74/08* (2009.01)
H04W 84/18 (2009.01)

(21) International Application Number:
PCT/US2012/023115

(22) International Filing Date:
30 January 2012 (30.01.2012)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
11188905.1 11 November 2011 (11.11.2011) EP

(71) Applicant (for all designated States except US): **ITRON, INC.** [US/US]; 2111 North Molter Road, Liberty Lake, WA 99019 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MAINAUD, Bastien** [FR/FR]; c/o Itron, Inc., 2111 North Molter Road, Liberty Lake, WA 99019 (US). **NGUYEN, Viet-Hung** [FR/FR]; c/o Itron, Inc., 2111 North Molter Road, Liberty Lake, WA 99019 (US).

(74) Agents: **DIVINE, David, A.** et al.; Lee & Hayes, PLLC, 601 W. Riverside Ave., Suite 1400, Spokane, WA 99201 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ROUTING COMMUNICATIONS BASED ON LINK QUALITY




FIG. 1

(57) Abstract: A node may determine a link quality between the node and multiple neighbor nodes. For each of the multiple neighbor nodes, the node compares the determined link quality between the node and each respective neighbor node to a predetermined threshold quality. If the link quality meets the predetermined threshold quality, the node may qualify the link and add the link to a list of qualified links that meet the threshold link quality. The node may then route communications to neighbor nodes with which the node has a qualified link.



Published:

— *with international search report (Art. 21(3))*