




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04N 7/50	A1	(11) International Publication Number: WO 99/66734 (43) International Publication Date: 23 December 1999 (23.12.99)
(21) International Application Number: PCT/US99/11928 (22) International Filing Date: 28 May 1999 (28.05.99) (30) Priority Data: 60/090,023 19 June 1998 (19.06.98) US 09/219,913 23 December 1998 (23.12.98) US (71) Applicant: GENERAL INSTRUMENT CORPORATION [US/US]; 101 Tournament Drive, Horsham, PA 19044 (US). (72) Inventors: CHEN, Xuemin; 8560 Foxcroft Place, San Diego, CA 92129 (US). BIFRIG, Robert, O.; 9640 Carroll Canyon Road #1-7, San Diego, CA 92126 (US). (74) Agent: LIPSITZ, Barry, R.; Building 8, 755 Main Street, Monroe, CT 06468 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: VIDEO ENCODER AND ENCODING METHOD WITH BUFFER CONTROL



(57) Abstract

A technique is provided for enabling data, such as video, to be broadcast using a push dataflow scenario without causing a data rate buffer (32) for the pushed data at a decoder (30) to overflow or underflow. At an encoder (20), data are encoded for communication to the decoder (30) to provide an output bitstream. The data rate buffer (32) of the decoder is simulated at the encoder (22). The simulation is used to control the output bitstream to preclude overflow or underflow of the decoder buffer (32). For example, a complementary encoder buffer (22), which operates in a manner opposite to the decoder buffer (32), can be monitored and inverted to provide the simulation. Various different techniques are disclosed for controlling the amount of data produced at the encoder to maintain the data within the confines of the decoder buffer (32).