

(51) International Patent Classification:
H04B 7/02 (2006.01)(21) International Application Number:
PCT/JP2010/005078(22) International Filing Date:
17 August 2010 (17.08.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09168370.6 21 August 2009 (21.08.2009) EP(71) Applicant (for all designated States except US): **PANA-
SONIC CORPORATION** [JP/JP]; 1006, Oaza Kadoma,
Kadoma-shi, Osaka, 5718501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PETROV, Mihail.
KIMURA, Tomohiro.**(74) Agents: **NAKAJIMA, Shiro** et al.; 6F, Yodogawa 5-
Bankan, 2-1, Toyosaki 3-chome, Kita-ku, Osaka-shi, Osa-
ka, 5310072 (JP).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG,
ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).


Published:

— with international search report (Art. 21(3))

— with amended claims (Art. 19(1))

(88) Date of publication of the international search report:
26 May 2011Date of publication of the amended claims: 15 September
2011(54) Title: TRANSMISSION APPARATUS, RECEPTION APPARATUS, TRANSMISSION METHOD, RECEPTION
METHOD, AND METHOD FOR GENERATING ROTATED MULTI - DIMENSIONAL CONSTELLATIONS

[Fig. 12]



(57) Abstract: The present invention relates to digital data communication and provides an efficient method for generating multi - dimensional constellations for digital data modulation with a high degree of modulation diversity, a method for transmitting and receiving data on the basis of such constellations, and a corresponding apparatus. This is achieved by considering only multi - dimensional rotation matrices with all elements on the diagonal having the same first absolute value and all other elements having the same non-zero second absolute value. In this manner, multi - dimensional rotation matrices can be generated having only a single independent parameter and a structure that is as regular as possible. The independent parameter can be configured in order to minimize the error probability for various constellation sizes.