

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
1 August 2002 (01.08.2002)

PCT

(10) International Publication Number
WO 02/059890 A1

(51) International Patent Classification⁷: **G11B 7/24, 7/26**

(21) International Application Number: PCT/IB01/02687

(22) International Filing Date:
20 December 2001 (20.12.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
01200274.7 25 January 2001 (25.01.2001) EP

(71) Applicant: **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:
— with international search report

(72) Inventor: **HENDRIKS, Bernardus, H., W.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: **DEGUELLE, Wilhelmus, H., G.**; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: OPTICAL INFORMATION MEDIUM AND A METHOD OF MANUFACTURING THE MEDIUM



(57) Abstract: An optical information medium (20) for recording, such as DVR-blue, and a method for manufacturing such a medium (20) is provided. Reading from and recording onto the medium (20) is performed by means of a focused radiation beam (10) having a radiation wavelength λ and a numerical aperture NA. Said medium has a substrate (1), and a stack (2) of layers provided thereon. The stack (2) comprises at least a first recording stack (3) and k radiation beam transmissive layers (4, 5). Each transmissive layer (4, 5) has a refractive index n_i and an average thickness d_i μm and $1 = i = k$ and $k = 2$. The thickness d_k of layer k (5) is determined by a simple formula which depends on the parameters n_i for $i = 1 \dots k$ and d_i for $i = 1 \dots k-1$. Such a medium (20) has zero or substantially zero spherical aberration at the focal point, being at the recording layer of the first recording stack (3), of said radiation beam (10).



WO 02/059890 A1