

Description

This invention relates to an electrically operated refrigerant expansion valve.

Several types of electrically actuated valves suitable for use as expansion valves in refrigeration or air conditioning systems are known in the prior art. One type includes a solenoid connected to an appropriate electrical supply which, in response to a pulsed electrical signal, actuates a plunger or control element alternately into and out of a flow path through the expansion valve body to permit or prevent fluid flow. Another type of electrically actuated expansion valve has a rotary actuator with a means for converting the rotary motion into linear motion for operating a valve element to increase or decrease the flow area available through the valve body by seating against the valve seat to close the valve and prevent flow, or, moving linearly away from the valve seat, to permit flow through an area defined by the area of the opening between the valve element and the valve seat.

Representative U. S. Patents which disclose solenoid actuated valves of this type include: U. S. Patent 4,632,358 entitled Automotive Air Conditioning System Including Electrically Operated Expansion Valve; U.S. Patent 4,807,445 entitled Refrigeration System, and, U. S. Patent 4,840,039 entitled Automated Expansion Valve For a Refrigeration Circuit.

U. S. Patent 4,986,085 entitled Incremental Electrically Actuated Valve discloses a refrigerant expansion valve of the type linearly actuated by a rotary stepper motor.

US-A-3 871 815 discloses a solenoid actuated valve having a tapered valve opening and a tapered valve member.

In US-A-4 840 039 there is described an expansion valve according to the preamble of claim 1. Specifically, US-A-4 840 039 discloses an electrically operated refrigerant expansion valve having access openings, a metering orifice, a transverse opening terminating in a blind end and having a cross-sectional area larger than that of the metering orifice, a valve member cooperating with the opening, and electrically actuatable means for operating the valve member to control flow through the orifice.

It is an object of the present invention to provide an electrically actuated refrigerant expansion valve of simple design which allows the metering of refrigerant therethrough in either direction and which is capable of complete shut off of flow through the valve.

It is another object of the present invention to achieve complete shut-off in such a valve.

To achieve these objects, the electrically operated refrigerant expansion valve of the invention

is characterized by the features of the characterizing part of claim 1.

The valve body includes a tapered opening extending therinto from one side. The tapered opening decreases in cross sectional area in the direction from the outside of the body into the body. A tapered valve member extends into the tapered opening and a seal means is positioned in the blind end of the opening. The cooperation of the tapered valve member and the tapered opening is such that the flow through the valve body is completely shut off and the tapered valve member sealingly engages the seal means when the tapered valve member is fully inserted into the tapered opening.

Figure 1 is a schematic diagram of a heat pump system making use of an expansion device according to the present invention; and

Figure 2 is a longitudinal sectional view through a solenoid actuated expansion device according to the present invention;

With reference first to Figure 1, numeral 10 designates a heat pump of substantially conventional design which incorporates an electrically operated refrigerant expansion valve 12 according to the present invention. The expansion valve 12 is capable of controlling refrigerant flow in either direction therethrough and accordingly replaces the multiple expansion devices and check valves found in the refrigerant line between the heat exchangers of many prior art heat pumps. The operation of the dual flow electrically actuatable expansion valve 12 will be described more fully hereinafter.

The heat pump 10 also includes a compressor 14, an indoor heat exchanger assembly 16 and an outdoor heat exchanger assembly 18. An accumulator 20 is shown in the compressor suction line 21, however, it is contemplated that, because of the location of the expansion valve 12, and because of the variable metering capability of such a valve, the accumulator may not be needed.

The indoor heat exchange assembly 16 includes a refrigerant-to-air heat exchange coil 22 and an indoor fan 24. The indoor heat exchange assembly is also shown with a backup electrical resistance heating coil 26. The outdoor heat exchanger assembly 18 includes a refrigerant-to-air heat exchange coil 28 and an outdoor fan 30. The indoor and outdoor heat exchanger assemblies are of conventional design and will not be described further herein.

A four way reversing valve 32 is connected to the compressor discharge port by a refrigerant line 34, to the compressor suction port by suction line 21 and to coils 22 and 28 by refrigerant lines 36 and 38, respectively. The reversing valve 32 is also of conventional design for directing high pressure refrigerant vapor from the compressor to either the

indoor coil 22, in the heating mode of operation or, during the cooling mode and defrost, to the outdoor coil 28. Regardless of the mode of operation, the reversing valve 32 serves to return refrigerant from the coil which is operating as an evaporator to the compressor 14.

A refrigerant line 40 interconnects the indoor heat exchanger coil 22 and the outdoor heat exchanger coil 28. The dual flow, positive shut off electrically actuated expansion valve 12 according to the present invention, is located in the line 40 within the outdoor heat exchange assembly housing 18, adjacent to the outdoor coil 28. A controller 42 is shown located within the indoor heat exchanger assembly 16 and is interconnected to the expansion valve 12 by a suitable control cable 44.

The electrically actuatable expansion valve 12 could be of the type which includes a solenoid connected to an appropriate electrical supply which in response to a pulsed electrical signal actuates a plunger or control element alternately into and out of the flow path of the refrigerant through the expansion valve. It could also be of the type commonly referred to as an electrically actuated rotary actuator. Such an actuator, as described in previously noted U. S. Patent 4,986,085, includes means for converting rotary motion into linear motion for operating the valve element.

Referring now to Figure 2 an electrically actuated expansion valve 12 of the type actuated by a solenoid is shown. Preferably, the expansion valve 12 is a low cost, direct operated solenoid actuated valve. It will be understood, as the description continues, that, when the solenoid valve 12 is energized, it is fully opened, and, when it is de-energized, it is closed and all flow of refrigerant through the valve is blocked. The expansion valve 12 includes a valve body 46 having a pair of fluid access openings 48 and 50 formed in opposite sides thereof. The openings 48 and 50 are internally threaded to provide easy attachment thereof to appropriately threaded refrigeration line fittings. A refrigerant metering orifice 52 establishes fluid communication between the two access openings 48 and 50 to thereby complete the refrigerant flow path through the valve body 46.

Extending into the valve body 46 from one side thereof is a tapered opening 54. The tapered opening 54 is substantially perpendicular to the refrigerant metering orifice 52 and intersects with the refrigerant metering orifice. The tapered opening 54 extends into the valve body 46 a distance beyond the intersection with the orifice 52 where it terminates at a blind end 56. The tapered opening 54 is circular in cross section and has a cross sectional area that decreases from a maximum, at the outside of the body 46, to a minimum value at its interior blind end 56.

As generally indicated by reference numeral 58, a solenoid actuator is provided for the expansion valve 12. The solenoid actuator includes a moveable piston 60, which is axially moveable with respect to the valve body 46 as will be appreciated. The lower end of the piston 60 defines a tapered valve member 62. The tapered valve member is axially moveable with the piston 60 and extends into the tapered opening 54 to cooperate with the tapered opening to control the flow of refrigerant through the valve body 46. The tapered valve member 62 is configured so that the cooperation of the tapered valve member 62 and the tapered opening 54 is such that the flow through the valve body, i.e. through the orifice 52 is completely shut off when the tapered valve member 62 is fully inserted into the tapered opening 54.

As shown in Figure 2 the tapered valve member 62 is shown in a non-sealing position with respect to the tapered opening 54 in order to facilitate illustration of the elements.

Positioned in the blind end 56 of the tapered opening 54 is an elastomeric seal element 64. The lower end 66 of the tapered valve member 62 is configured to engage the seal 64 when the tapered valve member 62 is in its full downward, sealing position. The elastomeric seal 64 also lessens impact loads of the valve member 62 as it moves toward its closed position and as it engages the tapered opening 54. The solenoid actuator 58 further includes an axial tube 68 which has a solenoid core 70 disposed therein and which is fixedly held in place within the tube 68. The lower end of the tube 68 is sealingly secured, as by welding or the like, to an intermediate solenoid attachment plug 72. The plug 72 is adapted to be threadably mounted via external threads 74, to the valve body 46, by engagement with mating threads 76 formed in an opening 78 in the side of the valve body. The opening 78 is in co-axial relationship with the tapered opening 54.

A compression spring 80 is interposed between the upper end of the axially moveable piston 60 and the solenoid core 70 to thereby resiliently bias the piston and the tapered valve member 62 carried thereby away from the core 70 towards its closed position and engagement with the tapered opening 54. A solenoid coil 82 surrounds the tube 68. It will be understood that suitable electrical lead wires (not shown) extend from the coil to selectively energize and de-energize the coil.

As pointed out above, variable flow through the valve may be achieved by having the solenoid coil 82 energized by a pulse-width modulated voltage signal. A system for operating an expansion valve in such a manner is described in U. S. Patent No. 4,459,819 "Pulse Controlled Expansion Valve and Method".

As previously discussed in connection with Figure 1 the electrically operated dual flow refrigerant expansion valve 12 is installed in the refrigerant line 40 extending between the indoor coil 22 and the outdoor coil 28 of a heat pump system. As shown, the expansion device 12 is positioned in the outdoor heat exchanger assembly 18 close to the outdoor coil 28. As so positioned and operating under the pulse width modulated signal from the controller 42 the expansion valve 12 will operate to control the flow of refrigerant from the outdoor coil 28 to the indoor coil 22, when the system is operating in the cooling mode of operation, and, from the indoor coil 22 to the outdoor coil 28 when operating in the heating mode of operation.

As pointed out above, when the valve 12 is not energized the spring 80 will urge the valve member 60 downwardly to bias the tapered valve member 62 into sealing engagement with the tapered opening 54 to form a positive seal against refrigerant flow through the valve. As a result of the above described positive shut off feature, the expansion valve 12 is capable of preventing refrigerant migration therethrough when it is installed in a system and the system is shut off. It also follows that the system is able to maintain a pressure differential between the high and low sides of the system when shut off. A direct benefit of this is that the Degradation Coefficient Cd of the refrigeration system is reduced. The Degradation Coefficient is a term defined by the U.S. Department of Energy which relates to the measure of the efficiency loss of a system due to cycling of the system.

This invention may be practiced or embodied in still other ways without departing from the spirit or essential character thereof. The preferred embodiment described herein is therefore illustrative and not restrictive.

Claims

1. An electrically operated refrigerant expansion valve (12) of the type including a valve body (46) having:
 - first and second fluid access openings (48, 50) formed at opposite ends thereof,
 - a refrigerant metering orifice (52) establishing fluid communication between said first and second openings (48,50),
 - an opening (54) extending into said body (46) from one side thereof, said opening (54) being generally transverse to and intersecting said refrigerant metering orifice (52), said opening (54) being circular in cross-section and terminating in a blind end (56) at a position beyond said intersection with said orifice (52), said opening (54) having a cross-sectional area at the intersection with said orifice (52)

which is larger than the cross sectional area of said orifice (52),

a valve member (62) extending into said opening (54) to cooperate with said opening (54) to control the flow through said valve body (46), and

electrically actuatable means (58) mounted on said one side of said valve body (46) for operatively engaging said valve member (62) and for imparting axially movement to said valve member (62) into and out of said opening (54),

characterized in that both said opening (54) and said valve member (62) have a tapered form, said tapered opening (54) decreasing in cross-sectional area in the direction from said one side into said body (46), the cooperation of said tapered valve member (62) and said tapered opening (54) being such that the flow through said valve body is completely shut off when said tapered valve member (62) is fully inserted into said tapered opening (54), and

in further comprising seal means (64) positioned in said blind end (56), said tapered valve member (62) sealingly engaging said seal means (64) when it is fully inserted into said tapered opening (54).

2. The expansion valve of claim 1, characterized in that at least a part of said tapered valve member (62) is made from a magnetic material, and, said electrically actuatable means (58) comprises a solenoid coil (82).
3. The expansion valve of claim 2 characterized in further including spring means (80) for yieldably biasing said tapered valve member (62) into sealing engagement with said tapered opening (54).

Patentansprüche

1. Elektrisch betriebenes Expansionsventil (12) für Kühlmittel der Art, die einen Ventilkörper (46) umfasst, das:
 - erste und zweite Zugangsöffnungen (48, 50) für Fluid, die an gegenüberliegenden Enden von ihm ausgebildet sind,
 - eine Mündung (52) zum Dosieren von Kühlmittel, die eine Fluidverbindung zwischen der ersten und zweiten Öffnung (48, 50) herstellt,
 - eine Öffnung (54), die von einer Seite vom Körper (46) in ihn hinein geht, wobei die Öffnung (54) im allgemeinen quer zur Mündung (52) zum Dosieren von Kühlmittel liegt und diese kreuzt, und wobei die Öffnung (54) einen



As previously discussed in connection with Figure 1 the electrically operated dual flow refrigerant expansion valve 12 is installed in the refrigerant line 40 extending between the indoor coil 22 and the outdoor coil 28 of a heat pump system. As shown, the expansion device 12 is positioned in the outdoor heat exchanger assembly 18 close to the outdoor coil 28. As so positioned and operating under the pulse width modulated signal from the controller 42 the expansion valve 12 will operate to control the flow of refrigerant from the outdoor coil 28 to the indoor coil 22, when the system is operating in the cooling mode of operation, and, from the indoor coil 22 to the outdoor coil 28 when operating in the heating mode of operation.

As pointed out above, when the valve 12 is not energized the spring 80 will urge the valve member 60 downwardly to bias the tapered valve member 62 into sealing engagement with the tapered opening 54 to form a positive seal against refrigerant flow through the valve. As a result of the above described positive shut off feature, the expansion valve 12 is capable of preventing refrigerant migration therethrough when it is installed in a system and the system is shut off. It also follows that the system is able to maintain a pressure differential between the high and low sides of the system when shut off. A direct benefit of this is that the Degradation Coefficient Cd of the refrigeration system is reduced. The Degradation Coefficient is a term defined by the U.S. Department of Energy which relates to the measure of the efficiency loss of a system due to cycling of the system.

This invention may be practiced or embodied in still other ways without departing from the spirit or essential character thereof. The preferred embodiment described herein is therefore illustrative and not restrictive.

Claims

1. An electrically operated refrigerant expansion valve (12) of the type including a valve body (46) having:
 - first and second fluid access openings (48, 50) formed at opposite ends thereof,
 - a refrigerant metering orifice (52) establishing fluid communication between said first and second openings (48, 50),
 - an opening (54) extending into said body (46) from one side thereof, said opening (54) being generally transverse to and intersecting said refrigerant metering orifice (52), said opening (54) being circular in cross-section and terminating in a blind end (56) at a position beyond said intersection with said orifice (52), said opening (54) having a cross-sectional area at the intersection with said orifice (52)

which is larger than the cross sectional area of said orifice (52),

a valve member (62) extending into said opening (54) to cooperate with said opening (54) to control the flow through said valve body (46), and

electrically actuatable means (58) mounted on said one side of said valve body (46) for operatively engaging said valve member (62) and for imparting axially movement to said valve member (62) into and out of said opening (54),

characterized in that both said opening (54) and said valve member (62) have a tapered form, said tapered opening (54) decreasing in cross-sectional area in the direction from said one side into said body (46), the cooperation of said tapered valve member (62) and said tapered opening (54) being such that the flow through said valve body is completely shut off when said tapered valve member (62) is fully inserted into said tapered opening (54), and

in further comprising seal means (64) positioned in said blind end (56), said tapered valve member (62) sealingly engaging said seal means (64) when it is fully inserted into said tapered opening (54).

2. The expansion valve of claim 1, characterized in that at least a part of said tapered valve member (62) is made from a magnetic material, and, said electrically actuatable means (58) comprises a solenoid coil (82).
3. The expansion valve of claim 2 characterized in further including spring means (80) for yieldably biasing said tapered valve member (62) into sealing engagement with said tapered opening (54).

Patentansprüche

1. Elektrisch betriebenes Expansionsventil (12) für Kühlmittel der Art, die einen Ventilkörper (46) umfasst, das:
 - erste und zweite Zugangsöffnungen (48, 50) für Fluid, die an gegenüberliegenden Enden von ihm ausgebildet sind,
 - eine Mündung (52) zum Dosieren von Kühlmittel, die eine Fluidverbindung zwischen der ersten und zweiten Öffnung (48, 50) herstellt,
 - eine Öffnung (54), die von einer Seite vom Körper (46) in ihn hinein geht, wobei die Öffnung (54) im allgemeinen quer zur Mündung (52) zum Dosieren von Kühlmittel liegt und diese kreuzt, und wobei die Öffnung (54) einen



kreisförmigen Querschnitt hat und bei einem toten Ende (56) in einer Position unterhalb der Kreuzung mit der Mündung (52) endet, und wobei die Öffnung (54) bei der Kreuzung mit der Mündung (52) eine Querschnittfläche hat, die grösser ist als die Querschnittfläche der Mündung (52),

ein Ventiltteil (62), das sich in die Öffnung (54) hinein erstreckt um mit der Öffnung (54) zusammen zu arbeiten und damit die Strömung durch den Ventilkörper (46) zu steuern, und

eine elektrisch zu betätigende Einrichtung (58), die an der einen Seite des Ventilkörpers (46) montiert ist, um das Ventiltteil wirkend zu berühren und um eine axiale Bewegung auf das Ventiltteil (62) in die Öffnung (54) hinein und hinaus zu übertragen, aufweist,

dadurch gekennzeichnet, dass sowohl die Öffnung (54) als auch das Ventiltteil (62) kegelförmig sind, wobei die kegelförmige Öffnung (54) in Richtung von der einen Seite in den Körper (46) hinein eine abnehmende Querschnittfläche hat, und dass die Zusammenarbeit zwischen dem kegelförmigen Ventiltteil (62) und der kegelförmigen Öffnung (54) derart ist, dass die Strömung durch den Ventilkörper hindurch vollständig ausgeschaltet wird, wenn das kegelförmige Ventiltteil (62) vollständig in die kegelförmige Öffnung (54) eingeschoben ist, und

dass es weiter eine Dichtungseinrichtung (64) umfasst, die im toten Ende (56) angeordnet ist, wobei das kegelförmige Ventiltteil (62) die Dichtungseinrichtung (64) abdichtend berührt, wenn es vollständig in die kegelförmige Öffnung (54) eingeschoben ist.

2. Expansionsventil nach Anspruch 1, dadurch gekennzeichnet, dass mindestens ein Teil des kegelförmigen Ventiltteils (62) aus magnetischem Material hergestellt ist, und dass die elektrisch zu betätigende Einrichtung (58) eine Wicklung (82) für einen Elektromagnet umfasst.
3. Expansionsventil nach Anspruch 2, dadurch gekennzeichnet, dass es weiter eine Federeinrichtung (80) umfasst, um das kegelförmige Ventiltteil (62) nachgebend in einen abdichtenden Kontakt mit der kegelförmigen Öffnung (54) zu lenken.

Revendications

1. Une soupape de détente actionnée électriquement pour réfrigérant (12) du type comprenant un corps de soupape (46) ayant:

une première et une seconde ouvertures d'accès pour le fluide (48,50) formées à des extrémités opposées de celle-ci,

un orifice de mesure du réfrigérant (52) établissant une communication de fluide entre lesdites première et seconde ouvertures (48,50),

une ouverture (54) s'étendant dans ledit corps (46) à partir d'un côté de celui-ci, ladite ouverture (54) étant généralement transversale à et coupant ledit orifice de mesure du réfrigérant (52), ladite ouverture (54) étant circulaire, en coupe transversale et se terminant dans une impasse (56) au niveau d'une position au-delà de ladite intersection avec ledit orifice (52), ladite ouverture (54) ayant une aire en coupe transversale, au niveau de l'intersection avec ledit orifice (52), qui est plus grande que l'aire en coupe transversale dudit orifice (52),

un élément de soupape (62) s'étendant dans ladite ouverture (54) pour coopérer avec ladite ouverture (54) pour contrôler l'écoulement à travers ledit corps de la soupape (46), et

un moyen actionnable électriquement (58) monté sur ledit premier côté dudit corps de la soupape (46) pour engager de façon opérationnelle ledit élément de soupape (62) et pour conférer un mouvement axial audit élément de la soupape (62) dans et hors de ladite ouverture (54),

caractérisée en ce que à la fois ladite ouverture (54) et ledit moyen de soupape (62) ont une forme effilée, ladite ouverture effilée (54) diminuant, en ce qui concerne l'aire en coupe transversale, dans la direction allant dudit premier côté jusque dans ledit corps (46), la coopération dudit élément de soupape effilé (62) et de ladite ouverture effilée (54) étant telle que l'écoulement à travers ledit corps de la soupape est complètement arrêté quand ledit élément de la soupape effilé (62) est totalement inséré dans ladite ouverture effilée (54), et

en ce qu'elle comprend en outre un moyen de joint (64) placé dans ladite impasse (56), ledit élément de soupape effilé (62) engageant de façon étanche ledit moyen de joint (64) quand il est totalement inséré dans ladite ouverture effilée (54).

2. La soupape de détente de la revendication 1, caractérisée en ce que au moins une partie dudit élément de soupape effilé (62) est élaboré à partir d'un matériau magnétique et ledit moyen actionnable électriquement (58) comprend un solénoïde (82).



3. La soupape de détente de la revendication 2, caractérisée en ce qu'elle comprend en outre un moyen de ressort (80) pour pousser efficacement ledit élément de soupape effilé (62) dans un engagement étanche avec ladite ouverture effilée (54).

5

10

15

20

25

30

35

40

45

50

55

6