



- (51) **International Patent Classification:**
C10M 169/04 (2006.01) *C08G 81/02* (2006.01)
- (21) **International Application Number:**
PCT/US2014/018662
- (22) **International Filing Date:**
26 February 2014 (26.02.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/783,192 14 March 2013 (14.03.2013) US
- (71) **Applicant:** EXXONMOBIL RESEARCH AND ENGINEERING COMPANY [US/US]; 1545 Route 22 East, P.O. Box 900, Annandale, NJ 08801-0900 (US).
- (72) **Inventors:** EIRICH, Benjamin, D.; 306 West Cherry Street, Wenonah, NJ 08090 (US). HABEEB, Jacob, Joseph; 15364 Skyline Truck Trail, Jamul, CA 91935 (US). PATIL, Abhimanyu, O.; 12 Evergreen Court, Westfield, NJ 07090 (US). DECKMAN, Douglas, Edward; 5 Peachtree Lane, Mullica Hill, NJ 08062 (US).
- (74) **Agents:** SHANLEY, Matthew, T. et al.; ExxonMobil Research and Engineering Company, 1545 Route 22 East, P.O. Box 900, Annadale, NJ 08801-0900 (US).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) **Title:** METHOD FOR IMPROVING EMULSION CHARACTERISTICS OF ENGINE OILS

(57) **Abstract:** A method for improving the ability of an engine lubricating oil contaminated with water and fuel to emulsify water contamination by using as the engine lubricating oil a formulated oil including a lubricating oil base stock as a major component and a coupled block copolymer as a minor component. A method for improving thermo-oxidative stability and elastomer compatibility in an engine lubricated with a lubricating oil by using as the lubricating oil a formulated oil including a lubricating oil base stock as a major component and a coupled block copolymer as a minor component. A lubricating engine oil including a lubricating oil base stock as a major component and a coupled block copolymer as a minor component.

