



(43) International Publication Date
6 February 2014 (06.02.2014)

(10) International Publication Number
WO 2014/022334 A2

(51) International Patent Classification:

F15B 13/042 (2006.01) *F16K 37/00* (2006.01)
F16K 15/02 (2006.01) *B25B 13/46* (2006.01)

(21) International Application Number:

PCT/US2013/052614

(22) International Filing Date:

30 July 2013 (30.07.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

13/566,664 3 August 2012 (03.08.2012) US

(71) Applicant: **SPX CORPORATION** [US/US]; 13320 Ballantyne Corporate Place, Charlotte, North Carolina 28277 (US).

(72) Inventor: **LANDRUM, Michael T.**; 5045 Burningtree Drive, Rockford, Illinois 61114 (US).

(74) Agents: **LARSON, P. Alan** et al.; Baker & Hostetler LLP, 1050 Connecticut Avenue, NW, Suite 1100, Washington, District of Columbia 20036 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*

(54) Title: AN AUTO CYCLE PUMP AND METHOD OF OPERATION

(57) Abstract: A hydraulic flow sensing apparatus is provided. The apparatus includes: a manifold; a hole in the manifold in fluid communication with a fluid pathway; a poppet valve in the hole in the manifold configured to move when fluid in the pathway flows; and a proximity switch configured to detect movement of the poppet valve. A method of operating a hydraulic circuit may also be provided.



WO 2014/022334 A2