Claims

What is claimed is:

1. A display device, comprising:

a display medium module comprising a first electrode, a second electrode and a display medium, wherein the first electrode and the second electrode are separated from each other, and the display medium is disposed between the first electrode and the second electrode;

an active switching element electrically connected to the first electrode for allowing the first electrode and the second electrode to change the state of the display medium, wherein the active switching element comprises a wafer portion and a transistor portion with the transistor portion formed on the wafer portion, and the wafer portion is part of a silicon wafer, gallium arsenide wafer, sapphire wafer, indium phosphide wafer or gallium nitride wafer, a pixel unit structure comprises the display medium module and the active switching element; and

a housing structure, wherein the plurality of pixel unit structures are disposed in the housing structure, the pixel unit structure is capable of independently being disassembled from the housing structure through a connection between the active switching element and the housing structure.

2. The display device of claim 1, wherein the display medium module further comprises a first substrate and a second substrate, which are disposed facing each other and separated from each other; wherein the first electrode is disposed on the first substrate and the second electrode is disposed on the first substrate or the second substrate; wherein the active switching element is disposed on the first substrate and/or the second substrate.

3. The display device of claim 2, wherein the first substrate or the second substrate is made of at least one of transparent material, opaque material, flexible material, rigid material, metallic material, ceramic material, insulating material, metal compound material, metal alloy material, organic material, inorganic material, composite material and semiconductor material.

4. The display device of claim 1, further comprising a package carrier, therein is packaged the active switching element.

5. The display device of claim 4, further comprising a functional element packaged in the package carrier, the functional element comprising at least one of a displacement sensing functional element, a hygrothermal sensing functional element, an acoustic sensing functional element, an electromagnetic sensing functional element, a touch sensing functional element, an image capturing functional element, a memory functional element, a control functional element, a wireless communication functional element, a passive functional element, a self-luminous functional element and a photovoltaic functional element.

6. The display device of claim 3, further comprising a functional element disposed on the first substrate and/or the second substrate, the functional element comprising at least one of a displacement sensing functional element, a hygrothermal sensing functional element, an acoustic sensing functional element, an electromagnetic sensing functional element, a touch sensing functional element, an image capturing functional element, a memory functional element, a control functional element, a wireless communication functional element, a passive functional element, a self-luminous functional element and a photovoltaic functional element.

7. The display device of claim 2, wherein the first substrate and/or the second substrate comprise a concave groove or a through hole, and the active switching element is disposed in the concave groove or the through hole.

8. The display device of claim 1, further comprising a carrier board, wherein the display medium module is disposed on the carrier board and the active switching element is disposed on the carrier board.

9. The display device of claim 8, wherein the carrier board includes a concave groove or a through hole and the active switching element is disposed in the concave groove or the through hole.

10. The display device of claim 8, further comprising a control signal line and a data signal line, wherein the control signal line and the data signal line are formed on the carrier board and electrically connected to the active switching element.

11. The display device of claim 2, further comprising a control signal line and a data signal line, wherein the control signal line and the data signal line are formed on the first substrate and/or the second substrate of the display medium module and electrically connected to the active switching element.

12. The display device of claim 1, wherein the display medium module further comprises an optical element optically coupled with the display medium and the optical element comprises at least one of a convex lens, a concave lens and an optical prism.

13. The display device of claim 1, wherein the display medium comprises at least one of self-luminous medium material, nonself-luminous medium material, light-filtering material, electric conductive material, insulating material, light absorbing material, light reflecting material, photorefractive material, light deflecting material and light diffusing material.

14. The display device of claim 13, wherein the non-selfluminous medium material comprises at least one of electrophoretic material, electric fluid material, liquid crystal material, micro electromechanical reflective material, electrowetting material, electric ink material, magnetic fluid material, electrochromic material, electromorphous material and thermochromic material; the self-luminous medium material may include at least one of electroluminescent material, photoluminescent material, cathodoluminescent material, field emissive luminescent material, vacuum fluorescent material and light-emitting diode material.

15. The display device of claim 1, wherein a shape of the display medium module is one of square, rectangular, fan-shaped, triangular, trapezoid, round, polygonal, irregular.

16. The display device of claim 1, further comprising a light source module, which is disposed in the housing structure and positioned on any side of the display medium module of the pixel unit structure.