


This Sheet Has Been Replaced




1



" Method and Device for Extinguishing Fires"

The present invention relates to a device for extinguishing fires, with a container for receiving an extinguishing agent, and with an explosive in or on said container, by means of the detonation of which the extinguishing agent is atomised to form a mist and is
5 applied to the fire. The invention further relates to a method of extinguishing forest or terrain fires with the described device.

Atomisation of an extinguishing agent into microfine particles by means of an explosive with the aim of extinguishing fires, is known.
10 During detonation of a preferably high-explosive charge within or in the vicinity of a homogenous medium such for example as water, a pressure of several thousand bar is developed, so that the water is atomised into microfine particles and is thrown by the resultant pressure wave from the centre of the explosive charge into the
15 surrounding area. By a high-explosive charge is meant one which develops a detonation wave with a propagation speed of above 5000 metres per second. The mist of extinguishing agent, in relation to the amount of such agent used, and due to the small size of the individual droplets of extinguishing agent, has an extremely large
20 overall surface area, by means of which the extinguishing agent is applied in the neighbourhood of the detonated container to the fire, and extinguishes it by means of the known supercooling effect. In addition, the extinguishing effect during detonation of an extinguishing agent also results in a known way from the blowing-out
25 effect of the detonation wave.



There are known from US 1 119 799 and from EP 390 384 fire extinguishers provided for stationary use, and which utilise the effect described above of detonation of an extinguishing agent.

- 5 These known devices for extinguishing fires have a cylindrical container for receiving an extinguishing agent, and a concentrically-disposed elongate internal container which extends in the longitudinal direction in the extinguishing agent container, and which is filled with an explosive charge.

10

From EP 488 536 there is known such a fire extinguisher, in which the explosive charge, in contrast to the fire extinguishers described above, is attached externally to the extinguishing agent container.

15

- US 3 980 139 and FR 1 473 621 respectively disclose a "fire-extinguishing bomb" comprising a cylindrical glass or plastics container for receiving an extinguishing agent, and also comprising a cylindrical, concentrically-disposed internal container, which in
- 20 turn contains the explosive material. The difference between these fire-extinguishing bombs and the fire extinguishers described before consists purely in the ignition of the explosive, which is effected in the bombs either by a radio signal or by the effect of heat when the fire-extinguishing bomb is thrown into a fire.

25



All the fire-extinguishing devices described above have a common disadvantage, namely that in practical use in extinguishing fires they are insufficiently flexible and effective. Thus stationary fire extinguishers always have only a localised effect, so that fire-
5 protection over a large area, or also in large-area firefighting, are impracticable for economic reasons, as too many of this type of fire-extinguisher would have to be used. With respect to mobile firefighting, for example in forest or other terrain fires, the "fire-extinguishing bombs" described have proved disadvantageous, as
10 when the extinguishing bomb is launched they do not exert a directed extinguishing effect due to the detonation, and moreover rather fan the flames when they are ignited in the centre of the fire. Finally, launching these extinguishing devices over the seat of the fire is to a great extent complex and cost-intensive, not to mention
15 unsatisfactory as regards hit accuracy.

The object underlying the present invention is to indicate a more adaptive and effective device for extinguishing fires.

20 This object is fulfilled by the device for extinguishing fires with the features of claim 1, and by the method for extinguishing forest or terrain fires with the features of claim 11.

Both the device according to the invention and the method have a
25 whole series of advantages which considerably increase their



effectiveness in firefighting. For the purposes of the following description of the advantages, the term "mobile" firefighting should be taken to mean extinguishing of fires by task forces. Such fires are for example forest or terrain fires, or also fires in industrial
5 installations or normal buildings. "Stationary" firefighting should be taken to mean extinguishing fires by means of an extinguishing device according to the invention which is permanently installed and ready for use at the site at risk. The installations or structures to be protected in this way cover a wide range; this may contain for
10 example oil or gas tanks, refineries, oil drilling or pumping installations, runways or fuelling areas in airports, and similar.

In mobile use, the extinguishing device according to the invention is characterised in that it is adaptable over almost unrestricted
15 lengths to the configuration of the flame front, and thus to the threat. Thus the hose, at first not filled with extinguishing agent, is unrolled like a conventional firefighting hose, for example from drums, and is laid out. Thus an almost limitless spatial usable width is obtained. When a plurality of hose lines are spaced out
20 parallel to one another, a plurality of firefighting lines may be produced, and thus an operational depth of almost any magnitude. The flexible hose may be manufactured by the metre, and is easily transportable when rolled up.



These advantages make it clear that the extinguishing device according to the invention is outstandingly suitable for combating a large fire. By means of corresponding layout of the flexible hose, the fire may be "contained", to use the technical term for encirclement of the seat of a fire while at the same time fighting it from all sides.

With regard to stationary firefighting, i.e. in particular for industrial applications, the extinguishing device according to the invention is characterised likewise by its high degree of flexibility in layout. As even the smallest layout radii are possible, the extinguishing device can for example, when installed in a warehouse, be passed around installation components such as shelving or the like, or around constructive obstacles such as pillars or the like. It may also be imagined that the flexible hose may be suspended above high shelving. Here also then maximum adaptation of the stationary extinguishing device to potential centres of risk is possible.

It should be named as an advantage of the device according to the invention, both for mobile and for stationary firefighting, that the mist of extinguishing agent may be produced rapidly, flexibly and economically at the site of the event. The basic materials required for this purpose, i.e. water and if necessary an extinguishing additive ("RETARDER"), as well as the explosive, may be stored



without difficulty and for long periods in a small space, and moreover are easily transportable. It follows from this that the device according to the invention for stationary fire protection may be permanently installed or - for mobile firefighting - may be

5 variably used on site, even where conventional extinguishing methods fail, for example due to shortage of water. Furthermore, different classes of fire may be securely extinguished by the device according to the invention. As due to the increase in surface area because of atomisation of the extinguishing agent, a relatively small amount of

10 extinguishing agent is used, considerably less damage is caused in firefighting than when conventional extinguishing methods are used. Neither proper detonation itself, nor the atomised extinguishing agent, represent any risk to the environment of the fire. When the extinguishing device is used in industries which manufacture or

15 process pulverulent products, it is in addition of great advantage that the powder is bound by the mist of extinguishing agent over a large surface after a dust explosion or the like.

Advantageous further developments of the invention are given in the

20 secondary claims.


Two alternative forms are provided of the explosive material extending linearly in or on the container: on the one hand the explosive may be in the form of a flexible explosive cord extending

25 longitudinally along the hose, and on the other hand discrete linear



explosive charges may be provided, which are likewise distributed at regular intervals in or on the hose. An advantage common to both forms of the explosive is that the hose, with explosive, may be produced as a completed product by the metre. This reduces both
5 manufacturing costs and also the time required for its utilisation on site.

The flexible hose preferably consists of a thin-walled but resistant material. The selection of the hose material is effected from the
10 viewpoint that it is as resistant as necessary, and as flexible as possible. In this connection, the resistance during mobile use is intended merely to ensure that when the hose is laid out and subsequently filled with extinguishing agent, no holes will be made in it by branches or sharp stones. Flexibility will be in terms of
15 the criteria that the hose is to be capable of being rolled up, and that the smallest layout radii are possible. Furthermore, the hose should have the smallest possible intrinsic weight. Preferably used are thin-walled plastics hoses which might be described as
"burstable" within the framework of the above requirements. By means
20 of the described selection of the hose material, also, danger to persons by projection of hard materials such as are for example used in the known fire-extinguishing bombs or the like, is avoided. Even hard PVC could be a risk to personnel, even at a large distance.



The hose also has protection against radiated heat, consisting for example of white material or of an aluminium coating.

Whereas the hose will normally have a circular cross-section, it may
5 also be envisaged for special applications that the hose in the
filled condition has a triangular cross-section. This cross-section
enables a stable position of the hose and thus the opportunity of
identifying by colour a specific side of the triangle, which is
intended to face the seat of the fire. This is of particular
10 advantage when the explosive cord is located in the angle of the
triangular hose which lies opposite the side of the triangle facing
the seat of the fire. Thus a directed explosive effect can be
achieved in a particularly effective way. This may be further
reinforced by the fact that the side of the triangular hose facing
15 the seat of the fire is weaker in construction than the two other
sides.

One aim of the hose filled with extinguishing agent is to take as
much pressure as possible from the lower surface upon which the hose
20 rests, in order to bring as much extinguishing agent as possible
into the air. For this purpose, the explosive, i.e. for example one
or more explosive cords, is/are preferably disposed at a spacing of
approximately one-third of the hose diameter from the ground or from
a retaining means upon which the hose rests. Such positioning is
25 most simply realised in that two hoses are glued together in



parallel, and the explosive cord is contained between the two hoses in contact with each other. Raising the explosive cord from the underlying surface achieves an outstanding distribution and direction of the mist of extinguishing agent.

5

When using the extinguishing device for stationary protection of specific objects, the hose with the explosive is disposed on a longitudinally-extended carrier which in cross-section is for example shell-shaped or angled. In this way on the one hand a stable
10 mount is obtained for the hose, and on the other hand a directed effect upon detonation of the extinguishing agent, as the hose is shielded at the rear by the carrier, while the effect in the forward direction, towards the centre of the risk, is not impaired.

15 The advantage of a stable stationary mounting for the ready-to-use extinguisher hose can be seen in the fact that the hose, on the carrier, can preferably be permanently filled with the extinguishing agent.

20 The extinguishing device according to the invention, in addition to being a fire-protection device for specific objects for stationary installations or devices, is also suitable for dust abatement during blasting operations, for example when destroying buildings by
blasting, when the hose, laid at least partly around the object to
25 be blasted, is filled with water and is detonated by ignition of the



explosive when the dust front occurs. If necessary a plurality of protective walls may be laid around the object to be blasted, which are then detonated in timed sequence. In this way it is possible effectively to counteract the serious dust nuisance which previously
5 occurred during blasting of buildings.

The extinguishing device according to the invention may in addition be used as a preventative fire-protection device at or on an airport runway or an aircraft parking area. It is known from prior art as a
10 preventative measure, upon announcement of an emergency landing of an aircraft, to apply a foam carpet approximately 1000 metres long and 60 metres wide to the runway. The time required for this however is 45 to 60 minutes, and the cost of the equipment required is extremely high. Foaming of runways has been discontinued for some
15 time, as in addition to the enormous outlay in time and cost, the logic of such foaming has been questioned. The aircraft executing an emergency landing can become uncontrollable due to the foam carpet, and may sheer laterally off the runway, so that rescue operations are rather hindered by this. In this connection the critical moment
20 and thus also the critical position during the emergency landing is only reached when the aircraft comes to a halt, and leaking fuel is ignited. The extinguishing device takes effect precisely at this point, the hose, laid out along the runway and filled with the extinguishing agent, being detonated at the critical moment by
25 ignition of the explosive. The microfine particles of extinguishing



agent produced by the detonation rain down on the activated critical area, and form a surface film which leads in a minimum space of time to an enclosed surface, thus preventing ignition of the fuel.

5 A further possible use for the extinguishing device according to the invention consists in preventative fire protection of an aircraft parking position, where aircraft as a rule are also refuelled. It may be envisaged at this point that a hose line may be installed between the aircraft and the terminal building, said hose line being
10 permanently filled with extinguishing agent and, in an emergency, laying a microfine film of extinguishing agent over the protected area by detonation.

The invention will be explained in more detail in the following by
15 means of some embodiments given by way of example, and with reference to a drawing, which shows:

Fig. 1: a diagrammatic cross-section of an explosive
extinguishing hose with internal explosive;

20 Fig. 2: a diagrammatic cross-section of an explosive
extinguishing hose with external explosive;

Fig. 3: a diagrammatic cross-section of a hose bundle
comprising three explosive extinguishing hoses;

Fig. 4: a diagrammatic cross-section of a triangular
explosive extinguishing hose;



Fig. 5: a diagrammatic front elevation of a forest fire
with a linear configuration of the flame front;

Fig. 6: a diagrammatic front elevation of a forest fire
with an irregular configuration of the flame
5 front;

Fig. 7: a diagrammatic illustration of an oil tank with a
stationary extinguishing device, in cross-section,
and

Fig. 8: a diagrammatic illustration of an airport runway
10 with stationary extinguishing device, in plan
view.

In the figures of the drawing, the arrows 7 respectively show the
principal direction of propagation of the detonated extinguishing
15 agent, and of the pressure wave.

Fig. 1 shows a flexible hose 2 of circular cross-section and of
optional length comprising a thin-walled plastics material, filled
with an extinguishing agent 10. At the point where the hose 2 rests
20 on the ground (not shown), there extends within the hose, at a
distance of approximately one-third of the hose diameter from the
ground, a linear flexible explosive cord 4 consisting of high
explosive, which is water-resistant, burns only with difficulty and
may be stored almost indefinitely. With these properties, the
25 explosive may be used both in a mobile and in a stationary



application of the extinguishing device. When the explosive cord 4 is ignited, the extinguishing agent, due to the high pressure, is atomised in fractions of a second to form microfine droplets of extinguishing agent, and is almost uniformly distributed in all
5 directions in the direction of the arrows 7. Thus there results a delivery, approximately semicircular in cross-section, of the mist of extinguishing agent to the surroundings.

If, instead, as Fig. 2 shows, the explosive cord 4 is disposed
10 outside the filled hose 2, a substantially directed explosive and extinguishing effect may be achieved. In this case the explosive cord 4 is positioned on the side of the hose 2 facing away from the seat of the fire, on the ground (not shown). In this way the fire is likewise highly effectively combated; more than 50% of the
15 extinguishing agent can develop a direct extinguishing effect.

In many cases it can be meaningful to form a hose bundle from a plurality of hoses 2, as shown in diagrammatic cross-section in Fig. 3. In this case the explosive cord 4 is located in the centre of the
20 hose bundle. Naturally, other positioning may be envisaged, up to and including the use of a plurality of explosive cords at various points.

Fig. 4 shows a different cross-sectional shape of the hose 2. The
25 hose 2 illustrated therein has a triangular cross-sectional shape,



and the explosive cord 4 is located in the angle of the triangular hose 2 which lies opposite the triangle side or hose wall 1 facing the seat of the fire. A substantially directed explosive and extinguishing effect in the direction of arrows 7 are also

5. achievable by this arrangement. This directional effect might for example be reinforced by the fact that the side 1 of the hose 2 facing the seat of the fire is made of weaker material than the two other triangle sides 3, 5. Moreover, the side 1 may be colour-coded, in order to ensure when the extinguishing device is laid out that

10 the explosive cord located in the hose is correctly positioned in relation to the seat of the fire or the direction of risk.

Fig. 5 shows a diagram of a forest fire. In this illustration, the fire front moves from the right to the left. In order to extinguish

15 the fire, a hose according to Fig. 1, for example, with the explosive cord 4 contained therein, has been laid out along the entire fire front 8 and filled with extinguishing agent. When the explosive cord 4 is detonated, the extinguishing agent, atomised to form a mist, spreads to both sides of the hose 2 over a width of 50

20 metres in each case. The flames 9 are extinguished in the way described above, both by the supercooling effect, and by the detonation wave resulting from the explosion. On the opposite side of the hose 2, the area of the forest not affected by the fire front 8, has been wetted by the mist of extinguishing agent.



Fig. 6 shows a diagrammatic view of an irregularly-conformed fire front 8. An advantage of the extinguishing device according to the invention is particularly clearly shown by this illustration: if the fire was fought with known non-flexible extinguishing devices, for example by interconnection of rigid extinguishing agent containers along the line 14 shown in dashed lines, the extinguishing agent included in the containers would, after detonation, affect only the furthest-advanced area 17 of the fire front 8, whereas no extinguishing effect would be achieved in the areas 15, 16. In contrast to this, the flexible extinguishing agent hose 2 enables adaptation of the firefighting line to the configuration of the flame front 8, and thus highly effective use of the extinguishing agent. Moreover, the extinguishing device can be brought into use in the shortest time, as the hose 2 can be laid out in front of the fire front 8 like a normal C hose, filled with extinguishing agent 10, and exploded by detonation of the explosive. Thus, due to the surface enlargement of the extinguishing agent as a result of atomisation to form a fine mist, an optimum degree of effectiveness of the amount of extinguishing agent used can be achieved.

Furthermore, use of the method according to the invention is ecologically harmless. The use of extinguishing agent leaves scarcely any traces behind it, and the loss of biomass may be reduced to a minimum by the high efficiency of the method.

This Sheet Has Been Replaced



Fig. 7 shows an example for a stationary application of the extinguishing device, in the protection of specific objects. Shown is a diagrammatic cross-section of an oil tank 12, which has level with its upper edge 13 a surrounding bracket-like carrier 6 of angular cross-section. Resting on the carrier 6 is the hose 2, filled with extinguishing agent. The position of the explosive cord 4, not shown here, is of secondary importance in this case. Alignment of the explosive and extinguishing effect in the direction of the arrow 7 is achieved in this embodiment by the shielding of the hose on the rear side by the carrier 6. The extinguishing device is automatically detonated by sensors when the fuel in the tank 12 ignites. Immediately after the detonation the mist of extinguishing agent is laid like a lid over the burning fuel, and extinguishes the fire in the way described above. The stationary application thus described for the extinguishing device may of course also be transferred to the protection of high-level shelving in warehouses or the like.

Fig. 8 shows a diagrammatic plan view of an airport runway 18, with an aircraft 19 located thereon. The area on a runway 18 upon which an aircraft 19 comes to a halt after an emergency landing, is termed a critical area 20, which is indicated here by a dashed/dotted line. This critical area is approximately 600 to 1000 metres long, and its position can be generally predicted for every aircraft type. To the left and right of the runway 18 are for example respectively 5



lengths of hoses 21, in ten segments 22 to 31 in all. Depending on where the aircraft 19 comes to a halt during an emergency landing, the corresponding segments 22 to 31 are activated. As a plurality of such hoses 21 may be arranged parallel next to one another, a second
5 row of hoses (not shown here) could be used as a so-called "second alarm wave", which will be activated if the supply of extinguishing agent in the extinguishing vehicles is exhausted.


10

15

20



This Sheet Has Been Replaced

**CLAIMS**

1. Device for extinguishing fires, with a container for receiving an extinguishing agent, and with an explosive in or on said container, by means of the detonation of which the extinguishing agent is atomised to form a mist and is applied to the fire, characterised in that the container is a flexible hose closable at both ends.
2. Device according to claim 1, characterised in that the explosive is in the form of a flexible explosive cord which extends in the longitudinal direction of the hose.
3. Device according to claim 1, characterised in that the explosive is in the form of discrete linear explosive charges, and is distributed at regular intervals.
4. Device according to one of claims 1 to 3, characterised in that the hose comprises a thin-walled but resistant material.



This Sheet Has Been Replaced



5. Device according to one of claims 1 to 4,

characterised in that

the hose comprises a material reflective of radiant heat, or has a protective coating for this purpose.

6. Device according to one of claims 1 to 5,

characterised in that

the explosive is located at a distance of approximately one-third of the hose diameter away from the ground or from a retaining means upon which the hose rests.

7. Device according to one of claims 1 to 6,

characterised in that

the hose is disposed with the explosive on a longitudinally-extended carrier which is for example shell-shaped or angled in cross-section.

8. Use of the device according to one or more of claims 1 to 7 as a fire-protection device for specific objects, for stationery installations or devices.

9. Use of the device according to one or more of claims 1 to 7 for dust-abatement during blasting operations,

characterised in that

the hose is laid at least partly around the object to be blasted, is filled with water and is detonated by ignition of the explosive when the dust front arises.



10. Use of the device according to one or more of claims 1 to 7 as a preventive fire-protection device at or on an aircraft runway, or an aircraft parking area, characterised in that

the hose is laid out at least partly along the runway or around the parking area to be protected, is filled with the extinguishing agent, and is detonated by ignition of the explosive when a fire risk occurs.

11. Method of extinguishing forest or terrain fires with a device according to one or more of claims 1 to 7,

characterised in that

the hose is laid out in front of the flame front, is filled with the extinguishing agent and is detonated by ignition of the explosive.

This Sheet Has Been Replaced

