

SOLID-STATE LIGHT EMITTING DEVICE HAVING CONTROLLABLE MULTIPHASE REACTIVE POWER

BACKGROUND OF THE INVENTION

5 (a) Field of the Invention

The present invention utilizes a three-phase or multiphase AC power source, and the electric power of each phase respectively drives its corresponding solid-state light emitting member, and the solid-state light emitting members respectively driven by each phase power are arranged
10 adjacently or arranged with an overlapping means, so that the light of the individual solid-state light emitting members respectively driven by the multiphase power source and arranged adjacently or arranged with an overlapping means can reduce the brightness pulse through synthetic illumination; and through being controlled by a solid-state switch device for
15 controlling AC conductivity phase angle (1000) installed on the power source of each phase, when the illumination brightness of corresponding solid-state light emitting member is lower than that of other solid-state light emitting members arranged adjacently or arranged with an overlapping means, the power source is cut for saving energy.

20 (b) Description of the Prior Art

One primary disadvantage of the conventional single phase AC power lamp is that the illumination brightness of the driven solid-state light emitting member is in a pulse state due to the voltage pulse of the AC power source; and in a multiphase AC power source, each phase power
25 respectively drives individual solid-state light emitting member, because each phase power belongs to different phase, the peak values of different phase voltages are different at the same temporary time period, thereby the individual solid-state light emitting members respectively driven by each phase power generate the optical energy with different brightness for
30 achieving a synthetic illumination, so the brightness pulse is reduced,

wherein the driving power of the solid-state light emitting member with lower brightness would be formed as reactive power.

SUMMARY OF THE INVENTION

5 The present invention utilizes a three-phase or multiphase AC power source, and each phase power respectively drives individual solid-state light emitting members arranged adjacently or arranged with an overlapping means, so that the synthetic illumination brightness is overlapped through the illumination brightness waveforms generated by the AC power voltage
10 of each phase, thereby the synthetic pulse rate of illumination brightness can be lowered, and the sine waveform voltages at different phases between each power source enable the individual solid-state light emitting members respectively driven by each phase power and arranged adjacently or arranged with an overlapping means generate the optical energy having
15 different brightness with respect to the instant value of the voltage waveform. When the individual solid-state light emitting members having different brightness and arranged adjacently or arranged with an overlapping means emit light, the power passing through the individual solid-state light emitting member having a relatively low brightness is defined as reactive
20 power. The solid-state light emitting device having controllable multiphase reactive power, provided by the present invention, utilizes a solid-state switch device for controlling AC conductivity phase angle (1000) for controlling the reactive power to be cut so as to save power, and to further regulate the current and voltage supplied to the individual solid-state light
25 emitting member.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a synthetic illumination pulse waveform and current waveform showing utilizing a three-phase AC power source and each phase
30 power respectively driving individual solid-state light emitting members

arranged adjacently or arranged with an overlapping means.

FIG. 2 is a synthetic illumination pulse waveform and current waveform showing utilizing the three-phase AC power source and each phase power being regulated by the solid-state switch device for controlling
5 AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members arranged adjacently or arranged with an overlapping means.

FIG. 3 is a circuit schematic view of utilizing the three-phase AC power source and each phase power being regulated by the solid-state switch
10 device for controlling AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members connected in a Delta (Δ) format and arranged adjacently or arranged with an overlapping means.

FIG. 4 is a circuit schematic view of utilizing the three-phase AC power source and each phase power being regulated by the solid-state switch
15 device for controlling AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members connected in an Wye (Y) format and arranged adjacently or arranged with an overlapping means.

FIG. 5 is a circuit schematic view of utilizing a three-phase four-wire AC power source and each phase power being regulated by the solid-state
20 switch device for controlling AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members connected in an Wye (Y) format and arranged adjacently or arranged with an overlapping means.

FIG. 6 is the circuit schematic view in which each phase of the
25 three-phase AC power source being individually connected in parallel to a circuit device in series connected by the AC current limiting circuit device (Z10), the AC solid-state light emitting member and the AC terminal of single-phase bridge rectifier (BR100), then the DC output terminal of each phase of single-phase bridge rectifier (BR100) being homo-polar connected
30 in parallel with the solid-state switch device for controlling electric

conduction phase angle (2000).

FIG. 7 is the circuit schematic view in which a circuit device in series connected by the AC current limiting circuit device (Z10), the AC solid-state light emitting member and the AC terminal of single-phase bridge rectifier (BR100) being individually installed in parallel between each phase of R, S, and T of three-phase four-wire AC power source and the neutral wire of three-phase four-wire AC power source (N), then the DC output terminal of each phase of single-phase bridge rectifier (BR100) being homo-polar connected in parallel with the solid-state switch device for controlling electric conduction phase angle (2000).

DESCRIPTION OF MAIN COMPONENT SYMBOLS

(101)、(102)、(103) : Solid-state light emitting member

(1000) : Solid-state switch device for controlling AC conductivity phase angle

(2000) : Solid-state switch device for controlling electric conduction phase angle

(BR100) : Single-phase bridge rectifier

(Va)、(Vb)、(Vc) : Voltage waveform of the three-phase AC power source respectively driving individual solid-state light emitting members arranged adjacently or arranged with an overlapping means

(Ia)、(Ib)、(Ic) : Current waveform of the three-phase AC power source respectively driving individual solid-state light emitting members arranged adjacently or arranged with an overlapping means

(e) : Synthetic light waveform of the three-phase AC power source respectively driving individual solid-state light emitting members arranged adjacently or arranged with an overlapping means

(Vda)、(Vdb)、(Vdc) : Voltage waveform of the three-phase AC power source being regulated by the solid-state switch device for controlling AC conductivity phase angle (1000) then respectively driving individual

solid-state light emitting members arranged adjacently or arranged with an overlapping means

(Ida)、(Idb)、(Idc) : Current waveform of the three-phase AC power source being regulated by the solid-state switch device for controlling AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members arranged adjacently or arranged with an overlapping means

(de) : Synthetic light waveform of the three-phase AC power source being regulated by the solid-state switch device for controlling AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members arranged adjacently or arranged with an overlapping means

(COM) : Common connection end

(ECU) : Electric power control unit

(N) : Neutral wire of three-phase four-wire AC power source

(R)、(S)、(T) : Three-phase AC power wire

(Z10) : AC current limiting circuit device

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

One primary disadvantage of the conventional single phase AC power lamp is that the illumination brightness of the driven solid-state light emitting member is in a pulse state due to the voltage pulse of the AC power source; and in a multiphase AC power source, each phase power respectively drives individual solid-state light emitting member, because each phase power belongs to different phase, the peak values of different phase voltages are different at the same temporary time period, thereby the individual solid-state light emitting members respectively driven by each phase power generate the optical energy with different brightness for achieving a synthetic illumination, so the brightness pulse is reduced, wherein the driving power of the solid-state light emitting member with

lower brightness would be formed as reactive power;

FIG. 1 is a synthetic illumination pulse waveform and current waveform showing utilizing a three-phase AC power source and each phase power respectively driving individual solid-state light emitting members arranged adjacently or arranged with an overlapping means.

As shown in FIG. 1, wherein:

(Va), (Vb) and (Vc) are voltage waveforms of the three-phase AC power source respectively driving individual solid-state light emitting members arranged adjacently or arranged with an overlapping means;

(Ia), (Ib) and (Ic) are current waveforms of the three-phase AC power source respectively driving individual solid-state light emitting members arranged adjacently or arranged with an overlapping means;

(e) is a synthetic illumination waveform of the three-phase AC power source respectively driving individual solid-state light emitting members arranged adjacently or arranged with an overlapping means;

The present invention utilizes a three-phase or multiphase AC power source, and each phase power respectively drives individual solid-state light emitting members arranged adjacently or arranged with an overlapping means, so that the synthetic illumination brightness is overlapped through the illumination brightness waveforms generated by the AC power voltage of each phase, thereby synthetic pulse rate of illumination brightness can be lowered, and the sine waveform voltage at different phase between each power source enables the individual solid-state light emitting members respectively driven by each phase power and arranged adjacently or arranged with an overlapping means generate the optical energy having different brightness with respect to the instant value of the voltage waveform. When the individual solid-state light emitting members having different brightness and arranged adjacently or arranged with an overlapping means emit light, the power passing through the individual solid-state light emitting member having a relatively low brightness is defined as reactive

power. The solid-state light emitting device having controllable multiphase reactive power, provided by the present invention, utilizes a solid-state switch device for controlling AC conductivity phase angle (1000) for controlling the reactive power to be cut so as to save power, and to further
5 regulate the current and voltage supplied to the individual solid-state light emitting member.

The solid-state light emitting device having controllable multiphase reactive power adopts a three-phase AC power source, and the electric power of each phase respectively drives individual solid-state light emitting
10 members arranged adjacently or arranged with an overlapping means for synthetic illumination, so that the pulse of illumination brightness is reduced, and a solid-state switch device for controlling AC conductivity phase angle (1000) is connected in series with each phase for saving reactive power, and the current and voltage supplied to the individual solid-state light
15 emitting member can be further regulated;

FIG. 2 is a synthetic illumination pulse waveform and current waveform showing utilizing the three-phase AC power source and each phase power being regulated by the solid-state switch device for controlling AC conductivity phase angle (1000) then respectively driving individual
20 solid-state light emitting members arranged adjacently or arranged with an overlapping means.

As shown in FIG. 2, wherein:

(Vda), (Vdb) and (Vdc) are voltage waveforms of the three-phase AC power source being regulated by the solid-state switch device for controlling
25 AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members arranged adjacently or arranged with an overlapping means;

(Ida), (Idb) and (Idc) are current waveforms of the three-phase AC power source being regulated by the solid-state switch device for controlling
30 AC conductivity phase angle (1000) then respectively driving individual

solid-state light emitting members arranged adjacently or arranged with an overlapping means;

(de) is a synthetic illumination waveform of the three-phase AC power source being regulated by the solid-state switch device for controlling AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members arranged adjacently or arranged with an overlapping means;

FIG. 3 is a circuit schematic view of utilizing the three-phase AC power source and each phase power being regulated by the solid-state switch device for controlling AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members connected in a Delta (Δ) format and arranged adjacently or arranged with an overlapping means; as shown in FIG. 3, it mainly consists of:

--AC solid-state light emitting member (101), (102), (103): constituted by two or more than two AC-power driven solid-state light emitting members, including a light emitting diode (LED) or an organic light emitting diode (OLED) provided as a foundational light emitting member for being driven by AC power source, or including other solid-state light emitting member capable of being driven by AC power source;

The AC-power driven solid-state light emitting member (102) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), then connected in parallel between the three-phase AC power wire (S) and the three-phase AC power wire (T);

The AC-power driven solid-state light emitting member (103) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), then connected in parallel between the three-phase AC power wire (T) and the three-phase AC power wire (R);

--AC current limiting circuit device (Z10): constituted by one or more

than one of the following circuit structures, including:

1) Regulating the driving current of the AC solid-state light emitting member (LED) by increasing/decreasing the reactive power conductivity angle controlled by the solid-state switch device for controlling AC conductivity phase angle (1000);

2) One or more than one of resistant type impedance member, induction type impedance member or capacitor type impedance member being connected in series, in parallel or in series and parallel;

3) The control circuit structured by a solid-state semiconductor circuit which performs analog or chopper type constant current or limiting current to the solid-state light emitting member;

4) AC stabilizing transformer;

5) AC constant current output transformer;

-- Solid-state switch device for controlling AC conductivity phase angle (1000): constituted by one or more than one of the following circuit structures:

1) A thyristor power component capable of controlling conductivity phase angle, for example TRIAC (Tri-Electrode AC Switch), SCR (Silicon Controlled Rectifier) or GTO (Gate Turn-off Thyristor) serving as an active component, and through the operations of the voltage comparison circuit between each phase voltage from the each phase voltage detection circuit, the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component is enabled to be controlled;

2) A solid-state switch device composed of a field effect power component, for example MOSFET (Metal Oxide Semiconductor Field Effect Transistor) or IGBT (Insulated Gate Bipolar Transistor) serving as the active component, and through the operations of the voltage comparison circuit between each phase voltage from the voltage detection circuit of multiphase power source, the driving circuit of the field effect component is controlled, so as to control the control timing of both or at least one of the

turn-on phase angle and the turn-off phase angle of the field effect component;

3) With properties of the zener voltage of the zener diode, or with the voltage forward drop feature of the diode, the zener diode or the diode is
5 connected in series between the gate of the thyristor and the voltage source, so as to set the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component during the power source performing the voltage variation in a sine waveform;

4) Through the voltage of the used AC power source, to set the
10 operations of the turn-on phase angle and the turn-off phase angle of the solid-state light emitting member according to the voltage forward (VF) feature of the AC solid-state light emitting member itself (LED), during the power source performing the voltage variation in a sine waveform;

--Electric power control unit (ECU): according to the internal setting of
15 the electric control unit (ECU) or receiving external controls, and referring to the voltage of power source and the current passing through the AC current limiting circuit device (Z10), for controlling the turn-on phase angle of the solid-state switch device for controlling AC conductivity phase angle (1000) is controlled, so as to regulate the voltage and current passing
20 through the solid-state light emitting member;

The illumination waveform and current waveform diagrams obtained during the operation disclosed in the embodiment illustrated in FIG. 3 are the same as what is disclosed in FIG. 2.

FIG. 4 is a circuit schematic view of utilizing the three-phase AC power
25 source and each phase power being regulated by the solid-state switch device for controlling AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members connected in an Wye (Y) format and arranged adjacently or arranged with an overlapping means; as shown in FIG. 4, it mainly consists of:

30 --AC solid-state light emitting member (101), (102), (103): constituted

by two or more than two AC-power driven solid-state light emitting members, including a light emitting diode (LED) or an organic light emitting diode (OLED) provided as a foundational light emitting member for being driven by AC power source, or including other solid-state light emitting member capable of being driven by AC power source;

--The AC-power driven solid-state light emitting member (101), the AC-power driven solid-state light emitting member (102) and the AC-power driven solid-state light emitting member (103) are connected in the Wye (Y) format at the common connection end (COM);

10 The non-common connection end of the AC-power driven solid-state light emitting member (101) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), and after the series connection, one end thereof is connected to the three-phase AC power wire (R);

The non-common connection end of the AC-power driven solid-state light emitting member (102) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), and after
20 the series connection, one end thereof is connected to the three-phase AC power wire (S);

The non-common connection end of the AC-power driven solid-state light emitting member (103) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state
25 switch device for controlling AC conductivity phase angle (1000), and after the series connection, one end thereof is connected to the three-phase AC power wire (T);

--AC current limiting circuit device (Z10): constituted by one or more than one of the following circuit structures, including:

30 1) Regulating the driving current of the AC solid-state light emitting

member (LED) by increasing/decreasing the reactive power conductivity angle controlled by the solid-state switch device for controlling AC conductivity phase angle (1000);

2) One or more than one of resistant type impedance member, induction type impedance member or capacitor type impedance member being connected in series, in parallel or in series and parallel;

3) The control circuit structured by a solid-state semiconductor circuit which performs analog or chopper type constant current or limiting current to the solid-state light emitting member;

4) AC stabilizing transformer;

5) AC constant current output transformer;

-- Solid-state switch device for controlling AC conductivity phase angle (1000): constituted by one or more than one of the following circuit structures:

1) A thyristor power component capable of controlling conductivity phase angle, for example TRIAC (Tri-Electrode AC Switch), SCR (Silicon Controlled Rectifier) or GTO (Gate Turn-off Thyristor) serving as an active component, and through the operations of the voltage comparison circuit between each phase voltage from the each phase voltage detection circuit, the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component is enabled to be controlled;

2) A solid-state switch device composed of a field effect power component, for example MOSFET (Metal Oxide Semiconductor Field Effect Transistor) or IGBT (Insulated Gate Bipolar Transistor) serving as the active component, and through the operations of the voltage comparison circuit between each phase voltage from the voltage detection circuit of multiphase power source, the driving circuit of the field effect component is controlled, so as to control the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the field effect component

3) With properties of the zener voltage of the zener diode, or with the voltage forward drop feature of the diode, the zener diode or the diode is connected in series between the gate of the thyristor and the voltage source, so as to set the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component during the power source performing the voltage variation in a sine waveform;

4) Through the voltage of the used AC power source, to set the operations of the turn-on phase angle and the turn-off phase angle of the solid-state light emitting member according to the voltage forward (VF) feature of the AC solid-state light emitting member itself (LED), during the power source performing the voltage variation in a sine waveform;

--Electric power control unit (ECU): according to the internal setting of the electric control unit (ECU) or receiving external controls, and referring to the voltage of power source and the current passing through the AC current limiting circuit device (Z10), for controlling the turn-on phase angle of the solid-state switch device for controlling AC conductivity phase angle (1000) is controlled, so as to regulate the voltage and current passing through the solid-state light emitting member;

The illumination waveform and current waveform diagrams obtained during the operation disclosed in the embodiment illustrated in FIG. 4 are the same as what is disclosed in FIG. 2.

FIG. 5 is a circuit schematic view of utilizing a three-phase four-wire AC power source and each phase power being regulated by the solid-state switch device for controlling AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members connected in an Wye (Y) format and arranged adjacently or arranged with an overlapping means; as shown in FIG. 5, mainly consists of:

--AC solid-state light emitting member (101), (102), (103): constituted by two or more than two AC-power driven solid-state light emitting members, including a light emitting diode (LED) or an organic light

emitting diode (OLED) provided as a foundational light emitting member for being driven by AC power source, or including other solid-state light emitting member capable of being driven by AC power source constituted by two or more than two AC-power driven solid-state light emitting members, including a light emitting diode (LED) or an organic light emitting diode (OLED) provided as a foundational light emitting member for being driven by AC power source, or including other solid-state light emitting member capable of being driven by AC power source;

-- The AC-power driven solid-state light emitting member (101), the AC-power driven solid-state light emitting member (102) and the AC-power driven solid-state light emitting member (103) are connected in the Wye (Y) format at the common connection end (COM), and connected to the neutral wire (N) of the three-phase four-wire AC power source;

The non-common connection end of the AC-power driven solid-state light emitting member (101) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), and after the series connection, one end thereof is connected to the three-phase four-wire AC power wire (R);

The non-common connection end of the AC-power driven solid-state light emitting member (102) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), and after the series connection, one end thereof is connected to the three-phase four-wire AC power wire (S);

The non-common connection end of the AC-power driven solid-state light emitting member (103) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), and after the series connection, one end thereof is connected to the three-phase

four-wire AC power wire (T);

--AC current limiting circuit device (Z10): constituted by one or more than one of the following circuit structures, including:

1) Regulating the driving current of the AC solid-state light emitting member (LED) by increasing/decreasing the reactive power conductivity angle controlled by the solid-state switch device for controlling AC conductivity phase angle (1000);

2) One or more than one of resistant type impedance member, induction type impedance member or capacitor type impedance member being connected in series, in parallel or in series and parallel;

3) The control circuit structured by a solid-state semiconductor circuit which performs analog or chopper type constant current or limiting current to the solid-state light emitting member;

4) AC stabilizing transformer;

5) AC constant current output transformer;

-- Solid-state switch device for controlling AC conductivity phase angle (1000): constituted by one or more than one of the following circuit structures:

1) A thyristor power component capable of controlling conductivity phase angle, for example TRIAC (Tri-Electrode AC Switch), SCR (Silicon Controlled Rectifier) or GTO (Gate Turn-off Thyristor) serving as an active component, and through the operations of the voltage comparison circuit between each phase voltage from the each phase voltage detection circuit, the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component is enabled to be controlled;

2) A solid-state switch device composed of a field effect power component, for example MOSFET (Metal Oxide Semiconductor Field Effect Transistor) or IGBT (Insulated Gate Bipolar Transistor) serving as the active component, and through the operations of the voltage comparison circuit between each phase voltage from the voltage detection circuit of

multiphase power source, the driving circuit of the field effect component is controlled, so as to control the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the field effect component;

5 3) With properties of the zener voltage of the zener diode, or with the voltage forward drop feature of the diode, the zener diode or the diode is connected in series between the gate of the thyristor and the voltage source, so as to set the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component during the
10 power source performing the voltage variation in a sine waveform;

 4) Through the voltage of the used AC power source, to set the operations of the turn-on phase angle and the turn-off phase angle of the solid-state light emitting member according to the voltage forward (VF) feature of the AC solid-state light emitting member itself (LED), during the
15 power source performing the voltage variation in a sine waveform;

 --Electric power control unit (ECU): according to the internal setting of the electric control unit (ECU) or receiving external controls, and referring to the voltage of power source and the current passing through the AC current limiting circuit device (Z10), for controlling the turn-on phase angle
20 of the solid-state switch device for controlling AC conductivity phase angle (1000) is controlled, so as to regulate the voltage and current passing through the solid-state light emitting member;

 The illumination waveform and current waveform diagrams obtained during the operation disclosed in the embodiment illustrated in FIG. 5 are the
25 same as what is disclosed in FIG. 2.

 FIG. 6 is the circuit schematic view in which each phase of the three-phase AC power source being individually connected in parallel with a circuit device in series connected by the AC current limiting circuit device (Z10), the AC solid-state light emitting member and the AC terminal of
30 single-phase bridge rectifier (BR100), then the DC output terminal of the

single-phase bridge rectifier (BR100) of each phase being homo-polar connected in parallel with the solid-state switch device for controlling electric conduction phase angle (2000), as shown in FIG. 6, it mainly consists of:

5 --AC solid-state light emitting member (101), (102), (103): constituted by two or more than two AC-power driven solid-state light emitting members, including a light emitting diode (LED) or an organic light emitting diode (OLED) provided as a foundational light emitting member for being driven by AC power source, or including other solid-state light
10 emitting member capable of being driven by AC power source;

 The solid-state light emitting member (101) driven by AC power is in series connected to the AC current limiting circuit device (Z10) and in series connected to the AC terminal of single-phase bridge rectifier (BR100), then connected in parallel between the three-phase AC power wire (R) and the
15 three-phase AC power wire (T);

 The solid-state light emitting member (102) driven by AC power is in series connected to the AC current limiting circuit device (Z10) and in series connected to the AC terminal of single-phase bridge rectifier (BR100), then connected in parallel between the three-phase AC power wire (S) and the
20 three-phase AC power wire (R);

 The solid-state light emitting member (103) driven by AC power is in series connected to the AC current limiting circuit device (Z10) and in series connected to the AC terminal of single-phase bridge rectifier (BR100), then connected in parallel between the three-phase AC power wire (T) and the
25 three-phase AC power wire (S);

 --AC current limiting circuit device (Z10): constituted by one or more than one of the following circuit structures, including:

 1) Regulating the driving current of the AC solid-state light emitting member (LED) by increasing/decreasing the reactive power conductivity
30 angle controlled by the solid-state switch device for controlling AC

conductivity phase angle (1000);

2) One or more than one of resistant type impedance member, induction type impedance member or capacitor type impedance member being connected in series, in parallel or in series and parallel;

5 3) The control circuit structured by a solid-state semiconductor circuit which performs analog or chopper type constant current or limiting current to the solid-state light emitting member;

4) AC stabilizing transformer;

5) AC constant current output transformer;

10 --Solid-state switch device for controlling electric conduction phase angle (2000): connected in parallel between the positive and negative terminals of each set of single-phase bridge rectifier (BR100), controlled by the electric power control unit (ECU) for performing regulation of conducting phase angle, and the solid-state switch for controlling electric
15 conduction phase angle (2000) is constituted by one or more than one of the following electric circuit structures:

1) A thyristor power component capable of controlling conductivity phase angle, for example TRIAC (Tri-Electrode AC Switch), SCR (Silicon Controlled Rectifier) or GTO (Gate Turn-off Thyristor) serving as an active
20 component, and through the operations of the voltage comparison circuit between each phase voltage from the each phase voltage detection circuit, the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component is enabled to be controlled;

2) A solid-state switch device composed of a field effect power
25 component, for example MOSFET (Metal Oxide Semiconductor Field Effect Transistor) or IGBT (Insulated Gate Bipolar Transistor) serving as the active component, and through the operations of the voltage comparison circuit between each phase voltage from the voltage detection circuit of multiphase power source, the driving circuit of the field effect component is
30 controlled, so as to control the control timing of both or at least one of the

turn-on phase angle and the turn-off phase angle of the field effect component;

3) With properties of the zener voltage of the zener diode, or with the voltage forward drop feature of the diode, the zener diode or the diode is
5 connected in series between the gate of the thyristor and the voltage source, so as to set the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component during the power source performing the voltage variation in a sine waveform;

4) Through the voltage of the used AC power source, to set the
10 operations of the turn-on phase angle and the turn-off phase angle of the solid-state light emitting member according to the voltage forward (VF) feature of the AC solid-state light emitting member itself (LED), during the power source performing the voltage variation in a sine waveform;

--Electric power control unit (ECU): according to the internal setting of
15 the electric control unit (ECU) or receiving external controls, and referring to the voltage of three-phase AC power source and the current passing through the AC current limiting circuit device (Z10), for controlling the turn-on phase angle of the solid-state switch device for controlling electric conduction phase angle (2000) connected in parallel between the positive
20 and negative terminals of each set of single-phase bridge rectifier (BR100), so as to regulate the voltage and current passing through the solid-state light emitting member;

The illumination waveform and current waveform diagrams obtained during the operation disclosed in the embodiment illustrated in FIG. 6 are the
25 same as what is disclosed in FIG. 2.

FIG. 7 is the circuit schematic view in which a circuit device in series connected by the AC current limiting circuit device (Z10), the AC solid-state light emitting member and the AC terminal of single-phase bridge rectifier (BR100) being individually installed in parallel between each phase of R, S,
30 and T of three-phase four-wire AC power source and the neutral wire of

three-phase four-wire AC power source (N), then the DC output terminal of the single-phase bridge rectifier (BR100) of each phase being homo-polar connected in parallel with the solid-state switch device for controlling electric conduction phase angle (2000); as shown in FIG. 7, it mainly
5 consists of:

--AC solid-state light emitting member (101), (102), (103): constituted by two or more than two AC-power driven solid-state light emitting members, including a light emitting diode (LED) or an organic light emitting diode (OLED) provided as a foundational light emitting member
10 for being driven by AC power source, or including other solid-state light emitting member capable of being driven by AC power source;

The AC current limiting circuit device (Z10) is in series connected to the solid-state light emitting member (101), and in series connected to the AC terminal of single-phase bridge rectifier (BR100), then connected in
15 parallel between the three-phase four-wire AC power wire (R) and the neutral wire of three-phase four-wire AC power source (N);

The AC current limiting circuit device (Z10) is in series connected to the solid-state light emitting member (102), and in series connected to the AC terminal of single-phase bridge rectifier (BR100), then connected in
20 parallel between the three-phase four-wire AC power wire (S) and the neutral wire of three-phase four-wire AC power source (N);

The AC current limiting circuit device (Z10) is in series connected to the solid-state light emitting member (103), and in series connected to the AC terminal of single-phase bridge rectifier (BR100), then connected in
25 parallel between the three-phase four-wire AC power wire (T) and the neutral wire of three-phase four-wire AC power source (N);

--AC current limiting circuit device (Z10): constituted by one or more than one of the following circuit structures, including:

1) Regulating the driving current of the AC solid-state light emitting
30 member (LED) by increasing/decreasing the reactive power conductivity

angle controlled by the solid-state switch device for controlling AC conductivity phase angle (1000);

2) One or more than one of resistant type impedance member, induction type impedance member or capacitor type impedance member
5 being connected in series, in parallel or in series and parallel;

3) The control circuit structured by a solid-state semiconductor circuit which performs analog or chopper type constant current or limiting current to the solid-state light emitting member;

4) AC stabilizing transformer;

10 5) AC constant current output transformer;

--Solid-state switch device for controlling electric conduction phase angle (2000): connected in parallel between the positive and negative terminals of each set of single-phase bridge rectifier (BR100), controlled by the electric power control unit (ECU) for performing regulation of
15 conducting phase angle, and the solid-state switch for controlling electric conduction phase angle (2000) is constituted by one or more than one of the following electric circuit structures:

1) A thyristor power component capable of controlling conductivity phase angle, for example TRIAC (Tri-Electrode AC Switch), SCR (Silicon
20 Controlled Rectifier) or GTO (Gate Turn-off Thyristor) serving as an active component, and through the operations of the voltage comparison circuit between each phase voltage from the each phase voltage detection circuit, the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component is enabled to be controlled;

25 2) A solid-state switch device composed of a field effect power component, for example MOSFET (Metal Oxide Semiconductor Field Effect Transistor) or IGBT (Insulated Gate Bipolar Transistor) serving as the active component, and through the operations of the voltage comparison circuit between each phase voltage from the voltage detection circuit of
30 multiphase power source, the driving circuit of the field effect component is

controlled, so as to control the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the field effect component;

3) With properties of the zener voltage of the zener diode, or with the voltage forward drop feature of the diode, the zener diode or the diode is connected in series between the gate of the thyristor and the voltage source, so as to set the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component during the power source performing the voltage variation in a sine waveform;

4) Through the voltage of the used AC power source, to set the operations of the turn-on phase angle and the turn-off phase angle of the solid-state light emitting member according to the voltage forward (VF) feature of the AC solid-state light emitting member itself (LED), during the power source performing the voltage variation in a sine waveform;

--Electric power control unit (ECU): according to the internal setting of the electric control unit (ECU) or receiving external controls, and referring to the voltage of three-phase four-wire AC power source and the current passing through the AC current limiting circuit device (Z10), for controlling the turn-on phase angle of the solid-state switch device for controlling electric conduction phase angle (2000) connected in parallel between the positive and negative terminals of each set of single-phase bridge rectifier (BR100), so as to regulate the voltage and current passing through the solid-state light emitting member;

The illumination waveform and current waveform diagrams obtained during the operation disclosed in the embodiment illustrated in FIG. 7 are the same as what is disclosed in FIG. 2.

In the solid-state light emitting member having controllable multiphase reactive power, when the AC solid-state light emitting members (101), (102), (103) are structured by light emitting diodes (LEDs) or organic light emitting diodes (OLEDs), including one or more than one of the following

means:

1) two or more than two light emitting diodes (LEDs) or organic light emitting diodes (OLEDs) is reverse-polarity connected in parallel; or

2) two or more than two light emitting diodes (LEDs) or organic light emitting diodes (OLEDs) is reverse-polarity connected in series then
5 respectively reverse-polarity connected in parallel with diodes; or

3) one or more than one light emitting diodes (LEDs) or organic light emitting diodes (OLEDs) is connected in series, or in parallel or in series and parallel and normal-polarity connected to an DC output end of a bridge
10 rectifying device.

In the solid-state light emitting member having controllable multiphase reactive power, when the AC solid-state light emitting members (101), (102), (103) are structured by single-way conductivity solid-state light emitting members, including one or more than one of the following means

15 1) two or more than two single-way conductivity solid-state light emitting members are reverse-polarity connected in parallel; or

2) two or more than two single-way conductivity solid-state light emitting members are reverse-polarity connected in series then respectively reverse-polarity connected in parallel with diodes; or

20 3) one or more than one single-way conductivity solid-state light emitting members are connected in series, or in parallel or in series and parallel and normal-polarity connected to a DC output end of a bridge rectifying device.

In the solid-state light emitting member having controllable multiphase reactive power, the AC solid-state light emitting members (101), (102), (103) are structured by one or more than one light emitting members in series connection, parallel connection or series and parallel connection, provided for being directly operated with an AC power source, so as to be directly operated with a AC power source.

30 According to the solid-state light emitting device having controllable

multiplephase reactive power of the present invention, the mentioned multiplephase AC power source not only includes the three-phase power source adopted in aforesaid embodiments, the same theory and principle is also applicable in an AC power source having two or more than two phases.

5

CLAIMS

1. A solid-state light emitting device having controllable multiphase reactive power, which utilizes a three-phase or multiphase AC power source, and each phase power respectively drives individual solid-state light emitting members arranged adjacently or arranged with an overlapping means, so that the synthetic illumination brightness is overlapped through the illumination brightness waveforms generated by the AC power voltage of each phase, thereby the synthetic pulse rate of illumination brightness can be lowered, and the sine waveform voltages at different phases between each power source enable the individual solid-state light emitting members respectively driven by each phase power and arranged adjacently or arranged with an overlapping means generate the optical energy having different brightness with respect to the instant value of the voltage waveform; when the individual solid-state light emitting members having different brightness and arranged adjacently or arranged with an overlapping means emit light, the power passing through the individual solid-state light emitting member having a relatively low brightness is defined as reactive power; the solid-state light emitting device having controllable multiphase reactive power, provided by the present invention, utilizes a solid-state switch device for controlling AC conductivity phase angle (1000) for controlling the reactive power to be cut so as to save power, and to further regulate the current and voltage supplied to the individual solid-state light emitting member; wherein

Each phase power of the three-phase AC power source is regulated by the solid-state switch device for controlling AC conductivity phase angle (1000) then respectively drives individual solid-state light emitting members connected in a Delta (Δ) format and arranged adjacently or arranged with an overlapping means, which mainly consist of:

--AC solid-state light emitting member (101), (102), (103): constituted by two or more than two AC-power driven solid-state light emitting

members, including a light emitting diode (LED) or an organic light emitting diode (OLED) provided as a foundational light emitting member for being driven by AC power source, or including other solid-state light emitting member capable of being driven by AC power source;

5 The AC-power driven solid-state light emitting member (101) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), then connected in parallel between the three-phase AC power wire (R) and the three-phase AC power wire (S);

10 The AC-power driven solid-state light emitting member (102) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), then connected in parallel between the three-phase AC power wire (S) and the three-phase AC power wire (T);

15 The AC-power driven solid-state light emitting member (103) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), then connected in parallel between the three-phase AC power wire (T) and the three-phase AC power wire (R);

20 --AC current limiting circuit device (Z10): constituted by one or more than one of the following circuit structures, including:

25 1) Regulating the driving current of the AC solid-state light emitting member (LED) by increasing/decreasing the reactive power conductivity angle controlled by the solid-state switch device for controlling AC conductivity phase angle (1000);

 2) One or more than one of resistant type impedance member, induction type impedance member or capacitor type impedance member being connected in series, in parallel or in series and parallel;

30 3) The control circuit structured by a solid-state semiconductor circuit which performs analog or chopper type constant current or limiting

current to the solid-state light emitting member;

4) AC stabilizing transformer;

5) AC constant current output transformer;

5 -- Solid-state switch device for controlling AC conductivity phase angle (1000): constituted by one or more than one of the following circuit structures:

10 1) A thyristor power component capable of controlling conductivity phase angle, for example TRIAC (Tri-Electrode AC Switch), SCR (Silicon Controlled Rectifier) or GTO (Gate Turn-off Thyristor) serving as an active component, and through the operations of the voltage comparison circuit between each phase voltage from the each phase voltage detection circuit, the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component is enabled to be controlled;

15 2) A solid-state switch device composed of a field effect power component, for example MOSFET (Metal Oxide Semiconductor Field Effect Transistor) or IGBT (Insulated Gate Bipolar Transistor) serving as the active component, and through the operations of the voltage comparison circuit between each phase voltage from the voltage detection circuit of multiphase power source, the driving circuit of the field effect component is controlled, so as to control the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the field effect component;

25 3) With properties of the zener voltage of the zener diode, or with the voltage forward drop feature of the diode, the zener diode or the diode is connected in series between the gate of the thyristor and the voltage source, so as to set the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component during the power source performing the voltage variation in a sine waveform;

30

4) Through the voltage of the used AC power source, to set the operations of the turn-on phase angle and the turn-off phase angle of the solid-state light emitting member according to the voltage forward (VF) feature of the AC solid-state light emitting member itself (LED), during the power source performing the voltage variation in a sine waveform;

--Electric power control unit (ECU): according to the internal setting of the electric control unit (ECU) or receiving external controls, and referring to the voltage of power source and the current passing through the AC current limiting circuit device (Z10), for controlling the turn-on phase angle of the solid-state switch device for controlling AC conductivity phase angle (1000) is controlled, so as to regulate the voltage and current passing through the solid-state light emitting member.

2. A solid-state light emitting device having controllable multiphase reactive power as claimed in claim 1, wherein each phase power of the three-phase AC power source is regulated by the solid-state switch device for controlling AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members connected in an Wye (Y) format and arranged adjacently or arranged with an overlapping means, which mainly consist of:

--AC solid-state light emitting member (101), (102), (103): constituted by two or more than two AC-power driven solid-state light emitting members, including a light emitting diode (LED) or an organic light emitting diode (OLED) provided as a foundational light emitting member for being driven by AC power source, or including other solid-state light emitting member capable of being driven by AC power source;

--The AC-power driven solid-state light emitting member (101), the AC-power driven solid-state light emitting member (102) and the AC-power driven solid-state light emitting member (103) are connected in the Wye (Y) format at the common connection end (COM);

The non-common connection end of the AC-power driven solid-state

light emitting member (101) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), and after the series connection, one end thereof is connected to the three-phase AC power wire (R);

The non-common connection end of the AC-power driven solid-state light emitting member (102) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), and after the series connection, one end thereof is connected to the three-phase AC power wire (S);

The non-common connection end of the AC-power driven solid-state light emitting member (103) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), and after the series connection, one end thereof is connected to the three-phase AC power wire (T);

--AC current limiting circuit device (Z10): constituted by one or more than one of the following circuit structures, including:

- 1) Regulating the driving current of the AC solid-state light emitting member (LED) by increasing/decreasing the reactive power conductivity angle controlled by the solid-state switch device for controlling AC conductivity phase angle (1000);
- 2) One or more than one of resistant type impedance member, induction type impedance member or capacitor type impedance member being connected in series, in parallel or in series and parallel;
- 3) The control circuit structured by a solid-state semiconductor circuit which performs analog or chopper type constant current or limiting current to the solid-state light emitting member;
- 4) AC stabilizing transformer;

5) AC constant current output transformer;

-- Solid-state switch device for controlling AC conductivity phase angle (1000): constituted by one or more than one of the following circuit structures:

5 1) A thyristor power component capable of controlling conductivity phase angle, for example TRIAC (Tri-Electrode AC Switch), SCR (Silicon Controlled Rectifier) or GTO (Gate Turn-off Thyristor) serving as an active component, and through the operations of the voltage comparison circuit between each phase voltage from the each phase voltage detection circuit, the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component is enabled to be controlled;

15 2) A solid-state switch device composed of a field effect power component, for example MOSFET (Metal Oxide Semiconductor Field Effect Transistor) or IGBT (Insulated Gate Bipolar Transistor) serving as the active component, and through the operations of the voltage comparison circuit between each phase voltage from the voltage detection circuit of multiphase power source, the driving circuit of the field effect component is controlled, so as to control the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the field effect component;

25 3) With properties of the zener voltage of the zener diode, or with the voltage forward drop feature of the diode, the zener diode or the diode is connected in series between the gate of the thyristor and the voltage source, so as to set the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component during the power source performing the voltage variation in a sine waveform;

30 4) Through the voltage of the used AC power source, to set the operations of the turn-on phase angle and the turn-off phase angle of the

solid-state light emitting member according to the voltage forward (VF) feature of the AC solid-state light emitting member itself (LED), during the power source performing the voltage variation in a sine waveform;

--Electric power control unit (ECU): according to the internal setting of the electric control unit (ECU) or receiving external controls, and referring to the voltage of power source and the current passing through the AC current limiting circuit device (Z10), for controlling the turn-on phase angle of the solid-state switch device for controlling AC conductivity phase angle (1000) is controlled, so as to regulate the voltage and current passing through the solid-state light emitting member.

3. A solid-state light emitting device having controllable multiphase reactive power as claimed in claim 1, wherein each phase power of the three-phase four-wire AC power source is regulated by the solid-state switch device for controlling AC conductivity phase angle (1000) then respectively driving individual solid-state light emitting members connected in an Wye (Y) format and arranged adjacently or arranged with an overlapping means, which mainly consist of:

--AC solid-state light emitting member (101), (102), (103): constituted by two or more than two AC-power driven solid-state light emitting members, including a light emitting diode (LED) or an organic light emitting diode (OLED) provided as a foundational light emitting member for being driven by AC power source, or including other solid-state light emitting member capable of being driven by AC power source constituted by two or more than two AC-power driven solid-state light emitting members, including a light emitting diode (LED) or an organic light emitting diode (OLED) provided as a foundational light emitting member for being driven by AC power source, or including other solid-state light emitting member capable of being driven by AC power source;

-- The AC-power driven solid-state light emitting member (101), the AC-power driven solid-state light emitting member (102) and the

AC-power driven solid-state light emitting member (103) are connected in the Wye (Y) format at the common connection end (COM), and connected to the neutral wire (N) of the three-phase four-wire AC power source;

5 The non-common connection end of the AC-power driven solid-state light emitting member (101) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), and after the series connection, one end thereof is connected to the three-phase
10 four-wire AC power wire (R);

 The non-common connection end of the AC-power driven solid-state light emitting member (102) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state switch device for controlling AC conductivity phase angle (1000), and
15 after the series connection, one end thereof is connected to the three-phase four-wire AC power wire (S);

 The non-common connection end of the AC-power driven solid-state light emitting member (103) is connected in series with the AC current limiting circuit device (Z10) and connected in series with the solid-state
20 switch device for controlling AC conductivity phase angle (1000), and after the series connection, one end thereof is connected to the three-phase four-wire AC power wire (T);

--AC current limiting circuit device (Z10): constituted by one or more than one of the following circuit structures, including:

- 25 1) Regulating the driving current of the AC solid-state light emitting member (LED) by increasing/decreasing the reactive power conductivity angle controlled by the solid-state switch device for controlling AC conductivity phase angle (1000);
- 2) One or more than one of resistant type impedance member, induction
30 type impedance member or capacitor type impedance member being

connected in series, in parallel or in series and parallel;

3) The control circuit structured by a solid-state semiconductor circuit which performs analog or chopper type constant current or limiting current to the solid-state light emitting member;

5 4) AC stabilizing transformer;

5) AC constant current output transformer;

-- Solid-state switch device for controlling AC conductivity phase angle (1000): constituted by one or more than one of the following circuit structures:

10 1) A thyristor power component capable of controlling conductivity phase angle, for example TRIAC (Tri-Electrode AC Switch), SCR (Silicon Controlled Rectifier) or GTO (Gate Turn-off Thyristor) serving as an active component, and through the operations of the voltage comparison circuit between each phase voltage from the each phase voltage detection circuit, the control timing of both or at least one of the
15 turn-on phase angle and the turn-off phase angle of the thyristor component is enabled to be controlled;

2) A solid-state switch device composed of a field effect power component, for example MOSFET (Metal Oxide Semiconductor Field
20 Effect Transistor) or IGBT (Insulated Gate Bipolar Transistor) serving as the active component, and through the operations of the voltage comparison circuit between each phase voltage from the voltage detection circuit of multiphase power source, the driving circuit of the field effect component is controlled, so as to control the control timing of
25 both or at least one of the turn-on phase angle and the turn-off phase angle of the field effect component;

3) With properties of the zener voltage of the zener diode, or with the voltage forward drop feature of the diode, the zener diode or the diode is connected in series between the gate of the thyristor and the voltage
30 source, so as to set the control timing of both or at least one of the turn-on

phase angle and the turn-off phase angle of the thyristor component during the power source performing the voltage variation in a sine waveform;

4) Through the voltage of the used AC power source, to set the operations of the turn-on phase angle and the turn-off phase angle of the solid-state light emitting member according to the voltage forward (VF) feature of the AC solid-state light emitting member itself (LED), during the power source performing the voltage variation in a sine waveform;

--Electric power control unit (ECU): according to the internal setting of the electric control unit (ECU) or receiving external controls, and referring to the voltage of power source and the current passing through the AC current limiting circuit device (Z10), for controlling the turn-on phase angle of the solid-state switch device for controlling AC conductivity phase angle (1000) is controlled, so as to regulate the voltage and current passing through the solid-state light emitting member.

4. A solid-state light emitting device having controllable multiphase reactive power as claimed in claim 1, wherein each phase of the three-phase AC power source is individually connected in parallel with a circuit device in series connected by the AC current limiting circuit device (Z10), the AC solid-state light emitting member and the AC terminal of single-phase bridge rectifier (BR100), then the DC output terminal of the single-phase bridge rectifier (BR100) of each phase is homo-polar connected in parallel with the solid-state switch device for controlling electric conduction phase angle (2000), and it mainly consists of:

--AC solid-state light emitting member (101), (102), (103): constituted by two or more than two AC-power driven solid-state light emitting members, including a light emitting diode (LED) or an organic light emitting diode (OLED) provided as a foundational light emitting member for being driven by AC power source, or including other solid-state light emitting member capable of being driven by AC power source;

The solid-state light emitting member (101) driven by AC power is in series connected to the AC current limiting circuit device (Z10) and in series connected to the AC terminal of single-phase bridge rectifier (BR100), then connected in parallel between the three-phase AC power wire (R) and the three-phase AC power wire (T);

The solid-state light emitting member (102) driven by AC power is in series connected to the AC current limiting circuit device (Z10) and in series connected to the AC terminal of single-phase bridge rectifier (BR100), then connected in parallel between the three-phase AC power wire (S) and the three-phase AC power wire (R);

The solid-state light emitting member (103) driven by AC power is in series connected to the AC current limiting circuit device (Z10) and in series connected to the AC terminal of single-phase bridge rectifier (BR100), then connected in parallel between the three-phase AC power wire (T) and the three-phase AC power wire (S);

--AC current limiting circuit device (Z10): constituted by one or more than one of the following circuit structures, including:

1) Regulating the driving current of the AC solid-state light emitting member (LED) by increasing/decreasing the reactive power conductivity angle controlled by the solid-state switch device for controlling AC conductivity phase angle (1000);

2) One or more than one of resistant type impedance member, induction type impedance member or capacitor type impedance member being connected in series, in parallel or in series and parallel;

3) The control circuit structured by a solid-state semiconductor circuit which performs analog or chopper type constant current or limiting current to the solid-state light emitting member;

4) AC stabilizing transformer;

5) AC constant current output transformer;

--Solid-state switch device for controlling electric conduction phase angle

(2000): connected in parallel between the positive and negative terminals of each set of single-phase bridge rectifier (BR100), controlled by the electric power control unit (ECU) for performing regulation of conducting phase angle, and the solid-state switch for controlling electric conduction phase angle (2000) is constituted by one or more than one of the following electric circuit structures:

1) A thyristor power component capable of controlling conductivity phase angle, for example TRIAC (Tri-Electrode AC Switch), SCR (Silicon Controlled Rectifier) or GTO (Gate Turn-off Thyristor) serving as an active component, and through the operations of the voltage comparison circuit between each phase voltage from the each phase voltage detection circuit, the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component is enabled to be controlled;

2) A solid-state switch device composed of a field effect power component, for example MOSFET (Metal Oxide Semiconductor Field Effect Transistor) or IGBT (Insulated Gate Bipolar Transistor) serving as the active component, and through the operations of the voltage comparison circuit between each phase voltage from the voltage detection circuit of multiphase power source, the driving circuit of the field effect component is controlled, so as to control the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the field effect component;

3) With properties of the zener voltage of the zener diode, or with the voltage forward drop feature of the diode, the zener diode or the diode is connected in series between the gate of the thyristor and the voltage source, so as to set the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component during the power source performing the voltage variation in a sine waveform;

4) Through the voltage of the used AC power source, to set the operations of the turn-on phase angle and the turn-off phase angle of the solid-state light emitting member according to the voltage forward (VF) feature of the AC solid-state light emitting member itself (LED), during the power source performing the voltage variation in a sine waveform;

--Electric power control unit (ECU): according to the internal setting of the electric control unit (ECU) or receiving external controls, and referring to the voltage of three-phase AC power source and the current passing through the AC current limiting circuit device (Z10), for controlling the turn-on phase angle of the solid-state switch device for controlling electric conduction phase angle (2000) connected in parallel between the positive and negative terminals of each set of single-phase bridge rectifier (BR100), so as to regulate the voltage and current passing through the solid-state light emitting member

5. A solid-state light emitting device having controllable multiphase reactive power as claimed in claim 1, wherein a circuit device in series connected by the AC current limiting circuit device (Z10), the AC solid-state light emitting member and the AC terminal of single-phase bridge rectifier (BR100) is individually installed in parallel between each phase of R, S, and T of three-phase four-wire AC power source and the neutral wire of three-phase four-wire AC power source (N), then the DC output terminal of the single-phase bridge rectifier (BR100) of each phase is homo-polar connected in parallel with the solid-state switch device for controlling electric conduction phase angle (2000), and it mainly consists of:

--AC solid-state light emitting member (101), (102), (103): constituted by two or more than two AC-power driven solid-state light emitting members, including a light emitting diode (LED) or an organic light emitting diode (OLED) provided as a foundational light emitting member for being driven by AC power source, or including other solid-state light emitting member capable of being driven by AC power

source;

The AC current limiting circuit device (Z10) is in series connected to the solid-state light emitting member (101), and in series connected to the AC terminal of single-phase bridge rectifier (BR100), then connected in parallel between the three-phase four-wire AC power wire (R) and the neutral wire of three-phase four-wire AC power source (N);

The AC current limiting circuit device (Z10) is in series connected to the solid-state light emitting member (102), and in series connected to the AC terminal of single-phase bridge rectifier (BR100), then connected in parallel between the three-phase four-wire AC power wire (S) and the neutral wire of three-phase four-wire AC power source (N);

The AC current limiting circuit device (Z10) is in series connected to the solid-state light emitting member (103), and in series connected to the AC terminal of single-phase bridge rectifier (BR100), then connected in parallel between the three-phase four-wire AC power wire (T) and the neutral wire of three-phase four-wire AC power source (N);

--AC current limiting circuit device (Z10): constituted by one or more than one of the following circuit structures, including:

1) Regulating the driving current of the AC solid-state light emitting member (LED) by increasing/decreasing the reactive power conductivity angle controlled by the solid-state switch device for controlling AC conductivity phase angle (1000);

2) One or more than one of resistant type impedance member, induction type impedance member or capacitor type impedance member being connected in series, in parallel or in series and parallel;

3) The control circuit structured by a solid-state semiconductor circuit which performs analog or chopper type constant current or limiting current to the solid-state light emitting member;

4) AC stabilizing transformer;

5) AC constant current output transformer;

--Solid-state switch device for controlling electric conduction phase angle (2000): connected in parallel between the positive and negative terminals of each set of single-phase bridge rectifier (BR100), controlled by the electric power control unit (ECU) for performing regulation of conducting phase angle, and the solid-state switch for controlling electric conduction phase angle (2000) is constituted by one or more than one of the following electric circuit structures:

1) A thyristor power component capable of controlling conductivity phase angle, for example TRIAC (Tri-Electrode AC Switch), SCR (Silicon Controlled Rectifier) or GTO (Gate Turn-off Thyristor) serving as an active component, and through the operations of the voltage comparison circuit between each phase voltage from the each phase voltage detection circuit, the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component is enabled to be controlled;

2) A solid-state switch device composed of a field effect power component, for example MOSFET (Metal Oxide Semiconductor Field Effect Transistor) or IGBT (Insulated Gate Bipolar Transistor) serving as the active component, and through the operations of the voltage comparison circuit between each phase voltage from the voltage detection circuit of multiphase power source, the driving circuit of the field effect component is controlled, so as to control the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the field effect component;

3) With properties of the zener voltage of the zener diode, or with the voltage forward drop feature of the diode, the zener diode or the diode is connected in series between the gate of the thyristor and the voltage source, so as to set the control timing of both or at least one of the turn-on phase angle and the turn-off phase angle of the thyristor component during the power source performing the voltage variation in a sine

waveform;

5) Through the voltage of the used AC power source, to set the operations of the turn-on phase angle and the turn-off phase angle of the solid-state light emitting member according to the voltage forward (VF) feature of the AC solid-state light emitting member itself (LED), during the power source performing the voltage variation in a sine waveform;

--Electric power control unit (ECU): according to the internal setting of the electric control unit (ECU) or receiving external controls, and referring to the voltage of three-phase four-wire AC power source and the current passing through the AC current limiting circuit device (Z10), for controlling the turn-on phase angle of the solid-state switch device for controlling electric conduction phase angle (2000) connected in parallel between the positive and negative terminals of each set of single-phase bridge rectifier (BR100), so as to regulate the voltage and current passing through the solid-state light emitting member.

6. A solid-state light emitting device having controllable multiphase reactive power as claimed in claims 1, 2, 3, 4 or 5, wherein when the AC solid-state light emitting members (101), (102), (103) are structured by light emitting diodes (LEDs) or organic light emitting diodes (OLEDs), including one or more than one of the following means:

1) two or more than two light emitting diodes (LEDs) or organic light emitting diodes (OLEDs) is reverse-polarity connected in parallel; or

2) two or more than two light emitting diodes (LEDs) or organic light emitting diodes (OLEDs) is reverse-polarity connected in series then respectively reverse-polarity connected in parallel with diodes; or

3) one or more than one light emitting diodes (LEDs) or organic light emitting diodes (OLEDs) is connected in series, or in parallel or in series and parallel and normal-polarity connected to an DC output

end of a bridge rectifying device.

7. A solid-state light emitting device having controllable multiphase reactive power as claimed in claims 1, 2, 3, 4 or 5, wherein when the AC solid-state light emitting members (101), (102), (103) are structured by single-way conductivity solid-state light emitting members, including one or more than one of the following means:

1) two or more than two single-way conductivity solid-state light emitting members are reverse-polarity connected in parallel; or

2) two or more than two single-way conductivity solid-state light emitting members are reverse-polarity connected in series then respectively reverse-polarity connected in parallel with diodes; or

3) one or more than one single-way conductivity solid-state light emitting members are connected in series, or in parallel or in series and parallel and normal-polarity connected to a DC output end of a bridge rectifying device.