

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



RTMP's copy

9702330-3

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : F02B 57/00		A1	(11) International Publication Number: WO 96/17162
			(43) International Publication Date: 8 June 1996 (06.06.96)
(21) International Application Number: PCT/AU95/00815		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, LS, MW, SD, SZ, UG).	
(22) International Filing Date: 4 December 1995 (04.12.95)			
(30) Priority Data: PM 9827 2 December 1994 (02.12.94) AU			
(71) Applicant (for all designated States except US): ADVANCED ENGINE TECHNOLOGY PTY. LTD. [AU/AU]; Alford Ebbage, 5 Hicks Street, Southport, QLD 4215 (AU).		Published With international search report.	
(72) Inventor; and (75) Inventor/Applicant (for US only): MANTHEY, Steven, Charles [AU/AU]; 490 Tallebudgera Connection Road, Currumbin Valley, QLD 4223 (AU).			
(74) Agent: AHEARN, Thomas, Gipps; Ahearns, G.P.O. Box 185, Brisbane, QLD 4001 (AU).			
		REPLACED SHEETS SG ☐ Description : paged to paged ☒ Claim(s) : paged 16 to paged 19 ☐ Drawing(s) : paged to paged ☐ Abstract : paged to paged	

(54) Title: AXIAL PISTON ROTARY ENGINE

(57) Abstract

A rotary internal combustion engine of the type having pistons mounted for reciprocatory movement in respective cylinders which are arranged in equally-spaced relationship around a longitudinal axis of rotation, said axis being the axis of rotation of an output shaft passing rotatably and sealably through apertures of respective first and second end plates of a housing within which the pistons and cylinders move as part of a rotatable rotor assembly secured to said output shaft, while the pistons are simultaneously movable reciprocally in the cylinders, cam follower means being associated with each piston and adapted to coact with undulating cam track means around the housing. Cyclical combustion of fuel in the cylinders imparts reciprocation to the pistons with resultant thrust against the cam track means so as to cause rotation of the rotor assembly and output shaft. The pistons include two sets thereof each having at least two pistons, the pistons of each set being at opposite sides of the axis of rotation of the rotor assembly and output shaft and are interconnected by piston-connection means so that the pistons of each set move in unison, the parts being so made and arranged that the piston cam follower means coact with the cam track means in a manner ensuring that movement of either set of pistons in their cylinders is in the direction opposite to the direction of movement of the other set of pistons.

