

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
1 February 2001 (01.02.2001)

PCT

(10) International Publication Number
WO 01/07713 A1

(51) International Patent Classification⁷: D21H 13/26

Surreywood Drive, Richmond, VA 23235 (US). WHITFIELD, Christopher, Roger [US/US]; 103 North Harvie Street, Richmond, VA 23220 (US).

(21) International Application Number: PCT/US00/17891

(22) International Filing Date: 29 June 2000 (29.06.2000)

(74) Agent: SHAFER, Robert, J.; E. I. Du Pont de Nemours and Company, Legal Patent Records Center, 1007 Market Street, Wilmington, DE 19898 (US).

(25) Filing Language: English

(26) Publication Language: English

(81) Designated States (*national*): AU, BR, CA, CN, CZ, IN, KR, MX, PL, RU, SG, UA, US.

(30) Priority Data:
11/208033 22 July 1999 (22.07.1999) JP

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

(71) Applicant (*for all designated States except US*): E. I. DU PONT DE NEMOURS AND COMPANY [US/US]; 1007 Market Street, Wilmington, DE 19898 (US).

Published:

— With international search report.

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): SUZUKI, Hiroyuki [JP/JP]; 637-45 Kamitomatsuricho, Utsunomiya, Tochigi 320-0051 (JP). HESSLER, Lee, James [US/US]; 8217

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 01/07713 A1

(54) Title: WHOLLY AROMATIC POLYAMIDE FIBER PAPER AND LAMINATED SHEET THEREFROM

(57) Abstract: A type of fiber paper is provided that is made of completely aromatic polyamide fiber formed by means of liquid crystal spinning. The fiber paper can be used as the base material of a substrate for electric circuit, and it can display high reliability in electric insulation under a high humidity, excellent post-heating dimensional stability, and high heat resistance.