



159159

WO 02/15339

- 1 -

PCT/EP01/08651

Electrical plug connector

The invention relates to an electrical plug connector, a cable manager for an electrical plug connector, a method for assembly of an electrical plug connector, and a tool for assembly and connection of the cores of the electrical plug connector.

EP 0 445 376 B1 discloses a plug connector for connecting a plug to electrically insulated conductors, having a housing which has a cavity to accommodate the plug, and with a first and a second set of connecting elements being provided. Each connecting element in the first set has an insulation-displacement contact for holding an insulated conductor and for making a contact connection with its core, and has a foot section. Each connecting element in the second set has a contact strip and a contact tongue, with each of the connecting elements in the second set being electrically connected via the contact tongue to the foot section of the connecting elements in the first set and extending from the first set to the cavity in order thus to make an electrical connection to the contacts fitted to the plug, and with the first and the second set of connecting elements being fixed in their position in the housing of the plug connector by guide means. The connection between the conductors and the insulation-displacement contacts is in this case made by means of known connection tools. In the process, the individual conductors or cores must be routed to the insulation-displacement contact and must be pressed into the insulation-displacement contact by means of the connection tool. One disadvantage of the known plug connector is its wide tolerances in its transmission response, which lead to major problems at high transmission rates.

The invention is thus based on the technical problem of reducing the tolerances in the transmission response of a plug connection. A further technical problem is the provision of a method for assembly of an electrical plug connector and of a tool for assembly of the plug connector, and for the connection of the cores of the electrical plug connector.

The technical problem is solved by the subject matter having the features of patent claims 1, 12, 18 and 19. Further advantageous refinements of the invention can be found in the dependent claims.

000002



G00002

To this end, the plug connector comprises a cable manager which has a through-opening and is formed on the front face with guides for cores which are intended to make contact with the insulation-displacement contacts, in which case the guides in the region of the insulation-displacement contacts are formed with recessed holders for the insulation-displacement contacts, and the cable manager can be latched to the plug connector housing. This results in a number of major advantages in comparison to the prior art, which restrict the transmission response tolerances. The guides fix the length of the cores with which contact is to be made, in a defined manner. For this purpose, the respective core is passed through the openings and is inserted into the guides. Projecting parts of the core are then cut off at the edge of the cable manager, so that the length of the cores is the same in each plug connector. Furthermore, the guides mean that the cores can each all be located in a reproducible position with respect to one another. These two facts result in a fixed value for the crosstalk. A further advantage is that, once the cores have been fitted in the cable manager, contact between them and the insulation-displacement contacts can be made simultaneously, or virtually simultaneously.

To this end, the rear face of the cable manager is formed with an incline on one side. The cable manager and plug connector housing can be latched to one another without exerting any relatively high force, by means of an essentially, U-shaped tool like a bracket, on whose lower limb face, parallel-running guides are arranged which point inward, run at right angles to the rear wall of the tool, and are designed with obliquely running guide edges in the upper region on the inside of the limbs. In this case, the inclines on the cable manager and on the tool are aligned to be complementary to one another, so that the process of pushing the tool on leads to a travel movement, by means of which the cable manager is moved in the direction of the plug connector housing, so that the insulation-displacement contacts cut through the insulation on the cores and enter the holder within the guides. The transformation ratio from the sliding movement to the travel movement can in this case be varied via the gradient of the inclines.

A guide cross is preferably arranged in the opening in the cable manager, so that the cores are also guided in a defined manner within the openings. In the case of known RJ-45 plug connections, the associated core pairs are in this case each guided in one segment of the guide

CROSS.

In order to reduce the defined crosstalk in the contact area as much as possible, the cores of different pairs are guided and made contact with at a distance from one another.

To this end, the guides run, for example, radially from the opening into the corners of the cable manager.

In another preferred embodiment, all the guides run parallel, but in different sectors of the cable manager.

In a further preferred embodiment, a hold-down device is arranged between the cable manager and the printed circuit board and allows the printed circuit board to be fixed with respect to the plug connector housing. Tensile forces on the cable, which would otherwise act on the printed circuit board, are thus absorbed.

In a further preferred embodiment, the guides are at offset levels in either direction with respect to one another, so that some of the cores make contact with one another at different times. This also results in the necessary contact forces being distributed better, so that the user requires less force for assembly and connection.

A cable grip is preferably arranged above the cable manager, in order to absorb tensile forces on the cable.

In a further preferred embodiment, the cable grip is designed with a number of parts, with the assembly tool at the same time forming a part of the cable grip.

To this end, the tool or the first part of the cable grip comprises two jaw parts which are located together and whose joint flexing can be limited by means of a spring which engages around the jaw parts and can be inserted at different points on the first part. A force-fitting connection to the cable can be produced by means of a third part, which can be latched to the first part and/or to

the spring. In addition to the force-fitting connection, this multipart cable grip also allows cables of different diameter to be centered, which in turn has a positive effect on the tolerances relating to the transmission response.

In the case of cables with a shield, the cable grip can, furthermore, be used as a universal shield contact. To this end, the first and the third parts of the cable grip are either in the form of a die-cast zinc part or a metallized plastic part, which is or can be connected to a ground plate in the plug connector housing.

The invention will be explained in more detail in the following text with reference to a preferred exemplary embodiment. In the figures:

- Figure 1 shows an exploded illustration of a plug connector,
- Figure 2 shows a perspective illustration of a cable manager from the rear face,
- Figure 3 shows a plan view of the front face of a first embodiment of a cable manager,
- Figure 4 shows a plan view of a front face of a second embodiment of a cable manager,
- Figure 5 shows a perspective illustration of a tool for assembling the plug connector, and/or a first part of a cable grip,
- Figure 6 shows a perspective illustration of a cable grip in the open state,
- Figure 7 shows a perspective illustration of a cable grip in the closed state without any cable,
- Figure 8 shows a side view of the electrical plug connector with the first part or tool partially pushed on,
- Figure 9 shows a perspective illustration of the assembled plug connector with the cable grip and cable,
- Figure 10 shows a perspective illustration of a cable manager from the rear face, and
- Figure 11 shows a plan view of the front face of a third embodiment of a cable manager.

Figure 1 shows an exploded illustration of a plug connector 1. The plug connector 1 comprises a plug connector housing 2, a printed circuit board 3, a hold-down device 4 and a cable manager 5. The plug connector housing 2 in the illustrated example is in the form of a socket housing with various latching and insertion means. The plug connector housing 2 is designed with a shielding plate 6 on the side surfaces. The printed circuit board 3 is fitted with a first set of contacts 7 on its front face and with a second set of insulation-displacement contacts 8 on its rear face. One contact 7 in the first set is in each case connected to one contact 8 in the second set. The printed circuit board 3 is then inserted into the plug connector housing 2. In the process, cylindrical pins 9 on the plug connector housing 2 pass through holes in the printed circuit board 3, so that the plug connector housing 2 and printed circuit board 3 can be adjusted and fixed with respect to one another. The contacts 7 in the first set, which are in the form of RF contacts, then project into an opening which is accessible from the front face of the plug connector housing. The hold-down device 4 is then pushed over the contacts 8 in the second set, and is latched to the plug connector housing 2. For this purpose, the hold-down device 4 is designed with latching tabs 10 on the end face, and has through-openings 11 for the insulation-displacement contacts 8. Furthermore, the hold-down device 4 is designed with two latching hooks 12, which are used for latching to the cable manager 5. Before describing this assembly process, the cable manager 5 will first of all be explained in more detail with reference to Figures 2-4.

The cable manager 5 is essentially cuboid and has a central opening 13 around which a cylindrical attachment 14 is arranged. The opening 13 extends through from the rear face 15 to the front face 16. A guide cross 17 is arranged in the opening 13, and subdivides the opening 13 into four segments. Half of the rear face 15 is in the form of an incline 18. The cable manager 5 is designed with guides 19 on the front face 16, into which the cores with which contact is to be made can be inserted. Each guide 19 is designed with a recessed holder 20. The holders 20 are in this case arranged at the same positions as the insulation-displacement contacts 8 in Figure 1. The guides 19 run either radially from the opening 13 to the edges of the cable manager 5 (as illustrated in Figure 3), or each run parallel to one another (as illustrated in Figure 4). In this case, if there are eight guides 19, as are required, by way of example, for a known RJ-45 plug connection, two guides 19 of a core pair are allocated to each quadrant. As can be seen from

Figures 3 and 4, the holders 20, and thus the insulation-displacement contacts 8 of the various pairs, are relatively far away from one another, so that the crosstalk is reduced. In preparation for the actual contact-making process, the cores are passed in pairs from the rear face 15 to the front face 16 in one segment of the guide cross 17, and are pressed into the associated guides 19 on the front face 16. In this case, colored markings can be used both on the rear face 15 and on the front face 16, in order to associate the core pairs with correct segments, and the cores with the correct guides 19. Once the cores have been pressed into the guides 19, they are cut off along the side edges. In principle, the cable manager 5 together with the plug connector housing 2 and the hold-down device 4 could now be latched to one another by finger pressure, although this would require a not inconsiderable amount of force to be used. A tool 21 is thus preferably used which, if required, can at the same time form a first part of a cable grip. This tool 21 is illustrated in perspective in Figure 5.

The tool 21 is essentially U-shaped with two side walls 22, which act as limbs. A guide 23, which points inward, is arranged on the lower face of each of the side walls 22. The two guides 23 run parallel and are at right angles to a rear wall 24. A guide edge 25, which likewise points inward and runs obliquely to the rear, is arranged on the upper face of each of the side walls 22. The guide edge 25 is in this case complementary to the incline 18 on the cable manager 5 shown in Figure 2. In order to make contact, the tool 21 is then pushed onto the incline 18 on the cable manager 5, as is shown in Figure 8, with part of the side wall 22 being cut away in the illustration. The guide 23 in this case runs parallel along one edge on the plug connector housing 2, so that the two inclines 18, 25 result in the cable manager 5 being pressed downward in the direction of the hold-down device 4. In the process, the insulation-displacement contacts 8 are pressed into the holder 20, and make contact with the cores located in the guides 19.

Furthermore, the tool 21 has two jaw parts 26 which flex jointly and are articulated in a sprung manner on a base 27 which is arranged on the upper face of the guide edges 25. There are jaw parts 26 in the form of steps at the sides. There are four openings 28, which are in the form of elongated holes, at each of the two sides on the upper face of the base 27. In the inner region, the two jaw parts 26 have pyramid-like structures 29. This tool 21 can now be used together with a spring 30, which acts as a locking means, and a closure element 31 as a cable clamp with a

defined force fit and a defined centering for cables of different diameter.

Figure 6 shows such a cable clamp. As can be seen from the illustration, the two jaw parts 26 can be pressed together to different extents by virtue of the stepped design, depending on the pair of openings 28 into which the spring 30 is inserted. In the illustrated example, the two jaw parts 26 are pressed together to the maximum extent, so that the holder formed in the region of the structures 29 has its maximum diameter. The closure element 31 is essentially U-shaped. Latching grooves 33, which act as barbs and run obliquely to the rear, are arranged on the insides of the limbs 32. The number of latching grooves 33 in this case corresponds to the number of openings 28. Furthermore, the closure element 31 has a curved attachment 34, likewise with pyramid-like structures 35 formed on the inside. A cable can now be fixed in a defined, force-fitting and centered manner by means of the cable clamp. In this case, it may be assumed that the cable clamp will be used for force-fitting connection with cables whose diameters are 6, 7, 8 or 9 mm. If it is intended to fix a 6 mm cable, then the spring 30 is first of all inserted into the first openings 28, so that the jaw parts 26 are pressed together to the maximum extent. The closure part 31 above the guide edge 25 is then pushed onto the base 27 until the rearmost latching groove 33 latches in on the spring leg of the spring 30. This is shown without a cable in Figure 7, with a part of the base 27 having been cut away in the region of the openings 28 in the illustration. The barb-like shape of the latching grooves 33 results in robust latching, with a 6 mm diameter cable held between the structures 29, 35 always being fixed with the same force fit.

For unlocking, the spring legs of the spring 30 which have been inserted into the openings 28 are pressed in the direction of the jaw parts 26, and the closure element 31 or the spring 30 is pulled out once again. If, on the other hand, a 7 mm cable is now intended to be fitted, then the spring 30 is inserted offset by one opening 28 to the rear. The stepped outside of the jaw parts 26 means that they can now be pressed together to a lesser extent. In the process, the accommodation area for a cable is widened by 0.5 mm. Furthermore, the closure element 31 is pushed on only as far as the last-but-one latching groove 33, with the distance between the latching grooves 33 likewise being 0.5 mm. The increasing diameter is thus split equally between the tool 21 and the closure element 31, so that the center point of the cable is always

located at the same point, even if the cable diameters differ. A corresponding situation applies to the increasing diameters, in that the spring 30 is offset in a corresponding manner to the rear, and the closure element 31 in each case latches on to a latching groove 33 whose width is less. When using shielded cables, the cable clamp can, furthermore, be used as a shield contact. To this end, the tool 21 and the closure element 31 are designed to be electrically conductive, with electroplated plastic parts preferably being used, in which case the tool 21 is or can be electrically connected to a ground plate in the plug connector housing 2.

Figure 9 illustrates a completely assembled plug connector 1, with a cable 36, in perspective.

Figures 10 and 11 illustrate a third embodiment of the cable manager 5. The rear face 15 is once again designed with a cylindrical attachment 14 and an incline 18. In contrast to the embodiment shown in Figure 2, the opening is not subdivided by a guide cross into four equal segments, and the channels 37-40 which extend from the front face 15 to the rear face 16 have different shapes. The two channels 37, 38 are each eye-shaped. The channel 39 is in the form of a segment of an annulus, and the channel 40 is in the form of a slot with a widened base. Furthermore, the cable manager has eight openings 41 as a result of the injection molding technique. As shown in the embodiment in Figure 4, the guides 19 are each arranged parallel to one another, with two guides each being arranged in pairs in one quadrant. The guides 19 are each designed with a clamping rib 42 towards the side edges of the cable manager 5. Furthermore, the guides 19 are designed to each have two spherical elements 43 at their ends facing the channels 37-40, which spherical elements 43 are located in the region of the openings 41 and are used to hold the cores down. A guide web 44, whose function will be explained in more detail later, is arranged between the channel 39 and the channel 40. The region between the channels 37-40 and the associated guides 19 is in each case rounded, with a radius.

If the cable manager 5 is inserted on both sides of a cable, then two core pairs must be interchanged on one side owing to the mirror-image symmetrical constellation and, with free wiring, this leads to the crosstalk between these pairs increasing in an undefined manner. The guide web 44 is used to avoid this undefined crosstalk, and will now be explained in more detail in the following text with reference to RJ-45 wiring. An RJ-45 cable comprises eight cores, which

are combined in pairs, with the two outer cores 1, 2 and 7, 8 forming a pair. The inner cores are combined crossed over, so that the cores 3, 6 and 4, 5 form a pair. The mirror-image symmetrical situation at the two ends of a cable as described above in this case means that either the two outer pairs or the two inner pairs must be interchanged at one end. In the following text, it is assumed that the inner pairs 3, 6 and 4, 5 are intended to be interchanged. The core pair 1, 2 is then arranged in the channel 37, the core pair 7, 8 in the channel 38, the core pair 3, 6 in the channel 39 and the core pair 4, 5 in the channel 40. The guides 19 in the upper left-hand quadrant are then permanently assigned to the core pair 1, 2, and the guides 19 in the upper quadrant are permanently assigned to the core pair 7, 8, independently of the side of the channel. The core pair 3, 6, on the other hand, must, depending on the cable side, be assigned firstly to the guides 19 in the lower left-hand quadrant and secondly to the guide 19 in the lower right-hand quadrant. A corresponding situation applies, but in the opposite sense, to the core pair 4, 5 in the channel 40. In this case, the guide web 44 makes it impossible for the two core pairs 4, 5 and 3, 6 to touch. Apart from providing detection against contact, a further function of the guide web 44 is to guide the two core pairs 4, 5 and 3, 6 as far away from one another as possible in a defined manner, in order thus to reduce the crosstalk. Alternatively, the guide web 44 may be semicircular or V-shaped, in order to provide better guidance, with the edges of the guide web 44 in each case being rounded in order not to kink the cores.

List of reference symbols

- 1) Plug connector
- 2) Plug connector housing
- 3) Printed circuit board
- 4) Hold-down device
- 5) Cable manager
- 6) Ground plate
- 7) Contacts
- 8) Insulation-displacement contacts
- 9) Cylindrical pin
- 10) Latching tab
- 11) Opening
- 12) Latching hook
- 13) Opening
- 14) Attachment
- 15) Rear face
- 16) Front face
- 17) Guide cross
- 18) Incline
- 19) Guide
- 20) Holder
- 21) Tool
- 22) Side wall
- 23) Guide
- 24) Rear wall
- 25) Guide edge
- 26) Jaw part
- 27) Base
- 28) Opening
- 29) Structures

- 30) Spring
- 31) Closure element
- 32) Limb
- 33) Latching groove
- 34) Attachment
- 35) Structures
- 36) Cable
- 37-40) Channels
- 41) Openings
- 42) Clamping rib
- 43) Spherical elements
- 44) Guide web

Electrical plug connector**Patent Claims:**

1. An electrical plug connector, comprising a plug connector housing, a printed circuit board with two sets of contact elements, with the first set of contact elements being arranged on the front face of the printed circuit board and projecting into an opening in the plug connector housing, and the second set of contact elements being arranged on the rear face of the printed circuit board, and the contact elements of the second set being in the form of insulation-displacement contacts,
wherein
the plug connector (1) comprises a cable manager (5) which has a through-opening (13) and is formed on the front face (16) with guides (19) for cores which are intended to make contact with the insulation-displacement contacts (8), in which case the guides (19) in the region of the insulation-displacement contacts (8) are formed with recessed holders (20) for the insulation-displacement contacts (8), and the cable manager (5) can be latched to the plug connector housing (2).
2. The electrical plug connector as claimed in claim 1, wherein a guide cross (17) is arranged in the opening (13) in the cable manager (5).
3. The electrical plug connector as claimed in claim 1 or 2, wherein the guides (19) run radially with respect to the opening (13).
4. The electrical plug connector as claimed in claim 1 or 2, wherein the guides (19) run parallel, with two guides (19) being arranged in each quadrant of the cable manager (5).
5. The electrical plug connector as claimed in one of the preceding claims, wherein the rear face (15) of the cable manager (5) is formed with an incline (18) on one side.
6. The electrical plug connector as claimed in one of the preceding claims, wherein a hold-down device (4) is arranged between the cable manager (5) and the printed circuit

board (3) and allows the printed circuit board (3) to be fixed with respect to the plug connector housing (2).

7. The electrical plug connector as claimed in one of the preceding claims, wherein the guides (19) of the cable manager (5) are arranged at offset levels with respect to one another.
8. The electrical plug connector as claimed in one of the preceding claims, characterized in that a cable grip is arranged above the cable manager (5).
9. The electrical plug connector as claimed in claim 8, wherein the cable grip is designed with a number of parts, with the first part (21) being designed with two jaw parts (26) which flex jointly and whose joint flexing can be limited in an adjustable manner by means of a spring (30) which engages around the jaw parts (26), and with a third part being designed as a closure element (31) which can be latched in an adjustable manner to the first part and/or to the spring (30), such that a cable (36) which is to be attached can be centered in a defined, force-fitting manner.
10. The electrical plug connector as claimed in claim 9, wherein the first and the third part of the cable grip are in the form of metallized plastic parts which can be connected to a ground plate (6) in the plug connector housing (2).
11. The electrical plug connector as claimed in one of the preceding claims, wherein the electrical plug connector (1) is in the form of a socket for an RJ-45 plug.
12. A cable manager for an electrical plug connector,
wherein
the cable manager (5) has openings (13) which extend from the rear face (15) to the front face (16) and is designed with guides (19) on the front face (16) for cores which are intended to make contact with insulation-displacement contacts (8), with the guides (19) in the region of the insulation-displacement contacts (8) being designed with

recessed holders (20) for the insulation-displacement contacts (8).

13. The cable manager as claimed in claim 12, wherein a guide cross (17) is arranged in the opening (13) in the cable manager (5).
14. The cable manager as claimed in claim 12 or 13, wherein the cable manager (5) is designed with a cylindrical attachment (14) in the region of the opening (13) on the rear face (15).
15. The cable manager as claimed in one of claims 12 to 14, wherein the guides (19) run radially with respect to the opening (13).
16. The cable manager as claimed in one of claims 12 to 14, wherein the guides (19) run parallel, with two guides (19) being arranged in each quadrant of the cable manager (5).
17. The cable manager as claimed in one of claims 12 to 16, wherein the rear face (15) of the cable manager (5) is formed with an incline (18) on one side.
18. A method for assembly of an electrical plug connector as claimed in one of claims 5 to 11, comprising the following method steps:
 - a) The printed circuit board (3) is inserted into the plug connector housing (2),
 - b) The cores of a cable with which contact is to be made are passed through the openings (13) in the cable manager (5) from the rear face (15) to the front face (16), with the cores being pressed into the associated guides (19) and being cut off at the side edges,
 - c) The cable manager (5) is aligned with respect to the insulation-displacement contacts (8) on the printed circuit board (3), and
 - d) A bracket-like tool (21), which has a guide edge (25) complementary to the incline (18) on the rear face (15) of the cable manager (5) and has a guide (23) formed parallel to the plug connector housing (2), is pushed on so that the sliding movement is converted into a travel movement of the cable manager (5)

and plug connector housing (2) toward one another, with the insulation-displacement contacts (8) making contact with the cores, and the plug connector (2) and the cable manager (5) being latched to one another.

19. A tool for assembly of a plug connector as claimed in one of claims 5 to 11,

wherein

the tool (21) is essentially U-shaped, with parallel-running guides (23) being arranged on the lower face of the limbs (22), which guides (23) point inward, run at right angles to the rear wall (24) of the tool (21) and, in the upper region, are designed with an obliquely running guide edge (25) on the inside of each of the limbs (22).