

DESCRIPTION

RECORDING APPARATUS, RECORDING METHOD, AND RECORDING PROGRAM, AND IMAGE CAPTURING APPARATUS, IMAGE CAPTURING METHOD AND IMAGE CAPTURING PROGRAM

5 Technical Field

The present invention relates to a recording apparatus, a recording method, a recording program, an image capturing apparatus, an image capturing method, and an image capturing program that are suitable for recording stream data of which video data and audio data have been multiplexed to a record medium.

Background Art

As a record medium that is recordable and detachable from a recording and reproducing apparatus, that has a relatively large recording capacity, and that is suitable for recording AV (Audio/Video) data composed of video data and audio data, so far, DVD (Digital Versatile Disc) that has a recording capacity of 4.7 GB (Giga Bytes) or more has been widely used.

15 Patent document "Japanese Patent Application Laid-Open No. 2004-350251" describes an image capturing apparatus that records DVD-Video formatted data to a recordable type DVD.

Video data and audio data are generally recorded on a record medium in the unit of video data created after the record start operation until the record stop operation. A reproduction region and a

reproduction order of the video data created after the
record start operation until the record stop operation
are generally designated with reproduction list
information. When a recorded AV stream is managed in
5 the unit of video data created after the record start
operation until the record stop operation with
reproduction list information, the AV stream can be
easily edited by freely setting the reproduction region
and the reproduction order of the AV stream without
10 necessity of processing the AV stream on the record
medium.

It is assumed that video data and audio data
are recorded as files to a record medium. For example,
video data and audio data are recorded as files in the
15 unit of data created after the record start operation
until the record stop operation. Since video data and
audio data are recorded as files, they have a more
affinity to other apparatus such as a computer
apparatus. Thus, recorded data can be expected to be
20 more effectively used.

Thus, when video data and audio data that
have been continuously recorded as files to one record
medium according to a sequences of record start
operations and record stop operations are reproduced in
25 the order of which they have been recorded, it is
necessary to perform a particular technique. For
example, it can be contemplated that information about

a plurality of units of video data and audio data that are continuously recorded to one record medium according to a sequence of record start operations and record stop operations is controlled to be additionally written to one reproduction list file that stores reproduction list information. When such a recording control is performed, it becomes easy to continuously reproduce a plurality of units of video data and audio data that have been recorded.

When information about video data and audio data that are continuously recorded is controlled to be additionally written to a reproduction list file whenever the record start operation and the record stop operation are performed, the data size of the reproduction list file increases whenever the record start operation and the record stop operation are performed. On the other hand, it is contemplated that in a recording apparatus and a reproducing apparatus, the reproduction list file is temporarily read to the memory and video data and audio data recorded as files are reproduced according to the reproduction list file. In addition, another management information with which video data and audio data that have been recorded to the record medium is read to the memory. Thus, as the size of the reproduction list file becomes large, it consumes the memory space. Thus, as a problem of the conventional apparatus, other processes may be

adversely affected.

When video data and audio data are recorded as files, it is necessary to provide a mechanism that can search video data for a frame to be reproduced and easily edit video data in the unit of one frame. To do that, it can be contemplated that for example reproduction time information of video data and addresses of files of video data are correlated. Data that represent the relationship between the reproduction time information and addresses of files increases as video data are recorded. Thus, in this case, when video data and audio data are recorded or reproduced, the data that represent such a relationship becomes large and it consumes the memory space. Thus, as a problem of the conventional apparatus, other processes may be adversely affected.

In addition, as a problem of the conventional apparatus, when video data are tried to be recorded in the state that the memory space is insufficient, the system may forcibly stop recording video data and audio data or hang up.

Moreover, in recent years, a variety of video formats have been commonly used. With respect to scanning lines and scanning methods, these formats include 480i having 480 scanning lines, 576i having 576 scanning lines, 1080i having 1080 scanning lines, and so forth as interlace scanning formats and 480p having

480 scanning lines, 576p having 576 scanning lines, 720p having 720 scanning lines, 1080p having 1080 scanning lines, and so forth as progressive scanning formats.

In addition, a recording apparatus needs to record video data according to such various types of formats. Moreover, video data need to be recorded in a plurality of formats to one record medium. However, as described above, when information of video data and audio data continuously recorded as files to the record medium is controlled to be additionally written to one reproduction list file, it is likely that a trouble occurs on the reproducing apparatus side that reproduces files from the record medium. As a problem of the conventional apparatus, when video data and audio data recorded as files are continuously reproduced according to the reproduction list file, if the format of video data of the next file is different from that of the preceding file, the decoder cannot perform its process at a proper timing or the apparatus may stop because of a hang-up of the decoder.

Disclosure of the Invention

Therefore, example embodiments can provide a recording apparatus, a recording method, a recording program, an image capturing apparatus, an image capturing method, and an image capturing program that allow user-friendliness in recoding video data and

audio data created after a record start operation until a record stop operation on to be improved.

A first aspect of the present invention provides in a recording apparatus which multiplexes video data and audio data and records multiplexed data to a record medium, characterized in that the recording apparatus comprise a data input section which inputs the video data and the audio data, a record command input section which inputs a record start command and a record stop command for the video data and the audio data, a recording section which multiplexes the video data and the audio data and records the multiplexed stream as a stream file to the record medium, and a management information creation section which creates reproduction management information for controlling a reproduction of the stream file recorded on the record medium, the reproduction management information being composed of first management information which represents attribute information of the stream file and second management information which contains information which represents a reproduction method for the stream file, and the management information creation section determines whether or not the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to a predetermined entry of the second management

information contained in an existing entry of the reproduction management information according to the record start command by the record command input section based on the existing entry of the reproduction management information.

In addition, a second aspect of the present invention provides in a recording method of multiplexing video data and audio data and recording multiplexed data to a record medium, characterized in that the recording method comprise a record command input step of inputting a record start command and a record stop command for the video data and the audio data that have been input to a data input section, a recording step of multiplexing the video data and the audio data and recording the multiplexed stream as a stream file to the record medium, and a management information creation step of generating reproduction management information for controlling a reproduction of the stream file recorded on the record medium, the reproduction management information being composed of first management information which represents attribute information of the stream file and second management information which contains information which represents a reproduction method for the stream file, the management information creation step being performed by determining whether or not the information which represents the reproduction method for the stream file

recorded on the record medium is additionally written to a predetermined entry of the second management information contained in an existing entry of the reproduction management information according to the record start command by the record command input section based on the existing entry of the reproduction management information.

A third aspect of the present invention provides in a recording program of causing a computer apparatus to execute a recording method of multiplexing video data and audio data and recording multiplexed data to a record medium, characterized in that the recording method comprise a record command input step of inputting a record start command and a record stop command for the video data and the audio data that have been input to a data input section, a recording step of multiplexing the video data and the audio data and recording the multiplexed stream as a stream file to the record medium, and a management information creation step of generating reproduction management information for controlling a reproduction of the stream file recorded on the record medium, the reproduction management information being composed of first management information which represents attribute information of the stream file and second management information which contains information which represents a reproduction method for the stream file, the

management information creation step being performed by determining whether or not the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to a predetermined entry of the second management information contained in an existing entry of the reproduction management information according to the record start command by the record command input section based on the existing entry of the reproduction management information.

A fourth aspect of the present invention provides in an image capturing apparatus which multiplexes video data captured and obtained from a subject by an image capturing section and audio data collected and obtained by a sound collecting section and records multiplexed video data and audio data to a record medium, characterized in that the image capturing apparatus comprises the image capturing section which captures the image of the subject and outputs the video data, the sound collecting section which collects a sound and outputs audio data, a recording section which multiplexes the video data and the audio data and records the multiplexed stream as a stream file to the record medium, an operation section which accepts user's operations for a record start command and a record stop command for the video data and the audio data to the record medium, and a management information

creation section which creates reproduction management information for controlling a reproduction of the stream file recorded on the record medium, the reproduction management information being composed of first management information which represents attribute information of the stream file and second management information which contains information which represents a reproduction method for the stream file, the management information creation section determines whether or not the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to a predetermined entry of the second management information contained in an existing entry of the reproduction management information according to the record start command corresponding to the user's operations to the operation section based on the existing entry of the reproduction management information.

A fifth aspect of the present invention provides in an image capturing method of multiplexing video data captured and obtained from a subject by an image capturing section and audio data collected and obtained by a sound collecting section and recording multiplexed video data and audio data to a record medium, characterized in that the image capturing method comprises a recording step of multiplexing the video

data and the audio data captured and obtained from an
subject by the image capturing section and the audio
data collected and obtained by the sound collecting
section and recording the multiplexed stream as a
5 stream file to the record medium, an accepting step of
accepting user's operations for a record start command
and a record stop command for the video data and the
audio data to the record medium against an operation
section, and a management information creation step for
10 generating reproduction management information for
controlling a reproduction of the stream file recorded
on the record medium, the reproduction management
information being composed of first management
information which represents attribute information of
15 the stream file and second management information which
contains information which represents a reproduction
method for the stream file, the management information
creation step being performed by determining whether or
not the information which represents the reproduction
20 method for the stream file recorded on the record
medium is additionally written to a predetermined entry
of the second management information contained in an
existing entry of the reproduction management
information according to the record start command
25 corresponding to the user's operations to the operation
section based on the existing entry of the reproduction
management information.

A sixth aspect of the present invention provides in an image capturing program of causing a computer apparatus to execute an image capturing method of multiplexing video data captured and obtained from a subject by an image capturing section and audio data collected and obtained by a sound collecting section and recording multiplexed video data and audio data to a record medium, characterized in that the image capturing method comprises a recording step of multiplexing the video data and the audio data captured and obtained from a subject by the image capturing section and the audio data collected and obtained by the sound collecting section and recording the multiplexed stream as a stream file to the record medium, an accepting step of accepting user's operations for a record start command and a record stop command for the video data and the audio data to the record medium against an operation section, and a management information creation step for generating reproduction management information for controlling a reproduction of the stream file recorded on the record medium, the reproduction management information being composed of first management information which represents attribute information of the stream file and second management information which contains information which represents a reproduction method for the stream file, the management information creation

step being performed by determining whether or not the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to a predetermined entry of the second management information contained in an existing entry of the reproduction management information according to the record start command corresponding to the user's operations to the operation section based on the existing entry of the reproduction management information.

As described, in example embodiments relating to the first, second, and third aspects of the present invention, reproduction management information for controlling the reproduction of a stream file recorded on a record medium is created. The reproduction management information is composed of first management information that represents attribute information of a stream file composed of a stream of which video data and audio data have been multiplexed and second management information that contains information that represents a reproduction method for the stream file. An additionally recording ability/inability determination of determining whether or not the information that represents the reproduction method for the stream file recorded on the record medium is additionally written to a predetermined entry of the second management information contained in an existing entry of the reproduction management

information according to a record start command for the video data on the basis of the existing entry of the reproduction management information. Thus, even if the record start operation and the record stop operation are repeatedly performed, the second management information is controlled to be adequately created without necessity of user's recognition for the second management information.

As described, in example embodiments relating to the fourth, fifth, and sixth aspects of the present invention, reproduction management information for controlling the reproduction of a stream file recorded on a record medium is created. The reproduction management information is composed of first management information that represents attribute information of a stream file composed of a stream of which captured and obtained video data and collected and obtained audio data have been multiplexed and second management information that contains information that represents a reproduction method for the stream file. An additionally recording ability/inability determination of determining whether or not the information that represents the reproduction method for the stream file composed of video data captured and obtained from a subject and recorded on the record medium is additionally written to a predetermined entry of the second management information contained in an existing entry of the

reproduction management information according to a record start command corresponding to a user's operation against an operation section on the basis of the existing entry of the reproduction management information. Thus, even if the record start operation and the record stop operation are repeatedly performed for capturing, the second management information is controlled to be adequately created without necessity of user's recognition for the second management information.

As described, in example embodiments relating to the first, second, and third aspects of the present invention, reproduction management information for controlling the reproduction of a stream file recorded on a record medium is created. The reproduction management information is composed of first management information that represents attribute information of a stream file composed of a stream of which video data and audio data have been multiplexed and second management information that contains information that represents a reproduction method for the stream file. An additionally recording ability/inability determination of determining whether or not the information that represents the reproduction method for the stream file recorded on the record medium is additionally written to a predetermined entry of the second management information contained in an existing entry of the reproduction management

information according to a record start command for the video data on the basis of the existing entry of the reproduction management information. Thus, there is provided an effect of which even if the record start operation and the record stop operation are repeatedly performed, the second management information is controlled to be adequately created without necessity of user's recognition for the second management information.

As described, in example embodiments relating to the fourth, fifth, and sixth aspects of the present invention, reproduction management information for controlling the reproduction of a stream file recorded on a record medium is created. The reproduction management information is composed of first management information that represents attribute information of a stream file composed of a stream of which captured and obtained video data and collected and obtained audio data have been multiplexed and second management information that contains information that represents a reproduction method for the stream file. An additionally recording ability/inability determination of determining whether or not the information that represents the reproduction method for the stream file composed of video data captured and obtained from a subject and recorded on the record medium is additionally written to a predetermined entry of the second management

information contained in an existing entry of the reproduction management information according to a record start command corresponding to a user's operation against an operation section on the basis of the existing entry of the reproduction management information. Thus, there is provided an effect of which even if the record start operation and the record stop operation are repeatedly performed for capturing, the second management information is controlled to be adequately created without necessity of user's recognition for the second management information.

Brief Description of Drawings

Fig. 1 is a schematic diagram showing an outline of a data model prescribed in the AVCHD format applicable to the present invention; Fig. 2 is a schematic diagram for describing an index table; Fig. 3 is an UML diagram showing the relationship of a clip AV stream, clip information, a clip, a play item, and a play list; Fig. 4 is a schematic diagram for describing a method of referring to the same clip from a plurality of play lists; Fig. 5 is a schematic diagram for describing a management structure of files recorded on a record medium; Fig. 6 is a schematic diagram showing syntax that represents an example of the structure of a file "index.bdmv"; Fig. 7 is a schematic diagram showing syntax that represents an example of the structure of a block blkIndexes(); Fig. 8 is a

schematic diagram showing syntax that represents an example of the structure of a file "MovieObject.bdmv"; Fig. 9 is a schematic diagram showing syntax that represents an example of the structure of a block blkMovieObjects(); Fig. 10 is a schematic diagram showing syntax that represents an example of the structure of a play list file "xxxxx.mpls"; Fig. 11 is a schematic diagram showing syntax that represents an example of the structure of a block blkPlayList(); Fig. 12 is a schematic diagram showing syntax that represents an example of the structure of a block blkPlayItem (); Fig. 13A and Fig. 13B are schematic diagrams for describing first and second seamless connections, respectively; Fig. 14 is a schematic diagram showing syntax that represents an example of the structure of a block blkPlayListMark(); Fig. 15 is a schematic diagram showing syntax that represents an example of the structure of a click information file; Fig. 16 is a schematic diagram showing syntax that represents an example of the structure of a block blkClipInfo(); Fig. 17 is a schematic diagram showing syntax that represents an example of the structure of a block blkProgramInfo(); Fig. 18 is a schematic diagram showing syntax that represents an example of the structure of a block blkStreamCodingInfo (stream_index); Fig. 19 is a schematic diagram showing an example of a list of formats of video data

represented in a field VideoFormat; Fig. 20 is a
schematic diagram showing an example of a list of frame
rates represented in a field FrameRate; Fig. 21 is a
schematic diagram showing an example of a list of frame
rates represented in a field AspectRatio; Fig. 22 is a
schematic diagram showing syntax that represents an
example of the structure of a block blkCPI(); Fig. 23
is a schematic diagram showing syntax that represents
an example of the structure of a block blkEPMMap(); Fig.
24 is a schematic diagram showing syntax that
represents an example of the structure of a block
blkEPMMapForOneStreamPID (EP_stream_type, Nc, Nf); Fig.
25 is a schematic diagram showing an example of the
formats of an entry PTSEPCoarse and an entry PTSEPFine;
Fig. 26 is a schematic diagram showing an example of
the formats of an entry SPNEPCoarse and an entry
SPNEPFine; Fig. 27 is a schematic diagram showing
syntax that represents an example of the structure of a
block blkExtensionData(); Fig. 28 is a schematic
diagram showing a reference relationship of each entry
of data of a block blkExtensionData(); Fig. 29 is a
flow chart showing an example of a process of writing
data to a block blkExtensionData(); Fig. 30 is a flow
chart showing an example of a process of reading
extension data from a block blkExtensionData(); Fig. 31
is a schematic diagram showing syntax that represents
an example of the structure of a block DataBlock() of a

field blkExtensionData() in a file "index.bdmv"; Fig. 32 is a schematic diagram showing syntax that represents an example of the structure of a block blkTableOfPlayList(); Fig. 33 is a schematic diagram showing syntax that represents an example of the structure of a block DataBlock() of a block blkExtensionData() in a play list file "xxxxx.mpls"; Fig. 34 is a schematic diagram showing syntax that represents an example of the structure of a block blkPlayListMeta(); Fig. 35 is a schematic diagram showing syntax that represents an example of the structure of a block blkMakersPrivateData() in a play list file; Fig. 36 is a schematic diagram showing syntax that represents an example of the structure of a block DataBlock() of a block blkExtensionData() in a clip information file; Fig. 37 is a schematic diagram showing syntax that represents an example of the structure of a block blkProgramInfoExt(); Fig. 38 is a schematic diagram showing syntax that represents an example of the structure of a block blkStreamCodingInfoExt(i, j); Fig. 39A and Fig. 39B are flow charts showing an outline of an operation of a virtual player; Fig. 40 is a schematic diagram showing an outline of an operation of the virtual player; Fig. 41 is a block diagram showing an example of the structure of a recording apparatus according to an embodiment of the present invention; Fig. 42 is a

schematic diagram showing an example of a data structure according to an embodiment of the present invention; Fig. 43 is a flow chart showing an example of a process of determining whether or not a chapter can be additionally written to a play list file; Fig. 44 is a flow chart showing an example of an additionally writing ability/inability determination on the basis of the number of play items; Fig. 45 is a flow chart showing an example of the additionally writing ability/inability determination process on the basis of the number of play list marks; Fig. 46 is a flow chart showing an example of the additionally writing ability/inability determination process on the basis of a video attribute; Fig. 47 is a flow chart showing an example of the additionally writing ability/inability determination process on the basis of a file size; Fig. 48 is a flow chart showing an example of the additionally writing ability/inability determination process on the basis of a total file size of clip information files referred from a play list file as an additionally writable candidate; Fig. 49 is a flow chart showing an example of the additionally writing ability/inability determination process on the basis of a total number of entry points stored in a clip information file referred from a play list file as an additionally writable candidate; Fig. 50 is a flow chart showing an example of the additionally writing

ability/inability determination process on the basis of presence or absence of unique extension data of another apparatus; Fig. 51 is a flow chart showing an example of the additionally writing ability/inability determination process on the basis of a last update apparatus of a play list file as an additionally writable candidate; Fig. 52 is a flow chart showing an example of a recording method of a clip according to an embodiment of the present invention; Fig. 53 is a block diagram showing an example of the structure of a video camera apparatus according to another embodiment of the present invention.

Best Modes for Carrying out the Invention

Next, with reference to accompanying drawings, an embodiment of the present invention will be described. For easy understanding, an example of a format applicable to the present invention will be described (hereinafter, referred to as the AVCHD format). The AVCHD format is currently being proposed as a record format of which an AV (Audio/Video) stream of which video data and audio data have been multiplexed in a predetermined manner is recorded to a recordable record medium. The AVCHD format allows an AV stream recorded on a record medium to be managed in the unit of one clip with a play list.

A bit stream that has been encoded, for example, according to the ITU-U (International

Telecommunication Union - Telecommunication
Standardization Sector) recommendation H. 264 or the
ISO (International Organization for Standardization)/
IEC (International Electrotechnical Commission)

5 International Standard 14496-10 (MPEG-4 part 10)
Advanced Video Coding (hereinafter, referred to as the
H. 264 | AVC) and that has been multiplexed according
to the MPEG2 systems is referred to as a clip AV stream
(or an AV stream). A clip AV stream is recorded as a
10 file to a disc by a predetermined file system. This
file is referred to as a clip AV stream file (or an AV
stream file).

A clip AV stream file is a management unit on
a file system. Thus, a clip AV stream file is not
15 always a user-friendly management unit. To facilitate
user-friendliness, it is necessary to provide a
mechanism of continuously reproducing a plurality of
clip AV stream files into which video contents are
divided and a mechanism of partly reproducing a clip AV
20 stream file and record information necessary to
smoothly perform a special reproduction operation, a
cue reproduction operation, and so forth as a database
to a disc.

Fig. 1 shows an outline of a data model
25 prescribed in the AVCHD format applicable to the
present invention. As shown in Fig. 1, the AVCHD
format has a data structure with four hierarchical

layers. The lowest layer is a layer on which a clip AV stream is placed (for convenience, hereinafter, referred to as the clip layer). Placed above the clip layer is a layer for play lists (PlayList) with which reproduction positions of the clip AV stream are designated and play items (PlayItem) (for convenience, referred to as the play list layer). Placed above the play list layer is a layer for movie objects (Movie Object) each of which is composed of commands that designate the reproduction order of play lists and so forth (for convenience, referred to as the object layer). The highest layer is a layer for an index table with which titles and so forth stored on the record medium are managed (for convenience, referred to as the index layer).

Next, the clip layer will be described. A clip AV stream is a bit stream of which video data and audio data have been multiplexed, for example, according to the MPEG2 TS (transport stream) format. Information about the clip AV stream is recorded as clip information (Clip Information) in a file.

In addition, an OB stream (Overlay Bitmap stream) that is a graphic stream for a subtitle and an MB stream (Menu Bitmap stream) as a stream of data (such as button image data) for a menu indication can be multiplexed with a clip AV stream.

A pair of a clip AV stream file and a clip

information file in which clip information
corresponding to the clip AV stream file has been
recorded is treated as an object and referred to as a
clip (Clip). In other words, a clip is one object
5 composed of a clip AV stream and clip information.

A file is generally treated as a sequence of
bytes. Contents of a clip AV stream file are mapped on
the time base. An entry point of a clip is mainly
designated on the time base. When a time stamp of an
10 access point is given to a predetermined clip, a clip
information file can be used to find address
information with which data are read from the clip AV
stream file.

Next, the play list layer will be described.
15 A play list designates an AV stream file to be
reproduced. A play list is composed of pairs of a
reproduction start point (IN point) and a reproduction
end point (OUT point) with which a reproduction
position of a designated AV stream file is designated.
20 A pair of the reproduction start point and the
reproduction end point is referred to as a play item
(PlayItem). A play list is composed of a set of play
items. When a play item is reproduced, a part of an AV
stream file referred from the play item is reproduced.
25 In other words, a region of a clip is reproduced on the
basis of information of an IN point and an OUT point of
a play item.

Next, the object layer will be described. A movie object contains a navigation command program and terminal information that is associated with the movie object. The navigation program is a command
5 (navigation command) for controlling the reproduction of a play list.

Next, the index layer will be described. The index layer is composed of an index table (Index Table). The index table is a table in the top level
10 that defines titles of contents recorded on a disc. A module manager of player resident system software controls the reproduction of data of the record medium on the basis of title information stored in the index table.

15 In other words, as schematically shown in Fig. 2, any entries in the index table are referred to as titles. All of a first playback title (First PlaybackTitle), a menu title (MenuTitle), and movie title (MovieTitle) #1, #2, and so forth that are
20 entries in the index table are titles. Each title represents a link to a movie object.

For easy understanding, for example, in a reproduction-only record medium, when contents stored in this record medium are a movie, the first playback
25 title corresponds to an advertisement picture of a movie maker, which is followed by the main body of the movie. When contents are a movie, the menu title

corresponds to a menu screen with which operations for which the main body is reproduced, a chapter is searched, a subtitle and a language are set, and a bonus picture is reproduced are selected. The movie titles are pictures selected from the menu title. A title may be structured as a menu screen.

Fig. 3 is a UML (Unified Modeling Language) diagram showing the relationship of the foregoing clip AV stream, clip information (Stream Attributes), a clip, a play item, and a play list. A play list is correlated with one or a plurality of play items. A play item is correlated with one clip. One clip can be correlated with a plurality of play items whose start point and/or end point different from each other. One clip refers to one clip AV stream file. Likewise, one clip refers to one clip information file. A clip AV stream file and a clip information file have a relationship of one to one. With such a structure, the reproduction order can be non-destructively designated to reproduce only a desired portion of a clip AV stream file without necessity of changing it.

In addition, as shown in Fig. 4, the same clip can be referred from a plurality of play lists. In addition, a plurality of clips can be designated from one play list. A clip is referred with an IN point and an OUT point of a play item in a play list. In the example shown in Fig. 4, a clip 300 is referred

from a play item 320 of a play list 310. In addition,
the clip 300 is referred for a region designated by an
IN point and an OUT point of a play item 321 of a play
list 311 that has the play item 321 and a play item
5 322. In addition, a clip 301 is referred for a region
designated by an IN point and an OUT point of the play
item 322 of the play list 312. In addition, the clip
301 is referred for a region designated by an IN point
and an OUT point of a play item 323 of a play list 312
10 that has the play item 323 and a play item 324. In
the example shown in Fig. 4, the clip 301 is also
referred from another play list.

Next, with reference to Fig. 5, the
management structure for files in the AVCHD format on a
15 record medium will be described. Files are
hierarchically managed with a directory structure. One
directory (in Fig. 5, a root directory) is created on a
record medium. Below the directory is the range
managed by one recoding and reproducing system.

20 Placed below the root directory is a
directory "BDMV". When necessary, placed below the
root direction is a directory "AVCHDTN". Placed in the
directory "AVCHDTN" are thumbnail files of which
representative images of clips have been reduced in a
25 predetermined size. Placed in the directory "BDMV" is
the data structure described with reference to Fig. 1.

Placed immediately below the directory "BDMV"

are only two files, a file "index.bdmv" and a file
"MovieObject.bdmv". Placed below the directory "BDMV"
are a directory "PLAYLIST", a directory "CLIPINF", a
directory "STREAM", and a directory "BACKUP". The
5 directory "BACKUP" stores backups of individual
directories and files.

The file "index.bdmv" describes the contents
of the directory "BDMV". In other words, this file
"index.bdmv" corresponds to the index table in the
10 index layer, which is the foregoing highest layer. The
file "MovieObject.bdmv" stores information about at
least one movie object. In other words, this file
"MovieObject.bdmv" corresponds to the foregoing object
layer.

15 The directory "PLAYLIST" is a directory in
which the database of play lists is placed. In other
words, the directory "PLAYLIST" contains a file
"xxxxxx.mpls" that is a file with respect to a play
list. The file "xxxxxx.mpls" is a file created for each
20 play list. In the file name, "xxxxxx" followed by a "."
(period) is a five-digit numeral. "mpls" preceded by
the period is a fixed extension of a file of this type.

The directory "CLIPINF" is a directory in
which a database of clips is placed. In other words,
25 the directory "CLIPINF" contains a file "zzzzz.clpi"
that is a clip information file corresponding to a clip
AV stream file. In the file name, "zzzzz" followed by

a "." (period) is a five-digit numeral. "clpi" preceded by the period is a fixed extension of a file of this type.

5 The directory "STREAM" is a directory in which an AV stream file as an entity is placed. In other words, the directory "STREAM" contains a clip AV stream file corresponding to a clip information file. A clip AV stream file is composed of an MPEG2 (Moving Pictures Experts Group 2) transport stream (hereinafter
10 abbreviated as an MPEG2 TS). The file name of a clip AV stream file is "zzzzz.m2ts". When "zzzzz" followed by the period of the file name of the clip AV stream file is the same as that of the corresponding clip information file, their relationship can be easily
15 recognized.

 Two types of thumbnail files thumbnail.tidx and thumbnail.tdt2 can be placed in the directory "AVCHDTN". The thumbnail file thumbnail.tidx stores a thumbnail image that has been encrypted in a
20 predetermined system. In contrast, the thumbnail file thumbnail.tdt2 stores a thumbnail image that has not been encrypted. Since it is likely that a thumbnail image corresponding to a clip that the user has captured, for example, with a video camera is copy-
25 free, this thumbnail image is stored in thumbnail file thumbnail.tdt2.

 Next, among files shown in Fig. 5, those that

strongly relate to the present invention will be described in more detail. First of all, the file "index.bdmv", which is placed immediately below the directory "BDMV", will be described. Fig. 6 shows syntax that represents an example of the structure of the file "index.bdmv". In this example, syntax is represented according to syntax of the C language, which is used as a programming language for computer devices and so forth. This applies to drawings that show syntax of other files.

In Fig. 6, a field TypeIndicator has a data length of 32 bits and denotes that this file is an index table. A field TypeIndicator2 has a data length of 32 bits and represents the version of the file "index.bdmv". A field "IndexesStartAddress" has a data length of 32 bits and represents the start address of a block blkIndexes() in this syntax.

A field ExtensionDataStartAddress has a data length of 32 bits and represents the start address of a block blkExtensionData() in this syntax. The block blkExtensionData() is a block that can store predetermined extension data. The field ExtensionDataStartAddress represents the start address of the block blkExtensionData() as the relative number of bytes from the beginning of bytes of this file "index.bdmv". The relative number of bytes starts with "0". If the value of the field

ExtensionDataStartAddress is "0", it denotes that this file "index.bdmv" does not contain the block blkExtensionData().

5 The field ExtensionDataStartAddress is followed by an area reserved that has a data length of 192 bytes. The area reserved is an area reserved for a byte alignment, a future field addition, and so forth. This applies to the description that follows. A block blkAppInfoBDMV() is a block in which the contents
10 creator can describe any information and does not affect the operation of the player and so forth.

 A block blkIndexes() is substantial contents of this file "index.bdmv". The contents described in this file "index.bdmv" designate the first playback
15 reproduced when the disc is loaded into the player, and a title (a movie object) that is called from the top menu. A play list file (that will be described later) is read according to a command described in a movie object or the like called by an index table.

20 Fig. 7 shows syntax that represents an example of the structure of the block blkIndexes(). A field length has a data length of 32 bits and represents the data length immediately after this field Length until the end of this block blkIndexes(). The
25 field length is followed by a block FirstPlaybackTitle() and a block MenuTitle().

 The block FirstPlaybackTitle() describes

information about an object used in the first playback.

The block `FirstPlaybackTitle()` describes an area reserved having a data length of 1 bit, followed by a fixed value "1". The block `FirstPlaybackTitle()`

5 further describes a fixed value "1" through an area reserved having a data length of 31 bits. Followed by an area reserved having a data length of 14 bits, a field `FirstPlaybackTitleMobjIDRef` having a data length of 16 bits is placed. This field

10 `FirstPlaybackTitleMobjIDRef` represents the ID of a movie object used in the first playback title.

The ID of a movie object is represented by a value `mobj_id` used as a loop variable in a for loop statement of a movie object based on syntax of a movie object that will be described later, for example, with reference to Fig. 8 and Fig. 9. In this example, the field `FirstPlaybackTitleMobjIDRef` stores a value `mobj_id` corresponding to a movie object to be referred.

15 The field `FirstPlaybackTitleMobjIDRef` of the block `FirstPlaybackTitle()` in the block `blkIndexes()` may represent a movie object of the top menu or a title.

20 The block `MenuTitle()` describes information about an object used in the top menu. The block `MenuTitle()` describes an area reserved having a data length of 1 bits, followed by a fixed value "1". Followed by an area reserved having a data length of 31

bits, a fixed value "1" is described. In addition,
followed by an area reserved having a data length of 14
bits, a field MenuTitleMobjIDRef having a data length
of 16 bits is placed. The field MenuTitleMobjIDRef
5 represents the ID of a movie object used in the menu
title.

The block MenuTitle() is followed by a field
NumberOfTitles that has a data length of 16 bits and
that represents the number of titles that the user can
10 select and that can be reproduced. According to the
next for loop statement, the number of times
represented by this field NumberOfTitles, a block
MovieTitle[title_id]() is described with an argument of
a value title_id. The block MovieTitle[title_id]()
15 describes information of each title. The value
title_id is a numeric value from "0" to a value
represented by the field NumberOfTitles and identifies
a title.

In the block MovieTitle[title_id](), followed
20 by an area reserved having a data length of 1 bit, a
fixed value "1" is described. In addition, followed
by an area reserved having a data length of 46 bits, a
field MovieTitleMobjIDRef is described. The field
MovieTitleMobjIDRef has a data length of 16 bits and
25 represents the ID of a movie object used in this title.
The field MovieTitleMobjIDRef is followed by an area
reserved having a data length of 32 bits.

Fig. 8 shows syntax that represents an example of the structure of the file "MovieObject.bdmv" placed immediately below the directory "BDMV". A field TypeIndicator has a data length of 32 bits (4 bytes) and denotes that this file is the file "MovieObject.bdmv". The field TypeIndicator describes a four-letter character string encoded according to an encoding system prescribed in the ISO (International Organization for Standardization) 646. In the example shown in Fig. 8, the field TypeIndicator describes a four-letter character string "MOBJ" encoded according to a system prescribed in the ISO 646 and denotes that this file is the file "MovieObject.bdmv".

A field TypeIndicator2 has a data length of 32 bits (4 bytes) and represents the version number of this file "MovieObject.bdmv". In this file "MovieObject.bdmv", the field TypeIndicator2 should be four-letter character string "0100" encoded according to an encoding system prescribed in the ISO 646.

A field ExtensionDataStartAddress has a data length of 32 bits and represents the start address of blkExtensionData() in this syntax. The field ExtensionDataStartAddress represents the start address of the block blkExtensionData() as the relative number of bytes from the beginning of bytes of this file "MovieObject.bdmv". The relative number of bytes starts with "0". If the value of this field

ExtensionDataStartAddress is "0", it denotes that the block blkExtensionData() does not exist in the file "MovieObject.bdmv".

5 A field padding_word in syntax shown in Fig. 8 has a data length of 16 bits. According to syntax of this file "MovieObject.bdmv", the field padding_word is inserted the number of times represented by a value N1 or a value N2 into a for loop statement. The value N1 or the value N2 is "0" or any positive integer. As the
10 field padding_word, any value can be used.

Followed by the field ExtensionDataStartAddress, an area reserved having a data length of 224 bits is placed. Thereafter, a block blkMovieObjects() that is the main
15 body of this file "MovieObject.bdmv" is stored.

Fig. 9 shows syntax that represents an example of the structure of the block blkMovieObjects(). A field Length has a data length of 32 bits and represents the data length immediately
20 after this field Length until the end of this block blkMovieObjects(). Followed by an area reserved having a data length of 32 bits, a field NumberOfMobjs is placed. The field NumberOfMobjs represents the number of movie objects stored according to a for loop
25 statement immediately preceded by the field NumberOfMobjs. A movie object is uniquely identified by a value mobj_id used as a loop variable of the for

loop statement. The value `mobj_id` starts with "0".
Movie objects are defined in the order described in the
for loop statement.

A block `TerminalInfo()` in the for loop
5 statement describes a fixed value "1", followed by an
area reserved having a data length of 15 bits.
Thereafter, a field `NumberOfNavigationCommands[mobj_id]`
having a data length of 16 bits is placed. This field
`NumberOfNavigationCommands[mobj_id]` represents the
10 number of navigation commands (`NavigationCommand`)
contained in a movie object `MovieObject[mobj_id]()`
represented by a value `mobj_id`.

According to a for loop statement with a loop
variable of value `command_id`, navigation commands are
15 described for the number represented by a field
`NumberOfNavigationCommands[mobj_id]`. In other words,
the field `NavigationCommand[mobj_id][command_id]` placed
in this for loop statement contains navigation commands
`NavigationCommand`'s in the order represented by a value
20 `command_id` contained in a block `MovieObject[mobj_id]()`
represented by a value `mobj_id`. The value `command_id`
starts with "0". The navigation commands
`NavigationCommand`'s are defined in the order described
in this for loop statement.

25 Fig. 10 shows syntax that represents an
example of the structure of a play list file
"xxxxx.mpls". A field `TypeIndicator` has a data length

of 32 bits (4 bytes) and denotes that this file is a
play list file. A field TypeIndicator2 has a data
length of 32 bits (4 bytes) and represents the version
of this play list file. A field PlayListStartAddress
5 has a data length of 32 bits and represents the start
address of a block blkPlayList() in this syntax.

A field PlayListMarkStartAddress has a data
length of 32 bits and represents the start address of a
block blkPlayListMark() in this syntax. A field
10 ExtensionDataStartAddress has a data length of 32 bits
and represents the start address of a block
blkExtensionData() in this syntax. The field
ExtensionDataStartAddress represents the start address
of a block blkExtensionData() as the relative number of
15 bytes from the beginning of bytes of the file
"xxxxx.mpls". The relative number of bytes starts with
"0". If the value of the field
ExtensionDataStartAddress is 0, it denotes that the
block blkExtensionData() does not exist in this file
20 "xxxxx.mpls".

Followed by an area reserved having a data
length of 160 bits, a block blkAppInfoPlayList() is
placed. The block blkAppInfoPlayList() describes
information such as the type and reproduction
25 restrictions of a play list described in the next block
blkPlayList(). The block blkPlayList() describes a
play list. The block blkPlayListMark() describes a

point to be jumped as in a chapter jump. The block `blkExtensionData()` is a block that can store predetermined extension data.

Fig. 11 shows syntax that represents an example of the structure of the block `blkPlayList()`. A field `Length` has a data length of 32 bits and represents the data length immediately after this field `Length` until the end of the block `blkPlayList()`. The field `Length` is followed by an area reserved having a data length of 16 bits, followed by a field `NumberOfPlayItems`. The field `NumberOfPlayItems` has a data length of 16 bits and represents the number of play items contained in this block `blkPlayList()`. A field `NumberOfSubPath` represents the number of sub paths contained in this block `blkPlayList()`.

According to the next for loop statement, blocks `blkPlayItem()`'s that describe a play item are described for the number represented by the field `NumberOfPlayItems`. A count value based on the for loop statement becomes an identifier `PlayItem_id` of a block `blkPlayItem()`. According to the next for loop statement, blocks `blkSubPath()`'s are described for the number represented by the field `NumberOfSubPath`. A count value based on the for loop statement becomes an identifier `SubPath_id` of a block `blkSubPath()`.

A sub path can be provided corresponding to a sub play item while a main path is provided

corresponding to a play item that is mainly reproduced.
A sub path can be used to designate for example audio
data for after-recording, and a sub image to be
reproduced in synchronization with a clip designated in
5 a play item.

Fig. 12 shows syntax that represents an
example of the structure of a block blkPlayItem(). A
field Length has a data length of 16 bits and
represents the data length immediately after this field
10 Length until the end of the block blkPlayItem().

A field ClipInformationFileName has a data
length of 40 bits (5 bytes) and represents the file
name of a clip information file to which this block
blkPlayItem() refers. In this play item, a clip
15 information file having a filename represented by the
field ClipInformationFileName is read. A field
ClipCodecIdentification has a data length of 32 bits (4
bytes) and represents the codec system of a clip AV
stream used in this play item in this block
20 blkPlayItem().

Followed by an area reserved having a data
length of 12 bits, a field ConnectionCondition is
placed. The field ConnectionCondition has a data
length of 4 bits and represents information about a
25 connection state of clips. For recordable record
mediums, as the value of the field ConnectionCondition,
"1", "5", or "6" is used. When the value of the field

ConnectionCondition is "1", it denotes that a clip referred from the current play item and a clip referred from the immediately earlier play item are not seamlessly connected. When the value of the field

5 ConnectionCondition is "5" or "6", it denotes that a clip referred from the current play item and a clip referred from the immediately earlier play item are seamlessly connected. The term "seamlessly connected" means that the reproduction of clips is controlled such
10 that one clip and the next clip are successfully reproduced at frame timings.

When the value of the field ConnectionCondition is "5", the recording length of audio data of a clip to which the current play item
15 refers is longer than the recording length of video data thereof (refer to Fig. 13A). Thus, when clips are connected, a fade-out process for audio data can be performed. For example, when a clip is closed by a user's record stop operation, the value of the field
20 ConnectionCondition is "5". Hereinafter, the clip connection method of which the value of the field ConnectionCondition is "5" is referred to as the first seamless connection.

When the value of the field
25 ConnectionCondition is "6", the recording length of audio data of a clip to which the current play item refer is the same as the recording length of video data

thereof (refer to Fig. 13B). Thus, clips can be seamlessly connected. For example, when a clip is closed due to a cause of the system other than a user's record stop operation, the value of the field ConnectionCondition is "6". Hereinafter, the clip connection method of which the value of the field ConnectionCondition is referred to as the second seamless connection.

A field RefToSTCID has a data length of 8 bits and represents information about a discontinuous point of a system timebase (STC). A field INTime and a field OUTTime each have a data length of 32 bits and represent the reproduction range of a main clip AV stream. The field INTime represents a start point (IN point), whereas the field OUTTime represents an end point (OUT point).

A block blkUOMaskTable() is a table in which an acceptance restriction for a user's input is set. A flag PlayItemRandomAccessFlag that has a data length of 1 bit prescribes permission/restriction of random access for the play item of this block blkPlayItem(). Thereafter, followed by an area reserved having a data length of 7 bits, a field StillMode is placed. The field StillMode has a data length of 8 bits and denotes whether or not the last picture of the play item in the block blkPlayItem() is displayed as a still image. When the value of the field StillMode is "0x01"

(binary), a field StillTime that has a data length of 16 bits represents a still time based on an if statement. When the value of the field StillMode is not "0x01", an area having a data length of 16 bits is reserved.

A numeric value with "0x" denotes that it is expressed in hexadecimal notation. This applies to the similar notation.

A block blkSTNTable() manages an attribute of the clip AV stream, PID number, record position on the record medium, and so forth that the play item of this block blkPlayItem() manages.

Fig. 14 shows syntax that represents an example of the structure of a block blkPlayListMark(). A field Length has a data length of 32 bits and represents the data length immediately after this field Length until the end of the block blkPlayListMark().

A field NumberOfPlayListMark has a data length of 16 bits and represents the number of play list marks contained in this block blkPlayListMark(). According to the next for loop statement, information of play list marks for the number represented by the field NumberOfPlayListMarks is described.

In the for loop statement, followed by an area reserved having a data length of 8 bits, a field MarkType is placed. The field MarkType has a data length of 8 bits and represents the type of a mark.

Play list marks are defined as two types of marks that are an entry mark (Entry Mark) and a link point (Link Point). This field MarkType represents one of these types. To define a chapter, an entry mark is used.

5 Since link points less relate to the present invention, its description will be omitted. The foregoing field NumberOfPlayListMarks represents the total value of entry marks and link points.

10 A field RefToPlayItemID has a data length of 16 bits and describes identification information PlayItem_id that represents a play item to which a mark is placed. A field MarkTimeStamp has a data length of 32 bits and describes a time stamp that represents a point to which a mark is placed. A field EntryESPID
15 has a data length of 16 bits and represents the value of the PID of a TS packet that contains an elementary stream represented by a mark. A field Duration is an unsigned integer that has a data length of 32 bits and that represents a measured result in the unit of a 45
20 kHz clock. When the value stored in this field Duration is "0", this field is meaningless.

Fig. 15 shows syntax that represents an example of the structure of a clip information file. A field TypeIndicator has a data length of 32 bits (4
25 bytes) and denotes that this file is a clip information file. A field TypeIndicator2 has a data length of 32 bits (4 bytes) and represents the version of this clip

information file.

5 This clip information file has a block
blkClipInfo(), a block blkSequenceInfo(), a block
blkProgramInfo(), a block blkCPI(), a
10 block blkClipMark(), and a block blkExtensionData(). A
field SequenceInfoStartAddress, a field
ProgramInfoStartAddress, a field CPIStartAddress, a
field ClipMarkStartAddress, and a field
ExtensionDataStartAddress each have a data length of 32
10 bits and represent the start address of their
corresponding block.

The field ExteensionDataStartAddress
represents the start address of the block
blkExtensionData() as the relative number of bytes from
15 the beginning of bytes of this clip information file.
The relative number of bytes starts with "0". If the
value of this field ExtensionDataStartAddress is "0",
it denotes that the block blkExtensionData() does not
exist in this file "index.bdmv".

20 The block blkClipInfo() after an area
reserved having a data length of 96 bits preceded by
the fields that represents their start address. The
block blkClipInfo() describes information about a clip
AV stream that this clip information file manages. The
25 block blkSequenceInfo() describes information with
which sequences having continuous STCs and ATCs
(arrival time base) are managed as one sequence. The

block blkProgramInfo() describes information, for example, about the encoding system and aspect ratio of the clip AV stream managed in this clip information file. The block blkCPI() stores information, for example, about characteristic point information CPI that represents characteristic points such as a random access start point in the AV stream.

The block blkClipMark() describes an index point (jump point) such as a chapter position added to a clip for a cue operation. The block blkExtensionData() is an area that can store extension data. Since the block blkClipMark() and the block blkSequenceInfo() in the clip information file less relate to the present invention, their description will be omitted.

Fig. 16 shows syntax that represents an example of the structure of a block blkClipInfo(). A field Length has a data length of 32 bits and represents the data length immediately after this field Length until the end of the block blkClipInfo(). Followed by an area reserved having a data length of 16 bits, a field ClipStreamType is placed.

The field ClipStreamType has a data length of 8 bits and represents the type of a clip AV stream. The value of this field ClipStreamType is fixed, for example, "1". A field ApplicationType has a data length of 8 bits and denotes how a clip AV stream (a

file having an extension "m2ts") has been multiplexed.
When the value of the field ApplicationType is "1", the
corresponding clip AV stream is reproduced as a regular
moving picture. The field ApplicationType is followed
5 by an area reserved having a data length of 31 bits.

A flag IsCC5 has a data length of 1 bit and
denotes whether or not the corresponding clip and the
next clip are connected by the foregoing first seamless
connection, namely the method of which the value of the
10 field ConnectionCondition is "5" with the block
blkPlayItem() of the play list. When the value of the
flag IsCC5 is "1" (binary value), it denotes that clips
are connected by the first seamless connection.

A field TSRecordingRate represents the
15 recording rate of a clip AV stream file in the unit of
bytes/second. A field NumberOfSourcePackets represents
the number of source packets contained in a clip AV
stream. Followed by an area reserved having a data
length of 1024 bits, a block TSTypeInfoBlock() is
20 placed. The block TSTypeInfoBlock() stores information
that represents the type of packets that store a clip
AV stream. Since this block TSTypeInfoBlock() less
relates to the present invention, its detailed
description will be omitted.

25 When the value of the foregoing flag IsCC5 is
"1", followed by an if statement, information is
described. Followed by an area reserved having a data

length of 8 bits after the if statement, a field
FollowingClipStreamType is placed. The field
FollowingClipStreamType has a data length of 8 bits and
represents the type of a clip preceded by the clip
5 corresponding to the clip information file. Followed
by an area reserved having a data length of 32 bits, a
field FollowingClipInformaionFileName is placed.

The field FollowingClipInformaionFileName has
a data length of 40 bits and describes the file name of
10 the clip information file corresponding to the next
clip of the clip corresponding to this clip information
file. The next field ClipCodecIdentifier has a data
length of 32 bits (4 bytes) and represents the encoding
system of the next clip. In this example, the field
15 ClipCodecIdentifier is a fixed four-letter character
string "M2TS" encoded according to a system prescribed
in the ISO 646. Next, an area reserved having a data
length of 8 bits is placed.

Fig. 17 shows syntax showing an example of
20 the structure of a block blkProgramInfo(). A field
Length has a data length of 32 bits and represents the
data length immediately after this field Length until
the end of the block blkProgramInfo(). Followed by an
area reserved having a data length of 15 bits, a fixed
25 value "1" having a data length of 1 bit is described.

A field SPNProgramSequenceStart has a data
length of 32 bits and describes a source packet number

with which a program sequence starts in the corresponding clip AV stream. A field ProgramMapPID has a data length of 16 bits and represents the value of the PID of a TS packet that contains a program map section applicable to the program sequence. A field
5 NumberOfStreamsInPS has a data length of 8 bits and represents the number of elementary streams defined in the program sequence. The field NumberOfStreamsInPS is followed by an area reserved having a data length of 8
10 bits.

According to the next for loop statement, with a loop variable of a value [stream_index], pairs of a field StreamPID[stream_index] and a block
blkStreamCodingInfo(stream_index) are stored for the
15 number represented by the field NumberOfStreamInPS. The field StreamPID[stream_index] represents the value of the PID corresponding to the elementary stream described in the PMT (Program Map Table) referred by the program sequence. The next block
20 blkStreamCodingInfo(stream_index) describes information about the encoding system of the elementary stream represented by the corresponding field StreamPID[stream_index].

Fig. 18 shows syntax that represents an
25 example of the structure of a block blkStreamCodingInfo(stream_index). A field Length has a data length of 8 bits and represents the data length

immediately after this field Length to the end of the block blkStreamCodingInfo(stream_index).

The field Length is followed by a field StreamCodingType having a data length of 8 bits. The field StreamCodingType represents the encoding type of the elementary stream represented by the value [stream_index]. As the value of the field StreamCodingType, for example, value "0x1B", value "0x80", value "0x81", value "0x90", and value "0x91" are defined. When the value of the field StreamCodingType is "0x1B", it denotes that the encoding type of the stream is a video stream. When the value of the field StreamCodingType is "0x80" or "0x81", it denotes that the encoding type of the stream is an audio stream. When the value of the field StreamCodingType is "0x90", it denotes that the encoding type of the stream is an OB stream. When the value of the field StreamCodingType is "0x91", it denotes that the encoding type of the stream is an MB stream. According to the next if statement, information is described on the basis of the value of this field StreamCodingType.

When the value of field StreamCodingType is, for example, "0x1B" and thereby the elementary stream represented by the value [stream_index] is a video stream, according to the if statement, a field VideoFormat, a field FrameRate, and a field AspectRatio

are described, followed by an area reserved having a data length of 2 bits, and a flag CCFlag is described. After the flag CCFlag, an area reserved having a data length of 17 bits and an area reserved having a data length of 128 bits are placed.

The field VideoFormat has a data length of 4 bits and represents the format of video data represented by the value [stream_index]. Fig. 19 shows an example of a list of formats of video data represented by the field VideoFormat. As exemplified in Fig. 19, the format of video data is identified by value "0" to value "15" represented by 4 bits. Value "0" and value "8" to value "15" are reserved. Value "1" to value "7" represent 480i, 576i, 480p, 1080i, 720p, 1080p, and 576p of formats of video data, respectively.

Suffixes "i" and "p" of the video formats represent interlace scanning and progressive scanning, respectively. On the other hand, numerals of the video formats represent the numbers of scanning lines. These video formats have been standardized by ITU (International Telecommunication Union)-R, BT.601-4 (480i and 576i), ITU-R BT.1358 (576p), SMPTE (Society of Motion Picture and Television Engineers) 293M (480p), SMPTE 274M (1080i and 1080p) and SMPTE 296M (720p).

In the block blkStreamCodingInfo(stream_index), the field FrameRate

has a data length of 4 bits and represents the frame rate of video data represented by the value [stream_index]. Fig. 20 shows an example of a list of frame rates represented by the field FrameRate. As exemplified in Fig. 20, the frame rates of video data are identified by value "0" to value "15" represented by 4 bits. Value "0", value "5", and value "8" to value "15" are reserved. Value "1" to value "4" represent (24000/1001) Hz (namely around 23.97 Hz), 24 Hz, 25 Hz, and (30000/1001) Hz (namely around 29.97 Hz) as frame rates (field frequencies), respectively. Value "6" and value "7" represent 50 Hz and (60000/1001) Hz (namely around 59.94 Hz) as frame rates, respectively.

In the block blkStreamCodingInfo(stream_index), the field AspectRatio has a data length of 4 bits and represents the aspect ratio of video data represented by the value [stream_index]. Fig. 21 shows an example of a list of frame rates represented by the field AspectRatio. As exemplified in Fig. 21, the aspect ratio of video data is identified by value "0" to value "15" of the field AspectRatio represented by 4 bits. Value "0", value "1", and value "4" to value "15" are reserved. Value "2" represents 4 : 3 as an aspect ratio. Value "3" represents 16 : 9 as an aspect ratio.

In the block

blkStreamCodingInfo(stream_index), when the value of the field StreamCodingType is "0x80", "0x81", "0x90", or "0x91", according to the description of "else if" of the if statement, information is described on the basis of the encoding type represented by the value. Since the description about streams of encoding types other than a video stream less relates to the present invention, the detailed description will be omitted.

Fig. 22 shows syntax that represents an example of the structure of a block blk(PIC) of a clip information file. In an encoded stream such as an MPEG stream that has been inter-frame compressed, the decoding start position is limited to a part of the encoded stream such as the beginning of a GOP (Group Of Picture). A CPI (Characteristic Point Information) is a database of information of decoding start positions. The CPI correlates reproduction times and addresses of a file. In other words, the CPI has a table of information that represents start positions of decoding units.

When such a database is defined, if video data are reproduced from any time, the address of the file corresponding to the reproduction position can be obtained by referring to the CPI on the basis of the reproduction time. Since this address is the beginning of a decoding unit, the player can read the data from the address of the file and quickly display a picture.

The start position of a decoding unit contained in the CPI (in this example, the start position of a GOP) is referred to as an EP (Entry Point) entry.

5 In Fig. 22, a field Length has a data length of 32 bits and represents the data length immediately after this field Length until the end of the block blkCPI(). According to the next if statement, unless the value of the field Length is "0", followed by an
10 area reserved having a data length of 12 bits, a field CPIType is placed. The field CPIType has a data length of 4 bits and represents the type of the CPI. The next block blkEPMMap stores a table that associates PTS
15 values with byte addresses of the corresponding clip AV stream file.

 Fig. 23 shows syntax that represents an example of the structure of a block blkEPMMap(). Followed by an area reserved having a data length of 8 bits, a field NumberOfStreamPIDEntries is placed. The
20 field NumberOfStreamPIDEntries has a data length of 8 bits and represents the number of entries of blocks blkEPMMapForOneStreamPID's in the block blkEPMMap(). According to a for loop statement, with a loop variable of a value [k], information about entry points is
25 described for the number represented by the field NumberOfStreamPIDEntries.

 In the for loop statement, a field

StreamPID[k] has a data length of 16 bits and represents the value of the PID of a transport packet that transports an elementary stream referred from a block blkEPMAPForOneStreamPID as a 14-th entry of the
5 block blkEPMAP() (hereinafter, described as the [k]-th block blkEPMAPForOneStreamPID).

Followed by an area reserved having a data length of 10 bits, a field EPStreamType[k] is placed. The field EPStreamType[k] has a data length of 4 bits
10 and represents the type of an elementary stream referred from the [k]-th block blkEPMAPForOneStreamPID. A field NumberOfEPCoarseEntries[k] has a data length of 16 bits and represents the number of entries in a coarse unit search sub table (EP coarse table) in the
15 [k]-th block blkEPMAPForOneStreamPID. A field NumberOfEPFineEntries[k] has a data length of 18 bits and represents the number of entries in a fine unit search sub table (EP fine table) in the [k]-th block blkEPMAPForOneStreamPID. A field
20 EPMapForOneStreamPIDStartAddress[k] has a data length of 32 bits and represents the relative byte position of the beginning of the [k]-th block blkEPMAPForOneStreamPID in the block blkEPMAP(). This value is represented by the number of bytes from the
25 first byte of the block blkEPMAP().

After the description of the foregoing for loop statement, followed by a padding word having a

data length of an integer multiple of 16 bits,
according to a for loop statement, with a loop variable
of a value [k], blocks

blkEPMAPForOneStreamPID(EPStreamType[k],

5 NumberOfEPCoarseEntries[k], and

NumberOfEPFineEntries[k])'s are stored for the number
represented by the field NumberOfStreamPIDEntries. In
other words, the argument NumberOfEPCoarseEntries[k]
represents the number of entries PTSEPCoarse's and
10 entries SPNEPCoarse's stored in the sub table (EP
coarse table). Likewise, the argument

NumberOfEPFineEntries[k] represents the number of
entries PTSEPFine's and entries SPNEPFie's stored in
the sub table (EP fine table). Hereinafter, the
15 argument NumberOfEPCoarseEntries[k] and the argument
NumberOfEPFineEntries[k] are sometimes referred to as
the number of entries Nc and the number of entries Nf,
respectively.

Fig. 24 shows syntax that represents an
20 example of the structure of a block

blkEPMAPForOneStreamPID(EP_stream_type, Nc, Nf). To
describe semantics of the block

blkEPMAPForOneStreamPID(EP_stream_type, Nc, Nf),
meaning of an entry PTSEPStart and an entry SPNEPStart
25 that are entries as the sources of data stored in the
block blkEPMAPForOneStreamPID(EP_stream_type, Nc, Nf)
will be described.

An entry PTSEPStart and an entry SPNEPStart associated with the entry PTSEPStart represent entry points of an AV stream. An entry PTSEPFine and an entry PTSEPCoarse associated with an entry PTSEPFine are obtained from the same entry PTSEPStart. In addition, an entry SPNEPFine and an entry SPNEPCoarse associated with an entry SPNEPFine are obtained from the same entry SPNEPStart.

Fig. 25 shows an example of formats of the entry PTSEPCoarse and the entry PTSEPFine. The PTS, namely the entry PTSEPStart, has a data length of 33 bits. When the MSB and the LSB of the entry PTSEPStart are 32-th bit and 0-th bit, respectively, in the example shown in Fig. 25, 14 bits from the 32-th bit to the 19-th bit of the entry PTSEPStart are used for the entry PTSEPCoarse for a coarse unit search. The entry PTSEPCoarse allows for a search with a resolution in the range from 5.8 seconds. to 26.5 hours. Eleven bits from the 19-th bit to the 9-th bit of the entry PTSEPStart are used for the entry PTSEPFine for a fine unit search. The entry PTSEPFine allows for a search with a resolution in the range from 5.7 milliseconds to 11.5 seconds. The 19-th bit of the entry PTSEPStart is commonly used for the entry PTSEPCoarse and the entry PTSEPFine. Nine bits from the 0-th bit to the 8-th bit on the LSB side of the entry PTSEPStart are not used.

Fig. 26 shows an example of the formats of

the entry SPNEPCoarse and the entry SPNEPFine. The source packet number, namely the entry SPNEPStart has a data length of 32 bits. When the MSB and the LSB of the entry SPNEPStart are 31-st bit and 0-th bit, in the example shown in Fig. 26, all bits from the 31-st bit to the 0-th bit of the entry SPNEPStart are used for the entry SPNEPCoarse for a coarse unit search.

Seventeen bits from the 16-th bit to the 0-th bit of the entry SPNEPStart are used for the entry SPNEPFine for a fine unit search. The entry SPNEPFine allows for a search for up to around 25 MB (Mega Byte) AV stream file.

For a source packet number, a predetermined number of bits on the MSB side of the entry SPNEPCoarse may be used. For example, seventeen bits from the 31-st bit to the 16-th bit of the entry SPNEPStart may be used for the entry SPNEPCoarse and seventeen bits from the 16-th bit to the 0-th bit of the entry SPNEPStart may be used for the entry SPNEPFine.

Based on the foregoing, the entry PTSEPStart and the entry SPNEPStart are defined as follows.

As shown in Fig. 25, the entry PTSEPStart is an unsigned integer that has a data length of 33 bits and represents a PTS having a data length of 33 bits of a video access unit that starts with a random accessible picture (for example, an IDR (Instantaneous Decoding Refresh) picture or an I (Intra) picture) of

an AV stream.

As shown in Fig. 26, the entry SPNEPStart is an unsigned integer having a data length of 32 bits and represents the address of a source packet including the first byte of a video access unit associated with the entry PTSEPStart in an AV stream file. The entry SPNEPStart is represented as a source packet number. The entry SPNEPstart is counted as a value that starts with "1" and increments by 1 for each source packet from the first source packet of an AV stream file.

Referring to Fig. 24, the block blkEPMMapForOneStreamPID(EP_stream_type, Nc, Nf) describes a first for loop statement and a second for loop statement. The first for loop statement describes a sub table (EP coarse table) for a coarse unit search. The second for loop statement describes a sub table (EP fine table) for a fine unit search performed on the basis of the search result of the sub table (EP coarse table).

The first for loop statement is immediately preceded by a field EPFineTableStartAddress. The field EPFineTableStartAddress has a data length of 32 bits and represents the start address of the first byte of a field ReservedEPFine[EP_fine_id] of the second for loop as the relative number of bytes from the first byte of the block blkEPMMapForOneStreamPID(EP_stream_type, Nc, Nf). The relative number of bytes starts with value

"0".

The first for loop statement is repeated with a loop variable [i] the number of times presented by the number of entries of the sub table (EP coarse table). Pairs of a field RefToEPFineID[i], an entry PTSEPCoarse[i], and an entry SPNEPCoarse[i] are stored for the number represented by the number of entries Nc. In the first for loop statement, the field RefToEPFine[i] has a data length of 18 bits and represents the entry number in the sub table (EP fine table) of the entry PTSEPFine associated with the entry PTSEPCoarse represented by the field PTSEPCoarse[i] preceded by the field RefToEPFineID[i]. The entry PTSEPFine and the entry PTSEPCoarse associated with this entry PTSEPFine are obtained from the same entry PTSEPStart. The field RefToEPFineID[i] is obtained by the value of the loop variable [EP_fine_id] defined in the order described in the second for loop statement.

After the first for loop statement, followed by a padding word, the second for loop statement is described. The second for loop statement is repeated with a loop variable [EP_fine_id] the number of times represented by the number of entries Nf of the sub table (EP fine table). Pairs of a field ReservedEPFine[EP_fine_id] having a data length of 1 bit, a field IEndPositionOffset[EP_fine_id] having a data length of 3 bits, a field PTSEPFine[EP_fine_id]

having a data length of 11 bits, and a field
 SPNEPFine[EP_fine_id] having a data length of 17 bit
 are stored for the number represented by the number of
 entries Nf. Among of these fields, the field
 5 PTSEPFine[EP_fine_id] and the field
 SPNEPFine[EP_fine_id] stores the entry PTSEPFine and
 the entry SPNEPFine, respectively, referred from the
 sub table (EP fine table) on the basis of the loop
 variable [EP_fine_id].

10 The entry PTSEPCoarse and the entry PTSEPFine
 and the entry SPNEPCoarse and the entry SPNEPFine are
 obtained as follows. Assuming that sub table (EP fine
 table) contains Nf entries arranged in the ascending
 order of the values of associated data SPNEPStart.

15 Each entry PTSEPFine is obtained from the corresponding
 entry PTSEPStart according to the following formula (1).

$$\text{PTSEPFine}[\text{EP_fine_id}] = (\text{PTSEPStart}[\text{EP_fine_id}] \gg 9) / 2^{11} \dots (1)$$

The relationship between the entry PTSEPCoarse and the
 20 corresponding entry PTSEPFine is expressed by the
 following formulas (2) and (3).

$$\text{PTSEPCoarse}[i] = (\text{PTSEPStart}[\text{RefToEPFineID}[i]] \gg 19) / 2^{14} \dots (2)$$

$$\text{PTSEPFine}[\text{ReFTToEPFineID}[i]] = (\text{PTSEPStart}[\text{RefToEPFineID}[i]] \gg 9) / 2^{11} \dots (3)$$

25 Each entry SPNEPFine is obtained from the
 corresponding entry SPNEPStart according to the

following formula (4).

$$\text{SPNEPFine}[\text{EP_fine_id}] = \text{SPNEPStart}[\text{EP_fine_id}] / 2^{17} \dots$$

(4)

The relationship between the entry

5 SPNEPCoarse and the corresponding entry SPNEPFine is expressed by the following formulas (5) and (6).

$$\text{SPNEPCoarse}[i] = \text{SPNEPStart}[\text{RefToEPFineID}[i]] \dots (5)$$

$$\text{SPNEPFine}[\text{RefToEPFineID}[i]] =$$

$$\text{SPNEPStart}[\text{RefToEPFineID}[i]] / 2^{17} \dots (6)$$

10 In the foregoing formulas (1) to (6), symbol ">> x" denotes that bits having digits in excess of x bits on the LSB side are used.

Next, a block blkExtensionData() for storing extension data will be described. This block

15 blkExtensionData() is defined such it can store predetermined extension data. The block blkExtensionData() can be described in each of the file "index.bdmv" that stores an index table, the file "xxxxx.mpls" that stores a play list, and a clip
20 information file "zzzzz.clpi".

Fig. 27 shows syntax that represents an example of the structure of a block blkExtensionData(). A field Length has a data length of 32 bits and represents the data length immediately after this field
25 Length until the end of the block blkExtensionData() in bytes. Unless the data length represented by the field Length is "0", followed by an if statement, information

is described.

A field `DataBlockStartAddress` has a data length of 32 bits and represents the start address of a block `DataBlock()` that stores the main body of extension data of this syntax as the relative number of bytes from the beginning of bytes of the block `blkExtensionData()`. In other words, the relative number of bytes starts with "0". The field `DataBlockStartAddress` needs to satisfy a 32-bit alignment condition that follows.

$$\text{DataBlockStartAddress} \% 4 = 0$$

Followed by an area reserved having a data length of 24 bits, a field `NumberOfExtDataEntries` is placed. The field `NumberOfExtDataEntries` has a data length of 8 bits and represents the number of entries of extension data stored in the block `DataBlock()` of the block `blkExtensionData()`. Entries of extension data store information necessary to obtain the main body of extension data. In this example, entries of extension data are a block `ext_data_entry()` that is composed of a field `ExtDataType`, a field `ExtDataVersion`, a field `ExtDataStartAddress`, and a field `ExtDataLength`. In the block `blkExtensionData()`, blocks `ext_data_entry()`'s exist for the number represented by the field `NumberOfExtDataEntries` according to the first for loop statement.

The field `ExtDataType` has a data length of 16

bits and denotes that extension data contained in this block blkExtensionData() are extension data for a recording apparatus. The value of this field ExtDataType is a first value with which extension data are identified. The value of the field ExtDataType can be defined to be assigned by a licensor of a standard including this block blkExtensionData(). The field ExtDataVersion is a second value with which extension data are identified. The field ExtDataVersion can be defined to represent the version number of this extension data. In this block blkExtensionData(), two or more entries of block ext_data_entry() cannot exist when the values of the field ExtDataType and the field ExtDataVersion of these entries are the same.

The field ExtDataStartAddress has a data length of 32 bits and represents the start address of extension data corresponding to the entry (block ext_data_entry()) of extension data that contain this field ExtDataStartAddress. The field ExtDataStartAddress represents the start address of extension data ext_data as the relative number of bytes from the beginning of bytes of the block blkExtensionData(). The field ExtDataStartAddress needs to satisfy a 32-bit alignment condition that follows.

$$\text{ExtDataStartAddress} \% 4 = 0$$

The field ExtDataLength has a data length of

32 bits and represents the data length of extension data corresponding to the entry (block ext_data_entry()) of extension data that contain the field ExtDataStartAddress. The data length is
5 represented in bytes.

When entries (blocks ext_data_entry()'s) of extension data are described for the number represented by the field NumberOfExtDataEntries, a field padding_word having a data length of 16 bits and
10 composed of any data sequence is repeated the number of times L1 as pairs of two fields. Thereafter, the block DataBlock() that stores the main body of extension data is described. The block DataBlock() stores at least one entry of extension data. Each entry of extension
15 data ext_data is obtained from the block DataBlock() based on the foregoing field ExtDataStartAddress and field ExtDataLength.

Fig. 28 shows the relationship of references of entries of data in the block blkExtensionData(). A
20 field length represents the data length immediately after the field Length until the end of the block blkExtensionData(). A field DataBlockStartAddress represents the start position of a block DataBlock(). Blocks ext_data_entry's are described for the number
25 represented by a field NumberOfExtDataEntries. A field padding_word having any data length is placed between the last block ext_data_entry and the block DataBlock().

In the block `DataBlock()`, extension data `ext_data` represented by a block `ext_data_entry()` is placed. The position and data length of each of extension data `ext_data`'s are represented by a field `ExtDataStartAddress` and a field `ExtDataLength` of the corresponding block `ext_data_entry()`. Thus, the order of extension data `ext_data`'s in the block `DataBlock()` may not need to match the order of the corresponding block' `ext_data_entry()`'s.

When extension data are structured in two layers of the block `DataBlock()` that stores the main body of the extension data and the block `ext_data_entry()` that stores access information for extension data contained in the block `DataBlock()`, a plurality of entries of extension data can be stored.

Next, an example of a method of creating and reading the foregoing extension data will be described. Fig. 29 is a flow chart showing an example of a process of writing data in the block `blkExtensionData()`. Fig. 29 shows an example of which extension data are added as an $(n+1)$ -th entry to the block `blkExtensionData()` such that the block `blkExtensionData()` is rewritten.

First of all, at step S10, the data length of extension data to be written is obtained and set as the value of the field `ExtDataLength[n+1]`. The notation "[n+1]" represents an $(n+1)$ -th entry number. At the next step S11, the values of the field `ExtDataLength`

and the field ExtDataStartAddress of blocks
ext_data_entry()'s listed in the current block
blkExtensionData() are checked and the use state of the
block DataBlock() is obtained.

5 At the next step S12, it is determined
whether or not the block DataBlock() has a continuous
free area equal to or larger than the data length
represented by the field ExtDataLength[n+1] that
represents the data length of extension data to be
10 written. When the determined result denotes that block
DataBlock() has such an area, the flow of the process
advances to step S14.

 In contrast, when the determined result
denotes that the block DataBlock() does not have a
15 continuous free area that is in excess of the data
length represented by the field ExtDataLength[n+1], the
flow of the process advances to step S13. At step S13,
the value of the field Length of the block
blkExtensionData() is increased such that a continuous
20 free area that is equal to or larger than the data
length represented by the field ExtDataLength[n+1] is
created in the block DataBlock(). After such a free
area has been created, the flow of the process advances
to step S14.

25 At step S14, the start address of the area in
which the extension data are written is decided such
that the value of the start address is set to the field

ExtDataStartAddress[n+1]. At the next step S15, the extension data ext_data[n+1] having the data length represented by the field ExtDataLength[n+1] that has been set at step S10 are written from the field

5 ExtDataStartAddress[n+1].

After the data have been written, the flow of the process advances to step S16. At step S16, the field ExtDataLength[n+1] and the field ExtDataStartAddress[n+1] are added to the block
10 ext_data_entry().

In the foregoing, it is assumed that the block blkExtensionData() to be rewritten has been read from a record medium such as a disc and stored in the memory of the recording apparatus. Thus, the increase
15 of the block blkExtensionData() by changing the value of the field Length at step S13 is performed by the system. The system properly allocates the memory.

Fig. 30 is a flow chart showing an example of a process of reading extension data from the block
20 blkExtensionData(). The process of the flow chart shown in Fig. 30 can be applied both to a reproduction-only record medium and a recordable record medium. First of all, at step S20, the value of the field ExtDataType is obtained from the standard on which
25 extension data to be read are based. At step S21, the value of the field ExtDataVersion is obtained from the type of extension data to be read.

At the next step S22, each of blocks
ext_data_entry()'s listed in the block
blkExtensionData() is read one by one. At step S23, it
is determined whether or not the values of the field
5 ExtDataType and the field ExtDataVersion of each of
blocks ext_data_entry()'s match the values of the field
ExtDataType and the field ExtDataVersion obtained at
the foregoing steps S20 and S21.

When the determined result denotes that they
10 do not match, the flow of the process advances to step
S26. At step S26, it is determined whether or not all
blocks ext_data_entry()'s listed in the block
blkExtensionData() have been read. When the determined
result denotes that all blocks ext_data_entry()'s have
15 been read, the flow of the process advances to step S27.
At step S27, since extension data to be read do not
exist in the block blkExtensionData(), the process is
completed. In contrast, when the determined result
denotes that all blocks ext_data_entry()'s have not
20 been read, the flow of the process returns to step S22.
At step S22, the next block ext_data_entry() is read.

When the determined result at step S23
denotes that the values of the field ExtDataType and
the field ExtDataVersion of the block ext_data_entry()
25 match the values of the field ExtDataType and the field
ExtDataVersion obtained at the foregoing steps S20 and
S21, the flow of the process advances to step S24. In

this example, it is assumed that they match for the [i]-th entry of the block blkExtensionData().

At step S24, the value of the field ExtDataLength[i] and the value of the field ExtDataStartAddress[i] are read from the [i]-th entry of the block ext_data_entry(). At step S25, data are read from the address represented by the field ExtDataStartAddress[i] that has been read at step S24 for the data length represented by the field ExtDataLength[i].

Next, the extension data block blkExtensionData() that stores extension data and that can be defined in the foregoing index file "index.bdmv", movie object file "MovieObject.bdmv", play list file "xxxxx.mpls", and clip information file "zzzzz.clpi" will be described.

First of all, an example of an extension data block defined in the index file "index.bdmv" will be described. In this example, an extension data block of which attribute information unique to a recordable record medium is added to each play list will be described. Fig. 31 shows syntax that represents an example of the structure of a block DataBlock() (refer to Fig. 27) of a block blkExtensionData() in the file "index.bdmv". In the example shown in Fig. 31, the block DataBlock() is described as the block blkIndexExtensionData().

First of all, with reference to Fig. 27,
value "0x1000" and value "0x0100" are set to the field
ExtDataType and the field ExtDataVersion of the block
blkExtensionData(), respectively. The values that have
5 been described in these field ExtDataType and field
ExtDataVersion are identified with reference to a table
that has been stored, for example, in the ROM (Read
Only Memory) on the reproducing apparatus side. The
block blkIndexExtensionData() is stored in an area
10 represented by the field ExtDataStartAddress and the
field ExtDataLength in the block DataBlock().

In the block blkIndexExtensionData(), a field
TypeIndicator describes a four-letter character string
encoded according to an encoding system prescribed in
15 the ISO 646. The four-letter character string
represents the type of data that follow. In the
example shown in Fig. 31, the field TypeIndicator
describes a four-letter character string "IDEX" that
has been encoded according to the system prescribed in
20 the ISO 646 and that denotes that the type of data that
follow is extension data of an index file.

The field TypeIndicator is followed by an
area reserved having a data length of 32 bits, followed
by a field TableOfPlayListStartAddress having a data
25 length of 32 bits. The field
TableOfPlayListStartAddress represents the start
address of the block blkTableOfPlayList() based on the

beginning of this block blkIndexExtensionData().

The field TableOfPlayListStartAddress is followed by a field MakersPrivateDataStartAddress having a data length of 32 bits. The field

5 MakersPrivateDataStartAddress represents the start address of a block blkMakersPrivateData() based on the beginning of the block blkIndexExtensionData().

Followed by an area reserved having a data length of

10 192 bits, a block blkUIAppInfoAVCHD() is placed. A padding word padding_word having a data length of 16 bits is repeated the number of times represented by a value N1. Thereafter, the block blkTableOfPlayList()

is placed. Thereafter, a padding word padding_word having a data length of 16 bits is repeated the number
15 of times represented by a value N2. Thereafter, a

block blkMakersPrivateData() is placed. The block blkMakersPrivateData() is followed by a padding word padding_word having a data length of 16 bits. The
padding word padding_word is repeated the number of
20 times represented by a value N3.

Since the block blkUIAppInfoAVCHD() and the block blkMakersPrivateData() less relate to the present invention, their description will be omitted.

Fig. 32 shows syntax that represents an
25 example of the structure of the foregoing block blkTableOfPlayList(). A field length has a data length of 32 bits and represents the data length immediately

after this field Length until the end of the block
blkTableOfPlayList() in bytes. The field Length is
followed by a block blkFirstPlaybackTitlePlayLists()
that describes information about a play list with which
5 a playback title is reproduced and a block
blkMenuTitlePlayLists() that describes information
about a menu title. Since these block
blkFirstPlaybackTitlePlayLists() and block
blkMenuTitlePlayLists() less relate to the present
10 invention, their description will be omitted.

Thereafter, a field NumberOfTitlePlayListPair
having a data length of 16 bits is placed. The field
NumberOfTitlePlayListPair describes the number of play
lists with which a title other than a playback title
15 and a menu title is reproduced. According to the next
for loop statement, blocks
blkMovieTitlePlayListPair()'s are described for the
number represented by the field
NumberOfTitlePlayListPair. The block
20 blkMovieTitlePlayListPair() contains a field
PlayListFileName, a field PlayListAttribute, and a
field RefToTitleId. In other words, the block
blkMovieTitlePlayListPair() structurizes information of
composed of the file name, attributes, and reference
25 title ID for the [i]-th play list represented by this
for loop statement.

Entries in the for loop statement are based

on the order of which they are recorded. In other words, when one play list is added, the value of the field NumberOfTitlePlayListPair is incremented by "1" and information of the added play list is additionally written after information of existing play lists.

The field PlayListFileName has a data length of 40 bits (5 bytes) and describes the file name of the play list that has been encoded according to an encoding system prescribed in the ISO 646. The field PlayListFileName is followed by an area reserved having a data length of 6 bits, followed by the field PlayListAttribute. The field PlayListAttribute has a data length of 2 bits and represents an attribute assigned to the current play list. Play lists are categorized on the basis of their causes as a first type created together with a clip, a second type corresponding to a play list created with an existing title or all or a part of a play list, and a third type used to reproduce a menu. Each play list is assigned an attribute "Real" (first type), an attribute "Virtual" (second type), or an attribute "Menu" (third type) depending on the type of the play list.

Hereinafter, a play list assigned the attribute "Real" is referred to as a real play list. A play list assigned the attribute "Virtual" is referred to as a virtual play list. A play list assigned the attribute "Menu" is referred to as a menu play list.

The field RefToTitleId describes the ID (number) of the title to which the play list represented in the field PlayListFileName of the same loop belongs when the play list is created. As a more specific example, the field RefToTitleId describes the corresponding value title_id of the block blkIndexes() in the index file "index.bdmv". When this play list is reproduced only from a first play back title, the value of the field RefToTitleId is a first fixed value, for example, "0xFFFF". On the other hand, when this play list is reproduced only from a menu title, the value of the field RefToTitleId is a second fixed value, for example, "0xFFFE".

Next, a real play list, a virtual play list, and a menu play list will be described in brief. A real play list assigned the attribute "Real" is created together with for example a clip and recorded on a disc. Since a real play list is the first play list that represents a material, it is also referred to as an original play list. For example, in a real play list, the beginning and last end of a created clip are designated as an IN point and an OUT point, respectively.

A real play list is a play list that refers to a clip that is the entity of a stream. When a clip is newly created, a real play list that refers to the created clip is always created. In other words, there

is no clip that is not referred from any real play list. Thus, the total reproduction time of real play lists on a disc matches the total reproduction time of clips recorded on the disc. In other words, the remaining
5 recordable time of the disc matches the recordable time of real play lists or a title composed of only real play lists from the view point of the user.

A real play list and a clip as a material always have the relationship of one to one. Thus, when
10 a real play list is deleted, for example, by editing, the corresponding clip is also deleted from the disc. In addition, when a part of a real play list to which clip refers is deleted, a part of the clip corresponding to the real play list is also deleted.
15 Thus, when a real play list is edited, the entity of a clip recorded on the disc is also changed. Thus, this editing is referred to as, for example, entity editing or real editing.

A virtual play list assigned the attribute
20 "Virtual" is a play list created with an existing title or a part or all of a play list. A virtual play list is a play list created by setting an IN point and an OUT point to an existing clip and referring to a region defined by the IN point and the OUT point.

25 For example, a virtual play list designates an IN point and an OUT point for the foregoing real play list. For example, a virtual play list designates

an IN point and an OUT point for each of a plurality of real play lists and designates the reproduction order of the plurality of regions designated by these IN points and OUT points. In addition, based on a virtual play list, another virtual play list may be created. In other words, a virtual play list that designates an IN point and an OUT point for one or each of a plurality of virtual play lists can be created.

A virtual play list can be quickly created without necessity of changing a clip for example having a large size (stream entity). In addition, a virtual play list can be deleted by deleting the reference relation to a clip without necessity of changing the entity of the clip. Since a virtual play list is edited without necessity of changing the entity of a clip, this editing is referred to as virtual editing or the like.

A menu play list assigned the attribute "Menu" is a play list used to reproduce a menu. A menu play list is created when a menu is created or updated. A menu play list is a play list called from a movie object used to reproduce a menu title.

Next, an example of an extension data block defined to the play list file "xxxxx.mpls" will be described. Fig. 33 shows syntax that represents an example of the structure of a block DataBlock() (refer to Fig. 27) of the block blkExtensionData() in the play

list file "xxxxx.mpls". In the example shown in Fig. 33, the block `DataBlock()` is represented as the block `blkPlayListExtensionData()`.

First of all, with reference to Fig. 27, it is assumed that the values of the field `ExtDataType` and the field `ExtDataVersion` of the block `blkExtensionData()` in the play list file "xxxxx.mpls" are predetermined values, for example, value "0x1000" and value "0x0100", respectively, as in the foregoing example.

In the block `blkPlayListExtensionData()`, a field `TypeIndicator` describes a predetermined four-letter character string that has been encoded according to an encoding system prescribed in the ISO 646 and that represents the type of data that follow. The character string described in this field `TypeIndicator` denotes that the type of data that follow is extension data of a play list file.

The field `TypeIndicator` is followed by an area reserved having a data length of 32 bits (4 bytes), followed by a field `PlayListMarkExtStartAddress` having a data length of 32 bits, followed by a field `MakersPrivateDataStartAddress` having a data length of 32 bits. The field `PlayListMarkExtStartAddress` and the field `MakersPrivateDataStartAddress` represent the start addresses of the block `blkPlayListExt()` and the block `blkMakersPrivateData()` based on the beginning of the

block blkPlayListExtensionData().

5 The field MakersPrivateDataStartAddress is
followed by an area reserved having a data length of
192 bits, followed by a block blkPlayListMenu(). A
padding word padding_word having a data length of 16
bits is repeated the number of times represented by a
value N1. Thereafter, a block blkPlayListMarkExt() is
placed. In addition, a padding word padding_word
having a data length of 16 bits is repeated the number
10 of times represented by a value N2, followed by a block
blkMakersPrivateData(). The block
blkMakersPrivateData() is followed by a padding word
padding_word having a data length of 16 bits. The
padding word padding_word is repeated the number of
15 times represented by a value N3.

Fig. 34 shows syntax that represents an
example of the structure of the block blkPlayListMeta().
A field Length has a data length of 32 bits and
represents the data length immediately after this field
20 Length until the end of this block blkPlayListMenu().
The field Length is followed by a field MakerID and a
field MakerModelCode each having a data length of 16
bits. The field MakerID and the field MakerModelCode
describe a maker that has updated this play list file
25 and information that identifies the model of this maker,
respectively.

The field MakerModelCode is followed by an

area reserved having a data length of 32 bits, followed by a field RefToMenuThumbnailIndex having a data length of 16 bits. When a thumbnail image that represents a sequence of clips reproduced by this play list file exists, this field RefToMenuThumbnailIndex describes a thumbnail number that identifies the thumbnail image. Thereafter, a block blkTimeZone() that has a data length of 8 bits is placed. When this play list file is updated, information that represents the time zone that has been set to the apparatus is described in the block blkTimeZone(). Thereafter, a field RecordTimeAndData that has a data length of 56 bits is placed. The field RecordTimeAndData represents the time and data at and on which this play list file was updated.

The field RecordTimeAndData is followed by an area reserved having a data length of 8 bits, followed by a field PlayListCharacterSet and a field PlayListNameLength each having a data length of 8 bits, followed by a field PlayListName having a data length of 255 bytes. These field PlayListCharacterSet, field PlayListNameLength, and field PlayListName describes information with respect to the name of a play list represented by this play list file.

In other words, the field PlayListCharacterSet represents a character set of a character string described in the field PlayListName.

The field `PlayListNameLength` represents the byte length of the play list name described in the field `PlayListName`. The field `PlayListName` describes the name assigned to this play list. In the field `PlayListName`, the number of bytes from the left represented by the field `PlayListNameLength` is a significant character string that is the name of this play list. In the field `PlayListName`, the significant character string represented by the field `PlayListNameLength` may be followed by any value.

The field `PlayListName` is followed by a block `Additional_data()`. This block `Additional_data()` is a reserved area that stores additional information. In the block `Additional_data()`, an area having a data length of the number of bytes represented by a field `Length2` having a data length of 32 bits is reserved.

Fig. 35 shows syntax that represents an example of the structure of the block `blkMakersPrivateData()` in a play list file. The block `blkMakersPrivateData()` is a block that describes maker's unique information about this play list file. A field `length` has a data length of 32 bits and represents the data length immediately after this field `length` until the end of this block `blkMakersPrivateData()`. When the value of this field `length` is "0", it denotes that this `MakersPrivateData()` does not describe information. Unless the value of the

field Length is "0", followed by an if statement,
information is described.

A field DataBlockStartAddress has a data
length of 32 bits and represents the start address of
5 block DataBlock() that stores the main body of maker's
unique information in this syntax as the relative
number of bytes from the beginning of this block
blkMakersPrivateData(). Followed by an area reserved
having a data length of 24 bits, a field
10 NumberOfMakerEntries having a data length of 8 bits is
placed.

According to the next for statement, entries
of extension data, namely fields MakerID's, fields
MakerModelCode's, fields MpdStartAddress's, and fields
15 MpdLength's, are described for the number represented
by the field NumberOfMakerEntries. The field MakerID
and the field MakerModelCode each have a data length of
16 bits and represent identification information of the
maker and identification information of the model of
20 the maker, respectively. The field MpdStartAddress and
the field MpdLength each have a data length of 32 bits
and represent the start address of the block
DataBlock() that stores the main body of extension data
from the beginning of the block blkExtensionData() as
25 the relative number of bytes and the data length of the
block DataBlock(), respectively.

When entries of extension data are described

for the number represented by the field
NumberOfMakerEntries, a field padding_word that has a
data length of 16 bits and that is composed of any data
sequence is repeated the number of times L1 as pairs of
5 two fields. Thereafter, the block DataBlock() that
stores the main body of extension data is described.
The block DataBlock() stores at least one extension
data ext_data. In other words, maker's unique
extension data are stored in the block DataBlock() for
10 each maker and each model represented by the field
MakerID and the field MakerModelCode, respectively.
Each entry of extension data is obtained from the block
DataBlock() based on the foregoing field
MpdStartAddress and field MpdStartAddress.

15 Since the block blkPlayListMarkExt() in the
block blkPlayListExtensionData() of extension data of a
play list file less relates to the present invention,
the description will be omitted.

20 Next, an example of an extension data block
defined for the clip information file "zzzzz.clpi" will
be described. Fig. 36 shows syntax that represents an
example of the structure of the block DataBlock()
(refer to Fig. 27) in the block blkExtensionData () in
a clip information file. In the example shown in Fig.
25 36, the block DataBlock() is represented as a block
blkClipExtensionData().

In the block blkClipExtensionData(), a field

TypeIndicator describes a predetermined character string composed of four letters that represents the type of data that follow and that has been encoded according to an encoding system prescribed in the ISO 646. The character string described in the field TypeIndicator denotes that the type of data that follow is extension data of a clip information file.

The field TypeIndicator is followed by an area reserved having a data length of 32 bits (4 bytes), followed by a field ProgramInfoExtStartAddress and a field MakersPrivateDataStartAddress each of which has a data length of 32 bits, respectively. The field ProgramInfoExtStartAddress and the field MakersPrivateDataStartAddress represent the start address of the block blkProgramInfoExt() and the block blkMakersPrivateData() in the block blkClipExtensionData() based on the beginning of this block blkClipExtensionData().

The field MakersPrivateDataStartAddress is followed by an area reserved having a data length of 192 bits, followed by a block blkClipInfoExt(). A padding word padding_word having a data length of 16 bits is repeated the number of times represented by a value N1, followed by a block blkProgramInfoExt(). Thereafter, a padding word padding_word having a data length of 16 bits is repeated the number of times represented by a value N2, followed by a block

blkMakersPrivateData(). The block
blkMakersPrivateData() is followed by a padding word
padding_word having a data length of 16 bits. The
padding word padding_word is repeated the number of
5 times represented by a value N3.

Fig. 37 shows syntax that represents an
example of the structure of the block blkClipInfoExt().
A field Length has a data length of 32 bits and
represents the data length immediately after this field
10 Length until the end of the block blkProgramInfoExt().
Thereafter, followed by an area reserved having a data
length of 8 bits, a field NumberOfProgramSequence is
placed.

The field NumberOfProgramSequence has a data
15 length of 8 bits and represents the number of entries
of information of the program sequence contained in
this block blkProgramInfoExt(). In this example, the
value of the field NumberOfProgramSequence is fixed to
"1". According to the next first for loop statement, a
20 field NumberOfStreamCodingInfoExtInPs[i] and the next
second for loop statement are repeated the number of
times represented by the field NumberOfProgramSequence.
The second for loop statement stores pairs of fields
StreamPIP[i][j]'s and blocks blkStreamCodingInfoExt(i,
25 j)'s for the number represented by the field
NumberOfStreamCodingInfoExtInPs[i] having a data length
of 8 bits.

The field StreamPIP[i][j] has a data length of 16 bits. The field StreamPIP[i][j] composes a table designated by a value [i] and a value [j] and represents the value of the PID corresponding to an elementary stream described in a PMT (Program Map Table) referred from an [i]-th program sequence. The next block blkStreamCodingInfoExt(i, j) describes information with respect to the encoding system of the elementary stream designated by the value [i] and the value [j].

Fig. 38 shows syntax that represents an example of the structure of the block blkStreamCodingInfoExt(i, j). A field Length has a data length of 8 bits and represents the data length immediately after this field Length until the end of the block blkStreamCodingInfoExt(i, j). The next field StreamCodingType has a data length of 8 bits and represents the type of encoding of the corresponding stream. When the value of the field StreamCodingType is "0x1B", followed by an if statement, information is described. The first field HorizontalSize having a data length of 8 bits represents the vertical size of the screen, namely the number of lines of the screen. Since information preceded by the field HorizontalSize in the block blkStreamCodingInfoExt(i, j) less relates to the present invention, the description will be omitted.

In addition, since the block ClipEnfoExt()
and the block blkMakersPrivateData() in the block
blkClipExtensionData() of a clip information file less
relate to the present invention, their description will
5 be omitted.

Next, a virtual player will be described in
brief. When a disc having the foregoing data structure
is loaded into a player, the player needs to convert
commands contained in a movie object or the like that
10 has been read from the disc into unique commands with
which hardware of the player is controlled. The player
has stored software with which such conversion is
performed for these commands in a ROM (Read Only
Memory) built in the player. Since this software
15 causes the player to operate in accordance with
prescriptions of the AVCHD format through the disc and
the player, this software is referred to as the virtual
player.

Fig. 39A and Fig. 39B show an outline of the
20 operation of the virtual player. Fig. 39A shows an
example of which the virtual player loads a disc. When
the disc is loaded into the player and the disc is
initially accessed (at step S30), registers that store
common parameters commonly used for one disc are
25 initialized (at step S31). At the next step S32, a
program described in a movie object or the like is read
from the disc and executed. The initial access denotes

that data are initially reproduced from the disc, for example, when the disc is loaded.

Fig. 39B shows an example of the operation of the player in the case that the user presses, for example, a play key in the stop state to command the player to reproduce data from the disc. In the initial stop state (at step S40), the user commands the player to reproduce data from the disc, for example, with a remote control commander or the like (UO: User Operation). When the player is commanded to reproduce data from the disc, the registers, namely common parameters, are initialized (at step S41). At the next step S42, a movie object execution phase starts.

Next, with reference to Fig. 40, the reproduction of a play list in the movie object execution phase will be described. It is assumed that by the UO or the like, the player has been commanded to start reproducing contents of title #1 from the disc. When the player has been commanded to start reproducing contents from the disc, the player refers to the index table (Index Table) shown in the foregoing Fig. 2 and obtains an object number corresponding to the reproduction of contents of title #1. Assuming that the number of an object that accomplishes the execution of contents of title #1 is #1, the player starts executing movie object #1.

In the example shown in Fig. 40, assuming

that a program described in movie object #1 is composed of two lines and a command of the first line is "Play Playlist(1)", the player starts reproducing play list #1. Play list #1 is composed of one or more play items. The player continuously reproduces the play items. After the player has completed the reproduction of all the play items of play list #1, the player restores the execution of movie object #1 and executes a command of the second line. In the example shown in Fig. 40, the command of the second line is "jump MenuTitle". The player executes this command and starts executing a movie object that accomplishes the menu title (MenuTitle) described in the index table.

Next, an embodiment of the present invention will be described. According to the present invention, when a clip is recorded to a record medium, a chapter based on the clip to be recorded is additionally written to an existing play list. When a chapter is additionally written to an existing play list, it is determined whether or not the chapter based on the clip can be additionally written to the play list based on predetermined restrictions of the play list. When the determined result denotes that the chapter can be additionally written, the chapter based on the clip is additionally written to the play list. In contrast, when the determined result denotes that the chapter cannot be additionally written, a play list is newly

created and the chapter based on the recorded clip is registered thereto.

When such a recording control is performed, the user can record a clip without necessity of recognizing restrictions of the play list. As a result, the operability of the apparatus is improved and the user friendliness becomes excellent.

Fig. 41 shows an outline of an example of the structure of a recording apparatus according to an embodiment of the present invention. This recording apparatus records an AV stream of which input digital video data and digital audio data have been compression-encoded and multiplexed in a predetermined system to a record medium.

The recording apparatus exemplified in Fig. 41 may be a single recording apparatus that records video data and audio data that are input from the outside to a record medium or a recording block that is used for a video camera apparatus together with a camera block having an optical system, an image capturing device, and so forth and that records video data based on a captured image signal to a record medium.

It can be contemplated that there are many types of applicable compression-encoding systems and multiplexing systems. For example, a system defined in the H. 264 | AVC may be applied for a compression-

encoding system of an embodiment of the present invention. Instead, compression-encoding may be performed on the basis of the MPEG2 system. On the other hand, as a multiplexing system, for example, the MPEG2 systems may be used. In the following, it is assumed that video data are compression-encoded on the basis of a system prescribed in the H. 264 | AVC and video data and audio data are multiplexed on the basis of a system prescribed in the MPEG2 systems.

A control section 30 is composed of, for example, a CPU (Central Processing Unit), a RAM (Random Access Memory), a ROM (Read Only Memory), and so forth (not shown). The control section 30 controls each section of a recording section 10 of the recording apparatus using the RAM as a work memory on the basis of a program and data stored in the ROM. In Fig. 41, lines that connect the control section 30 and each section of the recording section 10 are omitted to prevent the drawing from becoming complicated.

A UI (User Interface) section 31 has operation switches with which the user operates the recording apparatus and outputs control signals according to the operations of the operation switches. The control signals are supplied to the control section 30. The control section 30 controls the operation of each section of the recording section 10 with processes of software performed on the basis of the control

signals supplied from the UI section 31 according to the user's operation. For example, the control section 30 controls the record start and stop operations of the recording apparatus according to operations for the UI section 31.

For example, the control section 30 executes application software that provides a user interface and controls each section of the recording section 10 on an OS (Operating System) that is composed of predetermined programs and provides fundamental functions of software. In addition, the control section 30 executes driver software that mediates software and hardware of each section of the recording section 10. The OS also provides a file system that manages files and data recorded on a record medium 20. The file system will be described later. The application software accesses files recorded on the record medium 20 through the file system provided by the OS.

Base band digital video data are input from a terminal 40. As the digital video data are input, base band digital audio data are input from a terminal 41.

The digital video data are input from the terminal 40 to the recording section 10 and supplied to a video encoder 11. The video encoder 11 compression-encodes the supplied digital video data according to the predetermined system. In this example of which compression-encoding is performed on the basis of the

system prescribed in the H. 264 | AVC, intra-frame compression is performed, for example, using DCT (Discrete Cosine Transform) and intra-screen prediction. Inter-frame compression is performed using a moving
5 vector. Entropy encoding is performed to improve the compression efficiency. Digital video data that have been compression-encoded by the video encoder 11 are supplied as an H. 264 | AVC elementary stream (ES) to a multiplexer (MUX) 13.

10 Digital audio data are input from the terminal 41 to the recording section 10 and supplied to an audio encoder 12. The audio encoder 12 compression-encodes the digital audio data according to the predetermined compression-encoding system, for example,
15 AC3 (Audio code number 3). The compression-encoding system for audio data is not limited to AC3. Instead, base band audio data are contemplated to be used without compression-encoding audio data. The digital audio data that have been compression-encoded are
20 supplied to a multiplexer 13.

The multiplexer 13 multiplexes the digital video data and digital audio data, which have been compression-encoded and provided, according to the predetermined system and outputs the multiplexed data
25 as one data stream. In this example of which multiplexing is performed on the basis of the MPEG2 systems, the provided compressed video data and audio

data are multiplexed on the time division basis using an MPEG2 transport stream. For example, the multiplexer 13 has a buffer memory. The multiplexer 13 stores the compressed video data and audio data that have been supplied in the buffer memory.

The compressed video data stored in the buffer memory are PES (packetized Elementary Stream) packetized by dividing them in a predetermined size and adding a header to each divided portion. Likewise, the compressed audio data are PES-packetized by dividing them in a predetermined size and adding a header to each divided portion. The header stores predetermined information prescribed in the MPEG2 systems, such as a PTS that represents the reproduction time of data stored in the packet and a DTS (Decoding Time Stamp) that represents the decoding time. The PES packet is further divided and stored in a payload of a transport packet (TS packet). A header of the TS packet stores a PID (Packet Identification) that identifies data stored in the payload. The TS packet that is output from the multiplexer 13 is temporarily stored in a stream buffer 14.

Specifically, a header having a predetermined size is added to the TS packet by the multiplexer 13. The TS packet with the header is output. A packet to which the predetermined header is added to the TS packet is referred to as a source packet.

A recording control section 15 controls recording of data to the record medium 20. As the record medium 20, for example, a recordable type DVD (Digital Versatile Disc) may be used. Instead, as the record medium 20, a hard disk drive may be used. Instead, a semiconductor memory may be applied for the record medium 20. A Blu-ray Disc (registered trademark) that accomplishes a larger capacity than other record mediums can be contemplated to be applied for the record medium 20.

The recording control section 15 monitors the amount of data stored in the stream buffer 14. When data stored in the stream buffer 14 is in excess of a predetermined amount, data are read from the stream buffer 14 for the amount of the recording unit of the record medium 20 and written to the record medium 20.

A management information processing section 16 is composed of, for example, a CPU, a RAM as a work memory, and a ROM that pre-stores a program and predetermined data (these sections are not shown). In addition, the management information processing section 16 can accomplish its function by a program process of, for example, the control section 30. In this case, the RAM of, for example, the control section 30 is used as a nonvolatile memory 17 and a nonvolatile memory 18 is connected to the control section 30.

The management information processing section

16 uses the nonvolatile memory 17 as a work memory on the basis of record data and creates information to be stored in the foregoing index file "index.bdmv", movie object file "MovieObject.bdmv", play list file "xxxxx.mpls", and clip information file "zzzzz.clpi".
The created information is written to the record medium 20 at a predetermined timing.

For example, the management information processing section 16 obtains time information of the record data from the multiplexer 13 and address information of the record data for the record medium 20 from the recording control section 15 and creates EP_map information based on the obtained these time information and address information. In addition, the clip information file "zzzzz.clpi" is created on the basis of a control signal that is output from the control section 30 according to the record start operation or the record stop operation for the UI section 31 and information about the record data supplied from the multiplexer 13a and the recording control section 15. Information about the created clip information file is additionally written to the play list file. In such a manner, the play list file "xxxxx.mpls" is updated.

When the play list file is updated, it is determined whether or not the predetermined restrictions for the play list file to which

information about the clip information file is additionally written are satisfied. When the determined result denotes that the restrictions are not satisfied, a play list file is newly created.

5 Information about the created clip information file is recorded to the newly created play list file.

10 In addition, when data are newly recorded to the record medium 20, the index file "index.bdmv" and the movie object file "MovieObject.bdmv" are created or updated.

Fig. 42 shows an example of the data structure applicable to an embodiment of the present invention. The index file "index.bdmv" has one or a plurality of titles. The movie object file "MovieObject.bdmv" contain one or a plurality of movie objects corresponding to the title (titles) that the index file "index.bdmv" has. Each movie object calls one play list file "xxxxx.mpls". The play list file "xxxxx.mpls" contains one or a plurality of play items. Each play item refers to clip information file "zzzzz.clpi". A clip information file "zzzzz.clpi" and a clip AV stream file "zzzzz.m2ts" that is the entity of a clip have the relationship of one to one.

25 In such a structure, the user can see a clip recorded on the record medium in the unit of a title that index file "index.bdmv" has. When the user selects his or her desired title, a movie object

corresponding to the title is referred from the movie object file "MovieObject.bdmv". A play list file "xxxxx.mpls" described in the referred movie object is called, the clip information file "zzzzz.clpi" is referred according to a play item contained in the play list file, and the corresponding clip AV stream file "zzzzz.m2ts" is reproduced.

When a mark (play list mark) that represents time information is added to a play list file "xxxxx.mpls", a jump position can be set. A chapter is defined with a mark. A chapter is a reproduction unit of a title that the user can see. A mark is always placed at a record start position. A mark may be placed at a position other than a record start position.

In other words, when a play list mark for the record start operation is set in a play list file "xxxxx.mpls" and a play item that refers to a clip is registered, a chapter is formed in the play list file. In other words, when a play list mark is recorded to a play list file and a play item is recorded, it can be said that a chapter is recorded to the play list file.

As described above, a real play list is created together with a clip. In the example shown in Fig. 42, play list files "00000.mpls", "00200.mpls", and "00018.mpls" have an attribute of a real play list.

Among them, the play list file "00000.mpls" is an example of which information about a newly

created clip is additionally written to a play list.

For example, play item #1 that refers to a clip

information file "00125.m2ts" corresponding to the

newly recorded clip AV stream file "00125.m2ts" is

5 additionally recorded to a play list file "00000.mpls"

that has stored play item #0 that refers to a clip

information file "00001.clpi" corresponding to a clip

AV stream file "00001.m2ts". A mark is placed at the

start time that a play item represents. When the play

10 list file "00000.mpls" is reproduced, the clip AV

stream file "00001.m2ts" is reproduced on the basis of

play item #0. Thereafter, the clip AV stream file

"00125.m2ts" is reproduced on the basis of play item #1.

The play list file "00200.mpls" is an example

15 of which one play list file is created for one clip and

the play list file contains only one play item.

In addition, the play list file "00018.mpls"

is an example of which a plurality of play items refer

to one clip. It can be contemplated that when the

20 record start operation or the record stop operation is

performed, control is performed such that a play item

is created and data are additionally written to one

clip. A mark is placed at the beginning of play item

#0. By continuously reproducing play item #0 and play

25 item #1, the entire clip AV stream file "00002.m2ts" is

reproduced.

On the other hand, as represented as a play

list file "00005.mpls" shown in Fig. 42, a virtual play
list designates a reproduction region for existing
clips. In this example, play item #0 contained in the
play list file "00005.mpls" refers to a clip
5 information file "00028.clpi" and designates a region.
Play item #1 refers to the clip information file
"00002.clpi" and designates a region. Marks are placed
at the beginning of the play item #0 and play item #1.
When the play list file "00005.mpls" is reproduced, a
10 designated region of the clip AV stream file
"00028.m2ts" is reproduced on the basis of the play
item #0. Thereafter, the clip AV stream file
"00002.m2ts" is reproduced on the basis of the play
item #1.

15 According to the present invention, as
described above, it is determined whether a chapter
based on a newly recorded clip is additionally written
to an existing play list file or recorded to a newly
created play list file based on the restrictions of the
20 play list file. An example of restrictions of a play
list file is as follows. Restrictions of a play list
file can be contemplated to include those on the format,
those on the mounting specifications, and those on
product specifications.

25 Restrictions on the format can be
contemplated to be the following restriction (1) to
restriction (7).

Restriction (1): The upper limit of the number of play items that can exist in one play list file.

Restriction (2): The upper limit of the number of play list marks that can exist in one play list file.

5 Restriction (3): When one play list file refers to a plurality of clips, their predetermined video attributes need to match each other.

Restriction (4): The upper limit of the file size of one play list file.

10 Restriction (5): The upper limit of the total file size of a clip information file associated with one play list file.

Restriction (6): The upper limit of the total of entry points for coarse unit searches in a clip information file associated with one play list file.

15 Restriction (7): The upper limit of the total of entry points for fine unit searches in a clip information file associated with one play list file.

20 Among those, with respect to the number of play items of the restriction (1) and the number of play list marks of the restriction (2), the upper limit of the number of play items that can exist in one play list is restricted, for example, to 999 and the upper limit of the number of play list marks that can exist in one play list file is restricted, for example, to 999 on the format. Thus, when a chapter based on a clip that is newly recorded is additionally written to

a play list file, it is necessary to determine whether or not these restrictions are satisfied.

With respect of video attributes of the restriction (3), the format prescribes that in a plurality of clip AV stream files to which one play list file refers, their attributes about encoding of video data such as frame size, scanning system, aspect ratio, frame rate, and codec type of a plurality of clip AV stream files to which one play list file refers need to match each other. Thus, when a clip is newly recorded, it is necessary to compare the attributes of a clip referred from a play item that has been recorded in a play list file to which a chapter based on the clip is additionally written with those of the clip newly recorded.

With respect to the file size of one play list of the restriction (4) and the total file size of a clip information file associated with one play list file of the restriction (5), their upper limits are prescribed. The prescription of the file size is associated with the memory capacity of the recording apparatus and the reproducing apparatus.

In other words, when the record operation is performed, a play list corresponding to a clip that has been recorded and a clip information file of a clip that has been recorded are temporarily stored in the memory of the recording apparatus. When the record

operation is performed, an update process is performed for the play list file and the clip information file on the memory. These play list file and clip information file stored in the memory are written to the record medium at a predetermined timing. With the restriction about the total file size of a play list file and a clip information file associated with one play list file, a situation of which the memory becomes full during the record operation and it is forcedly stopped can be prevented.

The upper limit of the file size of a play list file is, for example, 600 kB (kilobytes). When the upper limit of the file size of one clip information file is, for example, 1 MB (megabytes), the upper limit of the total file size of a clip information file associated with one play list file is, for example, 2 MB.

The upper limits of the restriction (6) and the restriction (7) are associated with the upper limit of the file size of the foregoing clip information file. In other words, as described above, an entry point for a coarse unit search and an entry point for a fine unit search are information stored in the block blkEPMMap() of the block blkCPI() in a clip information file. In other words, an entry point for a coarse unit search is the field PTSEPCoarse and the field SPNEPCoarse of the block blkEPMMap(). An entry point for a fine unit

search is the field PTSEPFine and the field SPNEPFine of the block blkEPMMap().

The upper limit of the total of entry points for coarse unit searches and that of entry points for fine unit searches in a clip information file associated with one play list file are prescribed on the format. Thus, when a clip is newly recorded, it is necessary to determine whether or not these restrictions are satisfied in a play list file to which a play item that refers to the clip is additionally written.

Restrictions on the mounting specifications can be contemplated to have the following items.

Restriction (8): With respect to the block blkMakersPrivateData() in an extension data block of a play list file, when information of the block blkMakersPrivateData() of a play list file recorded by another apparatus cannot be taken over, the play list file must not be updated.

For example, as represented in the block DataBlock() shown in Fig. 35, the data size of the block blkMakersPrivateData() of extension data block of a play list file is not restricted. Thus, it can be contemplated that data having a relatively large data size, for example, several 100 kB, are written depending on specifications of the apparatus. It may be difficult to update or edit a play list file with

taken-over information of the block
blkMakersPrivateData() having a large size recorded by
another apparatus, for example, due to the restriction
of the memory capacity.

5 Restrictions on the product specifications
can be contemplated to be the following items.

Restriction (9): Even if concepts of titles and
chapters of one apparatus are different from those of
another apparatus, it is necessary to prevent the user
10 from confusing them.

Restriction (10): It is necessary to be able to
continuously perform a capturing operation and a
recording operation for a prescribed time period or
more.

15 With respect to titles and chapters of the
restriction (9), play lists and chapters can be
contemplated to have different structures depending on
the apparatus. Thus, when a record medium on which a
clip has been recorded by one apparatus is reproduced
20 by another apparatus, there is a possibility of which a
title may be abnormally displayed.

For example, it is assumed that a stationary
type recording and reproducing apparatus (such as a
video deck) that records a television broadcast has the
25 following specifications. One program corresponds to
one play list. Play list marks are automatically placed
as chapters at intervals of 5 minutes. Whenever a

video camera apparatus captures one image, namely the apparatus performs the record start operation, a play list mark is placed as a chapter. A plurality of chapters are registered to one play list. In addition,
5 it is assumed that the stationary type recording and reproducing apparatus has the following specifications. A thumbnail image of only the beginning of a play list is displayed. Thus, a thumbnail image of each chapter is not displayed.

10 In these conditions, it is assumed that a record medium on which a play list file created by the stationary type recording and reproducing apparatus has been recorded is loaded into a video camera apparatus and a play item that refers to a clip recorded by the
15 video camera apparatus is additionally written and recorded to a play list file created by the stationary type recording and reproducing apparatus. In this case, as a later scene of a program recorded by the stationary type recording and reproducing apparatus, a
20 picture captured by the video camera apparatus is registered as a chapter. When the record medium of the video camera apparatus is loaded into the stationary type recording and reproducing apparatus again and the program is reproduced thereby, the chapter of the
25 picture captured by the video camera apparatus is not displayed as a thumbnail image. Instead, the chapter is unnaturally reproduced as the last scene of the

program recorded by the stationary type recording and reproducing apparatus.

With respect to the continuous capturing and recording for a prescribed time period or more of the restriction (10), specifications of a recoding apparatus commonly assure continuous recording for a predetermined time period or more. On the other hand, as described above, the format prescribes the upper limit of the total number of entry points in a clip information file associated with one play list. Even if the record medium has a sufficient free space, entry points for a predetermined time period to be assured in the play list file to which a play item that refers to a clip to be newly recorded may not be assured because of the total number of entry points of the clip information file that has been referred and the upper limit prescribed in the format. Thus, when a clip is newly recorded, it is necessary to determine whether or not continuous recording for the predetermined time period or more can be performed on the basis of the number of entry points associated with the play list file to which a play item that refers to the clip is additionally written.

Next, a process of determining whether or not a chapter based on a clip to be newly recorded can be additionally written to a play list file according to an embodiment of the present invention will be

described. The determinations for the foregoing restriction (1) to restriction (10) are performed one by one. When the determined result denotes that at least one of these restrictions cannot be satisfied, a
5 play list is newly created and a chapter based on a clip newly recorded is recorded to the newly created play list.

Fig. 43 is a flow chart showing an example of a process of determining whether or not a chapter based on a newly recorded clip can be additionally written to
10 a play list. First of all, with reference to the flow chart shown in Fig. 43, a flow of an overall process will be described in brief. In this example, it is assumed that the record medium 20 is a disc-shaped record medium such as a recordable type DVD
15 (hereinafter, referred to as the disc). In the recording apparatus described with reference to Fig. 41, each determination process and so forth that follow are performed by the control section 30.

20 When the record medium 20 is loaded into the recording apparatus, the control section 30 controls the recording control section 15 to read an index file "index.bdmv" from the record medium 20 (at step S100). The index file "index.bdmv" that has been read is
25 stored in the nonvolatile memory 17, for example, through the management information processing section 16.

At the next step S101, the control section 30 identifies a candidate of a play list (play list file) to which a chapter based on a clip to be recorded next is additionally written on the basis of information described in the index file "index.bdmv" stored in the nonvolatile memory 17.

For example, with reference to the block blkTableOfPlayLists() in the block blkIndexExtensionData() that is an extension data block of the index file "index.bdmv", the block blkTableOfPlayLists() is searched for the newest real play list that has been recorded and thereby the file name thereof is obtained.

More specifically, with reference to Fig. 29, blocks blkMovieTitlePlayListPair()'s listed in the block blkIndexExtensionData() are searched for a block blkMovieTitlePlayListPair() that has the field PlayListattribute assigned the attribute "Real" and that is described as the last block blkMovieTitlePlayListPair() in the block blkIndexExtensionData() and thereby data of the field PlayListFileName is obtained from the retrieved block blkMovieTitlePlayListPair().

At the next step S102, the play list file as the additionally writable candidate identified at step S101 is read from the record medium 20 and stored to the nonvolatile memory 17. Thereafter, all clip

information files associated with the play list file as the additionally writable candidate that has been read are read from the record medium 20. The clip information files that have been read are stored in the nonvolatile memory 17.

More specifically, with reference to Fig. 10 to Fig. 12, all blocks blkPlayItem()'s in the blocks blkPlayList()' are referred in the play list file as the additionally writable candidate. All data of the fields ClipInformationFileName's in the blocks blkPlayItem()'s are obtained. All clip information files represented in the data of the obtained fields ClipInformationFileName's are read from the record medium 20.

At the following step S104 to step S111, it is determined whether or not a chapter can be additionally written on the basis of the play list file as the additionally writable candidate and clip information files stored in the nonvolatile memory 17 according to the foregoing restrictions. In other words, at step S104, the additionally writing ability/inability determination is performed on the basis of the number of play items contained in the play list file as the additionally writable candidate obtained at step S101 according to the foregoing restriction (1). At the next step S105, the additionally writing ability/inability determination is

performed on the basis of the number of play list marks contained in the play list file as the additionally writable candidate according to the foregoing restriction (2). At the next step S106, the

5 additionally writing ability/inability determination is performed on the basis of video attributes described in the play list file as the additionally writable candidate and video attributes of the clip to be newly recorded according to the foregoing restriction (3).

10 At the next step S107, the additionally writing ability/inability determination is performed on the basis of the file size of the play list file of the additionally writable candidate according to the foregoing restriction (4). At the next step S108, the

15 additionally writing ability/inability determination is performed on the basis of the total file size of the clip information files referred from the play list file as the additionally writable candidate according to the foregoing restriction (5). At the next step S109, the

20 additionally writing ability/inability determination is performed on the basis of the total number of entry points stored in the clip information files referred from the play list file as the additionally writable candidate according to the foregoing restrictions (6)

25 and (7).

At the next step S110, the additionally writing ability/inability determination is performed on

the basis of presence or absence of unique extension data of another apparatus in the play list file as the additionally writable candidate according to the foregoing restriction (8). At the next step S111, the additionally writing ability/inability determination is performed on the basis of the last update apparatus of the play list file as the additionally writable candidate according to the foregoing restriction (9).

At the next step S112, it is finally determined whether or not the chapter based on the clip newly recorded can be additionally written to the play list file as the additionally writable candidate on the basis of the determination result of each of the determination processes from the foregoing step S104 to step S111. The determined result of each process of step S104 to step S111 is stored, for example, in the register or the like of the control section 30. At step S112, a determination is performed on the basis of the determined result of each process stored in the register.

In other words, when the determined result in each process at each of step S104 to step S111 represents additionally writable, the flow of the process advances to step S112. At step S112, it is determined whether or not the chapter based on the clip newly recorded be additionally written to the play list file as the additionally writable candidate obtained at

step S101.

In contrast, when at least one of the determined results of the additionally writing ability/inability determinations of step S104 to step S111 represents additionally not-writable, it is determined that the chapter based on the play list file as the additionally writable candidate obtained at step S101 be not able to be additionally written. In this case, a play list file of a real play list is newly created and the chapter based on the clip that is newly recorded is recorded to the newly created play list file.

The order of the processes from step S104 to step S111 is not limited to the foregoing order. In other words, the order of the processes from step S104 to step S111 may be changed in any manner. Instead, the processes from step S104 to step S111 may be performed in parallel. All the processes from step S104 to step S111 may not be performed. Instead, one or a plurality of these processes may be selectively performed.

Next, the processes from step S104 to step S111 will be described one by one in more detail. Fig. 44 shows an example of the additionally writing ability/inability determination process on the basis of the number of play items contained in the play list file as the additionally writable candidate according

to the restriction (1) at step S104. In this process,
as exemplified at step S120, with reference to the
block blkPlayList() (refer to Fig. 11) of the play list
file as the additionally writable candidate, the value
5 of the field NumberOfPlayItems is obtained. The
obtained value of the field NumberOfPlayItems is
compared with the upper limit value that has been set
for the number of play items that can exist in one play
list file, for example, value "999".

10 When the compared result denotes that the
value of the field NumberOfPlayItems is smaller than
the predetermined upper limit value, it is determined
that the chapter based on the clip that is newly
recorded be able to be additionally written to the play
15 list file as the additionally writable candidate. In
contrast, when the value of the field NumberOfPlayItems
is equal to or larger than the predetermined upper
limit value, it is determined that the chapter be not
able to be additionally written to the play list file
20 as the additionally writable candidate.

Fig. 45 shows an example of the additionally
writing ability/inability determination process on the
basis of the number of play list marks contained in the
play list mark as the additionally writable candidate
25 according to the foregoing restriction (2) at step S105.
In this process, as exemplified at step S130, with
reference to the value of the block blkPlayListMark()

(refer to Fig. 14) in the play list file as the additionally writable candidate, the value of the field NumberOfPlayListMarks is obtained. The obtained value of the field NumberOfPlayListMarks is compared with the predetermined upper limit value that has been set for the number of play list marks that can exist in one play list file, for example, value "999".

When the compared result denotes that the value of the field NumberOfPlayListMarks is smaller than the predetermined upper limit value, it is determined that the chapter based on the clip that is newly recorded be able to be additionally written to the play list file as the additionally writable candidate. In contrast, when the value of the field NumberOfPlayListMarks is equal to or larger than the predetermined upper limit value, it is determined that the chapter be not able to be additionally written to the play list file as the additionally writable candidate.

As described above, there are two types of play list marks, which are entry marks and link points. At step S130, it is determined whether or not the total of these entry marks and link points is smaller than the upper limit value.

Fig. 46 shows an example of the additionally writing ability/inability determination process on the basis of video attributes described in the play list

file as the additionally writable candidate and those of the clip that is newly recorded according to the foregoing restriction (3) at step S106. First of all, at the first step S140, attribute information of video data to be recorded is obtained. In this embodiment, frame size, aspect ratio, frame rate, and scanning type (interlace/progressive) are obtained as attribute information of video data to be recorded on the basis of the capturing mode or recording mode that has been currently set to the recording apparatus.

At the following step S141 to step S144, video attributes of a clip associated with the play list file as the additionally writable candidate are obtained. In this embodiment, when a plurality of play items are stored in the play list file as the additionally writable candidate, video attributes are obtained from a clip information file referred from a play item that was recorded as the oldest play item. In brief, as video attributes, at step S141, the image width is obtained; at step S142, the image height (the number of lines) and the scanning type are obtained; at step S143, the aspect ratio is obtained; and at step S144, the frame rate is obtained.

More specifically, with reference to a block blkPlayItem() (refer to Fig. 12) stored on the topmost side of the block blkPlayList() (refer to Fig. 11) in the play list file as the additionally writable

candidate, data of the field ClipInformationFileName
are obtained as the file name of a clip information
file to which the play item refers. A clip information
file corresponding to the obtained file name is
5 referred from all clip information files that have been
read in the process of step S103 of the flow chart
shown in Fig. 43 and that are associated with the play
list as the additionally writable candidate.

At step S141, with reference to the block
10 blkProgramInfoExt() (refer to Fig. 37) in the block
blkClipExtensionData() as extension data of the clip
information file and the block blkStreamCodingInfoExt(i,
j) (refer to Fig. 38) in the block
blkProgramInfoExt(), the value of the field
15 HorizontalSize is obtained from the block
blkStreamCodingInfoExt(i, j).

At step S142, with reference to the block
blkStreamCodingInfo() (refer to Fig. 18) in the block
blkProgramInfo() (refer to Fig. 17) of the clip
20 information file, the value of the field VideoFormat is
obtained. As described with reference to Fig. 19, the
field VideoFormat represents a combination of the
number of lines of video data and the scanning system
(interlace/progressive) with a value represented by 4
25 bits.

As at step S142, at step S143, with reference
to the block blkStreamCodingInfo(), the value of the

field AspectRatio is obtained. As described with reference to Fig. 21, the field AspectRatio represents the aspect ratio of the frame of video data with a value represented by 4 bits.

5 As at step S143 and step S143, at step S144, with reference to the block blkStreamCodingInfo(), the value of the field FrameRate is obtained. As described with reference to Fig. 20, the field FrameRate represents the frame rate of video data with a value
10 represented by 4 bits.

 At step S145, each entry of attribute information of video data that are recorded and that have been obtained from the recoding apparatus at step S140 is compared with each of video attributes of a
15 clip associated with the play list file as the additionally writable candidate and obtained at step S141 to step S144.

 When the compared result denotes that all the entries of attribute information of video data that are
20 recorded mach all the video attributes of the clip associated with the play list file as the additionally writable candidate, it is determined that the chapter based on the clip that is newly recorded be able to be additionally written to the play list file as the
25 additionally writable candidate. In contrast, even if each of the attribute information of the video data that are recorded does not match each of the video

attributes of the clip associated with the play list
file as the additionally writable candidate, it is
determined that the chapter be not able to be
additionally written to the play list file as the
5 additionally writable candidate.

Fig. 47 shows an example of the additionally
writing ability/inability determination process on the
basis of the file size of the play list file as the
additionally writable candidate according to the
10 restriction (4) at step S107. In this additionally
writing ability/inability determination process, it is
determined whether or not the file size of the play
list as the additionally writable candidate to which at
least a predetermined number of chapters are
15 additionally written is in excess of the upper limit of
the file size of one play list.

The predetermined number of chapters can be
contemplated to be one chapter, a plurality of chapters,
the remaining number of chapters against the maximum
20 number of chapters that can exist in one chapter, or
the like that depends on the design concept of the
recoding apparatus. In this example, the predetermined
number of chapters is considered to be the remaining
number of chapters against the maximum number of
25 chapters that can exist in one play list file.

First of all, at step S150, size increment
SIZE_1CHAP of the play list file per chapter that has

been pre-calculated is obtained. In other words, at this step S150, the data amount of play items and play list marks that compose one chapter is calculated.

With reference to Fig. 12, in a play item, the field StillMode, the field StillTime, the block blkUOMaskTable(), and the block blkSTNTable() are data whose data lengths may vary. Specifically, data of these fields and blocks have fixed lengths depending on the recording mode or the recording apparatus. With reference to Fig. 14, the value of each field of a play list mark has a fixed length. Thus, the data size of play items and play list marks created when one clip is recorded can be pre-calculated. In addition, the calculated value characteristically does not depend on record time. The value of the size increment SIZE_1CHAP of a play list file per chapter is pre-calculated and stored, for example, in a ROM or the like of the recording apparatus. Instead, the value of the size increment SIZE_1CHAP may be calculated whenever the process of the flow chart shown in Fig. 47 is executed.

When a chapter is additionally written to a play list, a play item and a play list mark are increased. Thus, when a chapter is additionally written to a play list, it is necessary to consider the number of play items and the number of play list marks that can exist in one play list file according to the

restriction (1) and restriction (2).

At step S151, the number of play items
PI_REMAIN that can be additionally written to the play
list file as the additionally writable candidate is
5 calculated. In other words, with reference to the
block blkPlayList() (refer to Fig. 11) in the play list
file as the additionally writable candidate, the value
of the field NumberOfPlayItems is obtained as the
number of play items contained in the play list as the
10 additionally writable candidate. By subtracting the
number of play items contained in the play list as the
additionally writable candidate from the predetermined
upper limit value PI_MAX that has been set for the
number of play items that can exist in one play item,
15 for example, "999", the number of play items PI_REMAIN'
that can be additionally written to the play list as
the additionally writable candidate is obtained.

In other words, the number of play items
PI_REMAIN that can be additionally written to the play
20 list file as the additionally writable candidate can be
obtained by the following formula (1).

$$PI_REMAIN = PI_MAX - NumberOfPlayItems \dots (1)$$

At step S152, the number of play list marks
MARK_REMAIN that can be additionally written to the
25 play list file as the additionally writable candidate
is calculated. In other words, with reference to the
block blkPlayListMark() (refer to Fig. 14) in the play

list file as the additionally writable candidate, the value of the field NumberOfPlayListMarks is obtained as the number of play list marks contained in the play list as the additionally writable candidate.

5 Thereafter, by subtracting the number of play list marks contained in the play list as the additionally writable candidate from predetermined upper limit value MARK_MAX that has been set for the number of play items that can exist in one play list, for example "999", the
10 number of play list marks MARK_REMAIN that can be additionally written to the play list as the additionally writable candidate is obtained.

 In other words, the number of play list marks MARK_REMAIN that can be additionally written to the
15 play list file as the additionally writable candidate can be obtained from the following formula (2).

$$\text{MARK_REMAIN} = \text{MARK_MAX} - \text{NumberOfPlayListMarks} \dots (2)$$

 At the next step S153, the smaller one of the number of play items PI_REMAIN that can be additionally
20 written to the play list as the additionally writable candidate obtained at step S151 and the number of play list marks MARK_REMAIN that can be additionally written to the play list file as the additionally writable candidate obtained at step S152 is treated as the
25 number of chapters CHAP_REMAIN that can be additionally written to the additionally writable candidate.

 In other words, the number of chapters

CHPA_REMAIN that can be additionally written to the play list file as the additionally writable candidate can be obtained from the following formula (3) with the results of the foregoing formula (1) and formula (2) assuming that "MIN" denotes that a smaller one of values in parentheses is selected. In the formula (3), "MIN" denotes that a smaller one of values in parentheses is selected.

$$\text{CHAP_REMAIN} = \text{MIN} (\text{PI_REMAIN}, \text{MARK_REMAIN}) \dots (3)$$

At the next step S154, by obtaining the file size of the play list file as the additionally writable candidate, the remaining data size SIZE_REMAIN against the upper limit PL_SIZE_MAX of the file size of one play list file according to the restriction (4) is obtained. The file size of the play list file can be obtained, for example, using a function that the file system of the OS provides. The data size SIZE_REMAIN (kB) can be obtained from the following formula (4). In the following formula, the file size of the play list file as the additionally writable candidate is designated by FILE_SIZE(kB).

$$\text{SIZE_REMAIN(kB)} = \text{PL_SIZE_MAX(kB)} - \text{FILE_SIZE(kB)} \dots (4)$$

At the next step S155, it is determined whether or not the file size of the play list file as the additionally writable candidate to which play items and play list marks for chapters that can be

additionally written to the play list file as the additionally writable candidate are additionally written is in excess of the upper limit of the file size of one play list file.

5 In other words, it is determined whether or not the following formula (5) is satisfied with the size increment SIZE_1CHAP of the play list file per chapter obtained at step S150 and the results of formula (3) and formula (4).

10
$$\text{SIZE_1CHAP} \times \text{CHAP_REMAIN} \geq \text{SIZE_REMAIN} \dots (5)$$

 If the formula (5) is satisfied, it is determined that the chapter based on the clip that is newly recorded be able to be additionally written to the play list file as the additionally writable candidate. In contrast, if the formula (5) is not

15 satisfied, it is determined that the chapter be not able to be additionally written to the play list file as the additionally writable candidate.

 Fig. 48 shows an example of the additionally writing ability/inability determination process on the

20 basis of the total file size of clip information files referred from the play list file as the additionally writable candidate according to the foregoing restriction (5) at step S108.

25 According to the foregoing restriction (5), the upper limit value CLIP_SUM_MAX, for example 2 MB, is set for the total file size of clip information

files referred from the play list file as the additionally writable candidate. When a clip information file is added to the play list as the additionally writable candidate as a chapter is additionally written thereto, the total size of the clip information files associated with the play list file as the additionally writable candidate needs not to be in excess of the upper limit value CLIP_SUM_MAX.

At step S160, the maximum size SIZE_1CLIP that has been calculated for one clip information file is obtained. In the clip information file, the block blkEPMMap() stores information of an entry point that associates a PTS value with the byte address of a clip AV stream file (refer to Fig. 23 to Fig. 26).

Information of this entry point is a value that varies on record time. Other information stored in the clip information file is a fixed value that does not depend on record time, but rather an encoding system. On the other hand, as described above, the minimum time that assures continuous recording is set as specifications of the recording apparatus. The number of entry points for the minimum time that assures continuous recording depends on the encoding systems of video and audio of the encoder. By calculating the total data size of entry points for the minimum time that assures continuous recording, the maximum size SIZE_1CLIP is obtained on the basis of the calculated result.

At the next step S161, by obtaining the file sizes of all clip information files referred from the play list file as the additionally writable candidate, the total size SIZE_TOTAL_CLIP is calculated.

5 In other words, with reference to all the blocks blkPlayItem()'s (refer to Fig. 12) in the play list file as the additionally writable candidate, data of the field ClipInformationFileName of each of the blocks blkPlayItem()'s is obtained. The file size of
10 the clip information file represented by the obtained data of the field ClipInformationFileName is obtained for each of the blocks blkPlayItem()'s in the play list file as the additionally writable candidate. The file size of each of the blocks blkPlayItem()'s is added.
15 The file size of each clip information file can be obtained, for example, using a function that the file system of the OS provides.

At the next step S162, the value of which the total size SIZE_TOTAL_CLIP of all the clip information
20 files referred from the play list file as the additionally writable candidate calculated at step S161 is subtracted from the upper limit value of the total file size of the clip information files that can be associated with one play list file is compared with the
25 maximum size SIZE_1CLIP of one clip information file calculated at step S160 according to the following formula (6) and it is determined whether or not the

clip information files having the maximum size
SIZE_1CLIP can be additionally written to the play list
file as the additionally writable candidate.

$CLIP_SUM_MAX - SIZE_TOTAL_CLIP \geq SIZE_1CLIP \dots (6)$

5 When the compared result denotes that the
value of which the total size SIZE_TOTAL_CLIP of all
the clip information files referred from the play list
file as the additionally writable candidate is
subtracted from the upper limit value of the total file
10 size of the clip information files that can be
associated with one play list file is compared with the
maximum size SIZE_1CLIP of one clip information file is
larger than the maximum size SIZE_1CLIP of one clip
information file, it is determined that the chapter
15 based on the clip that is newly recorded be able to be
additionally written to the play list file as the
additionally writable candidate.

 In contrast, when the value of which the
total size SIZE_TOTAL_CLIP of all the clip information
20 files referred from the play list file as the
additionally writable candidate is subtracted from the
upper limit value of the total file size of the clip
information files that can be associated with one play
list file is smaller than the maximum size SIZE_1CLIP
25 of one clip information file, it is determined that the
chapter be not able to be additionally written to the
play list file as the additionally writable candidate.

Fig. 49 shows an example of the additionally writing ability/inability determination process on the basis of the total number of entry points stored in clip information files referred from the play list file as the additionally writable candidate according to the restriction (6) and restriction (7) at the foregoing step S109.

As described above, with respect to clip information files referred from one play list file, an upper limit is set for the total number of entry points stored in the block blkEPMMap(). When a clip information file is additionally written to the play list as the additionally writable candidate as a chapter is additionally written thereto, the total number of entry points stored in clip information files associated with the play list file as the additionally writable candidate needs not to be in excess of the upper limit value.

According to the restriction (6) and restriction (7), an upper limit value of entry points for coarse unit searches and an upper limit value of entry points for fine unit searches have been set. Thus, the determinations need to be performed separately for entry points for coarse unit searches and for entry points for fine unit searches.

The upper limit value MAX_EP_COARSE of the total value of entry points for coarse unit searches in

clip information files associated with one play list file is, for example, 24576. On the other hand, the upper limit value MAX_EP_FINE of the total value of entry points for fine unit searches is, for example,
5 180000.

First of all, at step S170, the maximum number of entry points per chapter pre-calculated is obtained. As described above, generally as the specifications of the recoding apparatus, the minimum
10 time that assures continuous recording is set. The maximum number of entry points for the minimum time that assures continuous recording is pre-calculated. At step S170, this value is obtained.

As described with reference to Fig. 25 and
15 Fig. 26, an entry point for a coarse unit search is placed at an interval of 11.5 seconds (PTS: entry PTSEPCoarse) or 25 MB (source packet number: entry SPNEPCoarse). When it is assumed that the minimum time that assures continuous recording is designated by the
20 time MIN_TIME(hr) and the data amount of a clip AV stream file created in recording for the minimum time is designated by the data amount MIN_SIZE(MB), the maximum number of entry points NEEDED_EP_COARSE per chapter for entry points for coarse unit searches is
25 obtained from the following formula (7). In the formula (7) and formula (8) that will be described later, "CEIL" denotes that the fragment below the

decimal point is rounded up to the next whole number of the value.

$$\text{NEEDED_EP_COARSE} = \text{CEIL} (3600 [\text{SEC}] \times \text{MIN_TIME} [\text{hr}] / 11.5 [\text{sec}] + \text{CEIL} (\text{MIN_SIZE} [\text{MB}] / 25 [\text{BM}])) \dots (7)$$

5 Entry points for fine unit searches are placed at intervals of a GOP with an accuracy of a PTS (entry PTSEPFine) or an accuracy of a source packet (entry SPNEPFine). In this embodiment, as entry points for fine unit searches, only the entry PTSEPFine is
10 used. When the frame frequency is 29.97 Hz and 1 GPO is composed of 15 frames, with respect to entry points for fine unit searches, the maximum number of entry points NEEDED_EP_FINE per chapter is obtained from the following formula (8). In the formula (8), "90 [kHz] /
15 3003" represents the frame frequency (29.97 Hz) based on the PTS accuracy.

$$\text{NEEDED_EP_FINE} = \text{CEIL} (3600 [\text{sec}] \times \text{MIN_TIME} [\text{hr}] \times 90 [\text{kHz}] / 3003 / 15 [\text{Frames/GOP}]) \dots (8)$$

20 At the next step S171, with respect to all clip information files referred from the play list file as the additionally writable candidate, entry points for coarse unit searches and entry points for fine unit searches are obtained. The total number of entry points for coarse unit searches TOTAL_EP_COARSE and the
25 total number of entry points for fine unit searches TOTAL_EP_FINE are obtained.

More specifically, the total number of entry

points for coarse unit searches TOTAL_EP_COARSE and the total number of entry points for fine unit searches TOTAL_EP_FINE can be obtained on the basis of the field NumberOfStreamPIDEntries, the field
5 NumberOfEPCoarseEntries[k], and the field
NumberOfEPFineEntries[k] in a clip information file.

At the next step S172, it is determined whether or not entry points for coarse unit searches are in excess of the upper limit value MAX_EP_COARSE
10 when the chapter is additionally written to the play list file as the additionally writable candidate. In other words, the determination is performed on the basis of the maximum number of entry points for coarse unit searches per chapter NEEDED_EP_COARSE obtained at
15 the foregoing step S170 and the total number of entry points for coarse unit searches TOTAL_EP_COARSE obtained at step S171 according to the following formula (9).

$$\text{MAX_EP_COARSE} - \text{TOTAL_EP_COARSE} \geq \text{NEEDED_EP_COARSE} \dots$$

20 (9)

If the relationship of each value does not satisfy this formula (9), namely the maximum number of entry points for coarse unit searches per chapter NEEDED_EP_COARSE is larger than the difference between
25 the upper limit value MAX_EP_COARSE of the total value of entry points for coarse unit searches of clip information files associated with one play list file

and the total number of entry points for coarse unit searches TOTAL_EP_COARSE of the clip information files associated with the play list file as the additionally writable candidate, it is determined that the chapter
5 be not able to be additionally written to the play list file as the additionally writable candidate.

In contrast, when the determined result denotes that the relationship of each value satisfies the formula (9), the flow of the process advances to
10 step S173. At step S173, with respect to entry points for fine unit searches, the same determination is performed. In other words, the determination is performed for the upper limit value of entry points for coarse unit searches MAX_EP_FINE on the basis of the
15 maximum number of entry points for fine unit searches per chapter NEEDED_EP_FINE obtained at the foregoing step S170 and the total number of entry points for fine unit searches TOTAL_EP_FINE obtained at step S171 according to the following formula (10).

20
$$\text{MAX_EP_FINE} - \text{TOTAL_EP_FINE} \geq \text{NEEDED_EP_FINE} \dots (10)$$

If the determined result denotes that the relationship of each value does not satisfy this formula (10), it is determined that the chapter be not
25 able to be additionally written to the play list file as the additionally writable candidate. In contrast, when the relationship of each value satisfies this formula (10), it is determined that the chapter be able

to be additionally written to the play list file as the additionally writable candidate.

Fig. 50 shows an example of the additionally writing ability/inability determination process on the basis of presence/absence of unique extension data of another apparatus in the play list file as the additionally writable candidate according to restriction (8) at step S110.

First of all, at the first step S180, extension data of the play list file as the additionally writable candidate are searched for extension data based on the AVCDH format.

In other words, with reference to Fig. 10, the value of the field ExtensionDataStartAddress of the play list file as the additionally writable candidate is obtained and it is determined whether or not the obtained value is "0" (not shown). When the value is not "0", since the block blkExtensionData() of extension data exists in the play list file, the block blkExtensionData() is referred on the basis of the value of the field ExtensionDataStartAddress. With reference to Fig. 33, it is determined whether or not the values of the field ExtDataType and the field ExtDataVersion of the block blkPlayListExtensionData() of extension data in the play list file are values prescribed in the AVCHD format.

At the next step S181, it is determined

whether or not extension data based on the AVCHD format exist in extension data of the play list file as the additionally writable candidate contain on the basis of the searched result at step S180.

5 In other words, if the value of the field ExtensionDataStartAddress in the play list file as the additionally writable candidate is "0" or the values of the field ExtDatatype and the field ExtDataVersion in the block blkPlayListExtensionData() of extension data
10 are not the values defined in the AVCHD format based on the searched result at step S180, it is determined that extension data defined in the AVCHD format not exist in extension data of the play list file as the additionally writable candidate. In this case, it is
15 determined that the chapter be not able to be additionally written to the play list file as the additionally writable candidate.

 In contrast, when the determined result at step S181 denotes that extension data defined in the
20 AVCHD format exist in extension data of the play list file as the additionally writable candidate, the flow of the process advances to step S182. At step S182, it is determined whether or not extension data other than the extension data based on the AVCDH format exist in
25 extension data of the play list file as the additionally writable candidate. If the determined result denotes that they exist, it is determined that

the chapter be not able to be additionally written to the play list file as the additionally writable candidate.

When the determined result at step S182 denotes that extension data other than the extension data based on the AVCHD format do not exist in extension data of the play list file as the additionally writable candidate, the flow of the process advances to step S183. At step S183, with reference to the block blkMakersPrivateData() of the block blkPlayListExtensionData() of extension data of the play list file as the additionally writable candidate, it is searched for data of this apparatus. In other words, with reference to Fig. 35, the field MakerID and the field MakerModelCode in the block blkMakersPrivateData() are searched for data that represent this apparatus.

At the next step S184, the determination is performed on the basis of the searched result at step S183. At step S184, if the determined result denotes that extension data of this apparatus do not exist on the basis of the searched result at step S183, it is determined that the chapter be not able to be additionally written to the play list file as the additionally writable candidate. In contrast, when the determined result denotes that extension data of this apparatus exist on the basis of the searched result at

step S183, the flow of the process advances to step S185.

At step S185, it is determined whether or not extension data of an apparatus other than this apparatus exist in the block blkMakersPrivateData() on the basis of the searched result at step S183. In other words, when data other than those that represent this apparatus exist in the field MakerID and the field MakerModelCode in the block blkMakersPrivateData(), it is determined that extension data of an apparatus other than this apparatus exist in the block blkMakersPrivateData().

When the determined result at step S185 denotes that extension data of an apparatus other than this apparatus exist in the block blkMakersPrivateData(), it is determined that the chapter be not able to be additionally written to the play list file as the additionally writable candidate. In contrast, when the determined result denotes that extension data of only this apparatus exist in the block blkMakersPrivateData(), it is determined that the chapter be able to be additionally written to the play list file as the additionally writable candidate.

At the foregoing step S181, when extension data based on the AVCHD format do not exist in the play list file as the additionally writable candidate, it is determined that the chapter be not able to be

5 additionally written to the play list file as the
additionally writable candidate. However, the
determination performed at this step is not limited to
this example. In other words, depending on the
specifications of the recording apparatus, when no
block blkMakersPrivateData exists in the play list file
as the additionally writable candidate, it can be
contemplated that the chapter can be additionally
written to the play list file as the additionally
10 writable candidate.

Fig. 51 shows an example of the additionally
writing ability/inability determination process on the
basis of the last update apparatus of the play list
file as the additionally writable candidate according
15 to the restriction (9) at the foregoing step S111.

When the last update apparatus of the play list file as
the additionally writable candidate is not this local
apparatus, the concept of titles and chapters of the
play list file as the additionally writable candidate
is different from that of this apparatus. Thus, there
20 is a possibility of which a problem may occur when data
are reproduced. When control is performed such that
the chapter is additionally written to the play list
file as the additionally writable candidate on the
basis of information of the last update apparatus of
25 the play list file as the additionally recordable
candidate, only if the last update apparatus is this

apparatus, a trouble due to the difference of the concept of titles and chapters in one play list file can be solved.

First of all, at the first step S190,
5 extension data of the play list file as the additionally writable candidate is searched for extension data based on the AVCHD format. At the next step S191, it is determined whether or not extension data based on the AVCHD format exist in extension data
10 of the play list file as the additionally writable candidate on the basis of the searched result at step S190. Since the processes at the step S190 and step S191 are the same as those at step S180 and step S181 described with reference to Fig. 50, for preventing
15 complicity, their detailed description will be omitted.

When the determined result at step S191 denotes that extension data based on the AVCHD format do not exist in extension data of the play list file as the additionally writable candidate, it is determined
20 that the chapter be unable to be additionally written to the play list file as the additionally writable candidate.

In contrast, when the determined result at step S191 denotes that extension data based on the
25 AVCHD format exist in extension data of the play list file as the additionally writable candidate on the basis of the searched result at step S190, the flow of

the process advances to step S192. At step S192, the last update apparatus of the play list file as the additionally writable candidate is checked. In other words, with reference to the block blkPlayListMeta() of the block blkPlayListExtensionData() of extension data, data of the field MakerID and the field MakerModelCode are obtained.

When the last update apparatus of the play list file as the additionally writable candidate has been checked at step S192, the flow of the process advances to step S193. At step S193, it is determined whether or not the checked last update apparatus is this apparatus. In other words, when data of the field MakerID and the field MakerModelCode in the block blkPlayListMeta() of the block blkPlayListExtensionData() of extension data represent this apparatus, it can be determined that the last update apparatus be this apparatus.

When the determined result at step S193 denotes that the last update apparatus of the play list file as the additionally writable candidate is this apparatus, it is determined that the chapter be able to be additionally written to the play list file as the additionally writable candidate. In contrast, when the determined result denotes that the last update apparatus of the play list file as the additionally writable candidate is not this apparatus, it is

determined that the chapter is unable to be additionally written to the play list file as the additionally writable candidate.

Information about the last update apparatus
5 can be also stored in the index file. Information about the last update apparatus can be contemplated to be stored, for example, in the block blkMakersPrivateData() in the block blkMakersPrivateData() of extension data of the index
10 file. In this case, the determination of the flow chart shown in Fig. 51 may be performed with the information about the last update apparatus stored in the index file.

With respect to continuous capturing and
15 recording according to the foregoing restriction (10), they are included in the process with respect to the file size of clip information files described with reference to Fig. 43 (step S108) and Fig. 48 and the process with respect to entry points in clip
20 information files described with reference to Fig. 43 (step S109) and Fig. 49, their detailed description will be omitted.

In the foregoing description made with
reference to Fig. 43, a sequence of determinations of
25 whether a chapter is additionally written to a play list file as an additionally writable candidate or a play list file is newly created are performed when the

record medium 20 is loaded into the recording apparatus.
However, these determinations may not be performed in
such a manner. Instead, whenever a chapter is
5 additionally written, for example, the record start
operation is performed, these determinations may be
performed.

Next, a process of additionally writing a
chapter to a play list file as an additionally writable
candidate as the results of the processes described
10 with reference to the foregoing Fig. 43 to Fig. 51 will
be described. Fig. 52 is a flow chart showing an
example of the process of additionally writing a
chapter to a play list file.

When the record start operation is performed
15 at step S200, the flow of the process advances to step
S201. At step S201, a clip AV stream is started to be
recorded to the record medium 20. For example, when a
record start switch that is disposed in the UI section
31 and that commands the start of recording is operated,
20 a control signal that commands the start of recording
is supplied from the UI section 31 to the control
section 30. The control section 30 controls each
section of the recording section 10 to record base band
video data that are input from the terminal 40 and base
25 band audio data that are input from the terminal 41 to
the record medium 20 on the basis of the control signal
that commands the start of recording.

As the start of recording is controlled, a clip AV stream is recorded to the record medium 20 (at step S201). In other words, the input video data and audio data are compression-encoded by the video encoder 11 and the audio encoder 12, respectively, packetized as TS packets (specifically, source packets to which a predetermined header is added) by the multiplexer 13, and supplied to the stream buffer 14. When TS packets in excess of a predetermined amount have been stored in the stream buffer 14, the recording control section 15 reads the TS packets from the stream buffer 14. The TS packets that have been read are stored in a clip AV stream file that has been assigned a predetermined file name and recorded to the record medium 20.

For example, when a clip AV stream file having a file name "00001.m2ts" has been recorded on the record medium 20, a file name that is not redundant to file names of clip AV stream files that have been recorded is selected, for example, "00002.m2ts".

As a clip AV stream is recorded to the record medium 20, information that represents the relationship of the reproduction time and address of data that are recorded is created in real time by the management information processing section 16. This data are stored as data stored in the block blkEPMMap() of the foregoing clip information file "zzzzz.clpi".

At the next step S202, it is determined

whether or not the record stop operation has been preformed. When the user has operated the record stop switch disposed in the UI section 31 and the determined result denotes that the recording has been stopped, the flow of the process advances to step S203. In contrast, when the recording has not been stopped, the flow of the process returns to step S201. At step S201, a clip AV stream is continued to be recorded to the record medium 20.

At step S203, as the recording has been stopped, all streams stored in the stream buffer 14 are written to the record medium 20. For example, the recording control section 15 reads all streams (TS packets) stored in the stream buffer 14 and writes them to the record medium 20 according to the record stop command received from the control section 30.

According to the record stop command, the operations of, for example, the video encoder 11 and the audio encoder 12 are stopped. At this point, to perform the first seamless connection described with reference to Fig. 13A, control is performed, for example, such that the operation of the audio encoder 12 is stopped a predetermined time after the operation of the video encoder 11 is stopped.

At the next step S204 to step S208, a clip information file with respect to the clip AV stream file written to the record medium 20 is created and the

play list file as the additionally writable candidate is updated by the management information processing section 16.

5 First of all, at step S204, the clip information file "zzzzz.clpi" is created by the management information processing section 16. For example, the file name of the clip information file corresponds to the file name of the clip AV stream file that this clip information file represents. When the
10 file name of the clip AV stream file is "00002.m2ts", the file name of this clip information file is "00002.clpi" of which the portion before the extension is the same as that of the file name of the clip AV stream file.

15 According to each syntax exemplified in Fig. 15 to Fig. 21, values of fields and flags are set and stored in the clip information file "00002.clpi" in a predetermined manner. For example, information with respect to TS packets and information with respect to
20 the reproduction time (PTS) are created on the basis of information obtained from the multiplexer 13 by the management information processing section 16 while a clip is being recorded. In addition, information with respect to the record address on the record medium 20
25 is created on the basis of information obtained from the recording control section 15 by the management information processing section 16 while the clip is

being recorded. Values unique to the system are based on information stored, for example, in the ROM (not shown). In addition, information of the foregoing block blkEPMMap() that represents the relationship between the reproduction time and address is stored in the block blkCPI() of the clip information file "00002.clpi".

When the recording of the clip is stopped by a user's operation, the value of the flag IsCC5 in the block blkClipInfo() is set to "1" (binary value). Accordingly, data represented by the if statement (refer to Fig. 16) in the block blkClipInfo() are set in a predetermined manner.

After the clip information file has been created, the flow of the process advances to the next step S205. Processes from step S205 to step S208 are those for a play list file. In the processes from step S205 to step S208, a play item corresponding to the newly recorded clip AV stream file "00002.m2ts" is added to the play list file that exists on the record medium 20.

First of all, at step S205, the value of the field ConnectionCondition in the block blkPlayItem() in the play list file is set to "5" that denotes that this clip is connected to the next clip as the first seamless connection (refer to Fig. 12). At the next step S206, the value of the field NumberOfPlayItems of

the play item file is incremented by "1" that denotes that one play item has been added to the play list (refer to Fig. 11).

At the next step S207, the field
5 ClipInformationFileName, the field INTime, and the
field OUTTime of the block blkPlayItem() are set and
thereby the block blkPlayItem() that is added as a clip
is recorded is created. The file name "00002.clpi" of
the clip information file created at the foregoing step
10 S205 is stored in the field ClipInformationFileName.
Specifically, since the extension of a clip information
file is fixed, the portion "00002" before the period is
stored. The field INTime and the field OUTTime are
information that represents times of the beginning and
15 the last end of a video stream stored in the
corresponding clip AV stream file "00002.m2ts", for
example, based on information of the block blkEPMMap()
of the block blkCPI() in the clip information file
"00002.clpi".

20 At the next step S208, the value of the field
NumberOfPlayListMarks in the block blkPlayListMark() in
the play list file as the additionally writable
candidate is incremented by "1". Accordingly, the
value of the field MarkTimeStamp added to the for loop
25 statement is set to the value of the field INTime in
the block blkPlayItem() at the foregoing step S207. In
other words, a play list mark is placed at the

beginning of the newly recorded clip. As the play list mark is placed, a chapter is formed. In other words, accordingly, the chapter is additionally written to the play list file as the additionally writable candidate.

5 In such a manner, the clip information file "00002.clpi" is created for the newly recorded clip AV stream file "00002.m2ts" and the play list file as the additionally writable candidate is updated. In addition, at this point, information of the block
10 blkPlayListMeta() in the block blkPlayListExtensionData() of extension data of the play list file may be updated.

 The process of writing the data stored in the stream buffer 14 at the foregoing step S203 may be
15 performed after the process of step S208.

 When a chapter is formed by newly creating a play list file, the processes after step S205 slightly differ from the foregoing processes. In other words, data of each field of the play list file are newly
20 created. Instead, data of a template provided for a play list file may be contemplated to be changed.

 Next, another embodiment of the present invention will be described. In the foregoing, an example of which the present invention is applied to a
25 single recording apparatus (refer to Fig. 41) was described. In contrast, in the other embodiment, the present invention is applied to a video camera

apparatus that has an image capturing device and an optical system that inputs light emitted from a subject to the image capturing device and that records video data to a record medium based on a captured image signal captured by the image capturing device.

Fig. 53 shows an example of the structure of a video camera apparatus 100 according to the other embodiment of the present invention. Since the structure of the recording apparatus described with reference to Fig. 41 can be nearly applied for the structure of the recording system of the video camera apparatus 100, sections that are in common with those shown in Fig. 41 are designated by the same reference numerals and their detailed description will be omitted.

In the structure shown in Fig. 53, a camera section 50 has an optical system 51, an image capturing device 52, a captured image signal processing section 53, a camera control section 54, and a display section 55 as a structure with respect to a video signal. The camera section 50 has a microphone (MIC) 56 and an audio signal processing section 57 as a structure with respect to an audio signal. By exchanging various types of control signals and information with each section of the camera section 50, the control section 30 controls the operation of the camera section 50. In addition, the camera section 50 controls the operations of the camera section 50 on the basis of control

signals supplied from the UI section 31 according to user's operations.

When structured as the video camera apparatus 100, the record start operation and the record stop operation are normally performed, for example, such that a single record switch disposed in the UI section 31 is used and whenever the record switch is pressed, the start and stop of recording are alternately commanded. In this video camera apparatus 100, a disc record medium such as a recordable type DVD or Blu-ray Disc is applied for the record medium 20.

In the camera section 50, the optical system 51 has a lens system that guides light from a subject to the image capturing device 52, a diaphragm adjustment mechanism, a focus adjustment mechanism, a zoom mechanism, a shutter mechanism, and so forth. The operations of the diaphragm adjustment mechanism, the focus adjustment mechanism, the zoom mechanism, and the shutter mechanism are controlled by the camera control section 54 on the basis of control signals supplied from the control section 30.

The image capturing device 52 is composed, for example, of a CCD (Charge Coupled Device). The image capturing device 52 converts light emitted through the optical system 51 into an electric signal by photoelectric conversion, performs predetermined signal processes, and outputs the resultant signal as a

captured image signal. The captured image signal processing section 53 performs predetermined signal processes for the captured image signal that is output from the image capturing device and outputs the resultant signal as base band digital video data.

For example, the captured image signal processing section 53 causes a CDS (Correlated Double Sampling) circuit to sample only a signal that has image information of the captured image signal that has been output from the image capturing device 52 and remove noise from the sampled signal, and causes an AGC (Auto Gain Control) circuit to adjust the gain of the signal. Thereafter, the captured image signal processing section 53 converts the gain adjusted signal into a digital signal by A/D conversion. Thereafter, the captured image signal processing section 53 performs a detection signal process for the digital signal, extracts components of colors of R (red), G (green), and B (blue) from the digital signal, performs processes such as γ correction, white balance correction, and so forth, and finally outputs the resultant signal as digital video data of one base band.

In addition, the captured image signal processing section 53 supplies information about the captured image signal that has been output from the image capturing device 52 to the control section 30. The control section 30 generates control signals for

controlling the optical system 51 on the basis of the information and supplies the control signals to the camera control section 54. The camera control section 54 controls the focus adjustment mechanism, the diaphragm adjustment mechanism, and so forth on the basis of the control signals.

In addition, the captured image signal processing section 53 generates an image signal that causes the display section 55 that uses, for example, an LCD (Liquid Crystal Display) as a display device on the basis of the captured image signal that has been output from the image capturing device 52.

On the other hand, the microphone 56 collects a surrounding sound, converts it into an electric signal, and outputs the electric signal. An audio signal that has been output from the microphone 56 is supplied to the audio signal processing section 57. The audio signal processing section 57 performs an A/D conversion for the supplied audio signal through a limiter, performs predetermined audio signal processes such as noise reduction and sound quality correction, for the digital audio data and outputs the resultant data as base band digital audio data.

The base band digital video data that have been output from the captured image signal processing section 53 of the camera section 50 are supplied to the terminal 40 of the recording section 10. On the other

hand, the base band digital audio data that have been output from the audio signal processing section 57 are supplied to the terminal 41 of the recording section 10.

When the record medium 20 is loaded into the video camera apparatus 100 in a predetermined manner for capturing, a play list file as an additionally writable candidate for a chapter based on video data that has been obtained by the capturing is identified and it is determined whether or not the chapter can be additionally written to the identified play list file as the additionally writable candidate according to the processes described with reference to Fig. 43.

For example, an index file is read from the record medium 20 under the control of the control section 30 and stored to the nonvolatile memory 17 through the management information processing section 16. The control section 30 identifies the play list file as the additionally writable candidate based on information about the index file stored in the nonvolatile memory 17 and issues a command to the recording control section 15 to read the play list file as the additionally writable candidate from the record medium 20. The play list file as the additionally writable candidate that has been read from the record medium 20 based on the command is stored in the nonvolatile memory 17 through the management information processing section 16.

The control section 30 issues a command to the recording control section 15 to read all clip information files associated with the play list file as the additionally writable candidate from the record medium 20 based on the information about the play list file as the additionally writable candidate stored in the nonvolatile memory 17. The clip information files that have been read from the record medium 20 based on this command are stored to the nonvolatile memory 17.

The control section 30 performs the determinations from step S104 to step S111 in the flow chart shown in Fig. 43 on the basis of the play list file as the additionally writable candidate stored in the nonvolatile memory 17 and all the clip information files associated with the play list file as the additionally writable candidate. The determined results are stored, for example, in registers of the control section 30.

After the control section 30 has performed the determinations from step S104 to step S111, the flow of the process advances to step S112 shown in Fig. 43. At step S112, the control section 30 performs a total determination for the determined results from step S104 to step S111 and determines whether or not the chapter based on the video data that have been captured is additionally written to the play list file as the additionally writable candidate. The control

section 30 controls the management information
processing section 16 such that when the determined
result denotes that the chapter is additionally written
to the play list file, the chapter is additionally
5 written to the play list file as the additionally
writable candidate stored in the nonvolatile memory 17
and when the determined result denotes that the chapter
is not additionally written to the play list file, a
play list file is newly created and the chapter is
10 recorded thereto.

When the record switch disposed in the UI
section 31 is pressed in the record stop state, a
control signal that commands the start of recording is
supplied from the UI section 31 to the control section
15 30. The base band digital video signal and digital
audio data that have been output from the camera
section 50 are started to be recorded to the record
medium 20 under the control of the control section 30.

In other words, as described above, the
20 operations of the video encoder 11 and the audio
encoder 12 are started under the control of the control
section 30. The video data and the audio data are
compression-encoded by the video encoder 11 and the
audio encoder 12, respectively, and packetized and
25 multiplexed in a predetermined manner as AV stream data
by the multiplexer 13. The AV stream data are supplied
to the recording control section 15 through the stream

buffer 14 and recorded as a clip AV stream file to the record medium 20.

When the record switch of the UI section 31 is pressed again, the recording is stopped, a clip information file is created, and the play list file is updated. The management information processing section 16 creates a clip information file corresponding to a clip AV stream file recorded to the record medium 20 and a play item that refers to the clip information file on the basis of information supplied from the multiplexer 13 and the recording control section 15.

When the determined result denotes that the chapter is additionally written to the play list file as the additionally writable candidate, the created play item is added to the play list file as the additionally writable candidate and a play list mark is placed such that a chapter is formed. In contrast, when the determined result denotes that the chapter is unable to be additionally written to the play list file as the additionally writable candidate, the created play item is added to the newly created play list file and a play list mark is set.

When the record switch is pressed again in this state, recording is commanded to be started and thereby a new clip AV stream is started to be recorded to the record medium 20. When the recording is started again, the additionally recording ability/inability

determination for a new chapter based on new recording to the play list file as the additionally writable candidate may be performed according to the flow chart shown in Fig. 43.

5 In the foregoing, the recording apparatus shown in Fig. 41 and the recording section 10 of the video camera apparatus 100 shown in Fig. 53 are described as a hardware structure. However, the present invention is not limited to such an example. In
10 other words, the recording section 10 may be structured as software. In this case, software is pre-stored, for example, in the ROM (not shown) of the control section 30. Instead, the recording section 10 may be structured on a computer apparatus such as a personal
15 computer. In this case, software that causes the computer apparatus to execute the recording section 10 is recorded to a record medium such as a CD-ROM or a DVD-ROM and supplied therewith. When the computer apparatus can be connected to a network, the software
20 can be provided through the network such as the Internet.

CLAIMS

1. In a recording apparatus which multiplexes video data and audio data and records multiplexed data to a record medium, characterized in that

the recording apparatus comprise:

a data input section which inputs the video data and the audio data;

a record command input section which inputs a record start command and a record stop command for the video data and the audio data;

a recording section which multiplexes the video data and the audio data and records the multiplexed stream as a stream file to the record medium; and

a management information creation section which creates reproduction management information for controlling a reproduction of the stream file recorded on the record medium, the reproduction management information being composed of first management information which represents attribute information of the stream file and second management information which contains information which represents a reproduction method for the stream file, and

the management information creation section determines whether or not the information which represents the reproduction method for the stream file recorded on the record medium is additionally written

to a predetermined entry of the second management information contained in an existing entry of the reproduction management information according to the record start command by the record command input section based on the existing entry of the reproduction management information.

2. In the recording apparatus as set forth in claim 1, characterized in that

when the management information creation section has determined that the information which represents the reproduction method for the stream file recorded on the record medium according to the record start command by the record command input section be not additionally written to the predetermined entry of the second management information contained in the existing entry of the reproduction management information, the management information creation section newly creates the second management information which contains the information which represents the reproduction method for the stream file recorded on the record medium according to the record start command by the record command input section.

3. In the recording apparatus as set forth in claim 1, characterized in that

the management information creation section treats a latest updated entry of the second management information of the second management information

updated as the stream file is recorded as the
predetermined entry of the second management
information.

4. In the recording apparatus as set forth in
claim 1, characterized in that

the first management information is composed
of a file which stores information which represents at
least a relationship of reproduction time information
and address information of the stream file recorded to
the record medium,

the second management information is composed
of a file which contain at least one entry of
reproduction region information which designates a
reproduction region with a reproduction start point and
a reproduction end point which are set to the stream
file and which is capable of storing mark information
which represents reproduction time information for the
stream file, and

the second management information represents
the reproduction method for the stream file with
reference to the first management information from the
reproduction region information.

5. In the recording apparatus as set forth in
claim 4, characterized in that

the additionally recording ability/inability
determination by the management information creation
section is based on a number of entries of the

reproduction region information stored in the predetermined entry of the second management information.

6. In the recording apparatus as set forth in claim 5, characterized in that

when the management information creation section has determined that the number of entries of the reproduction region information which has been stored in the predetermined entry of the second management information be smaller than a pre-set upper limit, the management information creation section performs the additionally recording ability/inability determination such that the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to the predetermined entry of the second management information.

7. In the recording apparatus as set forth in claim 4, characterized in that

the additionally recording ability/inability determination by the management information creation section is based on the number of entries of the mark information stored in the predetermined entry of the second management information.

8. In the recording apparatus as set forth in claim 7, characterized in that

when the management information creation

section has determined that the number of entries of the mark information stored in the predetermined entry of the second management information is smaller than a pre-set upper limit, the management information creation section performs the additionally recording ability/inability determination such that the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to the predetermined entry of the second management information.

9. In the recording apparatus as set forth in claim 4, characterized in that

the first management information also stores video attribute information which represents an attribute of the video data stored in the corresponding stream file, and

the additionally recording ability/inability determination by the management information creation section is based on the video attribute information stored in the first management information.

10. In the recording apparatus as set forth in claim 9, characterized in that

the additionally recording ability/inability determination by the management information creation section is based both on a video attribute based on a current recording mode and a video attribute stored in at least one entry of the first management information

referred from the predetermined entry of the second management information.

11. In the recording apparatus as set forth in claim 10, characterized in that

5 when at least one of frame size, aspect ratio, frame rate, and scanning system of the video attribute based on the recording mode does not match that of the video attribute stored in the entry of the first management information, the management information creation section performs the additionally recording
10 ability/inability determination such that the information which represents the reproduction method for the stream file recorded on the record medium according to the record start command by the record
15 command input section is not additionally written to the predetermined entry of the second management information.

12. In the recording apparatus as set forth in claim 4, characterized in that

20 the additionally recording ability/inability determination by the management information creation section is based on a file size of the predetermined entry of the second management information.

13. In the recording apparatus as set forth in
25 claim 12, characterized in that

when the management information creation section has determined that the file size of the second

management information be not in excess of a pre-set upper limit based on the reproduction region information and a data size of the mark information created as the single stream file has been recorded, the management information creation section performs the additionally recording ability/inability determination such that the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to the predetermined entry of the second management information.

14. In the recording apparatus as set forth in claim 4, characterized in that

the additionally recording ability/inability determination by the management information creation section is based on a total file size of all entries of the first management information referred from the predetermined entry of the second management information.

15. In the recording apparatus as set forth in claim 14, characterized in that

when the management information creation section has determined that the total file size of the first management information referred from the predetermined entry of the second management information is not in excess of a pre-set upper limit based on a data size of the first management

information created as the single stream file has been recorded for an assured minimum continuous time, the management information creation section performs the additionally recording ability/inability determination such that the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to the predetermined entry of the second management information.

16. In the recording apparatus as set forth in claim 4, characterized in that

the additionally recording ability/inability determination by the management information creation section is based on a number of entries of information which represents a relationship of reproduction time information and address information contained in all entries of the first management information referred from the predetermined entry of the second management information.

17. In the recording apparatus as set forth in claim 16, characterized in that

when the management information creation section has determined that a total of all entries of the first management information referred from the second management information is not in excess of a pre-set upper limit of the entries of the second management information based on a number of entries of

the information which represents the reproduction time
information and the address information contained in
the first management information created as the single
stream file has been recorded for an assured minimum
5 continuous time, the management information creation
section performs the additionally recording
ability/inability determination such that the
information which represents the reproduction method
for the stream file recorded on the record medium to
10 the predetermined entry of the second management
information.

18. In the recording apparatus as set forth in
claim 4, characterized in that

the second management information is capable
15 of storing unique apparatus information, and

the additionally recording ability/inability
determination by the management information creation
section is based on the unique apparatus information
stored in the predetermined entry of the second
20 management information.

19. In the recording apparatus as set forth in
claim 18, characterized in that

if the management information creation
section has determined that the unique apparatus
25 information has been created by the recording apparatus
or another apparatus equivalent thereto when the unique
apparatus information has been stored in the

predetermined entry of the second management
information,

the management information creation section
performs the additionally recording ability/inability
5 determination such that the information which
represents the reproduction method for the stream file
recorded on the record medium is additionally written
to the predetermined entry of the second management
information.

10 20. In the recording apparatus as set forth in
claim 4, characterized in that

the second management information is capable
of also storing information which represents a last
update apparatus of the second management information,
15 and

the additionally recording ability/inability
determination by the management information creation
section is based on the last update information stored
in the predetermined entry of the second management
20 information.

21. In the recording apparatus as set forth in
claim 20, characterized in that

if it has been determined that when the last
update apparatus information has been stored in the
25 predetermined entry of the second management
information, the last update apparatus information
represents the recoding apparatus, the additionally

recording ability/inability determination is performed
such that the information which represents the
reproduction method for the stream file recorded on the
record medium is additionally written to the
predetermined entry of the second management
information.

22. In the recording apparatus as set forth in
claim 1, characterized in that

the management information creation section
performs the additionally recording ability/inability
determination for one or a plurality of items, and

when at least one of the items of the
additionally recording ability/inability determination
represents an additionally writing inability state, the
management information creation section performs the
additionally recording ability/inability determination
such that the second management information
corresponding to the stream file recorded on the record
medium be not additionally written to the predetermined
entry of the second management information.

23. In the recording apparatus as set forth in
claim 22, characterized in that

the one or plurality of items include at
least one item of a number of entries of reproduction
region information stored in the predetermined entry of
the second management information, a number of entries
of mark information stored in the predetermined entry

of the second management information, video attribute information stored in the first management information, a file size of the predetermined entry of the second management information, a total file size of all the entries of the first management information referred from the predetermined entry of the second management information, a number of entries of information which represents a relationship of reproduction time information and address information contained in all the entries of the first management information referred from the predetermined entry of the second management information, unique apparatus information stored in the predetermined entry of the second management information, and last update apparatus information stored in the predetermined entry of the second management information.

24. In a recording method of multiplexing video data and audio data and recording multiplexed data to a record medium, characterized in that the recording method comprise:

- a record command input step of inputting a record start command and a record stop command for the video data and the audio data that have been input to a data input section;

- a recording step of multiplexing the video data and the audio data and recording the multiplexed stream as a stream file to the record medium; and

a management information creation step of generating reproduction management information for controlling a reproduction of the stream file recorded on the record medium, the reproduction management information being composed of first management information which represents attribute information of the stream file and second management information which contains information which represents a reproduction method for the stream file,

the management information creation step being performed by determining whether or not the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to a predetermined entry of the second management information contained in an existing entry of the reproduction management information according to the record start command by the record command input section based on the existing entry of the reproduction management information.

25. In a recording program of causing a computer apparatus to execute a recording method of multiplexing video data and audio data and recording multiplexed data to a record medium, characterized in that the recording method comprise:

a record command input step of inputting a record start command and a record stop command for the video data and the audio data that have been input to a

data input section;

a recording step of multiplexing the video data and the audio data and recording the multiplexed stream as a stream file to the record medium; and

5 a management information creation step of generating reproduction management information for controlling a reproduction of the stream file recorded on the record medium, the reproduction management information being composed of first management
10 information which represents attribute information of the stream file and second management information which contains information which represents a reproduction method for the stream file,

the management information creation step
15 being performed by determining whether or not the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to a predetermined entry of the second management information contained in an existing
20 entry of the reproduction management information according to the record start command by the record command input section based on the existing entry of the reproduction management information.

26. In an image capturing apparatus which
25 multiplexes video data captured and obtained from a subject by an image capturing section and audio data collected and obtained by a sound collecting section

and records multiplexed video data and audio data to a record medium, characterized in that

the image capturing apparatus comprises:

the image capturing section which captures
5 the image of the subject and outputs the video data;
the sound collecting section which collects a sound and outputs audio data,

a recording section which multiplexes the video data and the audio data and records the
10 multiplexed stream as a stream file to the record medium;

an operation section which accepts user's operations for a record start command and a record stop command for the video data and the audio data to the
15 record medium; and

a management information creation section which creates reproduction management information for controlling a reproduction of the stream file recorded on the record medium, the reproduction management
20 information being composed of first management information which represents attribute information of the stream file and second management information which contains information which represents a reproduction method for the stream file,

25 the management information creation section determines whether or not the information which represents the reproduction method for the stream file

recorded on the record medium is additionally written
to a predetermined entry of the second management
information contained in an existing entry of the
reproduction management information according to the
5 record start command corresponding to the user's
operations to the operation section based on the
existing entry of the reproduction management
information.

27. In the image capturing apparatus as set forth
10 in claim 26, characterized in that

when the management information creation
section has determined that the information which
represents the reproduction method for the stream file
recorded on the record medium according to the record
15 start command by the operation section be not
additionally written to the predetermined entry of the
second management information contained in the existing
entry of the reproduction management information, the
management information creation section newly creates
20 the second management information which contains the
information which represents the reproduction method
for the stream file recorded on the record medium
according to the record start command by the operation
section.

28. In the image capturing apparatus as set forth
25 in claim 26, characterized in that

the management information creation section

treats a latest updated entry of the second management information of the second management information updated as the stream file is recorded as the predetermined entry of the second management information.

29. In the image capturing apparatus as set forth in claim 26, characterized in that

the first management information is composed of a file which stores information which represents at least a relationship of reproduction time information and address information of the stream file recorded to the record medium,

the first management information is composed of a file which contain at least one entry of reproduction region information which designates a reproduction region with a reproduction start point and a reproduction end point which are set to the stream file and which is capable of storing mark information which represents reproduction time information for the stream file, and

the second management information represents the reproduction method for the stream file with reference to the first management information from the reproduction region information.

30. In the image capturing apparatus as set forth in claim 29, characterized in that

the additionally recording ability/inability

determination by the management information creation section is based on a number of entries of the reproduction region information stored in the predetermined entry of the second management information.

31. In the image capturing apparatus as set forth in claim 30, characterized in that

when the management information creation section has determined that the number of entries of the reproduction region information which has been stored in the predetermined entry of the second management information be smaller than a pre-set upper limit, the management information creation section performs the additionally recording ability/inability determination such that the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to the predetermined entry of the second management information.

32. In the image capturing apparatus as set forth in claim 29, characterized in that

the additionally recording ability/inability determination by the management information creation section is based on the number of entries of the mark information stored in the predetermined entry of the second management information.

33. In the image capturing apparatus as set forth

in claim 32, characterized in that

when the management information creation section has determined that the number of entries of the mark information stored in the predetermined entry of the second management information is smaller than a pre-set upper limit, the management information creation section performs the additionally recording ability/inability determination such that the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to the predetermined entry of the second management information.

34. In the image capturing apparatus as set forth in claim 29, characterized in that

the first management information also stores video attribute information which represents an attribute of the video data stored in the corresponding stream file, and

the additionally recording ability/inability determination by the management information creation section is based on the video attribute information stored in the first management information.

35. In the image capturing apparatus as set forth in claim 34, characterized in that

the additionally recording ability/inability determination by the management information creation section is based both on a video attribute based on a

current recording mode and a video attribute stored in at least one entry of the first management information referred from the predetermined entry of the second management information.

5 36. In the image capturing apparatus as set forth in claim 35, characterized in that

 when at least one of frame size, aspect ratio, frame rate, and scanning system of the video attribute based on the recording mode does not match that of the video attribute stored in the entry of the first management information, the management information creation section performs the additionally recording ability/inability determination such that the information which represents the reproduction method for the stream file recorded on the record medium according to the record start command by the operation section is not additionally written to the predetermined entry of the second management information.

20 37. In the image capturing apparatus as set forth in claim 29, characterized in that

 the additionally recording ability/inability determination by the management information creation section is based on a file size of the predetermined entry of the second management information.

25 38. In the image capturing apparatus as set forth in claim 37, characterized in that

when the management information creation section has determined that the file size of the second management information be not in excess of a pre-set upper limit based on the reproduction region

5 information and a data size of the mark information created as the single stream file has been recorded, the management information creation section performs the additionally recording ability/inability determination such that the information which
10 represents the reproduction method for the stream file recorded on the record medium is additionally written to the predetermined entry of the second management information.

39. In the image capturing apparatus as set forth
15 in claim 29, characterized in that

the additionally recording ability/inability determination by the management information creation section is based on a total file size of all entries of the first management information referred from the
20 predetermined entry of the second management information.

40. In the image capturing apparatus as set forth
in claim 39, characterized in that

when the management information creation
25 section has determined that the total file size of the first management information referred from the predetermined entry of the second management

information is not in excess of a pre-set upper limit based on a data size of the first management information created as the single stream file has been recorded for an assured minimum continuous time, the management information creation section performs the additionally recording ability/inability determination such that the information which represents the reproduction method for the stream file recorded on the record medium is additionally written to the predetermined entry of the second management information.

41. In the image capturing apparatus as set forth in claim 29, characterized in that

the second management information refers to the first management information from the reproduction region information so as to control reproduction of the stream file, and

the additionally recording ability/inability determination by the management information creation section is based on a number of entries of information which represents a relationship of reproduction time information and address information contained in all entries of the first management information referred from the predetermined entry of the second management information.

42. In the image capturing apparatus as set forth in claim 41, characterized in that

when the management information creation section has determined that a total of all entries of the first management information referred from the second management information is not in excess of a pre-set upper limit of the entries of the second management information based on a number of entries of the information which represents the reproduction time information and the address information contained in the first management information created as the single stream file has been recorded for an assured minimum continuous time, the management information creation section performs the additionally recording ability/inability determination such that the information which represents the reproduction method for the stream file recorded on the record medium to the predetermined entry of the second management information.

43. In the image capturing apparatus as set forth in claim 29, characterized in that

the second management information is capable of storing unique apparatus information, and

the additionally recording ability/inability determination by the management information creation section is based on the unique apparatus information stored in the predetermined entry of the second management information.

44. In the image capturing apparatus as set forth

in claim 43, characterized in that

if the management information creation
section has determined that the unique apparatus
information has been created by the image capturing
5 apparatus or another apparatus equivalent thereto when
the unique apparatus information has been stored in the
predetermined entry of the second management
information,

the management information creation section
10 performs the additionally recording ability/inability
determination such that the information which
represents the reproduction method for the stream file
recorded on the record medium is additionally written
to the predetermined entry of the second management
15 information.

45. In the image capturing apparatus as set forth
in claim 29, characterized in that

the second management information is capable
of also storing information which represents a last
20 update apparatus of the second management information,
and

the additionally recording ability/inability
determination by the management information creation
section is based on the last update information stored
25 in the predetermined entry of the second management
information.

46. In the image capturing apparatus as set forth

in claim 45, characterized in that

if it has been determined that when the last
update apparatus information has been stored in the
predetermined entry of the second management
5 information, the last update apparatus information
represents the recoding apparatus, the additionally
recording ability/inability determination is performed
such that the information which represents the
reproduction method for the stream file recorded on the
10 record medium is additionally written to the
predetermined entry of the second management
information.

47. In the image capturing apparatus as set forth
in claim 26, characterized in that

15 the management information creation section
performs the additionally recording ability/inability
determination for one or a plurality of items, and

when at least one of the items of the
additionally recording ability/inability determination
20 represents an additionally writing inability state, the
management information creation section performs the
additionally recording ability/inability determination
such that the second management information
corresponding to the stream file recorded on the record
25 medium be not additionally written to the predetermined
entry of the second management information.

48. In the image capturing apparatus as set forth

in claim 47, characterized in that

the one or plurality of items include at least one item of a number of entries of reproduction region information stored in the predetermined entry of the second management information, a number of entries of mark information stored in the predetermined entry of the second management information, video attribute information stored in the first management information, a file size of the predetermined entry of the second management information, a total file size of all the entries of the first management information referred from the predetermined entry of the second management information, a number of entries of information which represents a relationship of reproduction time information and address information contained in all the entries of the first management information referred from the predetermined entry of the second management information, unique apparatus information stored in the predetermined entry of the second management information, and last update apparatus information stored in the predetermined entry of the second management information.

49. In an image capturing method of multiplexing video data captured and obtained from a subject by an image capturing section and audio data collected and obtained by a sound collecting section and recording multiplexed video data and audio data to a record

medium, characterized in that

the image capturing method comprises:

a recording step of multiplexing the video data and the audio data captured and obtained from an
5 subject by the image capturing section and the audio data collected and obtained by the sound collecting section and recording the multiplexed stream as a stream file to the record medium;

an accepting step of accepting user's
10 operations for a record start command and a record stop command for the video data and the audio data to the record medium against an operation section; and

a management information creation step for generating reproduction management information for
15 controlling a reproduction of the stream file recorded on the record medium, the reproduction management information being composed of first management information which represents attribute information of the stream file and second management information which
20 contains information which represents a reproduction method for the stream file,

the management information creation step being performed by determining whether or not the information which represents the reproduction method
25 for the stream file recorded on the record medium is additionally written to a predetermined entry of the second management information contained in an existing

entry of the reproduction management information
according to the record start command corresponding to
the user's operations to the operation section based on
the existing entry of the reproduction management
5 information.

50. In an image capturing program of causing a
computer apparatus to execute an image capturing method
of multiplexing video data captured and obtained from a
subject by an image capturing section and audio data
10 collected and obtained by a sound collecting section
and recording multiplexed video data and audio data to
a record medium, characterized in that

the image capturing method comprises:

15 a recording step of multiplexing the video
data and the audio data captured and obtained from an
subject by the image capturing section and the audio
data collected and obtained by the sound collecting
section and recording the multiplexed stream as a
stream file to the record medium;

20 an accepting step of accepting user's
operations for a record start command and a record stop
command for the video data and the audio data to the
record medium against an operation section; and

25 a management information creation step for
generating reproduction management information for
controlling a reproduction of the stream file recorded
on the record medium, the reproduction management

information being composed of first management
information which represents attribute information of
the stream file and second management information which
contains information which represents a reproduction
method for the stream file,

the management information creation step
being performed by determining whether or not the
information which represents the reproduction method
for the stream file recorded on the record medium is
additionally written to a predetermined entry of the
second management information contained in an existing
entry of the reproduction management information
according to the record start command corresponding to
the user's operations to the operation section based on
the existing entry of the reproduction management
information.

Abstract

To improve user-friendliness in recording AV data created after recording is started until it is stopped as a file. AV data that are created after recording is started until it is stopped are recorded as a file. Information that represents a reproduction region and mark information that represents a jump position are additionally written to a reproduction list file. At this point, it is determined whether or not restrictions that have been set to the reproduction list file and an attribute file for additional writing are satisfied on the basis of the reproduction list file as an additionally writable candidate and the attribute file that correlates reproduction time and address of the AV data. When having been determined that they be satisfied, the reproduction region information and the mark information are additionally written to the reproduction list file as the additionally writable candidate. When having been determined that they be not satisfied, a new reproduction list file is created. As a result, the user can perform a recording operation for the AV data without necessity of recognizing the restrictions that have been set to the reproduction list file and the attribute file.