

Description

Technical Field

This invention relates generally to thermal ink jet pen construction and more particularly to a single or multi-compartment pen body having improved ink storage and distribution capabilities.

Background Art

In the art of thermal ink jet printing, it is known to provide a bladder type of ink reservoir for supplying ink to a thermal ink jet printhead. The printhead will typically include a thin film resistor (TFR) substrate having a plurality of heater resistors therein, and a barrier layer and orifice plate member is usually mounted on top of the thin film resistor substrate. This member will typically include the ink reservoirs which are disposed above the heater resistors and further defines the corresponding drop generator nozzles for ejecting ink onto a print medium.

The bladder reservoir for supplying ink to the entire printhead may, for example, take the form of a rubber thimble which is located within the housing to which the thermal ink jet printhead is affixed. This type of reservoir and printhead construction is disclosed, for example, in the Hewlett-Packard Journal, Volume 36, Number 5, May 1985.

The present invention provides an ink jet pen having a printhead mounted on a pen body housing, with a nozzle plate disposed on said printhead and at least one passage provided through said printhead for receiving ink from said housing, said nozzle plate being provided with at least one plurality of ink ejection orifices, each said plurality being arranged as a group to receive ink from a said passage, characterised in that the orifices in each group are disposed in a circle about their respective passage.

Preferably, the housing is divided into three compartments with a separate opening leading from each compartment to a separate plurality of ink ejection orifices. Preferably, the compartments store, respectively, cyan, magenta and yellow ink.

A specific embodiment of the present invention will now be described further, by way of example, with reference to the accompanying drawings, in which:-

Figure 1 is an exploded view of the pen body construction according to one embodiment of the invention; and

Figure 2 is a cross section view taken along lines 2-2 of Figure 1.

Referring now to Figure 1, there is shown a three compartment pen body designated generally as 10 and having three (3) ink storage compart-

ments 12, 14 and 16 therein as indicated by the dashed line divider partitions within the interior of the body 10. The pen body 10 further includes an output printhead support surface 18 which is joined to upstanding side walls 20 in a rectangular receptacle configuration. This structure further includes three (3) ink output ports 22, 24 and 26 respectively communicating with the three ink storage compartments 12, 14 and 16.

The rectangular support receptacle 18 is configured to receive a thin film resistor type printhead 28 having a plurality of ink ejection orifice groups 30, 32 and 34 respectively which are circular in geometry and which communicate with the ink flow passages 22, 24 and 26 extending to the surface 18 of the rectangular support receptacle.

In the assembly of Figure 1, three ink filters 36, 38 and 40 are mounted within the compartments 12, 14 and 16, respectively. These filters are typically constructed from stainless wire mesh of a desired porosity to provide good filtration of air bubbles and solid particles when passing ink from the three sections 42, 44 and 46 of polyurethane foam located in the three compartments 12, 14 and 16 of the pen body 10.

The back surface 48 of the foam body sections 42, 44 and 46 is fitted with a plug generally designated as 50, and this plug including its end cover 51 prevents back-pressure build up and facilitates the removal of ink from the foam and through the filters 36, 38 and 40 to the printhead 28. Air vents 52 are covered with porous plastic membranes 54 which prevent ink from leaking out through the air vents 52. The remaining structural detail of these three vents 52 and their intermediate wall partitions 66 and 68 is shown in a larger cross-section view in Figure 2 below. As previously indicated, the foam material of sections 42, 44 and 46 is a controlled porosity ether-type polyurethane foam which has been reticulated to break the membrane walls therein. This increases the capillary force of the foam and thereby renders it especially well suited for feeding ink along the ink feed paths to a thin film resistor thermal ink jet printhead. The plug 50 further includes foam compression tabs 56 which extend into the foam sections 42, 44 and 46 as shown and provide a desired amount of compressive forces to the foam for further increasing capillary forces in the foam and optimizing ink dispensation to the printhead.

The particular foam which has been used in actual practice is an ether-type foam material obtained from the Scott Paper Company of Philadelphia, Pennsylvania and had a porosity of between 60 and 75 pores per inch.

Referring now to Figure 2, the cross section view in this figure is taken along lines 2-2 of Figure 1 wherein like reference numerals have been used

in both figures to identify the same components therein. The pen body 10 includes interior walls 62 and 64 which serve to partially define the three compartments for receiving the rectangular sections 42, 44 and 46 of foam as shown in Figure 1. These interior walls 62 and 64 receive the corresponding T-shaped interior extensions 66 and 68 of the cover or end member 51 of the previously described end plug 50. This plug 50 further includes air vents 70, 72 and 74 which communicate with the cavities or recessed portions 76, 78 and 80 as shown. These recessed portions or cavities 76, 78 and 80 in the cover member 51 of the plug 50 receive a plurality of porous membranes 82, 84 and 59 which are fabricated from polytetrafluoroethylene (PTFE) and which provide adequate ventilation within the three compartments of foam. At the same time, these membranes 82, 82 and 54 are of sufficient mesh density to prevent ink back-flow through the three air vents 70, 72 and 74.

A plurality of ink chambers 88, 90 and 92 are provided as shown in the three ink pipes 94, 96 and 98, respectively, in the pen body 10. Each of these ink pipes 94, 96 and 98 are provided, respectively, with the three previously identified wire mesh filters 40, 38 and 36. These latter filters provide filtering of air bubbles and solid particles from the ink which ultimately passes through the ink pipes 88, 90 and 92 and to the TFR printhead 28. This ink flow path also includes the lateral ink passage located between the surface 100 of the pen body 10 and the facing surface of the semiconductor substrate member 102 of the TFR printhead substrate 28.

The geometrical configuration of the ink pipes 94, 96 and 98 in combination with the walls 62, 64 and 66 and the spacing therebetween beneath the foam increases the compression of the foam in the areas above the three filters as shown in Figure 2. This fact in turn increases the capillarity of the foam in the region thereof above these three filters and thus reduces the possibility of air bubbles interrupting the ink path through the foam and into the three ink pipes 94, 96 and 98.

The substrate member 102 is bonded to a nozzle plate 104 by means of an adhesive barrier 106. This barrier 106 may advantageously be a selected polymer material such as the RISTON or VACREL trade name polymer materials made available by the E. I. DuPont Company of Wilmington, Delaware. The ink will flow through the ink pipes 88, 90 and 92 and then into the three passages 108, 110 and 112 in the substrate member 102. These passageways 108, 110 and 112 will then feed ink to the plurality of groups of orifices 30, 32 and 34 in the nozzle plate 104 and located in a circular pattern as shown.

The nozzle plate 104 may advantageously be electroformed of nickel and plated with gold and then affixed to the polymer barrier material 106 using, for example, the heat staking process disclosed and claimed in EP-A-0 244 643. The nozzle plate 104 may be fabricated in the manner described in the above identified Hewlett Packard Journal, Vol. 38, No. 5 May 1985.

Finally, the thin film resistor structure 28 is secured to the bottom facing surface 100 of the pen body 10 by means of a suitable adhesive 114 which is disposed as shown at the outer periphery of the substrate 102, as well as at interior recessed wall surfaces 116 and 118 thereof.

The present invention is not limited to thermal ink jet applications and may instead be used in other types of ink jet applications in which the above foam storage-of-ink capability is desirable and compatible.

Claims

1. An ink jet pen having a printhead (28) mounted on a pen body housing (10), with a nozzle plate (104) disposed on said printhead and at least one passage (108,110,112) provided through said printhead for receiving ink from said housing, said nozzle plate (104) being provided with at least one plurality of ink ejection orifices (30,32,34), each said plurality being arranged as a group to receive ink from a said passage, characterised in that the orifices in each group are disposed in a circle about their respective passage.
2. An ink jet pen according to claim 1 wherein the housing (10) is divided into three compartments (12,14,16) with a separate opening (22,24,26) leading from each compartment to a separate plurality of ink ejection orifices (30,32,34).
3. An ink jet pen according to claim 2 wherein the compartments store, respectively, cyan, magenta, and yellow ink.

Patentansprüche

1. Ein Tintenstrahlstift mit einem Druckkopf (28), der auf einem Stiftkörpergehäuse (10) befestigt ist, mit einer Düsenplatte (104), die auf dem Druckkopf angeordnet ist, und zumindest einem Durchgang (108, 110, 112), der durch den Druckkopf zur Aufnahme von Tinte aus dem Gehäuse vorgesehen ist, wobei die Düsenplatte (104) mit zumindest einer Mehrzahl von Tintenauswurföffnungen (30, 32, 34) vorgesehen ist, wobei jede der Mehrzahl als eine

in both figures to identify the same components therein. The pen body 10 includes interior walls 62 and 64 which serve to partially define the three compartments for receiving the rectangular sections 42, 44 and 46 of foam as shown in Figure 1. These interior walls 62 and 64 receive the corresponding T-shaped interior extensions 66 and 68 of the cover or end member 51 of the previously described end plug 50. This plug 50 further includes air vents 70, 72 and 74 which communicate with the cavities or recessed portions 76, 78 and 80 as shown. These recessed portions or cavities 76, 78 and 80 in the cover member 51 of the plug 50 receive a plurality of porous membranes 82, 84 and 86 which are fabricated from polytetrafluoroethylene (PTFE) and which provide adequate ventilation within the three compartments of foam. At the same time, these membranes 82, 84 and 86 are of sufficient mesh density to prevent ink back-flow through the three air vents 70, 72 and 74.

A plurality of ink chambers 88, 90 and 92 are provided as shown in the three ink pipes 94, 96 and 98, respectively, in the pen body 10. Each of these ink pipes 94, 96 and 98 are provided, respectively, with the three previously identified wire mesh filters 40, 38 and 36. These latter filters provide filtering of air bubbles and solid particles from the ink which ultimately passes through the ink pipes 88, 90 and 92 and to the TFR printhead 28. This ink flow path also includes the lateral ink passage located between the surface 100 of the pen body 10 and the facing surface of the semiconductor substrate member 102 of the TFR printhead substrate 28.

The geometrical configuration of the ink pipes 94, 96 and 98 in combination with the walls 62, 64 and 66 and the spacing therebetween beneath the foam increases the compression of the foam in the areas above the three filters as shown in Figure 2. This fact in turn increases the capillarity of the foam in the region thereof above these three filters and thus reduces the possibility of air bubbles interrupting the ink path through the foam and into the three ink pipes 94, 96 and 98.

The substrate member 102 is bonded to a nozzle plate 104 by means of an adhesive barrier 106. This barrier 106 may advantageously be a selected polymer material such as the RISTON or VACREL trade name polymer materials made available by the E. I. DuPont Company of Wilmington, Delaware. The ink will flow through the ink pipes 88, 90 and 92 and then into the three passages 108, 110 and 112 in the substrate member 102. These passageways 108, 110 and 112 will then feed ink to the plurality of groups of orifices 30, 32 and 34 in the nozzle plate 104 and located in a circular pattern as shown.

The nozzle plate 104 may advantageously be electroformed of nickel and plated with gold and then affixed to the polymer barrier material 106 using, for example, the heat staking process disclosed and claimed in EP-A-0 244 643. The nozzle plate 104 may be fabricated in the manner described in the above identified Hewlett Packard Journal, Vol. 38, No. 5 May 1985.

Finally, the thin film resistor structure 28 is secured to the bottom facing surface 100 of the pen body 10 by means of a suitable adhesive 114 which is disposed as shown at the outer periphery of the substrate 102, as well as at interior recessed wall surfaces 116 and 118 thereof.

The present invention is not limited to thermal ink jet applications and may instead be used in other types of ink jet applications in which the above foam storage-of-ink capability is desirable and compatible.

Claims

1. An ink jet pen having a printhead (28) mounted on a pen body housing (10), with a nozzle plate (104) disposed on said printhead and at least one passage (108,110,112) provided through said printhead for receiving ink from said housing, said nozzle plate (104) being provided with at least one plurality of ink ejection orifices (30,32,34), each said plurality being arranged as a group to receive ink from a said passage, characterised in that the orifices in each group are disposed in a circle about their respective passage.
2. An ink jet pen according to claim 1 wherein the housing (10) is divided into three compartments (12,14,16) with a separate opening (22,24,26) leading from each compartment to a separate plurality of ink ejection orifices (30,32,34).
3. An ink jet pen according to claim 2 wherein the compartments store, respectively, cyan, magenta, and yellow ink.

Patentansprüche

1. Ein Tintenstrahlstift mit einem Druckkopf (28), der auf einem Stiftkörpergehäuse (10) befestigt ist, mit einer Düsenplatte (104), die auf dem Druckkopf angeordnet ist, und zumindest einem Durchgang (108, 110, 112), der durch den Druckkopf zur Aufnahme von Tinte aus dem Gehäuse vorgesehen ist, wobei die Düsenplatte (104) mit zumindest einer Mehrzahl von Tintenauswurföffnungen (30, 32, 34) vorgesehen ist, wobei jede der Mehrzahl als eine



Gruppe angeordnet ist, um Tinte aus dem Durchgang zu empfangen, dadurch gekennzeichnet, daß die Öffnungen in jeder Gruppe in einem Kreis um ihren jeweiligen Durchgang angeordnet sind.

5

2. Ein Tintenstrahlstift gemäß Anspruch 1, bei dem das Gehäuse (10) in drei Abteile (12, 14, 16) mit einer getrennten Öffnung (22, 24, 26) unterteilt ist, die von jedem Abteil zu einer getrennten Mehrzahl von Tintenauswurföffnungen (30, 32, 34) führt.

10

3. Ein Tintenstrahlstift gemäß Anspruch 2, bei dem die Abteile Cyan-, Magenta- bzw. gelbe Tinte speichern.

15

Revendications

20

1. Dispositif d'écriture par jet d'encre comprenant une tête d'impression (28) montée sur un boîtier (10) de corps de dispositif d'écriture, avec une plaque à buses (104) placée sur ladite tête d'impression, et au moins un passage (108, 110, 112) situé à travers ladite tête d'impression pour recevoir de l'encre depuis ledit boîtier, ladite plaque à buses (104) étant munie d'au moins un ensemble d'orifices d'éjection d'encre (30, 32, 34), chaque dit ensemble étant agencé en groupe pour recevoir de l'encre depuis un dit passage, caractérisé en ce que les orifices dans chaque groupe sont disposés en un cercle autour de leur passage respectif.

25

30

35

2. Dispositif d'écriture par jet d'encre selon la revendication 1, dans lequel le boîtier (10) est divisé en trois compartiments (12, 14, 16) avec une ouverture séparée (22, 24, 26) conduisant de chaque compartiment vers un ensemble séparé d'orifices d'éjection d'encre (30, 32, 34).

40

3. Dispositif d'écriture par jet d'encre selon la revendication 2, dans lequel les compartiments contiennent, respectivement, de l'encre cyan, magenta et jaune.

45

50

55

