

Description

The present invention relates to a process for the preparation of compounds which are useful as anti-oxidants, and in particular, for anti-oxidants used in lubricants.

It is known from an article entitled The Condensation of 2-Hydroxyethylsulfides with Alcohols and Phenols by Richter et al, Journal of Polymer Science, Volume XLI, Pages 4076-4079, that a beta-dithiodialkanol when reacted in the presence of hydrochloric acid and an alcohol will give the corresponding ether as a reaction product. The technology in the Richter article is further reported in United States Patent 2,582,605 issued January 15, 1952.

It is suggested in German published patent application 1,520,040A that Guerbet alcohols may be condensed with thiodialkylols at a molar ratio of 0.5-0.9. United States Patent 4,366,307 issued December 28, 1982 to Singh et al describes non-crystallizing, water, solvent, duol and temperature resistant liquid polythioethers having 2-4 terminating radicals and at least 8 repeating sulfur-containing units.

Reid, in United States Patent 2,230,966, issued February 4, 1941, describes compositions which are alkylthio diethylsulfides. Reid states these materials may be used in lubricants and particularly as transformer fluids and motor oils.

Further information with regard to the polymerization of a beta-thiodialkanol is found in Thioglycol Polymers I Hydrochloric Acid-Catalyzed Auto Condensation of Thiodiglycol by Woodward, Journal of Polymer Science, Volume XLI, Pages 219-223 (1959). The hydroxyl groups in the beta position relative to the sulfur in an aliphatic chain are stated to be of unusual reactivity in the Woodward article. Further information on such beta-dialkanols is found in Thioglycol Polymers III Copolymerization of Thiodiglycol and Similar Thioglycols with Aliphatic Hydroxy Compounds by Andrews et al, Journal of Polymer Science, Volume XLI, Pages 231-239 (1959). The Andrews' reference describes copolymers obtained from dihydroxy compounds where one of the compounds is thiodiglycol.

United States Patent 3,450,771 issued June 17, 1969 to Dombro describes organic sulfides that may be prepared by reacting a mercaptan, such as an n-octyl mercaptan, with an alcohol, such as methanol, in an alkaline medium. Dombro further describes his process as being useful in removing mercaptans from petroleum products.

In an article Nucleophilic Substitution of Hydroxyl Groups in 2-Alkyl(Aryl)-Thioethanols, published by Fokin et al in the Bull. Acad. Sci. U.S.S.R. Div. Chem. Sci. 1982, Page 1667, there is de-

scribed the homocondensation of 2-alkylthioethanols. It is also disclosed in the Fokin paper that the 2-alkylthioethanol may be reacted with an alcohol to give a product containing both sulfur and ether linkages. Aromatic sulfur-containing compounds containing beta-hydroxy groups and their reaction properties are also discussed in the Fokin article. The Fokin paper does not discuss any particular utility or special advantage for the compositions described therein.


Musser and Koch in United States Patent 4,031,023 issued June 21, 1977 describe lubricating compositions which utilize hydroxy thioethers, methods of using these materials in lubricating compositions, and additive concentrates for forming such lubricant compositions. The compositions of Musser and Koch show terminal mercaptan and terminal hydroxy groups thereon.

It has been determined in accordance with the present invention that various products may be prepared from thiodialkanols which are reacted with a mercaptan. It is further described herein that beta-thiodialkanols may be polymerized, and the terminal hydroxyl groups on the polymerized thiodialkanol capped with the mercaptan as is later described.

The compositions prepared in accordance with the process of the present invention are particularly effective as anti-oxidants in lubricant compositions, and are capable of functioning in specialized uses as a lubricant per se with exceptional anti-oxidant properties.

Throughout the specification and claims, percentages and ratios are by weight, temperatures are in degrees Celsius, and pressures are expressed in KPa gauge unless otherwise indicated.

According to one aspect of the present invention there is provided a process for the preparation of a compound of formula



(wherein x is 1 or 2, y is 0 or greater, and R and R¹ are hydrocarbyl groups containing from 2 to 24 carbon atoms which may be the same or different, with the proviso that at least one of R and R¹ contains from about 5 carbon atoms up to about 24 carbon atoms) which comprises reacting at least one equivalent of a mercaptan of the formula RSH and at least one equivalent of a mercaptan of formula R¹SH, wherein R and R¹ are hydrocarbyl groups which may be the same or different and contain from 2 carbon atoms up to 24 carbon atoms, with the proviso that at least one of R and R¹ contains from about 5 to 24 carbon atoms, with at least two equivalents of a beta-thiodialkanol selected from thiodiglycol, dithiodiglycol and mixtures thereof.

The compounds prepared in accordance with the present invention may be conveniently employed in an automatic transmission fluid, or in a minor amount with a major amount of an oil of lubricating viscosity.

Various preferred features and embodiments of the present invention will now be described by way of non-limiting examples.

The first aspect of the process of the present invention are the mercaptans which are used therein. Mercaptans are a group of organo sulfur compounds that are derivatives of hydrogen sulfide in the same way that alcohols are derivatives of water. Mercaptans are also referred to generally as thiols. Mercaptans characteristically have a -SH group in the molecule.

In the process of the present invention the mercaptan contains a single thiol or -SH group. The mercaptans may be aliphatic in nature and have the formula

RSH OR R'SH

The mercaptan is highly reactive in the process of the invention, and the mercaptan (SH) condenses with the hydroxyl group from the thiodialkanol as later described to form the desired product and water.

The mercaptan is conveniently a material which has the hydrocarbyl group, R, (or R') as either an aliphatic or aromatic material which at least gives the product an oil-dispersible or oil-soluble character.

Where the mercaptan is aliphatic material, it will typically contain from about 2 to about 24 carbon atoms, preferably from about 4 to about 18 carbon atoms; provided, of course, that the reaction is carried out using at least one equivalent of a mercaptan containing at least 5 carbon atoms. Examples of the mercaptans include materials such as methyl mercaptan, ethyl mercaptan, propyl mercaptan, n-butyl mercaptan, n-pentyl mercaptan, and the various isomers of these compounds. Further mercaptans include dodecyl mercaptan. An example of an aromatic mercaptan is thiophenol. Further useful mercaptans herein include heterocycles containing pendant (-SH) groups such as mercaptothiadiazoles and mercaptobenzothiazole. It is very desirable in the present invention that the mercaptan be substantially free of hydroxyl groups such that the reaction product of the beta-thiodialkanol and the mercaptan is also substantially free of hydroxyl groups.

The second component for the process of the present invention is a beta-thiodialkanol so that the sulfur atom forming the sulfide linkage is located two carbon atoms from one or both of the hydroxyl groups.

The beta-thiodialkanol is thiodiglycol or dithiodiglycol which may be described by the formula

5 $\text{HOCH}_2\text{CH}_2\text{S}_x\text{CH}_2\text{CH}_2\text{OH}$, where x is 1 or 2.

The beta-thiodialkanol preferably contains only one sulfur atom per repeating unit, i.e., x is 1. However, it is acceptable and under some conditions desirable to have x at a value of 2 thereby having a disulfide structure in the molecule. It is also possible to have compositions where there are mixtures of monosulfide and disulfide. For an automatic transmission fluid, the monosulfide is desired. In lubricating oils for engines, some disulfide is desired to provide anti-wear as well as anti-oxidant properties.

Further, with regard to the structural formula for the products of the process of the invention given above, the value of y is stated to be 0 or greater, preferably from 1 to 5 for polymers, and most preferably from 1 to 3. Such polymerization is obtained by using at least an equivalent excess of the thiodialkanol. The polymerization of the thiodialkanol may be done independently of its introduction to the mercaptan, or may be conducted in situ, e.g., a one-pot reaction where the thiodialkanol and the mercaptan are present simultaneously. If it is desired to obtain the product where y is 0, the mercaptan is introduced to the pot, followed by slowly introducing the thiodialkanol. Where longer polymers are desired, e.g., y is a large number, it is possible to prepolymerize the thiodialkanol and to introduce the mercaptan at a later point.

Further, with regard to the above described structural formula, it is desirable that one of R or R' is an aliphatic group. A further desirable variation is where one of R or R' is an aromatic group. Where R or R' is an aliphatic group, it is desirable that the aliphatic group contain from 4 to 18, preferably 6 to 18 carbon atoms provided, of course, that at least one of R and R' contains 5 to 24 carbon atoms.

As previously noted, the product is capped with a mercaptan residue (RS or R'S).

This is done by preparing the product such that there are two equivalents of the mercaptan for each two equivalents of the thiodialkanol. As the thiodialkanol is a difunctional material, it will react with one equivalent of a monomercaptan at each end of the thiodiglycol molecule to liberate two equivalents of water, thereby giving the desired reaction product. As the mercaptan reacts somewhat slower than the thiodialkanol polymerizes, it is possible to use two equivalents of the mercaptan and a substantially greater number of equivalents of the thiodialkanol to obtain the desired reaction product. The equivalent weight of the thiodialkanol is one-half of its molecular weight.

The mercaptan and the thiodialkanol are conveniently reacted in a suitable reaction vessel which is constructed with a trap due to the odorous nature of the mercaptan. It is desirable that any unreacted mercaptan be scavenged or scrubbed out of the reaction product following the reaction to avoid any unpleasant odors in the work area. It is, of course, possible to include small amounts of the mercaptan or the thiodialkanol or the polymerized thiodialkanol in the final product for use in the later described lubricants.

The temperature conditions for conducting the reaction are typically between about 50°C to about 200°C, preferably from about 100°C to about 150°C. The reaction mixture is conveniently stirred at a moderate rate in order to facilitate full mixing of the ingredients to insure complete reactivity. The reaction is preferably acid catalyzed. Suitable acids are those mineral acids such as sulfuric or phosphoric or an organic acid such as para-toluene sulfonic acid. The catalyst need not be removed from the final product; however, if such is desired, the catalyst may be removed by base treatment and filtration.

The compounds prepared in accordance with the present invention are useful in various lubricating products and in particular in motor vehicle lubricants. The lubricants typically contain a lubricant base material which is an oil of lubricating viscosity such as further described below. The products obtained herein are peroxide decomposers and metal chelators.

Unrefined, refined and rerefined oils (and mixtures of each with each other) of the type disclosed hereinabove can be used in the lubricants and functional fluids of the present invention. Unrefined oils are those obtained directly from a natural or synthetic source without further purification treatment. For example, a shale oil obtained directly from retorting operations, a petroleum oil obtained directly from distillation or ester oil obtained directly from an esterification process and used without further treatment would be an unrefined oil. Refined oils are similar to the unrefined oils except they have been further treated in one or more purification steps to improve one or more properties. Many such purification techniques are known to those of skill in the art such as solvent extraction, acid or base extraction, filtration, percolation, etc. Rerefined oils are obtained by processes similar to those used to obtain refined oils applied to refined oils which have been already used in service. Such rerefined oils are also known as reclaimed or reprocessed oils and often are additionally processed by techniques directed to removal of spent additives and oil breakdown products.

The synthetic lubricating oils useful herein include hydrocarbon oils and halosubstituted hydrocarbon oils such as polymerized and interpolymerized olefins (e.g., polybutylenes, polypropylenes, propylene-isobutylene copolymers, chlorinated polybutylenes, etc.); poly(1-hexenes), poly(1-octenes), poly(1-decenes), etc. and mixtures thereof; alkylbenzenes (e.g., dodecylbenzenes, tetradecylbenzenes, dinonylbenzenes, di-(2-ethylhexyl)-benzenes, etc.); polyphenyls (e.g., biphenyls, terphenyls, alkylated polyphenyls, etc.); alkylated diphenyl ethers and alkylated diphenyl sulfides and the derivatives, analogs and homologs thereof and the like.

Alkylene oxide polymers and interpolymers and derivatives thereof where the terminal hydroxyl groups have been modified by esterification, etherification, etc., constitute another class of known synthetic lubricating oils that can be used. These are exemplified by the oils prepared through polymerization of ethylene oxide or propylene oxide, the alkyl and aryl ethers of these polyoxyalkylene polymers (e.g., methylpolyisopropylene glycol ether having an average molecular weight of about 100, diphenyl ether of polyethylene glycol having a molecular weight of about 500-1000, diethyl ether of polypropylene glycol having a molecular weight of about 1000±500, etc. or mono- and polycarboxylic esters thereof, for example, the acetic acid esters, mixed C₃-C₈ fatty acids esters, or the C₁₃Oxo acid diester of tetraethylene glycol.

Another suitable class of synthetic lubricating oils that can be used comprises the esters of dicarboxylic acids (e.g., phthalic acid, succinic acid, alkyl succinic acids, alkenyl succinic acids, maleic acid, azelaic acid, suberic acid, sebacic acid, fumaric acid, adipic acid, linoleic acid dimer, malonic acid, alkyl malonic acids, alkenyl malonic acids, etc.) with a variety of alcohols (e.g., butyl alcohol, hexyl alcohol, dodecyl alcohol, 2-ethylhexyl alcohol, ethylene glycol, diethylene glycol monoether, propylene glycol, etc.). Specific examples of these esters include dibutyl adipate, di(2-ethylhexyl) sebacate, di-n-hexyl fumarate, dioctyl sebacate, diisooctyl azelate, diisodecyl azelate, dioctyl phthalate, didecyl phthalate, dieicosyl sebacate, the 2-ethylhexyl diester of linoleic acid dimer, the complex ester formed by reacting one mole of sebacic acid with two moles of tetraethylene glycol and two moles of 2-ethylhexanoic acid, and the like.

Esters useful as synthetic oils also include those made from C₅ to C₁₂ monocarboxylic acids and polyols and polyol ethers such as neopentyl glycol, trimethylol propane, pentaerythritol, dipentaerythritol, tripentaerythritol, etc.

Silicon-based oils such as the polyalkyl-, polyaryl-, polyalkoxy- or polyaryloxy-siloxane oils

and silicate oils-comprise another useful class of synthetic lubricants (e.g., tetraethyl silicate, tetraisopropyl silicate, tetra-(2-ethylhexyl) silicate, tetra-(4-methyl-hexyl) silicate, tetra-(p-tert-butyl-phenyl)silicate, hexyl-4-methyl-2-pentoxyl-disiloxane, poly(methyl)siloxanes, poly-(methylphenyl)siloxanes, etc.). Other synthetic lubricating oils include liquid esters of phosphorus containing acids (e.g., tricresyl phosphate, trioctyl phosphate, diethyl ester of decane phosphoric acid, etc.), polymeric tetrahydrofurans and the like.

Polyolefin oligomers are typically formed by the polymerization reaction of alpha-olefins. Nonalpha-olefins may be oligomerized to give a synthetic oil within the present invention, however, the reactivity and availability of alpha-olefins at low cost dictates their selection as the source of the oligomer.

The polyolefin oligomer synthetic lubricating oils of interest in the present invention include hydrocarbon oils and halo-substituted hydrocarbon oils such as are obtained as the polymerized and interpolymerised olefins, e.g., oligomers, include the polybutylenes, polypropylenes, propylene-isobutylene copolymers, chlorinated polybutylenes, poly(1-hexenes), poly(1-octenes), poly(1-decenes), similar materials and mixtures thereof.

Typically, the oligomer is obtained from a monomer containing from about 6 to 18 carbon atoms. Most preferably, the monomer used to form the oligomer is decene, and preferably 1-decene. The nomenclature alpha-olefin is a trivial name and the IUPAC nomenclature of a 1-ene compound may be considered to have the same meaning within the present invention.

While it is not essential that the oligomer be formed from an alpha-olefin, such is desirable. The reason for forming the oligomer from an alpha-olefin is that branching will naturally occur at the points where the olefin monomers are joined together, and any additional branching within the backbone of the olefin can provide too high a viscosity of the end oil. It is also desirable that the polymer formed from the alpha olefin be hydrogenated. The hydrogenation is conducted according to known practices. By hydrogenating the polymer, free radical attack on the allylic carbons remaining after polymerization is minimized.

Additional materials which are desirably added to the hydrocarbon based fluids are as follows: Viscosity improving materials may be included in the compositions of the present invention. The viscosity index improvers typically include polymerized and copolymerized alkyl methacrylates and mixed esters or styrene-maleic anhydride interpolymers reacted with nitrogen-containing compounds.

Polyisobutylene compounds are also typically used as viscosity index improvers. The amount of viscosity improver which may be typically added to the fully formulated manual transmission fluid composition is about 1% to about 50%, preferably about 10% to about 25% by weight.

Zinc salts are also added to manual transmission lubricants. Zinc salts are ordinarily utilized as extreme pressure agents such as zinc dithiophosphates. The zinc salts are added at levels measured by weight of the zinc metal at from about 0.02% to about 0.2%, preferably from about 0.04% to about 0.15% by weight.

Additional ingredients which may be included in a transmission fluid are fatty acid amides which are useful as additional friction modifiers, particularly for reducing the static coefficient of friction. Further useful components herein include seal swell agents such as sulfones and sulfolanes. Suitable seal swell agents are disclosed in United States Patent 4,029,587 to Koch issued June 14, 1977. A still further useful component in the present invention is a foam suppression agent such as a silicone oil. Any other typical ingredient may be included herein such as pour point depressants, dyes, odorants and the like.

Additional components which are typically used in transmission fluids, motor oils or hydraulic fluids include the following.

Extreme pressure agents and corrosion and oxidation-inhibiting agents which may be included in the compositions of the invention are exemplified by chlorinated aliphatic hydrocarbons such as chlorinated wax; organic sulfides and polysulfides such as benzyl disulfide, bis(chlorobenzyl)disulfide, dibutyl tetrasulfide, sulfurized methyl ester of oleic acid, sulfurized alkylphenol, sulfurized dipentene, and bisulfurized terpene; phosphosulfurized hydrocarbons such as the reaction product of a phosphorus sulfide with turpentine or methyl oleate, phosphorus esters including principally dihydrocarbon and trihydrocarbon phosphites such as dibutyl phosphite, diheptyl phosphite, dicyclohexyl phosphite, pentylphenyl phosphite, dipentylphenyl phosphite, tridecyl phosphite, distearyl phosphite, dimethyl naphthyl phosphite, oleyl 4-pentylphenyl phosphite, polypropylene (molecular weight 500)-substituted phenyl phosphite, diisobutyl-substituted phenyl phosphite; metal thiocarbamates, such as zinc dioctyldithiocarbamate, and barium heptylphenyl dithiocarbamate; Group II metal phosphorodithioates such as Zinc dicyclohexylphosphorodithioate, Zinc dioctylphosphorodithioate, barium di(heptylphenyl)phosphorodithioate, cadmium dinonylphosphorodithioate, and the zinc salt of a phosphorodithioic acid produced by the reaction of phosphorus pentasulfide with an equimolar mixture of isopropyl alcohol and n-hexyl alcohol.

Many of the above-mentioned extreme pressure agents and corrosion-oxidation inhibitors also serve as anti-wear agents. Zinc dialkylphosphorodithioates are a well known example.

Anti-wear agents that are particularly useful in the hydraulic fluid compositions of the invention are those obtained from a phosphorus acid of the formula $(R'O)2PSSH$, wherein each R' is independently a hydrocarbon-based group, or the phosphorus acid precursors thereof with at least one phosphite of the formula $(R''O)3P$, R'' is a hydrocarbon-based group, under reaction conditions at a temperature of about $50^{\circ}C$ to about $200^{\circ}C$. R' is preferably an alkyl group of about 3 to about 50 carbon atoms, and R'' is preferably aromatic. The salt is preferably a zinc salt, but can be a mixed salt of at least one of said phosphorus acids and at least one carboxylic acid. These anti-wear agents are described more fully in U.S. Patent No. 4,263,150. These anti-wear agents as well as the anti-wear agents referred to above can be provided in the compositions of the invention at levels of about 0.1% to about 5%, preferably about 0.25% to about 1% by weight based on the total weight of said fluid compositions.

Additional oxidation inhibitors that are particularly useful in the fluid compositions of the invention are the hindered phenols (e.g., 2, 6-di-(t-butyl)-phenol); aromatic amines (e.g., alkylated diphenyl amines); alkyl polysulfides; selenides; borates (e.g., epoxide/boric acid reaction products); phosphorodithioic acids, esters and/or salts; and the dithiocarbamate (e.g., zinc dithiocarbamates). These oxidation inhibitors as well as the oxidation inhibitors discussed above are preferably present in the fluids of the invention at levels of about 0.05% to about 5%, more preferably about 0.25% to about 2% by weight based on the total weight of such compositions.

The rust-inhibitors that are particularly useful in the compositions of the invention are the alkenyl succinic acids, anhydrides and esters, preferably the tetrapropenyl succinic acids, acid/esters and mixtures thereof; metal (preferably calcium and barium) sulfonates; the amine phosphates; and the imidazolines. These rust-inhibitors are preferably present at levels of about 0.01% to about 5%, preferably about 0.02% to about 1% by weight based on the total weight of the product.

Pour point depressants may be included in the compositions described herein. The use of such pour point depressants in oil-based compositions to improve low temperature properties of oil-based compositions is well known in the art. See, for example, page 8 of "Lubricant Additives" by C. V. Smalheer and R. Kennedy Smith (Lezius-Hiles Co. Publishers, Cleveland, Ohio 1967).

Examples of useful pour point depressants are polymethacrylates; polyacrylates; polyacrylamides; condensation products of haloparaffin waxes and aromatic compounds; vinyl carboxylate polymers; and terpolymers of dialkylfumarates, vinyl esters of fatty acids and alkyl vinyl ethers. Pour point depressants useful for the purposes of this invention, techniques for their preparation and their uses are described in U.S. Patent Nos. 2,387,501; 2,015,748; 2,655,479; 1,815,022; 2,191,498; 2,666,746; 2,721,877; 2,721,878 and 3,250,715.

Anti-foam agents are used to reduce or prevent the formation of stable foam. Typical anti-foam agents include silicones or organic polymers. Additional anti-foam compositions are described in "Foam Control Agents", by Kerner (Noyes Data Corporation, 1976), pages 125-162.

The compounds prepared in accordance with the process of the present invention are typically used in automatic transmission fluids, hydraulic fluids, functional fluids or lubricating oil compositions at a level of about 0.025% to about 5%, preferably from about 0.1% to about 2% by weight. As the products of the invention are oleophilic, the blending of the products is relatively simple. Where the products of the process of the invention are intended for use in an aqueous based material, it is desirable to include such adjuvants and other materials as may be necessary to stably disperse the active ingredients in the aqueous formulation. When an aqueous composition is utilized, it is typically up to 85% and preferably up to 90% water with the remainder being the active ingredient of this invention and other materials typically placed in such aqueous formulations.

The following are examples of the present invention.

EXAMPLE I

A suitable reaction vessel is prepared and 2 moles of n-dodecyl mercaptan is added with 400 mls. of toluene. Five grams of para-toluene sulfonic acid catalyst is added to the reaction mixture. The reaction mixture is heated to reflux under nitrogen and one mole of thiodiglycol is introduced dropwise over a period of approximately 2 hours. The reaction is continued until no further water is evolved.

The acid catalyst is neutralized with 50% aqueous caustic and the solvent is removed under reduced pressure. The reaction product is then filtered at $80^{\circ}C$ and the filtrate is recovered as the product.

EXAMPLE II

A product is prepared from a mixture of mercaptans. One mole of mercaptobenzthiazole, one

mole of dodecyl mercaptan and 400 mls. of toluene are added to the reaction vessel. The reaction mixture is heated to reflux and 5 grams of sulfuric acid catalyst are added. With continued heating and stirring, one mole of thiodiglycol is added incrementally over a period of approximately 2 hours. The reaction is continued until no more water is evolved.

The solvent is removed under reduced pressure and the product is filtered. The filtrate is the recovered product.

EXAMPLE III

To a suitable reaction vessel is added 2 moles of thiodiglycol, 2 moles of thiophenol, 400 mls. of toluene and 5 grams of sulfuric acid catalyst. The reaction mixture is heated to reflux and the reaction is continued until no further water is evolved.

The acid catalyst is neutralized with 50% aqueous caustic and the solvent is removed under reduced pressure. The product is then filtered and the filtrate is recovered as the product.

EXAMPLE IV


A series of automatic transmission fluids without conventional antioxidants are prepared and labeled as A, B and C. The three products (A, B and C) are separately combined at 100 parts with 1 part of the reaction product of Examples I-III.

A fourth automatic transmission fluid is prepared as D. The product D is the same as A, however, 1 part of octylated diphenylamine is added as an additional antioxidant.

The compounds of the invention perform exceptionally well as anti-oxidants in the automatic transmission fluids. As a further variation of the invention an automatic transmission fluid is formulated as in Example B except that the thiodiglycol component of the antioxidant is replaced by the corresponding disulfide.

Claims

1. A process for the preparation of a compound of formula



(wherein x is 1 or 2, y is 0 or greater, and R and R¹ are hydrocarbyl groups containing from 2 to 24 carbon atoms which may be the same or different, with the proviso that at least one of R and R¹ contains from about 5 carbon atoms up to about 24 carbon atoms) which comprises reacting at least one equivalent of a mercaptan


of the formula RSH and at least one equivalent of a mercaptan of formula R¹SH, wherein R and R¹ are hydrocarbyl groups which may be the same or different and contain from 2 carbon atoms up to 24 carbon atoms, with the proviso that at least one of R and R¹ contains from about 5 to 24 carbon atoms, with at least two equivalents of a beta-thiodialkanol selected from thiodiglycol, dithiodiglycol and mixtures thereof.

2. A process according to claim 1 wherein RSH and R¹SH are the same.

3. A process of either of claims 1 and 2 wherein the equivalents of the beta-thiodialkanol present are greater than the equivalents of mercaptans.

Patentansprüche

1. Verfahren zur Herstellung von Verbindungen der allgemeinen Formel



wobei x den Wert 1 oder 2 hat, y den Wert 0 hat oder größer ist, und die Reste R und R¹ gleich oder verschieden und C₂₋₂₄-Hydrocarbylreste sind, mit der Maßgabe, daß mindestens einer der Reste R und R¹ etwa 5 bis etwa 24 C-Atome enthält,

umfassend die Umsetzung von mindestens einem Äquivalent eines Mercaptans der allgemeinen Formel RSH und mindestens einem Äquivalent eines Mercaptans der allgemeinen Formel R¹SH, wobei die Reste R und R¹ gleich oder verschieden und C₂₋₂₄-Hydrocarbylreste sind, mit der Maßgabe, daß mindestens einer der Reste R und R¹ etwa 5 bis 24 C-Atome enthält, mit mindestens zwei Äquivalenten eines β-Thiodialkanols ausgewählt aus der Gruppe Thiodiglykol, Dithiodiglykol und deren Gemischen.

2. Verfahren nach Anspruch 1, wobei RSH und R¹SH gleich sind.

3. Verfahren nach Anspruch 1 oder 2, wobei mehr β-Thiodialkanol-Äquivalente als Mercaptan-Äquivalente vorliegen.

Revendications

1. Procédé pour la préparation d'un composé de formule

mole of dodecyl mercaptan and 400 mls. of toluene are added to the reaction vessel. The reaction mixture is heated to reflux and 5 grams of sulfuric acid catalyst are added. With continued heating and stirring, one mole of thiodiglycol is added incrementally over a period of approximately 2 hours. The reaction is continued until no more water is evolved.

The solvent is removed under reduced pressure and the product is filtered. The filtrate is the recovered product.

EXAMPLE III

To a suitable reaction vessel is added 2 moles of thiodiglycol, 2 moles of thiophenol, 400 mls. of toluene and 5 grams of sulfuric acid catalyst. The reaction mixture is heated to reflux and the reaction is continued until no further water is evolved.

The acid catalyst is neutralized with 50% aqueous caustic and the solvent is removed under reduced pressure. The product is then filtered and the filtrate is recovered as the product.

EXAMPLE IV


A series of automatic transmission fluids without conventional antioxidants are prepared and labeled as A, B and C. The three products (A, B and C) are separately combined at 100 parts with 1 part of the reaction product of Examples I-III.

A fourth automatic transmission fluid is prepared as D. The product D is the same as A, however, 1 part of octylated diphenylamine is added as an additional antioxidant.

The compounds of the invention perform exceptionally well as anti-oxidants in the automatic transmission fluids. As a further variation of the invention an automatic transmission fluid is formulated as in Example B except that the thiodiglycol component of the antioxidant is replaced by the corresponding disulfide.

Claims

1. A process for the preparation of a compound of formula



(wherein x is 1 or 2, y is 0 or greater, and R and R¹ are hydrocarbyl groups containing from 2 to 24 carbon atoms which may be the same or different, with the proviso that at least one of R and R¹ contains from about 5 carbon atoms up to about 24 carbon atoms) which comprises reacting at least one equivalent of a mercaptan


of the formula RSH and at least one equivalent of a mercaptan of formula R¹SH, wherein R and R¹ are hydrocarbyl groups which may be the same or different and contain from 2 carbon atoms up to 24 carbon atoms, with the proviso that at least one of R and R¹ contains from about 5 to 24 carbon atoms, with at least two equivalents of a beta-thiodialkanol selected from thiodiglycol, dithiodiglycol and mixtures thereof.

2. A process according to claim 1 wherein RSH and R¹SH are the same.

3. A process of either of claims 1 and 2 wherein the equivalents of the beta-thiodialkanol present are greater than the equivalents of mercaptans.

Patentansprüche

1. Verfahren zur Herstellung von Verbindungen der allgemeinen Formel



wobei x den Wert 1 oder 2 hat, y den Wert 0 hat oder größer ist, und die Reste R und R¹ gleich oder verschieden und C₂₋₂₄-Hydrocarbylreste sind, mit der Maßgabe, daß mindestens einer der Reste R und R¹ etwa 5 bis etwa 24 C-Atome enthält, umfassend die Umsetzung von mindestens einem Äquivalent eines Mercaptans der allgemeinen Formel RSH und mindestens einem Äquivalent eines Mercaptans der allgemeinen Formel R¹SH, wobei die Reste R und R¹ gleich oder verschieden und C₂₋₂₄-Hydrocarbylreste sind, mit der Maßgabe, daß mindestens einer der Reste R und R¹ etwa 5 bis 24 C-Atome enthält, mit mindestens zwei Äquivalenten eines β-Thiodialkanols ausgewählt aus der Gruppe Thiodiglykol, Dithiodiglykol und deren Gemischen.


2. Verfahren nach Anspruch 1, wobei RSH und R¹SH gleich sind.

3. Verfahren nach Anspruch 1 oder 2, wobei mehr β-Thiodialkanol-Äquivalente als Mercaptan-Äquivalente vorliegen.

Revendications

1. Procédé pour la préparation d'un composé de formule





(dans laquelle x vaut 1 ou 2, y vaut 0 ou plus, et R et R' représentent des groupes hydrocarbyle contenant de 2 à 24 atomes de carbone qui peuvent être identiques ou différents, à condition qu'au moins un de R et R' contient d'environ 5 atomes de carbone jusqu'à environ 24 atomes de carbone) qui consiste à faire réagir au moins un équivalent d'un mercaptan de formule RSH et au moins un équivalent d'un mercaptan de formule R'SH, dans lesquelles R et R' représentent des groupes hydrocarbyle qui peuvent être identiques ou différents et qui contiennent de 2 atomes de carbone jusqu'à 24 atomes de carbone, à condition qu'au moins un de R et R' contient d'environ 5 à 24 atomes de carbone, avec au moins deux équivalents d'un béta-thiodialcanol choisi parmi le thiodiglycol, le dithiodiglycol et leurs mélanges.

2. Procédé selon la revendication 1, dans lequel RSH et R'SH sont identiques.

3. Procédé selon chacune des revendications 1 et 2, dans lequel les équivalents du béta-thiodialcanol présents sont supérieurs aux équivalents de mercaptans.

