

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
21 September 2023 (21.09.2023)



(10) International Publication Number
WO 2023/175399 A3

(51) International Patent Classification:
H02J 50/00 (2016.01) *H02J 7/02* (2016.01)
B60R 16/02 (2006.01)

(21) International Application Number:
PCT/IB2023/000167

(22) International Filing Date:
15 March 2023 (15.03.2023)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
63/320,590 16 March 2022 (16.03.2022) US
63/476,781 22 December 2022 (22.12.2022) US

(71) Applicant: **DAANAA RESOLUTION INC.** [CA/CA];
900 W Hastings Street, Suite 1200, Vancouver, BC V6C
1E5 (CA).

(72) Inventors: **MOHAMMADABADI, Soroush, Dehghani**;
900 W Hastings Street, Suite 1200, Vancouver, BC V6C
1E5 (CA). **SHARIATZADEH, Mohammadjavad**; 900
W Hastings Street, Suite 1200, Vancouver, BC V6C 1E5
(CA). **HAFSHEJANI, Ehsan, Hadizadeh**; 900 W Hast-
ings Street, Suite 1200, Vancouver, BC V6C 1E5 (CA).
DAON, Ehud; 900 W Hastings Street, Suite 1200, Vancou-
ver, BC V6C 1E5 (CA). **ASOODEH, Alireza**; 900 W Hast-
ings Street, Suite 1200, Vancouver, BC V6C 1E5 (CA).

(74) Agent: **LODENQUAI, Lauren**; Deeth William Wall LLP,
150 York St., Suite 400, Toronto, Ontario M5H 3S5 (CA).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,

(54) Title: POWER TRANSFER SYSTEM AND METHODS




FIG. 1

(57) Abstract: A system and associated method transfer power between a DC source and a variable load. Two power signals are extracted from the DC source at an HF frequency via two self-synchronous radio frequency rectifiers/amplifiers switched by two corresponding HF switching signals having between them a phase difference controlled by a duty cycle and overlap controller. The two HF power signals are mixed in a wired, wireless, or bimodal wireless HF power link system to produce a transferred power signal based on the mixing and on manipulating the phase difference. An unfolded output power signal is created from the transferred power signal by means of a power signal conversion circuit in communication with the HF power link system. The system and method allow transfer to the load of at least one of an adjustable DC power signal and an AC power signal phase locked to an existing power signal in the load.

[Continued on next page]

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CV, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IQ, IR, IS, IT, JM, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, MG, MK, MN, MU, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

- (84) Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, CV, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SC, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, ME, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

Published:

- *with international search report (Art. 21(3))*
— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

(88) Date of publication of the international search report:

26 October 2023 (26.10.2023)