

SIGNALING OF SLICE AND TILE PICTURE PARTITIONS

CROSS REFERENCE TO RELATED APPLICATIONS

[001] This application is based on International Patent Application No. PCT/CN2021/077216 filed on February 22, 2021, which claims the priority to and benefits of International Patent Application No. PCT/CN2020/076158, filed on February 21, 2020. All of the aforementioned patent applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

[002] This patent document relates to image and video coding and decoding.

BACKGROUND

[003] Digital video accounts for the largest bandwidth use on the internet and other digital communication networks. As the number of connected user devices capable of receiving and displaying video increases, it is expected that the bandwidth demand for digital video usage will continue to grow.

SUMMARY

[004] The present document discloses techniques that can be used by video encoders and decoders for processing coded representation of video using control information useful for decoding of the coded representation.

[005] In one example aspect, a video processing method is disclosed. The method includes performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more slices and the rule specifies that a syntax element indicating a difference between tile indices of two rectangular slices is present in the bitstream responsive to at least one condition being satisfied. A first rectangular slice of the two rectangular slices is represented as i -th rectangular slice, where i is an integer.

[006] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more sub-pictures and each sub-picture comprises one or more rectangular slices. The rule specifies that a slice index at a sub-picture

level for each rectangular slice in each sub-picture is derived to determine a number of coding tree units in each slice.

[007] In another example aspect, a video processing method is disclosed. The method includes determining, for a conversion between a video picture of a video that comprises one or more sub-pictures and a bitstream of the video, a mapping relationship between a sub-picture-level slice index of a slice in a sub-picture and a picture level slice index of the slice. The method also includes performing the conversion based on the determining.

[008] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more sub-pictures and the rule specifies that a tile of the video is positioned entirely within a single sub-picture of the video picture.

[009] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video picture of a video and a bitstream of the video, wherein the video picture comprises one or more sub-pictures. The bitstream conforms to a format rule specifying that information of partitioning a picture is included in a syntax structure associated with the picture.

[0010] In another example aspect, a video processing method is disclosed. The method includes determining, for a conversion between a video picture of a video that comprises one or more slices having a non-rectangular shape and a bitstream of the video, slice partitioning information of the video picture. The method also includes performing the conversion based on the determining.

[0011] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video picture of a video that comprises one or more slices and a bitstream of the video according to a rule. The rule specifies that a number of slices in the video picture is equal to or greater than a minimum number of slices determined based on whether rectangular partitioning or non-rectangular partitioning is applied to the video picture.

[0012] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more slices. In case slice partitioning

information of the video picture is included in a syntax structure of a video unit, a slice is represented by a top-left location and a dimension of the slice.

[0013] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more sub-pictures and each sub-picture comprises one or more slices. The rule specifies a manner by which partitioning information of the one or more slices in each sub-picture is present in the bitstream.

[0014] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more rectangular slices and each slice comprises one or more tiles. The rule specifies that signaling between a difference between a first tile index of a first tile in i th rectangular slice and a second tile index of a first tile in $(i+1)$ th rectangular slice is omitted in the bitstream.

[0015] In another example aspect, a video processing method is disclosed. The method includes determining, for a conversion between a video picture of a video and a bitstream of the video, that information for deriving a number of columns of tiles and a number of rows of tiles in the video picture is conditionally included in the bitstream responsive to a relationship between a dimension of the video picture and a dimension of a coding tree block. The method also includes performing the conversion based on the determining.

[0016] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video picture of a video and a bitstream of the video. The video picture comprises one or more sub-pictures. The bitstream conforms to a format rule specifying that, in case a variable that specifies a subpicture identifier of a subpicture that includes a slice is present in the bitstream, there is one and only one syntax element that satisfies a condition that a second variable corresponding to the syntax element is equal to the variable.

[0017] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video picture of a video and a bitstream of the video. The video picture comprises one or more sub-pictures. In case a non-rectangular partitioning is applied or sub-picture information is omitted in the bitstream, two tiles in a slice have different addresses.

[0018] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more tiles. The rule specifies that a syntax element is used to indicate a type of tile layout in case the one or more tiles are organized in both uniform spacing and non-uniform spacing.

[0019] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The rule specifies that whether or how a Merge Estimation Region (MER) size is processed in the conversion is conditioned on a minimum allowed coding block size.

[0020] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video that comprises at least a video tile and a bitstream of the video according to a rule. The rule specifies that a height of a slice in the video tile in units of coding tree units is derived based on a value of a first syntax element in the bitstream indicating a number of explicitly provided slice heights for slices in the video tile that includes the slice.

[0021] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video comprising a video picture comprising a video tile including one or more slices and a bitstream of the video according to a rule. The rule specifies that a second slice in a tile that includes a first slice in a picture has a height that is represented in a unit of coding tree units. The first slice has a first slice index, and the second slice has a second slice index that is determined based on the first slice index and a number of explicitly provided slice heights in the video tile. The height of the second slice is determined based on the first slice index and the second slice index.

[0022] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video comprising a video picture including one or more tiles and a bitstream of the video. The video picture refers to a picture parameter set and the picture parameter set conforms to a format rule specifying that the picture parameter set includes a list of column widths for N tile columns, where N is an integer. An (N-1)-th tile column exists in the video picture and the (N-1)-th tile column has a width that is equal to an (N-1)-th entry in a list of explicitly included tile column widths plus one number of coding tree blocks.

[0023] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video comprising a video picture including one or more tiles and a bitstream of the video. The video picture refers to a picture parameter set and the picture parameter set conforms to a format rule specifying that the picture parameter set includes a list of row heights for N tile rows, where N is an integer. An (N-1)-th tile row exists in the video picture and the (N-1)-th tile row has a height that is equal to an (N-1)-th entry in a list of explicitly included tile row heights plus one number of coding tree blocks.

[0024] In another example aspect, a video processing method is disclosed. The method includes performing a conversion between a video comprising one or more video pictures, wherein each video picture comprises one or more subpictures that comprise one or more slices and a coded representation of a video, wherein the coded representation conforms to a format rule; wherein the format rule specifies that, in case that a rectangular slices mode is enabled for a video picture, then a picture-level slice index for each slice in each subpicture in the video picture is derived without explicit signaling in the coded representation; and wherein the format rule specifies that a number of coding tree units in each slice is derivable from the picture-level slice index.

[0025] In another example aspect, another video processing method is disclosed. The method includes performing a conversion between a video comprising one or more video pictures, wherein each video picture comprises one or more subpictures that comprise one or more slices and a coded representation of a video, wherein the coded representation conforms to a format rule; wherein the format rule specifies that a subpicture level slice index is derivable based on information in the coded representation without signaling the sub-picture level slice index in the coded representation.

[0026] In another example aspect, another video processing method is disclosed. The method includes performing a conversion between a video comprising one or more video pictures, wherein each video picture comprises one or more subpictures and/or one or more tiles and a coded representation of a video, wherein the coded representation conforms to a format rule; and wherein the conversion conforms to a constraint rule.

[0027] In another example aspect, another video processing method is disclosed. The method includes performing a conversion between a video comprising one or more video pictures, wherein each video picture comprises one or more tiles and/or one more slices; wherein the

coded representation conforms to a format rule; wherein the format rule specifies that a field at a video picture level carries information about portioning of slices and/or tiles in the video picture.

[0028] In another example aspect, another video processing method is disclosed. The method includes performing a conversion between a video comprising one or more pictures and a coded representation of the video, wherein the conversion conforms to a partitioning rule that a minimum number of slices in which a video picture is partitioned is a function of whether rectangular partitioning is used for partitioning the video picture.

[0029] In another example aspect, another video processing method is disclosed. The method includes performing a conversion between a video slice of a video region of a video and a coded representation of the video; wherein the coded representation conforms to a format rule; wherein the format rule specifies that the coded representation signals the video slice based on a top-left location of the video slice and wherein the format rule specifies that the coded representation signals a height and/or a width of the video slice in partitioning information that is signaled at a video unit level.

[0030] In another example aspect, another video processing method is disclosed. The method includes performing a conversion between a video comprising video pictures and a coded representation of the video; wherein the coded representation conforms to a format rule; wherein the format rule specifies to omit signaling a difference between a tile index of a first tile in a rectangular slice and a tile index of a first tile in a next rectangular slice.

[0031] In another example aspect, another video processing method is disclosed. The method includes performing a conversion between a video and a coded representation of the video, wherein the coded representation conforms to a format rule, wherein the format rule specifies that a relationship between a width of a video picture and a size of a coding tree unit controls signaling of information used for deriving a number of tile columns or rows in the video picture.

[0032] In another example aspect, another video processing method is disclosed. The method includes performing a conversion between a video comprising one or more video pictures and a coded representation of the video, wherein the coded representation conforms to a format rule, wherein the format rule specifies that a tile layout information is included in the coded representation for a video picture that comprises uniform spacing tiles and non-uniform spacing tiles.

[0033] In yet another example aspect, a video encoder apparatus is disclosed. The video encoder comprises a processor configured to implement above-described methods.

[0034] In yet another example aspect, a video decoder apparatus is disclosed. The video decoder comprises a processor configured to implement above-described methods.

[0035] In yet another example aspect, a computer readable medium having code stored thereon is disclosed. The code embodies one of the methods described herein in the form of processor-executable code.

[0036] These, and other, features are described throughout the present document.

BRIEF DESCRIPTION OF DRAWINGS

[0037] FIG. 1 shows an example of raster-scan slice partitioning of a picture, where the picture is divided into 12 tiles and 3 raster-scan slices.

[0038] FIG. 2 shows an example of rectangular slice partitioning of a picture, where the picture is divided into 24 tiles (6 tile columns and 4 tile rows) and 9 rectangular slices.

[0039] FIG. 3 shows an example of a picture partitioned into tiles and rectangular slices, where the picture is divided into 4 tiles (2 tile columns and 2 tile rows) and 4 rectangular slices.

[0040] FIG. 4 shows a picture that is partitioned into 15 tiles, 24 slices and 24 subpictures.

[0041] FIG. 5 shows a nominal vertical and horizontal locations of 4:2:2 luma and chroma samples in a picture.

[0042] FIG. 6 shows an example of picture partitioning. Blue lines represent boundaries of tiles; green lines represent boundaries of slices and Red dashed lines represent boundaries of subpictures. The picture-level indices, decoding order indices, subpicture-level indices of the four slices and the indices of subpictures and tiles are indicated in the figure.

[0043] FIG. 7 is a block diagram of an example video processing system.

[0044] FIG. 8 is a block diagram of a video processing apparatus.

[0045] FIG. 9 is a flowchart for an example method of video processing.

[0046] FIG. 10 is a block diagram that illustrates a video coding system in accordance with some embodiments of the present disclosure.

[0047] FIG. 11 is a block diagram that illustrates an encoder in accordance with some embodiments of the present disclosure.

[0048] FIG. 12 is a block diagram that illustrates a decoder in accordance with some embodiments of the present disclosure.

[0049] FIG. 13 is flowchart representation of a method for video processing in accordance with the present technology.

[0050] FIG. 14 is flowchart representation of another method for video processing in accordance with the present technology.

[0051] FIG. 15 is flowchart representation of another method for video processing in accordance with the present technology.

[0052] FIG. 16 is flowchart representation of another method for video processing in accordance with the present technology.

[0053] FIG. 17 is flowchart representation of another method for video processing in accordance with the present technology.

[0054] FIG. 18 is flowchart representation of another method for video processing in accordance with the present technology.

[0055] FIG. 19 is flowchart representation of another method for video processing in accordance with the present technology.

[0056] FIG. 20 is flowchart representation of another method for video processing in accordance with the present technology.

[0057] FIG. 21 is flowchart representation of another method for video processing in accordance with the present technology.

[0058] FIG. 22 is flowchart representation of another method for video processing in accordance with the present technology.

[0059] FIG. 23 is flowchart representation of another method for video processing in accordance with the present technology.

[0060] FIG. 24 is flowchart representation of another method for video processing in accordance with the present technology.

[0061] FIG. 25 is flowchart representation of another method for video processing in accordance with the present technology.

[0062] FIG. 26 is flowchart representation of another method for video processing in accordance with the present technology.

[0063] FIG. 27 is flowchart representation of another method for video processing in accordance with the present technology.

[0064] FIG. 28 is flowchart representation of another method for video processing in accordance with the present technology.

[0065] FIG. 29 is flowchart representation of another method for video processing in accordance with the present technology.

[0066] FIG. 30 is flowchart representation of another method for video processing in accordance with the present technology.

[0067] FIG. 31 is flowchart representation of another method for video processing in accordance with the present technology.

DETAILED DESCRIPTION

[0068] Section headings are used in the present document for ease of understanding and do not limit the applicability of techniques and embodiments disclosed in each section only to that section. Furthermore, H.266 terminology is used in some description only for ease of understanding and not for limiting scope of the disclosed techniques. As such, the techniques described herein are applicable to other video codec protocols and designs also.

1. Overview

[0069] This document is related to video coding technologies. Specifically, it is about signaling of subpictures, tiles, and slices. The ideas may be applied individually or in various combination, to any video coding standard or non-standard video codec that supports multi-layer video coding, e.g., the being-developed Versatile Video Coding (VVC).

2. Abbreviations

APS	Adaptation Parameter Set
AU	Access Unit
AUD	Access Unit Delimiter
AVC	Advanced Video Coding
CLVS	Coded Layer Video Sequence
CPB	Coded Picture Buffer
CRA	Clean Random Access

CTU	Coding Tree Unit
CVS	Coded Video Sequence
DPB	Decoded Picture Buffer
DPS	Decoding Parameter Set
EOB	End Of Bitstream
EOS	End Of Sequence
GDR	Gradual Decoding Refresh
HEVC	High Efficiency Video Coding
HRD	Hypothetical Reference Decoder
IDR	Instantaneous Decoding Refresh
JEM	Joint Exploration Model
MCTS	Motion-Constrained Tile Sets
NAL	Network Abstraction Layer
OLS	Output Layer Set
PH	Picture Header
PPS	Picture Parameter Set
PTL	Profile, Tier and Level
PU	Picture Unit
RBSP	Raw Byte Sequence Payload
SEI	Supplemental Enhancement Information
SPS	Sequence Parameter Set
SVC	Scalable Video Coding
VCL	Video Coding Layer
VPS	Video Parameter Set
VTM	VVC Test Model
VUI	Video Usability Information
VVC	Versatile Video Coding

3. Initial discussion

[0070] Video coding standards have evolved primarily through the development of the well-known ITU-T and ISO/IEC standards. The ITU-T produced H.261 and H.263, ISO/IEC produced MPEG-1 and MPEG-4 Visual, and the two organizations jointly produced the H.262/MPEG-2 Video and H.264/MPEG-4 Advanced Video Coding (AVC) and H.265/HEVC standards. Since H.262, the video coding standards are based on the hybrid video coding structure wherein temporal prediction plus transform coding are utilized. To explore the future video coding technologies beyond HEVC, the Joint Video Exploration Team (JVET) was founded by VCEG and MPEG jointly in 2015. Since then, many new methods have been adopted by JVET and put into the reference software named Joint Exploration Model (JEM). The JVET meeting is concurrently held once every quarter, and the new coding standard is targeting at 50% bitrate reduction as compared to HEVC. The new video coding standard was officially named as Versatile Video Coding (VVC) in the April 2018 JVET meeting, and the first version of VVC test model (VTM) was released at that time. As there are continuous effort contributing to VVC standardization, new coding techniques are being adopted to the VVC standard in every JVET meeting. The VVC working draft and test model VTM are then updated after every meeting. The VVC project is now aiming for technical completion (FDIS) at the July 2020 meeting.

3.1. Picture partitioning schemes in HEVC

[0071] HEVC includes four different picture partitioning schemes, namely regular slices, dependent slices, tiles, and Wavefront Parallel Processing (WPP), which may be applied for Maximum Transfer Unit (MTU) size matching, parallel processing, and reduced end-to-end delay.

[0072] Regular slices are similar as in H.264/AVC. Each regular slice is encapsulated in its own NAL unit, and in-picture prediction (intra sample prediction, motion information prediction, coding mode prediction) and entropy coding dependency across slice boundaries are disabled. Thus, a regular slice can be reconstructed independently from other regular slices within the same picture (though there may still have interdependencies due to loop filtering operations).

[0073] The regular slice is the only tool that can be used for parallelization that is also available, in virtually identical form, in H.264/AVC. Regular slice-based parallelization does not require

much inter-processor or inter-core communication (except for inter-processor or inter-core data sharing for motion compensation when decoding a predictively coded picture, which is typically much heavier than inter-processor or inter-core data sharing due to in-picture prediction).

However, for the same reason, the use of regular slices can incur substantial coding overhead due to the bit cost of the slice header and due to the lack of prediction across the slice boundaries.

Further, regular slices (in contrast to the other tools mentioned below) also serve as the key mechanism for bitstream partitioning to match MTU size requirements, due to the in-picture independence of regular slices and that each regular slice is encapsulated in its own NAL unit. In many cases, the goal of parallelization and the goal of MTU size matching place contradicting demands to the slice layout in a picture. The realization of this situation led to the development of the parallelization tools mentioned below.

[0074] Dependent slices have short slice headers and allow partitioning of the bitstream at treeblock boundaries without breaking any in-picture prediction. Basically, dependent slices provide fragmentation of regular slices into multiple NAL units, to provide reduced end-to-end delay by allowing a part of a regular slice to be sent out before the encoding of the entire regular slice is finished.

[0075] In WPP, the picture is partitioned into single rows of coding tree blocks (CTBs). Entropy decoding and prediction are allowed to use data from CTBs in other partitions. Parallel processing is possible through parallel decoding of CTB rows, where the start of the decoding of a CTB row is delayed by two CTBs, so to ensure that data related to a CTB above and to the right of the subject CTB is available before the subject CTB is being decoded. Using this staggered start (which appears like a wavefront when represented graphically), parallelization is possible with up to as many processors/cores as the picture contains CTB rows. Because in-picture prediction between neighboring treeblock rows within a picture is permitted, the required inter-processor/inter-core communication to enable in-picture prediction can be substantial. The WPP partitioning does not result in the production of additional NAL units compared to when it is not applied, thus WPP is not a tool for MTU size matching. However, if MTU size matching is required, regular slices can be used with WPP, with certain coding overhead.

[0076] Tiles define horizontal and vertical boundaries that partition a picture into tile columns and rows. Tile column runs from the top of a picture to the bottom of the picture. Likewise, tile

row runs from the left of the picture to the right of the picture. The number of tiles in a picture can be derived simply as number of tile columns multiply by number of tile rows.

[0077] The scan order of CTBs is changed to be local within a tile (in the order of a CTB raster scan of a tile), before decoding the top-left CTB of the next tile in the order of tile raster scan of a picture. Similar to regular slices, tiles break in-picture prediction dependencies as well as entropy decoding dependencies. However, they do not need to be included into individual NAL units (same as WPP in this regard); hence tiles cannot be used for MTU size matching. Each tile can be processed by one processor/core, and the inter-processor/inter-core communication required for in-picture prediction between processing units decoding neighboring tiles is limited to conveying the shared slice header in cases a slice is spanning more than one tile, and loop filtering related sharing of reconstructed samples and metadata. When more than one tile or WPP segment is included in a slice, the entry point byte offset for each tile or WPP segment other than the first one in the slice is signaled in the slice header.

[0078] For simplicity, restrictions on the application of the four different picture partitioning schemes have been specified in HEVC. A given coded video sequence cannot include both tiles and wavefronts for most of the profiles specified in HEVC. For each slice and tile, either or both of the following conditions must be fulfilled: 1) all coded treeblocks in a slice belong to the same tile; 2) all coded treeblocks in a tile belong to the same slice. Finally, a wavefront segment contains exactly one CTB row, and when WPP is in use, if a slice starts within a CTB row, it must end in the same CTB row.

[0079] A recent amendment to HEVC is specified in the JCT-VC output document JCTVC-AC1005, J. Boyce, A. Ramasubramonian, R. Skupin, G. J. Sullivan, A. Tourapis, Y.-K. Wang (editors), "HEVC Additional Supplemental Enhancement Information (Draft 4)," Oct. 24, 2017, publicly available herein: http://phenix.int-evry.fr/jct/doc_end_user/documents/29_Macau/wg11/JCTVC-AC1005-v2.zip. With this amendment included, HEVC specifies three MCTS-related SEI (supplemental enhancement information) messages, namely temporal MCTSs SEI message, MCTSs extraction information set SEI message, and MCTSs extraction information nesting SEI message.

[0080] The temporal MCTSs SEI message indicates existence of MCTSs in the bitstream and signals the MCTSs. For each MCTS, motion vectors are restricted to point to full-sample

locations inside the MCTS and to fractional-sample locations that require only full-sample locations inside the MCTS for interpolation, and the usage of motion vector candidates for temporal motion vector prediction derived from blocks outside the MCTS is disallowed. This way, each MCTS may be independently decoded without the existence of tiles not included in the MCTS.

[0081] The MCTSs extraction information sets SEI message provides supplemental information that can be used in the MCTS sub-bitstream extraction (specified as part of the semantics of the SEI message) to generate a conforming bitstream for an MCTS set. The information consists of a number of extraction information sets, each defining a number of MCTS sets and containing RBSP bytes of the replacement VPSs, SPSs, and PPSs to be used during the MCTS sub-bitstream extraction process. When extracting a sub-bitstream according to the MCTS sub-bitstream extraction process, parameter sets (VPSs, SPSs, and PPSs) need to be rewritten or replaced, slice headers need to be slightly updated because one or all of the slice address related syntax elements (including `first_slice_segment_in_pic_flag` and `slice_segment_address`) typically would need to have different values.

3.2. Partitioning of pictures in VVC

[0082] In VVC, A picture is divided into one or more tile rows and one or more tile columns. A tile is a sequence of CTUs that covers a rectangular region of a picture. The CTUs in a tile are scanned in raster scan order within that tile.

[0083] A slice consists of an integer number of complete tiles or an integer number of consecutive complete CTU rows within a tile of a picture.

[0084] Two modes of slices are supported, namely the raster-scan slice mode and the rectangular slice mode. In the raster-scan slice mode, a slice contains a sequence of complete tiles in a tile raster scan of a picture. In the rectangular slice mode, a slice contains either a number of complete tiles that collectively form a rectangular region of the picture or a number of consecutive complete CTU rows of one tile that collectively form a rectangular region of the picture. Tiles within a rectangular slice are scanned in tile raster scan order within the rectangular region corresponding to that slice.

[0085] A subpicture contains one or more slices that collectively cover a rectangular region of a picture.

[0086] FIG. 1 shows an example of raster-scan slice partitioning of a picture, where the picture is divided into 12 tiles and 3 raster-scan slices.

[0087] FIG. 2 shows an example of rectangular slice partitioning of a picture, where the picture is divided into 24 tiles (6 tile columns and 4 tile rows) and 9 rectangular slices.

[0088] FIG. 3 shows an example of a picture partitioned into tiles and rectangular slices, where the picture is divided into 4 tiles (2 tile columns and 2 tile rows) and 4 rectangular slices.

[0089] FIG. 4 shows an example of subpicture partitioning of a picture, where a picture is partitioned into 18 tiles, 12 on the left-hand side each covering one slice of 4 by 4 CTUs and 6 tiles on the right-hand side each covering 2 vertically-stacked slices of 2 by 2 CTUs, altogether resulting in 24 slices and 24 subpictures of varying dimensions (each slice is a subpicture).

3.3. Signalling of SPS/PPS/Picture header/Slice header in VVC

7.3.2.3 Sequence parameter set RBSP syntax

seq_parameter_set_rbsp() {	Descriptor
sps_seq_parameter_set_id	u(4)
sps_video_parameter_set_id	u(4)
sps_max_sublayers_minus1	u(3)
sps_reserved_zero_4bits	u(4)
sps_ptl_dpb_hrd_params_present_flag	u(1)
if(sps_ptl_dpb_hrd_params_present_flag)	
profile_tier_level(1, sps_max_sublayers_minus1)	
gdr_enabled_flag	u(1)
chroma_format_idc	u(2)
if(chroma_format_idc == 3)	
separate_colour_plane_flag	u(1)
res_change_in_clvs_allowed_flag	u(1)
pic_width_max_in_luma_samples	ue(v)
pic_height_max_in_luma_samples	ue(v)
sps_conformance_window_flag	u(1)
if(sps_conformance_window_flag) {	
sps_conf_win_left_offset	ue(v)
sps_conf_win_right_offset	ue(v)
sps_conf_win_top_offset	ue(v)
sps_conf_win_bottom_offset	ue(v)

}	
sps_log2_ctu_size_minus5	u(2)
subpic_info_present_flag	u(1)
if(subpic_info_present_flag) {	
sps_num_subpics_minus1	ue(v)
sps_independent_subpics_flag	u(1)
for(i = 0; sps_num_subpics_minus1 > 0 && i <= sps_num_subpics_minus1; i++) {	
if(i > 0 && pic_width_max_in_luma_samples > CtbSizeY)	
subpic_ctu_top_left_x[i]	u(v)
if(i > 0 && pic_height_max_in_luma_samples > CtbSizeY) {	
subpic_ctu_top_left_y[i]	u(v)
if(i < sps_num_subpics_minus1 && pic_width_max_in_luma_samples > CtbSizeY)	
subpic_width_minus1[i]	u(v)
if(i < sps_num_subpics_minus1 && pic_height_max_in_luma_samples > CtbSizeY)	
subpic_height_minus1[i]	u(v)
if(!sps_independent_subpics_flag) {	
subpic_treated_as_pic_flag[i]	u(1)
loop_filter_across_subpic_enabled_flag[i]	u(1)
}	
}	
sps_subpic_id_len_minus1	ue(v)
subpic_id_mapping_explicitly_signalled_flag	u(1)
if(subpic_id_mapping_explicitly_signalled_flag) {	
subpic_id_mapping_in_sps_flag	u(1)
if(subpic_id_mapping_in_sps_flag)	
for(i = 0; i <= sps_num_subpics_minus1; i++)	
sps_subpic_id[i]	u(v)
}	
}	
bit_depth_minus8	ue(v)
sps_entropy_coding_sync_enabled_flag	u(1)
if(sps_entropy_coding_sync_enabled_flag)	
sps_wpp_entry_point_offsets_present_flag	u(1)

sps_weighted_pred_flag	u(1)
sps_weighted_bipred_flag	u(1)
log2_max_pic_order_cnt_lsb_minus4	u(4)
sps_poc_msb_flag	u(1)
if(sps_poc_msb_flag)	
poc_msb_len_minus1	ue(v)
num_extra_ph_bits_bytes	u(2)
extra_ph_bits_struct(num_extra_ph_bits_bytes)	
num_extra_sh_bits_bytes	u(2)
extra_sh_bits_struct(num_extra_sh_bits_bytes)	
if(sps_max_sublayers_minus1 > 0)	
sps_sublayer_dpb_params_flag	u(1)
if(sps_ptl_dpb_hrd_params_present_flag)	
dpb_parameters(sps_max_sublayers_minus1, sps_sublayer_dpb_params_flag)	
long_term_ref_pics_flag	u(1)
inter_layer_ref_pics_present_flag	u(1)
sps_idr_rpl_present_flag	u(1)
rpl1_same_as_rpl0_flag	u(1)
for(i = 0; i < !rpl1_same_as_rpl0_flag ? 2 : 1; i++) {	
num_ref_pic_lists_in_sps[i]	ue(v)
for(j = 0; j < num_ref_pic_lists_in_sps[i]; j++)	
ref_pic_list_struct(i, j)	
}	
if(ChromaArrayType != 0)	
qtbtt_dual_tree_intra_flag	u(1)
log2_min_luma_coding_block_size_minus2	ue(v)
partition_constraints_override_enabled_flag	u(1)
sps_log2_diff_min_qt_min_cb_intra_slice_luma	ue(v)
sps_max_mtt_hierarchy_depth_intra_slice_luma	ue(v)
if(sps_max_mtt_hierarchy_depth_intra_slice_luma != 0) {	
sps_log2_diff_max_bt_min_qt_intra_slice_luma	ue(v)
sps_log2_diff_max_tt_min_qt_intra_slice_luma	ue(v)
}	
sps_log2_diff_min_qt_min_cb_inter_slice	ue(v)
sps_max_mtt_hierarchy_depth_inter_slice	ue(v)

if(sps_max_mtt_hierarchy_depth_inter_slice != 0) {	
sps_log2_diff_max_bt_min_qt_inter_slice	ue(v)
sps_log2_diff_max_tt_min_qt_inter_slice	ue(v)
}	
if(qtbtt_dual_tree_intra_flag) {	
sps_log2_diff_min_qt_min_cb_intra_slice_chroma	ue(v)
sps_max_mtt_hierarchy_depth_intra_slice_chroma	ue(v)
if(sps_max_mtt_hierarchy_depth_intra_slice_chroma != 0) {	
sps_log2_diff_max_bt_min_qt_intra_slice_chroma	ue(v)
sps_log2_diff_max_tt_min_qt_intra_slice_chroma	ue(v)
}	
}	
sps_max_luma_transform_size_64_flag	u(1)
if(ChromaArrayType != 0) {	
sps_joint_cbr_enabled_flag	u(1)
same_qp_table_for_chroma	u(1)
numQpTables = same_qp_table_for_chroma ? 1 : (sps_joint_cbr_enabled_flag ? 3 : 2)	
for(i = 0; i < numQpTables; i++) {	
qp_table_start_minus26[i]	se(v)
num_points_in_qp_table_minus1[i]	ue(v)
for(j = 0; j <= num_points_in_qp_table_minus1[i]; j++) {	
delta_qp_in_val_minus1[i][j]	ue(v)
delta_qp_diff_val[i][j]	ue(v)
}	
}	
}	
sps_sao_enabled_flag	u(1)
sps_alf_enabled_flag	u(1)
if(sps_alf_enabled_flag && ChromaArrayType != 0)	
sps_ccalf_enabled_flag	u(1)
sps_transform_skip_enabled_flag	u(1)
if(sps_transform_skip_enabled_flag) {	
log2_transform_skip_max_size_minus2	ue(v)
sps_bdpcm_enabled_flag	u(1)
}	

sps_ref_wraparound_enabled_flag	u(1)
sps_temporal_mvp_enabled_flag	u(1)
if(sps_temporal_mvp_enabled_flag)	
sps_sbtmvp_enabled_flag	u(1)
sps_amvr_enabled_flag	u(1)
sps_bdof_enabled_flag	u(1)
if(sps_bdof_enabled_flag)	
sps_bdof_pic_present_flag	u(1)
sps_smvd_enabled_flag	u(1)
sps_dmvr_enabled_flag	u(1)
if(sps_dmvr_enabled_flag)	
sps_dmvr_pic_present_flag	u(1)
sps_mmvd_enabled_flag	u(1)
sps_isp_enabled_flag	u(1)
sps_mrl_enabled_flag	u(1)
sps_mip_enabled_flag	u(1)
if(ChromaArrayType != 0)	
sps_cclm_enabled_flag	u(1)
if(chroma_format_idc == 1) {	
sps_chroma_horizontal_collocated_flag	u(1)
sps_chroma_vertical_collocated_flag	u(1)
}	
sps_mts_enabled_flag	u(1)
if(sps_mts_enabled_flag) {	
sps_explicit_mts_intra_enabled_flag	u(1)
sps_explicit_mts_inter_enabled_flag	u(1)
}	
six_minus_max_num_merge_cand	ue(v)
sps_sbt_enabled_flag	u(1)
sps_affine_enabled_flag	u(1)
if(sps_affine_enabled_flag) {	
five_minus_max_num_subblock_merge_cand	ue(v)
sps_affine_type_flag	u(1)
if(sps_amvr_enabled_flag)	
sps_affine_amvr_enabled_flag	u(1)

sps_affine_prof_enabled_flag	u(1)
if(sps_affine_prof_enabled_flag)	
sps_prof_pic_present_flag	u(1)
}	
sps_palette_enabled_flag	u(1)
if(ChromaArrayType == 3 && !sps_max_luma_transform_size_64_flag)	
sps_act_enabled_flag	u(1)
if(sps_transform_skip_enabled_flag sps_palette_enabled_flag)	
min_qp_prime_ts_minus4	ue(v)
sps_bcw_enabled_flag	u(1)
sps_ibc_enabled_flag	u(1)
if(sps_ibc_enabled_flag)	
six_minus_max_num_ibc_merge_cand	ue(v)
sps_ciip_enabled_flag	u(1)
if(sps_mmvd_enabled_flag)	
sps_fpel_mmvd_enabled_flag	u(1)
if(MaxNumMergeCand >= 2) {	
sps_gpm_enabled_flag	u(1)
if(sps_gpm_enabled_flag && MaxNumMergeCand >= 3)	
max_num_merge_cand_minus_max_num_gpm_cand	ue(v)
}	
sps_lmcs_enabled_flag	u(1)
sps_lfst_enabled_flag	u(1)
sps_ladf_enabled_flag	u(1)
if(sps_ladf_enabled_flag) {	
sps_num_ladf_intervals_minus2	u(2)
sps_ladf_lowest_interval_qp_offset	se(v)
for(i = 0; i < sps_num_ladf_intervals_minus2 + 1; i++) {	
sps_ladf_qp_offset[i]	se(v)
sps_ladf_delta_threshold_minus1[i]	ue(v)
}	
}	
log2_parallel_merge_level_minus2	ue(v)
sps_scaling_list_enabled_flag	u(1)
sps_dep_quant_enabled_flag	u(1)

if(!sps_dep_quant_enabled_flag)	
sps_sign_data_hiding_enabled_flag	u(1)
sps_virtual_boundaries_enabled_flag	u(1)
if(sps_virtual_boundaries_enabled_flag) {	
sps_virtual_boundaries_present_flag	u(1)
if(sps_virtual_boundaries_present_flag) {	
sps_num_ver_virtual_boundaries	u(2)
for(i = 0; i < sps_num_ver_virtual_boundaries; i++)	
sps_virtual_boundaries_pos_x[i]	u(13)
sps_num_hor_virtual_boundaries	u(2)
for(i = 0; i < sps_num_hor_virtual_boundaries; i++)	
sps_virtual_boundaries_pos_y[i]	u(13)
}	
}	
if(sps_ptl_dpb_hrd_params_present_flag) {	
sps_general_hrd_params_present_flag	u(1)
if(sps_general_hrd_params_present_flag) {	
general_hrd_parameters()	
if(sps_max_sublayers_minus1 > 0)	
sps_sublayer_cpb_params_present_flag	u(1)
firstSubLayer = sps_sublayer_cpb_params_present_flag ? 0 : sps_max_sublayers_minus1	
ols_hrd_parameters(firstSubLayer, sps_max_sublayers_minus1)	
}	
}	
field_seq_flag	u(1)
vui_parameters_present_flag	u(1)
if(vui_parameters_present_flag)	
vui_parameters() /* Specified in ITU-T H.266 ISO/IEC 23002-7 */	
sps_extension_flag	u(1)
if(sps_extension_flag)	
while(more_rbsp_data())	
sps_extension_data_flag	u(1)

rbsp_trailing_bits()	
}	

7.3.2.4 Picture parameter set RBSP syntax

pic_parameter_set_rbsp() {	Descriptor
pps_pic_parameter_set_id	ue(v)
pps_seq_parameter_set_id	u(4)
mixed_nalu_types_in_pic_flag	u(1)
pic_width_in_luma_samples	ue(v)
pic_height_in_luma_samples	ue(v)
pps_conformance_window_flag	u(1)
if(pps_conformance_window_flag) {	
pps_conf_win_left_offset	ue(v)
pps_conf_win_right_offset	ue(v)
pps_conf_win_top_offset	ue(v)
pps_conf_win_bottom_offset	ue(v)
}	
scaling_window_explicit_signalling_flag	u(1)
if(scaling_window_explicit_signalling_flag) {	
scaling_win_left_offset	ue(v)
scaling_win_right_offset	ue(v)
scaling_win_top_offset	ue(v)
scaling_win_bottom_offset	ue(v)
}	
output_flag_present_flag	u(1)
subpic_id_mapping_in_pps_flag	u(1)
if(subpic_id_mapping_in_pps_flag) {	
pps_num_subpics_minus1	ue(v)
pps_subpic_id_len_minus1	ue(v)
for(i = 0; i <= pps_num_subpic_minus1; i++)	
pps_subpic_id[i]	u(v)
}	
no_pic_partition_flag	u(1)
if(!no_pic_partition_flag) {	
pps_log2_ctu_size_minus5	u(2)
num_exp_tile_columns_minus1	ue(v)

num_exp_tile_rows_minus1	ue(v)
for(i = 0; i <= num_exp_tile_columns_minus1; i++)	
tile_column_width_minus1[i]	ue(v)
for(i = 0; i <= num_exp_tile_rows_minus1; i++)	
tile_row_height_minus1[i]	ue(v)
if(NumTilesInPic > 1)	
rect_slice_flag	u(1)
if(rect_slice_flag)	
single_slice_per_subpic_flag	u(1)
if(rect_slice_flag && !single_slice_per_subpic_flag) {	
num_slices_in_pic_minus1	ue(v)
if(num_slices_in_pic_minus1 > 0)	
tile_idx_delta_present_flag	u(1)
for(i = 0; i < num_slices_in_pic_minus1; i++) {	
if(NumTileColumns > 1)	
slice_width_in_tiles_minus1[i]	ue(v)
if(NumTileRows > 1 && (tile_idx_delta_present_flag tileIdx % NumTileColumns == 0))	
slice_height_in_tiles_minus1[i]	ue(v)
if(slice_width_in_tiles_minus1[i] == 0 && slice_height_in_tiles_minus1[i] == 0 && RowHeight[SliceTopLeftTileIdx[i] / NumTileColumns] > 1) {	
num_exp_slices_in_tile[i]	ue(v)
numExpSlicesInTile = num_exp_slices_in_tile[i]	
for(j = 0; j < numExpSlicesInTile; j++)	
exp_slice_height_in_ctus_minus1[j]	ue(v)
i += NumSlicesInTile[i]	
}	
if(tile_idx_delta_present_flag && i < num_slices_in_pic_minus1)	
tile_idx_delta[i]	se(v)
}	
}	
loop_filter_across_tiles_enabled_flag	u(1)
loop_filter_across_slices_enabled_flag	u(1)
}	

cabac_init_present_flag	u(1)
for(i = 0; i < 2; i++)	
num_ref_idx_default_active_minus1[i]	ue(v)
rpl1_idx_present_flag	u(1)
init_qp_minus26	se(v)
cu_qp_delta_enabled_flag	u(1)
pps_chroma_tool_offsets_present_flag	u(1)
if(pps_chroma_tool_offsets_present_flag) {	
pps_cb_qp_offset	se(v)
pps_cr_qp_offset	se(v)
pps_joint_cbr_qp_offset_present_flag	u(1)
if(pps_joint_cbr_qp_offset_present_flag)	
pps_joint_cbr_qp_offset_value	se(v)
pps_slice_chroma_qp_offsets_present_flag	u(1)
pps_cu_chroma_qp_offset_list_enabled_flag	u(1)
}	
if(pps_cu_chroma_qp_offset_list_enabled_flag) {	
chroma_qp_offset_list_len_minus1	ue(v)
for(i = 0; i <= chroma_qp_offset_list_len_minus1; i++) {	
cb_qp_offset_list[i]	se(v)
cr_qp_offset_list[i]	se(v)
if(pps_joint_cbr_qp_offset_present_flag)	
joint_cbr_qp_offset_list[i]	se(v)
}	
}	
pps_weighted_pred_flag	u(1)
pps_weighted_bipred_flag	u(1)
deblocking_filter_control_present_flag	u(1)
if(deblocking_filter_control_present_flag) {	
deblocking_filter_override_enabled_flag	u(1)
pps_deblocking_filter_disabled_flag	u(1)
if(!pps_deblocking_filter_disabled_flag) {	
pps_beta_offset_div2	se(v)
pps_tc_offset_div2	se(v)
pps_cb_beta_offset_div2	se(v)

pps_cb_tc_offset_div2	se(v)
pps_cr_beta_offset_div2	se(v)
pps_cr_tc_offset_div2	se(v)
}	
}	
rpl_info_in_ph_flag	u(1)
if(deblocking_filter_override_enabled_flag)	
dbf_info_in_ph_flag	u(1)
sao_info_in_ph_flag	u(1)
alf_info_in_ph_flag	u(1)
if((pps_weighted_pred_flag pps_weighted_bipred_flag) && rpl_present_in_ph_flag)	
wp_info_in_ph_flag	u(1)
qp_delta_info_in_ph_flag	u(1)
pps_ref_wraparound_enabled_flag	u(1)
if(pps_ref_wraparound_enabled_flag)	
pps_ref_wraparound_offset	ue(v)
picture_header_extension_present_flag	u(1)
slice_header_extension_present_flag	u(1)
pps_extension_flag	u(1)
if(pps_extension_flag)	
while(more_rbsp_data())	
pps_extension_data_flag	u(1)
rbp_trailing_bits()	
}	

7.3.2.7 Picture header structure syntax

picture_header_structure() {	Descriptor
gdr_or_irap_pic_flag	u(1)
if(gdr_or_irap_pic_flag)	
gdr_pic_flag	u(1)
ph_inter_slice_allowed_flag	u(1)
if(ph_inter_slice_allowed_flag)	
ph_intra_slice_allowed_flag	u(1)
non_reference_picture_flag	u(1)
ph_pic_parameter_set_id	ue(v)
ph_pic_order_cnt_lsb	u(v)

if(gdr_or_irap_pic_flag)	
no_output_of_prior_pics_flag	u(1)
if(gdr_pic_flag)	
recovery_poc_cnt	ue(v)
for(i = 0; i < NumExtraPhBits; i++)	
ph_extra_bit[i]	u(1)
if(sps_poc_msb_flag) {	
ph_poc_msb_present_flag	u(1)
if(ph_poc_msb_present_flag)	
poc_msb_val	u(v)
}	
if(sps_alf_enabled_flag && alf_info_in_ph_flag) {	
ph_alf_enabled_flag	u(1)
if(ph_alf_enabled_flag) {	
ph_num_alf_aps_ids_luma	u(3)
for(i = 0; i < ph_num_alf_aps_ids_luma; i++)	
ph_alf_aps_id_luma[i]	u(3)
if(ChromaArrayType != 0)	
ph_alf_chroma_idc	u(2)
if(ph_alf_chroma_idc)	
ph_alf_aps_id_chroma	u(3)
if(sps_ccalf_enabled_flag) {	
ph_cc_alf_cb_enabled_flag	u(1)
if(ph_cc_alf_cb_enabled_flag)	
ph_cc_alf_cb_aps_id	u(3)
ph_cc_alf_cr_enabled_flag	u(1)
if(ph_cc_alf_cr_enabled_flag)	
ph_cc_alf_cr_aps_id	u(3)
}	
}	
}	
if(sps_lmcs_enabled_flag) {	
ph_lmcs_enabled_flag	u(1)
if(ph_lmcs_enabled_flag) {	
ph_lmcs_aps_id	u(2)

if(ChromaArrayType != 0)	
ph_chroma_residual_scale_flag	u(1)
}	
}	
if(sps_scaling_list_enabled_flag) {	
ph_scaling_list_present_flag	u(1)
if(ph_scaling_list_present_flag)	
ph_scaling_list_aps_id	u(3)
}	
if(sps_virtual_boundaries_enabled_flag && !sps_virtual_boundaries_present_flag) {	
ph_virtual_boundaries_present_flag	u(1)
if(ph_virtual_boundaries_present_flag) {	
ph_num_ver_virtual_boundaries	u(2)
for(i = 0; i < ph_num_ver_virtual_boundaries; i++)	
ph_virtual_boundaries_pos_x[i]	u(13)
ph_num_hor_virtual_boundaries	u(2)
for(i = 0; i < ph_num_hor_virtual_boundaries; i++)	
ph_virtual_boundaries_pos_y[i]	u(13)
}	
}	
if(output_flag_present_flag)	
pic_output_flag	u(1)
if(rpl_info_in_ph_flag)	
ref_pic_lists()	
if(partition_constraints_override_enabled_flag)	
partition_constraints_override_flag	u(1)
if(ph_intra_slice_allowed_flag) {	
if(partition_constraints_override_flag) {	
ph_log2_diff_min_qt_min_cb_intra_slice_luma	ue(v)
ph_max_mtt_hierarchy_depth_intra_slice_luma	ue(v)
if(ph_max_mtt_hierarchy_depth_intra_slice_luma != 0) {	
ph_log2_diff_max_bt_min_qt_intra_slice_luma	ue(v)
ph_log2_diff_max_tt_min_qt_intra_slice_luma	ue(v)
}	
if(qtbtt_dual_tree_intra_flag) {	

ph_log2_diff_min_qt_min_cb_intra_slice_chroma	ue(v)
ph_max_mtt_hierarchy_depth_intra_slice_chroma	ue(v)
if(ph_max_mtt_hierarchy_depth_intra_slice_chroma != 0) {	
ph_log2_diff_max_bt_min_qt_intra_slice_chroma	ue(v)
ph_log2_diff_max_tt_min_qt_intra_slice_chroma	ue(v)
}	
}	
}	
if(cu_qp_delta_enabled_flag)	
ph_cu_qp_delta_subdiv_intra_slice	ue(v)
if(pps_cu_chroma_qp_offset_list_enabled_flag)	
ph_cu_chroma_qp_offset_subdiv_intra_slice	ue(v)
}	
if(ph_inter_slice_allowed_flag) {	
if(partition_constraints_override_flag) {	
ph_log2_diff_min_qt_min_cb_inter_slice	ue(v)
ph_max_mtt_hierarchy_depth_inter_slice	ue(v)
if(ph_max_mtt_hierarchy_depth_inter_slice != 0) {	
ph_log2_diff_max_bt_min_qt_inter_slice	ue(v)
ph_log2_diff_max_tt_min_qt_inter_slice	ue(v)
}	
}	
if(cu_qp_delta_enabled_flag)	
ph_cu_qp_delta_subdiv_inter_slice	ue(v)
if(pps_cu_chroma_qp_offset_list_enabled_flag)	
ph_cu_chroma_qp_offset_subdiv_inter_slice	ue(v)
if(sps_temporal_mvp_enabled_flag) {	
ph_temporal_mvp_enabled_flag	u(1)
if(ph_temporal_mvp_enabled_flag && rpl_info_in_ph_flag) {	
ph_collocated_from_l0_flag	u(1)
if((ph_collocated_from_l0_flag && num_ref_entries[0][PicRplsIdx[0]] > 1) (!ph_collocated_from_l0_flag && num_ref_entries[1][PicRplsIdx[1]] > 1))	
ph_collocated_ref_idx	ue(v)

}	
}	
mvd_l1_zero_flag	u(1)
if(sps_fpel_mmvd_enabled_flag)	
ph_fpel_mmvd_enabled_flag	u(1)
if(sps_bdof_pic_present_flag)	
ph_disable_bdof_flag	u(1)
if(sps_dmvr_pic_present_flag)	
ph_disable_dmvr_flag	u(1)
if(sps_prof_pic_present_flag)	
ph_disable_prof_flag	u(1)
if((pps_weighted_pred_flag pps_weighted_bipred_flag) && wp_info_in_ph_flag)	
pred_weight_table()	
}	
if(qp_delta_info_in_ph_flag)	
ph_qp_delta	se(v)
if(sps_joint_cbr_enabled_flag)	
ph_joint_cbr_sign_flag	u(1)
if(sps_sao_enabled_flag && sao_info_in_ph_flag) {	
ph_sao_luma_enabled_flag	u(1)
if(ChromaArrayType != 0)	
ph_sao_chroma_enabled_flag	u(1)
}	
if(sps_dep_quant_enabled_flag)	
ph_dep_quant_enabled_flag	u(1)
if(sps_sign_data_hiding_enabled_flag && !ph_dep_quant_enabled_flag)	
pic_sign_data_hiding_enabled_flag	u(1)
if(deblocking_filter_override_enabled_flag && dbf_info_in_ph_flag) {	
ph_deblocking_filter_override_flag	u(1)
if(ph_deblocking_filter_override_flag) {	
ph_deblocking_filter_disabled_flag	u(1)
if(!ph_deblocking_filter_disabled_flag) {	
ph_beta_offset_div2	se(v)
ph_tc_offset_div2	se(v)
ph_cb_beta_offset_div2	se(v)

ph_cb_tc_offset_div2	se(v)
ph_cr_beta_offset_div2	se(v)
ph_cr_tc_offset_div2	se(v)
}	
}	
}	
if(picture_header_extension_present_flag) {	
ph_extension_length	ue(v)
for(i = 0; i < ph_extension_length; i++)	
ph_extension_data_byte[i]	u(8)
}	
}	

7.3.7.1 General slice header syntax

slice_header() {	Descriptor
picture_header_in_slice_header_flag	u(1)
if(picture_header_in_slice_header_flag)	
picture_header_structure()	
if(subpic_info_present_flag)	
slice_subpic_id	u(v)
if((rect_slice_flag && NumSlicesInSubpic[CurrSubpicIdx] > 1) (!rect_slice_flag && NumTilesInPic > 1))	
slice_address	u(v)
for(i = 0; i < NumExtraPhBits; i++)	
sh_extra_bit[i]	u(1)
if(!rect_slice_flag && NumTilesInPic > 1)	
num_tiles_in_slice_minus1	ue(v)
if(ph_inter_slice_allowed_flag)	
slice_type	ue(v)
if(sps_alf_enabled_flag && !alf_info_in_ph_flag) {	
slice_alf_enabled_flag	u(1)
if(slice_alf_enabled_flag) {	
slice_num_alf_aps_ids_luma	u(3)
for(i = 0; i < slice_num_alf_aps_ids_luma; i++)	
slice_alf_aps_id_luma[i]	u(3)
if(ChromaArrayType != 0)	

slice_alf_chroma_idc	u(2)
if(slice_alf_chroma_idc)	
slice_alf_aps_id_chroma	u(3)
if(sps_ccalf_enabled_flag) {	
slice_cc_alf_cb_enabled_flag	u(1)
if(slice_cc_alf_cb_enabled_flag)	
slice_cc_alf_cb_aps_id	u(3)
slice_cc_alf_cr_enabled_flag	u(1)
if(slice_cc_alf_cr_enabled_flag)	
slice_cc_alf_cr_aps_id	u(3)
}	
}	
}	
if(separate_colour_plane_flag == 1)	
colour_plane_id	u(2)
if(!rpl_info_in_ph_flag && ((nal_unit_type != IDR_W_RADL && nal_unit_type != IDR_N_LP) sps_idr_rpl_present_flag))	
ref_pic_lists()	
if((rpl_info_in_ph_flag ((nal_unit_type != IDR_W_RADL && nal_unit_type != IDR_N_LP) sps_idr_rpl_present_flag)) && (slice_type != I && num_ref_entries[0][RplsIdx[0]] > 1) (slice_type == B && num_ref_entries[1][RplsIdx[1]] > 1)) {	
num_ref_idx_active_override_flag	u(1)
if(num_ref_idx_active_override_flag)	
for(i = 0; i < (slice_type == B ? 2 : 1); i++)	
if(num_ref_entries[i][RplsIdx[i]] > 1)	
num_ref_idx_active_minus1[i]	ue(v)
}	
if(slice_type != I) {	
if(cabac_init_present_flag)	
cabac_init_flag	u(1)
if(ph_temporal_mvp_enabled_flag && !rpl_info_in_ph_flag) {	
if(slice_type == B)	
slice_collocated_from_l0_flag	u(1)

if((slice_collocated_from_l0_flag && NumRefIdxActive[0] > 1) (! slice_collocated_from_l0_flag && NumRefIdxActive[1] > 1))	
slice_collocated_ref_idx	ue(v)
}	
if(!wp_info_in_ph_flag && ((pps_weighted_pred_flag && slice_type == P) (pps_weighted_bipred_flag && slice_type == B)))	
pred_weight_table()	
}	
if(!qp_delta_info_in_ph_flag)	
slice_qp_delta	se(v)
if(pps_slice_chroma_qp_offsets_present_flag) {	
slice_cb_qp_offset	se(v)
slice_cr_qp_offset	se(v)
if(sps_joint_cbr_enabled_flag)	
slice_joint_cbr_qp_offset	se(v)
}	
if(pps_cu_chroma_qp_offset_list_enabled_flag)	
cu_chroma_qp_offset_enabled_flag	u(1)
if(sps_sao_enabled_flag && !sao_info_in_ph_flag) {	
slice_sao_luma_flag	u(1)
if(ChromaArrayType != 0)	
slice_sao_chroma_flag	u(1)
}	
if(deblocking_filter_override_enabled_flag && !dbf_info_in_ph_flag)	
slice_deblocking_filter_override_flag	u(1)
if(slice_deblocking_filter_override_flag) {	
slice_deblocking_filter_disabled_flag	u(1)
if(!slice_deblocking_filter_disabled_flag) {	
slice_beta_offset_div2	se(v)
slice_tc_offset_div2	se(v)
slice_cb_beta_offset_div2	se(v)
slice_cb_tc_offset_div2	se(v)
slice_cr_beta_offset_div2	se(v)
slice_cr_tc_offset_div2	se(v)
}	

}	
slice_ts_residual_coding_disabled_flag	u(1)
if(ph_lmcs_enabled_flag)	
slice_lmcs_enabled_flag	u(1)
if(pic_scaling_list_enabled_flag)	
slice_scaling_list_present_flag	u(1)
if(NumEntryPoints > 0) {	
offset_len_minus1	ue(v)
for(i = 0; i < NumEntryPoints; i++)	
entry_point_offset_minus1[i]	u(v)
}	
if(slice_header_extension_present_flag) {	
slice_header_extension_length	ue(v)
for(i = 0; i < slice_header_extension_length; i++)	
slice_header_extension_data_byte[i]	u(8)
}	
byte_alignment()	
}	

3.4. Example specifications for tiles, slices and subpictures

3 Definitions

picture-level slice index: An index of a slice to the list of slices in a picture in the order as they are signalled in the PPS when the rect_slice_flag is equal to 1.

subpicture-level slice index: An index of a slice to the list of slices in a subpicture in the order as they are signalled in the PPS when the rect_slice_flag is equal to 1.

6.5.1 CTB raster scanning, tile scanning, and subpicture scanning processes

The variable NumTileColumns, specifying the number of tile columns, and the list colWidth[i] for i ranging from 0 to NumTileColumn – 1, inclusive, specifying the width of the i-th tile column in units of CTBs, are derived as follows:

```

remainingWidthInCtbsY = PicWidthInCtbsY
for( i = 0; i < num_exp_tile_columns_minus1; i++ ) {
    colWidth[ i ] = tile_column_width_minus1[ i ] + 1
    remainingWidthInCtbsY -= colWidth[ i ]
}
uniformTileColWidth = tile_column_width_minus1[ num_exp_tile_columns_minus1 ] + 1   (23)
while( remainingWidthInCtbsY >= uniformTileColWidth ) {

```

```

        colWidth[ i++ ] = uniformTileColWidth
        remainingWidthInCtbsY -= uniformTileColWidth
    }
    if( remainingWidthInCtbsY > 0 )
        colWidth[ i++ ] = remainingWidthInCtbsY
    NumTileColumns = i

```

The variable NumTileRows, specifying the number of tile rows, and the list RowHeight[j] for j ranging from 0 to NumTileRows – 1, inclusive, specifying the height of the j-th tile row in units of CTBs, are derived as follows:

```

        remainingHeightInCtbsY = PicHeightInCtbsY
        for( j = 0; j < num_exp_tile_rows_minus1; j++ ) {
            RowHeight[ j ] = tile_row_height_minus1[ j ] + 1
            remainingHeightInCtbsY -= RowHeight[ j ]
        }
        uniformTileRowHeight = tile_row_height_minus1[ num_exp_tile_rows_minus1 ] + 1
        while( remainingHeightInCtbsY >= uniformTileRowHeight ) {
            RowHeight[ j++ ] = uniformTileRowHeight
            remainingHeightInCtbsY -= uniformTileRowHeight
        }
        if( remainingHeightInCtbsY > 0 )
            RowHeight[ j++ ] = remainingHeightInCtbsY
        NumTileRows = j

```

(24)

The variable NumTilesInPic is set equal to NumTileColumns * NumTileRows.

The list tileColBd[i] for i ranging from 0 to NumTileColumns, inclusive, specifying the location of the i-th tile column boundary in units of CTBs, is derived as follows:

```

        for( tileColBd[ 0 ] = 0, i = 0; i < NumTileColumns; i++ )
            tileColBd[ i + 1 ] = tileColBd[ i ] + colWidth[ i ]

```

(25)

NOTE 1 – The size of the array tileColBd[] is one greater than the actual number of tile columns in the derivation of CtbToTileColBd[].

The list tileRowBd[j] for j ranging from 0 to NumTileRows, inclusive, specifying the location of the j-th tile row boundary in units of CTBs, is derived as follows:

```

        for( tileRowBd[ 0 ] = 0, j = 0; j < NumTileRows; j++ )
            tileRowBd[ j + 1 ] = tileRowBd[ j ] + RowHeight[ j ]

```

(26)

NOTE 2 – The size of the array tileRowBd[] in the above derivation is one greater than the actual number of tile rows in the derivation of CtbToTileRowBd[].

The list CtbToTileColBd[ctbAddrX] for ctbAddrX ranging from 0 to PicWidthInCtbsY, inclusive, specifying the conversion from a horizontal CTB address to a left tile column boundary in units of CTBs, is derived as follows:

```

tileX = 0
for( ctbAddrX = 0; ctbAddrX <= PicWidthInCtbsY; ctbAddrX++ ) {
    if( ctbAddrX == tileColBd[ tileX + 1 ] )
        tileX++
    CtbToTileColBd[ ctbAddrX ] = tileColBd[ tileX ]
}

```

(27)

NOTE 3 – The size of the array CtbToTileColBd[] in the above derivation is one greater than the actual number of picture width in CTBs in the slice_data() signalling.

The list CtbToTileRowBd[ctbAddrY] for ctbAddrY ranging from 0 to PicHeightInCtbsY, inclusive, specifying the conversion from a vertical CTB address to a top tile column boundary in units of CTBs, is derived as follows:

```

tileY = 0
for( ctbAddrY = 0; ctbAddrY <= PicHeightInCtbsY; ctbAddrY++ ) {
    if( ctbAddrY == tileRowBd[ tileY + 1 ] )
        tileY++
    CtbToTileRowBd[ ctbAddrY ] = tileRowBd[ tileY ]
}

```

(28)

NOTE 4 – the size of the array CtbToTileRowBd[] in the above derivation is one greater than the actual number of picture height in CTBs in the slice_data() signalling.

For rectangular slices, the list NumCtusInSlice[i] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, specifying the number of CTU in the i-th slice, the list SliceTopLeftTileIdx[i] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, specifying the index of the top-left tile of the slice, and the matrix CtbAddrInSlice[i][j] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, and j ranging from 0 to NumCtusInSlice[i] - 1, inclusive, specifying the picture raster scan address of the j-th CTB within the i-th slice, are derived as follows:

```

if( single_slice_per_subpic_flag ) {
    for( i = 0; i <= sps_num_subpics_minus1; i++ )
        NumCtusInSlice[ i ] = 0
    for( i = 0; i < PicSizeInCtbsY; i++ ) {
        sliceIdx = subpic_info_present_flag ? CtbToSubpicIdx[ i ] : 0
        CtbAddrInSlice[ sliceIdx ][ NumCtusInSlice[ sliceIdx ] ] = i
        NumCtusInSlice[ sliceIdx ]++
    }
} else {
    tileIdx = 0

```

```

for( i = 0; i <= num_slices_in_pic_minus1; i++ )
    NumCtusInSlice[ i ] = 0
for( i = 0; i <= num_slices_in_pic_minus1; i++ ) {
    SliceTopLeftTileIdx[ i ] = tileIdx
    tileX = tileIdx % NumTileColumns
    tileY = tileIdx / NumTileColumns
    if( i == num_slices_in_pic_minus1 ) {
        slice_width_in_tiles_minus1[ i ] = NumTileColumns - 1 - tileX
        slice_height_in_tiles_minus1[ i ] = NumTileRows - 1 - tileY
        NumSlicesInTile[ i ] = 1
    }
    if( slice_width_in_tiles_minus1[ i ] == 0 && slice_height_in_tiles_minus1[ i ] == 0 ) { (29)
        ctbY = tileRowBd[ tileY ]
        for( j = 0; j < NumSlicesInTile[ i ] - 1; j++ ) {
            AddCtbsToSlice( i, tileColBd[ tileX ], tileColBd[ tileX + 1 ],
                           ctbY, ctbY + SliceHeightInCtusMinus1[ i ] + 1 )
            ctbY += SliceHeightInCtusMinus1[ i ] + 1
            i++
        }
        AddCtbsToSlice( i, tileColBd[ tileX ], tileColBd[ tileX + 1 ], ctbY, tileRowBd[ tileY + 1 ] )
    } else
        for( j = 0; j <= slice_height_in_tiles_minus1[ i ]; j++ )
            for( k = 0; k <= slice_width_in_tiles_minus1[ i ]; k++ )
                AddCtbsToSlice( i, tileColBd[ tileX + k ], tileColBd[ tileX + k + 1 ],
                               tileRowBd[ tileY + j ], tileRowBd[ tileY + j + 1 ] )
    if( tile_idx_delta_present_flag )
        tileIdx += tile_idx_delta[ i ]
    else {
        tileIdx += slice_width_in_tiles_minus1[ i ] + 1
        if( tileIdx % NumTileColumns == 0 )
            tileIdx += slice_height_in_tiles_minus1[ i ] * NumTileColumns
    }
}
}
}

```

Where the function AddCtbsToSlice(sliceIdx, startX, stopX, startY, stopY) is specified as follows:

```

for( ctbY = startY; ctbY < stopY; ctbY++ )
  for( ctbX = startX; ctbX < stopX; ctbX++ ) {
    CtbAddrInSlice[ sliceIdx ][ NumCtusInSlice[ sliceIdx ] ] = ctbY * PicWidthInCtbsY + ctbX  (30)
    NumCtusInSlice[ sliceIdx ]++
  }

```

It is a requirement of bitstream conformance that the values of NumCtusInSlice[i] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, shall be greater than 0. Additionally, it is a requirement of bitstream conformance that the matrix CtbAddrInSlice[i][j] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, and j ranging from 0 to NumCtusInSlice[i] - 1, inclusive, shall include all CTB addresses in the range 0 to PicSizeInCtbsY - 1 once and only once.

The list CtbToSubpicIdx[ctbAddrRs] for ctbAddrRs ranging from 0 to PicSizeInCtbsY - 1, inclusive, specifying the conversion from a CTB address in picture raster scan to a subpicture index, is derived as follows:

```

for( ctbAddrRs = 0; ctbAddrRs < PicSizeInCtbsY; ctbAddrRs++ ) {
  posX = ctbAddrRs % PicWidthInCtbsY
  posY = ctbAddrRs / PicWidthInCtbsY
  CtbToSubpicIdx[ ctbAddrRs ] = -1
  for( i = 0; CtbToSubpicIdx[ ctbAddrRs ] < 0 && i <= sps_num_subpics_minus1; i++ ) { (31)
    if( ( posX >= subpic_ctu_top_left_x[ i ] ) &&
        ( posX < subpic_ctu_top_left_x[ i ] + subpic_width_minus1[ i ] + 1 ) &&
        ( posY >= subpic_ctu_top_left_y[ i ] ) &&
        ( posY < subpic_ctu_top_left_y[ i ] + subpic_height_minus1[ i ] + 1 ) )
      CtbToSubpicIdx[ ctbAddrRs ] = i
  }
}

```

The list NumSlicesInSubpic[i], specifying the number of rectangular slices in the i-th subpicture, is derived as follows:

```

for( j = 0; j <= sps_num_subpics_minus1; j++ )
  NumSlicesInSubpic[ j ] = 0
for( i = 0; i <= num_slices_in_pic_minus1; i++ ) {
  posX = CtbAddrInSlice[ i ][ 0 ] % PicWidthInCtbsY
  posY = CtbAddrInSlice[ i ][ 0 ] / PicWidthInCtbsY
  for( j = 0; j <= sps_num_subpics_minus1; j++ ) {
    if( ( posX >= subpic_ctu_top_left_x[ j ] ) &&
        ( posX < subpic_ctu_top_left_x[ j ] + subpic_width_minus1[ j ] + 1 ) &&
        ( posY >= subpic_ctu_top_left_y[ j ] ) &&
        ( posY < subpic_ctu_top_left_y[ j ] + subpic_height_minus1[ j ] + 1 ) ) {
      NumSlicesInSubpic[ j ]++
    }
  }
}

```

```

        NumSlicesInSubpic[ j ]++
    }
}
}

```

7.3.4.3 Picture parameter set RBSP semantics

subpic_id_mapping_in_pps_flag equal to 1 specifies that the subpicture ID mapping is signalled in the PPS.

subpic_id_mapping_in_pps_flag equal to 0 specifies that the subpicture ID mapping is not signalled in the PPS. If **subpic_id_mapping_explicitly_signalled_flag** is 0 or **subpic_id_mapping_in_sps_flag** is equal to 1, the value of **subpic_id_mapping_in_pps_flag** shall be equal to 0. Otherwise (**subpic_id_mapping_explicitly_signalled_flag** is equal to 1 and **subpic_id_mapping_in_sps_flag** is equal to 0), the value of **subpic_id_mapping_in_pps_flag** shall be equal to 1.

pps_num_subpics_minus1 shall be equal to **sps_num_subpics_minus1**.

pps_subpic_id_len_minus1 shall be equal to **sps_subpic_id_len_minus1**.

pps_subpic_id[i] specifies the subpicture ID of the i-th subpicture. The length of the **pps_subpic_id[i]** syntax element is **pps_subpic_id_len_minus1 + 1** bits.

The variable **SubpicIdVal[i]**, for each value of i in the range of 0 to **sps_num_subpics_minus1**, inclusive, is derived as follows:

```

for( i = 0; i <= sps_num_subpics_minus1; i++ )
    if( subpic_id_mapping_explicitly_signalled_flag )
        SubpicIdVal[ i ] = subpic_id_mapping_in_pps_flag ? pps_subpic_id[ i ] : sps_subpic_id[ i ]
    (80)
    else
        SubpicIdVal[ i ] = i

```

It is a requirement of bitstream conformance that both of the following constraints apply:

- For any two different values of i and j in the range of 0 to **sps_num_subpics_minus1**, inclusive, **SubpicIdVal[i]** shall not be equal to **SubpicIdVal[j]**.
- When the current picture is not the first picture of the CLVS, for each value of i in the range of 0 to **sps_num_subpics_minus1**, inclusive, if the value of **SubpicIdVal[i]** is not equal to the value of **SubpicIdVal[i]** of the previous picture in decoding order in the same layer, the **nal_unit_type** for all coded slice NAL units of the subpicture in the current picture with subpicture index i shall be equal to a particular value in the range of **IDR_W_RADL** to **CRA_NUT**, inclusive.

no_pic_partition_flag equal to 1 specifies that no picture partitioning is applied to each picture referring to the PPS.

no_pic_partition_flag equal to 0 specifies each picture referring to the PPS may be partitioned into more than one tile or slice.

It is a requirement of bitstream conformance that the value of **no_pic_partition_flag** shall be the same for all PPSs that are referred to by coded pictures within a CLVS.

It is a requirement of bitstream conformance that the value of `no_pic_partition_flag` shall not be equal to 1 when the value of `sps_num_subpics_minus1 + 1` is greater than 1.

`pps_log2_ctu_size_minus5` plus 5 specifies the luma coding tree block size of each CTU.

`pps_log2_ctu_size_minus5` shall be equal to `sps_log2_ctu_size_minus5`.

`num_exp_tile_columns_minus1` plus 1 specifies the number of explicitly provided tile column widths. The value of `num_exp_tile_columns_minus1` shall be in the range of 0 to `PicWidthInCtbsY - 1`, inclusive. When

`no_pic_partition_flag` is equal to 1, the value of `num_exp_tile_columns_minus1` is inferred to be equal to 0.

`num_exp_tile_rows_minus1` plus 1 specifies the number of explicitly provided tile row heights. The value of `num_exp_tile_rows_minus1` shall be in the range of 0 to `PicHeightInCtbsY - 1`, inclusive. When

`no_pic_partition_flag` is equal to 1, the value of `num_exp_tile_rows_minus1` is inferred to be equal to 0.

`tile_column_width_minus1[i]` plus 1 specifies the width of the *i*-th tile column in units of CTBs for *i* in the range of 0 to `num_exp_tile_columns_minus1 - 1`, inclusive.

`tile_column_width_minus1[num_exp_tile_columns_minus1]` is used to derive the width of the tile columns with index greater than or equal to `num_exp_tile_columns_minus1` as specified in clause 6.5.1. The value of `tile_column_width_minus1[i]` shall be in the range of 0 to `PicWidthInCtbsY - 1`, inclusive. When not present, the value of `tile_column_width_minus1[0]` is inferred to be equal to `PicWidthInCtbsY - 1`.

`tile_row_height_minus1[i]` plus 1 specifies the height of the *i*-th tile row in units of CTBs for *i* in the range of 0 to `num_exp_tile_rows_minus1 - 1`, inclusive. `tile_row_height_minus1[num_exp_tile_rows_minus1]` is used to derive the height of the tile rows with index greater than or equal to `num_exp_tile_rows_minus1` as specified in clause 6.5.1. The value of `tile_row_height_minus1[i]` shall be in the range of 0 to `PicHeightInCtbsY - 1`, inclusive. When not present, the value of `tile_row_height_minus1[0]` is inferred to be equal to `PicHeightInCtbsY - 1`.

`rect_slice_flag` equal to 0 specifies that tiles within each slice are in raster scan order and the slice information is not signalled in PPS. `rect_slice_flag` equal to 1 specifies that tiles within each slice cover a rectangular region of the picture and the slice information is signalled in the PPS. When not present, `rect_slice_flag` is inferred to be equal to 1. When `subpic_info_present_flag` is equal to 1, the value of `rect_slice_flag` shall be equal to 1.

`single_slice_per_subpic_flag` equal to 1 specifies that each subpicture consists of one and only one rectangular slice. `single_slice_per_subpic_flag` equal to 0 specifies that each subpicture may consist of one or more rectangular slices. When `single_slice_per_subpic_flag` is equal to 1, `num_slices_in_pic_minus1` is inferred to be equal to `sps_num_subpics_minus1`. When not present, the value of `single_slice_per_subpic_flag` is inferred to be equal to 0.

`num_slices_in_pic_minus1` plus 1 specifies the number of rectangular slices in each picture referring to the PPS. The value of `num_slices_in_pic_minus1` shall be in the range of 0 to `MaxSlicesPerPicture - 1`, inclusive, where `MaxSlicesPerPicture` is specified in Annex A. When `no_pic_partition_flag` is equal to 1, the value of `num_slices_in_pic_minus1` is inferred to be equal to 0.

`tile_idx_delta_present_flag` equal to 0 specifies that `tile_idx_delta` values are not present in the PPS and all rectangular slices in pictures referring to the PPS are specified in raster order according to the process defined in clause 6.5.1. `tile_idx_delta_present_flag` equal to 1 specifies that `tile_idx_delta` values may be present in the PPS

and all rectangular slices in pictures referring to the PPS are specified in the order indicated by the values of `tile_idx_delta`. When not present, the value of `tile_idx_delta_present_flag` is inferred to be equal to 0.

`slice_width_in_tiles_minus1[ i ]` plus 1 specifies the width of the *i*-th rectangular slice in units of tile columns. The value of `slice_width_in_tiles_minus1[ i ]` shall be in the range of 0 to `NumTileColumns - 1`, inclusive.

When `slice_width_in_tiles_minus1[ i ]` is not present, the following applies:

- If `NumTileColumns` is equal to 1, the value of `slice_width_in_tiles_minus1[ i ]` is inferred to be equal to 0.
- Otherwise, the value of `slice_width_in_tiles_minus1[ i ]` is inferred as specified in clause 6.5.1.

`slice_height_in_tiles_minus1[ i ]` plus 1 specifies the height of the *i*-th rectangular slice in units of tile rows. The value of `slice_height_in_tiles_minus1[ i ]` shall be in the range of 0 to `NumTileRows - 1`, inclusive.

When `slice_height_in_tiles_minus1[ i ]` is not present, the following applies:

- If `NumTileRows` is equal to 1, or `tile_idx_delta_present_flag` is equal to 0 and `tileIdx % NumTileColumns` is greater than 0), the value of `slice_height_in_tiles_minus1[ i ]` is inferred to be equal to 0.
- Otherwise (`NumTileRows` is not equal to 1, and `tile_idx_delta_present_flag` is equal to 1 or `tileIdx % NumTileColumns` is equal to 0), when `tile_idx_delta_present_flag` is equal to 1 or `tileIdx % NumTileColumns` is equal to 0, the value of `slice_height_in_tiles_minus1[ i ]` is inferred to be equal to `slice_height_in_tiles_minus1[ i - 1 ]`.

`num_exp_slices_in_tile[ i ]` specifies the number of explicitly provided slice heights in the current tile that contains more than one rectangular slices. The value of `num_exp_slices_in_tile[ i ]` shall be in the range of 0 to `RowHeight[ tileY ] - 1`, inclusive, where `tileY` is the tile row index containing the *i*-th slice. When not present, the value of `num_exp_slices_in_tile[ i ]` is inferred to be equal to 0. When `num_exp_slices_in_tile[ i ]` is equal to 0, the value of the variable `NumSlicesInTile[ i ]` is derived to be equal to 1.

`exp_slice_height_in_ctus_minus1[ j ]` plus 1 specifies the height of the *j*-th rectangular slice in the current tile in units of CTU rows. The value of `exp_slice_height_in_ctus_minus1[ j ]` shall be in the range of 0 to `RowHeight[ tileY ] - 1`, inclusive, where `tileY` is the tile row index of the current tile.

When `num_exp_slices_in_tile[ i ]` is greater than 0, the variable `NumSlicesInTile[ i ]` and

`SliceHeightInCtusMinus1[ i + k ]` for *k* in the range of 0 to `NumSlicesInTile[ i ] - 1` are derived as follows:

```

remainingHeightInCtbsY = RowHeight[ SliceTopLeftTileIdx[ i ] / NumTileColumns ]
numExpSliceInTile = num_exp_slices_in_tile[ i ]
for( j = 0; j < numExpSliceInTile - 1; j++ ) {
    SliceHeightInCtusMinus1[ i++ ] = exp_slice_height_in_ctu_minus1[ j ]
    remainingHeightInCtbsY -= SliceHeightInCtusMinus1[ j ]
}
uniformSliceHeightMinus1 = SliceHeightInCtusMinus1[ i - 1 ]
while( remainingHeightInCtbsY >= (uniformSliceHeightMinus1 + 1) ) {
    SliceHeightInCtusMinus1[ i++ ] = uniformSliceHeightMinus1
    remainingHeightInCtbsY -= (uniformSliceHeightMinus1 + 1)
}

```

(81)

```

        j++
    }
    if( remainingHeightInCtbsY > 0 ) {
        SliceHeightInCtusMinus1[ i++ ] = remainingHeightInCtbsY
        j++
    }
    NumSlicesInTile[ i ] = j

```

tile_idx_delta[i] specifies the difference between the tile index of the first tile in the i -th rectangular slice and the tile index of the first tile in the $(i + 1)$ -th rectangular slice. The value of **tile_idx_delta[i]** shall be in the range of $-\text{NumTilesInPic} + 1$ to $\text{NumTilesInPic} - 1$, inclusive. When not present, the value of **tile_idx_delta[i]** is inferred to be equal to 0. When present, the value of **tile_idx_delta[i]** shall not be equal to 0.

...

7.4.2.4.5 Order of VCL NAL units and their association to coded pictures

The order of the VCL NAL units within a coded picture is constrained as follows:

- For any two coded slice NAL units A and B of a coded picture, let **subpicIdxA** and **subpicIdxB** be their subpicture level index values, and **sliceAddrA** and **sliceddrB** be their **slice_address** values.
- When either of the following conditions is true, coded slice NAL unit A shall precede coded slice NAL unit B:
 - **subpicIdxA** is less than **subpicIdxB**.
 - **subpicIdxA** is equal to **subpicIdxB** and **sliceAddrA** is less than **sliceAddrB**.

7.4.8.1 General slice header semantics

The variable **CuQpDeltaVal**, specifying the difference between a luma quantization parameter for the coding unit containing **cu_qp_delta_abs** and its prediction, is set equal to 0. The variables **CuQpOffsetCb**, **CuQpOffsetCr**, and **CuQpOffsetCbCr**, specifying values to be used when determining the respective values of the **Qp'Cb**, **Qp'Cr**, and **Qp'CbCr** quantization parameters for the coding unit containing **cu_chroma_qp_offset_flag**, are all set equal to 0.

picture_header_in_slice_header_flag equal to 1 specifies that the PH syntax structure is present in the slice header. **picture_header_in_slice_header_flag** equal to 0 specifies that the PH syntax structure is not present in the slice header.

It is a requirement of bitstream conformance that the value of **picture_header_in_slice_header_flag** shall be the same in all coded slices in a CLVS.

When **picture_header_in_slice_header_flag** is equal to 1 for a coded slice, it is a requirement of bitstream conformance that no VCL NAL unit with **nal_unit_type** equal to **PH_NUT** shall be present in the CLVS.

When **picture_header_in_slice_header_flag** is equal to 0, all coded slices in the current picture shall have **picture_header_in_slice_header_flag** is equal to 0, and the current PU shall have a PH NAL unit.

slice_subpic_id specifies the subpicture ID of the subpicture that contains the slice. If **slice_subpic_id** is present, the value of the variable **CurrSubpicIdx** is derived to be such that **SubpicIdVal[CurrSubpicIdx]** is equal to

slice_subpic_id. Otherwise (slice_subpic_id is not present), CurrSubpicIdx is derived to be equal to 0. The length of slice_subpic_id is $\text{sps_subpic_id_len_minus1} + 1$ bits.

slice_address specifies the slice address of the slice. When not present, the value of slice_address is inferred to be equal to 0. When rect_slice_flag is equal to 1 and NumSlicesInSubpic[CurrSubpicIdx] is equal to 1, the value of slice_address is inferred to be equal to 0.

If rect_slice_flag is equal to 0, the following applies:

- The slice address is the raster scan tile index.
- The length of slice_address is $\text{Ceil}(\text{Log2}(\text{NumTilesInPic}))$ bits.
- The value of slice_address shall be in the range of 0 to NumTilesInPic – 1, inclusive.

Otherwise (rect_slice_flag is equal to 1), the following applies:

- The slice address is the subpicture-level slice index of the slice.
- The length of slice_address is $\text{Ceil}(\text{Log2}(\text{NumSlicesInSubpic}[\text{CurrSubpicIdx}]))$ bits.
- The value of slice_address shall be in the range of 0 to NumSlicesInSubpic[CurrSubpicIdx] – 1, inclusive.

It is a requirement of bitstream conformance that the following constraints apply:

- If rect_slice_flag is equal to 0 or subpic_info_present_flag is equal to 0, the value of slice_address shall not be equal to the value of slice_address of any other coded slice NAL unit of the same coded picture.
- Otherwise, the pair of slice_subpic_id and slice_address values shall not be equal to the pair of slice_subpic_id and slice_address values of any other coded slice NAL unit of the same coded picture.
- The shapes of the slices of a picture shall be such that each CTU, when decoded, shall have its entire left boundary and entire top boundary consisting of a picture boundary or consisting of boundaries of previously decoded CTU(s).

sh_extra_bit[i] may be equal to 1 or 0. Decoders conforming to this version of this Specification shall ignore the value of sh_extra_bit[i]. Its value does not affect decoder conformance to profiles specified in this version of specification.

num_tiles_in_slice_minus1 plus 1, when present, specifies the number of tiles in the slice. The value of num_tiles_in_slice_minus1 shall be in the range of 0 to NumTilesInPic – 1, inclusive.

The variable NumCtusInCurrSlice, which specifies the number of CTUs in the current slice, and the list CtbAddrInCurrSlice[i], for i ranging from 0 to NumCtusInCurrSlice – 1, inclusive, specifying the picture raster scan address of the i-th CTB within the slice, are derived as follows:

```

if( rect_slice_flag ) {
    picLevelSliceIdx = slice_address
    for( j = 0; j < CurrSubpicIdx; j++ )
        picLevelSliceIdx += NumSlicesInSubpic[ j ]
    NumCtusInCurrSlice = NumCtusInSlice[ picLevelSliceIdx ]
    for( i = 0; i < NumCtusInCurrSlice; i++ )
        CtbAddrInCurrSlice[ i ] = CtbAddrInSlice[ picLevelSliceIdx ][ i ]
}

```

(117)

```

    } else {
        NumCtusInCurrSlice = 0
        for( tileIdx = slice_address; tileIdx <= slice_address + num_tiles_in_slice_minus1; tileIdx++ ) {
            tileX = tileIdx % NumTileColumns
            tileY = tileIdx / NumTileColumns
            for( ctbY = tileRowBd[ tileY ]; ctbY < tileRowBd[ tileY + 1 ]; ctbY++ ) {
                for( ctbX = tileColBd[ tileX ]; ctbX < tileColBd[ tileX + 1 ]; ctbX++ ) {
                    CtbAddrInCurrSlice[ NumCtusInCurrSlice ] = ctbY * PicWidthInCtb + ctbX
                    NumCtusInCurrSlice++
                }
            }
        }
    }
}

```

The variables SubpicLeftBoundaryPos, SubpicTopBoundaryPos, SubpicRightBoundaryPos, and SubpicBotBoundaryPos are derived as follows:

```

if( subpic_treated_as_pic_flag[ CurrSubpicIdx ] ) {
    SubpicLeftBoundaryPos = subpic_ctu_top_left_x[ CurrSubpicIdx ] * CtbSizeY
    SubpicRightBoundaryPos = Min( pic_width_max_in_luma_samples - 1,
        ( subpic_ctu_top_left_x[ CurrSubpicIdx ] +
            subpic_width_minus1[ CurrSubpicIdx ] + 1 ) * CtbSizeY - 1 )
    SubpicTopBoundaryPos = subpic_ctu_top_left_y[ CurrSubpicIdx ] * CtbSizeY
    SubpicBotBoundaryPos = Min( pic_height_max_in_luma_samples - 1,
        ( subpic_ctu_top_left_y[ CurrSubpicIdx ] +
            subpic_height_minus1[ CurrSubpicIdx ] + 1 ) * CtbSizeY - 1 )
}

```

3.5. Color space and chroma subsampling

[0090] Color space, also known as the color model (or color system), is an abstract mathematical model which simply describes the range of colors as tuples of numbers, typically as 3 or 4 values or color components (e.g. RGB). Basically speaking, color space is an elaboration of the coordinate system and sub-space.

[0091] For video compression, the most frequently used color spaces are YCbCr and RGB.

[0092] YCbCr, Y'CbCr, or Y Pb/Cb Pr/Cr, also written as YCBCR or Y'CBCR, is a family of color spaces used as a part of the color image pipeline in video and digital photography systems. Y' is the luma component and CB and CR are the blue-difference and red-

difference chroma components. Y' (with prime) is distinguished from Y , which is luminance, meaning that light intensity is nonlinearly encoded based on gamma corrected RGB primaries.

[0093] Chroma subsampling is the practice of encoding images by implementing less resolution for chroma information than for luma information, taking advantage of the human visual system's lower acuity for color differences than for luminance.

3.5.1. 4:4:4

[0094] Each of the three $Y'CbCr$ components have the same sample rate, thus there is no chroma subsampling. This scheme is sometimes used in high-end film scanners and cinematic post production.

3.5.2. 4:2:2

[0095] The two chroma components are sampled at half the sample rate of luma: the horizontal chroma resolution is halved while the vertical chroma resolution is unchanged. This reduces the bandwidth of an uncompressed video signal by one-third with little to no visual difference. An example of nominal vertical and horizontal locations of 4:2:2 color format is depicted in FIG. 5 in VVC working draft.

3.5.3. 4:2:0

[0096] In 4:2:0, the horizontal sampling is doubled compared to 4:1:1, but as the Cb and Cr channels are only sampled on each alternate line in this scheme, the vertical resolution is halved. The data rate is thus the same. Cb and Cr are each subsampled at a factor of 2 both horizontally and vertically. There are three variants of 4:2:0 schemes, having different horizontal and vertical siting.

- In MPEG-2, Cb and Cr are cosited horizontally. Cb and Cr are sited between pixels in the vertical direction (sited interstitially).
- In JPEG/JFIF, H.261, and MPEG-1, Cb and Cr are sited interstitially, halfway between alternate luma samples.
- In 4:2:0 DV, Cb and Cr are co-sited in the horizontal direction. In the vertical direction, they are co-sited on alternating lines.

Table 3-1. SubWidthC and SubHeightC values derived from chroma_format_idc and separate_colour_plane_flag

chroma_format_i dc	separate_colour_plane_fl ag	Chroma format	SubWidth C	SubHeight C
0	0	Monochrome	1	1
1	0	4:2:0	2	2
2	0	4:2:2	2	1
3	0	4:4:4	1	1
3	1	4:4:4	1	1

4. Examples of technical problems solved by disclosed embodiments

[0097] The existing designs for signaling of SPS/PPS/Picture header/Slice header in VVC have the following problems:

- 1) When `rect_slice_flag` is equal to 1, according to the current VVC text, the following applies:
 - a. `slice_address` represents the subpicture-level slice index of the slice.
 - b. The subpicture-level slice index is defined as the index of a slice to the list of slices in a subpicture in the order as they are signalled in the PPS.
 - c. The picture-level slice index is defined as the index of a slice to the list of slices in a picture in the order as they are signalled in the PPS.
 - d. For any two slices belonging to two different subpictures, the one associated with the less subpicture index goes earlier in decoding order, and for any two slices belonging to the same subpicture, the one with the less subpicture-level slice index goes earlier in decoding order.
 - e. And the derivation of the variable `NumCtusInCurrSlice`, which specifies the number of CTUs in the current slice, by Equation 117 in the current VVC text, assumes that the order of increasing picture-level slice index values is the same as the decoding order of slices.

However, when some slices are resulted from splitting one tile, some of the above aspects may be violated. As an example shown in FIG. 6, when a picture is partitioned into two tiles by a vertical tile boundary, and each of the two tiles is partitioned into two slices by the same horizontal boundary across the entire picture, and the upper two slices are

included into the first subpicture and the lower two slices are included into the second subpicture. In this case, according to the current VVC text, the picture-level slice index values of the four slices in slice raster scan order would be 0, 2, 1, 3, while the decoding order index values of the four slices in slice raster scan order would be 0, 1, 2, 3. Consequently, the derivation of NumCtusInCurrSlice would be incorrect, and in turn the parsing of slice data would be problematic, the decoded sample values won't be correct, and the decoder would likely to crash.

- 2) There are two types of slice signaling methods. With the rectangular mode, all the slice partitioning information is signaled in PPS. With the non-rectangular mode, partial of the slice partitioning information is signaled in the slice header, thus in this mode the full slice partitioning of a picture cannot be known before parsing all slices of the picture.
- 3) With the rectangular mode, the slices may be signaled arbitrarily by setting **tile_idx_delta**. An evil bitstream may make the decoder crash with this mechanism.
- 4) In In some embodiments, an uninitialized **tile_idx_delta[i]** when *i* is equal to **num_slices_in_pic_minus1**.

[0098] FIG. 6 shows an example of picture partitioning. Solid lines 602 represent boundaries of tiles; dashed lines 604 represent boundaries of slices and dashed lines 606 represent boundaries of subpictures. The picture-level indices, decoding order indices, subpicture-level indices of the four slices and the indices of subpictures and tiles are indicated in the figure.

5. Example embodiments and techniques

[0099] To solve the above problems, and others, methods as summarized below are disclosed. The inventions should be considered as examples to explain the general concepts and should not be interpreted in a narrow way. Furthermore, these inventions can be applied individually or combined in any manner.

1. For slices of the rectangular slices mode (i.e., when **rect_slice_flag** is equal to 1), the picture-level slice index for each slice in each subpicture is derived, and the derived value is used for the derivation of the number of CTUs in each slice.
2. The subpicture-level slice index may be defined/derived in the following ways:

- a. In one example, the subpicture-level slice index is defined as "The index of a slice to the list of slices in a subpicture in their decoding order when the `rect_slice_flag` is equal to 1."
 - b. Alternatively, the subpicture-level slice index is defined as "The index of a slice to the list of slices in a subpicture when the `rect_slice_flag` is equal to 1, as specified by the variable `SubpicLevelSliceIdx[ i ]` as derived in Equation 32 (as in Embodiment 1), where `i` is the picture-level slice index of the slice."
 - c. In one example, the subpicture index of each slice with a particular value of picture-level slice index is derived.
 - d. In one example, the subpicture-level slice index of each slice with a particular value of picture-level slice index is derived.
 - e. In one example, when `rect_slice_flag` is equal to 1, the semantics of the slice address is specified as "The slice address is the subpicture-level slice index of the slice as specified by the variable `SubpicLevelSliceIdx[ i ]` as derived in Equation 32 (e.g., as in Embodiment 1), where `i` is the picture-level slice index of the slice."
3. A subpicture-level slice index of the slice is assigned to a slice in a first subpicture which contains the slice. The subpicture-level slice index for each slice may be stored in an array (e.g. `SubpicLevelSliceIdx[ i ]` in Embodiment 1) indexed by the picture-level slice index.
- a. In one example, the subpicture-level slice index is a non-negative integer.
 - b. In one example, the value of a subpicture-level slice index of the slice is greater than or equal to 0.
 - c. In one example, the value of a subpicture-level slice index of the slice is smaller than `N`, wherein `N` is the number of slices in the subpicture.
 - d. In one example, a first subpicture-level slice index (denoted as `subIdxA`) of a first slice (slice A) must be different to a second subpicture-level slice index (denoted as `subIdxB`) of a second slice (slice B) if the first slice and the second slice are in the same subpicture but they are different.
 - e. In one example, if a first subpicture-level slice index (denoted as `subIdxA`) of a first slice (slice A) in a first subpicture is smaller than a second subpicture-level slice index (denoted as `subIdxB`) of a second slice (slice B) in the same first subpicture,

IdxA is smaller than IdxB, wherein idxA and idxB represent the slice index in the whole picture (a.k.a. picture-level slice index, e.g. sliceIdx) for slice A and slice B, respectively.

- f. In one example, if a first subpicture-level slice index (denoted as subIdxA) of a first slice (slice A) in a first subpicture is smaller than a second subpicture-level slice index (denoted as subIdxB) of a second slice (slice B) in the same first subpicture, slice A is ahead of slice B in the decoding order.
 - g. In one example, the subpicture-level slice index in a subpicture is derived based on the picture-level slice index (e.g. sliceIdx).
4. It is proposed to derive a mapping function/table between the subpicture-level slice index in a sub-picture and the picture-level slice index.
- a. In one example, a two-dimensional array `PicLevelSliceIdx[ subPicIdx ][ SubPicLevelSliceIdx ]` is derived to map the subpicture-level slice index in a sub-picture to the picture-level slice index, wherein `PicLevelSliceIdx` denotes the picture-level slice index of a slice, `subPicIdx` denotes the index of the subpicture, and `SubPicLevelSliceIdx` denotes the subpicture-level slice index of the slice in the subpicture.
 - i. In one example, an array `NumSlicesInSubpic[ subPicIdx ]` is used to derive `PicLevelSliceIdx`, wherein `NumSlicesInSubpic[ subPicIdx ]` denotes the number of slices in the subpicture with index equal to `subPicIdx`.
 - 1) In one example, `NumSlicesInSubpic[ subPicIdx ]` and `PicLevelSliceIdx [ subPicIdx ][ SubPicLevelSliceIdx ]` are derived in a single process by scanning all the slices in the order of picture-level slice index.
 - a. `NumSlicesInSubpic[ subPicIdx ]` is set equal to 0 for all valid `subPicIdx` before the process.
 - b. When checking a slice with picture level index equal to S, if it is in the subpicture with subpicture index equal to P, `PicLevelSliceIdx [ P ][ NumSlicesInSubpic[ P ] ]` is set equal

to S, and then NumSlicesInSubpic[P] is set equal to NumSlicesInSubpic[P] + 1.

- ii. In one example, SliceIdxInPic[subPicIdx][SubPicLevelSliceIdx] is used to derive the picture level slice index (e.g. picLevelSliceIdx), which is then used to derive the number and/or addresses of CTBs in the slice when parsing the slice header.
5. It is required by a conformance bitstream that one tile cannot be in more than one subpictures.
6. It is required by a conformance bitstream that one subpicture cannot include two slices, denoted as slice A and slice B, wherein slice A is in but is smaller than a tile A, and slice B is in but is smaller than a tile B, and tile A and tile B are different.
7. It is proposed that the tile and/or slice portioning information of a picture may be signaled in the associated picture header.
 - a. In one example, it is signaled in an associated PPS whether the tile and/or slice portioning information of a picture is signaled in the PPS or in the associated picture header.
 - b. In one example, it is signaled in the picture header whether the tile and/or slice portioning information of a picture is in the associated picture header.
 - i. In one example, if the tile and/or slice portioning information of a picture is signaled both in an associated PPS and in an associated picture header, the tile and/or slice portioning information of a picture signaled in the picture header will be used.
 - ii. In one example, if the tile and/or slice portioning information of a picture is signaled both in an associated PPS and in an associated picture header, the tile and/or slice portioning information of a picture signaled in the PPS will be used.
 - c. In one example, it is signaled in a video unit at a level higher than picture (such as in SPS) to indicate whether the tile and/or slice portioning information of a picture is signaled in the associated PPS or in the associated picture header.

8. It is proposed that the slice partitioning information is signaled in a higher-level video unit (such as in PPS and/or picture header) higher than the slice level when the associated picture is partitioned in slices with the non-rectangular mode.
- a. In one example, the information to indicate the number of slices (e.g. **num_slices_in_pic_minus1**) may be signaled in the higher-level video unit when the associated picture is partitioned in slices with the non-rectangular mode.
 - b. In one example, the information to indicate the index (or address, or location, or coordinate) of the first block-unit of a slice in the higher-level video unit when the associated picture is partitioned in slices with the non-rectangular mode. For example, the block-unit may be a CTU or a tile.
 - c. In one example, the information to indicate the number of the block-units of a slice in the higher-level video unit when the associated picture is partitioned in slices with the non-rectangular mode. For example, the block-unit may be a CTU or a tile.
 - d. In one example, the slice partitioning information (e.g. **num_tiles_in_slice_minus1**) is not signaled in the slice header when the associated picture is partitioned in slices with the non-rectangular mode.
 - e. In one example, the slice index is signaled in the slice header when the associated picture is partitioned in slices with the non-rectangular mode.
 - i. In one example, **slice_address** is interpreted as the picture-level slice index when the associated picture is partitioned in slices with the non-rectangular mode.
 - f. In one example, the partitioning information (such as the index of the first block-unit and/or the number of the block-units) of each slice in a picture may be signaled in an order in the higher-level video unit when the associated picture is partitioned in slices with the non-rectangular mode.
 - i. In one example, the index of a slice may be signaled for each slice in the higher-level video unit when the associated picture is partitioned in slices with the non-rectangular mode.
 - ii. In one example, the partitioning information of each slice is signaled in an ascending order of slice indices.

- 1) In one example, the partitioning information of each slice is signaled in the order of slice 0, slice 1, ..., slice K-1, slice K, slice K+1, ..., slice S-2, slice S-1, wherein K represents a slice index and S represents the number of slices in the picture.
- iii. In one example, the partitioning information of each slice is signaled in a descending order of slice indices.
 - 1) In one example, the partitioning information of each slice is signaled in the order of slice S-2, slice S-1, ..., slice K+1, slice K, slice K-1, ..., slice 1, slice 0, wherein K represents a slice index and S represents the number of slices in the picture.
- iv. In one example, the index of the first block-unit for a slice may not be signaled in the higher-level video unit when the associated picture is partitioned in slices with the non-rectangular mode.
 - 1) For example, the index of the first block-unit for slice 0 (the slice with the slice index equal to 0) is inferred to be 0.
 - 2) For example, the index of the first block-unit for slice K (the slice with the slice index equal to K, $K > 0$) is inferred to be $\sum_{i=0}^{K-1} N_i$, wherein N_i represents the number of block-units in slice i .
- v. In one example, the index of the first block-unit for a slice may not be signaled in the higher-level video unit when the associated picture is partitioned in slices with the non-rectangular mode.
 - 1) For example, the index of the first block-unit for slice 0 (the slice with the slice index equal to 0) is inferred to be 0.
 - 2) For example, the index of the first block-unit for slice K (the slice with the slice index equal to K, $K > 0$) is inferred to be $\sum_{i=0}^{K-1} N_i$, wherein N_i represents the number of block-units in slice i .
- vi. In one example, the number of block-units for a slice may not be signaled in the higher-level video unit when the associated picture is partitioned in slices with the non-rectangular mode.

- 1) The number of block-units for slice 0 is M when there is only one slice in the picture and there are M blocks units in the picture.
 - 2) For example, the number of block-units for slice K (the slice with the slice index equal to 0) is inferred to be $T_{K+1} - T_K$, wherein T_K represents the index of the first block-unit for slice K when $K < S - 1$, wherein S is the number of slices in the picture and $S > 1$.
 - 3) For example, the number of block-units for slice S-1 is inferred to be $M - \sum_{i=0}^{S-2} N_i$, wherein S is the number of slices in the picture and $S > 1$, M is the number of blocks units in the picture,
- vii. In one example, the partitioning information of one or more slices may NOT be signaled in the higher-level video unit when the associated picture is partitioned in slices with the non-rectangular mode.
- 1) In one example, the partitioning information of one or more slices NOT be signaled in the higher-level video unit may be inferred by the partitioning information of other slices to be signaled.
 - 2) In one example, the partitioning information of the last C slices may NOT be signaled. E.g. C is equal to 1.
 - 3) For example, the number of block-units for slice S-1 is not signaled, wherein S is the number of slices in the picture and $S > 1$.
 - a. For example, the number of block-units for slice S-1 is inferred to be $M - \sum_{i=0}^{S-2} N_i$, wherein there are M blocks units in the picture.
9. It is proposed that the minimum number of slices in a picture may be different depending on whether rectangular partitioning is applied, or non- rectangular partitioning is applied.
- a. In one example, the picture is partitioned into at least two slices if non-rectangular partitioning mode is applied, and the picture is partitioned into at least one slice if rectangular partitioning mode is applied.
 - i. For example, **num_slices_in_pic_minus2** plus 2 specifying the number of slices in a picture may be signaled if non-rectangular partitioning mode is applied.

- b. In one example, the picture is partitioned into at least one slices if non-rectangular partitioning mode is applied, and the picture is partitioned into at least one slice if rectangular partitioning mode is applied.
 - i. For example, **num_slices_in_pic_minus2** plus 2 specifying the number of slices in a picture may be signaled if rectangular partitioning mode is applied.
 - c. In one example, the minimum number of slices in a picture may be different depending on whether rectangular partitioning is applied, or non- rectangular partitioning is applied when the picture is not partitioned into subpictures or partitioned into only one subpicture.
10. It is proposed that a slice is represented by the top-left location and the width/height of the slice when the partitioning information is signaled in a video unit such as PPS or picture header.
- a. In one example, the index/location/coordinate of the top-left block unit (such as CTU or tile) and/or the width measured with video unit (such as CTU or tile), and/or height measured with video unit (such as CTU or tile) of a slice is signaled.
 - b. In one example, the information of top-left location and the width/height of each slice is signaled in an order.
 - i. For example, the information of top-left location and the width/height of each slice is signaled in an ascending order of slice indices, such as 0, 1, 2,..., S-1, wherein S is the number of slices in a picture.
11. It is proposed that the partitioning information (such as location/width/height) for slices in a subpicture is signaled in a video unit such as SPS/PPS/picture header.
- a. In one example, the slice partitioning information for each subpicture is signaled in an order.
 - i. For example, the slice partitioning information for each subpicture is signaled in an ascending order of subpicture index.
 - b. In one example, the partitioning information (such as location/width/height) for each slice in a subpicture is signaled in an order.

- i. In one example, the partitioning information (such as location/width/height) for each slice in a subpicture is signaled in an ascending order of subpicture-level slice index.
12. It is proposed that the difference between the tile index of the first tile in the i -th rectangular slice and the tile index of the first tile in the $(i + 1)$ -th rectangular slice (denoted as **tile_idx_delta[i]**) is not signaled but derived.
 - a. In one example, the tile index of the first tile in the $(i + 1)$ -th rectangular slice is derived based on the rectangular slices from the 0th rectangular slice to the i -th rectangular slice.
 - b. In one example, the tile index of the first tile in the $(i + 1)$ -th rectangular slice is derived to be the minimum index of the tiles, which are not inside the rectangular slices from the 0th rectangular slice to the i -th rectangular slice.
13. It is proposed that the signaling of information to derive the number of tile columns/rows (e.g. NumTileColumns or NumTileRows) may be conditioned on the relationship between the width of a picture and the size of a CTU.
 - a. For example, **num_exp_tile_columns_minus1** and/or **tile_column_width_minus1** may not be signaled if the width of a picture is smaller than or equal to the size or width of a CTU.
 - b. For example, **num_exp_tile_rows_minus1** and/or **tile_row_height_minus1** may not be signaled if the height of a picture is smaller than or equal to the size or height of a CTU.
14. There must be one and only one CurrSubpicIdx that satisfies SubpicIdVal[CurrSubpicIdx] is equal to slice_subpic_id when slice_subpic_id is present.
15. If rect_slice_flag is equal to 0 or subpic_info_present_flag is equal to 0, the value of slice_address + i , wherein i is in the range of 0 to num_tiles_in_slice_minus1, inclusively, shall not be equal to the value of slice_address + j , wherein j is in the range of 0 to num_tiles_in_slice_minus1, inclusively, of any other coded slice NAL unit of the same coded picture, wherein i is in the range .
16. In case that there are both uniform spacing tiles and non-uniform spacing tiles in pictures, a syntax element may be signaled in PPS (or SPS) to specify the type of tile layout.

- a. In one example, there may be a syntax flag signaled in PPS to specify whether the tile layout is non-uniform spacing followed by uniform spacing, or, uniform spacing followed by non-uniform spacing.
 - b. For example, whenever there are non-uniform spacing tiles, the number of explicitly provided tile columns/rows (e.g., **num_exp_tile_columns_minus1**, **num_exp_tile_rows_minus1**) may be NO less than the total number of non-uniform tiles.
 - c. For example, whenever there are uniform spacing tiles, the number of explicitly provided tile columns/rows (e.g., **num_exp_tile_columns_minus1**, **num_exp_tile_rows_minus1**) may be less or equal to the total number of uniform tiles.
 - d. If the tile layout is like uniform spacing followed by non-uniform spacing (i.e., a picture is starting with uniform spacing tiles and ended with multiple non-uniform spacing tiles),
 - i. In one example, the widths of tile columns for non-uniform spacing tiles located in the latter of picture may be firstly assigned in inverse order (i.e., with the order of the tile index equal to NumTileColumns, NumTileColumns - 1, NumTileColumns - 2,...), and then the widths of tile columns for uniform spacing tiles located in the former of picture may be implicitly derived in inverse order (i.e., with the order of the tile index equal to NumTileColumns - T, NumTileColumns - T - 1, ..., 2, 1, 0, where T indicate the number of non-uniform tile columns).
 - ii. The heights of tile rows may be derived in a same way of the width of tile columns as mentioned above.
17. The syntax element to specify the difference between the representative tile indices of two rectangular slices, wherein one of them is the i-th slice (e.g. `tile_idx_delta[ i ]`) can only be used when a condition is true.
- a. In one example, the condition is ($i < \text{num_slices_in_pic_minus1}$), wherein `num_slices_in_pic_minus1` plus 1 represents the number of slices in the picture.

- b. In one example, the condition is ($i \neq \text{num_slices_in_pic_minus1}$), wherein $\text{num_slices_in_pic_minus1} + 1$ represents the number of slices in the picture.
18. Whether to and/or how to signal or interpret or restrict the Merge Estimation Region (MER) size (e.g. signaled by **log2_parallel_merge_level_minus2**) may depend on the minimum allowed coding block size (e.g. signaled/denoted as **log2_min_luma_coding_block_size_minus2** and/or MinCbSizeY).
- a. In one example, it is required that the size of MER cannot be smaller than the minimum allowed coding block size.
- i. For example, it is required that **log2_parallel_merge_level_minus2** shall be equal to or larger than **log2_min_luma_coding_block_size_minus2**.
- ii. For example, it is required that **log2_parallel_merge_level_minus2** shall be in the range of **log2_min_luma_coding_block_size_minus2** to $\text{CtbLog2SizeY} - 2$.
- b. In one example, the difference between $\text{Log2}(\text{MER size})$ and $\text{Log2}(\text{MinCbSizeY})$ is signaled, which is denoted as **log2_parallel_merge_level_minus_log2_mincb**.
- i. For example, **log2_parallel_merge_level_minus_log2_mincb** is coded by a unary code (ue).
- ii. For example, it is required that **log2_parallel_merge_level_minus_log2_mincb** shall be in the range of 0 to $\text{CtbLog2SizeY} - \text{log2_min_luma_coding_block_size_minus2} - 2$.
- iii. For example, $\text{Log2ParMrgLevel} = \text{log2_parallel_merge_level_minus_log2_mincb} + \text{log2_min_luma_coding_block_size_minus2} + 2$, wherein Log2ParMrgLevel is used to control the MER size.
19. It is proposed that, when $\text{num_exp_slices_in_tile}[i]$ is equal to 0, the slice height in units of CTU rows for the i -th slice, e.g., denoted as $\text{sliceHeightInCtus}[i]$, is derived.
- a. In one example, $\text{sliceHeightInCtus}[i]$ is derived to be equal to $\text{RowHeight}[\text{SliceTopLeftTileIdx}[i] / \text{NumTileColumns}]$ when $\text{num_exp_slices_in_tile}[i]$ is equal to 0.

20. It is proposed that the $(\text{num_exp_slices_in_tile}[i] - 1)$ -th slice in the tile containing the i -th slice in a picture always exists and the height is always $\text{exp_slice_height_in_ctus_minus1}[i][\text{num_exp_slices_in_tile}[i] - 1] + 1$ CTU rows.
- a. Alternatively, the $(\text{num_exp_slices_in_tile}[i] - 1)$ -th slice in the tile containing the i -th slice in a picture may or may not exist and the height is less than or equal to $\text{exp_slice_height_in_ctus_minus1}[i][\text{num_exp_slices_in_tile}[i] - 1] + 1$ CTU rows.
21. It is proposed that, during the derivation of information for rectangular slices, the variable `tileIdx` is only updated for slices with picture-level slice index less than `num_slices_in_pic_minus1`, i.e., not updated for the last slice in each picture referring to the PPS.
22. It is proposed that the `num_exp_tile_columns_minus1`-th tile column always exists in pictures referring to the PPS and the width is always $\text{tile_column_width_minus1}[\text{num_exp_tile_columns_minus1}] + 1$ CTBs.
23. It is proposed that the `num_exp_tile_rows_minus1`-th tile row always exists in pictures referring to the PPS and the height is always $\text{tile_column_height_minus1}[\text{num_exp_tile_rows_minus1}] + 1$ CTBs.
24. It is proposed that, when the max picture width and the max picture height are both not greater than `CtbSizeY`, the signalling of the syntax element `sps_num_subpics_minus1` may be skipped.
- a. Alternatively, additionally, the value of `sps_num_subpics_minus1` is inferred to be equal to 0 when the above condition is true.
25. It is proposed that, when the picture width is not greater than `CtbSizeY`, the signalling of the syntax element `num_exp_tile_columns_minus1` may be skipped.
- b. Alternatively, additionally, the value of `num_exp_tile_columns_minus1` is inferred to be equal to 0 when the above condition is true.
26. It is proposed that, when the picture height is not greater than `CtbSizeY`, the signalling of the syntax element `num_exp_tile_rows_minus1` may be skipped.
- c. Alternatively, additionally, the value of `num_exp_tile_row_minus1` is inferred to be equal to 0 when the above condition is true.

27. It is proposed that, when `num_exp_tile_columns_minus1` is equal to `PicWidthInCtbsY - 1`, the signalling of the syntax elements `tile_column_width_minus1[ i ]` for `i` ranging from 0 to `num_exp_tile_columns_minus1`, inclusive, may be skipped.
- d. Alternatively, additionally, the value of `tile_column_width_minus1[ i ]` is inferred to be equal to 0.
28. It is proposed that, when `num_exp_tile_rows_minus1` is equal to `PicHeightInCtbsY - 1`, the signalling of the syntax elements `tile_row_height_minus1[ i ]` for `i` ranging from 0 to `num_exp_tile_rows_minus1`, inclusive, may be skipped.
- e. Alternatively, additionally, the value of `tile_row_height_minus1[ i ]` is inferred to be equal to 0.
29. It is proposed that the height of uniform slices that partition a tile is indicated by the last entry of `exp_slice_height_in_ctus_minus1[ ]`s that indicate height of slices in that tile. Uniform slices are slices below slices explicitly signaled. For example:
- $$\text{uniformSliceHeight} = \text{exp_slice_height_in_ctus_minus1}[i][\text{num_exp_slices_in_tile}[i] - 1] + 1$$
30. It is proposed that the width of '`num_exp_tile_columns_minus1`'-th tile column is disallowed to be reset, that is, the parsed value from the bitstream (e.g., denoted by **`tile_column_width_minus1[num_exp_tile_columns_minus1]`**) may be directly used to derive the width without referring other information.
- a. In one example, the width of '`num_exp_tile_columns_minus1`'-th tile column is directly set to **`tile_column_width_minus1[num_exp_tile_columns_minus1]`** plus 1. Alternatively, furthermore, **`tile_column_width_minus1[num_exp_tile_columns_minus1]`** is used to derive the width of the tile columns with index greater than `num_exp_tile_columns_minus1`, e.g., as specified in clause 6.5.1.
- b. Similarly, for the height of '`num_exp_tile_columns_minus1`'-th tile row is disallowed to be reset, that is, the parsed value from the bitstream (e.g., denoted by **`tile_row_height_minus1[num_exp_tile_columns_minus1]`**) may be directly used to derive the height without referring other information.

- i. In one example, the height of 'num_exp_tile_columns_minus1'-th tile row is directly set to **tile_row_height_minus1[num_exp_tile_columns_minus1]** plus 1. Alternatively, furthermore, **tile_row_height_minus1[num_exp_tile_columns_minus1]** is used to derive the height of the tile rows with index greater than num_exp_tile_columns_minus1, e.g., as specified in clause 6.5.1.
31. It is proposed that the height of the (num_exp_slices_in_tile[i] - 1)-th slice in a tile is disallowed to be reset, that is, the parsed value from the bitstream (e.g., denoted by exp_slice_height_in_ctus_minus1[i] [num_exp_slices_in_tile[i] - 1]) may be directly used to derive the height without referring other information.
- a. In one example, the height of the (num_exp_slices_in_tile[i] - 1)-th slice in a tile is directly set to exp_slice_height_in_ctus_minus1[i] [num_exp_slices_in_tile[i] - 1] plus 1. Alternatively, furthermore, exp_slice_height_in_ctus_minus1[i] [num_exp_slices_in_tile[i] - 1] is used to derive the height of the slices with index greater than num_exp_slices_in_tile[i] - 1.

6. Embodiments

[00100] In the embodiments below, the added portions are marked as bold, underlined, and italicized texts. The deleted portions are marked within [[]].

6.1. Embodiment 1: example subpicture level slice index changes

3 Definitions

picture-level slice index: [[An]] *The* index of a slice to the list of slices in a picture in the order as they are signalled in the PPS when the rect_slice_flag is equal to 1.

[[subpicture-level slice index: An index of a slice to the list of slices in a subpicture in the order as they are signalled in the PPS when the rect_slice_flag is equal to 1.]]

subpicture-level slice index: The index of a slice to the list of slices in a subpicture in their decoding order when the rect slice flag is equal to 1.

6.5.1 CTB raster scanning, tile scanning, and subpicture scanning processes

...
 [[The list NumSlicesInSubpic[i], specifying the number of rectangular slices in the i-th subpicture,]] *The variable NumSlicesInSubpic[j], specifying the number of rectangular slices in the j-th subpicture, the variable SubpicIdxOfSlice[i], specifying the subpicture index of the slice with picture-level slice index i, the variable*

SubpicLevelSliceIdx[i], specifying the subpicture-level slice index of the slice with picture-level slice index i, and the variable PicLevelSliceIdx[m][n], specifying the picture-level slice index for the slice with subpicture-level slice index n in the m-th subpicture, are [[is]] derived as follows:

```

for( j = 0; j <= sps_num_subpics_minus1; j++ )
    NumSlicesInSubpic[ j ] = 0
for( i = 0; i <= num_slices_in_pic_minus1; i++ ) {
    posX = CtbAddrInSlice[ i ][ 0 ] % PicWidthInCtbsY
    posY = CtbAddrInSlice[ i ][ 0 ] / PicWidthInCtbsY
    for( j = 0; j <= sps_num_subpics_minus1; j++ ) {
        if( ( posX >= subpic_ctu_top_left_x[ j ] ) &&
            ( posX < subpic_ctu_top_left_x[ j ] + subpic_width_minus1[ j ] + 1 ) &&
            ( posY >= subpic_ctu_top_left_y[ j ] ) &&
            ( posY < subpic_ctu_top_left_y[ j ] + subpic_height_minus1[ j ] + 1 ) ) {
            SubpicIdxOfSlice[ i ] = j
            SubpicLevelSliceIdx[ i ] = NumSlicesInSubpic[ j ]
            PicLevelSliceIdx[ j ][ SubpicLevelSliceIdx[ i ] ] = i
            NumSlicesInSubpic[ j ]++
        }
    }
}
...

```

7.4.8.1 General slice header semantics

...

slice_address specifies the slice address of the slice. When not present, the value of slice_address is inferred to be equal to 0. When rect_slice_flag is equal to 1 and NumSlicesInSubpic[CurrSubpicIdx] is equal to 1, the value of slice_address is inferred to be equal to 0.

If rect_slice_flag is equal to 0, the following applies:

- The slice address is the raster scan tile index.
- The length of slice_address is Ceil(Log2(NumTilesInPic)) bits.
- The value of slice_address shall be in the range of 0 to NumTilesInPic – 1, inclusive.

Otherwise (rect_slice_flag is equal to 1), the following applies:

- The slice address is the subpicture-level slice index of the slice as specified by the variable SubpicLevelSliceIdx[i] derived in Equation 32, where i is the picture-level slice index of the slice.
- The length of slice_address is Ceil(Log2(NumSlicesInSubpic[CurrSubpicIdx])) bits.
- The value of slice_address shall be in the range of 0 to NumSlicesInSubpic[CurrSubpicIdx] – 1, inclusive.

It is a requirement of bitstream conformance that the following constraints apply:

- If `rect_slice_flag` is equal to 0 or `subpic_info_present_flag` is equal to 0, the value of `slice_address` shall not be equal to the value of `slice_address` of any other coded slice NAL unit of the same coded picture.
- Otherwise, the pair of `slice_subpic_id` and `slice_address` values shall not be equal to the pair of `slice_subpic_id` and `slice_address` values of any other coded slice NAL unit of the same coded picture.
- The shapes of the slices of a picture shall be such that each CTU, when decoded, shall have its entire left boundary and entire top boundary consisting of a picture boundary or consisting of boundaries of previously decoded CTU(s).

...

`num_tiles_in_slice_minus1` plus 1, when present, specifies the number of tiles in the slice. The value of `num_tiles_in_slice_minus1` shall be in the range of 0 to `NumTilesInPic - 1`, inclusive.

The variable `NumCtusInCurrSlice`, which specifies the number of CTUs in the current slice, and the list `CtbAddrInCurrSlice[ i ]`, for `i` ranging from 0 to `NumCtusInCurrSlice - 1`, inclusive, specifying the picture raster scan address of the `i`-th CTB within the slice, are derived as follows:

```

if( rect_slice_flag ) {
    picLevelSliceIdx = PicLevelSliceIdx / CurrSubpicIdx // slice_address /
    [[ for( j = 0; j < CurrSubpicIdx; j++ )
        picLevelSliceIdx += NumSlicesInSubpic[ j ] ] ]
    NumCtusInCurrSlice = NumCtusInSlice[ picLevelSliceIdx ]
    for( i = 0; i < NumCtusInCurrSlice; i++ )
        CtbAddrInCurrSlice[ i ] = CtbAddrInSlice[ picLevelSliceIdx ][ i ]
} else {
    NumCtusInCurrSlice = 0
    for( tileIdx = slice_address; tileIdx <= slice_address + num_tiles_in_slice_minus1; tileIdx++ ) {
        tileX = tileIdx % NumTileColumns
        tileY = tileIdx / NumTileColumns
        for( ctbY = tileRowBd[ tileY ]; ctbY < tileRowBd[ tileY + 1 ]; ctbY++ ) {
            for( ctbX = tileColBd[ tileX ]; ctbX < tileColBd[ tileX + 1 ]; ctbX++ ) {
                CtbAddrInCurrSlice[ NumCtusInCurrSlice ] = ctbY * PicWidthInCtb + ctbX
                NumCtusInCurrSlice++
            }
        }
    }
}

```

(117)

...

6.2. Embodiment 2: Signaling slices in PPS for non-rectangular mode

7.3.2.4 Picture parameter set RBSP syntax

	Descriptor
pic_parameter_set_rbsp() {	
pps_pic_parameter_set_id	ue(v)
...	
no_pic_partition_flag	u(1)
if(!no_pic_partition_flag) {	
pps_log2_ctu_size_minus5	u(2)
num_exp_tile_columns_minus1	ue(v)
num_exp_tile_rows_minus1	ue(v)
for(i = 0; i <= num_exp_tile_columns_minus1; i++)	
tile_column_width_minus1[i]	ue(v)
for(i = 0; i <= num_exp_tile_rows_minus1; i++)	
tile_row_height_minus1[i]	ue(v)
if(NumTilesInPic > 1)	
rect_slice_flag	u(1)
if(rect_slice_flag)	
single_slice_per_subpic_flag	u(1)
<u>if(!single_slice_per_subpic_flag)</u>	
<u>num_slices_in_pic_minus1</u>	<u>ue(v)</u>
<u>if(!rect_slice_flag) {</u>	
<u>for(i = 0; i < num_slices_in_pic_minus1; i++)</u>	
<u>num_tiles_in_slice_minus1[i]</u>	<u>ue(v)</u>
<u>}</u>	
<u>else</u> if([[rect_slice_flag &&]] !single_slice_per_subpic_flag) {	
[[num_slices_in_pic_minus1	ue(v)]]
if(num_slices_in_pic_minus1 > 0)	
tile_idx_delta_present_flag	u(1)
for(i = 0; i < num_slices_in_pic_minus1; i++) {	
if(NumTileColumns > 1)	
slice_width_in_tiles_minus1[i]	ue(v)
if(NumTileRows > 1 && (tile_idx_delta_present_flag tileIdx % NumTileColumns == 0))	
slice_height_in_tiles_minus1[i]	ue(v)
if(slice_width_in_tiles_minus1[i] == 0 && slice_height_in_tiles_minus1[i] == 0 && RowHeight[SliceTopLeftTileIdx[i] / NumTileColumns] > 1) {	

num_exp_slices_in_tile[i]	ue(v)
numExpSlicesInTile = num_exp_slices_in_tile[i]	
for(j = 0; j < numExpSlicesInTile; j++)	
exp_slice_height_in_ctus_minus1[j]	ue(v)
i += NumSlicesInTile[i]	
}	
if(tile_idx_delta_present_flag && i < num_slices_in_pic_minus1)	
tile_idx_delta[i]	se(v)
}	
}	
loop_filter_across_tiles_enabled_flag	u(1)
loop_filter_across_slices_enabled_flag	u(1)
}	

7.3.7.1 General slice header syntax

slice_header() {	Descriptor
picture_header_in_slice_header_flag	u(1)
if(picture_header_in_slice_header_flag)	
picture_header_structure()	
if(subpic_info_present_flag)	
slice_subpic_id	u(v)
if((rect_slice_flag && NumSlicesInSubpic[CurrSubpicIdx] > 1) (!rect_slice_flag && <u>NumSlicesInPic</u> [[NumTilesInPic]] > 1))	
slice_address	u(v)
for(I = 0; I < NumExtraPhBits; i++)	
sh_extra_bit[I]	u(1)
[[if(!rect_slice_flag && NumTilesInPic > 1)	
num_tiles_in_slice_minus1	ue(v)]]
if(ph_inter_slice_allowed_flag)	
slice_type	ue(v)
...	

7.4.3.4 Picture parameter set RBSP semantics

num_slices_in_pic_minus1 plus 1 specifies the number of [[rectangular]] slices in each picture referring to the PPS. The value of **num_slices_in_pic_minus1** shall be in the range of 0 to **MaxSlicesPerPicture** – 1, inclusive, where

MaxSlicesPerPicture is specified in Annex A. When no_pic_partition_flag is equal to 1, the value of num_slices_in_pic_minus1 is inferred to be equal to 0. NumSlicesInPic is set equal to be

num_slices_in_pic_minus1 + 1.

num_tiles_in_slice_minus1[i] plus 1, when present, specifies the number of tiles in the slice with the picture-level slice index equal to i. The value of num_tiles_in_slice_minus1[i] shall be in the range of 0 to NumTilesInPic - 1, inclusive.

The array FirstTileInSlice[i] specifying the tile index of the first tile in a slice with the picture-level slice index equal to i, and The array NumTileInSlice[i] specifying the number of tiles in a slice with the picture-level slice index equal to i are derived as follows when rect_slice_flag is equal to 0:

FirstTileInSlice[0] = 0

CurrNumSlices = 0

for(i = 0; i < num_slices_in_pic_minus1; i++){

NumTileInSlice[i] = num_tiles_in_slice_minus1[i] + 1

CurrNumSlices = CurrNumSlices + NumTileInSlice[i]

FirstTileInSlice[i + 1] = FirstTileInSlice[i] + NumTileInSlice[i]

}

NumTileInSlice[num_slices_in_pic_minus1] = NumTilesInPic - CurrNumSlices

FirstTileInSlice[i] shall be no smaller than 0 and not bigger than NumTilesInPic - 1.

NumTileInSlice[i] shall be no smaller than 1 and not bigger than NumTilesInPic.

The sum of NumTileInSlice[i] for i from 0 to NumSlicesInPic shall be equal to NumTilesInPic.

...

7.4.8.1 General slice header semantics

...

slice_address specifies the slice address of the slice. When not present, the value of slice_address is inferred to be equal to 0. When rect_slice_flag is equal to 1 and NumSlicesInSubpic[CurrSubpicIdx] is equal to 1, the value of slice_address is inferred to be equal to 0. When rect_slice_flag is equal to 0 and NumSlicesInPic is equal to 1, the value of slice_address is inferred to be equal to 0

If rect_slice_flag is equal to 0, the following applies:

- The slice address is the picture-level slice index of the slice [[raster scan tile index]].
- The length of slice_address is Ceil(Log2 (NumSlicesInPic [[NumTilesInPic]])) bits.
- The value of slice_address shall be in the range of 0 to NumSlicesInPic [[NumTilesInPic]] - 1, inclusive.

Otherwise (rect_slice_flag is equal to 1), the following applies:

- The slice address is the subpicture-level slice index of the slice.
- The length of slice_address is Ceil(Log2(NumSlicesInSubpic[CurrSubpicIdx])) bits.
- The value of slice_address shall be in the range of 0 to NumSlicesInSubpic[CurrSubpicIdx] - 1, inclusive.

It is a requirement of bitstream conformance that the following constraints apply:

- [[If rect_slice_flag is equal to 0 or subpic_info_present_flag is equal to 0, the value of slice_address shall not be equal to the value of slice_address of any other coded slice NAL unit of the same coded picture.
- Otherwise,]] If rect_slice_flag is equal to 1, the pair of slice_subpic_id and slice_address values shall not be equal to the pair of slice_subpic_id and slice_address values of any other coded slice NAL unit of the same coded picture.
- The shapes of the slices of a picture shall be such that each CTU, when decoded, shall have its entire left boundary and entire top boundary consisting of a picture boundary or consisting of boundaries of previously decoded CTU(s).

...

The variable NumCtusInCurrSlice, which specifies the number of CTUs in the current slice, and the list CtbAddrInCurrSlice[i], for i ranging from 0 to NumCtusInCurrSlice – 1, inclusive, specifying the picture raster scan address of the i-th CTB within the slice, are derived as follows:

```

if( rect_slice_flag ) {
    picLevelSliceIdx = slice_address
    for( j = 0; j < CurrSubpicIdx; j++ )
        picLevelSliceIdx += NumSlicesInSubpic[ j ]
    NumCtusInCurrSlice = NumCtusInSlice[ picLevelSliceIdx ]
    for( i = 0; i < NumCtusInCurrSlice; i++ )
        CtbAddrInCurrSlice[ i ] = CtbAddrInSlice[ picLevelSliceIdx ][ i ]
} else {
    NumCtusInCurrSlice = 0
    for( tileIdx = FirstTileInSlice slice_address L; tileIdx [[<=]] < FirstTileInSlice
slice_address L + NumTileInSlice slice_address L [[num_tiles_in_slice_minus1]]; tileIdx++ ) {
        tileX = tileIdx % NumTileColumns
        tileY = tileIdx / NumTileColumns
        for( ctbY = tileRowBd[ tileY ]; ctbY < tileRowBd[ tileY + 1 ]; ctbY++ ) {
            for( ctbX = tileColBd[ tileX ]; ctbX < tileColBd[ tileX + 1 ]; ctbX++ ) {
                CtbAddrInCurrSlice[ NumCtusInCurrSlice ] = ctbY * PicWidthInCtb + ctbX
                NumCtusInCurrSlice++
            }
        }
    }
}

```

6.3. Embodiment 3: Signaling tiles conditioned on picture dimensions

7.3.2.4 Picture parameter set RBSP syntax

pic_parameter_set_rbsp() {	Descriptor
-----------------------------	------------

pps_pic_parameter_set_id	ue(v)
...	
no_pic_partition_flag	u(1)
if(!no_pic_partition_flag) {	
pps_log2_ctu_size_minus5	u(2)
[[num_exp_tile_columns_minus1	ue(v)
num_exp_tile_rows_minus1	ue(v)
for(i = 0; i <= num_exp_tile_columns_minus1; i++)	
tile_column_width_minus1[i]	ue(v)
for(i = 0; i <= num_exp_tile_rows_minus1; i++)	
tile_row_height_minus1[i]	ue(v)]]
<u>if(pic_width_in_luma_samples > CtbSizeY) {</u>	
<u>num_exp_tile_columns_minus1</u>	<u>ue(v)</u>
<u>for(i = 0; i <= num_exp_tile_columns_minus1; i++)</u>	
<u>tile_column_width_minus1[i]</u>	<u>ue(v)</u>
<u>}</u>	
<u>if(pic_height_in_luma_samples > CtbSizeY) {</u>	
<u>num_exp_tile_rows_minus1</u>	<u>ue(v)</u>
<u>for(i = 0; i <= num_exp_tile_rows_minus1; i++)</u>	
<u>tile_row_height_minus1[i]</u>	<u>ue(v)</u>
<u>}</u>	
if(NumTilesInPic > 1)	
rect_slice_flag	u(1)
if(rect_slice_flag)	
single_slice_per_subpic_flag	u(1)
if(rect_slice_flag && !single_slice_per_subpic_flag) {	
num_slices_in_pic_minus1	ue(v)
if(num_slices_in_pic_minus1 > 0)	
tile_idx_delta_present_flag	u(1)
for(i = 0; i < num_slices_in_pic_minus1; i++) {	
if(NumTileColumns > 1)	
slice_width_in_tiles_minus1[i]	ue(v)
if(NumTileRows > 1 && (tile_idx_delta_present_flag tileIdx % NumTileColumns == 0))	
slice_height_in_tiles_minus1[i]	ue(v)

if(slice_width_in_tiles_minus1[i] == 0 && slice_height_in_tiles_minus1[i] == 0 && RowHeight[SliceTopLeftTileIdx[i] / NumTileColumns] > 1) {	
num_exp_slices_in_tile[i]	ue(v)
numExpSlicesInTile = num_exp_slices_in_tile[i]	
for(j = 0; j < numExpSlicesInTile; j++)	
exp_slice_height_in_ctus_minus1[j]	ue(v)
i += NumSlicesInTile[i]	
}	
if(tile_idx_delta_present_flag && i < num_slices_in_pic_minus1)	
tile_idx_delta[i]	se(v)
}	
}	
loop_filter_across_tiles_enabled_flag	u(1)
loop_filter_across_slices_enabled_flag	u(1)
}	
...	

6.4. Embodiment 4: Example 1 of semantics on tile_column_width_minus1 and tile_row_height_minus1

7.4.3.4 Picture parameter set RBSP semantics

...

tile_column_width_minus1[i] plus 1 specifies the width of the i-th tile column in units of CTBs for i in the range of 0 to num_exp_tile_columns_minus1 - 1, inclusive, when num_exp_tile_columns_minus1 is larger than 0.

tile_column_width_minus1[num_exp_tile_columns_minus1] is used to derive the width of the tile columns with index greater than or equal to num_exp_tile_columns_minus1 as specified in clause 6.5.1. The value of tile_column_width_minus1[i] shall be in the range of 0 to PicWidthInCtbsY - 1, inclusive. When not present, the value of tile_column_width_minus1[0] is inferred to be equal to PicWidthInCtbsY - 1.

tile_row_height_minus1[i] plus 1 specifies the height of the i-th tile row in units of CTBs for i in the range of 0 to num_exp_tile_rows_minus1 - 1, inclusive, when num_exp_tile_rows_minus1 is larger than 0.

tile_row_height_minus1[num_exp_tile_rows_minus1] is used to derive the height of the tile rows with index greater than or equal to num_exp_tile_rows_minus1 as specified in clause 6.5.1. The value of tile_row_height_minus1[i] shall be in the range of 0 to PicHeightInCtbsY - 1, inclusive. When not present, the value of tile_row_height_minus1[0] is inferred to be equal to PicHeightInCtbsY - 1.

...

6.5. Embodiment 5: Example 2 of semantics on tile_column_width_minus1 and tile_row_height_minus1

7.4.3.4 Picture parameter set RBSP semantics

...

tile_column_width_minus1[*i*] plus 1 specifies the width of the *i*-th tile column in units of CTBs for *i* in the range of 0 to Max(0, num_exp_tile_columns_minus1 - 1), inclusive.

tile_column_width_minus1[num_exp_tile_columns_minus1] is used to derive the width of the tile columns with index greater than or equal to num_exp_tile_columns_minus1 as specified in clause 6.5.1. The value of **tile_column_width_minus1**[*i*] shall be in the range of 0 to PicWidthInCtbsY - 1, inclusive. When not present, the value of **tile_column_width_minus1**[0] is inferred to be equal to PicWidthInCtbsY - 1.

tile_row_height_minus1[*i*] plus 1 specifies the height of the *i*-th tile row in units of CTBs for *i* in the range of 0 to Max(0, num_exp_tile_rows_minus1 - 1), inclusive. **tile_row_height_minus1**[num_exp_tile_rows_minus1] is used to derive the height of the tile rows with index greater than or equal to num_exp_tile_rows_minus1 as specified in clause 6.5.1. The value of **tile_row_height_minus1**[*i*] shall be in the range of 0 to PicHeightInCtbsY - 1, inclusive. When not present, the value of **tile_row_height_minus1**[0] is inferred to be equal to PicHeightInCtbsY - 1.

...

6.6. Embodiment 6: Example derivation of CTUs in slices

6.5 Scanning processes

6.5.1 CTB raster scanning, tile scanning, and subpicture scanning processes

...

For rectangular slices, the list **NumCtusInSlice**[*i*] for *i* ranging from 0 to num_slices_in_pic_minus1, inclusive, specifying the number of CTU in the *i*-th slice, the list **SliceTopLeftTileIdx**[*i*] for *i* ranging from 0 to num_slices_in_pic_minus1, inclusive, specifying the index of the top-left tile of the slice, and the matrix **CtbAddrInSlice**[*i*][*j*] for *i* ranging from 0 to num_slices_in_pic_minus1, inclusive, and *j* ranging from 0 to **NumCtusInSlice**[*i*] - 1, inclusive, specifying the picture raster scan address of the *j*-th CTB within the *i*-th slice, are derived as follows:

```

if( single_slice_per_subpic_flag ) {
    for( i = 0; i <= sps_num_subpics_minus1; i++ )
        NumCtusInSlice[ i ] = 0
    for( i = 0; i < PicSizeInCtbsY; i++ ) {
        sliceIdx = subpic_info_present_flag ? CtbToSubpicIdx[ i ] : 0
        CtbAddrInSlice[ sliceIdx ][ NumCtusInSlice[ sliceIdx ] ] = i
        NumCtusInSlice[ sliceIdx ]++
    }
} else {

```

```

tileIdx = 0
for( i = 0; i <= num_slices_in_pic_minus1; i++ )
    NumCtusInSlice[ i ] = 0
for( i = 0; i <= num_slices_in_pic_minus1; i++ ) {
    SliceTopLeftTileIdx[ i ] = tileIdx
    tileX = tileIdx % NumTileColumns
    tileY = tileIdx / NumTileColumns
    if( i == num_slices_in_pic_minus1 ) {
        slice_width_in_tiles_minus1[ i ] = NumTileColumns - 1 - tileX
        slice_height_in_tiles_minus1[ i ] = NumTileRows - 1 - tileY
    }
    if( slice_width_in_tiles_minus1[ i ] == 0 && slice_height_in_tiles_minus1[ i ] == 0 ) { (29)
        ctbY = tileRowBd[ tileY ]
        for( j = 0; j < NumSlicesInTile[ i ] - 1; j++ ) {
            AddCtbsToSlice( i, tileColBd[ tileX ], tileColBd[ tileX + 1 ],
                           ctbY, ctbY + SliceHeightInCtusMinus1[ i ] + 1 )
            ctbY += SliceHeightInCtusMinus1[ i ] + 1
            i++
        }
        AddCtbsToSlice( i, tileColBd[ tileX ], tileColBd[ tileX + 1 ], ctbY, tileRowBd[ tileY + 1 ] )
    } else
        for( j = 0; j <= slice_height_in_tiles_minus1[ i ]; j++ )
            for( k = 0; k <= slice_width_in_tiles_minus1[ i ]; k++ )
                AddCtbsToSlice( i, tileColBd[ tileX + k ], tileColBd[ tileX + k + 1 ],
                               tileRowBd[ tileY + j ], tileRowBd[ tileY + j + 1 ] )
    if( i < num_slices_in_pic_minus1 ) {
        if( tile_idx_delta_present_flag )
            tileIdx += tile_idx_delta[ i ]
        else {
            tileIdx += slice_width_in_tiles_minus1[ i ] + 1
            if( tileIdx % NumTileColumns == 0 )
                tileIdx += slice_height_in_tiles_minus1[ i ] * NumTileColumns
        }
    }
}
}

```

6.7. Embodiment 7: About signaling of MER size

7.3.2.3 Sequence parameter set RBSP syntax

seq_parameter_set_rbsp() {	Descriptor
sps_seq_parameter_set_id	u(4)
...	
log2_parallel_merge_level_minus_log2_mincb	ue(v)
...	
}	

7.4.3.3 Sequence parameter set RBSP semantics

log2_parallel_merge_level_minus_log2_mincb plus $\log_2 \text{min_luma_coding_block_size_minus2} + 2$ specifies the value of the variable **Log2ParMrgLevel**, which is used in the derivation process for spatial merging candidates as specified in clause 8.5.2.3, the derivation process for motion vectors and reference indices in subblock merge mode as specified in clause 8.5.5.2, and to control the invocation of the updating process for the history-based motion vector predictor list in clause 8.5.2.1. The value of **log2_parallel_merge_level_minus_log2_mincb** shall be in the range of 0 to $\text{CtbLog2SizeY} - \log_2 \text{min_luma_coding_block_size_minus2} - 2$, inclusive. The variable **Log2ParMrgLevel** is derived as follows:

$$\text{Log2ParMrgLevel} = \text{log2_parallel_merge_level_minus2} + \log_2 \text{min_luma_coding_block_size_minus2} + 2 \quad (68)$$

6.8. Embodiment 8: About signaling of rectangular slices

6.5.1 CTB raster scanning, tile scanning, and subpicture scanning processes

...

The list **ctbToSubpicIdx[ctbAddrRs]** for **ctbAddrRs** ranging from 0 to $\text{PicSizeInCtbsY} - 1$, inclusive, specifying the conversion from a CTB address in picture raster scan to a subpicture index, is derived as follows:

```
for( ctbAddrRs = 0; ctbAddrRs < PicSizeInCtbsY; ctbAddrRs++ ) {
    posX = ctbAddrRs % PicWidthInCtbsY
    posY = ctbAddrRs / PicWidthInCtbsY
    ctbToSubpicIdx[ ctbAddrRs ] = -1
    for( i = 0; ctbToSubpicIdx[ ctbAddrRs ] < 0 && i <= sps_num_subpics_minus1; i++ ) {
        if( ( posX >= subpic_ctu_top_left_x[ i ] ) &&
            ( posX < subpic_ctu_top_left_x[ i ] + subpic_width_minus1[ i ] + 1 ) &&
            ( posY >= subpic_ctu_top_left_y[ i ] ) &&
            ( posY < subpic_ctu_top_left_y[ i ] + subpic_height_minus1[ i ] + 1 ) )
            ctbToSubpicIdx[ ctbAddrRs ] = i
    }
}
```

When rect_slice_flag is equal to 1, the list NumCtusInSlice[i] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, specifying the number of CTUs in the i-th slice, the list SliceTopLeftTileIdx[i] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, specifying the tile index of the tile containing the first CTU in the slice, and the matrix CtbAddrInSlice[i][j] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, and j ranging from 0 to NumCtusInSlice[i] - 1, inclusive, specifying the picture raster scan address of the j-th CTB within the i-th slice, the variable NumSlicesInTile[i], specifying the number of slices in the tile containing the i-th slice (i.e., the tile with tile index equal to SliceTopLeftTileIdx[i]), are derived as follows:

```

if( single_slice_per_subpic_flag ) {
    for( i = 0; i <= sps_num_subpics_minus1; i++ )
        NumCtusInSlice[ i ] = 0
    for( i = 0; i < PicSizeInCtbsY; i++ ) {
        sliceIdx = ctbToSubpicIdx[ i ]
        CtbAddrInSlice[ sliceIdx ][ NumCtusInSlice[ sliceIdx ] ] = i
        NumCtusInSlice[ sliceIdx ]++
    }
} else {
    tileIdx = 0
    for( i = 0; i <= num_slices_in_pic_minus1; i++ )
        NumCtusInSlice[ i ] = 0
    for( i = 0; i <= num_slices_in_pic_minus1; i++ ) {
        SliceTopLeftTileIdx[ i ] = tileIdx
        tileX = tileIdx % NumTileColumns
        tileY = tileIdx / NumTileColumns
        if( i < num_slices_in_pic_minus1 ) {
            sliceWidthInTiles[ i ] = slice_width_in_tiles_minus1[ i ] + 1
            sliceHeightInTiles[ i ] = slice_height_in_tiles_minus1[ i ] + 1
        } else {
            sliceWidthInTiles[ i ] = NumTileColumns - tileX
            sliceHeightInTiles[ i ] = NumTileRows - tileY
            NumSlicesInTile[ i ] = 1
        }
        if( sliceWidthInTiles[ i ] == 1 && sliceHeightInTiles[ i ] == 1 ) {
            if( num_exp_slices_in_tile[ i ] == 0 ) {
                NumSlicesInTile[ i ] = 1
                sliceHeightInCtus[ i ] = RowHeight[ SliceTopLeftTileIdx[ i ] / NumTileColumns ]
            }
        }
    }
}

```

(30)

```

else {
    remainingHeightInCtbsY = RowHeight[ SliceTopLeftTileIdx[ i ] / NumTileColumns ]
    for( j = 0; j < num_exp_slices_in_tile[ i ]; j++ ) {
        sliceHeightInCtus[ i + j ] = exp_slice_height_in_ctus_minus1[ i ][ j ] + 1
        remainingHeightInCtbsY -= sliceHeightInCtus[ i + j ]
    }
    uniformSliceHeight = sliceHeightInCtus[ i + j - 1 ]
    while( remainingHeightInCtbsY >= uniformSliceHeight ) {
        sliceHeightInCtus[ i + j ] = uniformSliceHeight
        remainingHeightInCtbsY -= uniformSliceHeight
        j++
    }
    if( remainingHeightInCtbsY > 0 ) {
        sliceHeightInCtus[ i + j ] = remainingHeightInCtbsY
        j++
    }
    NumSlicesInTile[ i ] = j
}
ctbY = tileRowBd[ tileY ]
for( j = 0; j < NumSlicesInTile[ i ] - 1; j++ ) {
    AddCtbsToSlice( i, tileColBd[ tileX ], tileColBd[ tileX + 1 ],
        ctbY, ctbY + sliceHeightInCtus[ i ] )
    ctbY += sliceHeightInCtus[ i ]
    i++
}
AddCtbsToSlice( i, tileColBd[ tileX ], tileColBd[ tileX + 1 ], ctbY, tileRowBd[ tileY + 1 ] )
} else
    for( j = 0; j < sliceHeightInTiles[ i ]; j++ )
        for( k = 0; k < sliceWidthInTiles[ i ]; k++ )
            AddCtbsToSlice( i, tileColBd[ tileX + k ], tileColBd[ tileX + k + 1 ],
                tileRowBd[ tileY + j ], tileRowBd[ tileY + j + 1 ] )
if( i < num_slices_in_pic_minus1 ) {
    if( tile_idx_delta_present_flag )
        tileIdx += tile_idx_delta[ i ]
    else {
        tileIdx += sliceWidthInTiles[ i ]
    }

```

```

        if( tileIdx % NumTileColumns == 0 )
            tileIdx += ( sliceHeightInTiles[ i ] - 1 ) * NumTileColumns
    }
    }
}

```

It is a requirement of bitstream conformance that the values of NumCtusInSlice[i] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, shall be greater than 0. Additionally, it is a requirement of bitstream conformance that the matrix CtbAddrInSlice[i][j] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, and j ranging from 0 to NumCtusInSlice[i] - 1, inclusive, shall include each of all CTB addresses in the range of 0 to PicSizeInCtbsY - 1, inclusive, once and only once.

...

7.3.2.4 Picture parameter set RBSP syntax

pic_parameter_set_rbsp() {	Descriptor
...	
if(rect_slice_flag && !single_slice_per_subpic_flag) {	
num_slices_in_pic_minus1	ue(v)
if(num_slices_in_pic_minus1 > 0)	
tile_idx_delta_present_flag	u(1)
for(i = 0; i < num_slices_in_pic_minus1; i++) {	
if(NumTileColumns > 1)	
slice_width_in_tiles_minus1[i]	ue(v)
if(NumTileRows > 1 && (tile_idx_delta_present_flag <u><i>SliceTopLeftTileIdx[i]</i></u> % NumTileColumns == 0))	
slice_height_in_tiles_minus1[i]	ue(v)
if(slice_width_in_tiles_minus1[i] == 0 && slice_height_in_tiles_minus1[i] == 0 && RowHeight[<u><i>SliceTopLeftTileIdx[i]</i></u> / NumTileColumns] > 1) {	
num_exp_slices_in_tile[i]	ue(v)
for(j = 0; j < num_exp_slices_in_tile[i]; j++)	
exp_slice_height_in_ctus_minus1[<u><i>i</i></u>][j]	ue(v)
i += NumSlicesInTile[i] - 1	
}	
}	
if(tile_idx_delta_present_flag && i < num_slices_in_pic_minus1)	
tile_idx_delta[i]	se(v)

}	
}	
...	
}	

7.4.3.4 Picture parameter set semantics

...

tile_idx_delta_present_flag equal to 0 specifies that **tile_idx_delta[i]** syntax elements are not present in the PPS and all pictures referring to the PPS are partitioned into rectangular slice rows and rectangular slice columns in slice raster order. **tile_idx_delta_present_flag** equal to 1 specifies that **tile_idx_delta[i]** syntax elements may be present in the PPS and all rectangular slices in pictures referring to the PPS are specified in the order indicated by the values of the **tile_idx_delta[i]** in increasing values of *i*. When not present, the value of **tile_idx_delta_present_flag** is inferred to be equal to 0.

slice_width_in_tiles_minus1[i] plus 1 specifies the width of the *i*-th rectangular slice in units of tile columns. The value of **slice_width_in_tiles_minus1[i]** shall be in the range of 0 to **NumTileColumns** – 1, inclusive.

When *i* is less than **num_slices_in_pic_minus1** and **NumTileColumns** is equal to 1, the value of **slice_width_in_tiles_minus1[i]** is inferred to be equal to 0.

slice_height_in_tiles_minus1[i] plus 1 specifies the height of the *i*-th rectangular slice in units of tile rows when **num_exp_slices_in_tile[i]** is equal to 0. The value of **slice_height_in_tiles_minus1[i]** shall be in the range of 0 to **NumTileRows** – 1, inclusive.

When *i* is less than **num_slices_in_pic_minus1** and **slice_height_in_tiles_minus1[i]** is not present, it is inferred to be equal to **NumTileRows** – 1.

num_exp_slices_in_tile[i] specifies the number of explicitly provided slice heights for the slices in the tile containing the *i*-th slice (i.e., the tile with tile index equal to **SliceTopLeftTileIdx[i]**). The value of **num_exp_slices_in_tile[i]** shall be in the range of 0 to **RowHeight[SliceTopLeftTileIdx[i] / NumTileColumns]** – 1, inclusive. When not present, the value of **num_exp_slices_in_tile[i]** is inferred to be equal to 0.

NOTE 3 – If **num_exp_slices_in_tile[i]** is equal to 0, the tile containing the *i*-th slice is not split into multiple slices. Otherwise (**num_exp_slices_in_tile[i]** is greater than 0), the tile containing the *i*-th slice may or may not be split into multiple slices.

exp_slice_height_in_ctus_minus1[i][j] plus 1 specifies the height of the *j*-th rectangular slice in the tile containing the *i*-th slice in units of CTU rows. The value of **exp_slice_height_in_ctus_minus1[i][j]** shall be in the range of 0 to **RowHeight[SliceTopLeftTileIdx[i] / NumTileColumns]** – 1, inclusive.

tile_idx_delta[i] specifies the difference between the tile index of the tile containing the first CTU in the (*i* + 1)-th rectangular slice and the tile index of the tile containing the first CTU in the *i*-th rectangular slice. The value of

tile_idx_delta[i] shall be in the range of $-\text{NumTilesInPic} + 1$ to $\text{NumTilesInPic} - 1$, inclusive. When not present, the value of tile_idx_delta[i] is inferred to be equal to 0. When present, the value of tile_idx_delta[i] shall not be equal to 0.

...

6.9. Embodiment 9: About signaling of rectangular slices

6.5.1 CTB raster scanning, tile scanning, and subpicture scanning processes

...

When rect_slice_flag is equal to 1, the list NumCtusInSlice[i] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, specifying the number of CTUs in the i-th slice, the list SliceTopLeftTileIdx[i] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, specifying the tile index of the tile containing the first CTU in the slice, and the matrix CtbAddrInSlice[i][j] for i ranging from 0 to num_slices_in_pic_minus1, inclusive, and j ranging from 0 to NumCtusInSlice[i] - 1, inclusive, specifying the picture raster scan address of the j-th CTB within the i-th slice, the variable NumSlicesInTile[i], specifying the number of slices in the tile containing the i-th slice (i.e., the tile with tile index equal to SliceTopLeftTileIdx[i]), are derived as follows:

```

if( single_slice_per_subpic_flag ) {
    for( i = 0; i <= sps_num_subpics_minus1; i++ )
        NumCtusInSlice[ i ] = 0
    for( i = 0; i < PicSizeInCtbsY; i++ ) {
        sliceIdx = ctbToSubpicIdx[ i ]
        CtbAddrInSlice[ sliceIdx ][ NumCtusInSlice[ sliceIdx ] ] = i
        NumCtusInSlice[ sliceIdx ]++
    }
} else {
    tileIdx = 0
    for( i = 0; i <= num_slices_in_pic_minus1; i++ )
        NumCtusInSlice[ i ] = 0
    for( i = 0; i <= num_slices_in_pic_minus1; i++ ) {
        SliceTopLeftTileIdx[ i ] = tileIdx
        tileX = tileIdx % NumTileColumns
        tileY = tileIdx / NumTileColumns
        if( i < num_slices_in_pic_minus1 ) {
            sliceWidthInTiles[ i ] = slice_width_in_tiles_minus1[ i ] + 1
            sliceHeightInTiles[ i ] = slice_height_in_tiles_minus1[ i ] + 1
        } else {
            sliceWidthInTiles[ i ] = NumTileColumns - tileX
            sliceHeightInTiles[ i ] = NumTileRows - tileY
        }
    }
}

```

```

    NumSlicesInTile[ i ] = 1
}
if( sliceWidthInTiles[ i ] == 1 && sliceHeightInTiles[ i ] == 1 ) {
    if( num_exp_slices_in_tile[ i ] == 0 ) {
        NumSlicesInTile[ i ] = 1
        sliceHeightInCtus[ i ] = RowHeight[ SliceTopLeftTileIdx[ i ] / NumTileColumns ]
    }
    else {
        remainingHeightInCtbsY = RowHeight[ SliceTopLeftTileIdx[ i ] / NumTileColumns ]
        [[for( j = 0; j < num_exp_slices_in_tile[ i ]; j++ ) {}]
        for( j = 0; j < num_exp_slices_in_tile[ i ] - 1; j++ ) {
            sliceHeightInCtus[ i + j ] = exp_slice_height_in_ctus_minus1[ i ][ j ] + 1
            remainingHeightInCtbsY -= sliceHeightInCtus[ i + j ]
        }
        [[uniformSliceHeight = sliceHeightInCtus[ i + j - 1 ]]]
        uniformSliceHeight = exp_slice_height_in_ctus_minus1[ i ][ j ] + 1
        while( remainingHeightInCtbsY >= uniformSliceHeight ) {
            sliceHeightInCtus[ i + j ] = uniformSliceHeight
            remainingHeightInCtbsY -= uniformSliceHeight
            j++
        }
        if( remainingHeightInCtbsY > 0 ) {
            sliceHeightInCtus[ i + j ] = remainingHeightInCtbsY
            j++
        }
        NumSlicesInTile[ i ] = j
    }
}
ctbY = tileRowBd[ tileY ]
for( j = 0; j < NumSlicesInTile[ i ] - 1; j++ ) {
    AddCtbsToSlice( i, tileColBd[ tileX ], tileColBd[ tileX + 1 ],
        ctbY, ctbY + sliceHeightInCtus[ i ] )
    ctbY += sliceHeightInCtus[ i ]
    i++
}
AddCtbsToSlice( i, tileColBd[ tileX ], tileColBd[ tileX + 1 ], ctbY, tileRowBd[ tileY + 1 ] )
} else

```

```

        for( j = 0; j < sliceHeightInTiles[ i ]; j++ )
            for( k = 0; k < sliceWidthInTiles[ i ]; k++ )
                AddCtbsToSlice( i, tileColBd[ tileX + k ], tileColBd[ tileX + k + 1 ],
                               tileRowBd[ tileY + j ], tileRowBd[ tileY + j + 1 ] )
    if( i < num_slices_in_pic_minus1 ) {
        if( tile_idx_delta_present_flag )
            tileIdx += tile_idx_delta[ i ]
        else {
            tileIdx += sliceWidthInTiles[ i ]
            if( tileIdx % NumTileColumns == 0 )
                tileIdx += ( sliceHeightInTiles[ i ] - 1 ) * NumTileColumns
        }
    }
}
}
}
...

```

Alternatively, in the above, the following line:

$$\underline{\text{uniformSliceHeight} = \text{exp slice height in ctus minus1}[\text{i}][\text{j}] + 1}$$

is changed to be as follows:

$$\underline{\text{uniformSliceHeight} = \text{exp slice height in ctus minus1}[\text{i}][\text{num exp slices in tile}[\text{i}] - 1] + 1}$$

6.10. Embodiment 10: About signaling of subpictures and tiles

6.5.1 CTB raster scanning, tile scanning, and subpicture scanning processes

The variable NumTileColumns, specifying the number of tile columns, and the list colWidth[i] for i ranging from 0 to NumTileColumns - 1, inclusive, specifying the width of the i-th tile column in units of CTBs, are derived as follows:

```

remainingWidthInCtbsY = PicWidthInCtbsY
for( i = 0; i <= num_exp_tile_columns_minus1; i++ ) {
    colWidth[ i ] = tile_column_width_minus1[ i ] + 1
    remainingWidthInCtbsY -= colWidth[ i ]
}
uniformTileColWidth = tile_column_width_minus1[ num_exp_tile_columns_minus1 ] + 1
while( remainingWidthInCtbsY >= uniformTileColWidth ) {
    colWidth[ i++ ] = uniformTileColWidth
    remainingWidthInCtbsY -= uniformTileColWidth
}
if( remainingWidthInCtbsY > 0 )

```

(23)

```
colWidth[ i++ ] = remainingWidthInCtbsY
```

```
NumTileColumns = i
```

The variable NumTileRows, specifying the number of tile rows, and the list RowHeight[j] for j ranging from 0 to NumTileRows - 1, inclusive, specifying the height of the j-th tile row in units of CTBs, are derived as follows:

```
remainingHeightInCtbsY = PicHeightInCtbsY
```

```
for( j = 0; j <= num_exp_tile_rows_minus1; j++ ) {
```

```
    RowHeight[ j ] = tile_row_height_minus1[ j ] + 1
```

```
    remainingHeightInCtbsY -= RowHeight[ j ]
```

```
}
```

```
uniformTileRowHeight = tile_row_height_minus1[ num_exp_tile_rows_minus1 ] + 1
```

(24)

```
while( remainingHeightInCtbsY >= uniformTileRowHeight ) {
```

```
    RowHeight[ j++ ] = uniformTileRowHeight
```

```
    remainingHeightInCtbsY -= uniformTileRowHeight
```

```
}
```

```
if( remainingHeightInCtbsY > 0 )
```

```
    RowHeight[ j++ ] = remainingHeightInCtbsY
```

```
NumTileRows = j
```

7.3.2.3 Sequence parameter set RBSP syntax

seq_parameter_set_rbsp() {	Descriptor
...	
if(subpic_info_present_flag) {	
<u>if(pic_width_max_in_luma_samples > CtbSizeY </u> <u>pic_height_max_in_luma_samples > CtbSizeY)</u>	
sps_num_subpics_minus1	ue(v)
...	
}	

7.3.2.4 Picture parameter set RBSP syntax

pic_parameter_set_rbsp() {	Descriptor
...	
no_pic_partition_flag	u(1)
if(!no_pic_partition_flag) {	
pps_log2_ctu_size_minus5	u(2)
<u>if(pic_width_in_luma_samples > CtbSizeY)</u>	
num_exp_tile_columns_minus1	ue(v)
<u>if(pic_height_in_luma_samples > CtbSizeY)</u>	

num_exp_tile_rows_minus1	ue(v)
for(i = 0; i <= num_exp_tile_columns_minus1 && num_exp_tile_columns_minus1 != <i>PicWidthInCtbsY - 1</i> ; i++)	
tile_column_width_minus1[i]	ue(v)
for(i = 0; i <= num_exp_tile_rows_minus1 && num_exp_tile_rows_minus1 != <i>PicHeightInCtbsY - 1</i> ; i++)	
tile_row_height_minus1[i]	ue(v)
...	
}	

7.4.3.4 Picture parameter set semantics

...

num_exp_tile_columns_minus1 plus 1 specifies the number of explicitly provided tile column widths. The value of **num_exp_tile_columns_minus1** shall be in the range of 0 to *PicWidthInCtbsY - 1*, inclusive. *When not present, the value of num_exp_tile_columns_minus1 is inferred to be equal to 0.*

num_exp_tile_rows_minus1 plus 1 specifies the number of explicitly provided tile row heights. The value of **num_exp_tile_rows_minus1** shall be in the range of 0 to *PicHeightInCtbsY - 1*, inclusive. *When not present, the value of num_exp_tile_rows_minus1 is inferred to be equal to 0.*

tile_column_width_minus1[i] plus 1 specifies the width of the i-th tile column in units of CTBs for i in the range of 0 to **num_exp_tile_columns_minus1**, inclusive. **tile_column_width_minus1[num_exp_tile_columns_minus1]** is used to derive the width of the tile columns with index *greater than* **num_exp_tile_columns_minus1** as specified in clause 6.5.1. The value of **tile_column_width_minus1[i]** shall be in the range of 0 to *PicWidthInCtbsY - 1*, inclusive. When not present, the value of **tile_column_width_minus1[i]** is inferred to be equal to *no_pic_partition_flag ? (PicWidthInCtbsY - 1) : 0.*

tile_row_height_minus1[i] plus 1 specifies the height of the i-th tile row in units of CTBs for i in the range of 0 to **num_exp_tile_rows_minus1**, inclusive. **tile_row_height_minus1[num_exp_tile_rows_minus1]** is used to derive the height of the tile rows with index *greater than* **num_exp_tile_rows_minus1** as specified in clause 6.5.1. The value of **tile_row_height_minus1[i]** shall be in the range of 0 to *PicHeightInCtbsY - 1*, inclusive. When not present, the value of **tile_row_height_minus1[i]** is inferred to be equal to *no_pic_partition_flag ? (PicHeightInCtbsY - 1) : 0.*

...

[00101] FIG. 7 is a block diagram showing an example video processing system 1900 in which various techniques disclosed herein may be implemented. Various implementations may include some or all of the components of the system 1900. The system 1900 may include input 1902 for receiving video content. The video content may be received in a raw or uncompressed format,

e.g., 8 or 10 bit multi-component pixel values, or may be in a compressed or encoded format.

The input 1902 may represent a network interface, a peripheral bus interface, or a storage interface. Examples of network interface include wired interfaces such as Ethernet, passive optical network (PON), etc. and wireless interfaces such as Wi-Fi or cellular interfaces.

[00102] The system 1900 may include a coding component 1904 that may implement the various coding or encoding methods described in the present document. The coding component 1904 may reduce the average bitrate of video from the input 1902 to the output of the coding component 1904 to produce a coded representation of the video. The coding techniques are therefore sometimes called video compression or video transcoding techniques. The output of the coding component 1904 may be either stored, or transmitted via a communication connected, as represented by the component 1906. The stored or communicated bitstream (or coded) representation of the video received at the input 1902 may be used by the component 1908 for generating pixel values or displayable video that is sent to a display interface 1910. The process of generating user-viewable video from the bitstream representation is sometimes called video decompression. Furthermore, while certain video processing operations are referred to as “coding” operations or tools, it will be appreciated that the coding tools or operations are used at an encoder and corresponding decoding tools or operations that reverse the results of the coding will be performed by a decoder.

[00103] Examples of a peripheral bus interface or a display interface may include universal serial bus (USB) or high definition multimedia interface (HDMI) or Displayport, and so on. Examples of storage interfaces include SATA (serial advanced technology attachment), PCI, IDE interface, and the like. The techniques described in the present document may be embodied in various electronic devices such as mobile phones, laptops, smartphones or other devices that are capable of performing digital data processing and/or video display.

[00104] FIG. 8 is a block diagram of a video processing apparatus 3600. The apparatus 3600 may be used to implement one or more of the methods described herein. The apparatus 3600 may be embodied in a smartphone, tablet, computer, Internet of Things (IoT) receiver, and so on. The apparatus 3600 may include one or more processors 3602, one or more memories 3604 and video processing hardware 3606. The processor(s) 3602 may be configured to implement one or more methods described in the present document. The memory (memories) 3604 may be used

for storing data and code used for implementing the methods and techniques described herein. The video processing hardware 3606 may be used to implement, in hardware circuitry, some techniques described in the present document.

[00105] FIG. 10 is a block diagram that illustrates an example video coding system 100 that may utilize the techniques of this disclosure.

[00106] As shown in FIG. 10, video coding system 100 may include a source device 110 and a destination device 120. Source device 110 generates encoded video data which may be referred to as a video encoding device. Destination device 120 may decode the encoded video data generated by source device 110 which may be referred to as a video decoding device.

[00107] Source device 110 may include a video source 112, a video encoder 114, and an input/output (I/O) interface 116.

[00108] Video source 112 may include a source such as a video capture device, an interface to receive video data from a video content provider, and/or a computer graphics system for generating video data, or a combination of such sources. The video data may comprise one or more pictures. Video encoder 114 encodes the video data from video source 112 to generate a bitstream. The bitstream may include a sequence of bits that form a coded representation of the video data. The bitstream may include coded pictures and associated data. The coded picture is a coded representation of a picture. The associated data may include sequence parameter sets, picture parameter sets, and other syntax structures. I/O interface 116 may include a modulator/demodulator (modem) and/or a transmitter. The encoded video data may be transmitted directly to destination device 120 via I/O interface 116 through network 130a. The encoded video data may also be stored onto a storage medium/server 130b for access by destination device 120.

[00109] Destination device 120 may include an I/O interface 126, a video decoder 124, and a display device 122.

[00110] I/O interface 126 may include a receiver and/or a modem. I/O interface 126 may acquire encoded video data from the source device 110 or the storage medium/ server 130b. Video decoder 124 may decode the encoded video data. Display device 122 may display the decoded video data to a user. Display device 122 may be integrated with the destination device 120, or

may be external to destination device 120 which be configured to interface with an external display device.

[00111] Video encoder 114 and video decoder 124 may operate according to a video compression standard, such as the High Efficiency Video Coding (HEVC) standard, Versatile Video Coding (VVM) standard and other current and/or further standards.

[00112] FIG. 11 is a block diagram illustrating an example of video encoder 200, which may be video encoder 114 in the system 100 illustrated in FIG. 10.

[00113] Video encoder 200 may be configured to perform any or all of the techniques of this disclosure. In the example of FIG. 11, video encoder 200 includes a plurality of functional components. The techniques described in this disclosure may be shared among the various components of video encoder 200. In some examples, a processor may be configured to perform any or all of the techniques described in this disclosure.

[00114] The functional components of video encoder 200 may include a partition unit 201, a predication unit 202 which may include a mode select unit 203, a motion estimation unit 204, a motion compensation unit 205 and an intra prediction unit 206, a residual generation unit 207, a transform unit 208, a quantization unit 209, an inverse quantization unit 210, an inverse transform unit 211, a reconstruction unit 212, a buffer 213, and an entropy encoding unit 214.

[00115] In other examples, video encoder 200 may include more, fewer, or different functional components. In an example, predication unit 202 may include an intra block copy (IBC) unit. The IBC unit may perform predication in an IBC mode in which at least one reference picture is a picture where the current video block is located.

[00116] Furthermore, some components, such as motion estimation unit 204 and motion compensation unit 205 may be highly integrated, but are represented in the example of FIG. 11 separately for purposes of explanation.

[00117] Partition unit 201 may partition a picture into one or more video blocks. Video encoder 200 and video decoder 300 may support various video block sizes.

[00118] Mode select unit 203 may select one of the coding modes, intra or inter, e.g., based on error results, and provide the resulting intra- or inter-coded block to a residual generation unit 207 to generate residual block data and to a reconstruction unit 212 to reconstruct the encoded block for use as a reference picture. In some example, Mode select unit 203 may select a

combination of intra and inter predication (CIIP) mode in which the predication is based on an inter predication signal and an intra predication signal. Mode select unit 203 may also select a resolution for a motion vector (e.g., a sub-pixel or integer pixel precision) for the block in the case of inter-predication.

[00119] To perform inter prediction on a current video block, motion estimation unit 204 may generate motion information for the current video block by comparing one or more reference frames from buffer 213 to the current video block. Motion compensation unit 205 may determine a predicted video block for the current video block based on the motion information and decoded samples of pictures from buffer 213 other than the picture associated with the current video block.

[00120] Motion estimation unit 204 and motion compensation unit 205 may perform different operations for a current video block, for example, depending on whether the current video block is in an I slice, a P slice, or a B slice.

[00121] In some examples, motion estimation unit 204 may perform uni-directional prediction for the current video block, and motion estimation unit 204 may search reference pictures of list 0 or list 1 for a reference video block for the current video block. Motion estimation unit 204 may then generate a reference index that indicates the reference picture in list 0 or list 1 that contains the reference video block and a motion vector that indicates a spatial displacement between the current video block and the reference video block. Motion estimation unit 204 may output the reference index, a prediction direction indicator, and the motion vector as the motion information of the current video block. Motion compensation unit 205 may generate the predicted video block of the current block based on the reference video block indicated by the motion information of the current video block.

[00122] In other examples, motion estimation unit 204 may perform bi-directional prediction for the current video block, motion estimation unit 204 may search the reference pictures in list 0 for a reference video block for the current video block and may also search the reference pictures in list 1 for another reference video block for the current video block. Motion estimation unit 204 may then generate reference indexes that indicate the reference pictures in list 0 and list 1 containing the reference video blocks and motion vectors that indicate spatial displacements between the reference video blocks and the current video block. Motion estimation unit 204 may

output the reference indexes and the motion vectors of the current video block as the motion information of the current video block. Motion compensation unit 205 may generate the predicted video block of the current video block based on the reference video blocks indicated by the motion information of the current video block.

[00123] In some examples, motion estimation unit 204 may output a full set of motion information for decoding processing of a decoder.

[00124] In some examples, motion estimation unit 204 may do not output a full set of motion information for the current video. Rather, motion estimation unit 204 may signal the motion information of the current video block with reference to the motion information of another video block. For example, motion estimation unit 204 may determine that the motion information of the current video block is sufficiently similar to the motion information of a neighboring video block.

[00125] In one example, motion estimation unit 204 may indicate, in a syntax structure associated with the current video block, a value that indicates to the video decoder 300 that the current video block has the same motion information as the another video block.

[00126] In another example, motion estimation unit 204 may identify, in a syntax structure associated with the current video block, another video block and a motion vector difference (MVD). The motion vector difference indicates a difference between the motion vector of the current video block and the motion vector of the indicated video block. The video decoder 300 may use the motion vector of the indicated video block and the motion vector difference to determine the motion vector of the current video block.

[00127] As discussed above, video encoder 200 may predictively signal the motion vector. Two examples of predictive signaling techniques that may be implemented by video encoder 200 include advanced motion vector predication (AMVP) and merge mode signaling.

[00128] Intra prediction unit 206 may perform intra prediction on the current video block. When intra prediction unit 206 performs intra prediction on the current video block, intra prediction unit 206 may generate prediction data for the current video block based on decoded samples of other video blocks in the same picture. The prediction data for the current video block may include a predicted video block and various syntax elements.

[00129] Residual generation unit 207 may generate residual data for the current video block by subtracting (e.g., indicated by the minus sign) the predicted video block(s) of the current video block from the current video block. The residual data of the current video block may include residual video blocks that correspond to different sample components of the samples in the current video block.

[00130] In other examples, there may be no residual data for the current video block for the current video block, for example in a skip mode, and residual generation unit 207 may not perform the subtracting operation.

[00131] Transform processing unit 208 may generate one or more transform coefficient video blocks for the current video block by applying one or more transforms to a residual video block associated with the current video block.

[00132] After transform processing unit 208 generates a transform coefficient video block associated with the current video block, quantization unit 209 may quantize the transform coefficient video block associated with the current video block based on one or more quantization parameter (QP) values associated with the current video block.

[00133] Inverse quantization unit 210 and inverse transform unit 211 may apply inverse quantization and inverse transforms to the transform coefficient video block, respectively, to reconstruct a residual video block from the transform coefficient video block. Reconstruction unit 212 may add the reconstructed residual video block to corresponding samples from one or more predicted video blocks generated by the predication unit 202 to produce a reconstructed video block associated with the current block for storage in the buffer 213.

[00134] After reconstruction unit 212 reconstructs the video block, loop filtering operation may be performed reduce video blocking artifacts in the video block.

[00135] Entropy encoding unit 214 may receive data from other functional components of the video encoder 200. When entropy encoding unit 214 receives the data, entropy encoding unit 214 may perform one or more entropy encoding operations to generate entropy encoded data and output a bitstream that includes the entropy encoded data.

[00136] FIG. 12 is a block diagram illustrating an example of video decoder 300 which may be video decoder 114 in the system 100 illustrated in FIG. 10.

[00137] The video decoder 300 may be configured to perform any or all of the techniques of this disclosure. In the example of FIG. 12, the video decoder 300 includes a plurality of functional components. The techniques described in this disclosure may be shared among the various components of the video decoder 300. In some examples, a processor may be configured to perform any or all of the techniques described in this disclosure.

[00138] In the example of FIG. 12, video decoder 300 includes an entropy decoding unit 301, a motion compensation unit 302, an intra prediction unit 303, an inverse quantization unit 304, an inverse transformation unit 305, and a reconstruction unit 306 and a buffer 307. Video decoder 300 may, in some examples, perform a decoding pass generally reciprocal to the encoding pass described with respect to video encoder 200 (FIG. 11).

[00139] Entropy decoding unit 301 may retrieve an encoded bitstream. The encoded bitstream may include entropy coded video data (e.g., encoded blocks of video data). Entropy decoding unit 301 may decode the entropy coded video data, and from the entropy decoded video data, motion compensation unit 302 may determine motion information including motion vectors, motion vector precision, reference picture list indexes, and other motion information. Motion compensation unit 302 may, for example, determine such information by performing the AMVP and merge mode.

[00140] Motion compensation unit 302 may produce motion compensated blocks, possibly performing interpolation based on interpolation filters. Identifiers for interpolation filters to be used with sub-pixel precision may be included in the syntax elements.

[00141] Motion compensation unit 302 may use interpolation filters as used by video encoder 200 during encoding of the video block to calculate interpolated values for sub-integer pixels of a reference block. Motion compensation unit 302 may determine the interpolation filters used by video encoder 200 according to received syntax information and use the interpolation filters to produce predictive blocks.

[00142] Motion compensation unit 302 may use some of the syntax information to determine sizes of blocks used to encode frame(s) and/or slice(s) of the encoded video sequence, partition information that describes how each macroblock of a picture of the encoded video sequence is partitioned, modes indicating how each partition is encoded, one or more reference frames (and

reference frame lists) for each inter-encoded block, and other information to decode the encoded video sequence.

[00143] Intra prediction unit 303 may use intra prediction modes for example received in the bitstream to form a prediction block from spatially adjacent blocks. Inverse quantization unit 303 inverse quantizes, i.e., de-quantizes, the quantized video block coefficients provided in the bitstream and decoded by entropy decoding unit 301. Inverse transform unit 303 applies an inverse transform.

[00144] Reconstruction unit 306 may sum the residual blocks with the corresponding prediction blocks generated by motion compensation unit 202 or intra-prediction unit 303 to form decoded blocks. If desired, a deblocking filter may also be applied to filter the decoded blocks in order to remove blockiness artifacts. The decoded video blocks are then stored in buffer 307, which provides reference blocks for subsequent motion compensation/intra predication and also produces decoded video for presentation on a display device.

[00145] A listing of solutions preferred by some embodiments is provided next.

[00146] The following solutions show example embodiments of techniques discussed in the previous section (e.g., item 1).

[00147] 1. A video processing method (e.g., method 900 depicted in FIG. 9), comprising: performing (902) a conversion between a video comprising one or more video pictures, wherein each video picture comprises one or more subpictures that comprise one or more slices and a coded representation of a video, wherein the coded representation conforms to a format rule; wherein the format rule specifies that, in case that a rectangular slices mode is enabled for a video picture, then a picture-level slice index for each slice in each subpicture in the video picture is derived without explicit signaling in the coded representation; and wherein the format rule specifies that a number of coding tree units in each slice is derivable from the picture-level slice index.

[00148] The following solutions show example embodiments of techniques discussed in the previous section (e.g., item 2).

[00149] 2. A video processing method, comprising: performing a conversion between a video comprising one or more video pictures, wherein each video picture comprises one or more subpictures that comprise one or more slices and a coded representation of a video, wherein the

coded representation conforms to a format rule; wherein the format rule specifies that a subpicture level slice index is derivable based on information in the coded representation without signaling the sub-picture level slice index in the coded representation.

[00150] 3. The method of solution 2, wherein the format rule specifies that, due to use of a rectangular slice structure, the subpicture level slice index corresponds to an index to the slice in a list of slices in a subpicture.

[00151] 4. The method of solution 2, wherein the format rule specifies that the subpicture level slice index is derived from a particular value of picture-level slice index.

[00152] The following solutions show example embodiments of techniques discussed in the previous section (e.g., items 5, 6).

[00153] 5. A video processing method, comprising: performing a conversion between a video comprising one or more video pictures, wherein each video picture comprises one or more subpictures and/or one or more tiles and a coded representation of a video, wherein the coded representation conforms to a format rule; and wherein the conversion conforms to a constraint rule.

[00154] 6. The method of solution 5, wherein the constraint rule specifies that a tile cannot be in more than one subpictures.

[00155] 7. The method of solution 5, wherein the constraint rule specifies that a subpicture cannot include two slices that are smaller than corresponding tiles to which the two slices belong.

[00156] The following solutions show example embodiments of techniques discussed in the previous section (e.g., items 7, 8).

[00157] 8. A video processing method, comprising: performing a conversion between a video comprising one or more video pictures, wherein each video picture comprises one or more tiles and/or one more slices; wherein the coded representation conforms to a format rule; wherein the format rule specifies that a field at a video picture level carries information about portioning of slices and/or tiles in the video picture.

[00158] 9. The method of solution 8, wherein the field comprises a video picture header.

[00159] 10. The method of solution 8, wherein the field comprises a picture parameter set.

[00160] 11. The method of any of solutions 8-10, wherein the format rule specifies to omit slice partitioning information at slice level by including the slice partitioning information in the field at the video picture level.

[00161] The following solutions show example embodiments of techniques discussed in the previous section (e.g., item 9).

[00162] 12. A video processing method, comprising: performing a conversion between a video comprising one or more pictures and a coded representation of the video, wherein the conversion conforms to a partitioning rule that a minimum number of slices in which a video picture is partitioned is a function of whether rectangular partitioning is used for partitioning the video picture.

[00163] 13. The method of solution 12, wherein the partitioning rule specifies to use at least two slices for non-rectangular partitioning and at least one slice for rectangular partitioning.

[00164] 14. The method of solution 12, wherein the partitioning rule is also a function of whether and/or how many subpictures are used for partitioning the video picture.

[00165] The following solutions show example embodiments of techniques discussed in the previous section (e.g., items 10, 11).

[00166] 15. A method of video processing, comprising: performing a conversion between a video slice of a video region of a video and a coded representation of the video; wherein the coded representation conforms to a format rule; wherein the format rule specifies that the coded representation signals the video slice based on a top-left location of the video slice and wherein the format rule specifies that the coded representation signals a height and/or a width of the video slice in partitioning information that is signaled at a video unit level.

[00167] 16. The method of solution 15, wherein the format rule specifies that the video slice is signaled in an order of slices defined by the format rule.

[00168] 17. The method of solution 15, wherein the video region corresponds to a subpicture and wherein the video unit level corresponds to a video picture.

[00169] The following solutions show example embodiments of techniques discussed in the previous section (e.g., item 12).

[00170] 18. A method of video processing, comprising: performing a conversion between a video comprising video pictures and a coded representation of the video; wherein the coded

representation conforms to a format rule; wherein the format rule specifies to omit signaling a difference between a tile index of a first tile in a rectangular slice and a tile index of a first tile in a next rectangular slice.

[00171] 19. The method of solution 18, wherein the difference is derivable from a zeroth slice in the video picture and the rectangular slice.

[00172] The following solutions show example embodiments of techniques discussed in the previous section (e.g., item 13).

[00173] 20. A video processing method, comprising: performing a conversion between a video and a coded representation of the video, wherein the coded representation conforms to a format rule, wherein the format rule specifies that a relationship between a width of a video picture and a size of a coding tree unit controls signaling of information used for deriving a number of tile columns or rows in the video picture.

[00174] 21. The method of solution 20, wherein the format rule specifies to exclude signaling a number of tile rows or a number of tile columns in case that the width of the video picture is smaller than or equal to a width of the coding tree unit.

[00175] The following solutions show example embodiments of techniques discussed in the previous section (e.g., item 16).

[00176] 22. A method of video processing, comprising: performing a conversion between a video comprising one or more video pictures and a coded representation of the video, wherein the coded representation conforms to a format rule, wherein the format rule specifies that a tile layout information is included in the coded representation for a video picture that comprises uniform spacing tiles and non-uniform spacing tiles.

[00177] 23. The method of solution 22, wherein the tile layout information is included in a syntax flag that is included in a picture parameter set.

[00178] 24. The method of any of solutions 22-23, wherein a number of explicitly signaled number of tile rows or columns is no less than a number of non-uniform spacing tiles.

[00179] 25. The method of any of solutions 22-23, wherein a number of explicitly signaled number of tile rows or columns is no less than a number of uniform spacing tiles.

[00180] 26. The method of any of above solutions, wherein the video region comprises a video coding unit.

[00181] 27. The method of any of above solutions, wherein the video region comprises a video picture.

[00182] 28. The method of any of solutions 1 to 27, wherein the conversion comprises encoding the video into the coded representation.

[00183] 29. The method of any of solutions 1 to 27, wherein the conversion comprises decoding the coded representation to generate pixel values of the video.

[00184] 30. A video decoding apparatus comprising a processor configured to implement a method recited in one or more of solutions 1 to 29.

[00185] 31. A video encoding apparatus comprising a processor configured to implement a method recited in one or more of solutions 1 to 29.

[00186] 32. A computer program product having computer code stored thereon, the code, when executed by a processor, causes the processor to implement a method recited in any of solutions 1 to 29.

[00187] 33. A method, apparatus or system described in the present document.

[00188] FIG. 13 is flowchart representation of a method for video processing in accordance with the present technology. The method 1300 includes, at operation 1310, performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more slices. The rule specifies that a syntax element indicating a difference between tile indices of two rectangular slices is signaled responsive to a condition being satisfied, wherein one of the slice indices is represented as i , where i is an integer.

[00189] In some embodiments, a second rectangular slice of the two rectangular slices is represented as $(i+1)$ -th rectangular slice, and the syntax element indicates the difference between a first tile index of a first tile containing a first coding tree unit in the $(i + 1)$ -th rectangular slice and a second tile index of a second tile containing a first coding tree unit in the i -th rectangular slice. In some embodiments, the at least one condition being satisfied comprises i being smaller than (a number of rectangular slices in the video picture - 1). In some embodiments, the at least one condition being satisfied comprises i being not equal to (a number of rectangular slices in the video picture - 1).

[00190] FIG. 14 is flowchart representation of a method for video processing in accordance with the present technology. The method 1400 includes, at operation 1410, performing a conversion

between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more sub-pictures and each sub-picture comprises one or more rectangular slices. The rule specifies that a slice index at a sub-picture level for each rectangular slice in each sub-picture is derived to determine a number of coding tree units in each slice.

[00191] In some embodiments, the slice index at the sub-picture level is determined based on a decoding order of a corresponding slice in a list of slices in a sub-picture. In some embodiments, in case a first slice index at the sub-picture level for a first slice is smaller than a second slice index at the sub-picture level for a second slice, the first slice is processed ahead of the second slice according to the decoding order. In some embodiments, the slice index at the sub-picture level is represented using a variable SubpicLevelSliceIdx. In some embodiments, a slice address is determined based on the slice index at the sub-picture level. In some embodiments, the slice index at the sub-picture level of a slice is determined based on a first sub-picture that includes the slice. In some embodiments, the slice index at the sub-picture level is a non-negative integer. In some embodiments, the slice index at the sub-picture level is greater than or equal to 0 and smaller than N, N being a number of slices in a sub-picture.

[00192] In some embodiments, a first slice index at the sub-picture level for a first slice is different than a second slice index at the sub-picture level for a second slice in case the first slice and the second slice are different, where the first slice and the second slice are in a same sub-picture. In some embodiments, in case a first slice index at the sub-picture level for a first slice is smaller than a second slice index at the sub-picture level for a second slice, a first slice index at a picture-level for the first slice is smaller than a second slice index at the picture-level for the second slice. In some embodiments, the slice index at the sub-picture level of a slice is determined based on a slice index at a picture level of the slice.

[00193] FIG. 15 is flowchart representation of a method for video processing in accordance with the present technology. The method 1500 includes, at operation 1510, determining, for a conversion between a video picture of a video that comprises one or more sub-pictures and a bitstream of the video, a mapping relationship between a sub-picture-level slice index of a slice in a sub-picture and a picture level slice index of the slice. The method 1500 also includes, at operation 1520, performing the conversion based on the determining.

[00194] In some embodiments, the mapping relationship is represented as a two-dimensional array that is indexed using the picture-level slice index and a sub-picture index of the sub-picture. In some embodiments, the picture-level slice index is determined based on an array indicating a number of slices in each of the one or more sub-pictures. In some embodiments, the two-dimensional array and the array indicating the number of slices in each of the one or more sub-pictures are determined based on a process that scans all slices in an order of picture-level slice index. In some embodiments, the picture-level slice index of the slice is determined using the mapping relationship, and a number of coding tree blocks and/or addresses of the coding tree blocks in the slice are determined based on the picture-level slice index of the slice.

[00195] FIG. 16 is flowchart representation of a method for video processing in accordance with the present technology. The method 1600 includes, at operation 1610, performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more sub-pictures. The rule specifies that a tile of the video is positioned entirely within a single sub-picture of the video picture.

[00196] In some embodiments, a first slice is located in a first tile, the first slice being smaller than the first tile. A second slice is located in a second tile, the second slice being smaller than the second tile. The first tile is different than the second tile, and the first slice and the second slice are located in different slices of a sub-picture.

[00197] FIG. 17 is flowchart representation of a method for video processing in accordance with the present technology. The method 1700 includes, at operation 1710, performing a conversion between a video picture of a video and a bitstream of the video. The video picture comprises one or more sub-pictures. The bitstream conforms to a format rule specifying that information of partitioning a picture is included in a syntax structure associated with the picture.

[00198] In some embodiments, the syntax structure comprises a picture header or a picture parameter set. In some embodiments, a video unit includes a flag indicating whether the information of partitioning a picture is included in the syntax structure. In some embodiments, the video unit comprises a picture header, a picture parameter set, or a sequence parameter set. In some embodiments, in case the information of partitioning a picture is included in both the picture header and the picture parameter set, the information included in the picture header is used for the conversion.

[00199] FIG. 18 is flowchart representation of a method for video processing in accordance with the present technology. The method 1800 includes, at operation 1810, determining, for a conversion between a video picture of a video that comprises one or more slices having a non-rectangular shape and a bitstream of the video, slice partitioning information of the video picture. The method 1800 also includes, at operation 1820, performing the conversion based on the determining.

[00200] In some embodiments, the slice partitioning information is stored in a video unit of the video, and wherein the video unit comprises a picture parameter set or a picture header. In some embodiments, the bitstream conforms to a format rule specifying that the slice partitioning information of the video picture is included in a syntax structure associated with a video unit that includes the one or more slices. In some embodiments, the slice partitioning information of the video picture includes a value indicating a number of slices in a picture. In some embodiments, the slice partitioning information of the video picture comprises a value that indicates an index of a block-unit within a slice. In some embodiments, a value that indicates an index of a block-unit within a slice is omitted from the slice partitioning information of the video picture. In some embodiments, the slice partitioning information of the video picture comprises a value that indicates a number of block units within a slice. In some embodiments, a value that indicates a number of block units within a slice is omitted from the slice partitioning information of the video picture. In some embodiments, the block unit is a coding tree unit or a tile. In some embodiments, the slice partitioning information of the video picture is omitted in a slice header. In some embodiments, a slice index of a slice is included in a slice header, and a picture-level slice index of the slice is determined based on an address of the slice.

[00201] In some embodiments, the slice partitioning information of each of the one or more slices is organized in an order in the syntax structure associated with the video unit. In some embodiments, the slice partitioning information of each of the one or more slices is included in the syntax structure in an ascending order. In some embodiments, the slice partitioning information of each of the one or more slices is included in the syntax structure in a descending order.

[00202] In some embodiments, the slice partitioning information of at least one of the one or more slices is omitted in the bitstream. In some embodiments, the slice partitioning information

of the at least one of the one or more slices is inferred from slice partitioning information of other slices included in the bitstream. In some embodiments, a number of block-units for slice S-1 is not included in the bitstream, where S represent a number of slices in the video picture, S being greater than 1.

[00203] FIG. 19 is flowchart representation of a method for video processing in accordance with the present technology. The method 1900 includes, at operation 1910, performing a conversion between a video picture of a video that comprises one or more slices and a bitstream of the video according to a rule. The rule specifies that a number of slices in the video picture is equal to or greater than a minimum number of slices determined based on whether rectangular partitioning or non-rectangular partitioning is applied to the video picture.

[00204] In some embodiments, the minimum number of slices is two in case the non-rectangular partitioning is applied, and the minimum number of slices is one in case the rectangular partitioning is applied. In some embodiments, the minimum number of slices is one in case the non-rectangular partitioning is applied, and the minimum number of slices is one in case the rectangular partitioning is applied. In some embodiments, the minimum number of slices is further determined based on a number of sub-pictures in the video picture.

[00205] FIG. 20 is flowchart representation of a method for video processing in accordance with the present technology. The method 2000 includes, at operation 2010, performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more slices. In case slice partitioning information of the video picture is included in a syntax structure of a video unit, a slice is represented by a top-left location and a dimension of the slice.

[00206] In some embodiments, the top-left location and the dimension of the slice are indicated using a top-left location of a block unit that is within the slice, a dimension of the block unit, and the dimension of the slice measured using the dimension of the block unit. In some embodiments, a top-left location of each slice and a dimension of each slice is included in the syntax structure in an order.

[00207] FIG. 21 is flowchart representation of a method for video processing in accordance with the present technology. The method 2100 includes, at operation 2110, performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video

picture comprises one or more sub-pictures and each sub-picture comprises one or more slices. The rule specifies a manner by which partitioning information of the one or more slices in each sub-picture is present in the bitstream.

[00208] In some embodiments, the video unit comprises a sequence parameter set, a picture parameter set, or a picture header. In some embodiments, the partitioning information of the one or more sub-pictures is arranged in an ascending order based on sub-picture indices. In some embodiments, the partitioning information of the one or more slices in each sub-picture is arranged in an ascending order based on sub-picture-level slice indices.

[00209] FIG. 22 is flowchart representation of a method for video processing in accordance with the present technology. The method 2200 includes, at operation 2210, performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more rectangular slices and each slice comprises one or more tiles. The rule specifies that signaling between a difference between a first tile index of a first tile in i^{th} rectangular slice and a second tile index of a first tile in $(i+1)^{\text{th}}$ rectangular slice is omitted in the bitstream.

[00210] In some embodiments, the second tile index of the first tile in $(i+1)^{\text{th}}$ rectangular slice is derived based on rectangular slices indexed from 0^{th} to i^{th} . In some embodiments, the second tile index of the first tile in $(i+1)^{\text{th}}$ rectangular slice is derived to be a minimum tile index that is out of a range defined by rectangular slices indexed from 0^{th} to i^{th} .

[00211] FIG. 23 is flowchart representation of a method for video processing in accordance with the present technology. The method 2300 includes, at operation 2310, determining, for a conversion between a video picture of a video and a bitstream of the video, that information for deriving a number of columns of tiles and a number of rows of tiles in the video picture is conditionally included in the bitstream responsive to a relationship between a dimension of the video picture and a dimension of a coding tree block. The method 2300 also includes, at operation 2320, performing the conversion based on the determining.

[00212] In some embodiments, the information is omitted in case a width of the video picture is smaller than or equal to a width of the coding tree block. In some embodiments, the information is omitted in case a height of the video picture is smaller than or equal to a height of the coding tree block.

[00213] FIG. 24 is flowchart representation of a method for video processing in accordance with the present technology. The method 2400 includes, at operation 2410, performing a conversion between a video picture of a video and a bitstream of the video. The video picture comprises one or more sub-pictures. The bitstream conforms to a format rule specifying that, in case a variable that specifies a subpicture identifier of a subpicture that includes a slice is present in the bitstream, there is one and only one syntax element that satisfies a condition that a second variable corresponding to the syntax element is equal to the variable.

[00214] In some embodiments, the variable is represented as slice_subpic_id and the second variable is represented as SubpicIdVal. The syntax element corresponding to the syntax element is represented as SubpicIdVal [CurrSubpicIdx].

[00215] FIG. 25 is flowchart representation of a method for video processing in accordance with the present technology. The method 2500 includes, at operation 2510, performing a conversion between a video picture of a video and a bitstream of the video. The video picture comprises one or more sub-pictures. In case a non-rectangular partitioning is applied or sub-picture information is omitted in the bitstream, two tiles in a slice have different addresses.

[00216] In some embodiments, a first syntax flag rect_slice_flag indicates whether the non-rectangular partitioning is applied, and a second syntax flag subpic_info_present_info indicates whether the sub-picture information is present in the bitstream.

[00217] FIG. 26 is flowchart representation of a method for video processing in accordance with the present technology. The method 2600 includes, at operation 2610, performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The video picture comprises one or more tiles. The rule specifies that a syntax element is used to indicate a type of tile layout in case the one or more tiles are organized in both uniform spacing and non-uniform spacing.

[00218] In some embodiments, the syntax element is included in a picture parameter set indicating whether uniform spacing is followed by non-uniform spacing or non-uniform spacing is followed by uniform spacing in the tile layout. In some embodiments, the tile layout includes non-uniformly spaced tiles and wherein a number of explicitly indicated tile columns or rows is equal to or greater than a total number of the non-uniformly spaced tiles. In some embodiments, the tile layout includes uniformly spaced tiles, and a number of explicitly indicated tile columns

or rows is equal to or greater than a total number of the uniformly spaced tiles. In some embodiments, uniform spacing is followed by non-uniform spacing in the tile layout, dimensions of non-uniformly spaced tiles are determined first according to a first inverse order, and dimensions of uniformly spaced tiles are determined next according to a second inverse order. In some embodiments, the dimensions comprise widths of tile columns or heights of tile rows.

[00219] FIG. 27 is flowchart representation of a method for video processing in accordance with the present technology. The method 2700 includes, at operation 2710, performing a conversion between a video picture of a video and a bitstream of the video according to a rule. The rule specifies that whether or how a Merge Estimation Region (MER) size is processed in the conversion is conditioned on a minimum allowed coding block size.

[00220] In some embodiments, the MER size is equal to or greater than the minimum allowed coding block size. In some embodiments, the MER size is indicated by MER_size and the minimum allowed coding block size is indicated by MinCbSizeY, and a difference between $\text{Log2}(\text{MER_size})$ and $\text{Log2}(\text{MinCbSizeY})$ is included in the bitstream.

[00221] FIG. 28 is flowchart representation of a method for video processing in accordance with the present technology. The method 2800 includes, at operation 2810, performing a conversion between a video that comprises at least a video tile and a bitstream of the video according to a rule. The rule specifies that a height of a slice in the video tile in units of coding tree units is derived based on a value of a first syntax element in the bitstream indicating a number of explicitly provided slice heights for slices in the video tile that includes the slice.

[00222] In some embodiments, the height of the slice in the video tile in units of coding tree units is derived from information for the video in response to the value of the first syntax element being equal to 0. In some embodiments, the height of the slice in the video tile in units of coding tree units is represented as sliceHeightInCtus [i]. sliceHeightInCtus [i] is equal to a value of a row height $\text{RowHeight} [\text{SliceTopLeftTileIdx} [i] / \text{NumTileColumns}]$, where SliceTopLeftTileIdx specifies a tile index of a tile that includes a first coding tree unit in the slice and NumTileColumns specifies a number of tile columns, and the value of the row height $\text{RowHeight}[j]$ specifies a height of a j-th tile row in units of coding tree blocks.

[00223] In some embodiments, the height of the slice in the video tile in units of coding tree units is derived from information for the video in response to the height for the slice in the video

tile being not present in the bitstream. In some embodiments, the height of the slice in the video tile in units of coding tree units is derived according to a second syntax element present in the bitstream that indicates the height of the slice in the video tile. In some embodiments, in response to the first syntax element being equal to 0, the video tile that includes the slice is not split into multiple slices.

[00224] FIG. 29 is flowchart representation of a method for video processing in accordance with the present technology. The method 2900 includes, at operation 2910, performing a conversion between a video comprising a video picture comprising a video tile including one or more slices and a bitstream of the video according to a rule. The rule specifies that a second slice in a tile that includes a first slice in a picture has a height that is represented in a unit of coding tree units. The first slice has a first slice index, and the second slice has a second slice index that is determined based on the first slice index and a number of explicitly provided slice heights in the video tile. The height of the second slice is determined based on the first slice index and the second slice index.

[00225] In some embodiments, the first slice index is represented as i , and the second slice index is represented as $(\text{num_exp_slices_in_tile}[i] - 1)$, where $\text{num_exp_slices_in_tile}$ specifies a number of explicitly provided slice heights in the video tile. The height of the second slice is determined based on $\text{exp_slice_height_in_ctus_minus1}[i][\text{num_exp_slices_in_tile}[i] - 1] + 1$, where $\text{exp_slice_height_in_ctus_minus1}$ specifies slice heights in the unit of coding tree units in the video tile. In some embodiments, a height of uniform slices that partition the video tile is indicated by a last entry of $\text{exp_slice_height_in_ctus_minus1}$. In some embodiments, the second slice always exists in the picture. In some embodiments, the height of the second slice is disallowed to be reset for the conversion. In some embodiments, a height of a third slice having an index greater than $(\text{num_exp_slices_in_tile}[i] - 1)$ is determined based on $\text{exp_slice_height_in_ctus_minus1}[i][\text{num_exp_slices_in_tile}[i] - 1]$. In some embodiments, the second slice does not exist in the video tile. In some embodiments, the height of the second slice is smaller than or equal to $\text{exp_slice_height_in_ctus_minus1}[i][\text{num_exp_slices_in_tile}[i] - 1] + 1$.

[00226] FIG. 30 is flowchart representation of a method for video processing in accordance with the present technology. The method 3000 includes, at operation 3010, performing a conversion

between a video comprising a video picture including one or more tiles and a bitstream of the video. The video picture refers to a picture parameter set. The picture parameter set conforms to a format rule specifying that the picture parameter set includes a list of column widths for N tile columns, where N is an integer. An (N-1)-th tile column exists in the video picture and the (N-1)-th tile column has a width that is equal to an (N-1)-th entry in a list of explicitly included tile column widths plus one number of coding tree blocks.

[00227] In some embodiments, N-1 is represented as num_exp_tile_columns_minus1. In some embodiments, a width of the tile column in a unit of coding tree blocks is determined based on tile_column_width_minus1[num_exp_tile_columns_minus1] + 1, where tile_column_width_minus1 specifies a width of a tile column in the unit of coding tree blocks. In some embodiments, the width of the tile column in the unit of coding tree blocks is disallowed to be reset and is determined solely based on tile_column_width_minus1[num_exp_tile_columns_minus1]. In some embodiments, the width of the tile column in the unit of coding tree blocks is equal to tile_column_width_minus1[num_exp_tile_columns_minus1] + 1. In some embodiments, a width of a second tile column having an index that is greater than num_exp_tile_columns_minus1 is determined based on tile_column_width_minus1[num_exp_tile_columns_minus1].

[00228] FIG. 31 is flowchart representation of a method for video processing in accordance with the present technology. The method 3100 includes, at operation 3110, performing a conversion between a video comprising a video picture including one or more tiles and a bitstream of the video. The video picture refers to a picture parameter set. The picture parameter set conforms to a format rule specifying that the picture parameter set includes a list of row heights for N tile rows, where N is an integer. An (N-1)-th tile row exists in the video picture and the (N-1)-th tile row has a height that is equal to an (N-1)-th entry in a list of explicitly included tile row heights plus one number of coding tree blocks.

[00229] In some embodiments, N-1 is represented as num_exp_tile_rows_minus1. In some embodiments, a height of the tile row in a unit of coding tree blocks is determined based on tile_row_height_minus1[num_exp_tile_row_minus1] + 1, where tile_row_height_minus1 specifies a height of a tile row in the unit of coding tree blocks. In some embodiments, the height

of the tile row in the unit of coding tree blocks is disallowed to be reset and is determined solely based on `tile_row_height_minus1[ num_exp_tile_row_minus1 ]`. In some embodiments, the height of the tile row in the unit of coding tree blocks is equal to `tile_row_height_minus1[ num_exp_tile_row_minus1 ] + 1`. In some embodiments, a height of a second tile row having an index that is greater than `num_exp_tile_rows_minus1` is determined based on `tile_row_height_minus1[ num_exp_tile_row_minus1 ]`.

[00230] In some embodiments, the conversion includes encoding the video into the bitstream. In some embodiments, the conversion includes decoding the video from the bitstream.

[00231] In the solutions described herein, an encoder may conform to the format rule by producing a coded representation according to the format rule. In the solutions described herein, a decoder may use the format rule to parse syntax elements in the coded representation with the knowledge of presence and absence of syntax elements according to the format rule to produce decoded video.

[00232] In the present document, the term “video processing” may refer to video encoding, video decoding, video compression or video decompression. For example, video compression algorithms may be applied during conversion from pixel representation of a video to a corresponding bitstream representation or vice versa. The bitstream representation of a current video block may, for example, correspond to bits that are either co-located or spread in different places within the bitstream, as is defined by the syntax. For example, a macroblock may be encoded in terms of transformed and coded error residual values and also using bits in headers and other fields in the bitstream. Furthermore, during conversion, a decoder may parse a bitstream with the knowledge that some fields may be present, or absent, based on the determination, as is described in the above solutions. Similarly, an encoder may determine that certain syntax fields are or are not to be included and generate the coded representation accordingly by including or excluding the syntax fields from the coded representation.

[00233] The disclosed and other solutions, examples, embodiments, modules and the functional operations described in this document can be implemented in digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this document and their structural equivalents, or in combinations of one or more of them. The disclosed and other embodiments can be implemented as one or more computer program products, i.e., one or

more modules of computer program instructions encoded on a computer readable medium for execution by, or to control the operation of, data processing apparatus. The computer readable medium can be a machine-readable storage device, a machine-readable storage substrate, a memory device, a composition of matter effecting a machine-readable propagated signal, or a combination of one or more them. The term “data processing apparatus” encompasses all apparatus, devices, and machines for processing data, including by way of example a programmable processor, a computer, or multiple processors or computers. The apparatus can include, in addition to hardware, code that creates an execution environment for the computer program in question, e.g., code that constitutes processor firmware, a protocol stack, a database management system, an operating system, or a combination of one or more of them. A propagated signal is an artificially generated signal, e.g., a machine-generated electrical, optical, or electromagnetic signal, that is generated to encode information for transmission to suitable receiver apparatus.

[00234] A computer program (also known as a program, software, software application, script, or code) can be written in any form of programming language, including compiled or interpreted languages, and it can be deployed in any form, including as a stand-alone program or as a module, component, subroutine, or other unit suitable for use in a computing environment. A computer program does not necessarily correspond to a file in a file system. A program can be stored in a portion of a file that holds other programs or data (e.g., one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that store one or more modules, sub programs, or portions of code). A computer program can be deployed to be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

[00235] The processes and logic flows described in this document can be performed by one or more programmable processors executing one or more computer programs to perform functions by operating on input data and generating output. The processes and logic flows can also be performed by, and apparatus can also be implemented as, special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application specific integrated circuit).

[00236] Processors suitable for the execution of a computer program include, by way of example, both general and special purpose microprocessors, and any one or more processors of any kind of digital computer. Generally, a processor will receive instructions and data from a read only memory or a random-access memory or both. The essential elements of a computer are a processor for performing instructions and one or more memory devices for storing instructions and data. Generally, a computer will also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data, e.g., magnetic, magneto optical disks, or optical disks. However, a computer need not have such devices. Computer readable media suitable for storing computer program instructions and data include all forms of non-volatile memory, media and memory devices, including by way of example semiconductor memory devices, e.g., EPROM, EEPROM, and flash memory devices; magnetic disks, e.g., internal hard disks or removable disks; magneto optical disks; and CD ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in, special purpose logic circuitry.

[00237] While this patent document contains many specifics, these should not be construed as limitations on the scope of any subject matter or of what may be claimed, but rather as descriptions of features that may be specific to particular embodiments of particular techniques. Certain features that are described in this patent document in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

[00238] Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. Moreover, the separation of various system components in the embodiments described

in this patent document should not be understood as requiring such separation in all embodiments.

[00239] Only a few implementations and examples are described and other implementations, enhancements and variations can be made based on what is described and illustrated in this patent document.

CLAIMS

1. A method of processing video data, comprising:
 - determining, for a conversion between a video comprising a video picture referring to a picture parameter set (PPS) and a bitstream of the video, a scanning process is applied to the video picture, wherein the video picture is partitioned into one or more tiles, one or more slices, and multiple coding tree units,
 - determining, in the scanning process, that a first syntax element is conditionally included in the PPS in the bitstream to indicate a number of rectangular slices in the video picture,
 - determining, for a slice of the number of rectangular slices which has a first slice index, that a second syntax element is conditionally included in the bitstream to indicate a number of explicitly provided slice heights for slices in a video tile comprising the rectangular slice having the first slice index, wherein the number of explicitly provided slice heights for slices in the video tile is equal to N , and N is no less than 0,
 - determining, when N is no less than 1, N third syntax elements are included in the bitstream to indicate slice heights of N slices in units of coding tree unit (CTU) rows, respectively, and
 - performing the conversion based on the second syntax element and the N third syntax elements;
 - wherein when a height of the video tile is greater than a sum of the slice heights of the N slices, a slice height of a remaining slice in the video tile other than the N slices is determined based on a slice height of a last slice of the N slices, and
 - wherein when a difference between the height of the video tile in units of coding tree blocks and a sum of the slice heights of the N slices is no less than a uniform slice height, the uniform slice height is used to partition the remaining part of the video tile other than the N slices recursively to form one or more uniform slices, until the remaining part of the video tile other than the N slices and the one or more uniform slices has a height less than the uniform slice height.
2. The method of claim 1, wherein a slice height of a slice of the N slices in units of CTU rows is equal to 1 plus a value of a third syntax element of the N third syntax elements corresponding to the slice.

3. The method of claim 1 or 2, wherein when a difference between the height of the video tile in units of coding tree blocks and a sum of the slice heights of the N slices is no less than a slice height of the last slice of the N slices, a slice height of one remaining slice of the video tile other than the N slices is set to be equal to the slice height of the last slice of the N slices.
4. The method of claim 1, wherein the uniform slice height is equal to the slice height of the last slice of the N slices, and
wherein when the remaining part of the video tile other than the N slices and the one or more uniform slices has a slice height less than the uniform slice height, a slice height of a last slice of the video tile is set to be a difference between the height of the video tile and a sum of the slice heights of the N slices and the one or more uniform slices.
5. The method of any one of claims 1-4, wherein when a difference between the height of the video tile in units of coding tree blocks and a sum of the slice heights of the N slices is less than a uniform slice height, a slice height of a (N+1)-th slice of the video tile is set to be the difference.
6. The method of any one of claims 1-5, wherein the slice height of the last slice of the N slices is disallowed to be reset, and a value of a last third syntax element of the N third syntax elements is directly used to derive a uniform slice height without referring other information.
7. The method of any one of claims 1-6, wherein when a value of the second syntax element is equal to 0, the third syntax elements are absent from the bitstream, and a slice height of a slice in the video tile is derived to be equal to the height of the video tile in units of coding tree blocks.
8. The method of any one of claims 1-7, wherein the scanning process is applied to the video picture when the first syntax element is equal to 0, or when a syntax element which plus 1 specifies a width of the rectangular slice having the first slice index in units of tile columns is equal to 0, and a syntax element which plus 1 specifies a height of the rectangular slice having the first slice index in units of tile rows is equal to 0.

9. The method of any one of claims 1-8, wherein the conversion includes encoding the video into the bitstream.

10. The method of any one of claims 1-8, wherein the conversion includes decoding the video from the bitstream.

11. An apparatus for processing video data comprising a processor and a non-transitory memory with instructions thereon, wherein the instructions upon execution by the processor, cause the processor to:

determine, for a conversion between a video comprising a video picture referring to a picture parameter set (PPS) and a bitstream of the video, a scanning process is applied to the video picture, wherein the video picture is partitioned into one or more tiles, one or more slices, and multiple coding tree units,

determine, in the scanning process, that a first syntax element is conditionally included in the PPS in the bitstream to indicate a number of rectangular slices in the video picture,

determine, for a slice of the number of rectangular slices which has a first slice index, that a second syntax element is conditionally included in the bitstream to indicate a number of explicitly provided slice heights for slices in a video tile comprising the rectangular slice having the first slice index, wherein the number of explicitly provided slice heights for slices in the video tile is equal to N , and N is no less than 0,

determine, when N is no less than 1, N third syntax elements are included in the bitstream to indicate slice heights of N slices in units of coding tree unit (CTU) rows, respectively, and

perform the conversion based on the second syntax element and the N third syntax elements;

wherein when a height of the video tile is greater than a sum of the slice heights of the N slices, a slice height of a remaining slice in the video tile other than the N slices is determined based on a slice height of a last slice of the N slices, and

wherein when a difference between the height of the video tile in units of coding tree blocks and a sum of the slice heights of the N slices is no less than a uniform slice height, the uniform slice height is used to partition the remaining part of the video tile other than the N

slices recursively to form one or more uniform slices, until the remaining part of the video tile other than the N slices and the one or more uniform slices has a height less than the uniform slice height.

12. The apparatus of claim 11, wherein a slice height of a slice of the N slices in units of CTU rows is equal to 1 plus a value of a third syntax element of the N third syntax elements corresponding to the slice.

13. The apparatus of claim 11 or 12, wherein when a difference between the height of the video tile in units of coding tree blocks and a sum of the slice heights of the N slices is no less than a slice height of the last slice of the N slices, a slice height of one remaining slice of the video tile other than the N slices is set to be equal to the slice height of the last slice of the N slices.

14. The apparatus of claim 11, wherein the uniform slice height is equal to the slice height of the last slice of the N slices, and

wherein when the remaining part of the video tile other than the N slices and the one or more uniform slices has a slice height less than the uniform slice height, a slice height of a last slice of the video tile is set to be a difference between the height of the video tile and a sum of the slice heights of the N slices and the one or more uniform slices.

15. A non-transitory computer-readable storage medium storing instructions that cause a processor to:

determine, for a conversion between a video comprising a video picture referring to a picture parameter set (PPS) and a bitstream of the video, a scanning process is applied to the video picture, wherein the video picture is partitioned into one or more tiles, one or more slices, and multiple coding tree units,

determine, in the scanning process, that a first syntax element is conditionally included in the PPS in the bitstream to indicate a number of rectangular slices in the video picture,

determine, for a slice of the number of rectangular slices which has a first slice index, that a second syntax element is conditionally included in the bitstream to indicate a number of

explicitly provided slice heights for slices in a video tile comprising the rectangular slice having the first slice index, wherein the number of explicitly provided slice heights for slices in the video tile is equal to N , and N is no less than 0,

determine, when N is no less than 1, N third syntax elements are included in the bitstream to indicate slice heights of N slices in units of coding tree unit (CTU) rows, respectively, and perform the conversion based on the second syntax element and the N third syntax elements;

wherein when a height of the video tile is greater than a sum of the slice heights of the N slices, a slice height of a remaining slice in the video tile other than the N slices is determined based on a slice height of a last slice of the N slices, and

wherein when a difference between the height of the video tile in units of coding tree blocks and a sum of the slice heights of the N slices is no less than a uniform slice height, the uniform slice height is used to partition the remaining part of the video tile other than the N slices recursively to form one or more uniform slices, until the remaining part of the video tile other than the N slices and the one or more uniform slices has a height less than the uniform slice height.

16. The non-transitory computer-readable storage medium of claim 15, wherein a slice height of a slice of the N slices in units of CTU rows is equal to 1 plus a value of a third syntax element of the N third syntax elements corresponding to the slice.

17. A non-transitory computer-readable recording medium storing a bitstream of a video which is generated by a method performed by a video processing apparatus, wherein the method comprises:

determining, for a video comprising a video picture referring to a picture parameter set (PPS), a scanning process is applied to the video picture, wherein the video picture is partitioned into one or more tiles, one or more slices, and multiple coding tree units,

determining, in the scanning process, that a first syntax element is conditionally included in the PPS in the bitstream to indicate a number of rectangular slices in the video picture,

determining, for a slice of the number of rectangular slices which has a first slice index, that a second syntax element is conditionally included in the bitstream to indicate a number of

explicitly provided slice heights for slices in a video tile comprising the rectangular slice having the first slice index, wherein the number of explicitly provided slice heights for slices in the video tile is equal to N , and N is no less than 0,

determining, when N is no less than 1, N third syntax elements are included in the bitstream to indicate slice heights of N slices in units of coding tree unit (CTU) rows, respectively, and

generating the bitstream based on the second syntax element and the N third syntax elements,

wherein when a height of the video tile is greater than a sum of the slice heights of the N slices, a slice height of a remaining slice in the video tile other than the N slices is determined based on a slice height of a last slice of the N slices.

18. The non-transitory computer-readable recording medium of claim 17, wherein a slice height of a slice of the N slices in units of CTU rows is equal to 1 plus a value of a third syntax element of the N third syntax elements corresponding to the slice.