

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
1 August 2002 (01.08.2002)

PCT

(10) International Publication Number
WO 02/059540 A2

(51) International Patent Classification⁷: **F41C 33/02**

(21) International Application Number: PCT/US02/02337

(22) International Filing Date: 28 January 2002 (28.01.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/770,710 26 January 2001 (26.01.2001) US
10/058,564 28 January 2002 (28.01.2002) US

(71) Applicant: **SAFARILAND LTD., INC.** [US/US]; 3120
East Mission Boulevard, Ontario, CA 91761 (US).

(74) Agent: **YEAGER, Arthur, G.**; Suite 1305, 112 West
Adams Street, Jacksonville, FL 32202-3853 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: AUTOMATIC LOCKING HOLSTER



(57) Abstract: A quick release withdrawal restraint holster includes a blocking element (35) located to engage a portion of the handgun (16) adjacent its ejection port (19) to inhibit withdrawal upwardly prior to rearward handgun movement. A second blocking element (49) is located adjacent the rear of the trigger guard (17) biased into a first position to prevent rearward movement of gun (16) and a second position that allows for rearward movement of gun (16) when the second blocking element (49) is moved by pressure on a thumb ledge (57). A third blocking element (126) is provided to prevent motion of a handgun (16) when holstered in a manner to cause movement of the second blocking element (49) from its first position. Additionally a hood strap assembly (13) includes a thumb ledge (30) by which a leg (31) can be pushed downwardly to allow strap (29) to be rotated forwardly once the locking mechanism is cleared. Releasable blocking apparatus (32) includes a thumb ledge (33) by which a blocking element (34) can be moved rearwardly to allow the leg (31) to be pushed downwardly and allow rotation of the strap (29).



WO 02/059540 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.