-1 FEB 2007

166166

SPECIFICATION

COMPUTER, DISPLAY DEVICE SETTING METHOD, AND PROGRAM

Technical Field

The present invention relates to a computer apparatus such as a personal computer of notebook type (notebook PC), and more particularly to a computer apparatus capable of connecting a display device.

Background Art

Some of the computers represented by a personal computer of notebook type (notebook PC) are able to connect a display device such as a television (TV) projector or an external extension CRT. For example, employing a notebook PC, the same image is displayed on a liquid crystal display (LCD) equipped for itself or an external display, or the image is displayed on a multi-display consisting of a plurality of displays. Conventionally, various proposals have been made for such image display using a plurality of displays. For example, taking a presentation as an example, a computer screen is directly displayed using a projector (a projection type display for projecting onto the screen).

Herein, to enable a display device connected to the computer to be operative, it is required for the user to perform a complex setting operation. When a CRT display is connected to the notebook PC, the video signal must be output under the conditions adapted to the external CRT connected as well as the liquid crystal display (LCD) contained in the notebook PC. The user needs to set different synchronous frequencies to two CRT controllers (CRTC) for the LCD and external CRT in a synchronous mode of synchronizing the display, for example. Also, when a large desk top is constructed employing the LCD and the external CRT in a multi-monitor mode, for example,

G00002

it is required to make various different settings such as horizontal and vertical synchronizing frequencies, resolution and number of colors for the LCD and the external CRT, in which these complex settings must be made every time the external CRT is connected.

Also, when the screen display for presentation is realized on this multi-monitor, for example, when the presentation is made employing the external display connected to the notebook PC, it is often desired to display only an image different from the image displayed on the LCD of the notebook PC such as an image necessary for the presentation, by removing various kinds of icons and task bars. Also, it is not favorable for the presentation that the display screen transfers to a screen saver screen with a screen saver function, or the display image on the display disappears because of the operation of a power management function.

The present invention has been achieved to solve the above-mentioned technical problems, and it is an object of the invention to simply set up the configuration regarding a display function for a display device connected to the computer apparatus.

Also, it is another object of the invention to simply switch between the settings of the display device making up a multi-monitor in constructing the multi-monitor.

Disclosure of the Invention

In order to accomplish the above object, this invention provides a computer apparatus enabling a first display device and an external second display device to be connected, the computer apparatus comprising a profile creation means for creating, as a profile, the setting information for the second display device that is different from the setting information for the first display device, a profile storage means for storing the profile created by the profile creation means, a profile list display means for displaying a list of profiles stored in the profile storage means upon pushing down of a hot key

so as to allow a user to select the profile, and a setting means for setting the information for the second display device by invoking the profile stored in the profile storage means based on the profile displayed on the profile list display means and selected by the user, for example, upon pushing down of a hot key. The profile creation means can create the profile including the setting information of the first display device. That is, different setting information or common setting information for the first display device and the second display device may be included in the profile.

In essence, the invention provides a computer apparatus enabling plural types of display devices to be connected, the computer apparatus comprising a profile creation means for creating, for each display device, a profile including an information set for controlling the display device, a profile storage means for storing the profile created by the profile creation means, and a setting means for setting the information for controlling the display device on the computer apparatus based on the profile by invoking the profile stored in the profile storage means in response to a predetermined operation by the user.

Herein, the profile creation means creates the profile employing arbitrary name by the user, wherein the profile list display means displays the list employing the arbitrary name. Also, the profile creation means creates the setting information including any one of resolution, color depth and refresh rate of the second display device, or creates the setting information regarding a screen saver function and/or a power management function. The first display device may be a notebook PC in which the main system and the display device are provided within the same housing, or a desktop computer in which the display device is provided within a different housing from the main system.

According to another aspect, the invention provides a computer apparatus comprising a video controller having a plurality of CRT controllers (typically display device controllers), a memory for

storing the setting information of a plurality of display devices as the profiles corresponding to the plurality of display devices, the display devices being connected to the plurality of CRT controllers and having different characteristics, and a CPU for controlling the video controller based on the setting information included in a profile by invoking the profile from the memory in accordance with a designation from a user, wherein the video controller sets different synchronizing frequencies to the plurality of CRT controllers based on the setting information when displaying images on the plurality of display devices simultaneously.

Herein, the video controller comprises a first CRT controller and a second CRT controller, and the profile stored in the memory includes the information for making any one of a display device connected to the first CRT controller and a display device connected to the second CRT controller a primary display device. This constitution is preferable in that when an application is executed, the display device for simply displaying an application execution screen can be preset as the primary display device. This display device set as primary is employed as the main display device, in which an application on execution, if simply executed, is displayed on this main display device, and the icons and task bars are directly displayed.

On the other hand, the invention provides a display device setting method comprising a step of creating the setting information on each of a plurality of display devices to be connectable to a computer apparatus, a step of storing the created setting information as a profile for each display device, a step of displaying a list of profiles stored upon pushing down of a hot key by a user, a step of accepting a designation of the profile from the user from among the profiles displayed in the list, and a step of invoking a specific profile based on the designation, and setting up a corresponding display device based on the profile.

Also, the invention provides a display device setting method for

use with a computer apparatus to display an image on a first display device and an external second display device connected to the computer apparatus, comprising a step of selecting any one of the first display device and the second display device as a primary display device, a step of inputting the setting information in the first display device and/or the second display device, a step of storing a profile including the information indicating that the primary display device is selected, together with the input setting information, a step of selecting a screen saver off and/or a power management timer off for the first display device and/or the second display device, and a step of storing the information selected screen saver off and/or power management timer off in the profile.

Moreover, the invention may be grasped as a program that is executed on the computer. That is, the program of the invention enables a computer apparatus enabling a first display device and an external second display device to be connected to perform a creation function of creating the display setting information on the second display device, a storage function of storing the created display setting information as a profile on a predetermined storage device, a designation recognition function of displaying a list of profiles including their names upon pushing down of a hot key by a user and recognizing a designation of the profile from the user using the list, and a setting function of invoking the profile based on the recognition of the designation recognition function, and making the settings of a display on the second display device based on the profile.

Also, the invention provides a program for a computer apparatus enabling a first display device and an external second display device to be connected, the program enabling the computer to perform a primary setting display function of displaying the information for selecting any one of the first display device and the second display device as a primary display device, a setting information display function of displaying the information for inputting the setting information including the resolution, color depth and refresh rate (synchronizing frequency) on the first display device and/or the second display

device, and a storage function of storing an input of a user based on the information displayed with the primary setting display function and the setting information display function as the profile.

A way of providing these programs may be through the use of the recording medium that stores a program executed by the computer to be readable by the computer. Examples of the recording medium include a floppy disk, a CD-ROM medium, and so on. A program is read by a floppy disk drive (FDD) or a CD-ROM reader, stored in a flash ROM and executed by the computer. Also, these programs may be distributed via a network by a program transmission apparatus to the notebook computer. This program transmission apparatus comprises a memory provided in a server on the host side and storing the program, and program transmission means for providing the program via the network, for example. Moreover, when the computer is provided to the customer, the programs may be installed in the computer.

Brief Description of the Drawings

Figure 1 is a block diagram showing the hardware configuration of a computer system according to this embodiment;

Figure 2 is a diagram for explaining the software configuration;

Figure 3 is a flowchart showing a process that is performed by a display profile setting/switching program;

Figure 4 is a flowchart showing a process that is performed by a hot key switching component;

Figure 5 is a view showing an example of a main screen of wizard;

Figure 6 is a view showing an example of a wizard screen for setting up the display configuration for a video controller;

Figure 7 is a view showing an example of wizard screen for constructing

a large desktop with a multi-monitor configuration; and

Figure 8 is a view showing an example of a user selection screen for allowing the profile to be invoked and switched with a hot key.

Best Mode for Carrying Out the Invention

The present invention will be described below in detail in connection with the embodiments as shown in the accompanying drawings.

Figure 1 is a diagram showing the hardware configuration of a computer system according to this embodiment. Herein, an external CRT display 30 as a second display device is connected to a notebook PC (personal computer of notebook type) 10 that is a computer. The notebook PC 10 as shown in Figure 1 is normally equipped with a liquid crystal display (LCD) 20 as a first display device.

A system of the notebook PC 10 comprises a CPU that operates as a brain of the overall system and executes an OS, the utility programs running under the control of the OS, and various other kinds of programs, a memory 12, which is a writable memory, used as a reading area for reading an execution program of the CPU 11, or a working area for writing the processing data of the execution program, and a PCI (Peripheral Component Interconnect) bus 13, which is a bus capable of making the data transfer at relatively high speed, and standardized by such specifications as, for example, a data bus width of 32 bits or 64 bits, a maximum operation frequency of 33 MHz or 66 MHz, and a maximum data transfer rate of 132 MB/sec or 528 MB/sec. The execution programs of the CPU 11 include various kinds of drivers for operating the hardware of the OS and peripheral devices, application programs directed for specific applications, and a firmware such as BIOS (Basic Input/Output System).

A video controller 14 is connected to the PCI bus 13. This video controller 14 processes a drawing instruction from the CPU 11, writes the processed drawing instruction as drawing information into a video

memory (not shown), and reads this drawing information from the video memory to output drawing data to a display. The video controller 14 of this embodiment comprises a first CRT controller (CRTC-1) 15 for controlling the external CRT display 30 and a second CRT controller (CRTC-2) 16 for controlling the liquid crystal display 20.

Also, a hard disk controller 17 for controlling a hard disk drive (HDD) 18 that is an external storage unit is connected to the PCI bus 13. The HDD 18 stores a profile inherent to each display device, which is a feature in this embodiment. The external storage unit such as the HDD 18 is accommodated in storage space, called a "media bay" or "device bay", within the main body of the notebook PC 10, for example. The external storage unit normally equipped may be exclusively replaced with another device such as a FDD or a battery pack.

In this embodiment, there is provided a method for momentarily switching to the display device (liquid crystal display 20 connected to the notebook PC 10 or external CRT display 30) in which the profile inherent to the display device is loaded by software. The switching software sets up the display resolution, color depth and synchronizing frequency corresponding to each display by reading the profile stored in the HDD 18 and sending a series of commands to the video controller 14. As one example, when the CRT display 30 and the liquid crystal display 20 are operated at the same time, the first CRT controller (CRTC-1) 15 and the second CRT controller (CRTC-2) 16 of the video controller 14 are set at different synchronizing frequencies to enable synchronization of the display independently.

For example, in this embodiment, the profile has a favorite name (arbitrary designation) given by the user to register the setting information of each display unit. In a creation process of profile, a setting wizard is run to prompt the user to select the required and minimum parameters for input. Then, after connection to the display is made by pushing down a test button, for example, if it

is confirmed that the profile is usable without problem, the profile is registered. This profile includes the information regarding the settings of display, and the auxiliary information beneficial in the presentation, when practically employed for presentation. For example, there is a stop condition of a screen saver function or a power management function, as will be described later. One way of using the profile is to register the profile including a specific function necessary for displaying the screen for the new car, when a new car screen is employed many times for sales of the car.

A software processing of this embodiment will be described below.

Figure 2 is a diagram for explaining the software configuration. In this embodiment, two principal software components are provided. One of the components is a display profile setting/switching program 40 that is a program required to create the profile, and the other is a hot key switching component 50 enabling the momentary switching. The display profile data is simply set up by these software components, and the configuration of the display selected from the profile is promptly set up by momentarily invoking a list of display profiles already created, employing a hot key. The hot key as used herein is the key used when designating a running program, or calling an add-in soft or a resident program, for example, Fn+F7 key.

The display profile setting/switching program 40 includes, as a User Mode, a Presentation Director Wizard, GUI 41 that is a setting wizard for setting the display information, a Presentation Director DLL (Dynamic Link Library) 42, and a Display Interface DLL 43, and as a Kernel Mode, a Display Driver 44 and a Video BIOS 45. The video BIOS 45 controls the input/output of a display switching 46. One series of software from the Presentation Director DLL 42 to the Video BIOS 45 perform a switching process by invoking the profile and setting up the display device.

The Presentation Director Wizard 41 has a function of providing the user interface in creating the setting configuration information

of the display device as the profile. When the user performs the Presentation Director Wizard 41, the required display configuration is saved as the profile. When saving the profile, the user pushes down the test button to check whether or not the profile is actually valid. Thereby, the operation is confirmed in advance.

The Presentation Director DLL 42 is a set of common routines for extracting the necessary information in performing the profile created by the user, and making the settings regarding the Display Interface DLL 43. The Display Interface DLL 43 provides a calling source interface required in notifying the settings of the display to the Display Driver 44.

The Display Driver 44 is the driver for making the settings of the display. Also, the Video BIOS 45 is the BIOS (Basic Input/Output System) for internally sending a command to the video controller 14, and controlling the input/output for the display switching 46. The display switching 46 indicates the type of display device connected to the video controller 14. The display device may be the external CRT display 30, the liquid crystal display 20 connected to the main body of the notebook PC 10, an external TV or a projector.

The hot key switching component 50 includes, as the User Mode, a Hot key manager/On-screen utility 51 and a PM Driver Service 52, and as the Kernel Mode, a PM Driver, Fn key notify handler 53, and an Fn key ACPI control method 54 that is the BIOS. The Fn key ACPI control method 54 accepts an event of function (Fn) key made from an input part 55 and notifies it to the PM Driver, Fn key notify handler 53 that is the driver.

The Hot key manager/On-screen utility 51 is the software resident on the memory 12, and provides a user interface having a function of momentarily calling the display configuration Profile created beforehand by the Presentation Director Wizard 41 upon pushing down of the hot key of the notebook PC 10, and displaying it on the screen of the liquid crystal display 20, for example. The Hot key

manager/On-screen utility 51 displays a name list of profiles created beforehand by the user on the screen, in which the profile selected by the user is passed via this software to a module on the Presentation Director DLL 42.

The PM Driver Service 52, the PM Driver, Fn key notify handler 53, and the Fn key ACPI control method 54 are a module of device driver and BIOS to notify an event of the key to the Hot key manager/On-screen utility 51 when the user pushes down the hot key from the input part 55. Upon pushing down of the hot key in the input part 55, the BIOS of the Fn key ACPI control method 54 is called to notify the information of the pushed down key via the PM Driver, Fn key notify handler 53 and the device driver of the PM Driver Service 52 to the Hot key manager/On-screen utility 51.

Figure 3 is a flowchart showing a procedure performed by the display profile setting/switching program 40. First of all, the procedure is started by executing the Presentation Director Wizard 41 to create an extended mode profile. Firstly, various kinds of settings are made, corresponding to the display device to be connected. Herein, the configuration profile of the display device used for presentation, for example, is set up in terms of the resolution, color depth, power management timer off, screen saver off, and other settings (step 101). Then, the hot key (e.g., Fn+F7 key) is set to enable (step 102). With this settings, the set hot key is usable in the extended mode. Thereafter, the setting information of the set-up display device is stored as the extended mode profile (step 103), and the procedure is ended. In this manner, the extended mode profile is set, and the hot key is enabled as the extended mode.

The reason why the power management off and screen saver off are set up at step 101 is to prevent the screen from disappearing due to the power management function that is active if no operation continues for a certain time and prevent the screen from transferring to the screen saver screen due to action of the screen saver function when setting up the display on the CRT display 30 for presentation.

In this embodiment, besides the normal setting information of the display device, the display device is set up with those functions. In this embodiment, the "extended mode" is the mode of calling the already created display profile to set up the liquid crystal display 20 that is the first display and the CRT display 30 that is the second display by pushing down the hot key, or set up the power management mode and other modes required for specific purposes such as presentation. By this "extended mode", the functions can be specialized for specific purposes such as presentation. On the other hand, in a "normal mode", which is different from the "extended mode", the hot key performs the normally defined operation. For example, the Fn+F7 key effects a simple switching operation of the display (between LCD display, CRT display, and LCD/CRT concurrent display).

Figure 4 is a flowchart showing a procedure performed by the hot key switching component 50. First of all, the pushing down of the Fn+F7 key, for example, is recognized as an event of the function (Fn) key made from the input part 55 via the Fn key ACPI control method 54 that is the BIOS and the PM Driver, Fn key notify handler 53 that is the driver by the Hot key manager/On-screen utility 51 (step 111). Herein, it is determined whether or not the extended mode such as the mode used for presentation is set up (step 112). If the extended mode is not set up, the extended mode profile is reset (step 116), and the procedure is ended.

If the extended mode is set up at step 112, a selection menu, namely, a profile list, is displayed on the screen of the liquid crystal display 20 (step 113). Then, it is determined whether or not the corresponding display device designated by the hot key is connected (step 114). If not connected, its message is indicated, for example, and the selection menu at step 113 is displayed again. If connected, the extended mode profile is loaded (step 115), and then the setting/switching process of the display device is performed. In this manner, the event of the hot key (e.g., Fn+F7 key) is monitored, and if the hot key is pushed down, the extended mode profile is acquired.

Figures 5 to 7 are views showing the screen examples displayed in creating the display configuration profile by the Presentation Director Wizard 41. Figure 5 is a main screen of wizard, in which if the profile has been already created, the profile name is displayed as a list. The profile may be changed from this screen.

Figure 6 shows a screen example of wizard for setting the display configuration for the video controller 14 that is the dual CRT controller. For example, when the liquid crystal display 20 and the CRT display 30 are set up separately for the display configuration by the dual CRT controller having the first CRT controller (CRTC-1) 15 and the second CRT controller (CRTC-2) 16, the settings can be made on the screen display as shown in Figure 6. Herein, the set-up display is firstly selected, and set up in terms of the resolution, color depth and refresh rate.

Figure 7 is a view showing a screen example of wizard in configuring the large desktop with the multi-monitor. Herein, the settings of configuring the large desktop with the liquid crystal display 20 and the external CRT display 30 are shown. In Figure 7, various settings are made by selecting the display, and which is the primary monitor of the liquid crystal display 20 and the CRT display 30 is designated.

For example, the designation of the primary monitor is made by setting which of the displays is the main (principal) display and which is the sub (subsidiary) display. For example, an application on execution is simply displayed for the display set up as primary, with the icons and taskbars being displayed on the screen concurrently. On the other hand, it is not preferred that the icons and task bars are displayed on the display screen for presentation, but a window of necessary application may be only displayed, if possible. In this embodiment, the primary display device is set up. Thereby, if the display for presentation is set up as subsidiary, for example, the necessary information may be only displayed on the display device for presentation by dragging the image information onto the sub screen,

when in practical use.

Figure 8 is a view showing a user selection screen example in which the profile is invoked by the hot key and switched in the hot key switching component 50. In the user interface as shown here, a list of display profiles already created by the Presentation Director Wizard 41 is invoked momentarily, employing the hot key of the notebook PC 10, and the display configuration selected from the profile is settable at once. The profile list as shown in Figure 8 includes the list of arbitrary names, when the user creates the profile employing arbitrary name, for example. The profile list is displayed on the display screen, when the user pushes down the hot key, for example. The user can select a desired display from the displayed profile list and set up or change the configuration of selected display.

In this way, in this embodiment, the user sets up the external display for presentation, for example, employing the setting wizard, and stores it as the profile, thereby promptly switching the external display connected by the hot key. Also, a two CRT controller (CRTC) synchronous mode is supported, and the system can be switched to the multi-monitor mode, employing the hot key. Moreover, the user can set up a plurality of display configurations, store the setting information for use with these display configurations stored as the profile, and acquire the setting information using the hot key whereby the display configuration is promptly switched at the time of presentation, for example.

Moreover, in this embodiment, by setting up not the display for presentation mounted externally on the notebook PC 10 but the liquid crystal display 20 internally equipped as primary, for example, the optimal display configuration for performing the presentation is simply implemented, including inhibiting the display of task bars or icons, or displaying the necessary application alone.

As described above, with this invention, it is possible to simply

set up the configuration regarding the display function for the display device connected to the computer apparatus.

-1 FEB 2007

CLAIMS

1. A computer apparatus enabling plural types of display devices to be connected, said computer apparatus comprising:

a profile creation means for creating, for each display device, a profile including an information set for controlling said display device;

a profile storage means for storing said profile created by said profile creation means; and

a setting means for setting the information for controlling said display device on said computer apparatus based on said profile by invoking said profile stored in said profile storage means in response to a predetermined operation by a user.

2. The computer apparatus according to Claim 1, further comprising a profile list display means for displaying a list of profiles stored in said profile storage means in response to said operation by the user, wherein said setting means sets said information for controlling said display device on the computer apparatus, based on said profile displayed on said profile list display means and selected by the user.

3. The computer apparatus according to Claim 2, wherein said profile creation means creates said profile employing arbitrary name by the user, wherein said profile list display means displays said list employing said arbitrary name.

4. The computer apparatus according to Claim 1, wherein said information includes any one of resolution, color depth and refresh rate of the display device.

5. The computer apparatus according to Claim 1, wherein said profile creation means creates the setting information regarding a screen

saver function and/or a power management function.

6. A computer apparatus comprising:

a video controller having a plurality of display device controllers;

a memory for storing the setting information of a plurality of display devices as the profiles corresponding to said plurality of display devices, said display devices being connected to said plurality of display device controllers and having different characteristics; and

a control unit for controlling said video controller based on said setting information included in a profile by invoking said profile from said memory in accordance with a designation from a user;

wherein said video controller sets different synchronizing frequencies to said plurality of display device controllers based on said setting information when displaying images on said plurality of display devices simultaneously.

7. The computer apparatus according to Claim 6, wherein said video controller comprises a first display device controller and a second display device controller, and said profile stored in said memory includes the information for making any one of a display device connected to said first display device controller and a display device connected to said second display device controller a primary display device.

8. The computer apparatus according to Claim 6, wherein said setting information stored as said profile in said memory includes the information of resolution and color depth set on each display device.

9. The computer apparatus according to Claim 6, wherein said setting information stored as said profile in said memory includes the information regarding a power management timer function and a screen

saver function set on each display device.

10. A display device setting method comprising the steps of:

creating the setting information on each of a plurality of display devices to be connectable to a computer apparatus;

storing said created setting information as a profile for each display device;

accepting a designation of said profile from a user; and

invoking a specific profile based on said designation, and setting up a corresponding display device based on said profile.

11. The display device setting method according to Claim 10, further comprising a step of displaying a list of said profiles stored upon pushing down of a hot key by the user, wherein said step of accepting the designation of said profile comprises accepting the designation of said profile by the user from among the profiles displayed in said list.

12. A display device setting method for use with a computer apparatus to display an image on a first display device and an external second display device connected to said computer apparatus, comprising the steps of:

selecting any one of said first display device and said second display device as a primary display device;

inputting the setting information in said first display device and/or said second display device; and

storing a profile including the information indicating that said primary display device is selected, together with said input setting information.

13. The display device setting method according to Claim 12, further comprising a step of selecting a screen saver off and/or a power management timer off for said first display device and/or said second display device.

14. A program for a computer apparatus enabling a first display device and an external second display device to be connected, said program comprising:

a creation function of creating the display setting information on said second display device;

a storage function of storing said created display setting information as a profile on a predetermined storage device;

a designation recognition function of recognizing a designation of said profile from a user; and

a setting function of invoking said profile based on the recognition of said designation recognition function, and making the settings of a display on said second display device based on said profile.

15. The program according to Claim 14, wherein said designation recognition function comprises displaying a list including the names of said profiles upon pushing down of a hot key by the user, and recognizing the designation of said profile made by the user employing said list.

16. A program for a computer apparatus enabling a first display device and an external second display device to be connected, said program comprising:

a primary setting display function of displaying the information for selecting any one of said first display device and said second display device as a primary display device;

a setting information display function of displaying the information for inputting the setting information on said first display device and/or said second display device; and

a storage function of storing an input of a user based on the information displayed with said primary setting display function and said setting information display function.

17. The program according to claim 16, wherein said setting information display function displays the information for inputting the setting information of any one of resolution, color depth and refresh rate, and said storage fuunction stores said input as the profile.

18. A computer apparatus comprising:

a built-in liquid crystal display;

a CRT display;

a CPU for executing an operating system;

a video controller operable to receive drawing instructions from the CPU, write the drawing instructions as drawing information into a video memory, and read the drawing information from the video memory to output drawing data to one or more of the liquid crystal display and the CRT display, the video controller including a first CRT controller for controlling the CRT display, and a second CRT controller for controlling the liquid crystal display;

a hard disk controller for controlling a hard disk drive storing display profiles inherent to each of the CRT

display and the liquid crystal display, wherein the CPU is operable to load a profile from the hard disk drive for each of the CRT display and the liquid crystal display, and

the first CRT controller is set at a different synchronizing frequency to that of the second CRT controller in accordance with respective profiles loaded for their respective displays.

19. A display device setting apparatus comprising:

a display profile setting/switching means operable to create a display profile; and

a hot key switching means operable to enable momentary switching, wherein

the display profile setting/switching means and the hot key switching means set up display profile data,

a configuration of a display selected from the profile is set up by invoking, via a hot key, a list of display profiles already created,

the hot key is a key used when designating a running program,

the display profile setting/switching means comprises as a user mode:

a presentation director wizard,

a graphical user interface for setting display information,

a presentation director dynamic link library, and

a display interface dynamic link library;

the display profile setting/switching means comprises as a kernel mode:

a display driver, and

a video bios for controlling the input and output of a display switching;

a series of software from the presentation director dynamic link library to the video bios performs a switching process by invoking a profile and setting up the display device;

the presentation director wizard provides the graphical user interface to create setting configuration information of the display device as the profile, and saves the profile, the presentation director wizard further validates the profile when saving;

the presentation director dynamic link library extracts information necessary for performing a created profile, and makes settings in relation to the display interface dynamic link library;

the display driver makes settings of the display;

the video bios internally sends a command to the video controller, and controls the input/output for the display switching;

the display switching indicates the type of display device connected to the video controller;

the hot key switching means includes, as a user mode, a hot key manager utility and a PM driver service;

the hot key switching means includes, as a kernel mode, a PM driver, Fn key notifying handler, and an Fn key ACPI control method that is the BIOS, the Fn KEY ACPI control method accepting an event of function key made from an input part and notifying the event to the PM driver;

the hot key manager utility provides a user interface having a function of momentarily calling the display configuration profile created beforehand by the presentation director wizard upon the hot key being depressed, and displaying the configuration profile on the screen of the liquid crystal display, the hot key manager utility further displaying a name list of profiles created beforehand by a

user, and passes a profile selected by the user to a module on the presentation director dynamic link library; and

the PM driver service, the PM driver, Fn key notify handler, and the Fn key ACPI control method are a module of device driver and BIOS to notify an event of the key to the hot key manager utility when the hot key from the input part is depressed.

20. A display profile setting/switching method, comprising:

executing a presentation director wizard to create an extended mode profile, the presentation director wizard creating a plurality of settings corresponding to display devices to be connected, the settings including resolution, colour depth, power management timer off, and screen saver off, wherein, in the extended mode, a liquid crystal display is set up as a first display, and a CRT display is set up as a second display;

activating a hot key;

recognizing the activation of the hot key as an event from a Fn key ACPI control method;

determining if the extended mode is set up;

if the extended mode is set up, displaying a selection menu listing available profiles on the liquid crystal display;

determining whether or not a corresponding display device designated by the hot key is connected; and

if the corresponding device is connected, loading the extended mode profile and performing the setting/switching process of the display device.