WHAT IS CLAIMED IS:

1. A dredged soil sorting system for the utilization of reclamation soil, wherein the dredged soil sorting system comprises:

a hydro cyclone having a fine soil outflow portion, where dredged soil is inflowed through an inflow portion of the hydro cyclone and the inflowed dredged soil is sorted and separated, and a sand outflow portion;

a sand transfer portion which transfers sorted and separated sand to ground required to be reclamated; and

a fine soil transfer portion which transfer sorted and separated fine soil to the ground required to be reclamated.

2. The dredged soil sorting system for the utilization of reclamation soil of claim 1, wherein the dredged soil has a fine soil content of 10% by mass or more,

the fine soil has an average grain size of 0.06mm or less, and

the dredged soil sorting system further comprises:

a transfer pump which pumps dredged soil from seabed and transfers the same to the inflow portion of the hydro cyclone,

a measurement portion which is disposed to the sand outflow portion of the hydro cyclone and measures a fine soil content in outflowed sand; and

a control portion which controls at least one of an opening ratio of the sand outflow portion, a flow rate of dredged soil flowed into the hydro cyclone and a pressure of dredged soil flowed into the hydro cyclone, on the basis of values measured in the measurement portion, allowing controlling a fine soil content of the sand outflowed through the sand outflow portion to be 10% or less.

~~3~~2. The dredged soil sorting system for the utilization of reclamation soil of claim 1, wherein

the dredged soil has a fine soil content of 15 to 30% by mass.

~~4. The dredged soil sorting system for the utilization of reclamation soil of claim 2, wherein~~

~~the dredged soil sorting system further comprises a transfer pump which pumps dredged soil from seabed and transfers the same to the inflow portion of the hydro cyclone, and~~

~~the fine soil has an average grain size of 0.06mm or less.~~

~~5~~3. The dredged soil sorting system for the utilization of reclamation soil of claim ~~4~~1, wherein

the dredged soil sorting system further comprises a screen which is installed between the transfer pump and the hydro cyclone, allowing removing gravel or foreign substances from the dredged soil.

~~6~~4. The dredged soil sorting system for the utilization of reclamation soil of claim ~~5~~3, wherein

the dredged soil sorting system further comprises an inflow pump which transfers dredged soil to the inflow portion of the hydro cyclone~~, and~~

~~sand outflowed through the sand outflow portion has a fine soil content of 10 mass% or less~~.

~~7~~5. The dredged soil sorting system for the utilization of reclamation soil of claim ~~5~~3, wherein the dredged soil sorting system comprises:

a first stage hydro cyclone having an inflow portion which allows inflow of dredged soil, a fine soil outflow portion and which sorts and separates the inflowed dredged soil, allowing outflow of fine soil, a first sand outflow portion which allows outflow of sand containing 10% fine soil by mass or less, and a second sand outflow portion which allows outflow of sand containing more than 10% fine soil by mass; and

a second stage hydro cyclone having: a fine soil outflow portion which allows inflow of sand containing more than 10% fine soil by mass and outflowed from the second sand outflow portion of the first stage hydro cyclone and which sorts and separates the inflowed sand, allowing outflow of fine soil, and a sand outflow portion which allows outflow of sand containing 10% fine soil by mass or less, wherein

the sand transfer portion transfers sand having a fine soil content of 10% or less outflowed through the first sand outflow portion of the first stage hydro clone and sand having a fine soil content of 10% or less outflowed through the sand outflow portion of the second stage hydro cyclone to ground required to be reclamated,

the fine soil transfer portion transfers fine soil outflowed through the fine soil outflow portion of the first stage hydro cyclone, and fine soil outflowed through the fine soil outflow portion of the second stage hydro cyclone to ground required to be reclamated.

~~8~~6. The dredged soil sorting system for the utilization of reclamation soil of claim 1, wherein

the dredged soil sorting system further comprises a coagulation portion which coagulates fine soil separated from the hydro cyclone and transfers the same to the fine soil transfer portion.

~~9. The dredged soil sorting system for the utilization of reclamation soil of claim 6, wherein~~

~~the dredged soil sorting system further comprises:~~

~~a measurement portion which is disposed to the sand outflow portion of the hydro cyclone and measures a fine soil content in outflowed sand; and~~

~~a control portion which controls an opening ratio of the sand outflow portion and/or a flow rate and a pressure of dredged soil flowed into the hydro cyclone on the basis of values measured in the measurement portion, allowing controlling a fine soil content of the sand outflowed through the sand outflow portion to be 10% or less.~~

~~10~~7. The dredged soil sorting system for the utilization of reclamation soil of claim 1, wherein

the ground required to be reclamated includes a sand replacement layer, an embankment, a lower reclamation layer and an upper reclamation layer,

the fine soil transfer portion transfers the fine soil to the lower reclamation layer of the ground required to be reclamated, and the sand transfer portion transfers the sand to the sand replacement layer, the embankment and the upper reclamation layer.

~~11~~8. The dredged soil sorting system for the utilization of reclamation soil of claim ~~10~~7, wherein

the sorting system is installed on an embankment,

the sand transfer portion utilizes the sand as a sand replacement layer, an embankment and an upper reclamation layer, and the fine soil transfer portion utilizes the fine soil as a lower reclamation layer of the ground required to be reclamated.

~~12~~9. The dredged soil sorting system for the utilization of reclamation soil of claim ~~10~~7, wherein

the sorting system is installed on a barge,

the sand transfer portion transfers the sand to a sand replacement layer, an embankment and an upper reclamation layer, and the fine soil transfer portion transfers the fine soil to a barge for transportation or a settler.

~~13~~10. A method for the utilization of reclamation soil using a dredged soil sorting system comprising steps of:

pumping dredged soil having a fine soil content of 10% by mass or more from seabed by a transfer pump;

removing gravel and foreign substances from the dredged soil through a screen;

outflowing fine soil through a fine soil outflow portion where the dredged soil flows into an inflow portion of a hydro cyclone, followed by sorting and separating the inflowed dredged, and outflowing sand having a fine soil content of 10% or less through a sand outflow portion;

coagulating fine soil outflowed through the fine soil outflow portion in a coagulation portion and outflowing coagulated fine soil;

transferring sand having a fine soil content of 10% or less to a sand replacement layer, an embankment and an upper reclamation layer through a sand transfer portion and utilizing the same as reclamation soil; and

transferring coagulated fine soil to a barge for transportation or a settler through a fine soil transfer portion and utilizing the same as reclamation soil.

~~14~~11. The method for the utilization of reclamation soil using a dredged soil sorting system of claim ~~13~~10, wherein

the step of outflowing sand comprises steps of:

outflowing fine soil through a fine soil outflow portion where dredged soil flows into an inflow portion of a first stage hydro cyclone, followed by sorting and separating the inflowed dredged soil, outflowing sand containing 10% fine soil by mass or less through a first sand outflow portion and outflowing sand containing more than 10% fine soil by mass through a second sand outflow; and

outflowing fine soil through a fine soil outflow portion where sand containing more than 10% fine soil by mass, outflowed through a second sand outflow portion of the first stage hydro cyclone, followed by sorting and separating the inflowed sand, and outflowing sand containing 10% fine soil by mass or less through a sand outflow portion.

~~15~~12. The method for the utilization of reclamation soil using a dredged soil sorting system of claim ~~13~~10 further comprising steps of:

measuring a content of fine soil contained in outflowed sand by a measurement portion disposed to the sand outflow portion of the hydro cyclone; and

controlling, through a control portion, a fine soil content of sand outflowed through the sand outflow portion to be 10% or less by regulating at least one of an opening ratio of the sand outflow portion, ~~and~~ a flow rate of the dredged soil flowed into the hydro cyclone, and a pressure of the dredged soil flowed into the hydro cyclone, on the basis of values measured in the measurement portion.