

NEBULIZER FOR INFANTS AND RESPIRATORY COMPROMISED PATIENTS

This invention relates to a device and method for and dry nebulization of an aerosolizable material. The invention has particular application to delivery of powdered
5 pharmaceutical preparations to infants and respiratory compromised patients and will be described in connection with such utility, although other utilities are contemplated.

A majority of the drugs used to treat asthma and chronic obstructive pulmonary disease (COPD) are inhaled. Recently, however, there has been a move to deliver drugs to the lungs to treat other diseases, such as diabetes, through systemic absorption. The
10 delivery of the drug to the lungs requires that the drug be in the form of a fine aerosol suitable for inhalation. It is the opinion of the pharmaceutical industry that the particles in the aerosol need be between 1 to 5 microns in size for effective delivery and absorption. These particles in the aerosol may be either in a dry powder format or droplets of a liquid medium having the drug suspended or dissolved in it. The general advantages of
15 pulmonary delivery are avoidance of first pass metabolism, site specific delivery of the drug, potential higher bio availability, etc. Three types of devices have been traditionally used to create the aerosol needed for pulmonary delivery-- metered dose inhalers (MDIs), dry powder inhalers (DPIs) and aqueous nebulizers.

MDIs have a pressurized canister filled with a liquid propellant. The drug is either
20 suspended or dissolved in the propellant. The MDIs have a metering valve for metering out a known quantity of the propellant and hence the drug. When the canister is depressed against the MDI housing a known quantity of the propellant is discharged. The propellant evaporates leaving behind a fine aerosol of the drug suitable for inhalation by the patient. For effective delivery of the drug to the lungs the patient needs to co-ordinate breath
25 inhalation with the discharge of the drug from the canister. Patients are not always effective in achieving this co-ordination leading to dose variability. Incorporation of a breath actuation mechanism addresses this concern but the variability still exists because of the "cold" freon effect where the patient stops breathing when the cold aerosol hits the back of the throat. This is especially true of the pediatric patients where co-ordination is

of major concern. To overcome these limitations and to minimize the variability of the dose delivered, the MDI is normally recommended to be used with a spacer especially for children. This primary function of the spacer is to slow down the MDI discharge and function as a holding chamber for the aerosol plume. A face mask may be attached to the
5 end of the spacer. These spacers normally are made of plastic and therefore tend to build up electrostatic charge on the inside surface of the spacer. The large dead space between the inlet and outlet of the spacer coupled with the electrostatic charge has the effect of lowering the amount of dose delivered and the amount of drug that is in the respirable range. It is estimated that MDIs deliver about 10% to 20% of the dose to lungs in adults
10 with good co-ordination. Studies have shown that for pediatric patients between 3 years to 5 years using an MDI with a spacer and face mask, the lung delivery is <10% of the dose.

In DPIs the drug is micronized to the right size required for pulmonary delivery. If the drug is potent it normally is mixed with an excipient such as lactose. When drugs
15 are micronized to this size they tend to aggregate. As mentioned above, it is commonly accepted in the pharmaceutical industry that particle sizes, as a unit or in aggregate, need to be between 1 and 5 micron for effective delivery to the lungs. The aggregates are dispersed into an aerosol by introducing the drug into a strong airflow. The airflow needed to disperse the powder typically is high ranging from 30 L/min to 90 L/min.
20 Failure to establish this airflow can result in a lower dose being delivered to the lungs. Any inconsistency in the breathing will lead to variability in dose delivered. As an example a so-called Turbuhaler inspiratory flow-driven inhaler has been developed and is approved for children 6 years and above delivers 20- 30 % of the drug to the lungs when the airflow established by the patient is 60 L/min. However when the airflow drops to 36
25 L/min the amount of drug delivered is only 15%. The patient must therefore use rapid deep inhalation to adequately disperse the powder. This may not be possible for infants, young children and respiratory compromised patients of any age. Besides the inability of these patients to establish a strong airflow they also have low inhalation volumes. This

severely impedes their ability to effectively clear the aerosol created and stored in a holding chamber such as that used by Exubera® (Nektar, San Carlos, CA).

Nebulizers, such as the jet nebulizers, produce a fine aerosol mist/droplets which carry the drug either as a suspension or dissolved in the aqueous medium. The jet
5 nebulizers use compressed air to atomize the aqueous solution. The flow rate of the compressed air should be matched to the inhalation flow rate of the patient for optimum delivery of the drug. The patient can be administered the drug with repetitive non-forced inhalation over a prolonged period of time. The amount of drug delivered is influenced by a large number of factors such as viscosity, volume of drug fill, surface tension,
10 inhalation flow, etc. The amount of drug delivered ranges from 3% to 6% for pediatric patients and 3% to 13% for adults. For pediatric delivery the nebulizers are normally coupled to a face mask. Since the nebulizer continues to produce the aerosol during the exhale cycle of the breath this leads to drug wastage, increased exposure of the drug to the patient's face and eyes and also to the care-giver. The disadvantages of nebulizers in
15 general are their poor efficiency of delivery to the patient, a requirement for a compressor or compressed air and long delivery times, on the order of 5 to 15 minutes, etc.

Thus there is a need for a delivery mechanism for infants and young children, and also for respiratory compromised patients that overcomes the aforesaid and other disadvantages of the prior art, in a manner that delivers the drug efficiently, does not
20 require inhalation co-ordination, operates under low inhalation volume, minimizes the exposure of the care giver to the drug, delivers the drug in a short time (preferably less than a minute), and is low cost and portable.

According to a first aspect, there is provided a device for delivering dry powder medication to infants and respiratory-compromised patients, ventilated patients or
25 unconscious patients, comprising a housing defining an aerosol chamber into which an aerosolized medication may be introduced; an outlet for said chamber; a facemask connected to the outlet; a nebulizer including a vibratory element for aerosolizing said dry powder medication and introducing aerosolized medication into the chamber; a microprocessor and control for the vibratory element; a manual actuator for permitting a

patient, a user, or a caretaker to activate the vibratory element, wherein said manual activation of the vibratory element introduces a controlled amount of medication into the chamber independent of the infant's or respiratory-compromised, ventilated or unconscious patient's inhalation strength, rate and timing; a sensor for sensing an
5 inhalation and/or exhalation cycle of the infant or patient; and a controller for controlling the vibratory element over two or more inhalation cycles.

According to a second aspect, there is provided a device for delivering dry powder medication to infants and respiratory-compromised patients, ventilated patients or unconscious patients, comprising a housing defining an aerosol chamber into which an
10 aerosolized medication may be introduced; an outlet for said chamber; a nasal cannula connected to the outlet; a nebulizer including a vibratory element for aerosolizing said dry powder medication and introducing aerosolized medication into the chamber; a microprocessor and control for the vibratory element; a manual actuator for permitting a patient, a user, or a caretaker to activate the vibratory element, wherein said manual
15 activation of the vibratory element introduces a controlled amount of medication into the chamber independent of the infant's or respiratory-compromised, ventilated or unconscious patient's inhalation strength, rate and timing; a sensor for sensing an inhalation and/or exhalation cycle of the infant or patient; and a controller for controlling the vibratory element over two or more inhalation cycles.

20 According to a third aspect, there is provided a device for delivering dry powder medication to infants and respiratory-compromised patients, ventilated patients or unconscious patients, comprising a housing defining an aerosol chamber into which an aerosolized medication may be introduced; an outlet for said chamber; a mouthpiece connected to the outlet; a nebulizer including a vibratory element for aerosolizing said
25 dry powder medication and introducing aerosolized medication into the chamber; a microprocessor and control for the vibratory element; a manual actuator for permitting a patient, a user, or a caretaker to activate the vibratory element, wherein said manual activation of the vibratory element introduces a controlled amount of medication into the chamber independent of the infant's or respiratory-compromised, ventilated or

unconscious patient's inhalation strength, rate and timing; a sensor for sensing an inhalation and/or exhalation cycle of the infant or patient; and a controller for controlling the vibratory element over two or more inhalation cycles.

According to a fourth aspect, there is provided a propellant free device for
5 delivering nebulized dry powder medication to an inhaled airstream of an infant and a respiratory-compromised patient, a ventilated patient or an unconscious patient, comprising a vibratory element for aerosolizing the dry powder medication and introducing the medication into the airstream, a facemask into which the airstream is introduced; a microprocessor and control for the vibratory element; a manual actuator for
10 permitting a patient, user or a caretaker to activate the vibratory element, wherein said *manual activation of the vibratory element introduces a controlled amount of medication* into the airstream independent of the infant's or respiratory compromised, ventilated or unconscious patient's inhalation strength, rate and timing; a sensor for sensing an inhalation and/or exhalation cycle of the infant or patient; and a controller for controlling
15 the vibratory element over two or more inhalation cycles.

The present invention provides a device, its use and method for aerosolized dosing of dry powder pharmaceutical preparations, which overcomes the aforesaid and other problems of the prior art, and provides a simple and relatively low cost device operative independently of a source of compressed carrier air. More particularly, in
20 accordance with the present invention there is provided a device, its use and method for aerosolized dosing of dry powder pharmaceutical preparations, or pharmaceutical agents dissolved or suspended in a liquid medium comprising a pharmaceutical aerosolization

engine comprising a vibratory device. In one embodiment, the aerosolization engine is connected to a face mask and permits manual activation of the aerosolization engine by a caregiver, and presentation of aerosolized medication into the face mask. The face mask may be replaced with a nasal cannula or a mouth piece and the manual activation may be replaced with automated activation of the aerosolization engine through sensing of the patients' inhalation or tidal breathing maneuver, or through synchronization with hospital equipment operating to assist or substitute for the patient's breathing as in ventilators or in delivering oxygen or humidified air for example. The present invention has particular utility in connection with aerosolization and delivery of dry powdered pharmaceutical agents to an infant or small child and will be described in connection with such utility, although other utilities including continuous or semi-continuous or intermittent nebulization of dry powder pharmaceutical agents, pharmaceutical agents dissolved or suspended in a liquid medium, and delivery to infants and small children, and to respiratory compromised patients, ventilated patients and unconscious patients is also contemplated.

Features and advantages of the present invention will be seen from the following detailed description, taken into conjunction with the accompanying drawings, wherein:

Fig. 1 is a perspective view of a hand-held pediatric nebulizer in accordance with the preferred embodiment of the invention;

Fig. 2 is a top plan view of the device of Fig. 1;

Fig. 3 is a bottom plan view showing details of the facemask portion of the device of Fig. 1;

Fig. 4 is a schematic diagram illustrating generation of nebulized powder medication in accordance with the present invention;

Fig. 5 is a perspective view illustrating a pharmaceutical package in accordance with a preferred embodiment of the invention;

Fig. 6 is a flow diagram illustrating another embodiment of the invention; and

Fig. 7 is a schematic of the timing diagram for the intermittent excitation of the aerosol engine.

Turning now to Figs. 1-5 of the drawings, there is illustrated a dry powder pediatric nebulizer in accordance with the present invention. The nebulizer 10 comprises a housing or body 12 sized and shaped to fit comfortably within the hand of a human adult. Body 12 houses a dry powder aerosol engine, battery power and controls all as will be discussed below. Referring in particular to Figs. 2 and 3, the hand held nebulizer 10 is connected at its outlet 14 to a facemask 16. Facemask 16 is sized and shaped to fit over the mouth and nose of a patient, and is formed of a resiliently deformable material such as silicon rubber. Facemask 16 may comprise a single wall construction or, if desired may comprise a soft partially air-filled cuff 18 at its distal end, and optionally may include a one-way filter valve 19 to allow the patient's exhale breath to escape. Facemask 16 is friction fitted to the outlet end of nebulizer device 12 so that it may be removed for cleaning and/or disposal and a fresh facemask placed thereon. Also, if desired, facemask 16 may come in different sizes, e.g. for adults, children and infants. The face mask may incorporate a pressure sensor 17 to measure the quality of fit and seal over the patient or the sensor may be incorporated into the inhaler housing. A good seal is preferred to ensure high efficiency of delivery of the drug to the patient and to protect the care-giver from exposure to the drug and the patient from exposure of the drug to the eyes.

Body 12 includes a movable panel 20 for permitting one or more blister packs or molded bodies 22 containing a powdered medication to be introduced into a chamber 23 (shown in phantom) defined within the interior of body 12. A body, comprising blister pack 22, is guided by guides 24 to locate in contact with the top surface of an aerosolization engine in the form of a vibratory element 26. A molded body that is reused over a number of dosings, or a capsule, may be used as an alternative to the blister pack. The blister pack, molded body or capsule, in this case provides a way for introducing the drug into the chamber. Vibratory element 26 preferably comprises a piezo activator or piezo transducer or a mechanical vibrator, an electro-mechanical vibrator or a magnetostrictive element or other vibratory mechanism. Preferred are aerosolization engines and aerosolization

chambers such as described in U.S. Patent Nos. 6,026,809, 6,142,146, 6,152,130, 7,318,434, 7,334,577, 7,343,914 and

published U.S. Application Nos. 2005/0172962 and 2008/0202514, the contents of which are incorporated herein by reference.

Blister pack 22 preferably comprises a domed dry powder drug package made of cold formed or thermal formed film, and includes a conical, semi-spherical, elliptical, pyradidal or similar top part 34 and flat base 28 such as described in U.S. 7,080,644, assigned to the common assignee. Blister pack 22 has at least one drug ejection aperture 32 substantially opposite base 28 and serving primarily for injection of drug particles. Aperatures 32 may be pre-formed integrally with blister pack 22, or formed as puncture holes when the blister pack 22 is inserted into body 12.

Blister pack 22 carries a supply of a drug substance or substances which preferably are provided as a dry powder. A single component or several drug combinations may be used, or, the drug substance or substances combined with excipients, such as lactose or combinations thereof. Other additives such as pharmaceutically inactive ingredients, de-aggregation agents, etc., also may be added.

Body 12 carries a battery 25 for powering the vibratory element 26, as well as a microprocessor or electronic controller 27 for controlling operation of the vibratory element 26, sensor signal processing for inhalation and/or exhalation detection, etc. Body 12 also includes a control panel 38 including one or more activation buttons 40, 42, and a display 44. The display 44 may incorporate active dose feedbacks to indicate such things as device readiness, face mask seal integrity, activation of the aerosol engine during inhalation or tidal breathing and dosing complete, such as described in U.S. Published Application No. US-2005-0183725-A1, the contents of which are incorporated herein by reference. Body 12 also includes one or more side walled aperatures 46 which permit air to enter chamber (shown in phantom at 23) from the outside.

Operation of the nebulizer is as described below.

A caregiver places the facemask over the mouth and nose of the patient. Thereafter, the caregiver presses the start button 40 which activates the vibrating element 26 for a predetermined time, e.g. 1-2 seconds. The vibrating element engages with the base of blister pack 22 whereupon powdered medication is deaggregated and ejected out

of blister pack 22 into chamber 23 as a cloud or powder plume 50 where it is then inhaled by the patient.

The present invention has several advantages over the prior art. For one, the ability to aerosolize dry powders and deliver same in a nebulizer permits much higher
5 dose concentrations than are possible with liquid carried drugs. Thus, administration time for a dose may be significantly reduced over those of a liquid nebulizer. Also, many drugs are insoluble in water and can't be delivered using conventional nebulizers, or are soluble only in organic solvents which create other problems.

Another feature and advantage of the present invention is that the generation of
10 powder plume is independent of inhalation rate and inhalation timing. Thus, the nebulizer of the present invention is particularly useful in the case of infants and small children, respiratory compromised patients, and unconscious patients. The above described invention provides controlled, reproducible and recordable pulmonary doses from pre-measured blister packs. Alternatively, a plurality of blister packs may be
15 mounted in the body 12 as a cartridge, and advanced, as necessary. Alternatively the dose amount may be controlled by the number and duration of the delivery 'pulses', or aerosol activation cycles.

The invention is susceptible to modification. For example, facemask 16 may be removed, or the nebulizer mounted directly to a pre-existing ventilator/nebulizing system
20 where it may be run continuously or semi-continuously or intermittently. The nebulizer also may be triggered to turn on and off by sensing tidal breathing of a patient as illustrated in Fig. 6 and 7, and operate over one or several breaths. As shown in Figure 7 the inhalation and/or exhalation cycle is sensed and the aerosol generator is turned on for a short duration followed by an amount of chase air to carry or follow the particles into
25 the patient. A sufficient quantity of chase air is necessary to ensure lung deposition when inhalation volumes are low and inhalation cycles are short. Any sensor or combination of sensors that can be used to measure or identify the difference in properties between an inhalation and exhalation maneuver can be used to synchronize and turn the aerosol generator on and off. Example of sensors that may be used to detect the patients

inhalation/exhalation are flow sensors, pressure sensors, temperature sensors that measure the temperature difference between the inhaled and exhaled breath, carbon dioxide or nitric oxide or other gas sensors that measure the gas component level difference between inhaled and exhaled breath, and also physical measurement systems
5 such as chest straps to measure the expansion and contraction of the chest cavity, etc., can be employed for this purpose. Still other changes are possible. For example, active visual, audible or tactile feedback to the patient or caregiver indicating the status of the device and of dosing may be provided including, for example, visual or audible devices as taught in U.S. Patent 7,343,914, the contents of which are incorporated herein by
10 reference. Also, if desired, electronic communication may be provided for connecting the device to equipment connected to the patient for controlling or synchronizing the vibratory element. Also, if desired, the dose or amount delivered to a patient may be determined by the counting and controlling number of timed or pulsed activations of the vibratory element. Also animal or cartoon images may be printed on the inside surface
15 48 of the facemask 16, to make the instrument more friendly to a child patient, or the device feedback systems, e.g. lights and sounds and vibrations may be used for this purpose.

Also, while the invention has been described in particular for use with drugs for treating asthma and COPD, the invention also advantageously may be used for delivery
20 of other drugs including, but not limited to, anti-virals to treat viruses including but not limited to RSV, and anti-biotics, anti-fungals and anti-infectives for treating lung infections and other diseases, or drugs for treating lung cancer.

Still other changes are possible. For example, it is possible to control the amount of drug delivered to the nasal passages as opposed to just the lower respiratory track by
25 controlling particle size. Still other changes are possible.

CLAIMS

Claim 1: A device for delivering dry powder medication to infants and respiratory-compromised patients, ventilated patients or unconscious patients, comprising a housing defining an aerosol chamber into which an aerosolized medication may be introduced;

an outlet for said chamber;

a facemask connected to the outlet;

a nebulizer including a vibratory element for aerosolizing said dry powder medication and introducing aerosolized medication into the chamber;

a microprocessor and control for the vibratory element;

a manual actuator for permitting a patient, a user, or a caretaker to activate the vibratory element, wherein said manual activation of the vibratory element introduces a controlled amount of medication into the chamber independent of the infant's or respiratory-compromised, ventilated or unconscious patient's inhalation strength, rate and timing;

a sensor for sensing an inhalation and/or exhalation cycle of the infant or patient;

and

a controller for controlling the vibratory element over two or more inhalation cycles.

Claim 2: The device of claim 1, further comprising a dose-controlled blister pack carrying the medication, said dose-controlled blister pack comprising at least one drug ejection aperture, and wherein the medication is introduced into the chamber through said at least one drug ejection aperture.

Claim 3: The device of claim 1 or claim 2, further comprising a timer for controlling the vibratory element.

Claim 4: The device of any of claims 1-3, further comprising electronic communication for connecting to various hospital equipment connected to the infant or patient for controlling or synchronizing the vibratory element.

Claim 5: The device of any of claims 1-4, wherein a dose delivered amount is determined by the number of timed or pulsed activations of the vibratory element.

Claim 6: The device of any of claims 1-5, further comprising active visual, audible or tactile feedbacks to the infant, patient, user or a caregiver indicating the status of the device and of dosing.

Claim 7: The device of any of claims 1-6, further comprising a pressure sensor for measuring the quality of fit of the mask to the patient or infant.

Claim 8: The device of any of claims 1-7, wherein the mask is formed of a resiliently deformable material.

Claim 9: The device of any of claims 1-8, further comprising a switch for synchronizing the nebulizer to tidal breathing of the infant or patient.

Claim 10: The device of any of claims 1-9, wherein the sensor is selected from the group consisting of a flow sensor, a pressure sensor, a temperature sensor, a gas sensor and a chest strap.

Claim 11: A device for delivering dry powder medication to infants and respiratory-compromised patients, ventilated patients or unconscious patients, comprising a housing defining an aerosol chamber into which an aerosolized medication may be introduced;
an outlet for said chamber;

a nasal cannula connected to the outlet;

a nebulizer including a vibratory element for aerosolizing said dry powder medication and introducing aerosolized medication into the chamber;

a microprocessor and control for the vibratory element;

a manual actuator for permitting a patient, a user, or a caretaker to activate the vibratory element, wherein said manual activation of the vibratory element introduces a controlled amount of medication into the chamber independent of the infant's or respiratory-compromised, ventilated or unconscious patient's inhalation strength, rate and timing;

a sensor for sensing an inhalation and/or exhalation cycle of the infant or patient;

and

a controller for controlling the vibratory element over two or more inhalation cycles.

Claim 12: The device of claim 11, further comprising a dose-controlled blister pack containing the medication, said dose-controlled blister pack comprising at least one drug ejection aperture, and wherein the medication is introduced into the chamber through said at least one drug ejection aperture.

Claim 13: The device of claim 11 or claim 12, further comprising a timer for controlling the vibratory element.

Claim 14: The device of any of claims 11-13, further comprising electronic communication for connecting the device to various hospital equipment connected to the infant or patient for controlling or synchronizing the vibratory element.

Claim 15: The device of any of claims 11-14, wherein a dose delivered amount is determined by the number of timed or pulsed activations of the vibratory element.

Claim 16: The device of any of claims 11-15, further comprising active visual, audible or tactile feedbacks to the infant, patient, user, or a caregiver indicating the status of the device and of dosing.

Claim 17: The device of any of claims 11-16, further comprising a switch for synchronizing the nebulizer to tidal breathing of the infant or patient.

Claim 18: The device of any of claims 11-17, wherein the sensor is selected from the group consisting of a flow sensor, a pressure sensor, a temperature sensor, a gas sensor and a chest strap.

Claim 19: A device for delivering dry powder medication to infants and respiratory-compromised patients, ventilated patients or unconscious patients, comprising a housing defining an aerosol chamber into which an aerosolized medication may be introduced;

an outlet for said chamber;

a mouthpiece connected to the outlet;

a nebulizer including a vibratory element for aerosolizing said dry powder medication and introducing aerosolized medication into the chamber;

a microprocessor and control for the vibratory element;

a manual actuator for permitting a patient, a user, or a caretaker to activate the vibratory element, wherein said manual activation of the vibratory element introduces a controlled amount of medication into the chamber independent of the infant's or

respiratory-compromised, ventilated or unconscious patient's inhalation strength, rate and timing;

a sensor for sensing an inhalation and/or exhalation cycle of the infant or patient;

and

a controller for controlling the vibratory element over two or more inhalation cycles.

Claim 20: The device of claim 19, further comprising a dose-controlled blister pack, said dose-controlled blister pack comprising at least one drug ejection aperture, and wherein the medication is introduced into the chamber through said at least one drug ejection aperture.

Claim 21: The device of claim 19 or claim 20, further comprising a timer for controlling the vibratory element.

Claim 22: The device of any of claims 19-21, further comprising electronic communication for connecting the device to various hospital equipment connected to the infant or patient for controlling or synchronizing the vibratory element.

Claim 23: The device of any of claims 19-22, wherein a dose delivered amount is determined by the number of timed or pulsed activations of the vibratory element.

Claim 24: The device of any of claims 19-23, further comprising active visual, audible or tactile feedbacks to the infant, patient, user or a caregiver indicating the status of the device and of dosing.

Claim 25: The device of any of claims 19-24, further comprising a sensor for sensing an inhalation and/or exhalation cycle of the infant or patient, and a switch for synchronizing the nebulizer to tidal breathing of the infant or patient.

Claim 26: The device of any of claims 19-25, wherein the sensor is selected from the group consisting of a flow sensor, a pressure sensor, a temperature sensor, a gas sensor and a chest strap.

Claim 27: A propellant free device for delivering nebulized dry powder medication to an inhaled airstream of an infant and a respiratory-compromised patient, a ventilated patient or an unconscious patient, comprising a vibratory element for aerosolizing the dry powder medication and introducing the medication into the airstream,

a facemask into which the airstream is introduced;

a microprocessor and control for the vibratory element;

a manual actuator for permitting a patient, user or a caretaker to activate the vibratory element, wherein said manual activation of the vibratory element introduces a controlled amount of medication into the airstream independent of the infant's or respiratory compromised, ventilated or unconscious patient's inhalation strength, rate and timing;

a sensor for sensing an inhalation and/or exhalation cycle of the infant or patient;

and

a controller for controlling the vibratory element over two or more inhalation cycles.

Claim 28: The device of claim 27, further comprising a dose-controlled blister pack, said dose-controlled blister pack comprising at least one drug ejection aperture, and wherein the medication is introduced into the airstream through said at least one drug ejection aperture.

Claim 29: The device of claim 27 or claim 28, further comprising a timer for controlling the vibratory element.

Claim 30: The device of any of claims 27-29, further comprising a sensor for detecting inhalation, and for triggering operation of the vibratory element when inhalation is sensed.

Claim 31: The device of any of claims 27-30, further comprising electronic communication for connecting the device to various hospital equipment connected to the infant or patient for controlling or synchronizing the vibratory element.

Claim 32: The device of any of claims 27-31, wherein a dose delivered amount is determined by the number of timed or pulsed activations of the vibratory element.

Claim 33: The device of any of claims 27-32, further comprising active visual, audible or tactile feedbacks to the infant or patient or caregiver indicating the status of the device and of dosing.

Claim 34: The device of any of claims 27-33, further comprising a switch for synchronizing the nebulizer to tidal breathing of the infant or patient.

Claim 35: The device of any of claims 27-34, wherein the sensor is selected from the group consisting of a flow sensor, a pressure sensor, a temperature sensor, a gas sensor and a chest strap.

Claim 36: The device of any of claims 1-10, wherein the facemask includes a one-way filter valve to allow a patient's exhale breath to escape the facemask.

Claim 37: The device of any of claims 11-18, wherein the mouthpiece or chamber includes a one-way filter valve to allow a patient's exhale breath to escape the mouthpiece or chamber.

Claim 38: The device of any of claims 27-35, wherein the facemask includes a one-way filter valve to allow a patient's exhale breath to escape the facemask.