

STATOR FOR ELECTRIC MACHINE AND LAMINATION THEREOF

5 This invention relates to a stator for a rotating electrical machine. The invention is particularly, though not exclusively, applicable to a switched reluctance (SR) machine.

10 Rotating electrical machines can be arranged to run as generators or motors. Such machines of various types typically have stator laminations made of electrical sheet steel, having an outer lamination profile (which also constitutes the outer profile perpendicular to the axis of the stator) which is essentially circular, save for small keyways or cut-outs included to facilitate
15 manufacture and/or assembly. The radially inner profile defines the stator teeth which interact with the rotor rotating inside the stator. These circular laminations are packed together, to form the axially extending stator, and mounted in a frame.

20

Laminations are also known which have a generally rectangular outer profile. These are often used in a so-called 'frameless' construction in which the relatively thicker corners of the stator back iron are used to bear
25 a bolt or other clamping arrangement to hold the laminations together.

30

In some types of electrical machines, such as switched reluctance machines, a relatively small number of teeth are used and are normally called stator poles. Typically each stator pole is influenced by a coil which is one of a number connected in a group or groups to form machine phases. The selection of the number of poles and the number of coils in a group forming a phase are two of the

parameters of machine design. For example, an SR machine with four stator poles could be connected to form two phases each of two coils, as shown in Figure 1, or an SR machine with twelve stator poles could be connected to form three phases each of four coils, as shown in Figure 2.

A body can be excited into mechanical resonance by applying an impulsive or periodic force. The amplitude of the resonance vibrations is dependent on the frequency and amplitude of the exciting force and the position at which it is applied, as well as on the material and proportions of the structure.

A body which has a geometrically regular shape will have a well-defined pattern of resonance, usually with a range of frequencies of vibration present at resonance. The points on the body where vibration at a particular frequency gives rise to zero amplitude of vibration are known as nodes. The points at which the amplitude is at maximum are known as anti-nodes.

While it is known in the art of acoustic noise reduction to make the shape of a body irregular to minimise the effects of resonance, there is little or no opportunity to do this with laminations of common forms of electrical machines.

When a phase winding of an SR motor is excited, there is (in addition to the desired torque-producing force) a force generated which acts to pull the energised stator poles towards the centre of the machine. This has the effect of distorting the notional circle on which the end faces of the stator poles lie. Thus, successive



energisation of the phases (in whatever sequence is desired for a particular mode of operation) imparts a periodic radial force to the structure of the laminations. This has the effect of cyclically
5 distorting the laminations, the vibrations thus caused being responsible for producing acoustic noise.

It is an object of the present invention to provide a stator profile and a shape of lamination for a stator in
10 which the tendency to vibration, giving rise to acoustic noise, is reduced.

According to the present invention there is provided a stator for a rotatable electrical machine, the stator
15 comprising a body defining an outer ring and a plurality of stator poles which project radially inwardly from the ring and partially define a rotor space about an axis of rotation, the ring having a non-circular outer profile perpendicular to the axis of rotation and at least some
20 of the poles being angularly centred with respect to the said axis to be angularly intermediate radially thickest and thinnest parts of the ring to avoid the pole coinciding with a vibrational antinode of the stator ring.

25

A node of vibration may exist toward the relatively thickest part of the ring, whereas the antinode at which vibration of the greatest amplitude and frequency range occurs will be nearer the relatively thinnest part of the
30 ring. By positioning the pole to be centred away from the antinode, the forces tending to create the acoustic noise are of reduced effect.



Preferably, the outer profile has a line of symmetry passing through the said axis, one of the stator poles being centred angularly offset from the line of symmetry. The offset is desirably about one quarter of the angular stator pole pitch. Preferably, the line of symmetry from which the stator pole is offset is coincident with the radially thinnest part of the ring with respect to the said axis.

While the invention is particularly applicable to simple shapes, such as square profiles and four or eight poles, it is also relevant to any other number of stator poles and phases. For example, the outer profile may be square or hexagonal. The hexagonal outer profile may be used in a three-phase, six pole machine, whereas the square profile may be used in a two-phase, four pole machine. In general, a regular, even sided, shape of $4n$ sides (n an integer) is conveniently usable for a machine of n phases or $2n$ poles. However, the more sides to the polygonal outer profile there are, the more the shape approximates to a circle. The invention is not necessarily limited to regular arrangements of sides.

The stator may be for a switched reluctance machine having windings associated with the poles which are arranged to energise the poles. The stator windings may be arranged so that the stator poles of opposite polarity are disposed on opposite sides of the radially thinnest part of the ring. This is advantageous in a four or an eight stator pole machine. More particularly this advantage is realised in a 2 phase machine.

Preferably, the stator is made up of a plurality of laminations.

The invention extends to a lamination providing the outer profile and defining the stator poles as defined above.

5 Furthermore, the invention extends to an electrical machine having a stator as defined above, for example, a switched reluctance machine.

10 One purpose in offsetting the at least one stator pole is to make irregular the respective symmetries of the ring and the stator poles to reduce the amplitude of vibration at resonance.

15 The present invention can be put into practice in various ways some of which will now be described by way of example with reference to the accompanying drawings in which :

20 Figure 1 is a cross-section of a prior art stator for a two-phase switched reluctance machine;

Figure 2 is a cross-section of a prior art stator for a three-phase switched reluctance machine with only one phase winding shown;

25 Figure 3 is a cross-section of a switched reluctance machine according to the invention; and

30 Figure 4 is a cross-section of an alternative embodiment of a stator according to the invention.

Referring to Figure 3 of the drawings, a switched reluctance machine, which can be arranged to run either as a generator or a motor, comprises a stator 10 and a rotor 12. The stator 10 is made up of a plurality of

laminations of electrical sheet steel. The cross-sectional profile of the stator, in a plane perpendicular to the axis of rotation of the rotor 12, comprises four equi-angularly spaced stator poles 14 which project radially inwardly from a radially outer ring of back iron 16. The outer profile of the stator is square, having a centre coincident with the axis 17 of the notional circle on which the radially inner end faces 18 at the poles 14 are arranged. The roots of the stator poles 14 are joined by sections of the ring of back iron 16 defining a circle 20 having a centre also coincident with the axis of rotation of the rotor.

The rotor defines two equiangularly spaced rotor poles 22 which rotate about the axis 17 of the stator pole faces 18. Having a rectangular outer shape, the ring of back iron 16 has relatively thicker and thinner portions relative to the circle 20 from which the poles 14 project. When the poles are arranged symmetrically with respect to the outer profile of the stator (as shown in Figure 1), the position of the ovalising force pulling on the stator pole coincides with the position at which the antinode would occur if the structure vibrated in response to the ovalising force. In the prior art arrangement, the structure relatively easily achieves substantial resonance in which the amplitude of the vibrations makes the condition noticeable in the presence of relatively small ovalising forces.

In Figure 3 the angular axis of each stator pole 14 is shifted from a symmetrical position by one quarter of the angle of the pole pitch θ . Thus, the position of the exciting force is asymmetrical to the stator profile, i.e. the angular position of the stator pole is shifted

to one intermediate the thickest and thinnest radial extent of the stator back iron and the antinodes of all the low order harmonics are avoided. Thus, for a magnitude of exciting force which is substantially unchanged, the amplitude of the vibration at resonance is reduced which limits the amount of acoustic noise created.

When the outer profile of the stator is substantially square it is possible to use the invention with any number of phases, each phase number having an optimum angular position for the stator pole between adjacent thickest and thinnest portions on the back iron.

Figure 4 shows an eight pole machine stator 24 having a square outer profile. Stator poles 26 are angularly offset $\theta/4$ from the thinnest portion of the back iron which corresponds to a line of symmetry passing through the centre 17.

Similarly, where the number of phases is greater than two and the outer profile has more than four sides, the invention may be used, positioning each stator pole at a position $\theta/4$ from the thinnest part of the back iron. For example, a three-phase machine having an hexagonally profiled stator will have the position of each stator pole arranged to be between the relatively thinner and thicker portions of the back iron, e.g. shifted $\theta/4$.

There is a further benefit of the invention which accrues when certain pole and phase number combinations are used with certain outer profiles, for example, a two-phase machine with four or eight poles and a substantially square outer profile. In Figures 3 and 4, sections of

the back iron of the stator are effectively narrower than other parts. When one phase of the machine is excited this gives rise to a higher flux density in those sections than in other sections. This would normally be considered to be a limiting aspect of the design. There is the opportunity, however, to reduce this disadvantage by connecting the phase windings to the supply with a particular polarity.

10 The coil (not shown) around pole 14A of Figure 3 is connected to the supply so as to produce a 'north' pole and the coil around the pole 14B produces a 'south' pole. There is then a choice as to the connection of poles 14C and 14D. Either pole 14C is connected to produce a
15 'north' pole and pole 14D will then be a 'south' pole, so that like polarities are on opposite sides of the narrow part of the back of iron. Alternatively, pole 14C is connected to produce a 'south' pole and pole 14D will then be a 'north' pole, so that opposite polarities are
20 on opposite sides of the narrow section. If the machine is connected in the latter fashion and operated with an excitation pattern which involves flux existing simultaneously in both phases, then flux wave forms are produced which have lower flux densities in the narrow
25 section. This leads to lower excitation requirements and lower iron losses than would have been the case if the machine had been connected in the former fashion.

30 Various embodiments of the invention have been described by way of example. Those skilled in the art will recognise that many variations may be made without departing from the present invention. Accordingly, the above description of several embodiments is made by way of example and not for purposes of limitation. The

present invention is intended to be limited only by the spirit and scope of the following claims.

**CLAIMS:**

1. A stator for a rotatable electrical machine, the stator comprising a body defining an outer ring and a plurality of stator poles which project radially inwardly from the ring and partially define a rotor space about an axis, the ring having a non-circular outer profile perpendicular to the said axis and at least some of the poles being angularly arranged with respect to the said axis to be angularly intermediate radially thickest and thinnest parts of the ring to avoid the pole coinciding with a vibrational antinode of the stator rings.
2. A stator as claimed in claim 1 in which the outer profile has a line of symmetry passing through the said axis, at least one of the stator poles being angularly offset from the line of symmetry.
3. A stator as claimed in claim 2 in which the line of symmetry from which the pole is offset is coincident with the radially thinnest part of the ring with respect to the said axis.
4. A stator as claimed in claim 1 in which the outer profile is square.
5. A stator as claimed in claim 4 including four poles.
6. A stator as claimed in claim 1, 2 or 3 in which the outer profile is hexagonal.
7. A stator as claimed in claim 6 including six poles.



* C L H S *

This Sheet Has Been Replaced

8. A stator as claimed in claim 1, 2 or 3 in which the outer profile has the same number of sides as poles.

5 9. An electrical machine comprising a rotor and a stator, the stator comprising a body defining an outer ring and a plurality of stator poles which project radially inwardly from the ring and partially define a space for rotation of the rotor about an axis, the ring having a non-circular outer profile perpendicular to the
10 said axis and at least some of the poles being angularly arranged with respect to the said axis to be angularly intermediate radially thickest and thinnest parts of the ring to avoid the pole coinciding with a vibrational antinode of the stator ring.

15

10. A machine as claimed in claim 9 in which the outer profile has a line of symmetry passing through the said axis, one of the stator poles being angularly offset from the line of symmetry.

20

11. A machine as claimed in claim 10 in which the line of symmetry from which the pole is offset is coincident with the radially thinnest part of the ring with respect to the said axis

25

12. A machine as claimed in claim 9 including phase windings defining n phases, the outer profile having $2n$ sides and $2n$ poles (n an integer).

30

13. An machine as claimed in claim 9, 10, 11 or 12 including stator windings, the machine being constructed and arranged to run as a reluctance machine.



* C L M S *

This Sheet Has Been Replaced



12

14. A machine as claimed in claim 13 in which the stator poles of opposite plurality are disposed on opposite sides of the thinnest part of the ring.

5 15. A lamination for a stator for a rotatable electrical machine, the lamination comprising a ferromagnetic body defining an outer ring and a plurality of stator pole profiles which project radially inwardly from the ring and partially define a rotor space about an axis, the ring having a non-circular outer profile perpendicular to the said axis and at least some of the pole profiles being angularly arranged with respect to the said axis to be angularly intermediate radially thickest and thinnest parts of the ring to avoid the pole profiles coinciding with a vibrational antinode of the ring.

10 16. A lamination as claimed in claim 15 in which the outer profile has a line of symmetry passing through the said axis, at least one of the stator pole profiles being angularly offset from the line of symmetry.

15 17. A stator as claimed in claim 16 in which the line of symmetry from which the pole profile is offset is coincident with the radially thinnest part of the ring with respect to the said axis.


20 18. A lamination as claimed in claim 15, 16 or 17 in which the outer profile has n sides and n pole profiles (n an integer).

25 30

**ABSTRACT****STATOR FOR ELECTRIC MACHINE AND LAMINATION THEREOF**


5 A stator for an electric machine, in particular a
switched reluctance machine, has a non-circular, for
example, square, outer profile and a set of equi-
angularly spaced stator poles which are angularly
arranged to be intermediate radially thickest and
10 thinnest parts of the ring to avoid the poles coinciding
with vibrational antinodes of the outer ring. In a
particular embodiment the outer profile is square and the
stator poles are angularly offset from a line of symmetry
drawn through the centre of the square at right angles to
15 one pair of opposite sides.

FIG.1.



PRIOR ART

FIG.2.



PRIOR ART

FIG. 3.





FIG. 4.



0-781-078

**ABSTRACT****STATOR FOR ELECTRIC MACHINE AND LAMINATION THEREOF**

5 A stator for an electric machine, in particular a
switched reluctance machine, has a non-circular, for
example, square, outer profile and a set of equi-
angularly spaced stator poles which are angularly
10 arranged to be intermediate radially thickest and
thinnest parts of the ring to avoid the poles coinciding
with vibrational antinodes of the outer ring. In a
particular embodiment the outer profile is square and the
stator poles are angularly offset from a line of symmetry
drawn through the centre of the square at right angles to
15 one pair of opposite sides.


Fig. 3

energisation of the phases (in whatever sequence is desired for a particular mode of operation) imparts a periodic radial force to the structure of the laminations. This has the effect of cyclically
5 distorting the laminations, the vibrations thus caused being responsible for producing acoustic noise.

It is an object of the present invention to provide a stator profile and a shape of lamination for a stator in
10 which the tendency to vibration, giving rise to acoustic noise, is reduced.

According to the present invention there is provided a stator for a rotatable electrical machine, the stator
15 comprising a body defining an outer ring and a plurality of stator poles which project radially inwardly from the ring and partially define a rotor space about an axis, the ring having a non-circular outer profile perpendicular to the said axis, which profile has at
20 least one line of symmetry passing through the said axis, each pole being angularly intermediate radially thickest and thinnest parts of the ring and having a centre line which is angularly offset from the or each line of symmetry of the said profile such that the body has no
25 line of symmetry, thereby avoiding any pole centre line being angularly coincident with a vibrational antinode of the stator ring.

A node of vibration may exist toward the relatively
30 thickest part of the ring, whereas the antinode at which vibration of the greatest amplitude and frequency range occurs will be nearer the relatively thinnest part of the ring. By positioning the pole to be centred away from the antinode, the forces tending to create the acoustic



noise are of reduced effect.

5 The offset is desirably about one quarter of the angular
stator pole pitch. Preferably, the line of symmetry from
which the stator pole is offset is coincident with the
radially thinnest part of the ring with respect to the
said axis.

10 While the invention is particularly applicable to simple
shapes, such as square profiles and four or eight poles,
it is also relevant to any other number of stator poles
and phases. For example, the outer profile may be square
or hexagonal. The hexagonal outer profile may be used in
15 a three-phase, six pole machine, whereas the square
profile may be used in a two-phase, four pole machine.
In general, a regular, even sided, shape of $4n$ sides (n
an integer) is conveniently usable for a machine of n
phases or $2n$ poles. However, the more sides to the
20 polygonal outer profile there are, the more the shape
approximates to a circle. The invention is not
necessarily limited to regular arrangements of sides.

25 The stator may be for a switched reluctance machine
having windings associated with the poles which are
arranged to energise the poles. The stator windings may
be arranged so that the stator poles of opposite polarity
are disposed on opposite sides of the radially thinnest
part of the ring. This is advantageous in a four or an
eight stator pole machine. More particularly this
30 advantage is realised in a 2 phase machine.

Preferably, the stator is made up of a plurality of
laminations.

**CLAIMS:**

1. A stator for a rotatable electrical machine, the stator comprising a body defining an outer ring and a plurality of stator poles which project radially inwardly from the ring and partially define a rotor space about an axis, the ring having a non-circular outer profile perpendicular to the said axis, which profile has at least one line of symmetry passing through the said axis, each pole being angularly intermediate radially thickest and thinnest parts of the ring and having a centre line which is angularly offset from the or each line of symmetry of the said profile such that the body has no line of symmetry, thereby avoiding any pole centre line being angularly coincident with a vibrational antinode of the stator ring.
2. A stator as claimed in claim 1 in which the stator poles define an angular pole pitch, the said offset of the centre line of each stator pole adjacent a line of symmetry being about one quarter of the pole pitch.
3. A stator as claimed in claim 1 or 2 in which the line of symmetry from which the centre line of each pole is offset is coincident with the radially thinnest part of the ring with respect to the said axis.
4. A stator as claimed in claim 1 in which the outer profile is square.
5. A stator as claimed in claim 4 including four poles.
6. A stator as claimed in claim 1, 2 or 3 in which the outer profile is hexagonal.



REPLACEMENT SHEET

Date : 24/1/98

7. A stator as claimed in claim 6 including six poles.

8. A stator as claimed in claim 1 or 2 in which the outer profile has the same number of sides as poles.

5

9. An electrical machine comprising a rotor and a stator, the stator comprising a body defining an outer ring and a plurality of stator poles which project radially inwardly from the ring and partially define a space for rotation of the rotor about an axis, the ring having a non-circular outer profile perpendicular to the said axis, which profile has at least one line of symmetry passing through the said axis, each pole being angularly intermediate radially thickest and thinnest parts of the ring and having a centre line which is angularly offset from the or each line of symmetry of the said profile such that the body has no line of symmetry, thereby avoiding any pole centre line being angularly coincident with a vibrational antinode of the stator ring.

20


10. A machine as claimed in claim 9 in which the stator poles define an angular pole pitch, the said offset of the centre line of each stator pole adjacent a line of symmetry being about one quarter of the pole pitch.

25

11. A machine as claimed in claim 10 in which the line of symmetry from which the centre line of each pole is offset is coincident with the radially thinnest part of the ring with respect to the said axis

30

12. A machine as claimed in claim 9 including phase windings defining n phases, the outer profile having $2n$ sides and $2n$ poles (n an integer).



13. An machine as claimed in claim 9, 10, 11 or 12 including stator windings, the machine being constructed and arranged to run as a reluctance machine.

5 14. A machine as claimed in claim 13 in which the stator poles of opposite plurality are disposed on opposite sides of the thinnest part of the ring.


10 15. A lamination for a stator for a rotatable electrical machine, the lamination comprising a ferromagnetic body defining an outer ring and a plurality of stator pole profiles which project radially inwardly from the ring and partially define a rotor space about an axis, the ring having a non-circular outer profile perpendicular to
15 the said axis, which profile has at least one line of symmetry passing through the said axis, each pole being angularly intermediate radially thickest and thinnest parts of the ring and having a centre line which is angularly offset from the or each line of symmetry of the
20 said profile such that the body has no line of symmetry, thereby avoiding any pole centre line being angularly coincident with a vibrational antinode of the stator ring.

25 16. A lamination as claimed in claim 15 in which the stator poles define an angular pole pitch, the said offset of the centre line of each stator pole adjacent a line of symmetry being about one quarter of the pole pitch.

30 17. A stator as claimed in claim 16 in which the line of symmetry from which the centre line of each pole profile is offset is coincident with the radially thinnest part of the ring with respect to the said axis.



13



18. A lamination as claimed in claim 15, 16 or 17 in which the outer profile has n sides and n pole profiles (n an integer).

ABSTRACT**STATOR FOR ELECTRIC MACHINE AND LAMINATION THEREOF**

5 A stator for an electric machine, in particular a
switched reluctance machine, has a non-circular, for
example, square, outer profile and a set of equi-
angularly spaced stator poles which are angularly
10 arranged to be intermediate radially thickest and
thinnest parts of the ring to avoid the poles coinciding
with vibrational antinodes of the outer ring. In a
particular embodiment the outer profile is square and the
stator poles are angularly offset from a line of symmetry
drawn through the centre of the square at right angles to
15 one pair of opposite sides.