FOLDED ARRAY CT BAGGAGE SCANNER

SUMMARY OF THE INVENTION

The deficiencies of the prior art are substantially overcome by the CT scanner of the present invention which includes a wide angle x-ray tube and multiple sets of detectors. One set of detectors is centered on the x-ray source with one or more additional sets covering outer edges of the wide angle x-ray beam. The CT scanner of the present invention has a reduced size while maintaining the same tunnel size as conventional scanners. According to another aspect of the invention, the sets of detectors have different pitches in order to maintain a constant inter-detector angle. Thus, reconstruction algorithms can be simplified. According to another aspect of the invention, detectors are positioned on only half of the detector ring. According to another aspect of the invention, a second set of detectors sensitive to a different energy spectrum are positioned on the other half of the detector ring. The CT scanner of the present invention can provide dual energy analysis from a single scan of a bag, using the multiple sets of detectors.

According to another aspect of the invention, the x-ray source operates at a reduced flux level from conventional systems. Due to the compact size of the CT scanner of the invention, the shorter distances from the source to the detector allows for a less powerful x-ray. According to another aspect of the invention, a portion of a bag can be scanned multiple times with the results being averaged. The data from the multiple scans is averaged to remove noise. The resulting reduction in noise allows a reconstruction of heavy bags with a reduced flux x-ray source.

According to another aspect of the invention, the reduced size CT scanner is incorporated into an airline check-in desk. The CT scanner is positioned to allow the passenger to insert the bag to be checked. Upon successful scanning and analysis (or prior to scanning and analysis), the baggage is tagged by airline personnel in the regular manner and transferred to the existing baggage handling system. According to another aspect of the invention, a plurality of CT scanners are networked

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a cross sectional view of a conventional CT scanner.

Fig. 2 is a perspective view of a CT scanner according to an embodiment of the present invention.

Figs. 3A and 3B are perspective views of a gantry system according to an embodiment of the present invention.

Fig. 4 is a cross sectional illustration of a CT scanner gantry according to an embodiment of the present invention.

Fig. 5 is a perspective view of a detector array component of a CT scanner according to an embodiment of the present invention.

Fig. 6 is a front view of a portion of a detector of a CT scanner according to an embodiment of the present invention.

Fig. 7 is a cross sectional view of a detector component of a dual energy CT scanner according to an embodiment of the present invention.

Fig. 8 is a block diagram of the components of a CT scanner according to an embodiment of the present invention.

Fig. 9 is a block diagram of computer components of a CT scanner according to an embodiment of the present invention.

Fig. 10 is a perspective view of an airline check-in desk according to an embodiment of the present invention.

Fig. 11 is a block diagram of a networked CT scanner system according to an embodiment of the present invention.

Fig. 12 represents the pitch between detector elements according to an embodiment of the invention.

Fig. 13 is a cross sectional view of a CT scanner according to another embodiment of the present invention.

Fig. 14A-C represents data from the CT scanner of Fig. 13.

Fig. 15 is a cross sectional view of a CT scanner according to another embodiment of the present invention.

DETAILED DESCRIPTION

A CT scanner of the present invention has a more compact size than conventional scanners through the use of a wide angle x-ray source and a folded detector array, including sets of detector arrays at different distances from the x-ray source. Fig. 2 illustrates an embodiment of a CT scanner 100 according to an embodiment of the present invention. The CT scanner 100 includes a housing 110 with a substantially circular tunnel 120, there through. The tunnel 120 has an input end 121 and an output end 122. A conveyor 123 extends from the input end 121 to the output end 122 of the tunnel 120. For ease loading baggage, the conveyor may extend beyond the ends of the tunnel 120. Additionally, other conveyors may be positioned and used to

transfer baggage to or from the conveyor 123 in the CT scanner 100. Coverings (not shown), such as lead lined rubber or fabric, may be placed within the tunnel 120 or at the input end 121 and output end 122, to provide x-ray shielding. The CT scanner 100 has a x-ray area 130 towards its center. As illustrated in Fig. 2, the x-ray area 130 may be larger than the ends 121, 122 of the tunnel 130. Alternatively, the housing 110 could be formed of a single size to accommodate the size of the x-ray area 130.

Figs. 3A and 3B illustrate a gantry system disposed within the x-ray area 130 of the housing 110. The gantry system includes a support structure 210 (Fig. 3A) and a gantry 220 (Fig. 3B). The support structure 210 includes a base 211 and a circular shaped vertical support 212. The vertical support 212 is attached to the base 211. The gantry 220 includes a ring 221 which is rotatably attached to the vertical support 212 so that the tunnel 120 passes through the center of the ring 221. An x-ray source 230 is attached to the ring 221 to provide a wide angle x-ray beam over the entire area of the tunnel 120. Preferably, the x-ray source has a rounded shape on an upper surface, similar in shape to the outer surface of the gantry. In this manner, the size of the gantry can be reduced since it does not need to accommodate the extensions of a rectangular x-ray source. Furthermore, the gantry has a three sets of detector arrays240, 241, 242, positioned on the ring 221 within the projected beam of the x-ray source 230. Notably absent from the gantry is a computer. Conventional CT scanners include a computer on the gantry to process data from the detectors and format the data for transmission from the gantry to a host computer which operates the scanner. According to an embodiment of the present invention, the CT scanner does not include a computer on the gantry. Instead, data from the detectors are streamed directly to the host computer. Elimination of the computer on the gantry

permits a smaller and lighter gantry. As with conventional CT scanners, the gantry includes an edge contact (not shown) for transferring power and control signals to the gantry and data from the gantry while the gantry is rotating. Of course, the present invention may include a computer on the gantry to perform some of the processing of data as in conventional CT scanners.

Fig. 4 illustrates the positioning of the x-ray source 230 and the folded array detectors 240, 241, 242 on the ring 221. The ring 221 of the gantry 220 is substantially smaller than for conventional CT scanners with a similar size tunnel 120. According to an embodiment of the present invention, the gantry has a diameter of approximately 130 cm, when the tunnel is approximately 80 cm in diameter. A conventional CT scanner with a 80 cm diameter tunnel would be approximately 210 centimeters. Thus, with the present invention, the CT scanner is reduced in size by approximately 40%. The wide angle x-ray source 230 is located on the gantry 220 so that the x-ray beam intersects the entire area of the tunnel 120. Since the x-ray source 230 has a wider beam 250 than for a conventional CT scanner, it can be positioned closer to the tunnel. The CT scanner of the present invention includes a folded detector array including two or more sets of detectors 240, 241, 242 at different distances from the x-ray source 230. One set of detectors 240 covers a central portion of the gantry ring and is centered on the x-ray source at a distance equal to the source to center detector distance. The other sets of detectors 241, 242 are positioned to intersect the outer ranges of the x-ray fan beam 250. According to an embodiment of the invention, the second sets of detectors 241, 242 start at the point in the beam 250 where the inner detectors 240 reach the edge of the ring 221. Alternatively, the second set of detectors may start at any location in the beam 250 where the inner detectors end, depending upon the size

of the machine and the gantry. The second set of detectors 241, 242 are a closer distance to the x-ray source 230 than the inner detectors 240.

Since the detectors are closer to the x-ray source, they can have a shorter pitch than for conventional CT scanners without sacrificing flux levels or photon counts. According to an embodiment of the present invention, the detector elements are sized and positioned so that each set of detectors has substantially identical pitch and flux levels. The closer distance between the x-ray source 230 and the second sets of detectors 241, 242 allows a smaller detector pitch than for the first set of detectors 240. Since the distance is shorter, the photon count per unit area at the second sets of detectors 241, 242 is higher than for the first set of detectors 240. The higher photon count allows a reduced detector pitch without sacrificing the signal to noise ratio. Additionally, with the reduced pitch, a constant inter-detector angle can be maintained throughout the fan beam 250. Fig. 12 illustrates the relationship between the first set of detectors 240 and the second sets of detectors 241, 242. The angles between detectors (α) remains constant while the pitch between detectors ($\delta 1$, $\delta 2$) changes. To maintain the same angle, the equation $\delta 1/R1 = \delta 2/R2$ must be satisfied. Additionally, to maintain a minimum flux level, the following equation, $(\delta 2 \times w2)/R2^2 \geq (\delta 1 \times w1)/R1^2$, where w1 and w2 are the widths of the detectors, must be satisfied. Since the distance is reduced, both equations can be satisfied, with consistent angles and minimal noise interference. These features allow for simplified reconstruction software. Known 'equi-angular' fan beam reconstruction algorithms can be used with minimal modification. According to an embodiment of the invention, the detector elements of the first set of detectors 240 are approximately 10 mm long and 2.2 mm wide. The detector elements of the second sets of detectors 241, 242 are 8 mm long and 1.8 mm wide.

Figs. 5 and 6 illustrate detector assemblies for simplifying the assembly of the CT scanner of the present invention and to improve quality control. Fig. 5 illustrates a detector assembly 300 having a housing 310, a processing board 320 and a detector array 330. The detector array 330 includes a plurality of detectors (not shown) arranged along the width of the assembly 300. As illustrated in Fig. 6, detector assemblies 300, 301, 302 are attached to the ring 221 of the gantry 220. The detector assemblies 300, 301, 302 are positioned so that the detector or each end of the detector array 330 is adjacent to a detector on the end of an adjacent detector array. Ideally, for purposes of reconstruction, every detector in the array would be perpendicular to and equidistant from the x-ray source. However, with flat detector assemblies 300 there are slight variations in incidence angle and distance across the assembly. According to an embodiment of the invention, a detector assembly at the center of the first set of detectors 240 is arranged with a center detector element being perpendicular to the position of the x-ray source. For the remaining detector assemblies, the outermost detector element is perpendicular to the x-ray source. As illustrated in Fig. 6, the x-ray source direction 350, 351 is perpendicular to the left hand side of an assembly on the left hand side of the gantry. The right hand side of assemblies on the other side of the gantry would be positioned perpendicular to the direction of the x-ray source. Such positioning allows the detector arrays to be properly angled and nested, as illustrated in Fig. 6 to minimize the distance between adjacent elements on different assemblies.

The CT scanner of the present invention is smaller and less costly than conventional scanners. The wide beam width provides additional benefits in addition to reduced diameter. The shorter source to detector distances, allow for less powerful x-ray sources which translates to

lower part costs, simplified cooling (quieter) and power requirements. The decrease in x-ray flux also requires less shielding, again translating to a cheaper (and lighter) system.

According to an embodiment of the present invention, the CT scanner operates in a dual energy mode. Fig. 7 is a cross sectional view of a detector element 330 for dual energy operation. The detector element includes a low energy scintillator layer 331, a low energy photodiode layer 332, a copper layer 333, a high energy scintillator layer 334, and a high energy photodiode layer 335. The high energy layers 334, 335 are wider than the low energy layers 331, 332. According to an embodiment of the invention, the low energgry layers are approximately 5 mm long and the high energy layers are approximately 10 mm long. The different lengths create similar flux levels between the low and high energy layers, even with the greater shielding from the copper and additional layers, thereby simplifying data acquisition electronics and subsequent signal processing. Alternatively, a dual energy scan can be performed using known techniques with a pulsing x-ray source and a single photodiode layer in the detectors.

Fig. 8 illustrates the components of a CT scanner 100 according to an embodiment of the present invention. The CT scanner 100 includes the gantry 221, and two computers 400, 500. A host computer 400 controls operation of the scanner and retrieves data from the detectors. A detection algorithm computer 500 operates on the data to determine whether an explosive device or other object of interest is present. Of course, a single computer could be used to perform all of the functions for the CT scanner. However, the use of two computers prevents the extensive processing of the detection algorithm from slowing down the operation and data collection of the CT scanner. Also, control and data elements are connected between the gantry 221 and the computers 400, 500. An AC power input 224, connected to ordinary 240 V AC power, provides

the power for the CT scanner. A DC power supply 225 receives the AC power and converts it to DC power for powering the processing elements on the gantry. A set of motor drives 222, powered by the AC power, or alternatively by the DC power, operate the conveyor and rotate the gantry. A data link 223 connects the detector assemblies to the host computer 400. DC power and the data link are positioned on the ring of the gantry to provide data during rotation. The circuit boards 320 on the detector assemblies 300 sample the detectors 1440 times per second. The data is then transferred, through the data link 223 to the host computer 400. Encoders are also used to determine the rotational position of the gantry and of the conveyor. This data is also provided to the host computer.

The components of the computers are illustrated in Fig. 9. The host computer 400 includes a motherboard 410 and a data acquisition card 420. The data acquisition card 420 includes inputs from the imaging array 423, the conveyor belt encoder 422, and the gantry encoder. 421. It also includes a field programmable gate array card 424 for retrieving the data and forwarding it to the motherboard 410. The motherboard 410 includes a processor 411, such as a Pentium processor from Intel, a large RAM 412, and a back-projection accelerator card 520 for processing the data. It also includes a Host/PCI bridge for sending and receiving information from the data acquisition card and other computers. The data retrieved from the CT scanner is transferred to the detection algorithm computer 500. An ethernet connection allows quick transfer of the large amounts of data. The detection algorithm computer also includes a motherboard 510 for proper processing of the data to determine the existence of explosives or other materials.

The data from the CT scanner having a folded detector array can be processed using conventional CT operating and reconstruction techniques, such as helical scanning or start/stop scanning. The host computer is programmed to control the x-ray source, conveyor belt, and reading of detectors according to the desired scanning scheme. The detection algorithm computer, similarly, is programmed to reconstruct the CT data based upon the scanning scheme which is utilized.

The smaller size of the CT scanner of the present invention allows it to be more easily incorporated into the baggage handling process than existing EDS systems. Fig. 10 illustrates an airline check-in desk 700 incorporating a baggage scanner according to an embodiment of the present invention. As in some conventional check-in desks, the desk 700 of the present invention includes two check-in stations 710, 720 with a checked baggage loading area 730 between them. Multiple desks 700 could be positioned together in the airport lobby. The CT scanner 100 of the present invention is positioned at the baggage loading area 730. A passenger, upon checking in, places his or her baggage on the conveyor at the baggage loading area 730 or as a standalone system. The baggage is automatically scanned and processed for the existence of explosives. If the baggage passes, the check-in personnel can tag it in the ordinary manner and forward it to the baggage handling system. With the check-in desk of this embodiment of the present invention, very little additional lobby space is needed for scanning baggage, and no modifications to the baggage handling system are required. As an option, the bag can be processed as usual, with the bag tag placed by the ticket agent prior to scanning. Once checked-in, the bag is scanned and injected into the baggage handling system. If desired for improved operational flow, any suspect bag can be resolved in the baggage makeup area away from the

passengers in the terminal area. Alternatively, the CT scanner of the present invention may be incorporated into a self service check-in desk, either as part of a check-in area of the lobby or as a free standing kiosk.

As described above, the CT scanner of the present invention may be a free standing, standalone unit with a TSA operator available for reviewing images and addreesing potential threats. According to another embodiment of the present invention, the host computers of a plurality of CT scanners 700 are networked together to form a single EDS. The networked CT scanners may include any combination of free standing units, self check-in units and integrated check-in desk units. Most bags can be automatically cleared by analysis of the scan data. However, some may require further review by an operator. Rather than have an operator at each scanner, as is used with carry-on baggage, a threat control room 760 with a plurality of operators is connected to the network. If a bag cannot be cleared automatically, the projection and/or reconstruction data is transferred to an operator in the threat control room 760. The operator can then determine whether a threat exists or can be cleared. If the possible threat is cleared by the operator, the bag is passed to the baggage handling system in the ordinary manner. However, if the threat cannot be cleared, the bag would be passed to other operators for a manual hand search. The network may include additional equipment, such as network server computers 750, printers 771, network control stations 772, and remote resolution computers 773.

The small size of the baggage scanning system also allows it to be placed in other locations for distributed handling of checked baggage. For example, a scanner could be placed for curb-side check-in or at rental car return areas for simplified processing. Additionally, hotels or other locations could provide check-in baggage service by providing a scanner and a secure

area for scanned baggage. Guests could have their luggage automatically processed by the hotel and securely transferred to the airport without the need for further processing or delay during check-in. Additionally, the size of the scanner could permit it to be placed in a vehicle used to pick up baggage from various locations for transport to the airport. Free standing units can be provided at various locations in the airport for either self-checkin or assisted check-in of passengers. Alternatively, a CT scanner of the present invention may be used at security checkpoints for scanning of carry-on baggage. Each scanner, independent of its location in the airport or away from the airport, may be operated as a stand alone unit or may be networked for common review by TSA operators.

Fig. 13 illustrates another embodiment of the present invention which provides additional reductions in the size and cost. In the third embodiment, the CT scanner 810 has multiple detectors 841, 842, 843, 844, 845 located on half of the detector ring 811. As in the first two embodiments, the detectors are at different distances from the x-ray source 330 and at different angles. Using half a detector ring is sufficient for creating a CT reconstruction with a full 360 degrees of data. The half of a detector ring is mathematically equivalent to collecting data for 180 degrees plus fan beam, which is required for reconstruction. Figs. 14A-14C illustrate CT reconstruction. Fig. 14A illustrates reconstruction using a full detector ring. Fig. 14B illustrates reconstruction of the same data from half a detector ring. The data from Fig. 14B can be used to complete a full reconstruction as illustrated in Fig. 14C. Using only half a detector ring, as in this embodiment, allows the imaging cost to be substantially reduced because fewer detectors are required.

In order to cut the cost further, the present invention may operate with reduced flux levels from conventional CT scanners. In the design of x-ray systems for baggage, one often designs the flux to be enough to penetrate the heaviest 5% of the bags. The majority of the bags require significantly less flux. By designing the system to provide flux for only the 90th percentile bags, the amount of flux is significantly reduced. The reduced flux allows reduction in the noise levels and required shielding, which substantially reduces size and cost of the device. In order to handle the heavier bags, two or more scans are performed on the bags and the sinograms are averaged. The raw data can be analyzed, as discussed below, to determine which bags or regions of a bag are likely to require the extra flux. The bag slice gets scanned twice or more, averaging the second set of raw data with that obtained in the first rotation, which will reduce the noise in the reconstructed image and mimics a higher flux system. One can do this a 3rd or 4th time for those 1 thousandth bag slices of very heavily cluttered bags. The present invention reduces the need for manual bag searches by providing a practical solution to the "exceptional" or "shield" bag problem. Heavy or "shield" objects in unusual bags are scanned several times to obtain useful data with respect to heavily cluttered areas, without the need for a manual search.

According to another embodiment of the present invention, the CT scanner of the present invention can be used for dual energy CT scans with a single pass of the baggage through the scanner. Fig. 15 illustrates a CT scanner 910 according to this embodiment of the invention. The CT scanner 910 includes a wide-angle x-ray source 930 and two sets of detectors 940, 950. Each of the sets of detectors 940, 950 includes a plurality of detector elements 941, 942, 943, 944, 945, 951, 952, 953, 954, 955. The detector elements for each set are each positioned on one half of the detector ring 911, as in the third embodiment. The two sets of detectors 940, 950 are

sensitive to different energy spectrums. Using the CT scanner of this embodiment, two CT slices, of different energies, can be obtained from a single rotation of the detector ring. This will allow for a dual energy analysis of the CT images. One can also obtain dual energy CT images with back-to-back detectors. The dual energy CT is very useful to reduce the false alarm of the machine. This is very desirable in an airport environment. Although Fig. 15 illustrates five detector arrays for each set of detectors, any number of detector arrays may be used. Each set of detectors 940, 950, corresopnding to an energy level of the x-ray source, is positioned on one half of the detector ring 911.

The present invention has been described with respect to inspection of checked baggage, since it has substantial uses in that field. However, the reduced size of the folded array CT scanner according to the present invention can be used in many other applications for which CT scanners are used. For example, it may be used for cargo or pallette inspection or screening. A larger tunnel is typically necessary for cargo and pallette inspection, and conventional CT scanners are correspondingly much larger. The CT scanner of the present invention has a significantly smaller size, even with a large tunnel. The present invention may also be used in medical CT scanning applications.

Furthermore, the present invention has been described as including an x-ray source. Conventionally, CT scanners have used x-ray sources for radiation and appropriate detectors for x-rays. Of course, other radiation sources, such as gamma radiation, could also be used in connection with the present invention. With a different radiation source, the detectors and/or scintillator material would need to be changed as appropriate to measure the proper radiation spectrum.

Having described at least one embodiment of the invention, modifications, adaptations and improvements will be readily apparent to those of ordinary skill in the art. Such modification, changes and adaptations are considered part of the invention.

CLAIMS

1. A CT scanner for scanning of an object comprising:

a tunnel;

a conveyor for moving the object through the tunnel;

a gantry rotatable around the tunnel;

an x-ray source on the gantry for providing an x-ray beam perpendicular to the tunnel;

a first plurality of detectors on the gantry positioned a first distance from the x-ray source; and

a second plurality of detectors on the gantry positioned a second distance from the x-ray source, wherein the second distance is less than the first distance.

2. The CT scanner of claim 1, wherein one of the detectors in the first plurality of detectors is positioned within the x-ray beam adjacent to one of the detectors in the second plurality of detectors.

3. The CT scanner of claim 1 further comprising a third plurality of detectors on the gantry positioned the second distance from the x-ray source.

4. The CT scanner of claim 3, wherein:

one of the detectors in the first plurality of detectors is positioned within the x-ray beam adjacent to one of the detectors in the second plurality of detectors; and

another one of the detectors in the first plurality of detectors is positioned within the x-ray beam adjacent to one of the detectors in the third plurality of detectors.

5. The CT scanner of claim 4, wherein:

the x-ray beam intersects an entire cross section of the tunnel; and

the first, second, and third pluralities of detectors are positioned on the gantry so that the entire x-ray beam intersects at least one detector.

6. The CT scanner of claim 1, wherein a distance between adjacent detectors in the first plurality of detectors is different than a distance between adjacent detectors in the second plurality of detectors.

7. The CT scanner of claim 1, wherein an angle between beams from the x-ray source to adjacent detectors in the first plurality of detectors is the same as an angle between beams from the x-ray source to adjacent detectors in the second plurality of detectors.

8. The CT scanner of claim 1, further comprising a third plurality of detectors on the gantry positioned a third distance from the x-ray source.

9. The CT scanner of claim 8, wherein:

the x-ray beam intersects an portion of a cross section of the tunnel less than the entire cross section of the tunnel; and

the first, second, and third pluralities of detectors are positioned on the gantry so that the detectors intersect the entire x-ray beam.

10. The CT scanner of claim 9, wherein the x-ray beam intersects one-half of the cross section of the tunnel.

11. The CT scanner of claim 1, further comprising at least one computer for receiving data from the detectors and reconstructing at an image of at least a portion of the object.

12. The CT scanner of claim 11, further comprising a data link between the detectors on the gantry and the at least one computer not positioned on the gantry.

13. The CT scanner of claim 12, wherein the data link provides a constant stream of detector data from the detectors to the at least one computer.

14. The CT scanner of claim 1, wherein each detector in the first and second plurality of detectors includes:

a first photodiode layer responsive to x-ray energy at a first energy level, the first photodiode layer having a first x-ray reception area; and

a second photodiode layer responsive to x-ray energy at a second energy level higher than the first energy level, positioned behind the first photodiode layer relative to the x-ray source, and having a second x-ray reception area larger than the first x-ray reception area.

15. The CT scanner of claim 14, wherein each detector further includes a shielding layer between the first and second photodiode layers.

16. The CT scanner of claim 15, wherein first x-ray reception area and second x-ray reception areas are sized so that the x-ray flux levels for the first photodiode layer and second photodiode layer are substantially equal.

17. A CT scanner for scanning of an object comprising:

a tunnel;

a conveyor for moving the object through the tunnel;

a gantry rotatable around the tunnel;

an x-ray source on the gantry for providing an x-ray beam perpendicular to the tunnel, wherein the x-ray beam includes at least two energy levels;

a first plurality of detectors responsive to a first one of the at least two energy levels positioned on the gantry to intersect a first portion of the x-ray beam; and

a second plurality of detectors responsive to a second one of the at least two energy levels positioned on the gantry to intersect a second portion of the x-ray beam separate from the first portion.

18. The CT scanner of claim 17, wherein the first plurality of detectors includes:

a first subset of detectors positioned a first distance from the x-ray source; and

a second subset of detectors positioned a second distance from the x-ray source, wherein the second distance is less than the first distance.

19. The CT scanner of claim 18, wherein the second plurality of detectors includes:

a third subset of detectors positioned a third distance from the x-ray source; and

a fourth subset of detectors positioned a fourth distance from the x-ray source, wherein the fourth distance is less than the third distance.

20. The CT scanner of claim 17, wherein the first plurality of detectors further includes:

a third subset of detectors positioned a third distance from the x-ray source, wherein the third distance is less than the second distance.

21. A baggage processing system comprising:

a plurality of CT scanners for scanning a bag, each of the CT scanners including a computer for processing data from the CT scanner and for reconstructing an image of least a portion of the bag;

at least one operator review station for displaying a reconstructed image; and

a network for transferring a reconstructed image from at least one CT scanner to the at least one operator review station for display.

22. The baggage processing system of claim 21, wherein the computer in each of the CT scanners includes means for detecting a potential threat in a bag based upon reconstructed image, and

wherein a reconstructed image is transferred to the at least one operator review station upon detection of a potential threat.

23. The baggage processing system of claim 22, wherein at least one of the plurality of CT scanners is located at an airline check-in desk.

24. The baggage processing system of claim 22, wherein at least one of the plurality of CT scanners is located at an airport security check-point.

25. The baggage processing system of claim 22, wherein at least one of the plurality of CT scanners is located at an airport curb-side check-in area.

26. The baggage processing system of claim 22, wherein at least one of the plurality of CT scanners is located at a location other than an airport to which bags are to be transported.

27. A baggage check-in system comprising:

a first check-in station for passengers to check-in for a flight and to check baggage;

a second check-in station for passengers to check-in for a flight and to check baggage; and

a CT scanner positioned between the first check-in station and the second check-in station.

28. The baggage check-in system of claim 27, wherein the CT scanner includes:

a tunnel positioned between the first check-in station and the second check-in station; and

a conveyor through the tunnel to move bags from a first side of the first and second check-in stations to a second side of the first and second check-in stations; and

wherein the baggage check-in system further comprises a baggage handling system for removing bags from the second side of the first and second check-in stations for transport to an aircraft.

29. The baggage check-in system of claim 27, wherein the CT scanner includes a computer for detecting a potential threat in a bag prior to moving a bag to the baggage handling system.

30. A method for processing checked bags at an airport comprising the steps of:

at a plurality of locations in the airport performing the steps of:

scanning bags and reconstructing at least one image of a portion of each bag;

detecting a potential threat based upon reconstructed images;

distributing bags to airplanes if a potential threat is not detected; and

transferring the at least one image to a review location if a potential threat is detected; and

at the review location, performing the steps of:

displaying the transferred at least one image for review by an operator.

31. The method for processing checked bags of claim 30, further comprising the steps of:

at the review location performing the steps of:

receiving in indication from the operator of a threat or not a threat based upon the displayed image; and

transmitting the indication to the location which provided the image; and

at the plurality of locations performing the steps of:

receiving the indication from the review location;

distributing a bag to an airplane based upon an indication of not a threat; and

preventing distribution of the bag to an airplane upon indication of a threat.