

REFRIGERATION RECOVERY FROM REACTOR FEED IN A PROPANE DEHYDROGENATION SYSTEM

TECHNICAL FIELD

[0001] The present invention relates to a process for recovering propylene from a propane dehydrogenation (PDH) process, and more particularly relates to recovering refrigeration from reactor feed in a PDH process.

BACKGROUND

[0002] Propane dehydrogenation (PDH) is a process step in the production of propylene from propane. PDH is important to the petrochemical industry because propylene is the second most important starting product in the petrochemical industry after ethylene. The purpose of a deethanizer and chilling train systems in a PDH process is to separate the cracked gas into a methane-rich tail gas product, a C2 process stream and a C3 process stream.

[0003] It would always be beneficial to improve a PDH process, such as by reducing refrigeration power requirements and/or reducing the size and cost of the compressor system. In particular, the refrigeration power required to provide process cooling in the -5 to 30°C range typically is high. Presently, the depropanizer column overhead stream is produced as a vapor product, which feed to the reactor system without recovery of refrigeration. Process cooling in the -5 to 30°C range is provided through propylene refrigeration.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 is a non-limiting, schematic illustration of a portion of a PDH process as described herein.

SUMMARY

[0004a] In an aspect, there is provided a process for recovering propylene from a propane dehydrogenation process, the process comprising:

partially or fully condensing a purified propane-rich depropanizer overhead stream against a cooling medium having a temperature between 20°C to 50°C at a pressure between 10 barg (1101 kPa) to 20 barg (2101 kPa), to yield a liquid purified propane-rich overhead stream;

letting down the liquid purified propane-rich overhead stream in pressure; and

partially or fully vaporizing the liquid purified propane-rich overhead stream against at least one process stream to provide refrigeration to yield a partially or fully vaporized stream, wherein a vaporization pressure is based on back-pressure from a propane dehydrogenation reactor, and wherein at least a portion of the partially or fully vaporized stream is used as feed to the propane dehydrogenation reactor.

[0005] In one non-limiting example, there is provided a process for recovering propylene from a propane dehydrogenation process, where the process includes partially or fully condensing a depropanizer overhead stream

against a relatively warm cooling medium at relatively high pressure; letting down the liquid overhead stream in pressure; and partially or fully vaporizing the liquid overhead stream against at least one process stream to provide refrigeration.

[0005a] In an aspect, there is provided a system for recovering propylene from a propane dehydrogenation process, the system comprising:

- a depropanizer column generating a purified propane-rich depropanizer overhead stream (7);

- at least one condenser for partially or fully condensing the purified propane-rich depropanizer overhead stream against a cooling medium having a temperature between 20°C to 50°C at a pressure between 10 barg (1101 kPa) to 20 barg (2101 kPa), to yield a liquid purified propane-rich overhead stream;

- at least one device (40, 42, 44) for letting down the pressure of the liquid purified propane-rich depropanizer overhead stream (7) as determined by back-pressure of a propane dehydrogenation reactor; and

- at least one chiller (20, 28, 46) for partially or fully vaporizing the liquid purified propane-rich depropanizer overhead stream (7) to yield a partially or fully vaporized stream that is directed as feed to the propane dehydrogenation reactor.

[0006] In another non-restrictive version, there is provided a system for recovering propylene from a propane dehydrogenation process, where the system includes a depropanizer column generating a depropanizer overhead stream, at least one condenser for partially or fully condensing the depropanizer overhead stream, at least one device for letting down the pressure of the depropanizer overhead stream as determined by back-pressure of a reactor, and at least one chiller for partially or fully vaporizing the depropanizer overhead stream.

DETAILED DESCRIPTION

[0007] In a typical propane dehydrogenation process, fresh propane-rich feed as well as the propane-rich recycle from a C3 Splitter passes through a

Depropanizer column to remove C4+ components. The purified propane-rich stream is recovered as a vapor overhead product that feeds directly to the reactor system without refrigeration heat recovery.

[0008] In one non-limiting embodiment, it has been discovered that the Depropanizer column overhead stream may be partially or fully condensed against a relatively warm cooling medium such as cooling water at relatively high pressure. In one non-limiting embodiment, “relatively warm” is defined as between about 20°C independently to about 50°C, alternatively between about 28°C independently to about 34°C; where the term “independently” when used with reference to a range means any threshold may be used with any other threshold to give a suitable alternative range. In another non-restrictive version “relative high pressure” is defined as between about 10 barg (1101 kPa) independently to about 20 barg (2101 kPa); alternatively between about 12 barg (1301 kPa) independently to about 15 barg (1601 kPa). Other cooling media besides water may include, but not necessarily be limited to, air cooling.

[0009] The liquid overhead stream is then let down in pressure (based on back-pressure from the reactor) and vaporized against process streams to provide refrigeration in the temperature range of about -10°C independently to about $+30^{\circ}\text{C}$; alternatively of about -5°C independently to about 10°C , and offset the requirement for refrigeration typically provided by a propylene or propane refrigeration system in the same temperature range.

[0010] In more detail, and with reference to FIG. 1, dry process gas 1 from a Process Gas Dryer (not shown – coming from the left of FIG. 1) is chilled against Propane in First Deethanizer Feed Chiller 20 and sent to the First Deethanizer Feed Drum 22 as gas 2. Liquid from First Deethanizer Feed Drum 22 is fed to Deethanizer column 24. The overhead vapors go to Process Gas Compressor (PGC) 26. The discharge gas 3 from Process Gas Compressor 26 is cooled and partially condensed against propane in Second Deethanizer Feed Chiller 28, and is sent as stream 4 followed by chilling by propylene refrigerant in Third Deethanizer Feed Chiller 30 and sent to Second Deethanizer Feed Drum 32. Liquid from Second Deethanizer Feed Drum 32 is fed to Deethanizer 24 column. Also shown is Deethanizer Reboiler 38.

[0011] A pumparound on the Deethanizer Column 24 upper section 5 via pump 36 uses propane in Deethanizer First Side Cooler 46 and mid-level propylene refrigerant 6 in Deethanizer Second Side Cooler 48 to reduce the requirement for low-level refrigerant on an overhead condenser.

[0012] Liquid Propane 7 from the Depropanizer Column overhead stream (coming from the left of FIG. 1 – Depropanizer not shown) is let down in pressure (as determined by reactor back-pressure), in one non-limiting embodiment by using valves 40, 42, and 44, and fully vaporized in the combination of Second Deethanizer Feed Chiller 28, First Deethanizer Feed Chiller 20 and Deethanizer First Side Cooler 46. Vaporized propane 9 from the chillers is routed to Cold Box 34 to be reheated and from the Cold Box 34 to the reactor as propane stream 10.

[0013] Non-limiting examples of stream information are given in Table I, whereas non-limiting examples of duties for the chillers are given in Table II.

TABLE I
EXAMPLE STREAM INFORMATION

Stream Number		1	2	3	4	5	6	7	9	10
Description	Units	Gas to 20	Gas from 20	Gas to 28	Gas from 28	From 36 to 46	From 46 to 48	Propane from Depropanizer	Propane from chillers	Propane from cold box 34
Vapor Fraction		1.00	0.78	1.00	0.80	0.00	0.00	0.00	1.00	1.00
Temperature	°C	10.0	-1.8	29.7	-1.6	14.2	4.3	42.3	-5.7	38.0
Pressure	kg/cm ²	13.9	13.7	21.9	21.7	12.8	12.8	15.0	4.0	3.9
Mass Density	kg/cum	15.8	20.1	18.1	24.0	497.6	513.2	462.6	8.6	6.8
Total Mass Flow	kg/hr	121969	121969	75698	75698	500000	500000	194605	194605	194605

TABLE II
EXAMPLE DUTIES

Duties	Gcal/h
First Deethanizer Feed Chiller 20	4.7
Second Deethanizer Feed Chiller 28	4.0
Deethanizer First Pumparound Cooler 46	3.1
Cold Box (propane) 34	3.6

[0014] Use of the propane feed to the reactor for refrigeration recovery as described herein substantially reduces the requirements for refrigeration from a propylene or propane refrigeration system, and could reduce the size and cost of the compressor system. In one non-limiting embodiment the refrigeration requirements may be reduced by about 50% or more, alternatively by about 30% or more. In a different non-restrictive version the reduction in the cost of the compressor system may be about 30%, alternatively about 20%.

[0015] In the foregoing specification, the invention has been described with reference to specific embodiments thereof. However, the specification is to be regarded in an illustrative rather than a restrictive sense. For example, equipment, processes, and operating conditions falling within the claimed or disclosed parameters, but not specifically identified or tried in a particular example, are expected to be within the scope of this invention.

[0016] The present invention may be practiced in the absence of an element not disclosed. In addition, the present invention may suitably comprise, consist or consist essentially of the elements disclosed. For instance, there may be provided a process for recovering propylene from a PDH process, where the process consists essentially of or consists of: partially or fully condensing a depropanizer overhead stream against a relatively warm cooling medium at relatively high pres-

sure; letting down the liquid overhead stream in pressure; and partially or fully vaporizing the liquid overhead stream against at least one process stream to provide refrigeration.

[0017] There may also be provided a system for recovering propylene from a propane dehydrogenation process, where the system consists essentially of or consists of a depropanizer column generating a depropanizer overhead stream; at least one condenser for partially or fully condensing the depropanizer overhead stream; at least one device for letting down the pressure of the depropanizer overhead stream as determined by back-pressure of a reactor; and at least one chiller for partially or fully vaporizing the depropanizer overhead stream.

[0018] The words “comprising” and “comprises” as used throughout the claims, are to be interpreted to mean “including but not limited to” and “includes but not limited to”, respectively.

[0019] As used herein, the word “substantially” shall mean “being largely but not wholly that which is specified.”

[0020] As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.

[0021] As used herein, the term “about” in reference to a given parameter is inclusive of the stated value and has the meaning dictated by the context (e.g., it includes the degree of error associated with measurement of the given parameter).

[0022] As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

CLAIMS

What is claimed is:

1. A process for recovering propylene from a propane dehydrogenation process, the process comprising:
 - partially or fully condensing a purified propane-rich depropanizer overhead stream against a cooling medium having a temperature between 20°C to 50°C at a pressure between 10 barg (1101 kPa) to 20 barg (2101 kPa), to yield a liquid purified propane-rich overhead stream;
 - letting down the liquid purified propane-rich overhead stream in pressure;
 - and
 - partially or fully vaporizing the liquid purified propane-rich overhead stream against at least one process stream to provide refrigeration to yield a partially or fully vaporized stream, wherein a vaporization pressure is based on back-pressure from a propane dehydrogenation reactor, and wherein at least a portion of the partially or fully vaporized stream is used as feed to the propane dehydrogenation reactor.
2. The process of claim 1, wherein the letting down the liquid overhead stream in pressure is based on the back-pressure from the propane dehydrogenation reactor.
3. The process of claim 1, wherein in partially or fully vaporizing the liquid purified propane-rich overhead stream against at least one process stream to provide refrigeration, the refrigeration is in the range of -10 to 30°C.
4. The process of claim 1, wherein partially or fully vaporizing the liquid purified propane-rich overhead stream against at least one process stream to provide refrigeration offsets the requirement for refrigeration provided by a propylene or propane refrigeration system in the same temperature range.

5. A system for recovering propylene from a propane dehydrogenation process, the system comprising:
- a depropanizer column generating a purified propane-rich depropanizer overhead stream (7);
 - at least one condenser for partially or fully condensing the purified propane-rich depropanizer overhead stream against a cooling medium having a temperature between 20°C to 50°C at a pressure between 10 barg (1101 kPa) to 20 barg (2101 kPa), to yield a liquid purified propane-rich overhead stream;
 - at least one device (40, 42, 44) for letting down the pressure of the liquid purified propane-rich depropanizer overhead stream (7) as determined by back-pressure of a propane dehydrogenation reactor; and
 - at least one chiller (20, 28, 46) for partially or fully vaporizing the liquid purified propane-rich depropanizer overhead stream (7) to yield a partially or fully vaporized stream that is directed as feed to the propane dehydrogenation reactor.
6. The system of claim 5 where the device is a valve (40, 42, 44).
7. The system of claim 5, wherein refrigeration of the least one chiller is in the range of – 10°C to 30 °C.