

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
12 June 2003 (12.06.2003)

PCT

(10) International Publication Number  
**WO 03/048786 A2**

(51) International Patent Classification<sup>7</sup>: **G01R**

(21) International Application Number: PCT/US02/38350

(22) International Filing Date:  
27 November 2002 (27.11.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/338,538 30 November 2001 (30.11.2001) US

(71) Applicant (for all designated States except US): **BRISTOL-MYERS SQUIBB COMPANY** [US/US]; P. O. Box 4000, Route 206 and Provinceline Road, Princeton, NJ 08543-4000 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BULLEN, Andrew**

[NZ/US]; 61 White Tail Lane, Wallingford, CT 06492 (US). **WEAVER, Charles, David** [US/US]; 1287 Scard Road, Wallingford, CT 06492 (US).


(74) Agents: **LANGE, Keith** et al.; Bristol-Myers Squibb Company, P.O. Box 4000, Princeton, NJ 08543-4000 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: PIPETTE CONFIGURATIONS AND ARRAYS THEREOF FOR MEASURING CELLULAR ELECTRICAL PROPERTIES



(57) Abstract: The present application is directed to pipette configurations, arrays of the same and methods for using such pipettes and arrays to accomplish electrical measurements, including whole cell and on cell measurements. In one aspect of the present invention, a pipette includes a hollow tubular section having a distal portion and a tip portion. A bubble is formed at the tip and includes an interior chamber in communication with the hollow tubular section at an end adjacent to the bubble portion. The bubble may have a diameter greater than the diameter of an adjacent portion of the hollow tubular section. An aperture is formed between the internal chamber and an exterior surface of the bubble to accommodate seal formation. In a second aspect of the present invention, a method for forming a glass pipette of the present invention is provided which includes the following steps: (1) heating a glass tube, (2) pulling the glass tube to form a blunt tip, (3) heating the blunt tip, and (4) applying back pressure from the tube to form a bubble including an aperture from the blunt tip.

WO 03/048786 A2



ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *without international search report and to be republished upon receipt of that report*