

5

10

15

20

Device for separating sheet material

Specification

25 The present invention relates to a device for singularizing sheet material, according to the preamble of patent claim 1, and to a method for singularizing sheet material, according to the preamble of patent claim 15.

30 A device of the generic type for singularizing sheet material has an actuator and a sheet-material receiver coupled thereto. The actuator is configured for repositioning the sheet-material receiver, for example in such a manner that the sheet-material receiver is set in a translatory motion or in a rotary motion. For example, a previously known sheet-material receiver is designed in the manner of a roller. The sheet-material receiver herein is configured for receiving an individual sheet-material piece from a sheet-material stack,
35 wherein in which sheet-material stack has a multiplicity of sheet-material pieces that is disposed in a layered manner on top of one another along a plumb-line direction.

The sheet material may be paper sheets, cardboard sheets, for example, or paper securities, for example bank notes, currency notes, checks, or the like. A respective
40 sheet-material stack thus comprises a stack of paper securities, paper sheets, or cardboard sheets, for example.

A device of the generic type for singularizing sheet material is described in WO 2014/005715 A1, for example. The sheet-material receiver therein is configured in the shape of an oscillating conveyor belt by way of which individual sheet-material pieces may be retrieved from a sheet-material stack. However, the conveyor belt does not
5 engage the topmost sheet-material piece of the sheet-material stack, but the lowermost sheet-material piece of the sheet-material stack. The sheet-material pieces are thus drawn from the lower side of the sheet-material stack by the oscillating conveyor belt.

It is an object of the present invention to provide a means that permits secure and
10 reliable singularization of sheet material.

This technical object is achieved by one of the subject matter of independent patent claims 1 and 15. Features of advantageous embodiments are stated in the dependent
15 claims.

According to the invention, it is provided that the actuator is configured for setting the sheet-material receiver in an oscillating rotary motion about a rotation axis that lies substantially parallel with the plumb-line direction, so as to receive the individual sheet-material piece from the sheet-material stack. The individual sheet-material piece is
20 preferably the topmost or lowermost sheet-material piece of the sheet-material stack.

The sheet material is, for example, paper sheets, cardboard sheets, paper securities such as bank notes, currency notes, checks or similar. The sheet-material stack preferably has a multiplicity of sheet-material pieces of the same type. This facilitates
25 controlling of the actuator. The sheet-material pieces of the sheet-material stack are configured, for example, so as to be of a rectangular box shape, each having one length, one width, and one height, wherein the height of the respective sheet-material piece is a fraction of the length and of the width, as is the case with currency notes, for example.

30 The actuator comprises, for example, electromechanical means which are actuatable in order for the sheet-material receiver to be set in said oscillating rotary motion about the rotation axis. The exact design embodiment of the actuator will be discussed in more detail at a later point.

35 The oscillating rotary motion about the rotation axis extends along an angular range of less than 10°, for example. The angular range is approximately 1°, for example. Accordingly, the actuator is configured, for example, for rotating the sheet-material

receiver about the rotation axis by approximately 1°, and subsequently for causing a rotary motion in the opposite direction.

The frequency of the oscillating rotary motion is preferably greater than 1 kHz. For example, the frequency of the oscillating rotary motion is approximately 40 kHz. The frequency of the oscillating rotary motion is preferably determined so as to depend on the height of the individual sheet-material piece. For example, the frequency is proportional to a reciprocal value of the height.

In the case of a further embodiment of the device, the actuator is configured for setting the sheet-material receiver in a translatory motion along the plumb-line direction, so as to press the sheet-material receiver for receiving the individual sheet-material piece onto a surface of the individual sheet-material piece at a specific force. For example, the actuator positions the sheet-material receiver above the sheet-material stack, so as to thereupon press the sheet-material receiver onto a central point, for example onto a centerpoint, of the topmost sheet-material piece.

The sheet-material receiver, by virtue of the oscillating rotary motion thereof about the rotation axis and by virtue of a force exerted by the actuator for pressing the sheet-material receiver onto the surface of the individual sheet-material piece, is preferably configured for initiating an attractive force between the sheet-material receiver and the individual sheet-material piece, so as to remove the individual sheet-material piece from the sheet-material stack. For example, contact, for example a so-called surface-to-flexible-surface contact, is initiated between the sheet-material piece and the individual sheet-material piece to be received and to be removed, said contact initiating the generating of the attractive force. By way of the initiated attractive force it is possible for the individual sheet-material piece to be removed from the sheet-material stack. For this purpose, the actuator is preferably configured for setting the sheet-material receiver in a translatory motion along a first direction that lies substantially perpendicular to the plumb-line direction, so as to remove the received individual sheet-material piece from the sheet-material stack, wherein the first direction preferably lies substantially perpendicular to a longitudinal side of the individual sheet-material piece. Alternatively or additionally thereto, it is preferable for the actuator to be configured for setting the sheet-material receiver in a translatory motion along a second direction that lies substantially perpendicular to the plumb-line direction, so as to remove the received sheet-material piece from the sheet-material stack, wherein the second direction preferably lies substantially parallel with the longitudinal side of the individual sheet-material piece.

For example, the actuator is configured for initially positioning the sheet-material receiver above the sheet-material stack, so as to thereupon press the sheet-material receiver onto the surface of the topmost sheet-material piece. Prior, during, or thereafter, the
5 actuator sets the sheet-material receiver in said oscillating rotary motion. On account thereof, the attractive force is initiated between the distal end of the sheet-material receiver that lies on the surface of the sheet-material piece, and the surface of the individual sheet-material piece. The topmost sheet-material piece of the sheet-material stack thus adheres to the distal end of the sheet-material receiver. While maintaining the
10 oscillating rotary motion, a translatory motion along said first direction and/or along the second direction and/or along the plumb-line direction is performed, such that only the topmost sheet-material piece of the sheet-material stack is removed from the sheet-material stack and is fed to a sheet-material collection container or to a sheet-material input device and/or to a sheet-material output device, for example.

15 The sheet-material receiver, at the distal end thereof that during positioning of the sheet-material receiver above the sheet-material stack points to the surface of the topmost sheet-material piece, preferably has a receiving head. Furthermore, a coupling element for coupling to the actuator is preferably provided at the proximal end of the sheet-material receiver. The coupling element is preferably designed in such a manner that the
20 actuator is configured for setting the sheet-material receiver in said oscillating rotary motion.

For example, the sheet-material receiver, in terms of the mass distribution thereof and/or
25 in terms of the dimensions thereof, in relation to the rotation axis is configured so as to be rotationally symmetrical, for example so as to be substantially cylindrical. No or at most a minor imbalance force is created by virtue of the rotationally symmetrical configuration of the sheet-material receiver during the oscillating rotary motion.

30 The receiving head that is provided at the distal end of the sheet-material receiver may have a convex, a planar, or a concave circumferential profile. For example, the sheet-material receiver at the distal end thereof is designed so as to be rounded, that is to say convex or concave, for example in such a manner that the receiving head is configured so as to be approximately spherical-symmetrical in relation to a reference point that lies
35 on the rotation axis. The contact face between the surface of the topmost sheet-material piece of the sheet-material stack and the sheet-material receiver, by virtue of the

approximately spherical-symmetrical configuration of a convex receiving head of the sheet-material receiver, is comparatively minor.

5 In the case of a further preferred embodiment, the sheet-material receiver for contacting the individual sheet-material piece has an elastic material. The elastic material is silicone, for example, or another rubber-type material, for example an elastomer. The elastic material has a hardness of approximately 30 to 95 Shore A, for example, approximately 40 Shore A, for example.

10 In the case of an exemplary embodiment, the sheet-material receiver has a main body from a first material, and a coating applied thereto from a second material, wherein the second material contains the elastic material. The coating is provided on the receiving head, for example, and is designed as a surface coating, for example. For example, the main body is designed so as to be substantially cylindrical, having a length of
15 approximately 10 mm and a radius of approximately 5 mm, wherein the thickness of the coating is approximately 0.5 mm, for example.

The sheet-material receiver is preferably coupled to the actuator by way of a fixed bearing. The actuator has a rotary element and a translatable element, for example. The
20 translatable element is configured for setting the sheet-material receiver in said oscillating rotary motion. Repositioning of the sheet-material receiver along the plumb-line direction is preferably performed by way of the translatable element of the actuator. The coupling element of the sheet-material receiver is preferably coupled to the rotary element of the actuator. The translatable element and the rotary element of the actuator are preferably
25 intercoupled by way of a rotary joint.

The device has a control unit for controlling the actuator, for example. The control unit is configured, for example, for providing control signals according to a control program and for feeding said control signals to the actuator, said actuator transforming said control
30 signals into mechanical movements and thus setting the sheet-material receiver in said oscillating rotary motion and/or translatable motion.

Furthermore, the device may have a movably mounted coupling piece which couples the actuator to a base that is installed in a locationally fixed manner. For example, the
35 coupling piece is mounted so as to be movable in said first and/or second direction, the latter two being perpendicular to the plumb-line direction, and is likewise actuated by the control unit. In the case of this example, the positioning of the sheet-material receiver

may be performed above the topmost sheet-material piece of the sheet-material stack, by means of the coupling piece, wherein the actuator and the sheet-material receiver herein are not moved in relation to the coupling piece. The actuator and the sheet-material receiver are only moved in relation to the coupling piece for pressing the sheet-material receiver onto the surface of the topmost sheet-material piece, and for setting the sheet-material receiver in said oscillating rotary motion.

The method according to independent patent claim 15 forms a further aspect of the present invention. The method according to the invention for singularizing sheet material shares the advantages of the device according to the invention for singularizing sheet material, and has preferred embodiments which correspond to the above-described preferred embodiments of the device of the first aspect of the present invention, in particular as said preferred embodiments are defined in the dependent claims. To this extent reference is made to what has been discussed hereabove.

It is particularly preferable for the method to comprise positioning of the sheet-material receiver above the sheet-material stack, and pressing of the sheet-material receiver onto the surface of the topmost sheet-material piece of the sheet-material stack, and setting of the sheet-material receiver in the oscillating rotary motion about the rotation axis that lies substantially parallel with the plumb-line direction, so as to receive and remove the individual sheet-material piece from the sheet-material stack. In this case, the sheet-material receiver is set in the oscillating rotary motion before pressing, during pressing or after pressing the sheet-material receiver onto the topmost sheet-material piece.

The subject matter of the present invention is suitable for singularizing sheet material of any type. In particular, the subject matter of the present invention may be employed for singularizing paper securities, such as currency notes or bank notes.

One advantage of the present invention lies in particular in that the singularization of sheet material may be performed in a secure and reliable manner, using few components. In particular, the singularization of sheet material may be performed without a friction partner having to be provided in the case of the device, which friction partner prevents those sheet-material pieces that lie below the topmost sheet-material piece from being conjointly removed when the topmost sheet-material piece is being received by the sheet-material receiver.

In the case of the above explanation of the device and of the method for singularizing sheet material, it has always been assumed that the sheet-material receiver engages the topmost sheet-material piece of the sheet-material stack. However, it is also possible for the sheet-material receiver to engage the lowermost sheet-material piece of the sheet-material stack. In the case of this variant, the sheet-material receiver is pressed onto the lower side of the lowermost sheet-material piece and is likewise set in said oscillating rotary motion. This variant thus has preferred embodiments that correspond to the above-described preferred embodiments of the present invention, in particular as said embodiments are defined in the dependent claims. To this extent, reference is made to what has been discussed hereabove.

The concept underlying the invention is to be explained in more detail hereunder by means of the exemplary embodiments that are illustrated in the figures in which:

- fig. 1 shows a schematic cross-sectional view of three sheet-material pieces;
- fig. 2 shows a perspective and schematic view of a device for singularizing sheet material;
- fig. 3 shows a schematic cross-sectional view of the device shown in fig. 2;
- fig. 4 shows a further schematic cross-sectional view of the device shown in fig. 2; and
- figs. 5A-C show schematic cross-sectional views of a sheet-material receiver in the device shown in fig. 2.

Fig. 2 to fig. 4 show schematic views of a device 1 for singularizing sheet material. Fig. 2 shows the device 1 in a perspective view, and fig. 3 and fig. 4 show the device in cross-sectional views.

The device 1 is designed for singularizing sheet material. Specifically, it is intended that individual sheet-material pieces 5-1 to 5-n that are disposed in a layered manner on top of one another along a plumb-line direction y and thus configure a sheet-material stack 5 are singularized. To this end, the device 1 comprises a sheet-material receiver 12 which is driven by an actuator 11 of the device 1. The actuator 11 thus sets the sheet-material

receiver 12 in specific motions, as will be explained in more detail at a later point. A schematic cross-sectional view of this sheet-material receiver 12 is shown in fig. 5.

In order for the configuration of the device 1 for singularizing sheet material, and for a method for singularizing sheet material, to be explained, reference is made hereunder to all figs. 2 to 5. It is to be subsequently explained in an exemplary manner by means of fig. 1 how specific control parameters for operating the device 1 may be calculated.

The actuator 11 has a translatable element 111 and a rotary element 112. The actuator 11 is actuated by a control unit (not shown in the figures) of the device 1.

The translatable element 111 is configured for repositioning the sheet-material receiver 12 along the plumb-line direction y , and the sheet-material receiver is set in an oscillating rotary motion about a rotation axis r that lies parallel with the plumb-line direction y by way of the rotary element 112 of the actuator 11.

Moreover, the actuator 11, having the translatable element 111 and the rotary element 112, is disposed so as to be movable along a first direction x that lies substantially perpendicular to the plumb-line direction y , and/or a second direction z , such that a received sheet-material piece 5-1 may be removed from the sheet-material stack 5 in the x -direction or the z -direction.

The sheet-material stack 5 is, for example, a stack of paper sheets, cardboard sheets, paper securities (for example bank notes, currency notes, or checks), or similar sheet-shaped media. Said media is disposed in a layered manner on top of one another along the plumb-line direction y , thus configuring the sheet-material stack 5. Each of the sheet-material pieces 5-1 to 5- n in the example shown has the same length L , the same width B , and the same height H . However, the subject matter of the present invention does not require that all sheet-material pieces 5-1 to 5- n have the same dimensions.

In order for an individual sheet-material piece, specifically the topmost sheet-material piece 5-1, to be received, the actuator 11, having the sheet-material receiver 12 coupled thereto, is initially positioned above the sheet-material stack 5. Thereafter, the actuator 11 presses the sheet-material receiver 12 onto a surface 51 of the topmost sheet-material piece 5-1, for example onto a central point of the topmost sheet-material piece 5-1, as is schematically shown in fig. 2. Thereafter, the actuator 11 by means of the translatable element 111 presses the sheet-material receiver 12 onto the surface 51 of the

topmost sheet-material piece 5-1 at a specific force. Prior, during, or after pressing the sheet-material receiver 12 onto the surface 51, the actuator 11 by means of the rotary element 112 sets the sheet-material receiver 12 in an oscillating rotary motion about the rotation axis r.

5

The oscillating rotary motion about the rotation axis r extends across an angular range of less than 10° . For example, the actuator 11 rotates the sheet-material receiver 12 by an angle ϕ of 1° about the rotation axis r along a rotation direction rr. Thereafter, the actuator 11 sets the sheet-material receiver 12 in a rotation by 1° along the opposite rotation direction rr, repeating this procedure at a specific frequency. This oscillating rotary motion is performed at a frequency of greater than 1 kHz, for example. The frequency is approximately 20 to 40 kHz, for example. The frequency is determined so as to depend on the height H of the individual sheet-material piece 5-1, for example. For example, the frequency is proportional to a reciprocal value of the height H of the individual sheet-material piece 5-1. This will be explained in more detail at a later point with reference to fig. 1.

10

15

With reference to figs. 5A-C, exemplary potential design embodiments of the sheet-material receiver 12 are to be discussed in more detail initially. The sheet-material receiver 12 at the proximal end thereof comprises a coupling element 121 which in fig. 5 is illustrated in only a schematic manner. The sheet-material receiver 12 by way of the coupling element 121 is coupled to the rotary element 112 of the actuator 11.

20

The sheet-material receiver 12 is designed so as to be substantially cylindrical, in particular thus so as to be rotationally symmetrical in relation to the rotation axis r. The sheet-material receiver 12 at the distal end thereof has a receiving head 122.

25

In the case of the example shown in fig. 5A, the receiving head 122 is designed so as to be spherical-symmetrical and convex in relation to a reference point P that lies on the rotation axis r. In other words, the receiving head 122, and thus the distal end of the sheet-material receiver 12, has a convex circumferential profile. The surface of the receiving head 122 may thus be designed in such a manner that each point lying thereon has the same distance R, which consequently corresponds to a spherical radius, with respect to the reference point P. This spherical radius R is established so as to depend on the application or on the type of sheet material, respectively.

30

35

In the case of the example corresponding to fig. 5A, the sheet-material receiver 12 has a main body 12-1 that is molded from a first material, and a coating 12-2 from a second material that differs from the first material. The second material of the coating 12-2 comprises an elastic material, for example silicone or another rubber-type material. The first material of the main body 12-1 of the sheet-material receiver 12 has an elasticity that is lower than the elasticity of the material of the coating 12-2. The coating 12-2 in the case of the example shown is provided only on the receiving head 122, and has a minor thickness of one millimeter or less than one millimeter, for example 0.5 mm.

However, the sheet-material receiver 12 at the distal end thereof does not necessarily have to have a convex circumferential profile and/or said coating 12-2. In the case of the variant according to fig. 5B, the receiving head 122, and thus the distal end of the sheet-material receiver 12, has a substantially planar circumferential profile, and, in the variant according to fig. 5C, the receiving head 122, and thus the distal end of the sheet-material receiver 12, has a substantially convex circumferential profile.

Depending on the type of the sheet-material piece 5-1, ..., 5-n to be received, one specific circumferential profile of the receiving head 122 may be more expedient than another. Notwithstanding the sheet-material receiver 12 in fig. 3 and fig. 4 being shown having a receiving head 122 having a convex circumferential profile, the exemplary embodiments therein are not limited to such a receiving head 122. Rather, the receiving head 122 also in the case of the examples according to fig. 3 and fig. 4 may have a substantially planar or a concave circumferential profile.

Once the actuator 11 has pressed the sheet-material receiver 12 onto the surface 51 of the topmost sheet-material piece 5-1, and has set the sheet-material receiver 12 in said oscillating rotary motion, the topmost sheet-material piece 5-1 is repositioned by a first distance $\Delta 1$ in the x-direction, and a sheet-material piece 5-2 lying therebelow is repositioned by a second distance $\Delta 2$. It can be clearly seen in fig. 4 that the first distance $\Delta 1$ is significantly greater than the second distance $\Delta 2$.

Ultimately, the contact pressure of the sheet-material receiver 12 and the oscillating rotary motion of the sheet-material receiver 12 enable the removal of the topmost sheet-material piece 5-1 from the sheet-material stack 5. The actuator 11, while maintaining the oscillating rotary motion of the sheet-material receiver 12, may draw the topmost sheet-material piece 5-1 from the sheet-material stack 5, and convey said topmost sheet-material piece 5-1 to a sheet-material output device (not shown in the figures), for

example. Upon delivery of the conveyed sheet-material piece 5-1, the actuator 11 returns to the sheet-material stack 5 and proceeds in the same way with the next sheet-material piece 5-2.

5 The sheet-material receiver 12, by virtue of the oscillating rotary motion thereof about the rotation axis r , and by virtue of the force exerted by the actuator 11 for pressing the sheet-material receiver 12 onto the surface 51 of the topmost sheet-material piece 5-1, is thus configured for initiating an attractive force between the sheet-material receiver 12 and the individual sheet-material piece 5-1, such that the individual sheet-material piece
10 5-1 may be removed from the sheet-material stack 5.

In order for the frequency of the oscillating rotary motion of the sheet-material receiver 12 to be determined, the following procedure may be followed, for example: The sheet-material stack 5 is modeled as a monolithic bar having a rectangular cross section. This
15 bar comprises n imaginary elements, wherein n corresponds to the number of individual sheet-material pieces 5-1 to 5- n , each element corresponding to one sheet-material piece. Of these n elements, the elements $i-1$, i , and $i+1$, which thus in an exemplary manner represent three sheet-material pieces 5-1, 5-2, and 5-3, lying on top of one another, are illustrated in fig. 1.

20

By means of the equation 1

$$M \cdot \ddot{\varphi} + K \cdot \varphi = 0 \text{ with } M, K \in \mathbb{R}^{n \times n} \quad (1)$$

25 eigenmodes of this bar are determined. In the equation (1)

M refers to a mass matrix,

K refers to a rigidity matrix,

φ refers to a twisting angle of an element (sheet-material piece about the rotation
30 axis r), and

$\ddot{\varphi}$ refers to the second temporal derivation of φ .

Equations of motion are established in order for the mass matrix M and the rigidity matrix K to be determined. A respective connection between the individual n imaginary elements
35 is modulated as a torsion spring having a rigidity c . This rigidity c results from the following equations 2 for a twisting angle of an element subjected to torsion:

$$\varphi = T \cdot \frac{d}{G \cdot I_t} \rightarrow T = \frac{G \cdot I_t}{d} \cdot \varphi \rightarrow c = \frac{G \cdot I_t}{d} \quad (2)$$

In the equation (2)

5

T refers to the torque of torsion
 G refers to the shear modulus
 I_t refers to the area moment of inertia
 d refers to the length of the bar

10

The equation of motion 3 results for the i^{th} element (sheet-material piece):

$$J_i \cdot \ddot{\varphi}_i + c \cdot (\varphi_i - \varphi_{i+1}) + c \cdot (\varphi_i - \varphi_{i-1}) = 0 \text{ with } 1 \leq i < n \quad (3)$$

wherein J refers to a rotary inertia, and the following equation 4 results for the n^{th} equation of motion:

15

$$J_i \cdot \ddot{\varphi}_i + c \cdot (\varphi_i - \varphi_{i-1}) = 0 \quad (4)$$

In the case of a sheet-material stack having three sheet-material pieces ($n = 3$), the mass matrix M and the rigidity matrix K result as follows:

20

$$M = \begin{bmatrix} J & 0 & 0 \\ 0 & J & 0 \\ 0 & 0 & J \end{bmatrix} \quad \text{and} \quad K = \begin{bmatrix} 2 \cdot c & -c & 0 \\ -c & 2 \cdot c & -c \\ 0 & -c & c \end{bmatrix}$$

By means of the complete description of the bar by way of the two matrices M and K , the natural frequencies together with the respective eigenmodes that are described by the eigenvectors may be determined. For example, a calculation is performed using the following parameters which are reflected in the table:

25

30

Formula indicator	Variable	Value	Unit
φ_i	Twisting angle of the i^{th} element (sheet-material piece)		
n	Number of elements lying on top of one another (sheet-material pieces)	60	
m	Mass of an individual element (sheet-material piece)	0.001125	kg
G	Shear modulus	300000	$\frac{N}{m^2}$
B	Width of an individual element (sheet-material piece)	0.075	m
L	Length of an individual element (sheet-material piece)	0.15	m
I_t	Area moment of inertia to torsion	0.0000144842	m^4
k	Computation coefficient	0.22888542	
H	Height of an individual element (sheet-material piece)	0.001	m
J	Rotary inertia	0.00000263672	$kg\ m^2$
c	Rigidity torsion spring	4345.26	Nm

By means of this data, for example by means of the equation (2) and the values in the table, it may be determined that the frequency of the oscillating rotary motion is to be 40.595 kHz, for example, in order for the topmost sheet-material piece 5-1 to be removed from the sheet-material stack 5, without the remaining sheet-material pieces 5-2 to 5-n being removed conjointly from the sheet-material stack 5. In particular, it is also possible for the frequency of the oscillating rotary motion to be determined independently of the number n of the sheet-material pieces 5-1 to 5-n. Numerical values and computation methods stated above are to be understood as being merely exemplary, of course.

In the case of the above explanation of the device and of the method for singularizing sheet material, it has always been assumed that the sheet-material receiver 12 engages the topmost sheet-material piece 5-1 of the sheet-material stack 5. However, it is also possible for the sheet-material receiver 12 to engage the lowermost sheet-material piece 5-n of the sheet-material stack 5. In the case of this variant, the sheet-material receiver

12 is pressed onto the lower side of the lowermost sheet-material piece 5-n and is likewise set in said oscillating rotary motion about the rotation axis r.

List of reference signs / Abbreviations used

1	Device for singularizing sheet material
11	Actuator
12	Sheet-material receiver
12-1	Main body
12-2	Coating
121	Coupling element
122	Receiving head
5	Sheet-material stack
5-1, ..., 5-n	Sheet-material pieces
51	Surface of the topmost sheet-material piece 5-1
B	Width of an individual sheet-material piece
L	Length of an individual sheet-material piece
H	Height of an individual sheet-material piece
r	Rotation axis
rr	Direction of the oscillating rotary motion (Rotation direction)
R	Spherical radius
P	Reference point on the rotation axis r
x	x-axis / first direction
y	y-axis/ plumb-line direction
z	z-axis / second direction
$\Delta 1$	First distance
$\Delta 2$	Second distance

Patent claims

1. A device (1) for singularizing sheet material, having an actuator (11) and a sheet-material receiver (12) coupled thereto, wherein the actuator (11) is configured for repositioning the sheet-material receiver (12), and wherein the sheet-material receiver (12) is configured for receiving an individual sheet-material piece (5-1) from a sheet-material stack (5) in which a multiplicity of sheet-material pieces (5-1, ..., 5-n) are disposed in a layered manner on top of one another along a plumb-line direction (y),

characterized in that

the actuator (11) is configured for setting the sheet-material receiver (12) in an oscillating rotary motion about a rotation axis (r) that lies substantially parallel with the plumb-line direction (y), so as to receive the individual sheet-material piece (5-1) from the sheet-material stack (5).

2. The device (1) as claimed in claim 1, **characterized in that** the sheet-material receiver (12) at the distal end thereof has a receiving head (122), and/or at the proximal end thereof has a coupling element (121) for coupling to the actuator (11).

3. The device (1) as claimed in claim 1 or 2, **characterized in that** the sheet-material receiver (12) in relation to the rotation axis (r) is configured so as to be rotationally symmetrical, for example so as to be substantially cylindrical.

4. The device (1) as claimed in claim 2 or 3, **characterized in that** the receiving head (122) has a convex, a planar, or a concave circumferential profile.

5. The device (1) as claimed in one of the preceding claims, **characterized in that** the actuator (11) is configured for setting the sheet-material receiver (12) in a translatory motion along a first direction (x) that lies substantially perpendicular to the plumb-line direction (y), so as to remove the received individual sheet-material piece (5-1) from the sheet-material stack (5), wherein the first direction (x) preferably lies substantially perpendicular to a longitudinal side (L) of the individual sheet-material piece (5-1).

6. The device (1) as claimed in one of the preceding claims, **characterized in that** the actuator (11) is configured for setting the sheet-material receiver (12) in a translatory

motion along a second direction (z) that lies substantially perpendicular to the plumb-line direction (y), so as to remove the received individual sheet-material piece (5-1) from the sheet-material stack (5), wherein the second direction (y) preferably lies substantially parallel with a longitudinal side (L) of the individual sheet-material piece (5-1).

7. The device (1) as claimed in one of the preceding claims, **characterized in that** the actuator (11) is configured for setting the sheet-material receiver (12) in a translatory motion along the plumb-line direction (y), so as to press the sheet-material receiver (12) for receiving the individual sheet-material piece (5-1) onto a surface (51) of the individual sheet-material piece (5-1) at a specific force.

8. The device (1) as claimed in one of the preceding claims, **characterized in that** the oscillating rotary motion about the rotation axis (r) extends along an angular range of less than 10°, for example of approximately 1°.

9. The device (1) as claimed in one of the preceding claims, **characterized in that** the frequency of the oscillating rotary motion is greater than 1 kHz, for example approximately 20 kHz to 40 kHz.

10. The device (1) as claimed in one of the preceding claims, **characterized in that** the frequency of the oscillating rotary motion is determined so as to depend on a height (H) of the individual sheet-material piece (5-1), for example is proportional to a reciprocal value of the height (H).

11. The device (1) as claimed in one of the preceding claims, **characterized in that** the sheet-material receiver (12) for contacting the individual sheet-material piece (5-1) has an elastic material, for example silicone.

12. The device (1) as claimed in claim 11, **characterized in that** the sheet-material receiver (12) has a main body (12-1) from a first material, and a coating (12-2) applied thereto from a second material, wherein the second material contains the elastic material.

13. The device (1) as claimed in one of the preceding claims, **characterized in that** the sheet-material receiver (12), by virtue of the oscillating rotary motion thereof about the rotation axis (r) and by virtue of a force exerted by the actuator (11) for pressing

the sheet-material receiver (12) onto a surface (51) of the individual sheet-material piece (5-1), is configured for initiating an attractive force between the sheet-material receiver (12) and the individual sheet-material piece (5-1), so as to remove the individual sheet-material piece (5-1) from the sheet-material stack (5).

5

14. The device (1) as claimed in one of the preceding claims, **characterized in that** the actuator (11) a translatable element (111) and a rotary element (112), wherein the translatable element (111) is configured for repositioning the sheet-material receiver (12) along the plumb-line direction (y), and wherein the rotary element (112) is configured for setting the sheet-material receiver (12) in said oscillating rotary motion and the rotation axis (r).

10

15. A method for singularizing sheet material by means of a device (1) having an actuator (11) and a sheet-material receiver (12) coupled thereto, wherein the actuator (11) is configured for repositioning the sheet-material receiver (12), and wherein the sheet-material receiver (12) is configured for receiving an individual sheet-material piece (5-1) from a sheet-material stack (5) in which a multiplicity of sheet-material pieces (5-1, ..., 5-n) are disposed in a layered manner on top of one another along a plumb-line direction (y),

15

20

characterized in that the method comprises the following steps:

- setting the sheet-material receiver (12) in an oscillating rotary motion about a rotation axis (r) that lies substantially parallel with the plumb-line direction (y) by means of the actuator (11), so as to receive the individual sheet-material piece (5-1) from the sheet-material stack (5).

25

30