

DESCRIPTION

TITLE OF INVENTION: MESSAGE DEVICE

TECHNICAL FIELD

[0001] The present invention relates to a massage device which massages a human body by transmitting mechanical vibrations to the same.

BACKGROUND ART

[0002] Figure 5 shows a conventional massage device. This massage device is disclosed in the Patent Document 1.

As shown in Figure 5 an adhesive pad such as urethane gel or silicon gel is denoted by 110, and a vibrating motor which functions as a vibration generation means is denoted by 120. The opposite surface of the adhesive face of the adhesive pad 110 contains a magnetic piece and the vibrating motor 120 has a magnetically adherable surface respectively, which are not shown in the figure.

[0003] As shown in Figure 5 in order to alleviate stiffness in shoulders, the adhesive face of the adhesive pad 110 is adhered to an area affected by shoulder stiffness, and the vibrating motor 120 is placed on the adhesive pad 110. Thereafter, the magnetic piece of the adhesive pad 110 and the magnetically adherable surface of the vibrating motor 120 are adhered to each other so that the vibrating motor 120 is fixed on the affected area of shoulder stiffness.

[0004] Subsequently, when a power switch is turned on to vibrate the vibrating motor 120, the vibrations of the vibrating motor 120 are transmitted to the area affected by shoulder stiffness, resulting in the alleviation of the shoulder stiffness. To summarize, referring to Figure 5 the vibrating motor 120 is fixed on a given part of the body so as to produce vibrations by means of the adhesive pad 110 equipped

with the magnetic piece in order to produce massage therapy.

PRIOR ART DOCUMENT

PATENT DOCUMENT

[0005]

Patent Document 1:

Japanese Patent Application Laid-Open No. 2007-44319

SUMMARY OF THE INVENTION

TECHNICAL PROBLEMS

[0006] In the case of the massage device of Figure 5 the adhesive pad is utilized to hold the vibrating motor on a given part of the body. Therefore, it is difficult to knead or pinch a region being massaged while concurrently transmitting vibrations, and it ends up merely transmitting vibrations.

[0007] Moreover, since the adhesive pad is utilized to hold the vibrating motor on the body, there is a problem that the vibrations cannot be transmitted deeply inside the body. Instead, they are transmitted only to the surface part of the region being massaged.

[0008] Furthermore, since the adhesive pad is utilized to hold the vibrating motor on the body, there is also a problem that the vibrations cannot be transmitted to a region where the adhesive pad is difficult to be adhered to and accordingly the vibrating motor is not accommodating such as underneath clothes or on head hair.

[0009] To solve the problems described above, the present invention enables one to transmit vibrations to a region being massaged while concurrently kneading or pinching the same region so that the massaging effect can be enhanced.

[0010] The present invention also enables one to transmit vibrations to not only the surface part of the region being

massaged but also deeply inside of the body without difficulty so that the massaging effect can be enhanced.

[0011] Moreover, the present invention removes restrictions on the possible regions to get massaged. The vibration generation means can be placed on a region that is difficult to be massaged, such as underneath clothes or on head hair. Therefore, it becomes possible to apply massage anywhere on the body.

SOLUTION TO PROBLEM

[0012] The massage device of the present invention is a device which massages a human body by transmitting mechanical vibrations provided with a vibration generation means which generates said vibrations and a glove means which is worn on hands that apply massage and each of which is equipped with at least one of the said vibration generation means.

[0013] The massage device of the present invention is comprised of the glove means which are equipped with the vibration generation means on the palm side of them.

[0014] The massage device of the present invention is comprised of the glove means which are equipped with the vibration generation means on the fingertips side of them.

[0015] The massage device of the present invention is comprised of the glove means which are equipped with the vibration generation means on the back-of-hand side of them.

[0016] The massage device of the present invention is comprised of the glove means which are equipped with a plurality of the vibration generation means.

[0017] The massage device of the present invention comprises a plurality of the vibration generation means having

a vibration control means which allows the vibrations to be generated sequentially and separately.

[0018] The massage device of the present invention comprises the vibration generation means having a vibration control means which produces changes in the level of the vibrations periodically.

[0019] The massage device of the present invention is provided with the vibration generation means which is a coin-shaped vibrating motor.

ADVANCEOUS EFFECTS OF INVENTION

[0020] As the massage device of the present invention which massages a human body by transmitting mechanical vibrations is comprised of the vibration generation means which generates vibrations and the glove means which are worn on hands that apply massage and each of which is equipped with at least one of the said vibration generation means, it becomes possible to knead or pinch a region being massaged while concurrently transmitting vibrations from the vibration generation means, which enhances the massaging effect.

In addition, due to the glove means which are worn on the hands, it becomes possible to compress the vibration generation means on the body region so that the vibrations can be transmitted to not only the surface part of the body region being massaged but also deeply inside of the body without difficulty, resulting in the enhancement of the massaging effect.

Furthermore, due to the glove means which are worn on the hands, the vibration generation means can be placed on body regions such as on clothes or on head hair without difficulty, making massage possible in body regions which are conventionally considered difficult to get massaged.

[0021] As the glove means of the present invention are

equipped with the vibration generation means on the palm side of them, it becomes possible to use palms of the glove means to apply massage while concurrently transmitting the vibrations generated by the vibration generation means, resulting in the capability of providing a variety of massage therapy.

[0022] The glove means of the present invention are equipped with the vibration generation means on the fingertips side of them so that it becomes possible to use fingertips of the glove means to apply massage while concurrently transmitting the vibrations generated by the vibration generation means, resulting in the capability of providing a variety of massage therapy.

[0023] As the glove means of the present invention are equipped with the vibration generation means on the back-of-hand side of them, it becomes possible to use back-of-hand of the glove means to apply massage while concurrently transmitting the vibrations generated by the vibration generation means, resulting in the capability of providing a variety of massage therapy.

[0024] As the glove means of the present invention are equipped with a plurality of the vibration generation means, it becomes possible to transmit vibrations from the plurality of the vibration generation means, further enhancing the massaging effect.

[0025] The massage device of the present invention further comprises a vibration control means capable of controlling vibrations that are generated sequentially and separately from the plurality of vibration generation means, so that it becomes possible to create vibrations that are transmitted without having to move hands or fingers, resulting in the application of massage therapy along the lines of trigger

points of the body.

[0026] The massage device of the present invention further comprises a vibration control means which periodically produces changes in the level of the vibrations generated from the vibration generation means, making it possible to produce a variety of vibrational patterns, providing a varied massage therapy.

[0027] As the vibration generation means is formed as a coin-shaped vibrating motor, it becomes possible to make the glove means lighter and less bulky, resulting in a more practical embodiment of the massage device.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028]

[Figure 1] FIG. 1 is an appearance diagram of the massage device according to the embodiment 1 of the present invention.

[Figure 2] FIG. 2 is a block diagram which illustrates the internal constitution of the massage device according to the embodiment 1 of the present invention.

[Figure 3] FIG. 3 is an explanatory diagram which illustrates an example of how to use the massage device according to the embodiment 1 of the present invention.

[Figure 4] FIG. 4 is a configuration diagram which illustrates an example of a variation of how to arrange vibrating motors.

[Figure 5] FIG. 5 is a cross-section view of a coin-shaped vibrating motor,

(a) shows a state that vibrations are generated by rotating an eccentric weight, while

(b) shows a state that vibrations are generated toward normal

direction of the coin face in parallel with the radial direction.

[Figure 6] FIG. 6 is an explanatory diagram which illustrates an example of how to use the conventional massage device.

DETAILED DESCRIPTION OF THE INVENTION

[0029] Hereinafter, an embodiment of this invention will be concretely described with reference to the drawings. In each of the drawings, same numerical symbols are used to the same constitutions or corresponding constitutions.

[0030] Embodiment 1

Figure 1 is an appearance diagram of the massage device according to the first embodiment of the present invention.

In Figure 1, a pair of gloves (glove means) which are worn on the right hand and the left hand of a user are denoted by 10. Coin-shaped vibrating motors (vibration generation means) which are placed on regions corresponding to balls of thumbs, forefingers, middle fingers, annular fingers and little fingers of the gloves 10 are denoted by 21. A controller of the massage device is denoted by 30. It is possible to independently place a downsized controller 30 on each one of the gloves so as to upgrade the operational flexibility. Herein, a ball of a finger intends a region where finger pattern is found. Each of the names of regions on the gloves 10 corresponds to the part names of hands hereinafter.

[0031] The massage device shown in Figure 1 has a feature in a way that the gloves 10 are equipped with the vibrating motors 21. The vibrating motors 21 are the materials which are often utilized as vibrators for mobiles, and are capable of employing a variety of types of vibration generation, not only the way which rotates an eccentric weight around a motor shaft (shown in Figure 5(a)), but also the way in which vibrations are generated toward a normal direction of the coin face in

parallel with the radial direction, and so on.

In Figure 5(a), an oscillator 51 rotates around a motor shaft 50. Since the oscillator 51 is equipped with an eccentric weight 52, the whole of the case 53 vibrates through the motor shaft 50 around which the oscillator 51 rotates. 53 is a coil for rotations which rotates the oscillator 51 by drawing and repelling a magnet 54. It is ideal to set up the case 53 in the shape of a coin which is about 10 millimeters in outside diameter, about 3 to 5 millimeters in thickness, and weighs about 1.0 gram. This case is bonded with an adhesion bond to a certain place of the gloves 10 and wired to the controller 30 as in Figure 2.

Figure 5(b) shows another example of the vibrating motor which generates vibrations toward a normal direction of the coin face in parallel with the radial direction. Here, a circular plate 61 is eccentrically fixed to a shaft 60 made of elastic material. The circular plate 61 is equipped with a plurality of coils. Since a rotative force is generated between the circular plate 61 and magnets 63 which are placed opposite to the circular plate 61, the circular plate 61 rotates around the shaft 60 when it is energized. At this time, due to a magnet 62 placed on a part of the circular plate 61, a force which intergrades in the axial direction affects the circular plate 61 so that the circular plate 61 vibrates in the axial direction i.e. normal direction of the coin face concurrently vibrating in the radial direction by eccentricity of the center of gravity. When these kind of vibrating motors which generate multiple vibrations are fixed to the gloves, it is possible to further enhance the massaging effect.

[0032] The vibrating motors 21 are bonded with an adhesion bond or the like to balls of fingers of the gloves 10. Although Figure 1 shows an embodiment wherein the vibrating motors 21 are placed outside of the gloves 10, it is possible to place the vibrating motors 21 inside of the gloves 10 i.e. the side in which hands of the user are inserted. As the coin-shaped

vibrating motors are employed, it becomes possible to make the gloves 10 lighter and less bulky, resulting in a more practical embodiment of the massage device.

[0033] Figure 2 shows a block configuration according to the first embodiment of the massage device of the present invention.

In Figure 2, the controller 30 is comprised of the following parts: An operation panel which operates the massage device is denoted by 31; a CPU (vibration control means) which controls the massage device is denoted by 32; a memory which stores the program and the various settings of the massage device is denoted by 33; and a motor driver (vibration control means) which activates the respective vibrating motors 21 is denoted by 34.

[0034] Hereinafter it is explained how the device is used. When a user of the massage device wears the gloves 10 on their hands, the user starts up the massage device by operating the operation panel 31. The CPU 32 activates the respective vibrating motors 21 by means of the motor driver 34 based on a program of a normal mode which is stored in the memory 33. Subsequently, when the vibrations are generated from the vibrating motors 21, the user applies the gloves 10 to a body region to get massaged in order to transmit the vibrations and concurrently knead or pinch the same region by the gloves 10.

[0035] As described above, as the gloves 10 are equipped with vibrating motors 21 which are worn on hands that apply massage and transmit vibrations to the body region to get massaged while concurrently kneading or pinching the same region by the gloves 10, so that it becomes possible to enhance the massaging effect.

[0036] Also, since it is possible to compress the vibrating motors 21 to the region being massaged thanks to the

gloves 10, the vibrations can be transmitted to not only the surface part of the body region being massaged but also deeply inside of the body without difficulty, enhancing the massaging effect.

[0037] Furthermore, thanks to the gloves 10, it is possible to place the vibrating motors 21 on body regions such as underneath clothes or on head hair and transmit vibrations without difficulty. Accordingly, it becomes possible to reflect the massaging effect into the regions which are conventionally considered to be difficult to get massaged without difficulty.

In addition, the gloves 10 can be worn not only by the user themselves but also by an assistant when it is used.

[0038] In addition to what has been described above, below is another possible method of using the device.

Figure 3 is an explanatory diagram which illustrates an example of how to use the massage device according to the first embodiment of the present invention. It illustrates a case that a user applies massage to their own face 40 by using the massage device. However, the massage can be applied not only to the face but also to other parts of the body.

[0039] Figure 3(b) shows a state when the user who wears the gloves 10 on hands as shown in Figure 3(a) put the palm sides of the gloves 10 onto the face 40, selecting vibration modes in series. In the state of Figure 3(b), the respective vibrating motors 21 lies almost along the line of lymph nodes from around eyes to in front of ears. As the circled numbers in Figure 3(c) indicate, the CPU 32 activates the respective vibrating motors 21 in the order of fingers, i.e. little fingers, annular fingers, middle fingers, forefingers, thumbs, little fingers, annular fingers, middle fingers, forefingers, thumbs (and repeat), to generate vibrations in a series by means of the motor driver 34 for the vibration duration time of Δt , based on a program of

a sequential mode which is remembered in the memory 33.

[0040] In this way, as the palms of the gloves 10 are opened and put over the face 40, they sequentially vibrate the vibrating motors 21 in the order from little fingers to thumbs i.e. from the lymph nodes around the eyes to the lymph nodes in front of the ears of face 40 along the flow of lymph, it becomes possible to circulate the lymph in the direction of the arrow P in Figure 3(c) without moving the hands or fingers, resulting in the capability of the highly effective lymphatic massage from a health or aesthetic standpoint.

[0041] The order, timing of the beginning, duration time or level of the vibrations of the respective vibrating motors 21 are not limited to the cases shown in Figure 3. For example, referring to Figure 3, it is possible to divide the fingers into two groups, one of which is a combination of fingers and annular fingers and the other is a combination of middle fingers, fore fingers and thumbs. A pattern that sequentially vibrates the vibrating motors 21 of the two groups is possible. That is to say, it can be flexibly utilized depending on the positional relation between the flow of lymph and the respective vibrating motors 21 or the intention and preference of the user, by changing the setting of the program of the memory 33 by means of the operation panel 31. Further, it is possible to sequentially vibrate the respective vibrating motors 21 along not only the flow of lymph but also other flows of bodily fluid such as blood.

However, it is needless to say that the respective vibrating motors 21 can be sequentially vibrated irrespective of flows of bodily fluid, allowing one to transmit vibrations with directionality on the body, resulting in the capability of applying massage therapy without need of moving hands or fingers.

[0042] Although the case that the vibrating motors 21 are

fixed to the balls of fingers of the gloves 10 has been described above, it is not necessary to place the vibrating motors 21 on the balls of fingers of the gloves 10.

As shown in Figure 4, a variety of arrangement is possible.

[0043] Figure 4 is a configuration diagram which illustrates a variation of vibrating motors arrangement.

In Figure 4(a) and (b), the vibrating motors (vibration generation means) placed on the palm side of fingers of the glove 10 are denoted by 22. Here, the vibrating motors 22 are placed not on the balls of fingers, but on regions between the balls of fingers and the bases of fingers. In addition, the vibrating motors (vibration generation means) placed on the palm of the glove 10 are denoted by 23, the vibrating motors (vibration generation means) placed on the fingertips of the glove 10 are denoted by 24, and the vibrating motors (vibration generation means) placed on the back-of-hand side of fingers of the glove 10 are denoted by 25.

[0044] As described above, it is possible to arrange the vibrating motors 21 to 23 on the palm of the glove 10, the vibrating motors 24 on the fingertips of the glove 10, and the vibrating motors 25 on the back-of-hand side of the glove 10, respectively. Accordingly, it becomes possible to use the palm, fingertips and back-of-hand side of the glove 10 while concurrently transmitting the vibrations of the vibrating motors 21 to 25, resulting in the capability of providing a variety of massage therapy. However, it is needless to say that the arrangement shown in Figure 4 is just an example. It is possible to arrange the vibrating motors 21 to 25 on other locations aside from the locations shown in Figure 4.

[0045] Although the embodiment with the vibrating motors 21 to 25 has been described above, it is possible to constitute the vibration generation means by utilizing voice coils or

magnetostrictive materials instead of the vibrating motors 21 to 25.

[0046] Furthermore, it is possible that the CPU 32 and the motor driver 34 control vibrations to be generated by the vibrating motors 21 to 25 such that the vibrational amplitudes are modulated by periodic functions such as sine wave, triangle wave, saw-tooth wave, square wave or the like. By periodically producing changes in the level of the vibrations of the vibrating motors 21 to 25, it becomes possible to produce a variety of vibrational patterns, resulting in a varied massage therapy.

[0047] It is not necessary to provide the gloves 10 for both hands. Either one for a right hand or a left hand of the gloves 10 is sufficient. In addition, it is not necessary to form the glove as a five-finger glove.

[0048] Moreover, a plurality of the vibrating motors 21 to 25 are not necessarily needed. With a single vibrating motor, it is essentially possible to conduct a massage therapy other than the sequential vibration mode shown in Figure 3. However, it is ideal to provide a plurality of the vibrating motors 21 to 25, so that the vibrations can be transmitted from a plurality of the vibrating motors 21 to 25, resulting in the enhancement of the massaging effect.

[0049] Furthermore, it is not necessary to provide the gloves 10 and the controller 30 as separate bodies. When the controller 30 is downsized, the glove 10 and the controller 30 can be constituted as a combined one, resulting in the enhancement of the massage device.

[0050] As described above, according to the first embodiment of the massage device of the present invention which massages a human body by transmitting vibrations, it is

possible to enhance the massaging effect. This enhancement can be achieved since the device comprises vibrating motors 21 to 25 which generate vibrations and a pair of gloves 10 which are worn on the hands that apply massage, each of which is equipped with at least one of the vibrating motors 21 to 25, allowing a user to knead or pinch a region being massaged without difficulty. In addition, due to the gloves 10 being worn on the hands, it becomes possible to compress the vibrating motors 21 to 25 on the body so that the vibrations can be transmitted to not only the surface part of the body region being massaged but also deeply inside of the body without difficulty, resulting in the enhancement of the massaging effect. Furthermore, due to the gloves 10 being worn on the hands, the vibrating motors 21 to 25 can be placed on body regions such as underneath clothes or on head hair without difficulty, making massage possible in body regions which are conventionally considered difficult to get massaged.

[0051] In addition, according to the first embodiment, as the gloves 10 are equipped with the vibrating motors 21 to 23 on the palm side of them, it becomes possible to use palms of the gloves 10 for applying massage while concurrently transmitting the vibrations generated by the vibrating motors 21 to 23, resulting in the capability of providing a variety of massage therapy.

[0052] Furthermore, according to the first embodiment, as the gloves 10 are equipped with the vibrating motors 24 on the fingertips side of them, it becomes possible to use fingertips of the gloves 10 for applying massage while concurrently transmitting the vibrations generated by the vibrating motors 24, resulting in the capability of providing a variety of massage therapy.

[0053] Furthermore, according to the first embodiment, as the gloves 10 are equipped with the vibrating motors 25 on the

back-of-hand side of them, it becomes possible to use back-of-hand of the gloves 10 for applying massage while concurrently transmitting the vibrations generated by the vibrating motors 25, resulting in the capability of providing a variety of massage therapy.

[0054] Furthermore, according to the first embodiment, as the gloves 10 are equipped with a plurality of the vibrating motors 21 to 25, it becomes possible to transmit vibrations from a plurality of the vibrating motors 21 to 25, further enhancing the massaging effect.

[0055] Furthermore, according to the first embodiment, as the CPU 32 and the motor driver 34 which control vibrations that are generated sequentially from a plurality of the vibrating motors 21 to 25, it becomes possible to transmit vibrations with directionality on the body, resulting in the capability of applying massage therapy without need of moving hands or fingers.

[0056] Furthermore, according to the first embodiment, as the CPU 32 and the motor driver 34 which periodically produce changes in the level of the vibrations generated from the vibrating motors 21 to 25, it becomes possible to produce a variety of vibrational patterns, resulting in the capability of providing a varied massage therapy.

[0057] Furthermore, according to the first embodiment, as the vibrating motors 21 to 25 are coin-shaped vibrating motors, it becomes possible to make the gloves 10 lighter and less bulky, resulting in a more practical embodiment of the massage device.

[0058] Although the vibrating motors are pointed out as the vibration generation means in the embodiment described above, the present invention is not restricted to this embodiment. An electrodynamic vibration generation equipment

wherein an iron sheet is drawn and repelled by applying alternate current to a coil, or a vibration generation equipment wherein a magnetostrictive material is transformed by applying alternate current to a coil, are also possible.

EXPLANATION OF SYMBOLS

[0059]

10 Glove (Glove means)

21~25 Vibrating motor (Vibration generation means)

30 Controller

31 Operation panel

32 CPU (Vibration control means)

33 Memory

34 Motor Driver (Vibration control means)

40 Face

CLAIMS

[Claim 1] A massage device which applies massage therapy by transmitting vibrations to a human body, comprising:

a vibration generation means which generate the vibrations, and

a glove means which are worn on hands that apply massage and each of which is equipped with at least one of the said vibration generation means.

[Claim 2] The massage device of claim 1, wherein the glove means are equipped with the vibration generation means on the palm side of them.

[Claim 3] The massage device of claim 1, wherein the glove means are equipped with the vibration generation means on the fingertips side of them.

[Claim 4] The massage device of claim 1, wherein the glove means are equipped with the vibration generation means on the back-of-hand side of them.

[Claim 5] The massage device of claim 1, wherein the glove means are equipped with a plurality of the vibration generation means.

[Claim 6] The massage device of claim 5, wherein a vibration control means which controls vibrations that are generated sequentially from a plurality of the said vibration generation means is further comprised.

[Claim 7] The massage device of claim 1, wherein the vibration control means which periodically produces changes in the level of the vibrations that are generated from the vibration generation means is further comprised.

[Claim 8] The massage device of claim 1, wherein the vibration generation means is a coin-shaped vibrating motor.