

**Systems and Methods For Using DNS Messages
To Selectively Collect Computer Forensic Data**

BACKGROUND

5 **[0001]** The invention relates to systems and methods for fighting malicious software, and in particular, to selectively collecting network traffic samples for forensic analysis.

[0002] Malicious software, also known as malware, affects a great number of computer systems worldwide. In its many forms such as computer viruses, Trojan horses, spyware, and ransomware, malware presents a serious risk to millions of computer users, making them
10 vulnerable to loss of data and sensitive information, to identity theft, and to loss of productivity, among others.

[0003] A great variety of devices informally referred to as the Internet of Things (IoT) are increasingly being connected to communication networks and the Internet. Such devices include, among others, smartphones, smartwatches, TVs and other multimedia devices, game
15 consoles, home appliances, and various home sensors such as thermostats. As more such devices go online, they become exposed to security threats like malware and intrusion. Therefore, there is an increasing need of securing such devices against malware, as well as of protecting communications to and from such devices. A particular area wherein interest has been renewed by the advent of the Internet of Things includes access control applications, for instance parental
20 control and preventing confidential information from being transmitted via IoT devices.

[0004] Malicious software is constantly evolving, challenging computer security providers to keep up with an ever-changing threat landscape. A part of this effort is directed at the timely discovery and analysis of emerging malware. One particular category of anti-malware methods, usually known as behavioral detection, relies on monitoring the activity of a device and/or
25 software component according to a set of rules. Some activity patterns (e.g., sequences of hardware or software events) correspond to normal, legitimate uses of the respective device, whereas others may indicate malice. Reliable identification of abnormal, malware-indicative

behavior patterns typically requires a sufficient amount of forensic data harvested from infected devices. In the case of detecting malware-indicative data traffic, learning such patterns may require having access to the network traffic to and/or from infected IoT devices. However, in the case of emerging yet-unknown threats, the offender devices are not easily identifiable.

5 [0005] There is therefore considerable interest in developing systems and methods of collecting forensic data from a variety of device types, and in particular, of selectively collecting network traffic to and/or from IoT devices.

SUMMARY

10 [0006] According to one aspect, a method comprises employing at least one hardware processor of a computer system to intercept a domain name service (DNS) reply message received at the computer system, the DNS reply message comprising a target internet protocol (IP) address indicating a network location of a remote resource, the DNS reply message further comprising a service activation flag. The method further comprises employing at least one hardware processor of the computer system to determine according to a value of the service activation flag whether a
15 security service is active, and in response, if the service activation flag indicates that the security service is active, to modify the DNS reply message by replacing the target IP address with a dummy IP address. The method further comprises employing at least one hardware processor of the computer system to intercept an electronic communication directed towards a destination IP address, to determine whether the destination IP address matches the dummy IP
20 address, and in response to determining whether the destination IP address matches the dummy IP address, if the destination IP address matches the dummy IP address, to perform a computer security procedure according to the electronic communication. The method further comprises employing at least one hardware processor of the computer system, in response to determining whether the destination IP address matches the dummy IP address, if the destination IP address
25 does not match the dummy IP address, to forward the electronic communication to the destination IP address.

[0007] According to another aspect, a computer system comprises at least one hardware processor configured to execute a domain name service (DNS) proxy and a communication manager. The DNS proxy is configured to intercept a domain name service (DNS) reply message received at the computer system, the DNS reply message comprising a target internet protocol (IP) address indicating a network location of a remote resource, the DNS reply message further comprising a service activation flag. The DNS proxy is further configured to determine according to a value of the service activation flag whether a security service is active, and in response, if the service activation flag indicates that the security service is active, to modify the DNS reply message by replacing the target IP address with a dummy IP address. The communication manager is configured to intercept an electronic communication directed towards a destination IP address, to determine whether the destination IP address matches the dummy IP address, and in response, if the destination IP address matches the dummy IP address, to perform a computer security procedure according to the electronic communication. The communication manager is further configured, in response to determining whether the destination IP address matches the dummy IP address, if the destination IP address does not match the dummy IP address, to forward the electronic communication to the destination IP address.

[0008] According to another aspect, a non-transitory computer-readable medium stores instructions which, when executed by at least one hardware processor of a computer system, cause the computer system to form a domain name service (DNS) proxy and a communication manager. The DNS proxy is configured to intercept a domain name service (DNS) reply message received at the computer system, the DNS reply message comprising a target internet protocol (IP) address indicating a network location of a remote resource, the DNS reply message further comprising a service activation flag. The DNS proxy is further configured to determine according to a value of the service activation flag whether a security service is active, and in response, if the service activation flag indicates that the security service is active, to modify the DNS reply message by replacing the target IP address with a dummy IP address. The communication manager is configured to intercept an electronic communication directed towards a destination IP address, to determine whether the destination IP address matches the dummy IP address, and in response, if the destination IP address matches the dummy IP address, to perform

a computer security procedure according to the electronic communication. The communication manager is further configured, in response to determining whether the destination IP address matches the dummy IP address, if the destination IP address does not match the dummy IP address, to forward the electronic communication to the destination IP address.

5 **[0009]** According to another aspect, a server computer system engages in domain name service (DNS) transactions with a plurality of client systems, the server computer system comprising at least one hardware processor configured, in response to receiving a DNS query message from a client system of the plurality of client systems, the DNS query message comprising a target domain name, to identify the client system according to the DNS query message. The at least
10 one hardware processor is further configured, in response to identifying the client system, to determine whether a client selection condition is satisfied according to the domain name and further according to an identity of the client system. The at least one hardware processor is further configured, in response to determining whether the client selection condition is satisfied, if the client selection condition is satisfied, to transmit a DNS reply message to the client system,
15 the DNS reply message comprising a target Internet Protocol (IP) address associated with the target domain name, the DNS reply message further configured to include a service activation flag. The at least one hardware processor is further configured, in response to determining whether the client selection condition is satisfied, if the client selection condition is not satisfied, to transmit another DNS reply message to the client system, the other DNS reply message
20 comprising the target IP address and further configured to not include the service activation flag. The client system is configured to interpret receiving the service activation flag as a trigger for performing a computer security procedure according to an electronic communication directed to or incoming from the target IP address.

BRIEF DESCRIPTION OF THE DRAWINGS

25 **[0010]** The foregoing aspects and advantages of the present invention will become better understood upon reading the following detailed description and upon reference to the drawings where:

[0011] Fig. 1 shows an exemplary set of client devices protected against computer security threats according to some embodiments of the present invention.

[0012] Fig. 2-A shows a typical domain name service (DNS) transaction, as known in the prior art.

5 [0013] Fig. 2-B illustrates a modified DNS transaction according to some embodiments of the present invention.

[0014] Fig. 3 shows an exemplary tagged DNS query according to some embodiments of the present invention.

10 [0015] Fig. 4 shows an exemplary flagged DNS reply according to some embodiments of the present invention.

[0016] Fig. 5-A shows an exemplary embodiment wherein a client device transmits forensic data to a security server, the forensic data comprising a digest of a network traffic between the client device and a content server.

15 [0017] Fig. 5-B shows an alternative embodiment wherein at least a part of the network traffic between the client device and content server is re-routed via the security server.

[0018] Fig. 6 illustrates exemplary software executing on a client device according to some embodiments of the present invention.

[0019] Fig. 7 shows an exemplary sequence of steps performed by a DNS proxy executing on the client device, according to some embodiments of the present invention.

20 [0020] Fig. 8 shows an exemplary sequence of steps performed by a communication manager to process outbound communications, the communication manager executing on the client system according to some embodiments of the present invention.

[0021] Fig. 9 shows an exemplary sequence of steps carried out by the communication manager to process inbound communications according to some embodiments of the present invention.

[0022] Fig. 10 shows an exemplary sequence of steps performed by the DNS server according to some embodiments of the present invention.

5 [0023] Fig. 11 illustrates an exemplary hardware configuration of a computer system programmable to carry out methods and algorithms according to some embodiments of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

10 [0024] In the following description, it is understood that all recited connections between structures can be direct operative connections or indirect operative connections through intermediary structures. A set of elements includes one or more elements. Any recitation of an element is understood to refer to at least one element. A plurality of elements includes at least two elements. Unless otherwise required, any described method steps need not be necessarily performed in a particular illustrated order. A first element (e.g. data) derived from a second
15 element encompasses a first element equal to the second element, as well as a first element generated by processing the second element and optionally other data. Making a determination or decision according to a parameter encompasses making the determination or decision according to the parameter and optionally according to other data. Unless otherwise specified, an indicator of some quantity/data may be the quantity/data itself, or an indicator different from
20 the quantity/data itself. A computer program is a sequence of processor instructions carrying out a task. Computer programs described in some embodiments of the present invention may be stand-alone software entities or sub-entities (e.g., subroutines, libraries) of other computer programs. A domain name is a label/alias identifying a network address. The term 'database' is used herein to denote any organized collection of data. Computer readable media encompass
25 non-transitory media such as magnetic, optic, and semiconductor storage media (e.g. hard drives, optical disks, flash memory, DRAM), as well as communication links such as conductive cables and fiber optic links. According to some embodiments, the present invention provides, *inter*

alia, computer systems comprising hardware (e.g. one or more processors) programmed to perform the methods described herein, as well as computer-readable media encoding instructions to perform the methods described herein.

[0025] The following description illustrates embodiments of the invention by way of example and not necessarily by way of limitation.

[0026] Fig. 1 shows an exemplary set of client devices **10a-f** protected from computer security threats according to some embodiments of the present invention. Exemplary client systems **10a-f** include personal computer systems, corporate mainframe computers, mobile computing platforms (e.g., laptop computers, tablets, mobile telephones), entertainment devices (e.g., TVs, game consoles), wearable devices (e.g., smartwatches, fitness bands), household appliances (e.g., refrigerators, washing machines), and any other electronic device comprising a processor, a memory, and a communication interface enabling the respective device to communicate with other devices/computer systems. An exemplary client device may interact with a remote content server **18** over a communication link, to exchange data such as web content, electronic messages, various documents, etc.

[0027] In the exemplary configuration of Fig. 1, client devices **10a-e** are interconnected by a local network **13**, such as a local area network (LAN), home network, corporate network, etc. Devices **10a-e** may further be connected to an extended network **15**, such as a wide area network (WAN) and/or the Internet. In some embodiments, at least a part of network traffic between client devices **10a-e** and extended network **15** traverses a gateway **12** such as a router or network hub. Another exemplary client device **10f** may not be connected to local network **13**, but instead connect to extended network **15**, for instance by way of a mobile telephony network or a public WiFi hotspot.

[0028] In some embodiments, a domain name service (DNS) server **14** collaborates with a security server **16** to selectively harvest computer forensic data from client devices **10a-f**, as shown in detail below. Such forensic data may include, for instance, metadata describing a data transmission between a selected client and a selected content server, and/or an actual payload of

the respective data transmission. Metadata herein denote features of a transmission other than the transmission content or payload itself. Exemplary metadata includes, among others, network addresses of the sender and/or receiver, a size of the payload, and a timestamp indicating a real time of the respective transmission. The term 'forensic' is used herein to indicate that the
5 respective data may be used for computer security purposes, for instance to determine whether the respective client system is infected with malicious software, or to prospectively identify network traffic patterns characterizing yet-unknown computer security threats. Each of servers **14-16** generically represents a set of communicatively-coupled computers, which may or may not be in physical proximity to each other. A skilled artisan will know that actions
10 performed by servers **14-16** as described herein may be divided among multiple physical machines or processors.

[0029] Servers **14-16** are connected to a client profile database **19** and configured to access database **19** to carry out selective data insertion, data retrieval, and/or other database management operations. Database **19** is configured to store a plurality of client records related to
15 client devices **10a-f** and/or to the users of the respective client devices. In some embodiment, each client record corresponds to a distinct client device **10a-f**. In one such example, a client record may store a set of identifiers of the respective client device (e.g. media access control - MAC address, International Mobile Equipment Identity - IMEI number, etc.), an indicator of a device type (e.g., digital camera, thermostat, smartphone, tablet computer, router, car), various
20 hardware configuration indicators of the respective client device (e.g., whether the respective device has a camera, etc.), a list of software applications installed on the respective device, and an indicator of a geographical location of the respective client device. Other information stored in an exemplary client record comprises device usage data, such as statistics of network access by the respective client device, for instance the relative frequency of using various
25 communication ports, relative traffic volume during various time intervals, etc. Other exemplary client records may include metadata describing network traffic transmitted or received by the respective client device. In some embodiments, such metadata may be organized according to a format such as IP Flow Information Export (IPFIX) from the Internet Engineering Task Force, or NetFlow(R) from Cisco, Inc. Database **19** may be formatted and stored according to any

standard known in the art. Exemplary database formats include a relational database, an extensible markup language (XML) database, a spreadsheet, and a key-value store, among others.

[0030] In some embodiments, DNS server **14** provides domain name services to client devices **10a-f**, the respective services comprising, *inter alia*, translating domain names into network addresses and/or *vice versa*. A typical data transmission between a client device and a remote content server comprises several steps. Such transmission requires knowledge of a network address (e.g., Internet Protocol - IP address) of the content server. Often, this address is not known to the client, for various reasons. For instance, there may be multiple mirror content server machines, and the client may be dynamically directed to the most convenient one according to the current load of each mirror server or according to the current geographical location of the client device. The client device may however know a domain name comprising an alias of the unknown network address. To establish a connection to the remote content server, a software entity executing on the respective client device may thus issue a request to access the respective domain name, instead of the IP address *per se*. In response, another software entity (e.g., the operating system) of the client device may attempt to translate the alias/domain name to an actual network address, and subsequently transmit the request to the correct network location. Such translation may invoke a DNS provider such as server **14** in Fig. 1. Fig. 2-A illustrates a typical exchange of messages according to a DNS protocol as known in the art. A client device **10** transmits a DNS query **22** to DNS server **14**, query **22** comprising an encoding of a domain name. In response, DNS server **14** may return a DNS reply **24** to the requesting client, reply **24** including an encoding of a network address identified by the respective domain name/alias. Exemplary address encodings include IPv4 and IPv6 formats, among others.

[0031] Fig. 2-B shows an exemplary DNS exchange between client device **10** and DNS server **14** according to some embodiments of the present invention. In contrast to a conventional DNS exchange (Fig. 2-A), in some embodiments client device **10** may transmit a tagged DNS query **26** to DNS server **14**, the tagged query comprising an identifier of the respective client device **10**. An exemplary tagged query **26** is illustrated in Fig. 3 and includes an encoding of a

domain name **21** and a client ID **25**. Client ID **25** may comprise any item that enables distinguishing client device **10** from other client devices. Exemplary client ID's include a hash, a MAC address, an IMEI number, etc. In some embodiments, client ID **25** may not allow individually identifying client device **10**, but is nevertheless indicative of a group identity of the
5 respective client device. For instance, client ID **25** may selectively indicate a device group (e.g., devices within a certain department of a corporation, devices located within a certain network sub-domain, devices belonging to a certain home network, devices protected under a certain service contract), a device type (e.g., smartphones vs. desktop PCs vs. embedded), etc.

[0032] In an alternative embodiment, client ID **25** may comprise a digest of a client device
10 profile. Exemplary device profile information may include, for instance, encodings of a device type, operating system, current geographical location, and an identifier of a current user of the respective client device. Such information may be used by DNS server **14** and/or security server **16** to select the respective client device for activation/de-activation of security services, as shown in more detail below.

[0033] In response to receiving tagged DNS query **26**, some embodiments of DNS server **14**
15 return a flagged DNS reply **28**, an example of which is shown in Fig. 4. Flagged DNS reply **28** includes an encoding of a network address **23** and a service activation flag **27** indicating whether a specific security service is active for the respective requesting client device **10**. Exemplary security services selectively activated/de-activated by flag **27** include forensic data collection,
20 parental control (e.g., limiting access of certain users to certain domains), application control (e.g., prohibiting certain applications from running, for instance Facebook(R), instant messaging, gaming, etc.), anti-fraud, anti-malware, traffic introspection, etc.

[0034] In an alternative embodiment, flagged DNS reply **28** may include a plurality of service
25 activation flags, for instance a bitmap wherein each bit represents a distinct security service (e.g., parental control, traffic introspection, forensic data collection, etc.) and the value of the respective bit indicates whether the respective service is turned on or off. In another example, flagged DNS reply **28** may include a set of service parameter values along with or instead of a

simple service activation flag. In yet another example, distinct values of service activation flag **27** may indicate distinct modes of operation of the target client device. For instance, one value may instruct the client device to drop the respective traffic (e.g., interpret DNS reply **28** as a NXDomain reply), while another value may instruct the client device to force a timeout, or to redirect traffic to another IP address.

[0035] Data items like the client ID **25** and service activation flag **27** ID may be encoded and included in client queries and/or server reply messages using any method known in the art. Many current protocols/data formats used in electronic communication reserve a set of selected bits of each data packet for nonspecific use. Various embodiments may use such reserved bits to encode client ID **25** and/or service activation flag **27**. In a simplest example, a selected bit of the respective message may act as service activation flag; a value of 1 may indicate that service is on, while a value of 0 may indicate that the service is off or that the respective message is not flagged. Some embodiments use DNS messages formatted according to a standard currently in use, such as the one described in the Internet Engineering Task Force (IETF) Request for Comments (RFC) 1035, among others. In one such example, client ID **25** and/or service activation flag **27** may be inserted as an additional resource record or pseudo-resource record of a DNS query or reply, e.g., as contents of a RDATA field.

[0036] In some embodiments, DNS server **14** may selectively activate/de-activate a security service by appropriately setting a value of service activating flag **27** only for certain client devices and/or users. The decision whether to turn a certain service on or off may be taken by security server **16** according to the identity of the client device issuing the respective tagged DNS query, and further according to criteria such as a current geographical location of the client device, a device type, a hardware and/or software profile of the respective client device. Examples of decision algorithms and criteria will be shown below. To enable such decision algorithms, some embodiments collect device profile information from client devices and transmit such profile information to security server **16**, which may organize and store it in client profile database **19** (see Fig. **2-B**).

[0037] Some embodiments use service activation flag **27** to selectively collect forensic data, as shown in more detail below. In response to selecting a client device as a target for data collection, DNS server **14** may respond to a DNS query received from the respective client device with a flagged DNS reply wherein service activation flag **27** is set to indicate that data collection is on. In response to receiving the respective flagged DNS reply, a security application executing on the selected client device may collect forensic information from the selected device and transmit the respective information to security server **16** for analysis. Forensic data collection may proceed according several scenarios. In one example illustrated in Fig. **5-A**, security software executing on client device **10** may determine metadata and/or an actual payload of a communication between client device **10** and content server **18**, package such information as forensic data **30**, and add it to an outbound message queue for transmission to security server **16**. In another example illustrated in Fig. **5-B**, in response to receiving a flagged DNS reply indicating that data collection is active, security software executing on the respective client device may re-route at least a part of data traffic between client device **10** and content server **18** via a communication tunnel connecting client device **10** to security server **16**. An example of such a tunnel is a virtual private network (VPN) connection. Stated otherwise, in Fig. **5-B**, forensic data collection comprises routing live communications to and/or from the selected client device via security server **16**, where the respective traffic may be analyzed.

[0038] Fig. **6** shows exemplary software components executing on a client device according to some embodiments of the present invention. Such software may include an operating system (OS) **50**, which may be any widely available operating system such as Microsoft Windows®, MacOS®, Linux®, iOS®, or Android®, among others. OS **50** provides an interface between the hardware of client device **10** and a set of applications including a client application **52** and a security application **54**. Client application **52** generically represents any computer program such as a word processing application, spreadsheet application, image processing, gaming, electronic communication, web browsing, and social media application, among others. Security application **54** provides computer security services to client device **10**, for instance anti-malware, intrusion detection, and network access control.

[0039] In some embodiments, security application comprises a DNS proxy **56**, a profile builder **57**, and a communication manager **58**. Components **56-57-58** may execute as stand-alone executable entities, or may be incorporated into security application **54** for instance as dynamically loaded libraries. A skilled artisan will understand that some of the functionality of components **56-57-58** may be implemented on network gateway **12** (see Fig. **1**), instead of client system **10**.

[0040] In some embodiments, DNS proxy **56** is configured as an intermediary between client device **10** and DNS server **14**, in the sense that DNS proxy **54** intercepts and modifies the flow and/or content of DNS messages going into and/or out of client device **10**. Some embodiments configure OS **50** to selectively route outbound traffic to certain IP addresses via DNS proxy **56**. Such functionality may be implemented for instance using a split-tunnel VPN. In one such example, security application **54** will register the IP address(es) of DNS server **14** with OS **50**, thus declaring server **14** as the provider of DNS for the respective client system. Application **54** may further configure a VPN interface of client system **10** so that all traffic to the respective IP addresses will traverse DNS proxy **56**.

[0041] Fig. **7** shows an exemplary sequence of steps performed by DNS proxy **56** according to some embodiments of the present invention. The exemplary algorithm described herein enables a selective processing of network access requests, wherein selection is achieved with the granularity of a single DNS request.

[0042] A sequence of steps **202-204** intercepts in- and outbound DNS messages. In a step **206**, DNS proxy determines a type of the intercepted message. When the message is a DNS query (e.g., a request by client application **52** to access a certain domain name), in a sequence of steps **208-210**, DNS proxy **56** tags the respective DNS query with a client ID of the respective client device to produce tagged DNS query **26**, and transmits query **26** to DNS server **14**.

[0043] When the intercepted DNS message is a reply, a step **220** parses the message to determine whether it is flagged or not, i.e., whether it contains a service activation flag, and whether the value of the flag indicates that a security service is active for the respective client

device **10**. When no, a step **222** forwards the respective DNS reply to the requesting software entity (e.g., client application **52** or OS **50**).

[0044] In some embodiments, security application **54** maintains a pool of pre-determined dummy network addresses reserved for security purposes. Dummy addresses are herein used as substitutes for actual network addresses returned by DNS providers. A dummy address may or may not indicate a location of an actual online resource. Security application **54** maintains an address association table (e.g., a hash table) comprising a mapping between real and dummy addresses, as shown below. In some embodiments, security application **54** further registers dummy IP addresses with a VPN interface of client system **10**, so that all traffic to and/or from such dummy addresses will traverse security application **54**. This allows communication manager **58** to perform security operations on such traffic, for instance to redirect or introspect such traffic as further detailed below. Distinct dummy addresses may be used for distinct services, such as parental control, traffic sampling, access control, etc.

[0045] When the intercepted DNS message is a flagged reply wherein the value of the flag indicates that security services are active, in a step **224** an available dummy address is selected from the pool. Some embodiments select the dummy address further according to a value of service activation flag **27**, for instance when different values indicate activation of different services. Next, DNS proxy **56** may create an association between the respective dummy address and the actual network address contained in the DNS reply (e.g., a hash table entry mapping the dummy address to the real address or *vice versa*). A further step **228** may edit the flagged DNS reply to replace the actual network address with the selected dummy address. In step **228**, some embodiments further remove the service activation flag from the respective DNS message to make it look like a standard DNS reply. Such obfuscation strategies may help hide the actions of security software from potential malware executing on client device **10**. A further step **230** transmits the modified DNS reply to the requesting software entity (e.g., client application **52** or OS **50**).

[0046] In some embodiments, communication manager **58** intercepts and processes at least a part of the electronic communications between client device **10** and content server **18**. As shown above, some embodiments configure security application **54** to intercept communications coming from and/or going out to a pre-determined set of IP addresses. Fig. **8** shows an exemplary sequence of steps performed by communication manager **58** to process outgoing communications, for instance hypertext transfer protocol (HTTP) requests to content server **18**. When such a communication is detected (steps **242-244**), a step **246** determines whether the destination IP address of the respective communication matches any of the list of dummy IP addresses maintained by security application **54**. If no, communication manager **58** may forward the communication to a communication interface of client system **10** for transmission to its intended recipient.

[0047] If yes, indicating that the respective communication was selected for security processing, a step **248** performs some security actions according to the respective communication. Exemplary security actions include determining a set of metadata comprising, for instance, a real destination IP address associated with the respective dummy address, a communication port, a payload size, and a timestamp of the communication. Another security action may comprise making a copy of a payload of the respective communication. Yet another exemplary security action comprises inspecting a payload of the communication to determine whether the respective payload is encrypted or not, or whether the respective payload comprises a specific type of data (e.g., an image, executable code, etc.). In yet another example, step **248** comprises scanning a payload of the respective communication for malicious code. In some embodiments, step **248** further comprises placing the information extracted about/from the respective communication into a log or a queue for off-line transmission to security server **16**. Some embodiments determine a type of security action according to the dummy address. For instance, some dummy addresses may indicate a parental control action, while another dummy address may indicate malware scanning.

[0048] In a further step **252**, communication manager **58** may look up the address association table to determine a real IP address corresponding to the dummy address indicated by the

respective communication, and edit the respective communication to replace the dummy address with the real IP address. In some embodiments, step **252** may further re-package the original communication to re-route it via a virtual private network tunnel to security server **16** (see fig. **5-B**). A step **254** may then forward the communication to the communication interface of client device **10**.

[0049] Fig. **9** shows an exemplary sequence of steps performed by communication manager **58** while processing incoming communications. When such a communication is received (steps **262-264**), a step **266** may look up the address association table to determine whether the origin IP address of the communication matches a dummy address. If no, communication manager **58** may forward the incoming communication to its intended recipient (e.g., application **52**).

[0050] If yes, indicating that the respective communication is selected for security processing, a step **268** performs a set of security actions according to the incoming communication. Exemplary security actions include determining a set of communication metadata (e.g., origin IP address, payload size, timestamp, etc.), copying a payload of the respective communication, inspecting the payload to determine a set of features (e.g., whether the respective payload is encrypted, whether it contains executable code, etc.), and scanning the respective payload for malware, among others. Some embodiments may further transmit such information to security server **16**.

[0051] In a step **272**, communication manager **58** may then edit the incoming communication to replace the origin IP address with the associated dummy IP address. A further step **274** may then forward the edited communication to its intended recipient (e.g., client application **52**).

[0052] In some embodiments, profile builder **57** (Fig. **6**) is configured to determine various features of the hardware and/or software configuration of client device **10**, and to transmit such data in the shape of a profile indicator **29** to security server **16** (Fig. **2-B**). Exemplary hardware features may include, for instance, a device type of the respective client device (e.g., smartphone, PC, tablet computer, thermostat), an identification feature (e.g., a MAC address, IMEI, etc.),

hardware specifications of various components (e.g., manufacturer, model), an indicator of whether the respective client device **10** has a particular hardware component (e.g., camera, microphone, fingerprint reader, global positioning system - GPS sensor, etc.). Other exemplary hardware features include an amount of a resource currently being used (e.g., CPU throttle, RAM and disk usage, active screen time). Exemplary software features comprise, among others, a type and version of OS **50**, a list of currently installed software applications, and statistical data indicative of how much each application is being used on the respective device. Profile indicator **29** may further include an indicator of a current geographical location of the client device (e.g., country, geolocation coordinates, etc.). In response to receiving profile indicator **29**, security server **16** may store such information in client profile database **19**. In some embodiments, client profile information is used to select a client device from a plurality of client devices for security services such as forensic data harvesting as described below. For instance, such profile information may provide clues about which devices may be infected with malicious software.

[0053] Fig. **10** shows an exemplary sequence of steps performed by DNS server **14** according to some embodiments of the present invention. A sequence of steps **282-284** listens for DNS queries. In some embodiments, such queries are tagged with a client identifier (see description above in relation to Fig. **7**). When a query is received, a step **286** identifies the client device where the respective query originated according to client ID **25** (see e.g., Fig. **3**). In a further step **288**, DNS server **14** may look up a client profile of the respective client device in profile database **19**.

[0054] A step **290** may further determine whether a service activation condition is satisfied for the current DNS query and the respective client device. Stated otherwise, in step **290** server **14** may selectively activate a security service for some clients and/or some domain names. Client selection may proceed according to client profile data retrieved from database **19**. In an alternative embodiment wherein DNS proxy **56** sends client profile data encoded in tagged DNS query **26**, server **14** may select the respective client device according to such data. In yet another

embodiment, steps **288-290** are performed by security server **16**, which then transmits a list of selected client devices to DNS server **14**.

[0055] In an exemplary forensic data harvesting embodiment, DNS server **14** may select clients matching a specific device type (e.g., smartphones), clients from a specific region or country (e.g., Germany), clients running a particular operating system and/or version (e.g., Android, iOS 10), etc. Another exemplary client selection criterion comprises whether the respective client device is running a specific application, for instance unknown or suspect software. In one such example, HTTP requests to access IP addresses associated with specific domain names and received from devices running a specific monitored application will be copied or diverted via VPN to security server **16**.

[0056] Other client selection criteria may include a count of client devices and/or DNS queries. For instance, DNS server **14** may select a pre-determined number of client devices during each time interval (e.g., no more than 100 distinct clients per second), or a pre-determined number of DNS queries (e.g., no more than 50 distinct DNS queries from the same client). In an embodiment as depicted in Fig. **5-B**, wherein the client device may selectively re-route certain communications to security server **16** via a VPN tunnel according to a value of the service activation flag, another exemplary selection criterion includes a current load of the VPN service running on security server **16**. In an exemplary parental control embodiment, another selection criterion may include the current user of the respective client device (e.g., activate parental control rules selectively, only while children are using the device). Individual selection criteria may be combined into complex criteria involving multiple conditions (e.g., 100 DNS requests received from distinct smartphones in Belgium and The Netherlands).

[0057] If a selection condition is satisfied for the client device that issued the current DNS query, a step **294** may formulate a flagged DNS reply by setting service activation flag **27** to indicate that a security service is active (see e.g., Fig. **4**). In some embodiments, setting flag **27** to active effectively selects the respective client device for a specific security service such as forensic data

collection, parental control, etc. Such selection is herein activated per DNS query, and can be turned off for subsequent queries received from the same client device.

[0058] When the selection conditions is not satisfied for the respective client device and current DNS query, a step **296** may formulate a flagged DNS reply by setting activation flag **27** to indicate that the security service is inactive. In an alternative embodiment, step **296** may formulate a standard DNS reply lacking service activation flag **27** altogether. A further step **298** may transmit the DNS reply formulated in either step **294** or **296** to the requesting client device.

[0059] The description above shows exemplary computer programs performing various methods according to some embodiments of the present invention. Such computer programs are typically executed by a multi-purpose hardware processor, but a skilled artisan will understand that the methods and algorithms disclosed herein may be implemented using dedicated hardware components, such as an application-specific integrated circuit (ASIC) or field-programmable gate array (FPGA). Fig. **11** illustrates an exemplary hardware configuration of a computer system programmable to carry out methods and algorithms described herein. Fig. **11** shows a generic computer system, which may represent, for instance, any of client devices **10a-f**, DNS server **14**, and security server **16**, among others. A skilled artisan will understand that the hardware configuration of some client systems (e.g., mobile telephones, smartwatches) may differ somewhat from the one illustrated in Fig. **11**.

[0060] The illustrated computer system comprises a set of physical devices, including a hardware processor **32** and a memory unit **34**. Processor **32** comprises a physical device (e.g. a microprocessor, a multi-core integrated circuit formed on a semiconductor substrate, etc.) configured to execute computational and/or logical operations with a set of signals and/or data. In some embodiments, such operations are delivered to processor **32** in the form of a sequence of processor instructions (e.g. machine code or other type of encoding). Memory unit **34** may comprise volatile computer-readable media (e.g. DRAM, SRAM) storing instructions and/or data accessed or generated by processor **32**.

[0061] Input devices **36** may include computer keyboards, mice, and microphones, among others, including the respective hardware interfaces and/or adapters allowing a user to introduce data and/or instructions into the respective computer system. Output devices **38** may include display devices such as monitors and speakers among others, as well as hardware interfaces/adapters such as graphic cards, allowing the illustrated computer system to communicate data to a user. In some embodiments, input devices **36** and output devices **38** share a common piece of hardware, as in the case of touch-screen devices. Storage devices **42** include computer-readable media enabling the non-volatile storage, reading, and writing of software instructions and/or data. Exemplary storage devices **42** include magnetic and optical disks and flash memory devices, as well as removable media such as CD and/or DVD disks and drives. The set of network adapters **44**, together with associated communication interface(s), enables the illustrated computer system to connect to a computer network and/or to other devices/computer systems. Controller hub **40** represents the plurality of system, peripheral, and/or chipset buses, and/or all other circuitry enabling the communication between processor **32** and devices **34**, **36**, **38**, **42**, and **44**. For instance, controller hub **40** may include a memory controller, an input/output (I/O) controller, and an interrupt controller, among others. In another example, controller hub **40** may comprise a northbridge connecting processor **32** to memory **34**, and/or a southbridge connecting processor **32** to devices **36**, **38**, **42**, and **44**.

[0062] The exemplary systems and methods described above allow selectively performing computer security operations on heterogeneous clients such as personal computers and smartphones, as well as Internet of Things (IoT) devices like TVs, thermostats, refrigerators, and wearables, among others. Selectivity herein denotes the capability of precisely targeting a device from among a multitude of client devices and performing some security procedure on the respective device, as opposed to indiscriminately carrying out the respective security procedure on multiple client devices. In some embodiments, selection of target devices is centralized on a remote server computer system communicatively coupled to the multitude of client devices.

[0063] In some embodiments, a security application executes on each client device and comprises a domain name service (DNS) proxy that intercepts and processes DNS messages

exchanged between the respective client device and a remote DNS server. For clarity and simplicity, the disclosure above used the term 'domain name service' to denote a conventional DNS as currently used in Internet communications. However, a skilled artisan will understand that the methods and systems described herein may be easily adapted to any other format and protocol for mapping a domain name to a network address or *vice versa*.

[0064] In some embodiments, the DNS proxy component tags outgoing DNS queries addressed to the DNS server with an identifier of the respective client device. In response, the DNS server may respond with a flagged DNS reply comprising a service activation flag. In some embodiments, the DNS server selects a particular client device for a security procedure by setting the service activation flag to a pre-determined value when issuing a DNS reply to the respective client. In turn, the security application executing on the client may interpret some values of the service activation flag as a trigger for executing the respective security procedure. Distinct values of the flag may trigger distinct security procedures. In an alternative embodiment, the presence of a service activation flag in a DNS reply may trigger the security procedures, while the absence of such a flag may indicate to the security application not to carry out the respective procedures.

[0065] In view of the above, the exemplary systems and methods described above achieve a client selectivity at the level of individual DNS messages. Stated otherwise, security procedures may be turned on/off by any individual DNS exchange between the respective client device and the DNS server. In some conventional computer security applications, clients are selected for certain procedures according to individual client subscription options, or according to software configuration parameters. For instance, some clients may sign up for parental control, while others may not. Similarly, security software may divert via a VPN tunnel the traffic of some clients, but not others. However, such client selectivity is typically pre-determined and does not change in time, e.g., all access requests coming from a specific client are typically treated according to the same rule/procedure. In contrast to such conventional systems, some embodiments allow a more flexible client selection, done on a per-DNS message basis. This allows, for instance, to select a client for a specific procedure according to a schedule, according

to a current server load, according to a domain name that the client is attempting to access, according to a current geographical location of the client (e.g. geofencing), etc.

[0066] Exemplary security procedures selectively activated according to some embodiments of the present invention include, among others, selectively harvesting forensic information from clients, selectively routing traffic via a security server, parental control (e.g., selectively monitoring and/or restricting access of certain clients/users to certain online content), application or access control (e.g., selectively monitoring and/or restricting a client's use of selected applications and/or communication protocols such as Facebook(R) and online messaging).

[0067] An important class of applications enabled or facilitated by some embodiments of the present invention rely on a selective harvesting of computer forensic data from clients. Such harvesting may be useful, for instance, for a timely discovery of emerging computer security threats such as malware. New malicious software appears all the time, and in the absence of information about its behavior, such software may bypass conventional security measures and spread rapidly. IoT devices are particularly vulnerable to such infections. It is therefore important to gather as much information as possible about emerging infections, and ideally to selectively gather such information from devices that are already infected. Some malware selectively infects a particular type of devices (e.g., mobile phones) and/or devices running a particular type of operating system (e.g., Android®). Some embodiments enable such selective targeting of clients, and therefore an efficient gathering of information for security purposes. In one such example, the DNS server may select a client device that fits the profile of a likely target for particular malware (e.g., a smartphone from a particular country). In response, security software executing on the selected client device may take a snapshot of data traffic going into/out of the respective client device. By enabling a per-DNS message selective activation of data harvesting, some embodiments allow gathering data traffic going out to or coming in from a specific Internet domain or network address of interest (e.g., a suspected command-and-control server).

[0068] An alternative embodiment of data harvesting may redirect to a security server a communication between a selected client device and a suspect Internet domain or network address. Such redirection may be enabled using a VPN tunnel, for instance. The security server may then introspect the redirected traffic for signs of malice. Re-routing and introspecting network traffic are known in the art of computer security. However, typical configurations re-route all traffic of a selected client, thus ensuring its permanent protection from online threats. Such massive re-routing network of traffic from thousands of protected clients to a handful of VPN servers is relatively expensive in terms of equipment costs and computation load and may negatively affect user experience on the client side. In contrast to such conventional systems, in some embodiments of the present invention, traffic of each client device may be selectively re-routed via VPN. For instance, in a data harvesting embodiment, only traffic to/from certain domains considered of interest may be re-directed to the VPN servers. In addition, the systems and methods described herein allow randomly sampling network traffic from a plurality of client devices that fit a specific profile (e.g., smartphones and tablet computers running iOS(R)). Such random sampling may ensure that no particular client device is disproportionately affected by data harvesting procedures, the overall impact on user experience being substantially lower than in conventional systems.

[0069] Some embodiments may use a flagged DNS reply as a trigger for gathering other forensic data. In one such example, in response to a flagged DNS reply, security software may determine parameters of a current state of the respective client device (for instance, getting the current value of various OS variables and/or registry keys, taking a snapshot of a specific section of memory, etc.). Such data may be transmitted to the security server and used in forensic investigations alongside network traffic data.

[0070] An exemplary use case scenario of the systems and methods described herein comprises pro-actively detecting spyware. An outbreak of new malware affecting devices running the Android® operating system was detected in Western Europe. The malicious code is delivered via the Google Play® Store, packaged as a genuine-looking photo organizer tool. However, a

hidden intent of the application is to collect personal user data and submit it to a server. This technically qualifies as spyware.

Stage I - triggering a suspicion of malice

5 [0071] Client devices protected according to some embodiments of the present invention submit various DNS queries and client profile information to DNS server **14** and/or security server **16** (see Fig. **2-B**). Client profile indicator **29** may include a list of application currently installed on the device. Based on such information, the installation of an unknown application is detected. Furthermore, a record of DNS queries received from this client device reveals frequent access requests to the domain name `upload_application_name.serviceprovider.com`. Security
10 server **16** runs a series of malware-identifying heuristics on the DNS logs, revealing that domain `serviceprovider.com` is registered by a platform as a service (PAS) provider, and that DNS queries for the respective domain come at relatively regular time intervals. These two facts trigger a suspicion of malice, and security server **16** decides to sample and/or introspect network traffic exchanged between the respective client device and the suspect domain.

15 Stage II - traffic analysis

[0072] To collect a representative traffic sample, security server **16** identifies a selected subset of client devices considered representative for this threat, according to device profiles stored in profile database **19**. For instance, selection may be done according to the current location of candidate devices (e.g., Western European countries) and operating system (in this case, a
20 specific version of Android®). Security server **16** may transmit the list of selected devices to DNS server **14**. In response, DNS server **14** may flag at least some DNS replies to DNS queries comprising the `serviceprovider.com` domain and received from the selected clients, to indicate an activation of the forensic data collection service on the respective devices. In some embodiments, the value of service activation flag **27** instructs security software on the receiving
25 client device to divert traffic to `serviceprovider.com` through VPN to security server **16**. DNS server **14** will keep track for each selected client device, for instance recording how many DNS queries of `serviceprovider.com` were received from the respective client device, and

will stop forensic data collection from the respective client device when sufficient traffic samples were collected. To stop data collection, DNS server **14** may reset service activation flag **27** to indicate that data collection service is inactive, or may respond with a standard DNS reply that lacks service activation flag **27** altogether.

5 **[0073]** In turn, in response to receiving a flagged DNS reply indicating that forensic data collection is active, security software executing on a client device replaces the real IP address corresponding to `serviceprovider.com` with a dummy IP address. Thereafter, when suspected malware attempts to communicate with `serviceprovider.com`, it will send a connection request to the dummy IP. Such a request may be re-routed through the VPN interface of the
10 client device to security server **16**. Re-routing typically comprises replacing the dummy IP address with the corresponding real destination IP address, and re-packing network traffic according to a VPN protocol. Some embodiments of security application **54** further attach some metadata (e.g., destination port, destination IP address, network protocol, timestamp, etc) to the diverted traffic.

15 **[0074]** In an exemplary traffic analysis scenario, a VPN component of security server **16** logs the metadata attached to each received network packet, and stores a copy of the packet payload to disk for later inspection. The packet itself is then forwarded to its true destination IP address. Any response packet from the respective IP address will be redirected back to the respective client device. In some embodiments, the VPN component of security server **16** will also log
20 incoming traffic destined for the respective client device, thus capturing a complete exchange between the suspected malware and its remote service providers.

[0075] Using some of the systems and methods described herein, computer security analysts were able to collect the following types of information:

- telemetry to identify the outbreak of a new, potentially malicious application;
- 25 • a suspicious web service, identified by a suspect domain name; and
- samples of data exchanged between the new unknown application and the suspect domain name.

[0076] Using this data, the analysis team was able to apply heuristics to determine that the web service at the suspect domain is used for malicious command-and-control type communications. This exemplary determination of malice was made according to a timing and periodicity of packet exchanges, the fact that communications are encrypted, the identity of an owner of the encryption key, and an average size of communication payload (relatively small packets).
5 Another set of heuristics identified the suspect domain as a malicious uploader (collector of user data), according to an asymmetry of the exchanges (payload of packets originating at the client device is typically much larger than payload of incoming packets), and to the fact that such asymmetric traffic was only seen on some infected clients, suggesting that the respective clients
10 were somehow selected as interesting by the command-and-control server.

[0077] Several systems and methods of using DNS messages to selectively target individual clients for specific services are known in the art. However, in conventional systems and methods, typically the entity performing the respective service is the DNS server itself. In a parental control example, in response to receiving a DNS query tagged with a client identifier, a
15 DNS server may selectively choose to return an IP address or not, according to the identity of the client and/or to the requested domain name. In a load-balancing example, the DNS server may choose among a plurality of IP addresses according to a current geographical position of the requesting client.

[0078] In contrast to such conventional systems, in some embodiments of the present invention security tasks are split between software executing on the DNS server and software executing on the client device. For instance, the task of selecting a client for a specific service is performed by the DNS server, which communicates to the requesting client device by way of a flagged DNS reply. In turn, security software executing on the client actually performs the respective service (e.g., forensic data collection, redirecting traffic to a security server, parental control, etc.).
20 There are multiple advantages of such task splitting. On one hand, centralizing the decision process on a server allows for a unified management of security information and an optimal speed of response to emerging threats. On the other hand, executing security operations on the client itself allows for increased precision, sophistication, and flexibility of the respective
25

operations. Virtually any operation can thus be carried out on a client, while benefitting from the advantages of per-DNS-message selection as described above. For instance, a selective redirection of a client's network traffic via VPN to a security server is feasible using the systems and methods described herein, while it cannot be done by the DNS server alone, i.e., using a conventional DNS-server-centric security model.

[0079] Although the description above primarily focused on embodiments wherein security software such as DNS proxy **56** and communication manager **58** execute on the end-client device (e.g., smartphone, PC), in alternative embodiments at least some of the functionality of DNS proxy **56** and/or manager **58** may be implemented on a network appliance acting as gateway to a local network interconnecting multiple client devices. See, for instance, gateway **12** in Fig. **1**. In such configurations, gateway **12** may intercept DNS messages going into and/or out of local network **13**, and may modify them as shown above. When gateway **12** supplies local network addresses to clients (e.g. acting as DHCP server for local network **13**), gateway **12** distinguishes among individual client devices, and can therefore tag outgoing DNS queries with a respective client identifier. Furthermore, gateway **12** is in a good position to intercept and selectively route other electronic communications (e.g., HTTP requests) between clients on the local network and external IP addresses. Therefore, gateway **12** may execute security procedures as shown herein, for instance selectively harvesting forensic data, performing parental control activities, etc.

[0080] Some embodiments implement a hybrid configuration, wherein some of the client devices **10a-f** execute an instance of security application **54**, while others do not. In one such example, gateway **12** may attempt to automatically provision security application **54** to all client devices **10a-e** connected to local network **13**. Some such devices, for instance thermostats, smartwatches, etc., may have limited hardware resources and therefore may be unable to execute a full-blown instance of security application **54**. Some embodiments may then use software executing on gateway **12** to extend security services as described herein to such devices.

[0081] There may be multiple advantages to running at least a part of the functionality of security application **54** on gateway **12**, as opposed to on end-client devices **10a-f** as shown

above. One advantage is that operations carried out on gateway **12** (such as tagging DNS requests, detecting service activation flags, modifying IP addresses, etc.) are virtually undetectable by software executing on client devices. Furthermore, malware executing on client devices may not interfere with or subvert the activity of gateway **12**. Another advantage is that gateway **12** may efficiently collect and/or introspect data traffic by itself, *i.e.*, without re-directing the respective traffic to a VPN server. In one such example, gateway **12** may determine traffic metadata (e.g., origin and destination IP addresses, packet size, timestamps), and transmit such metadata to security server **16** for analysis.

[0082] Yet another advantage of configurations wherein at least a part of security application **54** executes on gateway **12** is insight into local network topology. In the example of Fig. 1, DNS server **14** is typically not aware that client devices **10a** and **10b** are connected to the same local network, but gateway **12** is. Therefore, when intercepting multiple DNS queries for the same domain name, gateway **12** may inform server **14** whether the respective DNS queries are coming from members of the same network or not. Such information is potentially relevant to computer security, for instance in situations wherein malware spreads from one network node to others. In another exemplary situation, multiple DNS queries for the same domain name coming from distinct device types (smartphone, PC, TV) connected to a home network may indicate legitimate usage of an online entertainment service such as Spotify® or Netflix®. In yet another example, multiple DNS queries for the same domain name coming from devices running the same OS (e.g., Windows®) may indicate a legitimate attempt to distribute a software update to multiple devices on a corporate network.

[0083] However, running at least a part of security application **54** on gateway **12** as opposed to individual client devices also has disadvantages. For instance, automatic device discovery (*i.e.*, using software executing on gateway **12** to determine a device type of each client **10a-f**) may be limited and computationally costly. Although some type-indicative client information may be available in the form of MAC addresses, etc., other data such as resource usage and installed software may be completely inaccessible to gateway **12**.

[0084] It will be clear to one skilled in the art that the above embodiments may be altered in many ways without departing from the scope of the invention. Accordingly, the scope of the invention should be determined by the following claims and their legal equivalents.

CLAIMS

1. A method performed by a computer system, the method comprising intercepting a domain name service (DNS) reply message [28] comprising a target internet protocol (IP) address indicating a network location of a remote resource, the method characterized by the DNS reply message further comprising a service activation flag [27],
and by having the computer system carry out the steps of:
 - determining according to a value of the service activation flag [27] whether a forensic data collection service is active;
in response, if the service activation flag [27] indicates that the forensic data collection service is active, modifying the DNS reply message [28] by replacing the target IP address with a dummy IP address;
intercepting an electronic communication directed towards a destination IP address;
determining whether the destination IP address matches the dummy IP address; and
in response to determining whether the destination IP address matches the dummy IP address, if the destination IP address matches the dummy IP address, performing a forensic data collection procedure for characterizing emerging malware, the forensic data collection procedure comprising determining a set of forensic data [30] characterizing the electronic communication and transmitting the set of forensic data [30] to a remote security server [16].
2. The method of claim 1, wherein performing the forensic data collection procedure further comprises having the computer system re-route the electronic communication via a tunnel connecting the computer system to the remote security server [16].
3. The method of claim 1, further characterized by having the computer system, in response to determining whether the destination IP address matches the dummy IP address, if the destination IP address matches the dummy IP address, forward the electronic communication to the target IP address.

- 31 4. The method of claim 1, wherein the set of forensic data [30] includes the target IP
32 address and a timestamp of the electronic communication.
33
- 1 5. The method of claim 4, wherein the set of forensic data [30] further comprises an
2 indicator of a size of a payload of the electronic communication.
3
- 1 6. A computer system configured to intercept a domain name service (DNS)
2 reply message [28] comprising a target internet protocol (IP) address indicating a
3 network location of a remote resource, the computer system characterized
4 by the DNS reply message [28] further comprising a service activation flag
5 [27], the computer system further characterized by executing a DNS proxy
6 [56] and a communication manager [58], wherein:
7 the DNS proxy [56] is configured to:
8 in response to intercepting the DNS reply message [28],
9 determine according to a value of the service activation flag [27] whether a forensic
10 data collection service is active, and
11 in response, if the service activation flag [27] indicates that the forensic data
12 collection service is active, modify the DNS reply message [28] by
13 replacing the target IP address with a dummy IP address; and
14 the communication manager [58] is configured to:
15 intercept an electronic communication directed towards a destination IP
16 address,
17 determine whether the destination IP address matches the dummy IP address, and
18 in response to determining whether the destination IP address matches the dummy IP
19 address, if the destination IP address matches the dummy IP address, perform a
20 forensic data collection procedure for characterizing emerging malware, the
21 forensic data collection procedure comprising determining a set of forensic data
22 [30] characterizing the electronic communication and transmitting the set of
23 forensic data [30] to a remote security server [16].
24

- 1 7. The computer system of claim 6, wherein performing the forensic data collection
2 procedure further comprises re-routing the electronic communication via a tunnel
3 connecting the computer system to the remote security server [16].
4
- 5 8. The computer system of claim 6, wherein the communication manager is further
6 configured, in response to determining whether the destination IP address matches the
7 dummy IP address, if the destination IP address matches the dummy IP address, to
8 forward the electronic communication to the target IP address.
9
- 10 9. The computer system of claim 6, wherein the set of forensic data [30] includes the
11 target IP address and a timestamp of the electronic communication.
12
- 1 10. The computer system of claim 9, wherein the set of forensic data [30] further comprises
2 an indicator of a size of a payload of the electronic communication.
3
- 1 11. A non-transitory computer-readable medium storing instructions which, when
2 executed by a computer system, cause the computer system to
3 intercept a domain name service (DNS) reply message [28] comprising a target internet
4 protocol (IP) address indicating a network location of a remote resource, the computer-
5 readable medium characterized by the DNS reply message [28] further comprising a
6 service activation flag [27], the computer-readable medium further characterized by
7 causing the computer system to form a DNS proxy [56] and a communication manager
8 [58], wherein:
9 the DNS proxy [56] is configured to:
10
11 in response to intercepting the DNS reply message [28], determine according to a
12 value of the service activation flag [27] whether a forensic data collection
13 service is active, and

14 in response, if the service activation flag [27] indicates that the forensic data
15 collection service is active, modify the DNS reply message [28] by
16 replacing the target IP address with a dummy IP address; and
17 the communication manager [58] is configured to:
18 intercept an electronic communication directed towards a destination IP
19 address,
20 determine whether the destination IP address matches the dummy IP
21 address, and
22 in response to determining whether the destination IP address matches the dummy
23 IP address, if the destination IP address matches the dummy IP
24 address, perform a forensic data collection procedure for characterizing
25 emerging malware, the forensic data collection procedure comprising
26 determining a set of forensic data [30] characterizing the electronic
27 communication and transmitting the set of forensic data [30] to a remote
28 security server [16].
29

- 1 12. A server computer system [14] configured to engage in domain name service (DNS)
2 transactions with a plurality of client systems [10a-f], the server computer system [14]
3 characterized by being further configured to:
4 in response to a determination that an Internet domain is suspected of malice,
5 determine a target device profile according to the Internet domain, the target
6 device profile collectively representing electronic devices characterized by
7 being located within a selected geographic area and executing a selected
8 operating system;
9 in response to receiving a DNS query message [26] comprising a domain name of the
10 Internet domain, identify according to the DNS query message [26] a client system
11 [10] where the DNS query message [26] originated;
12 in response to identifying the client system [10], determine whether the client system
13 [10] matches the target device profile;

14 in response to determining whether the client system [10] matches the target device
15 profile, when the client system [10] matches the target device profile, transmit a DNS
16 reply message [28] to the client system, the DNS reply message [28] comprising a
17 target Internet Protocol (IP) address associated with the domain name, the DNS reply
18 message [28] further configured to include a service activation flag [27] for activating
19 a forensic data collection procedure on the client system [10]; and
20 in response to determining whether the client system [10] matches the target device
21 profile, when the client system [10] does not match the target device profile,
22 transmit another DNS reply message to the client system, the other DNS reply message
23 comprising the target IP address and further configured to not include the service
24 activation flag [27].
25

- 26 13. The server computer system of claim 12, further characterized by being configured to:
27 in response to determining whether the client system [10] matches the target device
28 profile, when the client system [10] matches the target device profile, determine
29 whether the client system [10] is eligible for forensic data collection according
30 to a count of DNS query messages previously received from the client system
31 [10]; and
32 in response, transmit the DNS reply message [28] including the service activation flag
33 [27] only when the client system [10] is eligible for forensic data collection.
34

- 1 14. The server computer system of claim 12, further characterized by being configured to:
2 in response to determining whether the client system [10] matches the target device
3 profile, when the client system [10] matches the target device profile, determine
4 whether the client system [10] is eligible for forensic data collection according
5 to a count of DNS query messages including the domain name previously
6 received at the server computer system [14]; and
7 in response, transmit the DNS reply message [28] including the service activation flag
8 [27] only when the client system [10] is eligible for forensic data collection.
9

- 1 15. The server computer system of claim 12, further characterized by being configured to:
2 in response to determining whether the client system [10] matches the target device
3 profile, when the client system [10] matches the target device profile, determine
4 whether the client system [10] is eligible for forensic data collection according
5 to a count of distinct client systems [10a-f] having transmitted DNS query
6 messages to the server computer system [14] within a selected time interval;
7 and
8 in response, transmit the DNS reply message [28] including the service activation flag
9 [27] only when the client system [10] is eligible for forensic data collection.
10
- 1 16. The server computer system of claim 12, further characterized by being configured to:
2 in response to determining whether the client system [10] matches the target device
3 profile, when the client system [10] matches the target device profile, lookup a
4 client profile database [19] to determine whether a selected software application
5 is installed for execution on the client system [10]; and
6 in response, transmit the DNS reply message [28] including the service activation flag
7 [27] only when the selected software application is installed for execution on
8 the client system [10].
9
- 1 17. The server computer system of claim 12, further characterized by being configured to:
2 in response to determining whether the client system [10] matches the target device
3 profile, when the client system [10] matches the target device profile, randomly
4 select the client system [10] for forensic data collection; and
5 in response, transmit the DNS reply message [28] including the service activation flag
6 [27] only when the client system [10] is selected for forensic data collection.
7
- 1 18. The server computer system of claim 12, wherein the target device profile represents
2 electronic devices further characterized by being of a selected appliance type.
3

- 1 19. The server computer system of claim 12, further characterized by being configured to
2 identify the client system [10] according to a client ID [25] included in the DNS query
3 message [26], the client ID [25] uniquely identifying the client system [10] among the
4 plurality of client systems [10a-f].
5
- 1 20. The server computer system of claim 19, wherein the client ID [25] comprises a hash
2 value.