PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 :
G06F 11/00, 11/30, 1/26, 13/00, 13/38

A1

(11) International Publication Number: WO 00/16197

(43) International Publication Date: 23 March 2000 (23.03.00)

(21) International Application Number: PCT/US99/20550

(22) International Filing Date: 7 September 1999 (07.09.99)

(30) Priority Data:
09/151,484 11 September 1998 (11.09.98) US

(71) Applicant *(for all designated States except US)*: INTEL CORPORATION [US/US]; 2200 Mission College Boulevard, Santa Clara, CA 95052 (US).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: ILKBAHAR, Alper [TR/US]; 1418 Four Oaks Road, San Jose, CA 95131 (US). CHENG, Christopher [–/US]; Apartment #97, 720 North Fair Oaks Avenue, Sunnyvale, CA 94086 (US).

(74) Agents: MILLIKEN, Darren, J. et al.; Blakely, Sokoloff, Taylor & Zafman LLP, 7th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025 (US).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
With international search report.

(54) Title: A POWER FAILURE SAFE COMPUTER ARCHITECTURE

(57) Abstract

A component (100–103) powered by a first power supply (140) activates a driving signal. The driving signal indicates that both a second power supply voltage (150–153) has a magnitude greater than a reference voltage and an enable signal is active. A driver transfers the output signal when the driving signal is active.

