CLAIMS

1. A bracket comprising a mounting face and a fixing face, which faces are spaced apart from one another, in which:

the mounting face comprises a first end portion, a second, end portion, and a locating portion positioned between the first and second end portions; and

the fixing face comprises a first fixing portion and a second fixing portion;

the bracket comprises a first leg extending from the first end portion to a first end of the first fixing portion, a second leg extending from the second end portion to a first end of the second fixing portion, a third leg extending from a first end of the locating portion to a second end of the first fixing portion and a fourth leg extending from a second end of the locating portion to a second end of the second fixing portion.

2. A bracket according to Claim 1, in which the locating portion comprises a plurality of locating apertures adapted to engage with locating pins.

3. A bracket according to Claim 1, in which the bracket is symmetrical along two axes parallel to the mounting face.

4. A bracket according to Claim 1, in which the mounting face is integrally formed with the fixing face.

5. A bracket according to Claim 1, in which the bracket comprises at least one gusset.

6. A bracket according to Claim 5, in which a gusset is formed between a leg and an associated fixing portion.

7. A bracket according to Claim 6, in which a gusset is formed between each leg and its associated fixing portion.

8. A bracket according to Claim 7, in which the fixing face comprises a plurality of fixing apertures each of which is configured to engage with a fixing screw.

9. A bracket according to Claim 1, in which the mounting face and fixing face are parallel.

10. A bracket assembly comprising a bracket according to Claim 1, further comprising a fixing plate that is affixable to the fixing face.

11. A bracket assembly according to Claim 10, in which the bracket assembly further comprises a plurality of fixing screws.

12. A container assembly comprising a bracket according to Claim 1, comprising a container, which container comprises a mounting surface, which mounting surface comprises a mount locator configured to engage with the locating portion of the bracket, and in which the bracket is affixable to the mounting surface.

13. A container assembly comprising a bracket according to Claim 2, further comprising a container, which container comprises a mounting surface, which mounting surface comprises a mount locator, which mount locator comprises a plurality of locating pins which engage with the locating apertures.

14. A container assembly comprising a bracket assembly according to Claim 10, further comprising a container, which container comprises a mounting surface, which mounting surface comprises a mount locator.

15. A method of mounting a castor wheel on a container comprising the steps of:

providing a container assembly according to Claim 12;

abutting a castor wheel fixing plate against a bracket fixing face;

affixing the fixing plate to the fixing face;

locating a bracket mounting face to a predetermined position on a mounting surface of a container;

affixing the mounting face to the mounting surface.